Task 2: SQL Queries using JDBC

Create a table **'User'** with a following schema 'User ID' and 'Password' stored as hash format (note you have research on how to generate hash from a string), accept "User ID" and "Password" as input and check in the table if they match to confirm whether user access is allowed or not.

```
package test;
import java.security.MessageDigest;
import java.security.NoSuchAlgorithmException;
import java.sql.*;
public class UserAuthentication {
public static void main(String[] args) {
String url="jdbc:sqlite:users.db";
Connection conn=null;
try {
conn=DriverManager.getConnection(url);
System. out. println ("Connected to the SQLite database.");
createTable(conn);
String userId="john_doe";
String password="password123";
insertUser(conn,userId,password);
String inputUserId="john_doe";
String inputPassword="password123";
boolean isAuthenticated=authenticateUser(conn, inputUserId, inputPassword);
if (isAuthenticated){
System. out. println ("User authentication successful.");
} else {
System.out.println("Invalid credentials. Access denied.");
}
} catch (SQLException e){
System.out.println("SQL Exception: "+e.getMessage());
} catch (NoSuchAlgorithmException e){
```

```
System.out.println("Error creating password hash: "+e.getMessage());
} finally{
try {
if (conn!= null) {
conn.close();
}
} catch (SQLException ex) {
System.out.println("Error closing connection: " + ex.getMessage());
}
}
}
private static void createTable(Connection conn) throws SQLException {
String sql = "CREATE TABLE IF NOT EXISTS User (" +
"UserID TEXT PRIMARY KEY," +
"PasswordHash TEXT)";
try (Statement stmt = conn.createStatement()) {
stmt.execute(sql);
}
}
private static void insertUser(Connection conn, String userId, String password) throws
SQLException, NoSuchAlgorithmException {
String hashedPassword = hashPassword(password);
String sql = "INSERT INTO User(UserID, PasswordHash) VALUES(?, ?)";
try (PreparedStatement pstmt = conn.prepareStatement(sql)) {
pstmt.setString(1, userId);
pstmt.setString(2, hashedPassword);
pstmt.executeUpdate();
}
System.out.println("User inserted into the table.");
}
```

```
private static boolean authenticateUser(Connection conn, String userId, String password)
throws SQLException, NoSuchAlgorithmException {
String hashedPassword = hashPassword(password);
String sql = "SELECT UserID FROM User WHERE UserID = ? AND PasswordHash = ?";
try (PreparedStatement pstmt = conn.prepareStatement(sql)) {
pstmt.setString(1, userId);
pstmt.setString(2, hashedPassword);
ResultSet rs = pstmt.executeQuery();
return rs.next();
}
}
private static String hashPassword(String password) throws NoSuchAlgorithmException {
MessageDigest digest = MessageDigest.getInstance("SHA-256");
byte[] hash = digest.digest(password.getBytes());
StringBuilder hexString = new StringBuilder();
for (byte b: hash) {
String hex = Integer.toHexString(0xff & b);
if (hex.length() == 1) hexString.append('0');
hexString.append(hex);
}
return hexString.toString();
}
}
```