

8 Puzzle Using A* Algorithm:

> 8 puzzle using A* algorithm

Algorithm: Heuristic: Number tiles out of place

function A* search(problem) returns a solution or failure
node \leftarrow a node n with n -state: problem initial state,
 $n, g=0$

frontier \leftarrow a priority queue ordered by ascending
 $g+h$, only element n
 $h \leftarrow$ number of misplaced tiles

loop do

if empty?(frontier) then return failure

$n \leftarrow \text{pop}(\text{frontier})$

if problem.goalTest(n .state) then return solution(n)

for each action a in problem.actions(n .state) do

$n' \leftarrow \text{childNode}(\text{problem}, n, a)$

insert(n' , $g(n') + h(n')$, frontier)

Algorithm: Heuristic: Manhattan Distance

function A* search(problem) returns a solution or failure
node \leftarrow a node n with n -state: problem initial state,
 $n, g=0$

frontier \leftarrow a priority queue ordered by ascending
 $g+h$, only element n

$h \leftarrow$ Sum of distances between initial and goal state

loop do

if empty?(frontier) then return failure

$n \leftarrow \text{pop}(\text{frontier})$


if problem.goalTest(n .state) then return solution(n)

for each action a in problem.actions(n .state) do


$n' \leftarrow \text{childNode}(\text{problem}, n, a)$


insert(n' , $g(n') + h(n')$, frontier)

State Space Tree :- Heuristic : Number of Tiles out of place



Heuristic: Manhattan Distance





Soln

A star

November 9, 2024

```
[2]: print("Name:Vignesh Bhat", "USN:1BM22CS327", sep="\n")
import heapq

class PuzzleState:
    def __init__(self, board, g=0):
        self.board = board
        self.g = g
        self.zero_pos = board.index(0)

    def h(self):
        return sum(1 for i in range(9) if self.board[i] != 0 and self.board[i] !=
↪ i + 1) #misplaced tiles

    def f(self):
        return self.g + self.h()

    def get_neighbors(self):
        neighbors = []
        x, y = divmod(self.zero_pos, 3)
        directions = [(-1, 0), (1, 0), (0, -1), (0, 1)]
        for dx, dy in directions:
            new_x, new_y = x + dx, y + dy
            if 0 <= new_x < 3 and 0 <= new_y < 3:
                new_zero_pos = new_x * 3 + new_y
                new_board = self.board[:]

                new_board[self.zero_pos], new_board[new_zero_pos] = ↵
↪ new_board[new_zero_pos], new_board[self.zero_pos]
                neighbors.append(PuzzleState(new_board, self.g + 1))

        return neighbors

def a_star(initial_state, goal_state):
    open_set = []
    heapq.heappush(open_set, (initial_state.f(), 0, initial_state))
    came_from = {}
    g_score = {tuple(initial_state.board): 0}
```

```

while open_set:
    current_f, _, current = heapq.heappop(open_set)

    if current.board == goal_state:
        return reconstruct_path(came_from, current)

    for neighbor in current.get_neighbors():
        neighbor_tuple = tuple(neighbor.board)
        tentative_g_score = g_score[tuple(current.board)] + 1

        if neighbor_tuple not in g_score or tentative_g_score <
↪g_score[neighbor_tuple]:
            came_from[neighbor_tuple] = current
            g_score[neighbor_tuple] = tentative_g_score
            heapq.heappush(open_set, (neighbor.f(), neighbor.g, neighbor))
↪# Use neighbor.g as the tie-breaker

    return None

def reconstruct_path(came_from, current):
    path = []
    while current is not None:
        path.append(current.board)
        current = came_from.get(tuple(current.board), None)
    return path[::-1]

initial_state = PuzzleState([1, 2, 3, 4, 5, 6, 0, 7, 8])
goal_state = [1, 2, 3, 4, 5, 6, 7, 8, 0]

solution = a_star(initial_state, goal_state)

if solution:
    for step in solution:
        print(step)
else:
    print("No solution found")

```

Name:Vignesh Bhat

USN:1BM22CS327

[1, 2, 3, 4, 5, 6, 0, 7, 8]

[1, 2, 3, 4, 5, 6, 7, 0, 8]

[1, 2, 3, 4, 5, 6, 7, 8, 0]

```

[3]: print("Name:Vignesh Bhat", "USN:1BM22CS327", sep="\n")
import heapq

class PuzzleState:

```

```

def __init__(self, board):
    self.board = board
    self.zero_pos = board.index(0)

def h(self):
    distance = 0
    for i in range(9):
        if self.board[i] != 0:
            target_x, target_y = divmod(self.board[i] - 1, 3)
            current_x, current_y = divmod(i, 3)
            distance += abs(target_x - current_x) + abs(target_y -
current_y)
    return distance

def f(self):
    return self.h() # Just the heuristic value (Manhattan distance)

def get_neighbors(self):
    neighbors = []
    x, y = divmod(self.zero_pos, 3)
    directions = [(-1, 0), (1, 0), (0, -1), (0, 1)]
    for dx, dy in directions:
        new_x, new_y = x + dx, y + dy
        if 0 <= new_x < 3 and 0 <= new_y < 3:
            new_zero_pos = new_x * 3 + new_y
            new_board = self.board[:]
            new_board[self.zero_pos], new_board[new_zero_pos] =
new_board[new_zero_pos], new_board[self.zero_pos]
            neighbors.append(PuzzleState(new_board))
    return neighbors

def a_star(initial_state, goal_state):
    open_set = []
    heapq.heappush(open_set, (initial_state.f(), id(initial_state),
initial_state))
    came_from = {}
    g_score = {tuple(initial_state.board): 0}

    while open_set:
        current_f, _, current = heapq.heappop(open_set)

        if current.board == goal_state:
            return reconstruct_path(came_from, current)

        for neighbor in current.get_neighbors():
            neighbor_tuple = tuple(neighbor.board)

```

```
tentative_g_score = g_score[tuple(current.board)] + 1 # All edges
↳ have a cost of 1
```

```
    if neighbor_tuple not in g_score or tentative_g_score <
↳ g_score[neighbor_tuple]:
        came_from[neighbor_tuple] = current
        g_score[neighbor_tuple] = tentative_g_score
        heapq.heappush(open_set, (tentative_g_score + neighbor.h(),
↳ id(neighbor), neighbor))
```

```
    return None
```

```
def reconstruct_path(came_from, current):
    path = []
    while current is not None:
        path.append(current.board)
        current = came_from.get(tuple(current.board), None)
    return path[::-1]
```

```
initial_state = PuzzleState([1, 2, 3, 4, 5, 6, 0, 7, 8])
```

```
goal_state = [1, 2, 3, 4, 5, 6, 7, 8, 0]
```

```
solution = a_star(initial_state, goal_state)
```

```
if solution:
    for step in solution:
        print(step)
else:
    print("No solution found")
```

Name:Vignesh Bhat

USN:1BM22CS327

[1, 2, 3, 4, 5, 6, 0, 7, 8]

[1, 2, 3, 4, 5, 6, 7, 0, 8]

[1, 2, 3, 4, 5, 6, 7, 8, 0]