

```

Offending packet: ICMP [10.112.56.145 > 10.112.56.2 Echo request (type=8/code=0) id=33122 seq=0] IP [ttl=45 id=8418 iplen=7168 ]
sendto in send_ip_packet_sd: sendto(4, packet, 28, 0, 10.112.56.3, 16) => No route to host
Offending packet: ICMP [10.112.56.145 > 10.112.56.3 Echo request (type=8/code=0) id=5406 seq=0] IP [ttl=56 id=51492 iplen=7168 ]
sendto in send_ip_packet_sd: sendto(4, packet, 28, 0, 10.112.56.4, 16) => No route to host
Offending packet: ICMP [10.112.56.145 > 10.112.56.4 Echo request (type=8/code=0) id=36673 seq=0] IP [ttl=38 id=56825 iplen=7168 ]
sendto in send_ip_packet_sd: sendto(4, packet, 28, 0, 10.112.56.5, 16) => No route to host
Offending packet: ICMP [10.112.56.145 > 10.112.56.5 Echo request (type=8/code=0) id=12193 seq=0] IP [ttl=55 id=47548 iplen=7168 ]
sendto in send_ip_packet_sd: sendto(4, packet, 28, 0, 10.112.56.6, 16) => No route to host
Offending packet: ICMP [10.112.56.145 > 10.112.56.6 Echo request (type=8/code=0) id=31148 seq=0] IP [ttl=42 id=35073 iplen=7168 ]
sendto in send_ip_packet_sd: sendto(4, packet, 28, 0, 10.112.56.7, 16) => No route to host
Offending packet: ICMP [10.112.56.145 > 10.112.56.7 Echo request (type=8/code=0) id=46935 seq=0] IP [ttl=54 id=16341 iplen=7168 ]
Omitting future Sendto error messages now that 10 have been shown. Use -d2 if you really want to see them.
Stats: 0:00:38 elapsed; 0 hosts completed (0 up), 255 undergoing Ping Scan
Ping Scan Timing: About 18.63% done; ETC: 10:48 (0:02:50 remaining)
Stats: 0:00:41 elapsed; 0 hosts completed (0 up), 255 undergoing Ping Scan
Ping Scan Timing: About 20.10% done; ETC: 10:48 (0:02:47 remaining)
Nmap scan report for 10.112.56.113
Host is up (0.0063s latency).
Not shown: 999 closed tcp ports (reset)
PORT      STATE SERVICE
53/tcp    open  domain
MAC Address: 00:00:40:01:81:D5 (Applicon)

Nmap scan report for 10.112.56.145
Host is up (0.000014s latency).
Not shown: 999 closed tcp ports (reset)
PORT      STATE SERVICE
3306/tcp  open  mysql

Nmap done: 256 IP addresses (2 hosts up) scanned in 101.05 seconds
apple@Apples-MacBook-Pro ~ % sudo nmap -sS 10.112.56.0/24 -oN scan-results.txt
Starting Nmap 7.98 ( https://nmap.org ) at 2026-08-29 10:49 +0530
Nmap scan report for 10.112.56.113
Host is up (0.0093s latency).
Not shown: 999 closed tcp ports (reset)
PORT      STATE SERVICE
53/tcp    open  domain
MAC Address: 00:00:40:01:3E:42 (Applicon)

Nmap scan report for 10.112.56.145
Host is up (0.000016s latency).
Not shown: 999 closed tcp ports (reset)
PORT      STATE SERVICE
3306/tcp  open  mysql

Nmap done: 256 IP addresses (2 hosts up) scanned in 16.75 seconds
apple@Apples-MacBook-Pro ~ % cat scan-results.txt
# Nmap 7.98 scan initiated Sat Aug 29 10:49:12 2026 as: nmap -sS -oN scan-results.txt 10.112.56.0/24
Nmap scan report for 10.112.56.113
Host is up (0.0093s latency).
Not shown: 999 closed tcp ports (reset)
PORT      STATE SERVICE
53/tcp    open  domain
MAC Address: 00:00:40:01:3E:42 (Applicon)

Nmap scan report for 10.112.56.145
Host is up (0.000016s latency).
Not shown: 999 closed tcp ports (reset)
PORT      STATE SERVICE
3306/tcp  open  mysql

# Nmap done at Sat Aug 29 10:49:29 2026 -- 256 IP addresses (2 hosts up) scanned in 16.75 seconds
apple@Apples-MacBook-Pro ~ %
```