EXP NO: 3 DATE:

# DEVELOP A LEXICAL ANALYZER TO RECOGNIZE A FEW PATTERNS IN C. (EX. IDENTIFIERS, CONSTANTS, COMMENTS, AND OPERATORS, ETC.) USING LEX TOOL.

#### AIM:

To develop a Lexical Analyzer using the LEX tool that recognizes different tokens in a given C program snippet, including Identifier, Constants, Comments, Operators, Keywords, Special Symbols.

#### **ALGORITHM:**

- 1. Start
- 2. Define token patterns in LEX for:
  - Keywords (e.g., int, float, if, else)
  - Identifiers (variable/function names)
  - Constants (integer and floating-point numbers)
  - Operators (+, -, =, ==, !=, \*, /)
  - Comments (// single-line, /\* multi-line \*/)
  - Special Symbols ({, }, (, ), ;, ,)
- 3. Read input source code.
- 4. Match the code tokens using LEX rules.
- 5. Print each recognized token with its type.
- 6. End

### **PROGRAM:**

```
%{
#include <stdio.h>
%}
%option noyywrap
%%
// Keywords
"int"|"float"|"char"|"double"|"if"|"else"|"return"|"for"|"while"|"do" {
printf("Keyword: %s\n", yytext);
// Identifiers (starting with a letter or underscore, followed by letters, digits, or underscores)
[a-zA-Z][a-zA-Z0-9]* {
printf("Identifier: %s\n", yytext);
// Constants (integer and floating-point numbers)
[0-9]+(\.[0-9]+)? {
printf("Constant: %s\n", yytext);
// Operators
"+"|"-"|"*"|"/"|"="|"=="|"!="|"<"|">"|"&&"|"||"|"++"|"--" {
printf("Operator: %s\n", yytext);
```

```
26
// Single-line comments
"//".* {
printf("Comment: %s\n", yytext);
// Multi-line comments
"/*"([^*]|\*+[^*/])*\*+"/" {
printf("Multi-line Comment: %s\n", yytext);
// Special symbols
";"|","|"("|")"|"{"|"}"|"["|"]" {
printf("Special Symbol: %s\n", yytext);
// Ignore whitespaces and newlines
\lceil \langle t \rangle n \rceil;
%%
int main() {
printf("Enter a C code snippet:\n")
yylex();
return 0;
}
OUTPUT:
lex lexer.1
cc lex.yy.c -o lexer
./a.out
Sample Input
int main() {
int a = 10;
float b = 20.5;
/* This is a multi-line comment */
if (a > b) {
a = a + b;
return 0;
```

```
) ()nin
Special Symbol: ;
Multi-line Comment: /* This is a multi-line comment */
```

## **RESULT:**

Thus the above program reads a C code snippet, tokenizes it using LEX rules, recognizes and categorizes keywords, identifiers, constants, operators, comments, and special symbols, and then displays each token along with its type.