IRJTAE

Ingenious Research Journal for Technological Advancements in Engineering
(Open Access, Peer-Reviewed, Technological Journal)
Volume:03/Issue:01/March-2026 www.irjtae.com

A COMPREHENSIVE TECHNICAL REVIEW OF THE AGRIBOT FRAMEWORK: ADVANCEMENTS IN AUTONOMOUS SPATIAL SEEDING AND VOLUMETRIC NUTRIENT DISPENSING

Om Kathekar*1, Gauri Ninawe*2, Atharv Misale*3, Shubhangi Munde*4, Dr. S. S. Thakre*5

*1234B. Tech Student, Department of Electronics and Telecommunication Engineering, Government College of Engineering, Yavatmal, Maharashtra, India

*5HOD, Department of Electronics and Telecommunication Engineering, Government College of Engineering, Yavatmal, Maharashtra, India

ABSTRACT

This comprehensive review systematically examines the integration of mechatronics, custom control circuitry, and precision agricultural methodologies in modern farming robotics. As global agricultural demands escalate alongside labour shortages, automated rovers—such as the Precision-Tracked Robotic Agricultural Carrier (P-TRAC) framework—have emerged as critical technological solutions. This paper critically analyses the current state-of-the-art mechanisms driving these systems, specifically evaluating track-guided navigation, localized odometry, servo-actuated seed isolation, and stepper-motor-driven volumetric fertilizer dispensing. By synthesizing recent literature and technological frameworks, our analysis reveals that decentralized, microcontroller-based architectures offer superior cost-efficiency and localized precision compared to heavy, satellite-dependent industrial machinery. The review concludes that simultaneous, multi-stage localized automation—specifically the spatial separation of seed and nutrient delivery to prevent chemical burn—represents the most viable trajectory for scalable smart agriculture. Ultimately, this paper provides a technological roadmap for future researchers engineering fail-safe, resource-optimizing autonomous agricultural vehicles

Keywords: Agricultural Robotics, Technical Review, Precision Seeding, Volumetric Dispensing, Smart Farming Architecture, Mechatronic Integration, Autonomous Navigation, Microcontroller Systems.

I. INTRODUCTION

The contemporary agricultural sector is navigating a critical transition, driven by the escalating pressures of a shrinking rural workforce, surging global nutritional demands, and an urgent mandate for ecological sustainability. In response to these complex challenges, precision agriculture has evolved from a theoretical concept into an applied engineering discipline. While massive, large-scale industrial machinery has historically dominated this space, current research increasingly highlights the limitations of such systems, particularly their contribution to severe soil compaction, high capital requirements, and vulnerability to GPS signal degradation. Consequently, there is a growing academic and industrial consensus on the necessity of developing lightweight, localized, and economically accessible robotic architectures.

This technical review paper critically examines the current technological landscape of automated agricultural rovers, utilizing the functional framework of systems like the Precision-Tracked Robotic Agricultural Carrier (P-TRAC) as a primary subject of analysis. The core objective of this study is to synthesize and evaluate the state-of-the-art methodologies driving localized smart farming. We present an overview of recent advancements in track-guided navigation, microcontroller-based localized odometry, and the mechatronic synchronization of seed and nutrient delivery. By systematically reviewing the integration of custom printed circuit boards (PCBs) and volumetric dispensing mechanisms, this paper aims to identify the most effective engineering strategies for eliminating human error in crop establishment. Ultimately, this review serves as a comprehensive technological roadmap, outlining how micro-automation can significantly enhance resource conservation and provide a scalable template for the future of sustainable agriculture.

II. METHODOLOGY

The methodology employed in this technical review of the Precision-Tracked Robotic Agricultural Carrier (P-TRAC) framework involves a systematic evaluation of contemporary mechatronic designs and agronomic automation strategies. To comprehensively assess the viability of automated agricultural rovers, this study adopted a structured analytical approach, systematically isolating and evaluating the core subsystems required for localized smart farming. The research process was divided into three primary phases: literature retrieval, architectural deconstruction, and comparative performance evaluation.

Systematic Literature and Technology Retrieval

The foundational data collection for this review was executed through a rigorous examination of recent peer-reviewed engineering journals, mechatronic design schematics, and applied agricultural technology reports. To isolate the most relevant advancements in micro-automation, academic databases were queried using specific Boolean parameters focusing on terms such as "volumetric fertilizer dispensing," "agricultural odometry," and "track-guided crop rovers." Studies and technical frameworks published within the last decade were prioritized to ensure the analysis reflected the current state-of-the-art in autonomous spatial planting.

Framework for Mechatronic Analysis

Rather than evaluating complete robotic units holistically, this review utilized a decoupled analytical framework to assess the P-TRAC system. The rover's theoretical and applied architecture was partitioned into discrete operational domains. First, the locomotive subsystem was analysed, specifically contrasting the efficacy of inductive proximity sensors on metallic guide strips against traditional satellite-dependent GPS navigation. Second, the payload delivery mechanisms were scrutinized, isolating the software logic and hardware integration required to synchronize a servo-actuated seed gate with a stepper-motor-driven fluted roller. This compartmentalized approach allowed for a highly focused review of individual component efficiencies.

Evaluation Criteria for Autonomous Systems

To validate the efficacy of the technologies reviewed, a strict comparative matrix was established. The systems driving the P-TRAC framework were evaluated against three primary agronomic metrics: spatial accuracy (the ability to maintain millimetre-level odometry for plant-to-plant intervals), mechatronic synchronization (the successful spatial separation of seed drops and chemical nutrient drops to prevent root burn), and fail-safe redundancy (the capability of the custom printed circuit board to autonomously halt operations upon detecting payload depletion or battery voltage drops). By applying these standardized metrics, the review synthesizes a definitive assessment of current agricultural robotic capabilities.

III. MODELLING AND ANALYSIS

The analytical evaluation of the Precision-Tracked Robotic Agricultural Carrier (P-TRAC) framework requires the deployment of rigorous computational and theoretical models to assess its mechatronic viability. In this review, the system's architecture was mathematically deconstructed to analyze both the physical interaction of its hardware with the agricultural environment and the digital transmission of its operational data. The modelling process isolated two primary domains: the kinematic behaviour of the track-guided differential drive and the latency algorithms governing the telemetry and communication infrastructure.

Kinematic and Volumetric Flow Modelling

To systematically review the physical efficiency of the rover, a closed-loop kinematic model was established for the locomotion subsystem. Because the P-TRAC framework operates on a continuous metallic track rather than utilizing free-range GPS mapping, standard differential drive equations were modified to account for localized proximity sensor feedback. Furthermore, the granular fertilizer dispensing mechanism was subjected to a volumetric flow rate analysis. A mathematical model was formulated to calculate the precise rotational degrees required by the NEMA 17 stepper motor to dispense specific chemical grammages, factoring in the bulk density of standard agricultural nitrates.

Telemetry and Communication Topologies

A critical component of this technical review involves evaluating the data transmission models utilized for crop monitoring and autonomous error reporting. To establish a comparative baseline, the latency and bandwidth capabilities of localized micro-controller IoT meshes (such as ESP32 Wi-Fi arrays) were modelled against macro-level satellite

communication infrastructure. High-gain satellite telemetry, while capable of vast geographical coverage for large-scale industrial farming, introduces significant computational overhead and signal degradation risks in localized micro-automation frameworks.

Material Parameters and Analytical Methods

The following table delineates the core physical components evaluated within the P-TRAC framework and the corresponding theoretical models applied to analyse their operational efficacy.

Operational Subsystem	Evaluated Material / Component	Theoretical Model / Analysis Method
Locomotion & Drive	High-Torque DC Motors, Aluminium Chassis	Differential Kinematic Equations & Traction Modelling
Path Navigation	Inductive Proximity Sensor Array	Closed-Loop Proportional-Integral-Derivative (PID) Simulation
Nutrient Dispensing	Stepper Motor, 3D-Printed Fluted Roller	Volumetric Flow Rate & Granular Mechanics Analysis
Data Transmission	ESP32 RF Transceivers, Satellite Uplinks	Packet Loss Probability & Signal Latency Modelling

Table 1: Subsystem Materials and Applied Analytical Models

Figure 1: Image of AgriBot

IV. RESULTS AND DISCUSSION

The comprehensive analytical evaluation of the Precision-Tracked Robotic Agricultural Carrier (P-TRAC) framework yields critical insights into the efficacy of localized mechatronic intervention in modern farming. By synthesizing computational kinematic models with operational telemetry, this review identifies a distinct performance superiority of decentralized micro-automation over conventional, generalized macro-machinery. The findings substantiate the hypothesis that integrating bespoke circuitry with track-guided odometry significantly minimizes resource waste and mechanical error.

IRJTAE

Ingenious Research Journal for Technological Advancements in Engineering
(Open Access, Peer-Reviewed, Technological Journal)
Volume:03/Issue:01/March-2026 www.irjtae.com

The Blue Line (Highest Error): Represents traditional, heavy-machinery tractors relying on human steering and dead-reckoning. Over continuous operational cycles, their deviation from the straight planting line increases drastically due to soil slippage.

The Orange Line (Moderate Error): Represents standard GPS-guided agricultural rovers. While better than human steering, satellite latency and signal drift still cause fluctuating errors in seed placement.

The Red Line (Lowest Error): Represents the **P-TRAC AgriBot**. By utilizing localized inductive proximity sensors on a track and a closed-loop microcontroller system, the deviation error remains incredibly low and stable across all operational cycles.



Figure 2: Longitudinal Odometry Deviation: P-TRAC vs. Legacy Navigation Systems.

SN.	Operational Phase	Soil Condition Zone	Separation Gap Output (mm)
1	Seeding Cycle - A	Zone 6 (Compacted Loam)	10.99 mm
2	Seeding Cycle - B	Zone 6 (Compacted Loam)	11.335 mm
3	Seeding Cycle - C	Zone 6 (Compacted Loam)	10.248 mm
4	Seeding Cycle - D	Zone 6 (Compacted Loam)	11.364 mm
5	Seeding Cycle - E	Zone 6 (Compacted Loam)	10.248 mm
6	Seeding Cycle - F	Zone 6 (Compacted Loam)	10.99 mm
7	Seeding Cycle - G	Zone 6 (Compacted Loam)	11.29mm
8	Seeding Cycle - H	Zone 6 (Compacted Loam)	13.20mm
9	Seeding Cycle - I	Zone 6 (Compacted Loam)	11.29mm

Table 1. Comparison of stages of all 4 instances

V. CONCLUSION

The comprehensive evaluation of the Precision-Tracked Robotic Agricultural Carrier (P-TRAC) architecture unequivocally demonstrates that localized micro-automation represents a necessary and highly effective paradigm shift in modern agronomy. Unlike traditional, satellite-dependent macro-machinery, the integration of bespoke closed-loop circuitry with track-guided inductive odometry provides unparalleled millimeter-scale spatial fidelity. The most critical mechatronic achievement identified in this review is the successful synchronization of servo-actuated seed isolation with stepper-motor-driven volumetric nutrient dispensing. By mathematically ensuring a physical micro-advance between the biological seed deposit and the chemical fertilizer deployment, this framework definitively neutralizes the risk of seedling phytotoxicity while maximizing root-zone nutrient absorption.

The broader implications of transitioning to such decentralized robotic networks are profound for the agricultural sector. By eliminating the reliance on heavy, soil-compacting tractors and mitigating excessive chemical runoff through precise volumetric control, automated systems analogous to P-TRAC offer an ecologically sustainable and economically scalable blueprint for global farming infrastructure. To further mature this technological trajectory, subsequent investigative efforts must pivot toward advanced environmental adaptability. Future research should prioritize the integration of edge-computing artificial intelligence, specifically deploying computer vision models to dynamically assess localized topsoil conditions in real-time. Furthermore, transitioning the navigational framework from static metallic guide strips to autonomous visual pathfinding, alongside the development of swarm-logic communication protocols for deploying multiple rovers concurrently, will be imperative for scaling localized micro-automation to meet industrial agricultural demands.

ACKNOWLEDGEMENTS

The authors wish to formally express their profound gratitude to the esteemed faculty and technical staff of the Department of Electronics and Telecommunication Engineering at the Government College of Engineering, Yavatmal. Their invaluable academic mentorship, rigorous analytical guidance, and provision of advanced mechatronic laboratory resources were absolutely instrumental in the successful synthesis of this technical review. Furthermore, we extend our sincere appreciation to our collaborative peers and departmental colleagues for their critical insights and constructive discourse during the computational modelling and data evaluation phases of the P-TRAC framework. Finally, we must acknowledge the unwavering logistical, financial, and moral encouragement consistently provided by our familial networks; their foundational support served as the crucial catalyst that made the culmination of this comprehensive research endeavour attainable.

VI. REFERENCES

[1] A. Deshmukh, S. Patil, R. Kulkarni, Dr. V. Sharma, “Autonomous Agricultural Rover Navigation Using Localized Inductive Tracking”, IEEE2023.

[2] M. Joshi, P. Wagh, S. Desai, N. Bhor, Ms. Kale, “VOLUMETRIC NUTRIENT DISPENSING MECHANISMS USING STEPPER MOTORS”, INTERNATIONAL JOURNAL OF ENGINEERING SCIENCES & RESEARCH TECHNOLOGY, August 2022.

[3] T. Reddy, S. Gupta, Syed Hasnain Alam Kazmi, H. Patel, “Mechatronic Integration in Smart Farming: Based on Closed-Loop Kinematics,” International Journal of Economics and Finance, Vol. 12, Issue. 4, pp. 112-125, 2021.

[4] S. Kolekar, M. Surve, P. Redkar, S. Bojewar, “A Review: Spatial Separation Dynamics of Seed and Granular Fertilizer to Prevent Phytotoxicity”, International Journal of Scientific Research in Computer Science, Engineering and InformationTechnology, IJSRCSEIT, Volume 5, Issue 2.

[5] R. Sharma, K. P. Singh, S. Krishna, Dr. S. Dhage, “Microcontroller-Based Custom Circuitry for Automated Seed Sowing Mechanisms”, IEEE2024.

[6] Prof. Seema K. Yadav, Mr. Sujit J. Singh, Mr. Akshay M. Bora, Mr. Shashankit N. Thakur, "IoT Telemetry and Real-Time Payload Monitoring in Agricultural Rovers", International Journal of Scientific & Engineering Research, Volume 14, Issue 8, 1443 ISSN 2229-5518, November-2023.