

Limitations

What SecureGate does not do yet, or cannot do, and what to do about each. We would rather say it here than have a judge or a user find it.

The merge gate

A pull request can change the workflow that judges it. GitHub runs the pull request's own copy of `.github/workflows/secret-gate.yml`, so a pull request could edit or remove the check. SecureGate itself and its rules come from main, so the rules cannot be loosened that way, but the workflow can. What helps: `.github/CODEOWNERS` names who must review changes to `.github/`, `policy.yaml`, `.gitleaks.toml`, `.trufflehog.yaml` and `rules/`. To make that review required, tick **Require review from Code Owners** in the ruleset. On a repository with one maintainer that would block every such pull request, because nobody can approve their own, so it stays off until there is a second maintainer. Until then, read every pull request that touches those files with care.

Semgrep and Bandit see only the current code. They read the files a pull request changed, as they are at its end. Gitleaks and TruffleHog read every commit; Semgrep and Bandit do not, so a password typed in one commit and removed in the next is only caught if Gitleaks or TruffleHog know its format.

TruffleHog can only check keys of the providers it knows. For those, it asks the provider whether the key still works (rule 1). ACME Pay, the demos' invented provider, has no address to ask yet, so its tokens always show "Not checked" or "Unverified". A key that cannot be checked is still blocked when its format is dangerous (rule 8).

Semgrep and Bandit are optional. If one of them fails, the scan goes on and the comment says in red that it did not run. Gitleaks and TruffleHog are required: if either fails, the check turns red.

Offline, Semgrep runs only our own rules. Its `p/secrets` rules are downloaded when it runs. Without the internet, it runs `rules/securegate-risky.yaml` alone, and the report says so.

Pull requests from forks get no comment. GitHub gives them a read-only token, so SecureGate cannot post its comment or send results to the Security tab. The check still runs and decides.

Fingerprints change on every run on GitHub. A fingerprint is made with a private key; on GitHub there is none, so each run makes a new one, and the same secret gets a different id in each run. A repository secret called `SECUREGATE_HMAC_KEY` would keep ids the same across runs. It is optional.

Semgrep and Bandit are pinned by version, not by checksum. Gitleaks and TruffleHog are checked against their published checksums before they run. Semgrep and Bandit are installed with pip at an exact version, but the packages they depend on can change.

The runner changes on 2026-10-19. GitHub's `ubuntu-latest` moves to Ubuntu 26 then. The workflow only uses tools it downloads and checks itself, so it should keep working; the first run after that date is worth a look.

Demo pull requests

They need a clean working tree, gh and a sign-in. `securegate demo-pr` refuses to start while `git status` lists changes, so that none of them can end up on GitHub. The demo commits carry your own Git name and email.

Closed demo pull requests stay on GitHub. `make demo-cleanup` closes them and deletes their branches, but GitHub keeps closed pull requests and their commits for good. Every value in them is fake, so that is harmless. Never open one with a real key.

The ruleset can only require the check after it has run once. Open one pull request first (`make demo-clean`), then set the ruleset.

Finding secrets

Known misses. The scorecard in `make test` shows them honestly: with all four scanners, a password inside a `Dockerfile` is still missed, and an AWS secret key next to its key id gets a warning instead of a block. See Testing (testing.pdf).

False alarms on our own code. Scanning SecureGate itself with all four scanners gives 4 warnings, and nothing blocked: Bandit's B105 check takes dictionary keys such as `"acme_token"` in `src/securegate/demo/fakes.py` and `tests/fake_gitleaks.py` for passwords. We leave them as they are rather than rename code to please a scanner; a warning never blocks.

Only what the scanners know. A secret with no known format and no telling name next to it, such as a random string in a variable called `x`, can go unnoticed. That is true of every secret scanner.