

https://bhavik-portfolio.netlify.app/









Performance Accessibility

**Best Practices** 

**SEO** 

**PWA** 




## Performance

Values are estimated and may vary. The performance score is calculated directly from these metrics. See calculator.

0-49

50-89

90-100



**METRICS** Expand view

First Contentful Paint

 $0.7 \, s$ 

Speed Index

1.0 s

Largest Contentful Paint

1.2 s

Time to Interactive

 $0.7 \, s$ 

**Total Blocking Time** 

0 ms

**Cumulative Layout Shift** 

0.047





View Treemap






















Show audits relevant to:







**OPPORTUNITIES** 

Opportunity **Estimated Savings** 

about:blank 1/28

▲ Properly size images 3.48 s ∧

Serve images that are appropriately-sized to save cellular data and improve load time. Learn more.

		URL		Resource Size	Potential Savings
	img	/images/5.png	(bhavik-portfolio.netlify.app)	2,384.6 KiB	2,284.7 KiB
	img	/images/1.png	(bhavik-portfolio.netlify.app)	1,871.6 KiB	1,791.9 KiB
img	<b></b>	/images/6.png	(bhavik-portfolio.netlify.app)	329.6 KiB	309.5 KiB
	img	/images/4.png	(bhavik-portfolio.netlify.app)	52.9 KiB	48.9 KiB
img		/images/7.png	(bhavik-portfolio.netlify.app)	35.6 KiB	32.9 KiB

▲ Serve images in next-gen formats

3.15 s ^

Image formats like WebP and AVIF often provide better compression than PNG or JPEG, which means faster downloads and less data consumption. <u>Learn more</u>.

	URL	Resource Size	Potential Savings
img	/images/5.png (bhavik-portfolio.netlify.app)	2,384.6 KiB	2,109.9 KiB

about:blank 2/28

		URL	Resource Size	Potential Savings
	img	/images/1.png (bhavik-portfolio.netlify.app)	1,871.6 KiB	1,697.7 KiB
img		/images/6.png (bhavik-portfolio.netlify.app)	329.6 KiB	290.6 KiB
	img	/images/4.png (bhavik-portfolio.netlify.app)	52.9 KiB	29.1 KiB
img		/images/7.png (bhavik-portfolio.netlify.app)	35.6 KiB	19.9 KiB

# Reduce unused JavaScript 0.23 s ^

Reduce unused JavaScript and defer loading scripts until they are required to decrease bytes consumed by network activity. <u>Learn more</u>. <u>LCP</u>

URL	Transfer Size	Potential Savings
<pre>chrome-extension://fmkadmapgofadopljbjfkapdkoienihi/build/react_devtools_backend.js</pre>	512.2 KiB	322.3 KiB
js/main.3102d12d.js (bhavik-portfolio.netlify.app)	48.6 KiB	20.9 KiB
/node_modules/react-dom/cjs/react-dom.production.min.js	39.9 KiB	18.5 KiB
/node_modules/react/cjs/react.production.min.js	2.0 KiB	1.5 KiB

## Eliminate render-blocking resources

0.22 s ^

Resources are blocking the first paint of your page. Consider delivering critical JS/CSS inline and deferring all non-critical JS/styles. Learn more. (FCP) (LCP)

LIDI	Transfer	Potential
URL	Size	Savings

about:blank 3/28

URL	Transfer Size	Potential Savings
css/font-awesome.min.css (cdnjs.cloudflare.com)	6.2 KiB	230 ms
/css2? family=Space+Grotesk:wght@300;400;500;600&display=swap (fonts.googleapis.com)	1.0 KiB	290 ms

These suggestions can help your page load faster. They don't directly affect the Performance score.

#### DIAGNOSTICS

▲ Avoid enormous network payloads — Total size was 5,548 KiB

Large network payloads cost users real money and are highly correlated with long load times. Learn more. [LCP]

✓ Show 3rd-party resources (3)

URL	Transfer Size
/images/5.png (bhavik-portfolio.netlify.app)	2,386.0 KiB
/images/1.png (bhavik-portfolio.netlify.app)	1,872.7 KiB
<pre>chrome-extension://fmkadmapgofadopljbjfkapdkoienihi/build/react_devtools_backend.js</pre>	512.2 KiB
/images/6.png (bhavik-portfolio.netlify.app)	329.8 KiB
webfonts/fa-solid-900.woff2 (cdnjs.cloudflare.com)	151.4 KiB
webfonts/fa-brands-400.woff2 (cdnjs.cloudflare.com)	103.8 KiB
/images/4.png (bhavik-portfolio.netlify.app)	53.1 KiB
js/main.3102d12d.js (bhavik-portfolio.netlify.app)	48.6 KiB
/images/7.png (bhavik-portfolio.netlify.app)	35.8 KiB
v12/V8mDoQDjQwoff2 (fonts.gstatic.com)	21.3 KiB

O Avoid chaining critical requests — 5 chains found

The Critical Request Chains below show you what resources are loaded with a high priority. Consider reducing the length of chains, reducing the download size of resources, or deferring the download of unnecessary resources to improve page load. Learn more. FCP [LCP]

Maximum critical path latency: 1,310 ms

Initial Navigation

https://bhavik-portfolio.netlify.app

- ...css/font-awesome.min.css (cdnjs.cloudflare.com) 50 ms, 6.23 KiB
- ...css/all.min.css (cdnjs.cloudflare.com)
  - ...webfonts/fa-brands-400.woff2 (cdnjs.cloudflare.com) 200 ms, 103.78 KiB
  - ...webfonts/fa-solid-900.woff2 (cdnjs.cloudflare.com) 160 ms, 151.39 KiB

/css2?family=Space+Grotesk:wght@300;400;500;600&display=swap (fonts.googleapis.com)

- ...v12/V8mDoQDjQ....woff2 (fonts.gstatic.com) 30 ms, 21.29 KiB
- ...css/main.759d5324.css (bhavik-portfolio.netlify.app) 80 ms, 1.45 KiB
- User Timing marks and measures 2 user timings

Consider instrumenting your app with the User Timing API to measure your app's real-world performance during key user experiences. <u>Learn more</u>.

Name	Туре	Start Time Duration
v3	Mark	683.69 ms
v3	Mark	1,186.75 ms

Keep request counts low and transfer sizes small — 17 requests • 5,548 KiB

To set budgets for the quantity and size of page resources, add a budget json file. Learn more.


Resource Type	Requests	Transfer Size
Total	17	5,547.5 KiB
Image	5	4,677.4 KiB
Script	2	560.8 KiB
Font	3	276.5 KiB

about:blank 5/28

Resource Type	Requests	Transfer Size
Stylesheet	4	26.1 KiB
Other	2	6.0 KiB
Document	1	0.8 KiB
Media	0	0.0 KiB
Third-party	7	813.3 KiB

O Largest Contentful Paint element — 1 element found

This is the largest contentful element painted within the viewport. Learn More [LCP]



Avoid large layout shifts — 5 elements found

These DOM elements contribute most to the CLS of the page. CLS



about:blank 6/28



Avoid long main-thread tasks — 1 long task found

Lists the longest tasks on the main thread, useful for identifying worst contributors to input delay. Learn more [TBT]

URL	Start Time	Duration
https://bhavik-portfolio.netlify.app	427 ms	60 ms

More information about the performance of your application. These numbers don't directly affect the Performance score.

PASSED AUDITS (29)

Defer offscreen images

Consider lazy-loading offscreen and hidden images after all critical resources have finished loading to lower time to interactive. Learn more.

Minify CSS

Minifying CSS files can reduce network payload sizes. Learn more. FCP LCP

about:blank 7/28

Minifying JavaScript files can reduce payload sizes and script parse time. Learn more. FCP [LCP] Potential Transfer **URL** Size Savings chrome-extension://fmkadmapgofadopljbjfkapdkoienihi/build/react\_devtools\_backend.js 512.2 KiB 223.2 KiB Reduce unused CSS — Potential savings of 17 KiB Reduce unused rules from stylesheets and defer CSS not used for above-the-fold content to decrease bytes consumed by network activity. Learn more. FCP [LCP] Transfer Potential **URL** Size Savings ...css/all.min.css (cdnjs.cloudflare.com) 17.4 KiB 17.2 KiB Efficiently encode images Optimized images load faster and consume less cellular data. Learn more. Enable text compression Text-based resources should be served with compression (gzip, deflate or brotli) to minimize total network bytes. Learn more. FCP [LCP] Preconnect to required origins Consider adding 'preconnect' or 'dns-prefetch' resource hints to establish early connections to important third-party origins. Learn more. [FCP] [LCP] Initial server response time was short — Root document took 450 ms Keep the server response time for the main document short because all other requests depend on it. Learn more. [FCP] LCP URL Time Spent

8/28 about:blank

450 ms

https://bhavik-portfolio.netlify.app

	Avoid multiple page redirects	^
	Redirects introduce additional delays before the page can be loaded. Learn more. FCP LCP	
(	Preload key requests	^
	Consider using ` <li>k rel=preload&gt;` to prioritize fetching resources that are currently requested later in page load. <a href="Learn more"><u>Learn more</u></a>. <a href="FCP">FCP</a> <a href="LCP">LCP</a></li>	
	Use HTTP/2	^
	HTTP/2 offers many benefits over HTTP/1.1, including binary headers and multiplexing. Learn more.	
	Use video formats for animated content	^
	Large GIFs are inefficient for delivering animated content. Consider using MPEG4/WebM videos for animations and PNG/WebP for static images instead of GIF to save network bytes. Learn more (LCP)	
	Remove duplicate modules in JavaScript bundles	^
	Remove large, duplicate JavaScript modules from bundles to reduce unnecessary bytes consumed by network activity.	
	Avoid serving legacy JavaScript to modern browsers	^
	Polyfills and transforms enable legacy browsers to use new JavaScript features. However, many aren't necessary for modern browsers. For your bundled JavaScript, adopt a modern script deployment strategy using module/nomodule feat detection to reduce the amount of code shipped to modern browsers, while retaining support for legacy browsers. <a href="Learn More"><u>Learn More (TBT)</u></a>	ure
	Preload Largest Contentful Paint image	^
	Preload the image used by the LCP element in order to improve your LCP time. <u>Learn more</u> . <u>LCP</u>	
	Uses efficient cache policy on static assets — 0 resources found	^
	A long cache lifetime can speed up repeat visits to your page. <u>Learn more</u> .	
	Avoids an excessive DOM size — 205 elements	^
	A large DOM will increase memory usage, cause longer <u>style calculations</u> , and produce costly <u>layout reflows</u> . <u>Learn more TBT</u>	<u>e</u> .

about:blank 9/28

Statistic	Element	Valu	ue
Total DOM Elements		20	05
Maximum DOM Depth	mpath		10
Maximum Child Elements		svg.BgAnimationsv	16

JavaScript execution time — 0.0 s

Consider reducing the time spent parsing, compiling, and executing JS. You may find delivering smaller JS payloads helps with this. <u>Learn more</u>. (TBT)

URL	Total CPU Time	Script Evaluation	Script Parse
https://bhavik-portfolio.netlify.app	403 ms	20 ms	24 ms
Unattributable	107 ms	1 ms	0 ms

Minimizes main-thread work — 0.6 s

Consider reducing the time spent parsing, compiling and executing JS. You may find delivering smaller JS payloads helps with this. Learn more (TBT)

Category	Time Spent
Other	225 ms
Rendering	129 ms
Style & Layout	111 ms
Script Evaluation	87 ms
Script Parsing & Compilation	61 ms

about:blank 10/28

Category	Time Spent
Parse HTML & CSS	23 ms
Garbage Collection	3 ms

All text remains visible during webfont loads

Leverage the font-display CSS feature to ensure text is user-visible while webfonts are loading. Learn more. FCP LCP

Minimize third-party usage — Third-party code blocked the main thread for 0 ms

Third-party code can significantly impact load performance. Limit the number of redundant third-party providers and try to load third-party code after your page has primarily finished loading. <u>Learn more</u>. (TBT)

Third-Party	Transfer Size	Main-Thread Blocking Time	
Cloudflare CDN	279 KiB	0 ms	
webfonts/fa-solid-900.woff2 (cdnjs.cloudflare.com)	151 KiB	0 ms	
webfonts/fa-brands-400.woff2 (cdnjs.cloudflare.com)	104 KiB	0 ms	
css/all.min.css (cdnjs.cloudflare.com)	17 KiB	0 ms	
Google Fonts	22 KiB	0 ms	
v12/V8mDoQDjQwoff2 (fonts.gstatic.com)	21 KiB	0 ms	

Lazy load third-party resources with facades

Some third-party embeds can be lazy loaded. Consider replacing them with a facade until they are required. <u>Learn more</u>. <u>(TBT)</u>

Largest Contentful Paint image was not lazily loaded

Above-the-fold images that are lazily loaded render later in the page lifecycle, which can delay the largest contentful paint. **Learn more**.

Uses passive listeners to improve scrolling performance

Consider marking your touch and wheel event listeners as `passive` to improve your page's scroll performance. Learn more.

For users on slow connections, external scripts dynamically injected via `document.write()` can delay page load by tens of seconds. Learn more.

Avoid non-composited animations

Animations which are not composited can be janky and increase CLS. Learn more CLS

Image elements have explicit width and height

Set an explicit width and height on image elements to reduce layout shifts and improve CLS. Learn more CLS

Has a <meta name="viewport"> tag with width or initial-scale

A `<meta name="viewport">` not only optimizes your app for mobile screen sizes, but also prevents <u>a 300 millisecond delay</u> to user input. <u>Learn more</u>. (TBT)

Avoids unload event listeners

The `unload` event does not fire reliably and listening for it can prevent browser optimizations like the Back-Forward Cache.

Use `pagehide` or `visibilitychange` events instead. Learn more




# Accessibility

These checks highlight opportunities to improve the accessibility of your web app. Only a subset of accessibility issues can be automatically detected so manual testing is also encouraged.

### NAMES AND LABELS



about:blank 12/28




about:blank



These are opportunities to improve the semantics of the controls in your application. This may enhance the experience for users of assistive technology, like a screen reader.

#### NAVIGATION



These are opportunities to improve keyboard navigation in your application.

ADDITIONAL ITEMS TO MANUALLY CHECK (10)

Hide

The page has a logical tab order	^
Tabbing through the page follows the visual layout. Users cannot focus elements that are offscreen. <u>Learn more</u> .	
Interactive controls are keyboard focusable	^
Custom interactive controls are keyboard focusable and display a focus indicator. <u>Learn more</u> .	
Interactive elements indicate their purpose and state	^
Interactive elements, such as links and buttons, should indicate their state and be distinguishable from non-interactive elements. <u>Learn more</u> .	
The user's focus is directed to new content added to the page	^
If new content, such as a dialog, is added to the page, the user's focus is directed to it. <u>Learn more</u> .	
User focus is not accidentally trapped in a region	^
A user can tab into and out of any control or region without accidentally trapping their focus. <u>Learn more</u> .	
Custom controls have associated labels	^
Custom interactive controls have associated labels, provided by aria-label or aria-labelledby. <u>Learn more</u> .	
Custom controls have ARIA roles	^
Custom interactive controls have appropriate ARIA roles. <u>Learn more</u> .	
Visual order on the page follows DOM order	^
DOM order matches the visual order, improving navigation for assistive technology. <u>Learn more</u> .	
Offscreen content is hidden from assistive technology	^
Offscreen content is hidden with display: none or aria-hidden=true. <u>Learn more</u> .	
HTML5 landmark elements are used to improve navigation	^
Landmark elements ( <main>, <nav>, etc.) are used to improve the keyboard navigation of the page for assistive techno <a href="Learn more"><u>Learn more</u></a>.</nav></main>	logy.

about:blank 15/28

These items address areas which an automated testing tool cannot cover. Learn more in our guide on <u>conducting an accessibility</u> <u>review</u>.

PASSED AUDITS (10)

[aria-hidden="true"] is not present on the document <body> Assistive technologies, like screen readers, work inconsistently when `aria-hidden="true"` is set on the document `<body>`. Learn more. [user-scalable="no"] is not used in the <meta name="viewport"> element and the [maximum-scale] attribute is not less than 5. Disabling zooming is problematic for users with low vision who rely on screen magnification to properly see the contents of a web page. Learn more. The page contains a heading, skip link, or landmark region Adding ways to bypass repetitive content lets keyboard users navigate the page more efficiently. Learn more. Background and foreground colors have a sufficient contrast ratio Low-contrast text is difficult or impossible for many users to read. Learn more. Document has a <title> element The title gives screen reader users an overview of the page, and search engine users rely on it heavily to determine if a page is relevant to their search. Learn more. <html> element has a [lang] attribute If a page doesn't specify a lang attribute, a screen reader assumes that the page is in the default language that the user chose when setting up the screen reader. If the page isn't actually in the default language, then the screen reader might not announce the page's text correctly. Learn more. <html> element has a valid value for its [lang] attribute Specifying a valid BCP 47 language helps screen readers announce text properly. Learn more. Lists contain only elements and script supporting elements (<script> and <template>). ^

about:blank 16/28

and understand when using assistive technologies. <u>Learn more</u>.

Screen readers have a specific way of announcing lists. Ensuring proper list structure aids screen reader output. <u>Learn more</u> .	
List items ( <li>) are contained within <ul> or <ol> parent elements</ol></ul></li>	^
Screen readers require list items (` <li>') to be contained within a parent `<ul>' or `<ol>' to be announced properly. <u>Learn more</u>.</ol></ul></li>	
Heading elements appear in a sequentially-descending order	^
Properly ordered headings that do not skip levels convey the semantic structure of the page, making it easier to navigate	

NOT APPLICABLE (31) Hide

O [accesskey] values are unique
Access keys let users quickly focus a part of the page. For proper navigation, each access key must be unique. Learn more.
O [aria-*] attributes match their roles
Each ARIA `role` supports a specific subset of `aria-*` attributes. Mismatching these invalidates the `aria-*` attributes. Learn more.
O button, link, and menuitem elements have accessible names
When an element doesn't have an accessible name, screen readers announce it with a generic name, making it unusable for users who rely on screen readers. <u>Learn more</u> .
O [aria-hidden="true"] elements do not contain focusable descendents
Focusable descendents within an `[aria-hidden="true"]` element prevent those interactive elements from being available to users of assistive technologies like screen readers. <a href="Learn more"><u>Learn more</u></a> .
ARIA input fields have accessible names
When an input field doesn't have an accessible name, screen readers announce it with a generic name, making it unusable for users who rely on screen readers. <u>Learn more</u> .
ARIA meter elements have accessible names

about:blank 17/28

When an element doesn't have an accessible name, screen readers announce it with a generic name, making it unusable for users who rely on screen readers. <u>Learn more</u> .
O ARIA progressbar elements have accessible names
When a `progressbar` element doesn't have an accessible name, screen readers announce it with a generic name, making it unusable for users who rely on screen readers. <u>Learn more</u> .
O [role]s have all required [aria-*] attributes
Some ARIA roles have required attributes that describe the state of the element to screen readers. Learn more.
Elements with an ARIA [role] that require children to contain a specific [role] have all required children.
Some ARIA parent roles must contain specific child roles to perform their intended accessibility functions. Learn more.
O [role]s are contained by their required parent element
Some ARIA child roles must be contained by specific parent roles to properly perform their intended accessibility functions. <u>Learn more.</u>
O [role] values are valid
ARIA roles must have valid values in order to perform their intended accessibility functions. Learn more.
ARIA roles must have valid values in order to perform their intended accessibility functions. Learn more.  O ARIA toggle fields have accessible names
O ARIA toggle fields have accessible names  When a toggle field doesn't have an accessible name, screen readers announce it with a generic name, making it unusable
<ul> <li>ARIA toggle fields have accessible names</li> <li>When a toggle field doesn't have an accessible name, screen readers announce it with a generic name, making it unusable for users who rely on screen readers. <a href="Learn more"><u>Learn more</u></a>.</li> </ul>
<ul> <li>ARIA toggle fields have accessible names</li> <li>When a toggle field doesn't have an accessible name, screen readers announce it with a generic name, making it unusable for users who rely on screen readers. Learn more.</li> <li>ARIA tooltip elements have accessible names</li> <li>When an element doesn't have an accessible name, screen readers announce it with a generic name, making it unusable</li> </ul>
O ARIA toggle fields have accessible names  When a toggle field doesn't have an accessible name, screen readers announce it with a generic name, making it unusable for users who rely on screen readers. Learn more.  O ARIA tooltip elements have accessible names  When an element doesn't have an accessible name, screen readers announce it with a generic name, making it unusable for users who rely on screen readers. Learn more.

about:blank 18/28

Assistive technologies, like screen readers, can't interpret ARIA attributes with invalid values. Learn more.
O [aria-*] attributes are valid and not misspelled
Assistive technologies, like screen readers, can't interpret ARIA attributes with invalid names. <u>Learn more</u> .
O Buttons have an accessible name
When a button doesn't have an accessible name, screen readers announce it as "button", making it unusable for users who rely on screen readers. <u>Learn more</u> .
When definition lists are not properly marked up, screen readers may produce confusing or inaccurate output. Learn more.
O Definition list items are wrapped in <d1> elements</d1>
Definition list items (' <dt>' and '<dd>') must be wrapped in a parent '<dl>' element to ensure that screen readers can properly announce them. <u>Learn more</u>.</dl></dd></dt>
O ARIA IDs are unique
The value of an ARIA ID must be unique to prevent other instances from being overlooked by assistive technologies. <u>Learn more</u> .
No form fields have multiple labels
Form fields with multiple labels can be confusingly announced by assistive technologies like screen readers which use either the first, the last, or all of the labels. <u>Learn more</u> .
O <frame/> or <iframe> elements have a title</iframe>
Screen reader users rely on frame titles to describe the contents of frames. <u>Learn more</u> .
<pre></pre>
When an image is being used as an ` <input/> ` button, providing alternative text can help screen reader users understand the purpose of the button. Learn more.
Form elements have associated labels
Labels ensure that form controls are announced properly by assistive technologies, like screen readers. <u>Learn more</u> .


about:blank

The document does not use <meta http-equiv="refresh"/>	^
Users do not expect a page to refresh automatically, and doing so will move focus back to the top of the page. This may create a frustrating or confusing experience. <u>Learn more</u> .	/
O <object> elements have alternate text</object>	^
Screen readers cannot translate non-text content. Adding alternate text to ` <object>` elements helps screen readers comeaning to users. Learn more.</object>	nvey
No element has a [tabindex] value greater than 0	^
A value greater than 0 implies an explicit navigation ordering. Although technically valid, this often creates frustrating experiences for users who rely on assistive technologies. <u>Learn more</u> .	
Cells in a  element that use the [headers] attribute refer to table cells within the same table.	^
Screen readers have features to make navigating tables easier. Ensuring `` cells using the `[headers]` attribute only refer to other cells in the same table may improve the experience for screen reader users. Learn more.	у
elements and elements with [role="columnheader"/"rowheader"] have data cells they describe.	^
Screen readers have features to make navigating tables easier. Ensuring table headers always refer to some set of cell may improve the experience for screen reader users. <u>Learn more</u> .	S
O [lang] attributes have a valid value	^
Specifying a valid BCP 47 language on elements helps ensure that text is pronounced correctly by a screen reader. Leamore.	arn
O <video> elements contain a <track/> element with [kind="captions"]</video>	^
When a video provides a caption it is easier for deaf and hearing impaired users to access its information. <u>Learn more</u> .	




about:blank 20/28

#### TRUST AND SAFETY



#### **GENERAL**



PASSED AUDITS (12) Hide

about:blank 21/28

**Uses HTTPS** All sites should be protected with HTTPS, even ones that don't handle sensitive data. This includes avoiding mixed content, where some resources are loaded over HTTP despite the initial request being served over HTTPS. HTTPS prevents intruders from tampering with or passively listening in on the communications between your app and your users, and is a prerequisite for HTTP/2 and many new web platform APIs. Learn more. Avoids requesting the geolocation permission on page load Users are mistrustful of or confused by sites that request their location without context. Consider tying the request to a user action instead. Learn more. Avoids requesting the notification permission on page load Users are mistrustful of or confused by sites that request to send notifications without context. Consider tying the request to user gestures instead. Learn more. Avoids front-end JavaScript libraries with known security vulnerabilities Some third-party scripts may contain known security vulnerabilities that are easily identified and exploited by attackers. Learn more. Allows users to paste into password fields Preventing password pasting undermines good security policy. Learn more. Displays images with correct aspect ratio Image display dimensions should match natural aspect ratio. Learn more. Serves images with appropriate resolution Image natural dimensions should be proportional to the display size and the pixel ratio to maximize image clarity. Learn more. Page has the HTML doctype ^ Specifying a doctype prevents the browser from switching to quirks-mode. Learn more. Properly defines charset

about:blank 22/28

A character encoding declaration is required. It can be done with a `<meta>` tag in the first 1024 bytes of the HTML or in the Content-Type HTTP response header. <u>Learn more</u>.

Avoids deprecated APIs

Deprecated APIs will eventually be removed from the browser. Learn more.

No browser errors logged to the console

Errors logged to the console indicate unresolved problems. They can come from network request failures and other browser concerns. <u>Learn more</u>

No issues in the Issues panel in Chrome Devtools

Issues logged to the 'Issues' panel in Chrome Devtools indicate unresolved problems. They can come from network request failures, insufficient security controls, and other browser concerns. Open up the Issues panel in Chrome DevTools for more details on each issue.

NOT APPLICABLE (1) Hide

Fonts with font-display: optional are preloaded

Preload `optional` fonts so first-time visitors may use them. Learn more



SEU

These checks ensure that your page is following basic search engine optimization advice. There are many additional factors Lighthouse does not score here that may affect your search ranking, including performance on

Core Web Vitals. Learn more.

#### CONTENT BEST PRACTICES

▲ Image elements do not have [alt] attributes

Informative elements should aim for short, descriptive alternate text. Decorative elements can be ignored with an empty alt attribute. Learn more.

about:blank 23/28



Format your HTML in a way that enables crawlers to better understand your app's content.

```
ADDITIONAL ITEMS TO MANUALLY CHECK (1)

Structured data is valid

Run the Structured Data Testing Tool and the Structured Data Linter to validate structured data. Learn more.

Run these additional validators on your site to check additional SEO best practices.
```

```
PASSED AUDITS (10)

Has a <meta name="viewport"> tag with width or initial-scale

A `<meta name="viewport"> not only optimizes your app for mobile screen sizes, but also prevents a 300 millisecond delay to user input. Learn more. TBT

Document has a <title> element
```

about:blank 24/28

The title gives screen reader users an overview of the page, and search engine users rely on it heavily to determine if a page is relevant to their search. <u>Learn more</u>.

Document has a meta description	^
Meta descriptions may be included in search results to concisely summarize page content. Learn more.	
Page has successful HTTP status code	^
Pages with unsuccessful HTTP status codes may not be indexed properly. Learn more.	
Links have descriptive text	^
Descriptive link text helps search engines understand your content. <u>Learn more</u> .	
Links are crawlable	^
Search engines may use `href` attributes on links to crawl websites. Ensure that the `href` attribute of anchor element to an appropriate destination, so more pages of the site can be discovered. Learn More	s links
Page isn't blocked from indexing	^
Search engines are unable to include your pages in search results if they don't have permission to crawl them. Learn	more.
robots.txt is valid	^
If your robots.txt file is malformed, crawlers may not be able to understand how you want your website to be crawled of indexed. Learn more.	or
Document has a valid hreflang	^
hreflang links tell search engines what version of a page they should list in search results for a given language or regi <u>Learn more</u> .	on.
Document avoids plugins	^
Search engines can't index plugin content, and many devices restrict plugins or don't support them. Learn more.	
NOT APPLICABLE (3)	Hide

O Document has a valid rel=canonical about:blank 25/28

Canonical links suggest which URL to show in search results. <u>Learn more</u>.

Document uses legible font sizes

Font sizes less than 12px are too small to be legible and require mobile visitors to "pinch to zoom" in order to read. Strive to have >60% of page text ≥12px. <u>Learn more</u>.

Tap targets are sized appropriately

Interactive elements like buttons and links should be large enough (48x48px), and have enough space around them, to be easy enough to tap without overlapping onto other elements. <u>Learn more</u>.



#### PWA

These checks validate the aspects of a Progressive Web App. Learn more.

#### **INSTALLABLE**

▲ Web app manifest or service worker do not meet the installability requirements — 1 reason

Service worker is the technology that enables your app to use many Progressive Web App features, such as offline, add to homescreen, and push notifications. With proper service worker and manifest implementations, browsers can proactively prompt users to add your app to their homescreen, which can lead to higher engagement. <u>Learn more</u>.

Failure reason

No matching service worker detected. You may need to reload the page, or check that the scope of the service worker for the current page encloses the scope and start URL from the manifest.

#### PWA OPTIMIZED

▲ Does not register a service worker that controls page and start\_url

The service worker is the technology that enables your app to use many Progressive Web App features, such as offline, add to homescreen, and push notifications. <u>Learn more</u>.

about:blank 26/28

Configured for a custom splash screen	^
A themed splash screen ensures a high-quality experience when users launch your app from their homescreens. <u>Learn</u> more.	
Sets a theme color for the address bar.	^
The browser address bar can be themed to match your site. <u>Learn more</u> .	
O Content is sized correctly for the viewport	^
If the width of your app's content doesn't match the width of the viewport, your app might not be optimized for mobile screens. Learn more.	
Has a <meta name="viewport"/> tag with width or initial-scale	^
A ` <meta name="viewport"/> ` not only optimizes your app for mobile screen sizes, but also prevents <u>a 300 millisecond del</u> <u>to user input</u> . <u>Learn more</u> . <u>(TBT)</u>	l <u>ay</u>
Provides a valid apple-touch-icon	^
For ideal appearance on iOS when users add a progressive web app to the home screen, define an `apple-touch-icon`. It must point to a non-transparent 192px (or 180px) square PNG. <u>Learn More</u> .	
▲ Manifest doesn't have a maskable icon	^
A maskable icon ensures that the image fills the entire shape without being letterboxed when installing the app on a device Learn more.	e.
ADDITIONAL ITEMS TO MANUALLY CHECK (3)	Hide
O Site works cross-browser	^
To reach the most number of users, sites should work across every major browser. <u>Learn more</u> .	
O Page transitions don't feel like they block on the network	^
Transitions should feel snappy as you tap around, even on a slow network. This experience is key to a user's perception of performance. Learn more.	of

about:blank 27/28

Each page has a URL

Ensure individual pages are deep linkable via URL and that URLs are unique for the purpose of shareability on social media. <u>Learn more</u>.

These checks are required by the baseline <u>PWA Checklist</u> but are not automatically checked by Lighthouse. They do not affect your score but it's important that you verify them manually.

Captured at Jun 14, 2022, 12:00 PM GMT+5:30
Initial page load

Emulated Desktop with
Lighthouse 9.5.0

Custom throttling

Single page load

Using Chromium 102.0.0.0 with devtools

Generated by Lighthouse 9.5.0 | File an issue

about:blank 28/28