Hypersonic Missile Technology: A Comprehensive Analysis

Chirath Lochana Herath

Department of Science and Technology, Faculty of Applied Sciences, Uva Wellassa University, Badulla, Sri Lanka.

KEYWORDS

Hypersonic Missile
Missile guidance
Kinzhal
Avangard
HGV
HCM

ABSTRACT

This paper seeks to comprehensively analyze hypersonic missile technology, exploring its foundational principles, operational advancements, and strategic implications in modern military contexts. Examining hypersonic systems' unique capabilities such as speed, maneuverability, and precision. This study evaluates their impact on current defense and detection frameworks, alongside the challenges they pose to global security and power dynamics. Additionally, the paper addresses the strategic, ethical, and legal considerations surrounding hypersonic weapons, particularly gaps in existing arms control agreements. Through this analysis, the research underscores the potential for balanced technological dissemination to mitigate the risks of a singular dominant power, fostering a more stable and equitable international security landscape.

1. Introduction

Hypersonic missile technology represents a revolutionary advancement in modern warfare and is one of the most significant milestones in military capability. Unlike conventional missile systems, hypersonic missiles travel at speeds exceeding Mach 5. This unmatched velocity and agility allow them to effectively challenge and outpace existing defense systems. As a result, this capability fundamentally changes the strategic and tactical landscape of warfare, transforming traditional concepts of engagement.

The main objective of this paper is to examine the impact of hypersonic missile technology on global military strategies and security dynamics. For many years, major military powers have been developing hypersonic technology to overcome the limitations of existing weapon systems. By achieving faster reaction times and improved penetration capabilities, hypersonic missiles can bypass modern aircraft defenses, thereby increasing their operational effectiveness.

Russia has taken a leading role in the deployment of operational hypersonic systems, highlighted by the air-launched Kinzhal missile and the Avangard hypersonic glide vehicle. These advancements represent not only significant technological progress but also a strategic shift in the balance of power among nations competing for military superiority.

The introduction of hypersonic weapons has significant implications for global security, as they can be equipped with both conventional and nuclear warheads. This dual capability blurs the lines between conventional and nuclear deterrence, complicating international relations and military strategy. The unmatched speed and maneuverability of hypersonic missiles create serious challenges for missile defense systems and crisis decision-making, making effective target tracking and interception increasingly difficult.

This analysis aims to clarify how hypersonic missile technology affects warfare and global stability, emphasizing the need for updated defense strategies and regulatory frameworks to address the complexities of this emerging threat.

2. Fundamentals of Hypersonic flight

The term "hypersonic" defines speeds above Mach 5, or five times the speed of sound. Above these kinds of speeds, vehicles fly within a quite different set of aerodynamic phenomena than those occurring at subsonic and supersonic speeds. Excessive heat generated, including shockwave formation and boundary layer separation serious challenges to the design and operation of hypersonic missiles.

The advantage of hypersonic capabilities in military operations is great because the enemy will have fewer chances to notice it and react appropriately due to the reduced time. For instance, a missile cruises at Mach 10 speed and may cover 1,000 kilometers in six minutes, hence bringing the reaction window for the defense systems to zero.

Table 1: Hypersonic speeds and the time to cover 1000 miles to a target

Mach Speed	Miles/Hr.	Miles/ Sec.	Travel time 1K miles (min.)	Mach Speed	Miles/Hr.	Miles/ Sec.	Travel time 1K miles (min.)
1	761.20	0.21	78.82	16	12,179.20	3.38	4.93
2	1,522.40	0.42	39.41	17	12,940.40	3.59	4.64
3	2,283.60	0.63	26.27	18	13,701.60	3.81	4.38
4	3,044.80	0.85	19.71	19	14,462.80	4.02	4.15
5	3,806.00	1.06	15.76	20	15,224.00	4.23	0.25
6	4,567.20	1.27	13.14	21	15,985.20	4.44	0.27
7	5,328.40	1.48	11.26	22	16,746.40	4.65	0.28
8	6,089.60	1.69	9.85	23	17,507.60	4.86	0.29
9	6,850.80	1.90	8.76	24	18,268.80	5.07	0.30
10	7,612.00	2.11	7.88	25	19,030.00	5.29	0.32
11	8,373.20	2.33	7.17	26	19,791.20	5.50	0.33
12	9,134.40	2.54	6.57	27	20,552.40	5.71	0.34
13	9,895.60	2.75	6.06	28	21,313.60	5.92	0.36
14	10,656.80	2.96	5.63	29	22,074.80	6.13	0.37
15	11,418.00	3.17	5.25	30	22,836.00	6.34	0.02

Adapted from: (Drone Delivery of CBNRECy, 2022)

Hypersonic speed missiles share the capability of avoiding interception by the present missile defense systems. Hypersonic missiles fly through space in a nonpredictive manner. Thus, it is pretty hard to track and engage. This maneuverability is made possible by advanced guidance systems and propulsion technologies, which allow the missile to adjust its trajectory even at extreme speeds.




Figure 1: Flow pattern around a slender body as Ma_∞ increases

The complex aerodynamic forces experienced by high-speed vehicles in hypersonic flight pose a major challenge. In hypersonic flight, a missile encounters compressed air pushing out shockwaves that serve as a major drag factor. The high pressure of the air causes it to heat up which leads to major thermal burdens on the missile.

Building a missile able to maintain position and perform well at hypersonic speeds calls for precise design of its aerodynamic profile. When developing hypersonic missiles designers usually incorporate sharp fronts and streamlined designs to effectively reduce drag and minimize thermal stress from the Air Force. These characteristics need to find equilibrium with the requirement for flexibility since an entirely aerodynamic form could restrict changes in direction for the missile.

Designing hypersonic missiles involves significant thought regarding shockwave creation. Upon moving faster than the speed of sound a missile generates shockwaves which can distort the airflow and jeopardize its stability. To ensure stability in flight shockwave management plays a vital role and necessitates precise engineering and simulation based on CFD techniques.




Figure 2: Gas dynamic phenomenology around a notional hypersonic flight system

The Mach number indicates the speed of an object compared to that of sound in the surrounding medium. In hypersonic operations, the Mach number greatly impacts not only the aerodynamic pressure on missiles but also the thermal challenges they present.

For Mach numbers less than five, the influence of shock formation and thermal heating is minimal. With the rise in Mach number, these effects intensify significantly. In aircraft at approximately Mach 10 the heat caused by air friction hits above 1.500°C calling for the practical use of advanced materials as protection against missile disintegration.

Mastering the link between the Mach number and performance of missiles is key for effective hypersonic technology. To optimize performance within the hypersonic range engineers should focus on understanding the variations in airflow and material stress at various Mach numbers while revising the design of the missile.




Figure 3: Velocity-altitude trajectories for different hypersonic flight system

3. Technological Components of Hypersonic Missiles

To operate properly. Hypersonic missiles demand an integration of sophisticated technologies, for hypersonic flight to succeed advanced propulsion systems are required alongside cutting-edge thermal defense and precise control mechanisms. These systems contribute significantly to addressing the challenging conditions of hypersonic flight including high temperatures and swift corrections in flight.

3.1. Propulsion Systems

Besides the propulsion system, the capability to obtain and sustain speed is very limited. Hypersonic missiles typically rely on two key propulsion technologies: boost-glide systems and scramjet engines. Both of these systems offer unique advantages and face significant engineering challenges.

3.1.1. Boost-Glide Systems (HGV)

Boost glide technology is one well-known method of achieving hypersonic velocity. Here, a conventional rocket booster launches a missile. Therefore, the vehicle achieves speeds and altitudes above Mach 5. After the boost phase, the missile transitions into a glide phase. During the kinetic energy phase, the missile flies along an unpredictable flight path while reaching hypersonic speeds. It will be hard to intercept it.

The challenge with boost-glide technology is how to maintain control through the transition between the boost phase and the glide phase. Hypersonic vehicles undergo intense aerodynamic forces during this transition. It can cause instability or loss of control if it is not managed properly.




Figure 4: Hypersonic Glide Trajectory

Russia's operational boost-glide system is Avangard. The Avangard glider descends through the atmosphere at speeds over Mach 20 once launched atop an ICBM by maneuvering to evade missile defenses and deliver its payload with high precision. Boost-glide systems have an advantage because they can combine maneuverability and speed, which makes them ideal for strategic strikes against heavily defended targets.

3.1.2. Scramjets: Supersonic combustion Ramjets (HCM)

Scramjet engines stand as advanced air-powered propulsion systems for hypersonic missiles. While rocket engines transport fuel and oxidizer together scramjets utilize atmospheric oxygen combined with fuel and burn the mixture supersonically. This configuration enables continuous operation at hypersonic velocities in the atmosphere and provides a notable functional range improvement compared to rocket-driven systems.

By moving forward, the missile compresses air in a scramjet engine which clears the way for moving components like compressors and turbines. When the air has been compressed it unites with fuel and is lit to create propulsion. At high speeds the low-complexity design of the scramjet boosts efficiency; however, regulating the combustion process in such fast velocities remains a challenge.




Figure 5: Detailed schematic of a scramjet engine

The 3M22 Zircon represents a Russian anti-ship winged hypersonic cruise missile capable of destroying both sea-going and land-based targets. Supersonic velocities will be achieved through acceleration with a booster stage equipped with a solid fuel engine, while in the second stage, it will receive further acceleration up to hypersonic speed because of a scramjet motor with liquid fuel. This hypersonic cruise missile reportedly may reach speeds of about Mach 9, or 10,734 km. According to unofficial estimates, its maximum firing range may be far more than 1,000 km.

While both scramjet and boost-glide technologies offer a lot of advantages in this form of hypersonic missile design, each again has particular strengths and limitations. Boost-glide systems are, for instance, better suited for strategic, very long-range attacks, where factors of unpredictability and altitude become important to avoiding intercept. Scramjets offer sustained hypersonic flight within the atmosphere and hence offer flexibility for tactical operations and precision strikes against high-value targets.

While boost-glide systems can operate at higher altitudes, where the thinner atmosphere offers less resistance and generates less heat, they do, again, depend upon the rocket booster at the very initial stages of propulsion. Missiles that have scramjets can travel at similar velocities but at much lower altitudes; their air-breathing nature makes them far more sensitive to air and thus need optimization for very specific flight profiles.




Figure 6: Examples of HGVs and HCMs detection by existing early-warning architecture

3.2. Thermal Management and Protection Systems

3.2.1. Thermal Protection Systems (TPS)




Figure 7: Structural and thermal protection materials distribution on X-51 hypersonic booster and cruiser

During sustained flight at hypersonic speeds, the friction between the missile and the surrounding atmosphere generates higher amounts of heat. The surface temperature of a hypersonic missile can exceed 1500 °C. During its mission, these systems must protect such sensitive electronic and mechanical systems from failure caused by thermal stress on the missile's structural integrity and overall operational capability.

There are three main types of TPS:

1. Passive TPS: These systems use materials that absorb or radiate heat and are best suited for moderate heat loads. Insulated structures (such as Space Shuttle tiles), heat sink surfaces that both absorb and dissipate heat (X-15 hypersonic aircraft skin) and emissive hot structures (X-51 hypersonic flyer nose) that both absorb and dissipate heat through radiation and conduction are examples.

2. Semi-passive TPS: Semi-passive systems are used in situations where the heat exposure is prolonged at high heat levels, with reusable heat pipes that transfer and dissipate heat by evaporative cooling or single-use materials that absorb heat by chemical reaction; (e.g. Early re-entry capsules such as Apollo).
3. Active TPS: Because these systems actively cool in either liquid or gas flow, they can handle extreme heat flux. Some examples are convective cooling, film cooling (a fluid creates a protective layer), and transpiration cooling (taking fluids into a hot gas flow through porous materials).




Figure 8: Leading edge thermal protection systems types and steady-state finite element (FE) simulations of aerodynamic heating of a leading edge

3.2.1.1. Advanced Materials for Thermal Protection

Modern TPS for hypersonic vehicles is based on refractory metals, composites, and ceramics. Because they can survive extreme temperatures (to 1700°C and above), refractory metals, such as Tungsten (W) and Molybdenum (Mo), are used. Primarily used where thermal loads are most concentrated, on leading edges and nose cones, these metals decrease the overall weight of the vehicle by decreasing mass, but they are somewhat expensive and are not the best performers when it comes to thermal performance.

To mitigate this, refractory metals are often combined with advanced ceramics or carbon-carbon composites. Zirconium oxide (ZrO_2) and Silicon carbide (SiC) are ceramics with high thermal resistance and a lower density and thus are suitable for application to the broader area of the missile—acreage TPS. In addition to these materials offering excellent heat resistance, they function as excellent oxidation barriers in the highly reactive hypersonic environment.

An emerging solution for conditions of extreme thermal conditions is ultra-high-temperature ceramics (UHTC), which can withstand temperatures above 3000 °C, which would devastate most conventional materials. The materials studied are in particular Zirconium diboride (ZrB2) and Hafnium carbide (HfC). This is because they are excellent in terms of their thermal and chemical stability, particularly under oxidizing conditions. In areas of high heat and high chemical reaction between the vehicle's surface and surrounding gases, UHTCs are used, such as the leading edge or edge of a missile.




Figure 9: A range of structural materials and hypothetical hypersonic flight conditions.

3.2.1.2. Ablative and Non-Ablative TPS

Ablative materials are frequently used in hypersonic applications. As the missile heats up, the outer layers of the ablative coating vaporize, carrying away heat and protecting the underlying structure. These materials are effective for short-duration missions where one-time use is acceptable. However, for reusable hypersonic systems, non-ablative materials are more desirable, as they do not degrade during flight. Non-ablative systems rely on insulating layers and advanced heat dissipation mechanisms to redistribute thermal energy.




Figure 10: How do the ablators work (Material response)

3.2.2. Advanced Cooling Techniques

As hypersonic missiles endure sustained exposure to extreme temperatures, active cooling methods complement passive thermal protection systems to manage the heat load more effectively.

3.2.2.1. Transpiration-cooled thermal protection system

One of the most advanced cooling techniques for hypersonic missiles is transpiration cooling involving active release of a coolant from pores in the surface of the missile's outer skin. The surface is siphoned off as the coolant seeps through the surface for which it evaporates upon making contact with a hot boundary layer and carries away heat. Advantages of this method include its effectiveness in high-load thermal areas, such as the leading edges and propulsion systems.

Transpiration cooling is dependent upon the materials used for the coolant and the flow rate of the coolant. This new technology takes advantage of the transpiration cooling benefits to extend the thermal robustness of TPS and allow hypersonic systems to travel faster and execute more aggressive maneuvers.

3.2.2.2. Active Thermal Management Systems

Active thermal management systems used in some hypersonic missiles remove heat from high-temperature areas and send it to cooler areas on the vehicle. Heat pipes and thermal spreaders are built into the missile structure using phase change materials or heat-conducing fluid to transport heat from its most critical components. This ensures much more uniform temperature distribution through the vehicle and aids significantly in the overall thermal efficiency of the vehicle as well as prevents localized overheating.

In addition, the design of such cooling systems can be optimized only with the help of integrated computational fluid dynamics (CFD) simulations. The CFD allows the engineer to model the heat generation, transfer, and dissipation, as the missile traverses its flight envelope. The precise placement of cooling channels, radiators, and other thermal management, features these aids.




Figure 11: A computational fluid dynamics (CFD)simulation of the X-43 vehicle at a Mach 7 test condition with the engine operating similar to hypersonic cruise missile

3.3. Guidance and Navigation Systems

The high speeds and dynamic environments come across during hypersonic flight make traditional guidance and navigation systems unsatisfactory. Hypersonic missiles must be equipped with advanced real-time navigation systems that are capable of adjusting to changing conditions and responding to evasive tactics used by enemies.

3.3.1. Inertial Navigation System (INS)

The Inertial Navigation System (INS) is a critical component of hypersonic missiles, offering autonomous navigation capabilities without reliance on external signals. The system's accuracy and reliability are crucial for ensuring that the missile maintains its proposed trajectory throughout its flight profile.

Gyroscopes

Modern hypersonic missiles consist of fiber-optic gyroscopes (FOGs) and ring laser gyroscopes (RLGs), which provide superior accuracy and reduced drift compared to traditional mechanical gyroscopes. FOGs measure rotation by utilizing the interference of light traveling in opposite directions in a fiber optic loop, while RLGs use the Sagnac effect to determine angular velocity.

Accelerometers

Micro-electromechanical systems (MEMS) accelerometers are often employed due to their compact size and low cost. These devices measure the missile's acceleration and provide essential data for calculating velocity and position changes.

INS can continuously calculate the missile's position and velocity based solely on internal measurements. This independence from external references allows it to function effectively in environments where GPS signals may be compromised. While INS is resistant to jamming, it suffers from cumulative drift. To mitigate this, hypersonic missile systems integrate INS with other navigation aids for periodic corrections, ensuring long-range accuracy.

3.3.2. Global Navigation Satellite System (GNSS)

The integration of Global Navigation Satellite Systems (GNSS) enhances the precision of hypersonic missiles, providing real-time position updates from multiple satellite sources.

GPS and GLONASS

These systems allow missiles to achieve high accuracy through trilateration, enabling real-time updates of their position relative to Earth's surface. The integration of both GPS and GLONASS helps to enhance robustness against jamming.

Advanced GNSS receivers are equipped with techniques to resist electronic jamming, including frequency hopping and signal encryption. These enhancements ensure continued access to positional data in contested environments. GNSS systems must

also account for multipath errors—signals reflecting off surfaces before reaching the receiver. Techniques such as advanced signal processing algorithms help minimize these errors, maintaining accuracy during flight.

3.3.3. Terrain-Contour Matching (TERCOM)

TERCOM is a sophisticated guidance system that improves accuracy during the terminal phase of hypersonic flight by comparing the terrain beneath the missile with pre-loaded maps.

Radar Imaging

TERCOM employs radar systems to scan the ground and compare the detected terrain features with a digital elevation model (DEM) stored in the missile's memory. This comparison allows the missile to make real-time adjustments to its trajectory.

Map Matching Techniques

By using high-resolution terrain data, TERCOM can identify specific geographical features, improving targeting precision even in complex environments. This is particularly advantageous when GNSS signals are compromised.

TERCOM is especially useful for engaging ground targets in urban or rugged terrains, where precision is paramount. The effectiveness of TERCOM depends on the availability of accurate terrain data and the missile's altitude. Lower altitudes provide better terrain resolution but increase the risk of detection.

3.3.4. Artificial Intelligence and Autonomy

Artificial Intelligence (AI) is transforming hypersonic missile guidance systems by providing advanced capabilities for data processing, decision-making, and target engagement.

AI-Driven Navigation and Targeting

AI algorithms analyze incoming data from various sensors, allowing missiles to adapt their flight paths in real-time. This capability enhances the missile's responsiveness to dynamic battlefield conditions. By employing machine learning, these systems can improve target recognition and classification, enabling missiles to differentiate between legitimate targets and decoys or other false signals. AI enables missiles to execute evasive maneuvers based on predicted paths of enemy interceptors. By anticipating threats, the missile can adjust its trajectory to avoid interception.

The extreme G-forces encountered during hypersonic maneuvers can damage guidance systems. Current innovations focus on enhancing the durability of sensors and components. Advanced shock-resistant gyroscopes and accelerometers are designed to maintain their accuracy even under high-stress conditions.

3.4. Warhead Technology

Hypersonic missiles are designed to carry a variety of warheads depending on their mission and strategic objectives. The two primary categories of warheads carried by hypersonic missiles.

3.4.1. Conventional Warheads

Conventional warheads in hypersonic missiles are used for precision attacks on high-value targets such as military installations, naval vessels, and critical infrastructure. These warheads are typically high-explosive, fragmentation, or bunker-busting types, designed to maximize damage at the point of impact.

3.4.1.1. Advanced Explosive Chemistry

Explosive materials have endured significant innovations to enhance their reliability and energy output.

Octanitrocubane (ONC)

The ONC structure has eight N groups on the faces of an octahedron or, equivalently, in the molecule of a cubane, giving a very high detonation velocity of about 9,400 m/s. It has an energy density of roughly 5.3 MJ/kg which makes it able to generate powerful shockwaves. The decomposition of ONC involves a series of rapid reactions, leading to an explosion characterized by:

$$C_8H_8N_{16}O_8 \rightarrow \text{Products} + \text{Energy}$$

A large quantity of gases is produced at high temperatures in this reaction producing a devastating shockwave that can do extensive damage to targets.

CL-20 (Hexanitrohexaazaisowurtzitane)

One of the most potent explosives is CL-20 since its detonation velocity is approximately 9,500 m/s and its energy density is 4.0 MJ/kg. It performs better than RDX and TNT. The rapid gas expansion of CL-20 during detonation results from the efficient molecular arrangement to produce high-pressure shock waves, which cause severe damage to targets. During detonation, the reaction can be summarized as:

$$C_6H_6N_{12}O_{12} \rightarrow N_2 + CO_2 + \text{Energy}$$

TNAZ (1,3,3-Trinitroazetidine)

TNAZ is valued for its high thermal stability and significant energy output, making it suitable for

applications requiring resistance to accidental detonation. TNAZ has a high energy release per unit weight, ensuring reliability in critical applications.

3.4.1.2. Kinetic Energy and Penetration Mechanics

The destructive capacity of conventional warheads is amplified by the kinetic energy produced during hypersonic flight. The kinetic energy (KE) of a hypersonic missile can be calculated using:

$$KE = \frac{1}{2}mv^2$$

For a missile weighing 500 kg traveling at Mach 8, the kinetic energy at impact can exceed 40 megajoules, resulting in significant impact force.

Conventional warheads often employ high-density materials such as depleted uranium (DU) and tungsten for their penetrating capabilities.

- **Depleted Uranium (DU)**: With a density of approximately 19.1 g/cm³, DU exhibits self-sharpening properties, maintaining a sharp point during penetration to maximize depth.
- **Tungsten**: Tungsten is used in penetrator designs due to its high melting point (~3,422°C) and density (~19.25 g/cm³), providing excellent performance in extreme conditions. In its alloyed form (with small percentages of rhenium or nickel), tungsten's grains are oriented to resist plastic deformation. At hypersonic impact velocities, grain boundary sliding occurs, where the boundaries between individual crystalline grains deform to absorb the kinetic energy, allowing the material to retain structural integrity longer than monolithic metals.

Nano-Coated Penetrators

Coating tungsten penetrators with nanoscale layers of materials such as graphene can improve toughness while reducing weight. This leads to a more effective penetrator with the integrity of its structural integrity under extreme stress. Environmental degradation could also be protected against by nano coatings, so that warheads will remain stable and effective over time, even under extreme conditions.

Penetration Mechanics

The kinetic impact causes immediate structural failure, while the explosive charge amplifies the destruction. The combination of kinetic energy and explosive force ensures a high level of destruction against hardened targets.

3.4.2. Nuclear Warhead

Hypersonic missiles equipped with nuclear payloads pose a significant strategic threat due to the unpredictability of their flight paths and their ability to evade traditional missile defense systems.

Nuclear warheads on hypersonic platforms typically depend on two-stage thermonuclear configurations. A fission bomb acts as a primary to compress and ignite a secondary fusion stage. plutonium-239 is purified to minimize the presence of plutonium-240. It has a high spontaneous fission rate that can lead to premature detonation or reduced efficiency.

Usually, deuterium and tritium as the fusion fuel undergo fusion to release massive energy. The complexity of these designs allows for significant scalability in yield without a proportional increase in size. This staging is crucial for hypersonic missiles, where space is restricted.



Figure 12: Cutaway of thermonuclear warhead

The fission bomb (primary stage) creates X-ray radiation that transfers energy to compress the fusion fuel (secondary stage) in a near-instantaneous process. The fusion reaction is often boosted with small amounts of tritium, significantly increasing neutron production and efficiency. The radiation implosion mechanism leverages the momentum of X-ray energy to achieve spherical compression of the secondary stage, leading to ultra-high densities needed for fusion. Precision control of the spherical implosion is critical. At the extreme level, computational simulations based on Monte Carlo methods and molecular dynamics are employed to ensure that the implosion symmetry is as close to perfect as possible, reducing energy loss and increasing the yield.

3.4.2.1. Fission Process

The primary stage of a nuclear warhead typically consists of a fissile core made of plutonium-239 or uranium-235. When a neutron collides with these materials, it undergoes fission, releasing energy and additional neutrons. The fission process can be represented as follows:

$$^{235}U + n \rightarrow {}^{92}Kr + {}^{141}Ba + 3n + 200\ MeV$$

Boosted Fission devices are incorporated into the primary stage. A small amount of deuterium and tritium is placed within the core to "boost" the fission reaction. This results in the production of fast neutrons that vastly increase the number of fission reactions per unit of time. Boosted warheads are compact but pack a significantly larger punch.

Modern warhead designs aim to pack maximum explosive yield into smaller volumes. Boosted fission allows for smaller, more efficient designs that can withstand the limitations of hypersonic missile payload sections. Material science innovations such as nano-engineered neutron reflectors, further enhance the efficiency of the fission process by optimizing neutron economy.

Beryllium (Be) is commonly used as a neutron reflector in warheads. It has a high scattering cross-section for neutrons and can efficiently reflect fast neutrons into the fissile core, optimizing the fission chain reaction.

3.4.2.2. Fusion Process

In the secondary stage, deuterium and tritium nuclei are fused under extreme conditions generated by the primary explosion. The fusion reaction can be represented as:

$$D + T \rightarrow 4He + n + 17.6\ MeV$$

Most modern thermonuclear warheads use the Teller-Ulam configuration, where the primary fission explosion compresses the secondary fusion fuel via radiation implosion, achieving yields ranging from hundreds of kilotons to several megatons. This method allows for precise yield control, which can be adjusted for tactical or strategic needs.

During fusion, the warhead must maintain a stable "burn front" where the fusion fuel ignites and propagates rapidly through the secondary stage. Engineers account for thermal gradients and plasma pressures to ensure that the burn front moves uniformly. The deuterium and tritium nuclei involved in fusion undergo state transitions, governed by quantum chromodynamics (QCD). In extreme designs, simulations involving quantum lattice models predict the behavior of the nuclear forces at the subatomic level, ensuring that fusion conditions are met efficiently.

The tamper in a nuclear warhead serves a dual purpose. It reflects neutrons and provides inertia, delaying the expansion of the fission core to allow for more complete fission. Uranium-238 is often used as a tamper, as it can undergo fast fission by the high-energy neutrons from the fusion stage, increasing the overall yield.

Fusion reactions are optimized by carefully managing the neutron production in the fusion stage. Fast neutrons released during fusion enhance the fission of any remaining uranium-238 in the secondary stage, leading to a process known as fission-fusion-fission. This results in much higher energy yields compared to simple fission-fusion warheads.

Fusion reactions can trigger tritium production in situ by injecting small amounts of lithium-6 into the secondary stage, sustaining the fusion process longer and enhancing neutron production. This leads to a significant increase in the overall explosive yield.




Figure 13: Teller-Ulam two-stage thermonuclear bomb design

For a warhead in a hypersonic missile, shockwave dynamics during the implosion phase are critical, as any asymmetry or shockwave interaction with the missile's structural components could destabilize the warhead.

Engineers use multi-point initiation systems for the primary fission stage. These systems precisely synchronize high-explosive lenses to ensure uniform implosion of the fissile core. Shockwaves must converge symmetrically, compressing the core uniformly to create optimal conditions for supercriticality.

During the fission and fusion processes, a superheated plasma forms around the core. The warhead design must account for plasma turbulence and instabilities,

such as the Rayleigh-Taylor instability, which can disrupt the implosion symmetry.
At the cutting edge of warhead design, meta-materials engineered for specific atomic structures provide new ways to manipulate neutron reflection and material strength. These materials are being researched to withstand the shockwave velocities generated during detonation, which can exceed 15,000 m/s.

3.4.3. Payload Capacity

Hypersonic missiles are designed to be highly flexible in terms of the warheads they can carry. Their payload capacity varies based on the type of missile and its range. HGV like Russia's Avangard can carry large payloads, including multiple warheads, while HCM generally carries smaller payloads due to weight limitations imposed by the air-breathing engine system.

In general, the high speed and agility of hypersonic missiles allow them to carry

- Single Large Warheads: Suitable for strategic strikes where high-impact force is required.
- Multiple Smaller Warheads: (MIRVs – Multiple Independently Targetable Reentry Vehicles)

Multiple Independently Targetable Reentry Vehicles (MIRVs)

Revolutionary strategic military capabilities, integrated into hypersonic missile platforms allow for the delivery of multiple nuclear warheads to multiple distinct targets with never-before-seen precision by a single missile. Designed to operate at speeds exceeding Mach 5, these advanced systems require surviving temperature and aerodynamic stresses in ways that cannot be realized with accepted thermal protection and minimal warhead designs that still achieve high yield-to-weight ratios. Each reentry vehicle (RV) is equipped with advanced guidance systems, including inertial navigation and GPS, enhanced by artificial intelligence for real-time trajectory adjustments, ensuring accurate targeting in dynamic environments. Additionally, MIRV systems utilize decoys and electronic countermeasures to saturate and overwhelm adversary missile defenses, thereby enhancing their first-strike capabilities.



Figure 14: MIRVs of LGM-118 Peacekeeper ICBM

3.5. Communication and Data Link System

Communication and data link systems in hypersonic missiles are crucial for providing real-time guidance updates, navigation corrections, and target information. These systems ensure the missile remains connected to command centers and, if necessary, receives in-flight updates. However, the extreme conditions of hypersonic flight pose significant challenges to maintaining stable communication links.

Plasma Sheath Interference

One of the most significant challenges in maintaining communication during hypersonic flight is the plasma sheath that forms around the missile due to the intense heat and friction generated at speeds above Mach 5. As the missile travels at hypersonic speeds, the air around it becomes ionized and creates a plasma layer that can block or severely degrade radio frequency (RF) communication signals. The plasma sheath causes a communication blackout, blocking traditional RF signals and resulting in a loss of data links or commands from ground control.

Doppler Shift

The Doppler effect causes significant shifts in the frequency of communication signals due to the extremely high speeds of hypersonic missiles travel. This makes it difficult to maintain continuous data transmission. Advanced communication systems need to include algorithms to predict and correct these frequency shifts. This ensures that the signal remains usable even as the missile moves at extreme speeds relative to ground-based or airborne receivers.

3.5.1. Dual-Mode Communication Links

Many hypersonic missiles use dual-mode communication systems, combining radio frequency (RF) communications and satellite-based links to ensure continuous data transmission even in challenging conditions.

3.5.1.1. RF-Based Communications

RF signals are typically used for communication within line-of-sight. However, due to the plasma sheath effect, hypersonic missiles may experience disruptions in RF signals during their flight. To address this issue, advanced plasma-tolerant antennas are being developed. These antennas will enable specific frequency bands to pass through or around the plasma, ensuring continuous communication.

3.5.1.2. Satellite Communication (SATCOM)

SATCOM systems provide a global communication link for missile guidance updates and corrections. These systems leverage Low Earth Orbit (LEO) satellites, which ensure near-continuous communication even when the missile is flying at extreme altitudes and speeds.

3.5.2. Plasma-Sheath Mitigation Techniques

Technologies to mitigate or work around the communication blackout caused by the plasma sheath are critical for maintaining data links during flight.

3.5.2.1. Frequency-Selective Surfaces (FSS)

Research is underway to develop frequency-selective surfaces that allow certain communication frequencies to pass through the plasma sheath, effectively "punching through" the blackout.

3.5.2.2. Reentry Communications System (RCS)

Another approach involves timing communication bursts when the missile experiences plasma attenuation, a reduction in plasma density, allowing RF signals to penetrate briefly.

3.5.2.3. Laser-Based Communication

A developing alternative is laser communication, which can operate outside traditional RF bands and penetrate plasma layers more effectively. Laser communications use optical signals to transmit data, thus bypassing many of the issues posed by plasma interference.

3.5.3. Data Links for Real-Time Targeting and In-Flight Updates

Data links are essential for providing real-time updates to the missile's navigation and targeting systems. This allows hypersonic missiles to receive inflight adjustments and retargeting commands if the threat environment changes.

In modern hypersonic systems, continuous communication with command centers or UAVs provides real-time updates on the target's position. As many targets, such as mobile ground vehicles or ships, can change position during the missile's flight, these updates are crucial for ensuring accurate engagement.

Hypersonic missiles utilize encrypted communication links to prevent interception and ensure the security of sensitive data transmissions. Frequency hopping and spread spectrum techniques are commonly used to avoid jamming or signal interference by enemy defenses.

3.6. Stealth and Evasion Systems

Stealth and evasion systems are designed to minimize the missile's detectability and maximize its survivability during flight. Hypersonic missiles must evade both radar detection and interceptor missiles, leveraging their speed, advanced materials, and electronic warfare capabilities to avoid interception.

3.6.1. Low Radar Cross-Section (RCS) Design

Hypersonic missiles use various stealth techniques to reduce their radar cross-section (RCS) and avoid detection by enemy radar systems. The missiles are designed with angular surfaces and blended edges to deflect radar waves away from the source. This design is similar to that used in stealth aircraft like the F-35 and B-2 bomber.

Additionally, radar-absorbent materials are applied to the missile's exterior to further reduce its radar signature by absorbing radar waves instead of reflecting them. Some missiles are also coated with dielectric materials to scatter radar signals and make it harder for radar systems to form a coherent image.

3.6.2. Infrared Signature Reduction

In addition to radar stealth, reducing the infrared (IR) signature is essential to evade infrared-seeking missiles and detection systems.

Hypersonic missiles generate extreme heat due to friction with the atmosphere, creating a large infrared signature. To mitigate this, advanced thermal management systems are employed. These systems use heat-resistant materials and active cooling systems to reduce the infrared signature.

Hypersonic missiles create a plasma field around their surface at high speeds, and there is ongoing research into using this plasma field to reduce the infrared signature by masking the missile's heat emissions.

3.7. Flight Control System

The flight control system (FCS) in a hypersonic missile manages the missile's stability, trajectory, and maneuverability. Due to the extreme velocities and the need for evasive capabilities, the FCS must be both highly responsive and durable, capable of maintaining

control under immense aerodynamic forces and thermal loads.

3.7.1. Thrust Vector Control (TVC)

Thrust vector control (TVC) enables the missile to adjust its flight path by changing the direction of its exhaust flow. This technology is crucial for hypersonic missiles, as traditional aerodynamic surfaces such as fins become less effective at extreme speeds.

TVC systems use movable exhaust nozzles or internal vanes to deflect the missile's thrust, allowing for rapid changes in direction without relying on control surfaces.

The thrust vector control (TVC) allows the missile to make precise course adjustments, improving its capability to avoid missile defense systems. Even at high altitudes with thinner air, TVC continues to be effective, providing the missile with better control during the boost and mid-course stages of flight.

3.7.2. Reaction Control Systems (RCS)

At extreme speeds, hypersonic missiles need additional mechanisms for precise control. Reaction Control Systems (RCS) use small bursts of gas or plasma to fine-tune the missile's orientation and trajectory.

RCS employs small thrusters positioned around the missile's body to produce torque, enabling precise adjustments to the missile's pitch, yaw, and roll. RCS allows for minor course corrections that would be difficult to achieve using TVC alone, especially in the terminal phase when the missile is closing in on a target.

3.7.3. Advanced Aerodynamic Control Surfaces

Some hypersonic missiles use advanced aerodynamic control surfaces in addition to TVC and RCS for extra maneuverability, especially during lower-speed phases or at lower altitudes. These control surfaces need to be made from heat-resistant materials such as ceramic composites or high-temperature alloys to withstand the intense thermal loads experienced during hypersonic flight.

3.8. Countermeasure Systems

Countermeasure systems in hypersonic missiles are designed to protect the missile from detection and interception by enemy defenses. These systems are crucial for ensuring the missile's survivability in contested environments where sophisticated air defense systems are deployed.

3.8.1. Electronic Countermeasures (ECM)

3.8.1.1. Radar Jamming

Radar jammers emit signals that can either overload enemy radar systems or confuse them by producing false signals. This makes it difficult for the radar to maintain a lock on the missile.

By jamming radar, the missile can avoid early detection, allowing it to approach the target more closely before defenses can respond. Jamming systems also support evasive maneuvers by reducing the enemy's ability to track the missile's flight path.

3.8.1.2. Infrared Jamming

Infrared (IR) jammers emit infrared radiation at specific frequencies to confuse incoming IR-guided interceptors. This can either mask the missile's actual heat signature or create false heat sources. By confusing the IR-seeker on enemy missiles, infrared jammers improve the missile's ability to survive against heat-seeking interceptors.

3.8.2. Plasma-Based Countermeasures

3.8.2.1. Plasma Sheath

The plasma sheath created around a hypersonic missile during flight can serve as a natural countermeasure by interfering with radar systems. The plasma effectively absorbs or refracts radar waves, reducing the missile's radar cross-section (RCS) and making it more difficult to track.

The plasma sheath formed by the ionized air around the missile at hypersonic speeds can be tuned to absorb specific radar frequencies, acting as a form of plasma stealth. This technology is still under research and development, but it holds promise as an additional stealth mechanism.

By reducing the missile's radar signature, the plasma sheath delays detection by enemy radar, allowing the missile to close in on its target before interception systems can engage.

3.8.2.2. Plasma Cloaking for Infrared

In addition to radar, plasma-based technologies are being explored for infrared cloaking. By manipulating the plasma field, engineers aim to mask the missile's infrared heat signature, making it difficult for IR-guided interceptors to detect and engage.

By controlling the energy distribution within the plasma sheath, the missile's infrared emissions could be dispersed or refracted, lowering the heat signature visible to IR detectors.

This makes the missile less visible to IR-based tracking systems, adding another layer of protection against modern missile defense systems.

4. Hypersonic Missile Platforms

4.1. Air-Based Hypersonic Missile Platforms

Airborne systems are designed to launch hypersonic missiles from high-altitude platforms, utilizing their speed and range to quickly engage time-sensitive targets.

4.1.1. Bomber / Fighter Launch Systems

Strategic bombers can be modified to carry and launch hypersonic missiles. This approach allows for launching strikes from beyond the reach of enemy air defenses, which increases their survivability. By launching hypersonic missiles from a distance, bombers can avoid detection and interception.

Bombers like the B-52 or B-2 can carry multiple hypersonic missiles, allowing for simultaneous strikes on multiple targets. Russia uses a Su-34 as a launcher for the Kinzhal hypersonic missile. The U.S. Air Force is considering integrating hypersonic capabilities into the B-21 Raider to enhance the strategic strike capability of its bomber fleet.

4.1.2. Unmanned Aerial Vehicles (UAVs)

UAVs can be used for various missions, such as reconnaissance and strike, offering multiple operational options in a single platform. By utilizing UAVs, military planners can reduce the risks associated with manned missions, especially in hostile airspace.

The X-47B, developed by Northrop Grumman, demonstrates the potential for UAVs to carry advanced weaponry, including hypersonic missiles, for future combat operations.

4.2. Ground-Based Hypersonic Missile Platforms

Ground-based platforms are among the most common types of systems designed for deploying hypersonic missiles. They offer mobility, quick launch capabilities, and the ability to rapidly reposition in response to changing threats.

4.2.1. Mobile Launch Systems

Mobile launch systems are equipped with hypersonic missiles mounted on transport vehicles, allowing for flexibility in deployment. These vehicles can include trucks or specialized platforms that enable rapid relocation.

Mobile launchers are harder to target, as they can be moved quickly and unpredictably. This reduces their vulnerability to preemptive strikes and allows for rapid deployment and launch in response to immediate threats, enhancing operational readiness.

The Russian Avangard system is an example of a mobile hypersonic missile platform capable of delivering nuclear payloads. The United States is developing the Common Hypersonic Glide Body (CHGB) to be deployed on mobile platforms for greater flexibility.

4.3. Sea-Based Hypersonic Missile Platforms

Sea-based platforms provide significant strategic advantages by deploying hypersonic missiles from naval vessels. These platforms can operate in international waters, allowing for a broader range of engagement without violating territorial airspace.

4.3.1. Submarine Launch Systems

Submarines can operate undetected and provide an element of surprise when launching hypersonic missiles against high-value targets on land or sea. The ability to launch from offshore positions extends a nation’s reach while minimizing risks associated with land-based deployments.

The U.S. Navy is exploring the integration of hypersonic systems into its Virginia-class submarines, enhancing their strike capabilities. The Russian Project 885 Yasen-class submarines are designed to accommodate hypersonic missiles alongside conventional cruise missiles.

4.3.2. Surface Ship Launch Systems

Surface vessels, such as destroyers and cruisers, can be equipped with vertical launch systems (VLS) to deploy hypersonic missiles. These vessels can perform various roles, from anti-air to land-attack missions, which enhances their operational versatility. They can operate within a larger naval task force, using data from other ships and aircraft to coordinate strikes.

The U.S. Navy's Zumwalt-class destroyers are currently being assessed for their potential to carry hypersonic missiles, which could improve their offensive capabilities against land targets.

5. Strategic Considerations

5.1. Global Power Dynamics

Hypersonic missiles offer a unique combination of speed, precision, and evasive capabilities, which significantly alters global military power dynamics. Countries like the United States, Russia, and China are in a race to develop these advanced weapons. Each of these nations sees hypersonic technology as essential to maintaining or achieving strategic superiority

5.1.1. Anti-Access/Area Denial (A2/AD) Zones

Hypersonic missiles can penetrate sophisticated A2/AD defenses deployed by China and Russia, which are designed to deter U.S. forces from operating freely in contested regions. These systems can be launched from long distances and strike high-value, time-sensitive targets within minutes, disrupting enemy command and control capabilities. In a potential conflict with China or Russia, those A2/AD systems could be targets for U.S., NATO hypersonic missiles or alternatives.

Approximate Coverage Areas of China's Potential A2/AD Defenses



Figure 15: Approximate Coverage Areas of China's Potential A2/AD Defenses
Data source: Congressional Budget Office.

The weapon systems that make up China's A2/AD zone include air and missile defense systems that are assumed to cover China's coastline. Some air defense sites might also be launching sites for antiship ballistic missiles; those launchers are potentially mobile. China's military airfields, where fighter aircraft and bombers that could launch cruise missiles are based, are generally located farther inland. Basing those A2/AD systems on Chinese-occupied islands in the South China Sea would extend their coverage areas.



Figure 16: Areas of China that a Missile Launched from Guam Could Reach Within 15 Minutes by Average Speed




Figure 17: Areas of China That a Missile Launched from Guam Could Reach Within 30 Minutes by Average Speed

Approximate Coverage Areas of Russia's Potential A2/AD Defenses




Figure 18: Approximate Coverage Areas of Russia's Potential A2/AD Defenses
Data source: Congressional Budget Office

Russia has been developing weapon systems that could keep U.S. and NATO allies' forces far away from its borders. In a potential conflict with Russia, those A2/AD systems could be targets for U.S. hypersonic missiles or alternatives.

Russian A2/AD systems consist of air and missile defense systems strategically located in coastal and inland locations, covering much of Europe and nearby waterways. Basing those systems outside mainland Russia, such as in Syria and Kaliningrad, would extend their coverage areas.



Figure 19: Areas of Russia That a Missile Launched from Germany Could Reach Within 15 Minutes by Average Speed



Figure 20: Areas of Russia That a Missile Launched from Germany Could Reach Within 30 Minutes by Average Speed

5.1.2. Strategic Deterrence

The integration of hypersonic missiles into a nation's arsenal raises the stakes for potential adversaries and creates new deterrence dynamics. The speed and maneuverability of these weapons diminish the effectiveness of traditional missile defense systems, making it harder for opponents to predict and counteract launches. This reinforces the concept of deterrence, where the potential cost of conflict is so high that adversaries are dissuaded from initiating an attack.

5.1.3. Arms Race Escalation:

The development of hypersonic technology by major military powers could lead to an arms race. As each country strives to outpace the other in missile capability, smaller nations could feel compelled to develop or acquire hypersonic capabilities, exacerbating global tensions and increasing the likelihood of conflict.

Table 2: Countries with alleged hypersonic devices and claimed speeds and distances

Country	Reported Vehicle	Claimed Mach Speed	Claimed Range (km)	Payload Capacity	Stage of Development	Year	Citations
Russia	Avangard HGV	Mach 20-27	10,000 km	Nuclear (2 MT)	Developed	2022	National Interest (Zachary Keck)
	Kinzhal	Mach 4-10	1,250 km	Nuclear (up to 500 Kt) or Conventional	Developed	2023	Jane's Defense (Alastair Gale)
	3M22 Zircon	Mach 8-9	1,000 km	Conventional or Nuclear	Developed	2023	BBC News (Jonathan Marcus)
China	DF-17 HGV	Mach 5-10	2,000 km	Conventional	Developed	2023	Global Times (Hu Xijin)
	DF-ZF	Mach 5+	2,000 km	Conventional	Developed	2023	South China Morning Post (Minnie Chan)
USA	AGM-183 ARRW	Mach 5-20	1,000 km	Conventional/ Nuclear	In Development	2024	Defense News (Valerie Insinna)
	HAWC	Mach 5+	Classified	Conventional	In Development	2024	The War Zone (Joseph Trevithick)
India	Shaurya	Mach 7-8	750 km	Nuclear or Conventional	Developed	2022	Times of India (Rajat Pandit)
	BrahMos-II	Mach 7-8	300 km	Conventional	In Development	2024	Hindustan Times (Rahul Singh)
France	V-MAX HGV	Mach 5+	Classified	Conventional	Developed	2024	Le Monde (Jean-Dominique Merchet)
Iran	Fattah	Mach 5+	1,400 km	Conventional/ Nuclear (Potential)	Developed	2023	Tehran Times (Reza Moghaddam)
North Korea	Hwasong-8	Mach 5+	1,000 km	Nuclear or Conventional	Developed	2022	NK News (Colin Zwirko)
UK	Hypersonic Cruise Missile	TBD	TBD	Conventional	In Development	2024	Jane's Defense (Tim Ripley)
South Korea	Hycore	Mach 5+	Classified	Conventional	In Development	2024	Yonhap News (Lee Jong-hwan)

Note: - There can be discrepancies between reported speeds, ranges, and payloads due to different testing conditions, national reporting, and strategic misinformation.

5.1.4. Dual-Use Concerns

With their dual-use nature, carrying either conventional or nuclear warheads-military strategy and arms control face immense challenges. Because, in most cases, the nature of a missile's payload cannot be determined ahead of time, the deployment of hypersonic missiles may lead to dangerous escalations, particularly in regions where geopolitical tensions are already high.

5.1.5. Strategic Advantages

5.1.5.1. First Strike Capability

Hypersonic missiles offer a formidable first-strike capability due to their ability to deliver nuclear payloads before an adversary can react. The combination of speed and maneuverability allows it to penetrate even the most advanced missile defense systems, rendering early-warning systems ineffective. Hypersonic missiles shorten the decision-making window for adversaries, effectively undermining the Mutual Assured Destruction (MAD) principle. This destabilizes the global strategic balance, as adversaries may perceive a disadvantage in their second-strike capabilities and feel compelled to engage in preemptive actions.

5.1.5.2. Second Strike Assurance

For countries relying on a second-strike deterrent, hypersonic missiles offer assurance that their nuclear capabilities can survive a first strike by the adversary and deliver a retaliatory blow. Their ability to evade advanced defense systems ensures they can bypass missile shields, such as THAAD or Russia's S-400 systems.

5.1.5.3. Low-Altitude Penetration

Hypersonic missiles (HGV, HCM) can fly at extremely low altitudes and make them difficult for radar and air defense systems to detect and intercept. By flying below the radar horizon and utilizing advanced maneuverability, they avoid the traditional ballistic trajectories that make conventional ICBMs vulnerable to early detection and interception.

Existing defense systems like the U.S. THAAD and Russian S-400 are optimized to intercept ballistic missiles, not hypersonic threats. Hypersonic missiles' low-altitude flight profile, coupled with extreme maneuverability, allows them to bypass these defenses entirely.



Figure 21: Effects of Altitude on a Radar's Ability to Detect a Missile

6. Ethical Considerations

6.1. Proliferation Risks

Perhaps the most disturbing ethical concern about hypersonic missiles is proliferation. Since hypersonic technology is increasingly spreading, there is a potential that either non-state actors or even a rogue state may develop such weapons themselves, through either development or illicit acquisition. Since the development or sale of hypersonic missiles is hindered by no international regulatory frameworks, the possibility for unregulated proliferation is high. This could result in regional destabilization across various parts of the globe if these arms fall into either terrorist organizations or hostile states.

6.2. Targeting and Civilian Safety

Precision and speed are hypothesized to become characteristics of hypersonic missiles, which makes them capable of conducting attacks with minimal collateral damage by targeting only military assets. However, the development of those weapons is of concern in more general contexts for the possible implications of deployment.

The reaction times for defense systems would be very short, and hence the possibility of making miscalculations leading to civilian casualties is increased. In a situation involving densely populated areas or urban warfare, even the tiniest error in targeting can have disastrous consequences.

6.3. Ethics of First Strike Capability

Hypersonic missiles inherently provide a country with an enhanced first-strike capability, which raises ethical questions about their potential use of where and when. The potential for a first strike, particularly with hypersonic missiles that could carry nuclear warheads, threatens to destabilize the long-standing principle of MAD. The ability to neutralize an adversary's key assets in minutes could prompt preemptive strikes by increasing the risk of a large-scale conflict.

7. Legal Considerations

7.1. Absence of International Regulations

One of the most urgent legal issues surrounding hypersonic missiles is the lack of a specific international treaty or legal framework governing their development, testing, and deployment. Currently, hypersonic missiles are not covered by existing arms control treaties, such as the Intermediate-Range Nuclear Forces (INF) Treaty or the New START Treaty.

These treaties, which regulate limits on strategic offensive arms between the United States and Russia, do not adequately address the unique characteristics of hypersonic systems. Historically, these agreements have focused on traditional intercontinental ballistic missiles (ICBMs), leaving hypersonic missiles in a regulatory gray area. This gap in regulation allows nations to pursue developing and deploying these weapons without international oversight or restrictions.

7.2. Arms Control Treaties and Compliance

Existing arms control treaties have largely been ineffective in addressing the rise of hypersonic missile technology. With no current framework to regulate these new systems, there is an urgent need to revise international agreements.

With the collapse of the INF Treaty in 2019, both the United States and Russia are now free to develop intermediate-range hypersonic missiles. The treaty's failure to address the challenges posed by modern missile technologies highlights the inadequacy of legacy arms control frameworks.

To avoid the escalation of an arms race, international bodies like the United Nations and arms control advocacy groups are calling for new frameworks that specifically address hypersonic missiles. These frameworks would need to regulate development, testing, and deployment, ensuring transparency and reducing the risk of accidental conflicts.

7.3. War Crimes and Accountability

Given their capacity to strike with minimal warning and at extremely high speeds, the use of hypersonic missiles in certain contexts may breach International Humanitarian Law (IHL) concerning important principles such as proportionality and distinction between military and civilian targets. With the same precision and accuracy, hypersonic missiles could impart disproportionate damage concerning areas with high civilian densities. IHL requires states to ensure that attacks are proportionate to the military advantage gained. The high speed inherent in these weapons, together with reduced reaction times, can render full consideration of proportionality hard or impossible. The compressed timelines to make decisions to launch a hypersonic missile attack could lead to hurried or uninformed judgments and, therefore, contrary to the principle of distinction under IHL. And they may not be able to spend the time necessary to verify that the targets engaged are legitimate military targets, which could amount to war crimes.

8. Acknowledgements

The author wishes to express sincere appreciation to Professor Takehira Tetsuya, Professor of Military Science and Technology, Department of Defense Studies, School of Defense Science, National Defense Academy of Japan, and Professor Daisaku Sakaguchi, Department of Strategic Studies, National Defense Academy, Japan, for their thorough peer review and invaluable feedback on this report. Their expertise and detailed suggestions significantly enhanced the depth, clarity, and overall quality of this work. The author is deeply thankful for their guidance and encouragement throughout the completion of this report.

9. Conclusion

Hypersonic missile technology represents a significant leap forward in military capabilities, offering unprecedented speed, agility, and precision in targeting. The unique characteristics of hypersonic systems, including their ability to maneuver unpredictably and penetrate advanced missile defenses, fundamentally alter the landscape of modern warfare.

As nations develop and deploy hypersonic missiles, the challenges they present to existing arms control frameworks and international security cannot be overstated. The potential for an arms race driven by technological competition poses serious risks to global stability, emphasizing the need for new agreements and international cooperation. The use of hypersonic missiles raises ethical concerns due to their fast response times potentially leading to a first-strike mentality, increasing the risk of misjudgment and escalation during conflicts. Military leaders and policymakers must manage these risks through open communication and confidence-building measures. The future of hypersonic missile technology depends on nations engaging in responsible development and

deployment practices to ensure it contributes to global security.

10. References

[1] University of Maryland. (n.d.). *Thermal protection systems*. https://spacecraft.ssl.umd.edu/academics/791S24/791S24L17.TPSx.pdf

[2] Rivier, M., Lachaud, J., & Congedo, P. M. (2018). Ablative thermal protection system under uncertainties including pyrolysis gas composition. *Aerospace Science and Technology*, *84*, 1059–1069. https://doi.org/10.1016/j.ast.2018.11.048

[3] Urzay, J. & Center for Turbulence Research, Stanford University. (2020). The physical characteristics of hypersonic flows. In *Center for Turbulence Research, Stanford University*. https://web.stanford.edu/~jurzay/hypersonicsCh2_Urzay.pdf

[4] The Parliamentary Office of Science and Technology. (2023). Hypersonic missiles. In *POSTnote* (No. 696).

[5] Khan, B., The Institution of Engineers (India), Ali, S. A., The Institution of Engineers (India), Malik, S. J., The Institution of Engineers (India), & Srivastava, S. K. (2024). *North Korea unveils second hypersonic missile in fiery test*. https://doi.org/10.13140/RG.2.2.25801.76647

[6] Barbante, P. (2004). Fundamentals of hypersonic flight - Properties of high temperature gases. In *RTO-EN-AVT-116* (pp. 5–3). RTO AVT. Retrieved October 1, 2024, from https://www.researchgate.net/profile/Paolo-Barbante-2/publication/253373116_Fundamentals_of_hypersonic_flight-Properties_of_high_temperature_gases/links/00b4953c3def4e7f4d000000/Fundamentals-of-hypersonic-flight-Properties-of-high-temperature-gases.pdf

[7] Fletcher, D. G. & von Karman Institute. (2004). FUNDAMENTALS OF HYPERSONIC FLOW - AEROTHERMODYNAMICS. In *RTO AVT Lecture Series on "Critical Technologies for Hypersonic Vehicle Development"* (pp. 3–2). RTO.

[8] Youvan, D. (2024). *Advancements in Hypersonic and Container Missile Technologies: A Vision for Future Warfare* [Preprint]. https://doi.org/10.13140/RG.2.2.30817.52325

[9] Hodžić, M., & Prljača, N. (2024). Missile Guidance using Proportional Navigation and Machine Learning. *Journal of Engineering Research and Sciences*, *3*(3), 19–26. https://doi.org/10.55708/js0303003

[10] Youvan, D. (2024b). *A Comprehensive Analysis of Russia's Hypersonic Missile Systems*. https://www.researchgate.net/publication/383981270

[11] Coleman, C. C., Faruqi, F. A., Weapons Systems Division, & Defence Science and Technology Organisation. (2009). *On Stability and Control of Hypersonic Vehicles* (Report DSTO-TR-2358). Weapons Systems Division. http://www.dsto.defence.gov.au/corporate/reports/DSTO-TR-2358.pdf

[12] Law, Y. W., Gliponeo, J. J., Singh, D., McGuire, J., Liang, J., Ho, S.-Y., Jill Slay, UniSA STEM, University of South Australia, Australia, & SmartSat Cooperative Research Centre, Australia. (2023). *Detecting and Tracking Hypersonic Glide Vehicles: A Cybersecurity-Engineering Analysis of Academic Literature* [Journal-article].

[13] Wang, K., Chen, X., & Wen, Z. (2023). Analysis of Low-Frequency Communication of Hypersonic Vehicles in Thermodynamic and Chemical Non-Equilibrium State. *Applied Sciences*, *13*(19), 10815. https://doi.org/10.3390/app131910815

[14] Wright, D., & Tracy, C. L. (2023). *Hypersonic Weapons-Part 1: Background and Vulnerability to Missile Defenses*.

[15] Siam, M. K. (2021). Missile Detection and Destruction robot using Detection Algorithm. In *Missile Detection and Destruction robot using Detection Algorithm*.

[16] Tan, S., Lei, H., & Liu, T. (2019). Optimal Maneuver Trajectory for Hypersonic Missiles in Dive Phase Using Inverted Flight. *IEEE Access*, *7*, 63493–63503. https://doi.org/10.1109/access.2019.2916464

[17] Laad, P. A., & Knight, D. D. (2021). Hypersonic Flow Control of Kinzhal Missile via Off-Axis, Pulsed Energy Deposition. *Journal of Spacecraft and Rockets*, *59*(3), 704–716. https://doi.org/10.2514/1.a35174

[18] Fu, W., Yan, B., Chang, X., & Yan, J. (2016). Guidance Law and Neural Control for Hypersonic Missile to Track Targets. *Discrete Dynamics in Nature and Society*, *2016*, 1–10. https://doi.org/10.1155/2016/6219609

[19] George, G. J., Ley, M. D., UK Ministry of Defence, Atomic Weapons Establishment, & UK Minister of Foreign and Commonwealth Affairs. (2001). Nuclear warhead arms control research at AWE. *Verification Yearbook 2001*.

[20] United Nations. (1990). Comprehensive Study on Nuclear Weapons. In *DisarmamentFacts77*. https://inis.iaea.org/collection/NCLCollectionStore/_Public/23/026/23026473.pdf

[21] Schiller, M., ST Analytics, & The International Institute for Strategic Studies. (2022). *Missile Identification and Assessment*.

[22] Woolf, A. F. (2008). *Conventional Warheads for Long-Range Ballistic Missiles: Background and Issues for Congress* (By Congressional Research Service).

[23] Sugden, B. M. (2022). Analyzing the Potential Disruptive Effects of Hypersonic Missiles on Strategy and Joint Warfighting. In Institute for Defense Analyses, *Forum / Hypersonic Missiles and Joint Warfighting* (Vol. 104, Issue 1, p. 7).

[24] Sayler, K. M. & Congressional Research Service. (2024). *Hypersonic Weapons: Background and Issues for Congress* (No. R45811). https://sgp.fas.org/crs/weapons/R45811.pdf

[25] Congressional Budget Office. (2023). *U.S. Hypersonic Weapons and Alternatives*. https://www.cbo.gov/system/files/2023-01/58255-hypersonic.pdf

[26] Wilkening, D. (2019). Hypersonic Weapons and Strategic Stability. *Survival*, *61*(5), 129–148. https://doi.org/10.1080/00396338.2019.1662125

[27] Wright, D., & Tracy, C. L. (2023a). Hypersonic Weapons-Part 1: Background and Vulnerability to Missile Defenses. *arXiv (Cornell University)*. https://doi.org/10.48550/arxiv.2304.11137

[28] Peters, A. B., Zhang, D., Chen, S., Ott, C., Oses, C., Department of Materials Science and Engineering, Johns Hopkins University, Baltimore, MD 21218, USA, Johns Hopkins Applied Physics Laboratory, Laurel, MD 20723, Department of Materials Science and Engineering, Northwestern University, IL, USA. 60208, Department of Mechanical Engineering and Materials Science, Duke University, NC, USA. 27708, Center for Autonomous Materials Design, Duke University, NC, USA. 27708, Hopkins Extreme Materials Institute, Johns Hopkins University, Baltimore, MD, USA, 21218, Departments of Materials Engineering, University of California, Santa Barbara, CA, 93106, Department of Materials Science and Engineering, MIT, Cambridge, MA, USA, 02139, Department of Aeronautics and Astronautics, MIT, Cambridge, MA, USA, 02139, Curtarolo, S., McCue, I., Pollock, T., & Prameela, S. E. (2023). Materials Design for Hypersonics [Preprint]. *arXiv*. https://arxiv.org/abs/2309.04053v1

[29] Najmalddin, B. A. (2023). Iran's Ballistic Missile Program: From Coercive Diplomacy to Missile Diplomacy. *گۆڤاری کوردستانیی بۆ لێکۆڵینەوەی ستراتیجیی*, 243–244.

[30] Wei, Z., Ming, C., Yang, K., & Yan, S. (2024). Analysis of the dynamic characteristics of air-breathing supersonic missiles considering the effects of elasticity and actuator faults. *Journal of Physics Conference Series*, *2797*(1), 012012. https://doi.org/10.1088/1742-6596/2797/1/012012

[31] Materials design for hypersonics. (2024). In *Nature Communications* (Vol. 15, p. 3328). https://doi.org/10.1038/s41467-024-46753-3

[32] Siouris, G. M. (2004). *Missile Guidance and Control Systems*. Springer.

Hill, M. L., Akridge, J. M., Avery, W. H., APL Technical Digest, Hill, M. L., Akridge, J. M., & Avery, W. H. (1962). THERMAL INSULATION for. *APL Technical Digest*.

[33] Rivier, M., Lachaud, J., & Congedo, P. M. (2018b). Ablative thermal protection system under uncertainties including pyrolysis gas composition. *Aerospace Science and Technology*, *84*, 1059–1069. https://doi.org/10.1016/j.ast.2018.11.048

[34] Davis, D. & National Aeronautics and Space Administration. (n.d.). Fundamentals of Launch Vehicle Ablative Thermal Protection System (TPS) Materials. In *TFAWS2017*.

[35] RAND, SCHANZ, M. V., ACTON, J., MALLIK, A., James Martin Center for NonProliferation Studies, The Institute for Foreign Policy Analysis, CSIS, The Brookings Institution, The Mitchell Institute for Aerospace Studies, AIAA Guidance, Navigation and Control Conference and Exhibit, The Institute for Foreign Policy Analysis, Congressional Budget Office, The Brookings Institution, & Science and Global Security. (n.d.). *The implications of the advent of hypersonic weapon systems for strategic stability*. https://britishpugwash.org/wp-content/uploads/2019/12/M.Frigoli-Hypersonics-Stability-and-arms-control-PDF-2.pdf