






# PARAMETERIZED JUNIT TESTING

RICARDO JARDINEZ



# CREATE A JAVA PROJECT AND ADD JUNIT5 LIBRARY

- CREATE AND CALL THE JAVA PROJECT “Parameterized JUnit Testing”
- ADD THE JUNIT LIBRARY
  - RIGHT CLICK THE JAVA PROJECT WE JUST MADE (“Parameterized JUnit Testing”)
  - CLICK ON BUILD PATH → ADD LIBRARIES
  - SELECT JUNIT FROM THE POP UP WINDOW → NEXT
  - SELECT JUNIT5 → FINISH



# CREATE JAVA CLASS

- RIGHT CLICK ON OUR JAVA PROJECT → NEW → CLASS
- NAME JAVA CLASS “RandomMethods. JAVA ”
- CLICK FINISH



# RANDOM METHODS CODE

- ADD THE FOLLOWING METHODS INTO THE RandomMethods.JAVA CLASS

```
public static boolean isEven(int num)
{
    if (num %2 == 0)
        return true;
    else
        return false;
}
```



```
public static String Uppercase(String s)
{
    return s.toUpperCase();
}
```

```
public static int Add(int x, int y)
{
    return x + y;
}
```

```
public static String FullName(String first, String last)
{
    return first + " " + last;
}
```

# CREATE JUNIT TEST CASE

- RIGHT CLICK ON JAVA PROJECT → NEW → JUNIT TEST CASE
- NAME IT “Parameterized\_JUnit.JAVA” → CLICK FINISH



# WHAT IS PARAMETERIZED TESTING?

- PARAMETERIZED TESTING MAKES IT POSSIBLE TO RUN THE SAME TEST MULTIPLE TIMES WITH DIFFERENT ARGUMENTS
  - ALLOWS US TO QUICKLY VERIFY VARIOUS CONDITIONS WITHOUT HAVING TO WRITE A TEST FOR EACH CASE
- NEED TO USE THE `@ParameterizedTest` ANNOTATION
  - NEED TO IMPORT “org.junit.jupiter.params.ParameterizedTest” WHEN DOING PARAMETERIZED TESTS
- NEED TO DECLARE AN ARGUMENT SOURCE FOR THE TEST
  - DECLARE THESE ARGUMENTS SOURCES WITH DIFFERENT ARGUMENT SOURCE ANNOTATIONS
  - `@ValueSource` `@NullSource` `@MethodSource` `@ArgumentSource` `@CsvSource`

# @ValueSource

- SIMPLEST ARGUMENT SOURCE
- WE CAN PASS AN ARRAY OF LITERAL VALUES TO THE TEST METHOD
  - CAN SPECIFY AN ARRAY OF TYPES int, long, float, double, char, boolean, string, short, byte
- JUNIT WILL RUN THE TEST N NUMBER OF TIMES, EACH TIME ASSIGNS ONE ARGUMENT FROM THE ARRAY TO THE METHOD PARAMETER
- NEED TO IMPORT “org.junit.jupiter.params.provider.ValueSource”
- WHEN TO USE @ValueSource:
  - WHEN YOU HAVE A SINGLE DATA ENTRY
  - WHEN ITS POSSIBLE TO APPLY THE BOUNDARY VALUE ANALYSIS



# @ValueSource TEST CASE

- TESTING @VALUESOURCE WITH “IsEven” METHODS.

```
@ParameterizedTest
@ValueSource (ints = {2, 4, 6, 8, 10})
void testEven(int nums)
{
    assertEquals(true, RandomMethods.isEven(nums));
}
```

OR

```
@ParameterizedTest
@ValueSource (ints = {2, 4, 6, 8, 10})
void testEven2(int nums)
{
    //uses assertTrue instead of assertEquals
    assertTrue(RandomMethods.isEven(nums));
}
```



# @CsvSource

- ALLOWS IS TO USE A LIST/ARRAY OF COMMA-SEPARATED STRING VALUES
  - EACH ARRAY ENTRY CORRESPONDS TO A LINE IN A CSV FILE
- THIS SOURCE TAKES ONE ARRAY ENTRY EACH TIME, SPLITS IT BY THE COMMA AND PASSES EACH ARRAY TO THE ANNOTATED TEST METHOD AS SEPARATE PARAMETERS
- COMMA IS THE DEFAULT SEPARATOR BUT WE CAN CHANGE IT USING THE `delimiter` ATTRIBUTE
- THE `@CsvSource` ANNOTATION MAKES IT POSSIBLE TO PROVIDE MULTIPLE PARAMETERS TO THE TEST METHOD IN A COMPACT WAY
- NEED TO IMPORT “`org.junit.jupiter.params.provider.CsvSource`”

# @CsvSource TEST CASE

- TESTING @CsvSource WITH “Uppercase” AND “Add” METHODS

@ParameterizedTest

```
@CsvSource ({  
    "hello,HELLO", "bye,BYE", "asu,ASU", "GO,GO"  
})
```

OR

@ParameterizedTest



```
@CsvSource (value = {"hello~HELLO", "bye~BYE", "asu~ASU", "GO~GO"}, delimiter = '~')  
void testUpperCase(String n1, String n2)  
{  
    assertEquals(n2, RandomMethods.Uppercase(n1));  
}
```

@ParameterizedTest

```
@CsvSource ({  
    "1,2,3", "10,5,15", "0,100,100", "-16,8,-8"  
})
```

```
void testAdd(int n1, int n2, int answer)  
{
```

```
    assertEquals(answer, RandomMethods.Add(n1, n2));  
}
```





# @CsvSource TEST CASE CONT

- TESTING @CsvSource WITH "FullName" METHODS

```
@ParameterizedTest
@CsvSource ({
    "John, Doe, John Doe", "Bob, Ross, Bob Ross"
})
void testFirstAndLast(String first, String last, String FullName)
{
    assertEquals(FullName, RandomMethods.FullName(first, last));
}
```

```
@ParameterizedTest
@CsvSource ({
    "2", "4", "6", "8", "10"
})
void testFirstAndLast(int num1)
{
    assertEquals(true, RandomMethods.isEven(num1));
}
```



# @MethodSource

- APPROACH TO PROVIDING MORE COMPLEX ARGUMENTS
- @MethodSource ALLOWS IS TO REFER TO A FACTORY METHOD THAT RETURNS THE ARGUMENTS
- CREATING AND USING OBJECTS
- NEED TO IMPORT “org.junit.jupiter.params.provider.MethodSource”
- THE NAME WE GIVE TO @MethodSource NEEDS TO MATCH AN EXISTING METHOD
  - WHEN WE DON'T PROVIDE @MethodSource WITH A NAME FOR THE JUNIT WILL SEARCH FOR A SOURCE METHOD WITH THE SAME NAME AS THE TEST METHOD

# @MethodSource TEST CASE

- TESTING @MethodSource WITH “Add” AND “Uppercase” METHODS

```
private static Object[] inputs()
{
    return new Object[][]
    {
        {1,2,3},
        {10,5,15},
        {0,100,100},
        {-16,8,-8}
    };
}

@ParameterizedTest
@MethodSource("inputs")
void AddMethodSource (int num1, int num2, int answer)
{
    assertEquals(answer, RandomMethods.Add(num1, num2));
}
```

```
private static Object[] inputs()
{
    return new Object[][]
    {
        {"hello","HELLO"},
        {"bye","BYE"},
        {"asu","ASU"},
        {"GO","GO"}
    };
}

@ParameterizedTest
@MethodSource("inputs")
void UpperCaseMethodTesting (String users, String Answer)
{
    assertEquals(Answer,RandomMethods.Uppercase(users));
}
```

# @MethodSource TEST CASE CONT

- TESTING @MethodSource WITH “isEven” AND “FullName” METHODS

```
private static Object[] inputs()
{
    return new Object[][]
    {
        {2},
        {4},
        {6},
        {8},
        {10}
    };
}

@ParameterizedTest
@MethodSource("inputs")
void isEvenMethodTesting (int num1)
{
    assertEquals(true, RandomMethods.isEven(num1));
}
```

```
private static Object[] inputs()
{
    return new Object[][]
    {
        {"John", "Doe", "John Doe"},
        {"Bob", "Ross", "Bob Ross"}
    };
}

@ParameterizedTest
@MethodSource("inputs")
void AddMethodSource (String first, String last, String answer)
{
    assertEquals(answer, RandomMethods.FullName(first, last));
}
```