



## ☆ QUESTION-1



1

CLASS NAMED EXAMPLE IS HAVING TWO PRIVATE DATA MEMBERS NAMED AS A AND B.A FUNCTION WHICH IS OUTSIDE THE CLASS WANTS ACCESS THESE PRIVATE DATA MEMBERS AND FINALLY WANT TO DISPLAY THE SUM OF IT.

2

3

## YOUR ANSWER

4

We recommend you take a quick tour of our editor before you proceed.  
The timer will pause up to 90 seconds for the tour.

[Start tour](#)


5

Original code C++

```
1 ▶ #include <iostream>
23
24 using namespace std;
25 class EXAMPLE
26     {int A,B;
27
28     public:
29     void get(int x,int y)
30     {
31         A=x;
32         B=y;
33     }
34     friend void display(EXAMPLE o)
35     {
36         cout<<o.A+o.B;
37     }
38 };
39
40 int main()
41 {EXAMPLE e;
42     int a,b;
43     cin>>a>>b;
44     e.get(a,b);display(e);return 0;}
```

Line: 27 Col: 1



 [Download sample test cases](#)  
Notepad to edit them on windows.

*The input/output files have Unix line endings. Do not use*



1

[About](#) [Privacy Policy](#) [Terms of Service](#)

2

3

4

5