LeetCode SQL 50

Advanced Select and Joins

Created by: Bhawna Gupta

1731. The Number of Employees Which Report to Each Employee

Input:
Employees table:

employee_id	name	reports_to	age
9	Hercy	null	43
6	Alice	9	41
4	Bob	9	36
2	Winston	null	37

Output:

employee_id	name	reports_count	average_age
9	Hercy	2	39

```sql
Select
  m.employee_id,
  m.name,
  count(e.name) As reports_count,
  Round(Avg(e.age), 0) As average_age
From
  Employees e
  Join Employees m On e.reports_to = m.employee_id
Group by
  m.employee_id
Order by
  m.employee_id;
```

Created by: Bhawna Gupta

1789. Primary Department for Each Employee

Input:

Employee table:

employee_id	department_id	primary_flag
1	1	N
2	1	Y
2	2	N
3	3	N
4	2	N
4	3	Y
4	4	N

Output:

employee_id	department_id
1	1
2	1
3	3
4	3

```
Select
  employee_id, department_id
From
  Employee
Where
  primary_flag = 'Y'
Union
Select
  employee_id, department_id
From
  Employee
Group by
  employee_id
Having
  count(employee_id)= 1;
```

Created by: Bhawna Gupta

610. Triangle Judgement

Input:

Triangle table:

x	y	z
13	15	30
10	20	15

Output:

x	y	z	triangle
13	15	30	No
10	20	15	Yes

```
Select
  x, y, z,
  (If(
      x + y > z
      AND y + z > x
      And z + x > y,
      "Yes",
      "No")) As triangle
From
  Triangle;
```

Created by: Bhawna Gupta

180. Consecutive Numbers

Input:
Logs table:

id	num
1	1
2	1
3	1
4	2
5	1
6	2
7	2

Output:

ConsecutiveNums
1

```sql
With CTE As (
  Select
    id, num,
    lead(num) over(Order By id) as next,
    lag(num) over(Order By id) As previous,
    lead(id) over(Order By id) As nextid,
    lag(id) over(Order By id) As previousid
  From
    Logs
)
Select
  Distinct num As ConsecutiveNums
from
  CTE
Where
  num = next
  And num = previous
  And id+1=nextid And id-1=previousid;
```

Created by: Bhawna Gupta

1164. Product Price at a Given Date

Input:

Products table:

product_id	new_price	change_date
1	20	2019-08-14
2	50	2019-08-14
1	30	2019-08-15
1	35	2019-08-16
2	65	2019-08-17
3	20	2019-08-18

Output:

product_id	price
2	50
1	35
3	10

```sql
Select
  product_id, 10 As price
From Products
Group By product_id
Having
  Min(change_date)> '2019-08-16'
Union
Select
  product_id, new_price as price
From Products
Where
  (product_id, change_date) IN (
    Select
      product_id,
      Max(change_date)
    from Products
    Where change_date <= '2019-08-16'
    Group by product_id);
```

Created by: Bhawna Gupta

1204. Last Person to Fit in the Bus

Input:
Queue table:

person_id	person_name	weight	turn
5	Alice	250	1
4	Bob	175	5
3	Alex	350	2
6	John Cena	400	3
1	Winston	500	6
2	Marie	200	4

Output:

person_name
John Cena

```sql
Select person_name
From
  (Select person_name,
      sum(weight) over (
        order by
          turn) As Cumulative_weight
    From queue) As T2
Where
  Cumulative_weight <= 1000
Order by
  Cumulative_weight DESC
limit 1;
```

Created by: Bhawna Gupta

1907. Count Salary Categories

Input:

Accounts table:

account_id	income
3	108939
2	12747
8	87709
6	91796

Output:

category	accounts_count
Low Salary	1
Average Salary	0
High Salary	3

```
Select
  "Low Salary" as category,
  sum(if(income < 20000, 1, 0)
  ) As accounts_count From Accounts
Union
Select
  "Average Salary" as category,
  sum(if(income >= 20000
      And income <= 50000, 1, 0
    )) As accounts_count
From Accounts
Union
Select
  "High Salary" as category,
  sum(if(income > 50000, 1, 0)
  ) As accounts_count
From Accounts;
```

Created by: Bhawna Gupta