



Bikkad IT Institute

10. SQL Date & Time Formats

Compiled by Bikkad IT Institute | Teaching Notes

OUR LOCATIONS

+91 77220 82225
Pimpri-Chinchwad

+91 77220 82226
Chh. Sambhajinagar

+91 77220 82227
Nashik

+91 77220 82224
Hadapsar, Pune

SQL Date & Time Formats

10 · Date & Time Formats — Complete Reference Guide

Table of Contents

1. Numeric Format Specifiers
2. Date Format Specifiers
3. All Date Parts (DATEPART / DATENAME / DATETRUNC)
4. Culture Code Formatting

1. Numeric Format Specifiers

→ *FORMAT() numeric specifiers for 1234.56*

SELECT 'N'	AS FormatType, FORMAT(1234.56, 'N')	AS FormattedValue -- 1,234
UNION ALL		
SELECT 'P',	FORMAT(1234.56, 'P')	-- Percent
UNION ALL		
SELECT 'C',	FORMAT(1234.56, 'C')	-- Curren
UNION ALL		
SELECT 'E',	FORMAT(1234.56, 'E')	-- Scient
UNION ALL		
SELECT 'F',	FORMAT(1234.56, 'F')	-- Fixed
UNION ALL		
SELECT 'N0',	FORMAT(1234.56, 'N0')	-- No dec
UNION ALL		
SELECT 'N1',	FORMAT(1234.56, 'N1')	-- 1 deci
UNION ALL		
SELECT 'N2',	FORMAT(1234.56, 'N2')	-- 2 deci
UNION ALL		
SELECT 'N_de-DE',	FORMAT(1234.56, 'N', 'de-DE')	-- German
UNION ALL		
SELECT 'N_en-US',	FORMAT(1234.56, 'N', 'en-US')	-- US sty

2. Date Format Specifiers

→ *Common date/time format specifiers using FORMAT(GETDATE(), ...)*

OUR LOCATIONS

+91 77220 82225
Pimpri-Chinchwad

+91 77220 82226
Chh. Sambhajinagar

+91 77220 82227
Nashik

+91 77220 82224
Hadapsar, Pune

```
-- Day specifiers
FORMAT(GETDATE(), 'D')      -- Full date pattern
FORMAT(GETDATE(), 'd')      -- Short date pattern
FORMAT(GETDATE(), 'dd')     -- Day with leading zero    e.g. 05
FORMAT(GETDATE(), 'ddd')    -- Abbreviated day name    e.g. Mon
FORMAT(GETDATE(), 'dddd')   -- Full day name          e.g. Monday

-- Month specifiers
FORMAT(GETDATE(), 'M')      -- Month without leading zero
FORMAT(GETDATE(), 'MM')     -- Month with leading zero   e.g. 06
FORMAT(GETDATE(), 'MMM')    -- Abbreviated month         e.g. Jan
FORMAT(GETDATE(), 'MMMM')   -- Full month name           e.g. January

-- Year specifiers
FORMAT(GETDATE(), 'yy')     -- Two-digit year            e.g. 25
FORMAT(GETDATE(), 'yyyy')   -- Four-digit year           e.g. 2025

-- Time specifiers
FORMAT(GETDATE(), 'hh')     -- Hour 12-hr with zero     e.g. 09
FORMAT(GETDATE(), 'HH')     -- Hour 24-hr with zero     e.g. 21
FORMAT(GETDATE(), 'mm')     -- Minutes with zero        e.g. 05
FORMAT(GETDATE(), 'ss')     -- Seconds with zero        e.g. 07
FORMAT(GETDATE(), 'fff')    -- Milliseconds
FORMAT(GETDATE(), 'tt')     -- AM/PM designator         e.g. PM
```

3. All Date Parts — DATEPART / DATENAME / DATETRUNC

→ *Comparison of date part functions across all supported parts*

SELECT 'Year'	AS DatePart, DATEPART(year,	GETDATE()), DATENAME(year,
UNION ALL		
SELECT 'Quarter',	DATEPART(quarter,	GETDATE()), DATENAME(quarter,
UNION ALL		
SELECT 'Month',	DATEPART(month,	GETDATE()), DATENAME(month,
UNION ALL		
SELECT 'DayOfYear',	DATEPART(dayofyear,	GETDATE()), DATENAME(dayofyear,
UNION ALL		
SELECT 'Day',	DATEPART(day,	GETDATE()), DATENAME(day,
UNION ALL		
SELECT 'Week',	DATEPART(week,	GETDATE()), DATENAME(week,
UNION ALL		
SELECT 'Weekday',	DATEPART(weekday,	GETDATE()), DATENAME(weekday,
UNION ALL		
SELECT 'Hour',	DATEPART(hour,	GETDATE()), DATENAME(hour,
UNION ALL		
SELECT 'Minute',	DATEPART(minute,	GETDATE()), DATENAME(minute,

OUR LOCATIONS

```

UNION ALL
SELECT 'Second',          DATEPART(second,      GETDATE()), DATENAME(second,
UNION ALL
SELECT 'Millisecond',      DATEPART(millisecond, GETDATE()), DATENAME(millisecond,
UNION ALL
SELECT 'ISOWeek',          DATEPART(iso_week,    GETDATE()), DATENAME(iso_week,

```

4. Culture Code Formatting

→ *FORMAT() with culture codes for numbers and dates*

```

SELECT 'en-US' AS CultureCode,
      FORMAT(1234567.89, 'N', 'en-US') AS FormattedNumber,
      FORMAT(GETDATE(), 'D', 'en-US') AS FormattedDate
UNION ALL SELECT 'en-GB', FORMAT(1234567.89, 'N', 'en-GB'), FORMAT(GETDATE(), 'D', 'en-GB')
UNION ALL SELECT 'fr-FR', FORMAT(1234567.89, 'N', 'fr-FR'), FORMAT(GETDATE(), 'D', 'fr-FR')
UNION ALL SELECT 'de-DE', FORMAT(1234567.89, 'N', 'de-DE'), FORMAT(GETDATE(), 'D', 'de-DE')
UNION ALL SELECT 'es-ES', FORMAT(1234567.89, 'N', 'es-ES'), FORMAT(GETDATE(), 'D', 'es-ES')
UNION ALL SELECT 'zh-CN', FORMAT(1234567.89, 'N', 'zh-CN'), FORMAT(GETDATE(), 'D', 'zh-CN')
UNION ALL SELECT 'ja-JP', FORMAT(1234567.89, 'N', 'ja-JP'), FORMAT(GETDATE(), 'D', 'ja-JP')
UNION ALL SELECT 'ru-RU', FORMAT(1234567.89, 'N', 'ru-RU'), FORMAT(GETDATE(), 'D', 'ru-RU')
UNION ALL SELECT 'ar-SA', FORMAT(1234567.89, 'N', 'ar-SA'), FORMAT(GETDATE(), 'D', 'ar-SA')
UNION ALL SELECT 'hi-IN', FORMAT(1234567.89, 'N', 'hi-IN'), FORMAT(GETDATE(), 'D', 'hi-IN')

```