



Bikkad IT Institute

---

## 22. SQL Stored Procedures

*Compiled by Bikkad IT Institute | Teaching Notes*

---

---

### OUR LOCATIONS

+91 77220 82225  
Pimpri-Chinchwad

+91 77220 82226  
Chh. Sambhajinagar

+91 77220 82227  
Nashik

+91 77220 82224  
Hadapsar, Pune

# SQL Stored Procedures

22 · Stored Procedures — Complete Reference Guide

## Table of Contents

1. Basics — Creation and Execution
2. Parameters
3. Multiple Queries
4. Variables
5. Control Flow with IF/ELSE
6. Error Handling with TRY/CATCH

## 1. Basics — Create and Execute

→ *Define a basic stored procedure*

```
CREATE PROCEDURE GetCustomerSummary AS
BEGIN
    SELECT
        COUNT(*) AS TotalCustomers,
        AVG(Score) AS AvgScore
    FROM Sales.Customers
    WHERE Country = 'USA';
END
GO
```

→ *Execute the stored procedure*

```
EXEC GetCustomerSummary;
```

## 2. Parameters

→ *ALTER to add a parameter with a default value*

```
ALTER PROCEDURE GetCustomerSummary
    @Country NVARCHAR(50) = 'USA'
AS
```

### OUR LOCATIONS

**+91 77220 82225**  
Pimpri-Chinchwad

**+91 77220 82226**  
Chh. Sambhajnagar

**+91 77220 82227**  
Nashik

**+91 77220 82224**  
Hadapsar, Pune

```
BEGIN
    SELECT
        COUNT(*) AS TotalCustomers,
        AVG(Score) AS AvgScore
    FROM Sales.Customers
    WHERE Country = @Country;
END
GO
```

→ *Execute with different parameter values*

```
EXEC GetCustomerSummary @Country = 'Germany';
EXEC GetCustomerSummary @Country = 'USA';
EXEC GetCustomerSummary; -- uses default 'USA'
```

### 3. Multiple Queries

→ *Run two independent reports inside one procedure*

```
ALTER PROCEDURE GetCustomerSummary
    @Country NVARCHAR(50) = 'USA'
AS
BEGIN
    -- Query 1: Customer count and average score
    SELECT
        COUNT(*) AS TotalCustomers,
        AVG(Score) AS AvgScore
    FROM Sales.Customers
    WHERE Country = @Country;

    -- Query 2: Order count and total sales
    SELECT
        COUNT(OrderID) AS TotalOrders,
        SUM(Sales) AS TotalSales
    FROM Sales.Orders AS o
    JOIN Sales.Customers AS c
        ON c.CustomerID = o.CustomerID
    WHERE c.Country = @Country;
END
GO
```

### 4. Variables

→ *Declare variables, capture query results, print to console*

```
ALTER PROCEDURE GetCustomerSummary
    @Country NVARCHAR(50) = 'USA'
AS
BEGIN
```

#### OUR LOCATIONS

```

DECLARE @TotalCustomers INT, @AvgScore FLOAT;

SELECT
    @TotalCustomers = COUNT(*),
    @AvgScore       = AVG(Score)
FROM Sales.Customers
WHERE Country = @Country;

PRINT('Total Customers from ' + @Country + ':'
      + CAST(@TotalCustomers AS NVARCHAR));
PRINT('Average Score from '   + @Country + ':'
      + CAST(@AvgScore AS NVARCHAR));

END
GO

```

## 5. Control Flow — IF/ELSE

→ Check for NULL scores and update before generating report

```

ALTER PROCEDURE GetCustomerSummary
    @Country NVARCHAR(50) = 'USA'
AS
BEGIN
    DECLARE @TotalCustomers INT, @AvgScore FLOAT;

    -- Prepare & Cleanup
    IF EXISTS (
        SELECT 1 FROM Sales.Customers
        WHERE Score IS NULL AND Country = @Country
    )
    BEGIN
        PRINT('Updating NULL Scores to 0');
        UPDATE Sales.Customers
        SET Score = 0
        WHERE Score IS NULL AND Country = @Country;
    END
    ELSE
        PRINT('No NULL Scores found');

    -- Report
    SELECT
        @TotalCustomers = COUNT(*),
        @AvgScore       = AVG(Score)
    FROM Sales.Customers
    WHERE Country = @Country;

    PRINT('Total: ' + CAST(@TotalCustomers AS NVARCHAR));
    PRINT('Avg:   ' + CAST(@AvgScore AS NVARCHAR));

```

### OUR LOCATIONS

```
END  
GO
```

## 6. Error Handling — TRY/CATCH

→ Wrap entire procedure body in TRY/CATCH for robust error handling

```
ALTER PROCEDURE GetCustomerSummary  
    @Country NVARCHAR(50) = 'USA'  
AS  
BEGIN  
    BEGIN TRY  
        DECLARE @TotalCustomers INT, @AvgScore FLOAT;  
  
        SELECT  
            @TotalCustomers = COUNT(*),  
            @AvgScore        = AVG(Score)  
        FROM Sales.Customers  
        WHERE Country = @Country;  
  
        PRINT('Total: ' + CAST(@TotalCustomers AS NVARCHAR));  
        PRINT('Avg:    ' + CAST(@AvgScore AS NVARCHAR));  
  
        SELECT  
            COUNT(OrderID) AS TotalOrders,  
            SUM(Sales)      AS TotalSales,  
            1/0             AS FaultyCalculation -- intentional error  
        FROM Sales.Orders AS o  
        JOIN Sales.Customers AS c  
            ON c.CustomerID = o.CustomerID  
        WHERE c.Country = @Country;  
    END TRY  
    BEGIN CATCH  
        PRINT('An error occurred.');
```

```
        PRINT('Error Message:  ' + ERROR_MESSAGE());  
        PRINT('Error Number:   ' + CAST(ERROR_NUMBER()   AS NVARCHAR));  
        PRINT('Error Severity: ' + CAST(ERROR_SEVERITY() AS NVARCHAR));  
        PRINT('Error State:    ' + CAST(ERROR_STATE()    AS NVARCHAR));  
        PRINT('Error Line:     ' + CAST(ERROR_LINE()     AS NVARCHAR));  
        PRINT('Error Procedure: ' + ISNULL(ERROR_PROCEDURE(), 'N/A'));
```

```
    END CATCH;  
END  
GO
```

→ Execute the final stored procedure

```
EXEC GetCustomerSummary @Country = 'Germany';  
EXEC GetCustomerSummary @Country = 'USA';  
EXEC GetCustomerSummary;
```

### OUR LOCATIONS

---

**OUR LOCATIONS**

**+91 77220 82225**  
Pimpri-Chinchwad

**+91 77220 82226**  
Chh. Sambhajinagar

**+91 77220 82227**  
Nashik

**+91 77220 82224**  
Hadapsar, Pune