

SAFETY DATA SHEET

Page 1 Revised 01-01-21

SECTION 1 – PRODUCT AND COMPANY INFORMATION

PRODUCT NAME: LDPE Repro OR LDPE Powder

CHEMICAL NAME: RECYCLED POLYETHYLENE PLASTIC (100% post industrial scrap)

APPEARANCE: BLACK POWDER or BLACK PELLETS

COMPANY IDENTIFICATION: LDPE POWDER -

SECTION 2 – COMPOSITION

EXEMPT: This product is considered to be an article according to 29CFR, hazardous Communication – 1910.1200(b)(6)(v)

OSHA REGULATORY STATUS: While this material is not classified as hazardous under OSHA regulations, this SDS contains valuable information critical to the safe and proper use of the product.

SECTION 3 – HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW:

NFPA RATINGS: Health: 0 Flammability: 1 Reactivity: 0 PHYSICAL

STATE: Plastic, various colors, solid pellets or powder

HAZARDS: This product contains no materials which are considered hazardous. However, molten product will cause thermal burns to skin and eyes. This compound, when exposed to direct fire, can catch fire and/or smolder, and may release fumes which may cause upper respiratory irritation. Exposure to dust may cause upper respiratory irritation. Irritation is not expected to be either prolonged or significant.

Page 2

SECTION 4: FIRST AID MEASURES

EYE CONTACT: Flush eyes with water for fifteen minutes. Get medical attention.

SKIN CONTACT: Wash thoroughly with soap and water. Launder clothing. If there is skin irritation, seek medical attention.

INHALATION: Remove to fresh air. Seek medical attention if breathing becomes difficult.

INGESTION: No hazards anticipated from swallowing small amounts incidental to normal handling operations.

SECTION 5: FIRE FIGHTING MEASURES

NFPA RATINGS: Health: **0** Flammability: **1** Reactivity: **0** **FLASHPOINT:**

NA

AUTOIGNITION: NA

FLAMMABILITY (EXPLOSIVE) LIMITS (% BY VOLUME IN AIR): LOWER: NA UPPER: NA

EXTINGUISHING MEDIA : Carbon Dioxide, dry chemical, or foam recommended.

PROTECTION OF FIRE FIGHTERS: Wear SCBA gear and full protective equipment.

COMBUSTION PRODUCTS: Fire or excessive heat may produce hazardous decomposition products.

SECTION 6 : ACCIDENTAL RELEASE MEASURES

FOR SPILL: Stop leak, contain spill, and prevent entry into sewers and waterways. Spilled material may create a slipping hazard. Use appropriate instruments to sweep or vacuum up the spilled material for recycle or proper disposal. Ensure statutory and regulatory reporting requirements in the applicable jurisdiction are met.

SECTION 7: HANDLING AND STORAGE

HANDLING: Keep scrap material off walking surfaces as this can create slipping hazards. Avoid accumulation of dust in enclosed space. Use in well ventilated area. Use good housekeeping practices during storage, transfer, and handling.

STORAGE: Recommend storage indoors with adequate fire sprinkler protection. Store away from excessive heat, ignition sources, and oxidizing agents. Keep poly-bag container closed to prevent moisture exposure, soiling, and contamination.

SECTION 8: EXPOSURE CONTROLS AND PERSONAL PROTECTION

ENGINEERING CONTROLS: Ventilate storage and usage areas to prevent accumulation of dust.

PERSONAL PROTECTIVE EQUIPMENT:

EYES: Wear safety glasses

SKIN: Wear protective clothing such as long sleeves and impervious gloves.

INHALATION: Use appropriate respiratory protection such as dust mask.

EXPOSURE LIMITS: There are no ACGIH TLV limits or OSHA PEL limits for this product. Consult SECTION 3 for further information. However, the ACGIH exposure limit for nuisance dust is 10mg/m³ for inhalable particulate matter, and 3mg/m³ for respirable particulate matter.

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

APPEARANCE: Solid colored plastic pellets or powder (various colors) **VAPOR PRESSURE:**

N/A ODOR : Mild to no odor **BOILING POINT:** N/A **WATER SOLUBILITY:** Negligible

MELTING POINT: 90-140°C (194-284°F) **pH:** N/A **VISCOSITY:** N/A **EVAPORATION RATE:**

N/A VAPOR PRESSURE: N/A

SECTION 10: STABILITY AND REACTIVITY

REACTIVITY: This material is considered non-reactive under normal ambient and anticipated storage and handling temperatures and pressures

CHEMICAL STABILITY: This material is considered non-reactive under normal ambient and

SECTION 11: TOXICOLOGICAL INFORMATION

PRODUCT SUMMARY: This product is not considered to be toxic to humans or animals.

ACUTE ORAL TOXICITY: Presumed Not Toxic

ACUTE INHALATION TOXICITY: Presumed Not Toxic

ACUTE DERMAL TOXICITY: Presumed Not Toxic

SKIN IRRITATION: Presumed Not Toxic

EYE IRRITATION: Presumed Not Toxic

SECTION 12: ECOLOGICAL INFORMATION

ECOTOXICITY EFFECTS:

ELIMINATION INFORMATION (Persistence and degradability):

Bio-accumulation: Does not bio-accumulate

Mobility: Product is insoluble and floats on water

Biodegradability: Product is not readily biodegradable

Bioaccumulation: Fish or birds may eat pellets which may obstruct their digestive tracts.

SECTION 13: DISPOSAL CONSIDERATIONS

Use only licensed transporters and permitted facilities for waste disposal. Recycle whenever possible.

SECTION 14: TRANSPORT INFORMATION

US DOT INFORMATION:

SHIPPING NAME: Not regulated as a Hazardous Material for Transportation

CANADIAN TDG INFORMATION:

SHIPPING NAME: Not regulated as a Hazardous Material for Transportation

INTERNATIONAL AIR TRANSPORT ASSOCIATION (ATA) REGULATIONS:

SHIPPING NAME: Not regulated as a Hazardous Material for Transportation

INTERNATIONAL MARITIME DANGEROUS GOODS (IMDG) CODE:

SHIPPING NAME: Not regulated as a Hazardous Material for Transportation

SECTION 15: REGULATORY INFORMATION

NO ADDITIONAL REGULATORY INFORMATION IS AVAILABLE.

SECTION 16: OTHER INFORMATION

The information contained herein is based on data that is considered accurate. However, no warranty is expressed or implied regarding the accuracy of this data or the results obtained from the use thereof, Mosaic Color and Additives, LLC, assumes no responsibility for personal injury or property damage caused by this product. Users assume all risks associated with the use of this product.