

according to the OSHA Hazard Communication Standard

Version Revision Date: Date of last issue: 10/10/2025
Original 10/10/2025

Trade name	:	RES200B
CAS Number:	:	25213-02-9
Chemical characterization	:	Polyethylene copolymer
Chemical name	:	Ethylene/Hexene Copolymer
Synonyms	:	Ethylene-1-hexene copolymer, Ethylene-1-hexene copolymer, Ethylene-Hexene Copolymer
Identified uses	:	Manufacture of plastic articles by injection molding, extrusion, roto-molding or other conversion process.
Prohibited uses	:	FDA Class III medical devices; European class III medical devices; Health Canada class IV Medical Devices; Applications involving permanent implantation into the body; Life-sustaining medical applications

RG Industries, LLC
4101 A.J. Drive S.
Wadesville, IN 47638

812-270-0488

812-270-0488

E-mail address : curry658382@yahoo.com
Responsible/issuing person

GHS classification in accordance with the OSHA Hazard Communication Standard (29 CFR 1910.1200)

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard

RES200B

Version Revision Date: Date of last issue: 10/10/2025
Original 10/10/2025

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture

Components

Chemical name	CAS No./Unique ID	Concentration (% w/w)	Trade secret
1-Hexene,polymer with ethene	25213-02-9*	≥ 97%	-
Other	Proprietary	≤ 3%	Trade Secret

* Indicates that the identifier is a CAS No.

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard

RES200B

Version Revision Date: Date of last issue: 10/10/2025
Original 10/10/2025

SECTION 4. FIRST AID MEASURE

General advice	:	Take proper precautions to ensure your own health and safety before attempting rescue and providing first aid.
If inhaled	:	Remove person to fresh air. If signs/symptoms continue, get medical attention. In case of excessive inhalation of fumes that may be generated during heating of this material, move the person to fresh air. Oxygen or artificial respiration if needed. Obtain medical attention.
In case of skin contact	:	If molten material contacts the skin, immediately flush with large amounts of water to cool the affected tissue and polymer. Do not attempt to peel polymer from skin as this will remove the skin. Obtain immediate emergency medical attention if burn is deep or extensive.
In case of eye contact	:	Flush eyes with water at least 15 minutes. Get medical attention if eye irritation develops or persists. In case of eye contact with molten polymer: Continuously flush eye(s) with cool running water for at least 15 minutes. Beyond flushing, DO NOT attempt to remove the material adherent to the eye(s). Immediately seek medical attention.
If swallowed	:	Adverse health effects due to ingestion are not anticipated.
Most important symptoms and effects, both acute and delayed	:	Inhalation of process fumes and vapors may cause soreness in the nose and throat and coughing. Dust contact with the eyes can lead to mechanical irritation. Molten polymer may cause thermal burns.
Notes to physician	:	Treatment of overexposure should be directed at the control of symptoms and the clinical condition of the patient.

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard

RES200B

Version Revision Date: Date of last issue: 10/10/2025
Original 10/10/2025

SECTION 5. FIREFIGHTING MEASURES

Suitable extinguishing media : SMALL FIRE:
Use dry chemical, CO₂, or water spray.

LARGE FIRES:
Use water spray hose nozzles from a safe location.

Unsuitable extinguishing media : None known.

Specific hazards during firefighting : Keep away from heat and sources of ignition.
Dust particles from this product are combustible particulate solids that present a flash fire or explosion hazard when suspended in air.
Polymer dust layer melts on the hot surface before ignition can occur
In case of fire hazardous decomposition products may be produced such as:
Carbon monoxide, carbon dioxide and unburned hydrocarbons (smoke).

Further information : Combustible particulate solid, will decompose under fire conditions.
Calorific Value: 8000 - 11000 kcal/kg
Fight fire from safe distance with hose lines or monitor nozzles.
Heat from fire may melt, decompose polymer, and generate flammable vapors.
Move containers from fire area if it can be done without risk.
Evacuate immediately in the event of opening of storage container pressure relief devices or discoloration of container.
Always stay away from tanks engulfed in fire.
Do not attempt to get on top of storage containers involved in fire.
Cool storage containers with large volumes of water even after fire is out.

Special protective equipment for firefighters : Wear approved positive pressure self-contained breathing apparatus and firefighter protective clothing.

SECTION 6. ACCIDENTAL RELEASE MEASURES

Avoid dispersal of dust in the air (i.e., clearing dust surfaces with compressed air).
Potential combustible dust hazard.

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard

RES200B

Version Revision Date: Date of last issue: 10/10/2025
Original 10/10/2025

Environmental precautions : Polymer particles create slipping hazard on hard smooth surfaces.

Environmental precautions : Do not flush into surface water or sanitary sewer system.

Methods and materials for : On land, sweep/shovel into suitable disposal containers
containment and cleaning up or vacuum using equipment which avoids ignition risk. On
water, material is insoluble; collect and contain as any
solid.
All recovered material should be packaged, labeled,
transported and disposed of or reclaimed in conformance
with applicable laws and regulations and in conformance
with good engineering practices. Reclaim where possible.

SECTION 7. HANDLING AND STORAGE

Advice on safe handling : Avoid dust accumulation in enclosed space.
Use dust collection systems designed per NFPA 654 to avoid
dust accumulation.
Avoid generating dust; fine dust suspended in air and in the
presence of an ignition source is a potential dust explosion
hazard.
Polymer dust layer melts on the hot surface before ignition
can occur
Hot surface temperature shall be limited to less than 270°C to
avoid direct ignition of a dust cloud.
Static discharge (spark), or other ignition sources, in high dust
environments may ignite the dust and result in a dust
explosion
Electrostatic charge may build during conveying or handling.
Equipment handling polymer should be conductive and
grounded (earthed) and bonded.
Metal containers involved in the transfer of this material
should be grounded and bonded.
All electrical equipment should conform to applicable electric
codes and regulatory requirements for areas handling
combustible dusts.
After handling, always wash hands thoroughly with soap and
water.
When bringing the material to processing temperatures vapors
may develop may condense in the exhaust ventilation. See
section 10.

Conditions for safe storage : Refer to NFPA 654, Standard for the Prevention of Fire and
Dust Explosions from the Manufacturing, Processing, and
Handling of Combustible Particulate Solids, for safe handling.
Store in a dry location.
Use good housekeeping practices during storage, transferring

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard

RES200B

Version Revision Date: Date of last issue: 10/10/2025
Original 10/10/2025

and handling. Process enclosures and adequate ventilation should be used to avoid excessive dust accumulation. Degradation can occur because of exposure to temperature, light and oxidizing agent: trace amounts of light hydrocarbons, compounds of oxidation, aldehydes and acids can be generated.
Store away from excessive heat and away from strong oxidizing agents.
Keep container closed to prevent contamination.
Take measures to prevent the build up of electrostatic charge.

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Components with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
Non-specified (inert or nuisance) dust	Not Assigned	TWA	10 mg/m3 (inhalable)	US (ACGIH)
		TWA	3 mg/m3 (respirable)	US (ACGIH)
		TWA	15 mg/m3 (total dust)	US (OSHA)
		TWA	5 mg/m3 (respirable)	US (OSHA)

Engineering measures

: Follow the recommendations in NFPA 654 (as amended and adopted) for equipment used to handle this product.

Engineering controls, i.e. enclosed systems, should be used whenever feasible to maintain exposures below acceptable criteria. When such controls are not feasible, or sufficient to achieve full conformance, other engineering controls such as local exhaust ventilation should be used.

Equipment and vessels handling combustible dust from this material should be designed to either prevent dust explosions (inerting) or safely vent dust explosions per NFPA 654 Ensure that dust-handling systems (such as exhaust ducts, dust collectors, vessels, and processing equipment) are designed in a manner to prevent the escape of dust into the work area (i.e., there is no leakage from the equipment).

Personal protective equipment

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard

RES200B

Version Revision Date: Date of last issue: 10/10/2025
Original 10/10/2025

Respiratory protection : Use process enclosures, local exhaust ventilation, or other engineering controls to keep airborne levels below recommended exposure limits.
When workers are facing concentrations above the exposure limit they must use appropriate certified respirators. Use appropriate respiratory protection where atmosphere exceeds recommended limits.
Where workers could be exposed to dust concentrations

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard

RES200B

Version	Revision Date:	Date of last issue: 10/10/2025
Original	10/10/2025	

above the exposure limit they must use appropriate certified respirators.

Flammability (solid, gas) : May form combustible dust concentrations in air.

Polymer will burn but does not easily ignite.

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard

RES200B

Version Revision Date: Date of last issue: 10/10/2025
Original 10/10/2025

6 / 15

Hand protection

Remarks : Wear gloves that provide thermal protection where there is a potential for contact with heated material.

Eye protection : Dust service goggles should be worn to prevent mechanical injury or other irritation to eyes due to airborne particles which may result from handling this product.

Skin and body protection : Wear suitable protective clothing.

Hygiene measures : Selection of appropriate personal protective equipment should be based on an evaluation of the performance characteristics of the protective equipment relative to the task(s) to be performed, conditions present, duration of use, and the hazards and/or potential hazards that may be encountered during use.
Use good personal hygiene practices.
Wash hands before eating, drinking, smoking, or using toilet facilities.
Take off contaminated clothing and wash before reuse.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance : powder, flakes

Colour : Translucent to white

Odour : slight

Odour Threshold : no data available

pH : Not applicable

Melting point/range : 122 - 338 °F / 50 - 170 °C

Boiling point/boiling range : Not applicable

Flash point : no data available

Evaporation rate : Not applicable

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard

RES200B

Version Revision Date: : Date of last issue: 10/10/2025
Original 10/10/2025

Self-ignition	: > 572 °F / > 300 °C
Upper explosion limit / Upper flammability limit	: Not applicable
Lower explosion limit / Lower flammability limit	: The minimum explosive concentration (MEC) for polymer dust varies according to particle size distribution.
Vapour pressure	: Not applicable
Relative vapour density	: Not applicable
Density	: < 1 g/cm ³
Solubility(ies) Water solubility	: insoluble
Partition coefficient: noctanol/water	: no data available
Viscosity Viscosity, dynamic	: Not applicable
Explosive properties	: no data available
Oxidizing properties	: The substance or mixture is not classified as oxidizing.

SECTION 10. STABILITY AND REACTIVITY

Reactivity	: None reasonably foreseeable.
Chemical stability	: Stable under normal conditions.
Possibility of hazardous reactions	: None known.
Conditions to avoid	: Heat, flames and sparks.
Incompatible materials	: Material may be softened by some hydrocarbons.
Hazardous decomposition products	: No decomposition if stored and applied as directed.

SECTION 11. TOXICOLOGICAL INFORMATION

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard

RES200B

Version Revision Date: : Date of last issue: 10/10/2025
Original 10/10/2025

Acute toxicity

Components:

1-Hexene,polymer with ethene:

Acute oral toxicity : Assessment: The substance or mixture has no acute oral toxicity

Acute inhalation toxicity : Assessment: The substance or mixture has no acute inhalation toxicity

Acute dermal toxicity : Assessment: The substance or mixture has no acute dermal toxicity

Skin corrosion/irritation

Components:

1-Hexene,polymer with ethene:

Result : No skin irritation

Serious eye damage/eye irritation

Components:

1-Hexene,polymer with ethene:

Remarks : Mechanical irritation is possible.

Respiratory or skin sensitisation

Components:

1-Hexene,polymer with ethene:

Result : Does not cause skin sensitization.

Result : Does not cause respiratory sensitization.

Germ cell mutagenicity

Components:

1-Hexene,polymer with ethene:

Germ cell mutagenicity - Assessment : Based on available data, the classification criteria are not met.

Carcinogenicity

Components:

1-Hexene,polymer with ethene:

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard

RES200B

Version Revision Date: : Date of last issue: 10/10/2025
Original 10/10/2025

Carcinogenicity - Assessment : No evidence of carcinogenicity in animal studies.

IARC No ingredient of this product present at levels greater than or equal to 0.1% is identified as probable, possible or confirmed human carcinogen by IARC.

OSHA No component of this product present at levels greater than or equal to 0.1% is on OSHA's list of regulated carcinogens.

NTP No ingredient of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP.

Reproductive toxicity

Components:

1-Hexene,polymer with ethene:

Reproductive toxicity - Assessment : Based on available data, the classification criteria are not met.

STOT - single exposure

Components:

1-Hexene,polymer with ethene:

Assessment : The substance or mixture is not classified as specific target organ toxicant, single exposure.

STOT - repeated exposure

Components:

1-Hexene,polymer with ethene:

Assessment : The substance or mixture is not classified as specific target organ toxicant, repeated exposure.

Aspiration toxicity

Components:

1-Hexene,polymer with ethene:

No aspiration toxicity classification

SECTION 12. ECOLOGICAL INFORMATION

Ecotoxicity

Components:

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard

RES200B

Version Revision Date: : Date of last issue: 10/10/2025
Original 10/10/2025

1-Hexene,polymer with ethene:

Toxicity to fish : Remarks: Aquatic toxicity is unlikely due to low solubility.

Toxicity to daphnia and other : Remarks: No toxicity at the limit of solubility.
aquatic invertebrates

Toxicity to algae/aquatic : Remarks: No toxicity at the limit of solubility.
plants

Toxicity to fish (Chronic tox- : Remarks: No toxicity at the limit of solubility.
icity)

Toxicity to daphnia and other : Remarks: No toxicity at the limit of solubility.
aquatic invertebrates (Chron-
ic toxicity)

Toxicity to microorganisms : Remarks: No toxicity at the limit of solubility.

Persistence and degradability Components:

1-Hexene,polymer with ethene:

Biodegradability : Remarks: The polymer will bio-degrade over time period.

Bioaccumulative potential Components:

1-Hexene,polymer with ethene:

Bioaccumulation : Remarks: This material is not expected to bioaccumulate.

Mobility in soil Components:

1-Hexene,polymer with ethene:

Mobility : Remarks: no data available

Other adverse effects

Product:

Results of PBT and vPvB : Not applicable
assessment

Ozone-Depletion Potential : Regulation: 40 CFR Protection of Environment; Part 82 Pro-
tection of Stratospheric Ozone - CAA Section 602 Class I
Substances
Remarks: This product neither contains, nor was manufactured
with a Class I or Class II ODS as defined by the U.S. Clean Air
Act Section 602 (40 CFR 82, Subpt. A, App.A + B).

Components:

1-Hexene,polymer with ethene:

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard

RES200B

Version Revision Date: : Date of last issue: 10/10/2025
Original 10/10/2025

Environmental fate and pathways : This material is not volatile and insoluble in water.

Additional ecological information : Ecotoxicity is expected to be minimal based on the low water solubility of polymers.

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal methods

Waste from residues : All recovered material should be packaged, labeled, transported and disposed of or reclaimed in conformance with applicable laws and regulations and in conformance with good engineering practices. Reclaim where possible. Recycle if possible.

This material is classified as a Non-hazardous Material by RCRA.

SECTION 14. TRANSPORT INFORMATION

International Regulations

IATA-DGR

Not regulated as a dangerous good

IMDG-Code

Not regulated as a dangerous good

Transport in bulk according to IMO instruments Not applicable for product as supplied.

National Regulations

49 CFR Road

Not regulated as a dangerous good

Special precautions for user Not applicable

SECTION 15. REGULATORY INFORMATION

SARA 302 Extremely Hazardous Substances Threshold Planning Quantity This material does not contain any components with a section 302 EHS TPQ.

SARA 311/312 Hazards : Combustible dust

SARA 313 : This material does not contain any chemical components with known CAS numbers that exceed the threshold (De Minimis) reporting levels established by SARA Title III, Section 313.

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard

RES200B

Version Revision Date: : Date of last issue: 10/10/2025
Original 10/10/2025

Clean Air Act

This product neither contains, nor was manufactured with a Class I or Class II ODS as defined by the U.S. Clean Air Act Section 602 (40 CFR 82, Subpt. A, App.A + B).

This product does not contain any hazardous air pollutants (HAP), as defined by the U.S. Clean Air Act Section 112 (40 CFR 61).

This product does not contain any chemicals listed under the U.S. Clean Air Act Section 112(r) for Accidental Release Prevention (40 CFR 68.130, Subpart F).

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard

RES200B

Version Revision Date: Date of last issue: 10/10/2025
Original 10/10/2025

This product does not contain any chemicals listed under the U.S. Clean Air Act Section 111 SOCMI Intermediate or Final VOC's (40 CFR 60.489).

Clean Water Act

This product does not contain any Hazardous Substances listed under the U.S. CleanWater Act, Section 311, Table 116.4A.

This product does not contain any Hazardous Chemicals listed under the U.S. CleanWater Act, Section 311, Table 117.3.

This product does not contain any toxic pollutants listed under the U.S. Clean Water Act Section 307

This product does not contain any priority pollutants related to the U.S. Clean Water Act

US State Regulations

Massachusetts Right To Know

No components are subject to the Massachusetts Right to Know Act.

Pennsylvania Right To Know

Zinc Stearate

557-05-1

Vermont Chemicals of High Concern

Product does not contain any listed chemicals

Washington Chemicals of High Concern

Product does not contain any listed chemicals

California Prop. 65

WARNING: This product can expose you to chemicals including Ethylbenzene, which is/are known to the State of California to cause cancer. For more information go to www.P65Warnings.ca.gov.

The components of this product are reported in the following inventories:

TCSI	: On the inventory, or in compliance with the inventory
TSCA	: All substances listed as active on the TSCA inventory
AIIC	: On the inventory, or in compliance with the inventory
DSL	: All components of this product are on the Canadian DSL
ENCS	: Not in compliance with the inventory
KECI	: On the inventory, or in compliance with the inventory
PICCS	: On the inventory, or in compliance with the inventory
IECSC	: On the inventory, or in compliance with the inventory
NZIoC	: On the inventory, or in compliance with the inventory

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard

RES200B

Version Revision Date: Date of last issue: 10/10/2025
Original 10/10/2025

TECI	:	Not in compliance with the inventory
CH BAGREG	:	On the inventory, or in compliance with the inventory
MXINSQ	:	On the inventory, or in compliance with the inventory
NCI	:	On the inventory, or in compliance with the inventory

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard

RES200B

Version Revision Date: Date of last issue: 10/10/2025
Original 10/10/2025

TSCA list


No substances are subject to a Significant New Use Rule.

No substances are subject to TSCA 12(b) export notification requirements.

SECTION 16. OTHER INFORMATION

Further information

NFPA 704:



HMIS® IV:

HEALTH	0
FLAMMABILITY	1
PHYSICAL HAZARD	0

HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. The "*" represents Special hazard a chronic hazard, while the "/" represents the absence of a chronic hazard.

Full text of other abbreviations

US (ACGIH) : US (ACGIH)
US (OSHA) : US (OSHA)
US (ACGIH) / TWA : Time weighted average
US (OSHA) / TWA : Time weighted average

SARA - Superfund Amendments and Reauthorization Act; SDS - Safety Data Sheet; TCSI -;
TSCA - Toxic Substances Control Act (United States);

Revision Date : 10/10/2025

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

US / EN