

# Chapter 8

## Security

A note on the use of these PowerPoint slides:


We're making these slides freely available to all (faculty, students, readers). They're in PowerPoint form so you see the animations; and can add, modify, and delete slides (including this one) and slide content to suit your needs. They obviously represent a *lot* of work on our part. In return for use, we only ask the following:

- If you use these slides (e.g., in a class) that you mention their source (after all, we'd like people to use our book!)
- If you post any slides on a www site, that you note that they are adapted from (or perhaps identical to) our slides, and note our copyright of this material.

For a revision history, see the slide note for this page.

Thanks and enjoy! JFK/KWR

All material copyright 1996-2023  
J.F Kurose and K.W. Ross, All Rights Reserved



## *Computer Networking: A Top-Down Approach*

8<sup>th</sup> edition

Jim Kurose, Keith Ross  
Pearson, 2020

# Security: overview

## Chapter goals:

- understand principles of network security:
  - cryptography and its *many* uses beyond “confidentiality”
  - authentication
  - message integrity
- security in practice:
  - firewalls and intrusion detection systems
  - security in application, transport, network, link layers

# Chapter 8 outline

- What is network security?
- Principles of cryptography
- Message integrity, authentication
- Securing e-mail
- Network layer security: IPsec
- Operational security: firewalls and IDS



# What is network security (Security Goals)?

**confidentiality:** only sender, intended receiver should “understand” message contents

- sender encrypts message
- receiver decrypts message


**authentication:** sender, receiver want to confirm identity of each other

**message integrity:** sender, receiver want to ensure message not altered (in transit, or afterwards) without detection

**access and availability:** services must be accessible and available to users

# Friends and enemies: Alice, Bob, Trudy

- well-known in network security world
- Bob, Alice (lovers!) want to communicate “securely”
- Trudy (intruder) may intercept, delete, add messages



# Friends and enemies: Alice, Bob, Trudy

Who might Bob and Alice be?

- ... well, *real-life* Bobs and Alices!
- Web browser/server for electronic transactions (e.g., on-line purchases)
- on-line banking client/server
- DNS servers
- BGP routers exchanging routing table updates
- other examples?

# There are bad guys (and girls) out there!

Q: What can a “bad guy” do?

A: A lot! (recall section 1.6)

- **eavesdrop**: intercept messages
- actively **insert** messages into connection
- **impersonation**: can fake (spoof) source address in packet (or any field in packet)
- **hijacking**: “take over” ongoing connection by removing sender or receiver, inserting himself in place
- **denial of service**: prevent service from being used by others (e.g., by overloading resources)


# Chapter 8 outline

- What is network security?
- Principles of cryptography
- Message integrity, authentication
- Securing e-mail
- Network layer security: IPsec
- Operational security: firewalls and IDS





# The language of cryptography



$m$ : plaintext message

$K_A(m)$ : ciphertext, encrypted with key  $K_A$

$m = K_B(K_A(m))$


# Breaking an encryption scheme

- **cipher-text only attack:**  
Trudy has ciphertext she can analyze

- **two approaches:**
  - brute force: search through all keys
  - statistical analysis

- **known-plaintext attack:**  
Trudy has plaintext corresponding to ciphertext
  - *e.g.*, in monoalphabetic cipher, Trudy determines pairings for a,l,i,c,e,b,o,
- **chosen-plaintext attack:**  
Trudy can get ciphertext for chosen plaintext

# Symmetric key cryptography



**symmetric key crypto**: Bob and Alice share same (symmetric) key:  $K$

- e.g., key is knowing substitution pattern in mono alphabetic substitution cipher

Q: how do Bob and Alice agree on key value?

# Simple encryption scheme

*substitution cipher*: substituting one thing for another

- monoalphabetic cipher: substitute one letter for another

plaintext:	a	b	c	d	e	f	g	h	i	j	k	l	m	n	o	p	q	r	s	t	u	v	w	x	y	z
		↓																							↓	
ciphertext:	m	n	b	v	c	x	z	a	s	d	f	g	h	j	k	l	p	o	i	u	y	t	r	e	w	q

e.g.: Plaintext: bob. i love you. alice  
ciphertext: nkn. s gktc wky. mgsbc

🔑 *Encryption key*: mapping from set of 26 letters  
to set of 26 letters

# A more sophisticated encryption approach (1/2)

- n substitution ciphers,  $M_1, M_2, \dots, M_n$
- cycling pattern:
  - e.g.,  $n=4$ :  $M_1, M_3, M_4, M_3, M_2$ ;  $M_1, M_3, M_4, M_3, M_2$ ; ..
- for each new plaintext symbol, use subsequent substitution pattern in cyclic pattern
  - dog: d from  $M_1$ , o from  $M_3$ , g from  $M_4$
- 🔑 **Encryption key:** n substitution ciphers, and cyclic pattern
  - key need not be just n-bit pattern

# A more sophisticated encryption approach (2/2)

- Same letter at different position encoded differently

Plaintext letter:	a b c d e f g h i j k l m n o p q r s t u v w x y z
$C_1(k = 5)$ :	f g h i j k l m n o p q r s t u v w x y z a b c d e
$C_2(k = 19)$ :	t u v w x y z a b c d e f g h i j k l m n o p q r s

A polyalphabetic **cipher** using two Caesar **ciphers**

Two Caesar keys ( $k = 5$ ,  $k = 19$ ) and the pattern C1, C2, C2, C1, C2.

m = "bob, i love you." -> c = "ghu, n etox dhz."

# Symmetric key crypto: DES


## DES: Data Encryption Standard

- US encryption standard [NIST 1993]
- 56-bit symmetric key, 64-bit plaintext input
- block cipher with cipher block chaining
- how secure is DES?
  - DES Challenge: 56-bit-key-encrypted phrase can nowadays be decrypted (brute force) in less than a day
  - no known good analytic attack
- making DES more secure:
  - 3DES: encrypt 3 times with 3 different keys

### DES operation

initial permutation

16 identical “rounds” of function application, each using different 48 bits of key  
final permutation



# AES: Advanced Encryption Standard

- symmetric-key NIST standard, replaced DES (Nov 2001)
- processes data in 128 bit blocks
- 128, 192, or 256 bit keys
- brute force decryption (try each key) taking 1 sec on DES, takes 149 trillion years for AES




# Public Key Cryptography

## symmetric key crypto:


- requires sender, receiver know **shared secret key**
- Q: how to agree on key in first place (particularly if never “met”)?

## public key crypto

- sender, receiver do *not* share secret key
- *public* encryption key known to *all*
- *private* decryption key known only to receiver



# Public Key Cryptography



**Wow** - public key cryptography revolutionized 2000-year-old (previously only symmetric key) cryptography!

- similar ideas emerged at roughly same time, independently in US and UK (classified)

# Public key encryption algorithms

requirements:

① need  $K_B^+(\cdot)$  and  $K_B^-(\cdot)$  such that

$$K_B^-(K_B^+(m)) = m$$

② given public key  $K_B^+$ , it should be impossible to compute private key  $K_B^-$

**RSA:** Rivest, Shamir, Adleman algorithm

# Prerequisite: modular arithmetic

- $x \bmod n$  = remainder of  $x$  when divide by  $n$

- facts:

$$[(a \bmod n) + (b \bmod n)] \bmod n = (a+b) \bmod n$$

$$[(a \bmod n) - (b \bmod n)] \bmod n = (a-b) \bmod n$$

$$[(a \bmod n) * (b \bmod n)] \bmod n = (a*b) \bmod n$$

- thus

$$(a \bmod n)^d \bmod n = a^d \bmod n$$

- example:  $x=14$ ,  $n=10$ ,  $d=2$ :

$$(x \bmod n)^d \bmod n = 4^2 \bmod 10 = 6$$

$$x^d = 14^2 = 196 \quad x^d \bmod 10 = 6$$

# RSA: getting ready

- message: just a bit pattern
- bit pattern can be uniquely represented by an integer number
- thus, encrypting a message is equivalent to encrypting a number

## example:

- $m = 10010001$ . This message is uniquely represented by the decimal number 145.
- to encrypt  $m$ , we encrypt the corresponding number, which gives a new number (the ciphertext).

# RSA: another important property

The following property will be *very* useful later:

$$\underbrace{K_B^-(K_B^+(m))}_{\text{use public key first, followed by private key}} = m = \underbrace{K_B^+(K_B^-(m))}_{\text{use private key first, followed by public key}}$$

use public key  
first, followed  
by private key

use private key  
first, followed  
by public key

*result is the same!*

# RSA in practice: session keys

- exponentiation in RSA is computationally intensive
- DES or AES is at least 100 times faster than RSA
- use public key crypto to establish secure connection, then establish second key – symmetric session key – for encrypting data

## session key, $K_s$

- Bob and Alice use RSA to exchange a symmetric session key  $K_s$
- once both have  $K_s$ , they use symmetric key cryptography

# Chapter 8 outline

- What is network security?
- Principles of cryptography
- **Authentication**, message integrity
- Securing e-mail
- Network layer security: IPsec
- Operational security: firewalls and IDS





# Authentication

**Goal:** Bob wants Alice to “prove” her identity to him

**Protocol ap1.0:** Alice says “I am Alice”




*failure scenario??*



# Authentication

**Goal:** Bob wants Alice to “prove” her identity to him

**Protocol ap1.0:** Alice says “I am Alice”




*in a network, Bob  
can not “see”  
Alice, so Trudy  
simply declares  
herself to be Alice*



# Authentication: another try

**Goal:** Bob wants Alice to “prove” her identity to him


**Protocol ap2.0:** Alice says “I am Alice” in an IP packet containing her source IP address



# Authentication: another try

**Goal:** Bob wants Alice to “prove” her identity to him


**Protocol ap2.0:** Alice says “I am Alice” in an IP packet containing her source IP address



# Authentication: a third try

**Goal:** Bob wants Alice to “prove” her identity to him

**Protocol ap3.0:** Alice says “I am Alice” and sends her secret password to “prove” it.






# Authentication: a modified third try

**Goal:** Bob wants Alice to “prove” her identity to him

**Protocol ap3.0:** Alice says “I am Alice” and sends her **encrypted secret password** to “prove” it.



# Authentication: a modified third try

**Goal:** Bob wants Alice to “prove” her identity to him

**Protocol ap3.0:** Alice says “I am Alice” and sends her encrypted secret password to “prove” it.




# Authentication: a fourth try

**Goal:** avoid playback attack

**nonce:** number (R) used only once-in-a-lifetime

**protocol ap4.0:** to prove Alice “live”, Bob sends Alice nonce, R

- Alice must return R, encrypted with shared secret key




*Failures, drawbacks?*

# Authentication: ap5.0

ap4.0 requires **shared symmetric key** - can we authenticate using public key techniques?

**ap5.0:** use nonce, public key cryptography



Bob computes


$$K_A^+ (K_A^-(R)) = R$$

and knows only Alice could have the private key, that encrypted  $R$  such that

$$K_A^+ (K_A^-(R)) = R$$

# Authentication: ap5.0 – there's still a flaw!

man (or woman) in the middle attack: Trudy poses as Alice (to Bob) and as Bob (to Alice)



# Chapter 8 outline


- What is network security?
- Principles of cryptography
- Authentication, **message integrity**
- Securing e-mail
- Network layer security: IPsec
- Operational security: firewalls and IDS



# Digital signatures

cryptographic technique analogous to hand-written signatures:

- sender (Bob) digitally signs document: he is document owner/creator.
- *verifiable, nonforgeable*: recipient (Alice) can prove to someone that Bob, and no one else (including Alice), must have signed document
- **simple digital signature for message  $m$ :**
  - Bob signs  $m$  by encrypting with his private key  $K_B$ , creating “signed” message,  $K_B^-(m)$



# Digital signatures

- suppose Alice receives msg  $m$ , with signature:  $m, \bar{K}_B(m)$
- Alice verifies  $m$  signed by Bob by applying Bob's public key  $\bar{K}_B$  to  $\bar{K}_B(m)$  then checks  $\bar{K}_B(\bar{K}_B(m)) = m$ .
- If  $\bar{K}_B(\bar{K}_B(m)) = m$ , whoever signed  $m$  must have used Bob's private key

## Alice thus verifies that:

- Bob signed  $m$
- no one else signed  $m$
- Bob signed  $m$  and not  $m'$

## non-repudiation:


- ✓ Alice can take  $m$ , and signature  $\bar{K}_B(m)$  to court and prove that Bob signed  $m$

# Message digests

**computationally expensive** to public-key-encrypt long messages

**goal:** fixed-length, easy- to-compute digital “fingerprint”

- apply hash function  $H$  to  $m$ , get fixed size message digest,  $H(m)$



## Hash function properties:

- many-to-1
- produces fixed-size msg digest (fingerprint)
- given message digest  $x$ , computationally infeasible to find  $m$  such that  $x = H(m)$

# Internet checksum: poor crypto hash function

Internet checksum has some properties of hash function:

- produces fixed length digest (16-bit sum) of message
- is many-to-one


but given message with given hash value, it is easy to find another message with same hash value:

<u>message</u>	<u>ASCII format</u>		<u>message</u>	<u>ASCII format</u>
I O U 1	49 4F 55 31		I O U <u>9</u>	49 4F 55 <u>39</u>
0 0 . 9	30 30 2E 39		0 0 . <u>1</u>	30 30 2E <u>31</u>
9 B O B	39 42 D2 42		9 B O B	39 42 D2 42
<hr/>			<hr/>	
B2 C1 D2 AC		<i>different messages</i> <i>but identical checksums!</i>	B2 C1 D2 AC	




# Digital signature = signed message digest

Bob sends digitally signed message:



Alice verifies signature, integrity of digitally signed message:




# Hash function algorithms

- MD5 hash function widely used (RFC 1321)
  - computes 128-bit message digest in 4-step process.
  - arbitrary 128-bit string  $x$ , appears difficult to construct msg  $m$  whose MD5 hash is equal to  $x$
- SHA-1 is also used
  - US standard [NIST, FIPS PUB 180-1]
  - 160-bit message digest


# Authentication: ap5.0 – let's fix it!!

**Recall the problem:** Trudy poses as Alice (to Bob) and as Bob (to Alice)




# Public key Certification Authorities (CA)

- **certification authority (CA):** binds public key to particular entity, E
- entity (person, website, router) registers its public key with CE provides “proof of identity” to CA
  - CA creates certificate binding identity E to E’s public key
  - certificate containing E’s public key digitally signed by CA: CA says “this is E’s public key”



# Public key Certification Authorities (CA)

- when Alice wants Bob's public key:
  - gets Bob's certificate (Bob or elsewhere)
  - apply CA's public key to Bob's certificate, get Bob's public key




# Chapter 8 outline

- What is network security?
- Principles of cryptography
- Authentication, message integrity
- **Securing e-mail**
- Network layer security: IPsec
- Operational security: firewalls and IDS



# Secure e-mail: confidentiality

Alice wants to send *confidential* e-mail,  $m$ , to Bob.




Alice:

- generates random *symmetric* private key,  $K_S$
- encrypts message with  $K_S$  (for efficiency)
- also encrypts  $K_S$  with Bob's public key
- sends both  $K_S(m)$  and  $K_B^+(K_S)$  to Bob

# Secure e-mail: confidentiality (more)

Alice wants to send *confidential* e-mail,  $m$ , to Bob.




**Bob:**

- uses his private key to decrypt and recover  $K_S$
- uses  $K_S$  to decrypt  $K_S(m)$  to recover  $m$



# Secure e-mail: integrity, authentication


Alice wants to send  $m$  to Bob, with *message integrity, authentication*



- Alice digitally signs hash of her message with her private key, providing integrity and authentication
- sends both message (in the clear) and digital signature

# Secure e-mail: integrity, authentication

Alice sends  $m$  to Bob, with *confidentiality, message integrity, authentication*



**Alice uses three keys:** her private key, Bob's public key, new symmetric key

*What are Bob's complementary actions?*

# Chapter 8 outline

- What is network security?
- Principles of cryptography
- Authentication, message integrity
- Securing e-mail
- **Network layer security: IPsec**
- Operational security: firewalls and IDS



# What is network-layer confidentiality ?

*between two network entities:*


- sending entity encrypts datagram payload, payload could be:
  - TCP or UDP segment, ICMP message, OSPF message ....
- all data sent from one entity to other would be hidden:
  - web pages, e-mail, P2P file transfers, TCP SYN packets ...
- “blanket coverage”

# Virtual Private Networks (VPNs)

## *motivation:*


- institutions often want private networks for security.
  - costly: separate routers, links, DNS infrastructure.
- VPN: institution's inter-office traffic is sent over public Internet instead
  - encrypted before entering public Internet
  - logically separate from other traffic

# Virtual Private Networks (VPNs)




# IP Sec

- provides datagram-level encryption, authentication, integrity
  - for both user traffic and control traffic (e.g., BGP, DNS messages)
- two “modes”:



## transport mode:

- *only* datagram *payload* is encrypted, authenticated



## tunnel mode:

- entire datagram is encrypted, authenticated
- encrypted datagram encapsulated in new datagram with new IP header, tunneled to destination

# Two IPsec protocols

- Authentication Header (AH) protocol [RFC 4302]
  - provides source authentication & data integrity but *not* confidentiality
- Encapsulation Security Protocol (ESP) [RFC 4303]
  - provides source authentication, data integrity, *and confidentiality*
  - more widely used than AH




# Four combinations are possible!

Host mode with AH	Host mode with ESP
Tunnel mode with AH	Tunnel mode with ESP



most common and  
most important

# IPsec datagram




*tunnel mode  
ESP*

- ESP trailer: padding for block ciphers
- ESP header:
  - SPI, so receiving entity knows what to do
  - sequence number, to thwart replay attacks
- MAC in ESP auth field created with shared secret key

# ESP tunnel mode: actions

at R1:

- appends ESP trailer to original datagram (which includes original header fields!)
- encrypts result using algorithm & specified key
- appends ESP header to front of this encrypted quantity
- creates authentication MAC using algorithm and specified key
- appends MAC forming *payload*
- creates new IP header, new IP header fields, addresses to tunnel endpoint



# IPsec summary

- R Ether AH or ESP protocol (or both)
  - AH provides integrity, source authentication
  - ESP protocol (with AH) additionally provides encryption
- IPsec peers can be two end systems, two routers/firewalls, or a router/firewall and an end system

# Chapter 8 outline


- What is network security?
- Principles of cryptography
- Authentication, message integrity
- Securing e-mail
- Network layer security: IPsec
- **Operational security: firewalls and IDS**



# Firewalls

## firewall

isolates organization's internal network from larger Internet, allowing some packets to pass, blocking others



# Firewalls: why

prevent denial of service attacks:

- SYN flooding: attacker establishes many bogus TCP connections, no resources left for “real” connections

prevent illegal modification/access of internal data

- e.g., attacker replaces CIA’s homepage with something else


allow only authorized access to inside network

- set of authenticated users/hosts

## Three types of firewalls:

- stateless packet filters
- stateful packet filters
- application gateways


# Stateless packet filtering



- internal network connected to Internet via router **firewall**
- filters **packet-by-packet**, decision to forward/drop packet based on:
  - source IP address, destination IP address
  - TCP/UDP source, destination port numbers
  - ICMP message type
  - TCP SYN, ACK bits



# Stateless packet filtering: example



- **example 1:** block incoming and outgoing datagrams with IP protocol field = 17 and with either source or dest port = 23
  - **result:** all incoming, outgoing UDP flows and telnet connections are blocked
- **example 2:** block inbound TCP segments with ACK=0
  - **result:** prevents external clients from making TCP connections with internal clients, but allows internal clients to connect to outside

# Stateless packet filtering: more examples

Policy	Firewall Setting
no outside Web access	drop all outgoing packets to any IP address, port 80
no incoming TCP connections, except those for institution's public Web server only.	drop all incoming TCP SYN packets to any IP except 130.207.244.203, port 80
prevent Web-radios from eating up the available bandwidth.	drop all incoming UDP packets - except DNS and router broadcasts.
prevent your network from being used for a smurf DoS attack.	drop all ICMP packets going to a "broadcast" address (e.g. 130.207.255.255)
prevent your network from being tracerouted	drop all outgoing ICMP TTL expired traffic

# Access Control Lists

**ACL:** table of rules, applied top to bottom to incoming packets: (action, condition) pairs: looks like OpenFlow forwarding (Ch. 4)!

action	source address	dest address	protocol	source port	dest port	flag bit
allow	222.22/16	outside of 222.22/16	TCP	> 1023	80	any
allow	outside of 222.22/16	222.22/16	TCP	80	> 1023	ACK
allow	222.22/16	outside of 222.22/16	UDP	> 1023	53	---
allow	outside of 222.22/16	222.22/16	UDP	53	> 1023	----
deny	all	all	all	all	all	all

# Stateful packet filtering

- *stateless packet filter*: heavy handed tool
  - admits packets that “make no sense,” e.g., dest port = 80, ACK bit set, even though no TCP connection established:

action	source address	dest address	protocol	source port	dest port	flag bit
allow	outside of 222.22/16	222.22/16	TCP	80	> 1023	ACK

- *stateful packet filter*: track status of every TCP connection
  - track connection setup (SYN), teardown (FIN): determine whether incoming, outgoing packets “makes sense”
  - timeout inactive connections at firewall: no longer admit packets


# Stateful packet filtering

ACL augmented to indicate need to check connection state table before admitting packet

action	source address	dest address	proto	source port	dest port	flag bit	check connection
allow	222.22/16	outside of 222.22/16	TCP	> 1023	80	any	
allow	outside of 222.22/16	222.22/16	TCP	80	> 1023	ACK	X
allow	222.22/16	outside of 222.22/16	UDP	> 1023	53	---	
allow	outside of 222.22/16	222.22/16	UDP	53	> 1023	----	X
deny	all	all	all	all	all	all	

# Application gateways

- filter packets on application data as well as on IP/TCP/UDP fields.
- *example:* allow select internal users to telnet outside



1. require all telnet users to telnet through gateway.
2. for authorized users, gateway sets up telnet connection to dest host
  - gateway relays data between 2 connections
3. router filter blocks all telnet connections not originating from gateway

# Limitations of firewalls, gateways

- **IP spoofing:** router can't know if data “really” comes from claimed source
- if multiple apps need special treatment, each has own app. gateway
- client software must know how to contact gateway
  - e.g., must set IP address of proxy in Web browser
- filters often use all or nothing policy for UDP
- *tradeoff:* degree of communication with outside world, level of security
- many highly protected sites still suffer from attacks


# Intrusion detection systems

- packet filtering:
  - operates on TCP/IP headers only
  - no correlation check among sessions
- IDS: intrusion detection system
  - deep packet inspection: look at packet contents (e.g., check character strings in packet against database of known virus, attack strings)
  - examine correlation among multiple packets
    - port scanning
    - network mapping
    - DoS attack



# Intrusion detection systems

multiple IDSs: different types of checking at different locations



# Network Security (summary)

## basic techniques.....

- cryptography (symmetric and public key)
- message integrity and authentication

## .... used in many different security scenarios

- secure email
- IP sec

## operational security: firewalls and IDS

