Chapter 5
Network Layer: Control Plane

A note on the use of these PowerPoint slides:

We're making these slides freely available to all (faculty, students, readers). They're in PowerPoint form so you see the animations; and can add, modify, and delete slides (including this one) and slide content to suit your needs. They obviously represent a *lot* of work on our part. In return for use, we only ask the following:

- If you use these slides (e.g., in a class) that you mention their source (after all, we'd like people to use our book!)
- If you post any slides on a www site, that you note that they are adapted from (or perhaps identical to) our slides, and note our copyright of this material.

For a revision history, see the slide note for this page.

Thanks and enjoy! JFK/KWR



Computer Networking: A Top-Down Approach
8th edition
Jim Kurose, Keith Ross
Pearson, 2020

Network layer: “control plane” roadmap

- introduction
- routing protocols
- intra-ISP routing: OSPF
- routing among ISPs: BGP
- SDN control plane
- Internet Control Message Protocol

Software defined networking (SDN)

- Internet network layer: historically implemented via distributed, per-router control approach:
  - *monolithic* router contains switching hardware, runs proprietary implementation of Internet standard protocols (IP, RIP, IS-IS, OSPF, BGP) in proprietary router OS (e.g., Cisco IOS)
  - different "middleboxes" for different network layer functions: firewalls, load balancers, NAT boxes, ..
- ~2005: renewed interest in rethinking network control plane

Per-router control plane

Individual routing algorithm components *in each and every router* interact in the control plane to computer forwarding tables



Software-Defined Networking (SDN) control plane

Remote controller computes, installs forwarding tables in routers



Software defined networking (SDN)

Why a *logically centralized* control plane?

- easier network management: avoid router misconfigurations, greater flexibility of traffic flows
- table-based forwarding (recall OpenFlow API) allows "programming" routers
  - centralized "programming" easier: compute tables centrally and distribute
  - distributed "programming" more difficult: compute tables as result of distributed algorithm (protocol) implemented in each-and-every router
- open (non-proprietary) implementation of control plane
  - foster innovation: let 1000 flowers bloom

SDN analogy: mainframe to PC revolution

Specialized Applications

Specialized Operating System

Specialized Hardware

Vertically integrated
Closed, proprietary
Slow innovation
Small industry

App

Open Interface

Windows or Linux or MAC OS

Open Interface

Microprocessor

Horizontal
Open interfaces
Rapid innovation
Huge industry

* Slide courtesy: N. McKeown

Traffic engineering: difficult with traditional routing



<u>*Q:*</u> what if network operator wants u-to-z traffic to flow along *uvwz*, rather than *uxyz*?

<u>*A:*</u> need to re-define link weights so traffic routing algorithm computes routes accordingly (or need a new routing algorithm)!

link weights are only control "knobs": not much control!

Traffic engineering: difficult with traditional routing



Q: what if network operator wants to split u-to-z traffic along uvwz *and* uxyz (load balancing)?
A: can't do it (or need a new routing algorithm)

Traffic engineering: difficult with traditional routing



Q: what if w wants to route blue and red traffic differently from w to z?

A: can't do it (with destination-based forwarding, and LS, DV routing)

We learned in Chapter 4 that generalized forwarding and SDN can be used to achieve *any* routing desired

Software defined networking (SDN)

4. *programmable control applications*

3. *control plane functions external to data-plane switches*



2. *control, data plane separation*

1: *generalized "flow-based" forwarding (e.g., OpenFlow)*

Software defined networking (SDN)

Data-plane switches:

- fast, simple, commodity switches implementing generalized data-plane forwarding (Section 4.4) in hardware
- flow (forwarding) table computed, installed under controller supervision
- API for table-based switch control (e.g., OpenFlow)
  - defines what is controllable, what is not
- protocol for communicating with controller (e.g., OpenFlow)



Software defined networking (SDN)

SDN controller (network OS):

- maintain network state information
- interacts with network control applications "above" via northbound API
- interacts with network switches "below" via southbound API
- implemented as distributed system for performance, scalability, fault-tolerance, robustness



Software defined networking (SDN)

network-control apps:

- "brains" of control: implement control functions using lower-level services, API provided by SDN controller
- *unbundled:* can be provided by 3rd party: distinct from routing vendor, or SDN controller



Components of SDN controller

interface layer to network control apps: abstractions API

network-wide state management : state of networks links, switches, services: a *distributed database*

communication: communicate between SDN controller and controlled switches



OpenFlow protocol

- operates between controller, switch
- TCP used to exchange messages
  - optional encryption
- three classes of OpenFlow messages:
  - controller-to-switch
  - asynchronous (switch to controller)
  - symmetric (misc.)
- distinct from OpenFlow API
  - API used to specify generalized forwarding actions

OpenFlow Controller



OpenFlow: controller-to-switch messages

Key controller-to-switch messages

- *features:* controller queries switch features, switch replies
- *configure:* controller queries/sets switch configuration parameters
- *modify-state:* add, delete, modify flow entries in the OpenFlow tables
- *packet-out:* controller can send this packet out of specific switch port

OpenFlow Controller



OpenFlow: switch-to-controller messages

Key switch-to-controller messages

- *packet-in:* transfer packet (and its control) to controller. See packet-out message from controller
- *flow-removed:* flow table entry deleted at switch
- *port status:* inform controller of a change on a port.



Fortunately, network operators don't "program" switches by creating/sending OpenFlow messages directly. Instead use higher-level abstraction at controller

SDN: control/data plane interaction example



① S1, experiencing link failure uses OpenFlow port status message to notify controller

② SDN controller receives OpenFlow message, updates link status info

③ Dijkstra's routing algorithm application has previously registered to be called when ever link status changes. It is called.

④ Dijkstra's routing algorithm access network graph info, link state info in controller, computes new routes

SDN: control/data plane interaction example



⑤ link state routing app interacts with flow-table-computation component in SDN controller, which computes new flow tables needed

⑥ controller uses OpenFlow to install new tables in switches that need updating

SDN: selected challenges

- hardening the control plane: dependable, reliable, performance-scalable, secure distributed system
  - robustness to failures: leverage strong theory of reliable distributed system for control plane
  - dependability, security: “baked in” from day one?
- networks, protocols meeting mission-specific requirements
  - e.g., real-time, ultra-reliable, ultra-secure
- Internet-scaling: beyond a single AS
- SDN critical in 5G cellular networks

SDN and the future of traditional network protocols

- SDN-computed versus router-computer forwarding tables:
  - just one example of logically-centralized-computed versus protocol computed
- one could imagine SDN-computed congestion control:
  - controller sets sender rates based on router-reported (to controller) congestion levels

How will implementation of network functionality (SDN versus protocols) evolve?

Network layer: “control plane” roadmap

- introduction
- routing protocols
- intra-ISP routing: OSPF
- routing among ISPs: BGP
- SDN control plane
- Internet Control Message Protocol

ICMP: internet control message protocol

- used by hosts and routers to communicate network-level information
  - error reporting: unreachable host, network, port, protocol
  - echo request/reply (used by ping)
- network-layer "above" IP:
  - ICMP messages carried in IP datagrams
- *ICMP message:* type, code plus first 8 bytes of IP datagram causing error

Type	Code	description
0	0	echo reply (ping)
3	0	dest. network unreachable
3	1	dest host unreachable
3	2	dest protocol unreachable
3	3	dest port unreachable
3	6	dest network unknown
3	7	dest host unknown
4	0	source quench (congestion control - not used)
8	0	echo request (ping)
9	0	route advertisement
10	0	router discovery
11	0	TTL expired
12	0	bad IP header

Traceroute and ICMP



- source sends sets of UDP segments to destination
  - 1st set has TTL =1, 2nd set has TTL=2, etc.
- datagram in *n*th set arrives to nth router:
  - router discards datagram and sends source ICMP message (type 11, code 0)
  - ICMP message possibly includes name of router & IP address
- when ICMP message arrives at source: record RTTs

stopping criteria:

- UDP segment eventually arrives at destination host
- destination returns ICMP "port unreachable" message (type 3, code 3)
- source stops

Network layer: Summary

we've learned a lot!

- approaches to network control plane
  - per-router control (traditional)
  - logically centralized control (software defined networking)
- traditional routing algorithms
  - implementation in Internet: OSPF , BGP
- SDN controllers
- Internet Control Message Protocol

next stop: link layer!