

MediaMap

Interactive Map Suite

Complete Suite Documentation

[Media Map Plugin](#) · [Strata Backup Splitter](#) · [MediaMap Kiosk Plugin](#) · [Kiosk Map PWA](#)

Versions: Media Map 1.5.0 | MediaMap Kiosk 2.3.0 | Kiosk Map PWA 2.4.1
BhoomiTech Heritage and Development Foundation

1. Suite Overview

The MediaMap Suite is an integrated set of four components for collecting, curating, and displaying multimedia content pinned to real-world geographic coordinates. It spans the full lifecycle from community submission through curatorial review, data reformatting, and final presentation on interactive map kiosks, desktop browsers, or mobile devices.

1.1 What the Suite Does

Any registered user can visit a WordPress page running the Media Map Plugin, drop a pin on a Leaflet map at any real-world location, and attach a media URL — a YouTube video, an audio recording, an image, a PDF document, a text note, or a Google Street View embed. An administrator reviews the submission and approves it. Approved content appears as a styled marker on the public map. The full dataset can then be exported, reformatted by the Strata Backup Splitter utility, and loaded into the MediaMap Kiosk Plugin — which serves it to kiosk touchscreens, library PCs, or mobile devices via the Kiosk Map PWA.

1.2 Component Map

Component	Role
Media Map Plugin (v1.5.0)	Community submission and curatorial authoring. Provides the public map, submission form, admin approval workflow, import/export, and PDF proxy.
Strata Backup Splitter (PWA utility)	A standalone browser tool that converts the Kiosk Plugin's consolidated backup/export into the file-per-layer format the Kiosk PWA and the Kiosk Plugin's importer require. No server needed.
MediaMap Kiosk Plugin (v2.3.0)	Distribution and display server. Stores layers (points and GeoJSON shapes) in a dedicated database, serves them via REST API, and provides a fullscreen kiosk URL, shortcode embed, PIN-protected on-screen admin panel, PDF proxy, and domain allowlist.
Kiosk Map PWA — NT variant (v2.4.1)	Frontend player for network-connected kiosks. Runs in any browser, displays a remote Kiosk Plugin page via URL or renders USB data locally. Requires internet for PIN verification.
Kiosk Map PWA — SA variant	Identical to the NT variant but includes a first-time PIN bypass for permanently offline (air-gapped) kiosks running USB data only.

1.3 How the Components Work Together

Content moves through the suite in four stages:

- **Submit** — Community members log into a WordPress site running the Media Map Plugin, drop a pin, and attach media from hundreds of supported platforms. Each submission is held as pending.
- **Curate** — An administrator reviews pending submissions in wp-admin, approves or rejects each one, and exports the approved set as a JSON file from Media Map → Import / Export.
- **Reformat** — The exported JSON (a flat array of submissions) is opened in the Strata Backup Splitter. Strata reads the layer structure from a Kiosk Plugin backup and produces a settings.json plus one GeoJSON file per layer — the exact format the Kiosk Plugin's importer and the Kiosk PWA's USB mode expect.
- **Display** — The MediaMap Kiosk Plugin (installed on the same or a different WordPress site) imports each layer file. The Kiosk Map PWA runs on a kiosk device, a PC, or a mobile, either pointing at the Kiosk Plugin's fullscreen URL (Remote URL mode) or reading the layer files directly from a USB drive (USB mode).

All four components are released under the GNU General Public License v2 or later (GPLv2+), developed and maintained by the BhoomiTech Heritage and Development Foundation.

2. Media Map Plugin

Plugin slug: media-map **Version:** 1.5.0 **Requires:** WordPress 6.2+, PHP 7.4+

The Media Map Plugin is the community authoring layer of the suite. It turns any WordPress page into an interactive, crowdsourced map where registered users submit multimedia content pinned to real-world coordinates, and administrators review submissions before they appear publicly.

2.1 Installation

1. Upload the media-map folder to /wp-content/plugins/, or install the .zip via Plugins → Add New → Upload Plugin.
2. Activate the plugin from the WordPress Plugins menu.
3. Add [mediamap] to any page or post.
4. Configure the map via Media Map → Map Settings and Media Map → Marker Styles.
5. (Optional) Configure Media Map → PDF Sources to approve off-site domains for in-lightbox PDF preview.

2.2 The Shortcode

Shortcode	Effect
[mediamap]	Renders the full interactive map at the default height.
[mediamap height="600"]	Renders the map at 600 px height.
[mediamap height="400" class="my-class"]	Custom height and an extra CSS class on the wrapper.

2.3 Frontend Features (Logged-in Users)

Place Search and Pin Drop

A Nominatim-powered place search with autocomplete lets users find any location in the world. Clicking anywhere on the map drops a draggable pin at those coordinates; the user can also search and click a result to place the pin precisely.

Media Submission

Users paste any URL into the submission form. The plugin auto-detects the media type from the URL:

- Video — YouTube, Vimeo, Dailymotion, Twitch, TikTok, Facebook Watch, Twitter/X, Reddit, Streamable, Wistia, Loom, TED, Bilibili, Rumble, Odysee, Brightcove, Panopto, and others.
- Audio — Spotify, SoundCloud, Apple Podcasts, Bandcamp, Mixcloud, Audiomack, Buzzsprout, Podbean, Simplecast, Transistor, Audius, and others.
- Image — Imgur, Flickr, Unsplash, Pexels, Pixabay, 500px, DeviantArt, ArtStation, Behance, Dribbble, Giphy, Cloudinary, ImgBB, and direct image file URLs (.jpg, .png, .gif, .webp, .avif, etc.).
- PDF — Direct .pdf links and Google Drive/Docs viewer and share URLs. Rendered page-by-page in the lightbox via a bundled PDF.js viewer.
- Text — Omitting the URL entirely creates a text-only note with a description.

The detected type is previewed as a "Detected as..." hint while typing. Duplicate URL detection warns if the same URL has already been submitted. Configurable per-user rate limiting (submissions per hour) prevents abuse.

My Submissions Panel

Each user sees a panel listing all their own submissions with status (pending / approved / rejected), a rejection reason tooltip if applicable, Edit and Delete controls (pending submissions only are editable), and a checkbox-based JSON export that downloads selected entries in the same format as the admin import/export.

2.4 Map Display

Approved submissions appear as coloured markers on a Leaflet 1.9 map with an OpenStreetMap basemap. Clicking a marker opens an info panel showing a thumbnail on the left and the description on the right. From the info panel:

- Video or image thumbnail → opens a full-screen lightbox with the embed or full-resolution image.
- Audio thumbnail → opens an inline HTML5 audio player or a platform embed (SoundCloud, Spotify).
- PDF thumbnail → opens a paginated, fit-to-width PDF viewer (PDF.js) in the lightbox. Off-site PDFs require their domain to be approved under Media Map → PDF Sources first; until then the thumbnail falls back to "open link".
- Text-only submissions → info panel shows only the description; no media area.

Optional map features (all configurable from Map Settings): marker clustering for dense maps, fullscreen toggle button, zoom-to-bounds on load, current user location button.

2.5 Admin Workflow

Submissions Page

Filterable by status (All / Pending / Approved / Rejected) and searchable. Actions per submission: Approve (notifies the user by email), Reject (optional rejection note sent to user), Re-approve, Revoke, Delete. Bulk delete is supported. An admin notice on the WP Dashboard alerts when pending items exist.

Map Settings

Setting	Description
Basemap tile URL & attribution	Override the default OpenStreetMap basemap with any tile provider.
Min/max zoom	Restrict the zoom range visitors can use.
Map height	Default height in pixels for the [mediamap] shortcode.
Zoom-bound-to-content	Fit the map to approved markers on load.
Fullscreen button	Show/hide the fullscreen toggle.
Marker clustering	Group nearby markers into clusters at low zoom.
Submission Rate Limit	Maximum submissions per user per hour (0 to disable).
Email notifications	Toggle admin notification on new submission; toggle user notification on approval/rejection.

Marker Styles

Per-type colour pickers and optional custom icon URL for each media type: Image, Video, Audio, Text, PDF, and Pending. Pending markers use a distinctive cross/X symbol to distinguish unreviewed submissions to their own author.

PDF Sources (PDF Proxy Allowlist)

PDFs hosted on another domain cannot be fetched directly by a visitor's browser due to CORS restrictions. The plugin can proxy an approved domain's PDF through its own server so PDF.js can render it in the lightbox. The allowlist is empty by default; an administrator must explicitly add each domain. PDFs in the site's own Media Library are always same-origin and never need approval.

The PDF proxy includes layered SSRF defenses: scheme check (http/https only), admin-managed domain allowlist, IP resolution against private/loopback/reserved ranges, no redirect following, response size cap, timeout, "%PDF-" magic-byte validation, and per-IP rate limiting. Approved-domain proxied PDFs are cached for 24 hours.

2.6 Import / Export

Media Map → Import / Export supports both JSON and CSV formats:

- Export JSON — downloads all approved (or all) submissions as a JSON array, with each submission's coordinates, media type, URL, description, place name, and status.
- Export CSV — same data in CSV format, with proper quote-aware encoding (descriptions with line breaks are handled correctly).
- Import JSON or CSV — inserts submissions directly into the database using the same media-type auto-detection and validation as the live form. A "text" row cannot keep an attached media URL; media type is re-detected on import.
- Export (My Submissions) — individual users can also export their own selected submissions as JSON from the frontend My Submissions panel.

2.7 Database Tables

Table	Contents
wp_mediapmap_submissions	One row per submission: id, user_id, lat, lng, place_name, media_type, media_url, description, status, rejection_note, url_hash (SHA-256), submitted_at, reviewed_at, reviewed_by.
wp_mediapmap_rate_log	Tracks submission timestamps per user for rate limiting. Pruned daily.

2.8 Uninstallation

Deactivating the plugin does not touch any data. Deleting it from the Plugins screen removes both database tables, all plugin options, scheduled events, and the PDF proxy's disk cache. Export your data before deleting.

3. Strata Backup Splitter

Package: strata-backup-splitter **Type:** Standalone PWA utility (no server required)

Strata is a lightweight, single-page Progressive Web App that acts as the data bridge between the Media Map Plugin's export format and the file-per-layer format expected by both the MediaMap Kiosk Plugin's importer and the Kiosk Map PWA's USB mode. Everything runs locally in the browser — no file is ever sent to any server.

3.1 Why Strata Exists

The Media Map Plugin exports a flat JSON array of submissions, suitable for archiving and re-import. The MediaMap Kiosk Plugin's backup, however, uses a consolidated envelope format containing all layers, their points, their GeoJSON shapes, and their styling metadata in one file. The Kiosk Plugin's own importer and the Kiosk PWA's USB mode, by contrast, expect one file per layer — a settings.json listing the layers and their metadata, plus one .geojson file per layer containing that layer's geometries.

Strata reads the consolidated backup, detects all layers and their content type (point-only, shape-only, or mixed), and writes the split output — converting point objects to GeoJSON Point Features in the process.

3.2 Deployment

6. Serve the strata-backup-splitter folder from any web server, or open index.html directly in a browser. Because everything runs client-side, even a local double-click on index.html works in most browsers.
7. (Optional) The PWA can be installed from the browser's "Install" prompt, giving it a standalone window and an app icon. A service worker caches the app shell for offline use.

3.3 Workflow

The Strata UI steps through a four-panel flow:

Step 1 — Load Backup File

Drag and drop or browse to a consolidated .json backup from the MediaMap Kiosk Plugin (downloaded via MediaMap Kiosk → Backup, or from the on-screen admin panel). Strata parses the file entirely in the browser.

Step 2 — Detected Layers Preview

Strata shows a summary: total layers found, total features across all layers, and a split count of shape layers vs pin layers. Each layer is listed with its name, the output filename it will be written as (slugified from the layer name, with collision avoidance for duplicate names), a type badge (Shape layer / Pin layer / Shape + Pin / Empty), and a feature count. Layer colour is shown as a swatch taken from the layer's shapeStyle.

Step 3 — Split

Clicking "Split into files" generates all output files in memory. Point entries are converted to GeoJSON Point Features (coordinates in [lng, lat] order as GeoJSON requires). Shape features are passed through unchanged. Mixed layers contain both.

Step 4 — Download

Each output file is listed with its name, estimated file size, and an individual Download link. A "Download all (.zip)" button bundles everything into a single zip archive named after the original backup file.

3.4 Output File Format

settings.json

Contains the kiosk configuration from the original backup, plus one entry per layer pointing to its own GeoJSON file:

```
{
  "backupFormatVersion": 1,
  "exportedAt": "2026-06-22T10:00:00.000Z",
  "kiosk": {
    "idle_time_seconds": 90,
    "lock_bounds_to_data": false
  },
  "layers": [
    {
      "file": "heritage_sites.geojson",
      "name": "Heritage Sites",
      "type": "point",
      "enabled": true,
      "order": 0,
      "featureCount": 12,
      "shapeStyle": { "fillColor": "#4f46e5", "lineColor": "#312e81" },
      "createdAt": "2026-01-01T00:00:00",
    }
  ]
}
```

```
      "updatedAt": "2026-06-01T00:00:00"
    }
  ]
}
```

{layer-slug}.geojson

A standard GeoJSON FeatureCollection containing all features for that layer. Point entries become GeoJSON Point Features with all submission properties in the properties object. Shape entries are passed through verbatim as the original GeoJSON Features.

```
{
  "type": "FeatureCollection",
  "features": [
    {
      "type": "Feature",
      "properties": {
        "place_name": "Kamakhya Temple",
        "media_type": "image",
        "media_url": "https://example.com/photo.jpg",
        "description": "A Shakti Peetha temple on Nilachal Hill."
      },
      "geometry": { "type": "Point", "coordinates": [91.7362, 26.1445] }
    }
  ]
}
```

3.5 Layer Classification

Badge	Meaning
Pin layer	Layer contains only point (media-pin) features.
Shape layer	Layer contains only GeoJSON shape features (lines, polygons).
Shape + Pin	Mixed layer containing both points and shapes.
Empty	Layer exists in the backup but has no features; exports as an empty FeatureCollection.

4. MediaMap Kiosk Plugin

Plugin slug: mediamap-kiosk **Version:** 2.3.0 **Requires:** WordPress 6.0+, PHP 7.4+

The MediaMap Kiosk Plugin is the distribution and display server of the suite. It holds the curated layer data in its own database, serves it over a REST API, and renders it on any connected kiosk screen — either embedded in a themed WordPress page via shortcode, or in a dedicated fullscreen URL for kiosk hardware.

4.1 Installation

8. Upload the mediamap-kiosk folder to /wp-content/plugins/, or install the .zip via Plugins → Add New → Upload Plugin.
9. Activate the plugin. Three database tables are created (layers, points, shapes) and the manage_mediapmap_kiosk capability is granted to Administrators.
10. Go to MediaMap Kiosk → Settings and set a PIN. The on-screen admin panel remains locked until one is configured.
11. Go to MediaMap Kiosk → Layers and import your first layer (a JSON array of points or a GeoJSON file — see Section 4.6).
12. Deploy the kiosk via shortcode [mediapmap_kiosk] or the dedicated fullscreen URL shown under MediaMap Kiosk → Embed & Kiosk URL.

4.2 Admin Panel (wp-admin)

Layers

The central management page. Each layer appears in a table showing its name, point count, shape count, active/inactive status, display order, and available actions (Activate/Deactivate, Move Up, Move Down, Rename, Restyle, Delete). Layers are keyed internally by numeric ID, not by name — ensuring rename, reorder, toggle, and delete operations work correctly even when layer names contain spaces or special characters.

The right-hand sidebar contains the import form: select a JSON or GeoJSON file, enter a layer name, and the data is normalised and written to the database. The layer name can be changed later without losing data.

Settings

Setting	Description
Kiosk Admin PIN	A PIN stored as a one-way hash. Required to unlock the on-screen admin panel on kiosk devices. Leave blank to disable on-screen admin access.

Default idle auto-close timer	Seconds of inactivity before the kiosk returns to its default view. New devices start with this; operators can adjust per-device from the on-screen panel.
Default pan/zoom lock	When enabled, visitors cannot pan or zoom outside the bounding box of the active layers (plus a margin). Adjustable per-device.
Delete all data on uninstall	If checked before deleting the plugin, all layers, points, shapes, and settings are permanently removed. Unchecked (default): data persists for reinstall.

Embed & Kiosk URL

Shows the exact shortcode ([mediamap_kiosk] or [mediamap_kiosk height="800px"]) and the dedicated fullscreen URLs in both pretty-permalink and query-string forms:

URL Form	Example
Pretty permalink	<code>https://yoursite.com/map-kiosk/</code>
Query string (fallback)	<code>https://yoursite.com/?mediamap_kiosk=1</code>

Approved Kiosk URLs (Allowlist)

A curated list of hostnames that the standalone Kiosk Map PWA is permitted to connect to in its Remote URL mode. Exact hostname match only — no wildcards, no subdomain inheritance. Has no effect on the plugin's own embedded kiosk. See Section 6.3 for the full allowlist security model.

PDF Sources

A separate domain allowlist controlling which off-site domains the plugin's server-side PDF proxy may fetch from on a visitor's behalf. This list is distinct from the Approved Kiosk URLs list. Approving a domain for PDF fetching does not approve it as a kiosk URL, and vice versa. See Section 6.4 for the PDF proxy security model.

4.3 The On-Screen Admin Panel (PIN-Protected)

A gear icon on the kiosk interface opens a PIN prompt. A correct PIN exchanges for a short-lived session token; subsequent admin actions on that device use the token rather than requiring the PIN again until it expires. The panel provides:

- Import a new layer from a JSON or GeoJSON file (via file picker on the kiosk device).
- Rename layers.
- Reorder layers (drag or up/down arrows).
- Toggle layers active or inactive.
- Restyle a layer's shape fill colour, line colour, line weight, and label settings.

- Delete layers.
- Backup (download all layers as a consolidated JSON file) and Restore.
- Adjust the idle timer and pan/zoom lock for this device (local cache only — does not change the site-wide default).

4.4 Display Modes

Shortcode Embed ([mediamap_kiosk])

Renders the Leaflet map inside any WordPress page within the active theme's header and footer. Suitable for library portals, classroom pages, or any context where the map sits alongside other content.

Dedicated Fullscreen URL

A theme-agnostic URL rendering only the map — no WordPress header, footer, admin toolbar, or theme CSS. Optimised for dedicated kiosk hardware in a locked-down browser. The admin toolbar is suppressed even for logged-in administrators at this URL.

4.5 Offline Resilience

Each kiosk device caches its layer data in browser IndexedDB. A brief network interruption does not interrupt a visitor's session — the kiosk continues from its local cache. WordPress remains the single source of truth; the cache is refreshed each time the kiosk loads or is manually synced.

A full database flush from the on-screen admin panel (Flush button) or the REST API permanently deletes every layer, point, and shape from the shared database — affecting every kiosk device, not just the one the action is performed on. Back up before flushing.

4.6 Import File Format

The Layers import form accepts any of three shapes:

- A plain JSON array of point objects: [{ "lat": ..., "lng": ..., "place_name": ..., "media_type": ..., "media_url": ..., "description": ... }, ...]
- A wrapped object: { "data": [...same point objects...] }
- A GeoJSON FeatureCollection, single Feature, or bare geometry object. Point/MultiPoint geometries become map pins; LineString/Polygon/MultiLineString/MultiPolygon geometries become styled shapes.

media_type is optional — if omitted, it is auto-detected from the URL (YouTube domains, file extensions, Street View links, .pdf extension, etc.). Valid values: video, audio, image, streetview, text, pdf.

4.7 Database Tables

Table	Column	Description
wp_mediapmap_layers	id, group_name, active, layer_order, shape_style, created_at, updated_at	One row per layer. shape_style is stored as TEXT (JSON).
wp_mediapmap_points	id, layer_id, lat, lng, place_name, media_type, media_url, description	One row per media pin, foreign-keyed to a layer.
wp_mediapmap_shapes	id, layer_id, geojson_feature	One row per GeoJSON shape Feature, stored as raw LONGTEXT. Leaflet renders it directly without reconstruction.

4.8 REST API (mediapmap-kiosk/v1)

"Protected" endpoints accept either a logged-in WordPress user with the manage_mediapmap_kiosk capability, or a valid kiosk session token from /pin/verify passed as the X-Mediapmap-Kiosk-Token header.

Method + Endpoint	Auth	Description
GET /layers	Public	List all layers (metadata + point/shape counts). No inline data.
GET /layers/{id}	Public	Single layer with all points and shapes.
POST /layers	Protected	Create or overwrite a layer (import).
POST /layers/{id}/rename	Protected	Rename a layer.
POST /layers/{id}/active	Protected	Toggle a layer's active flag.
POST /layers/{id}/style	Protected	Update a layer's shape style.
POST /layers/reorder	Protected	Swap two layers' display order.
DELETE /layers/{id}	Protected	Delete a layer and all its points and shapes.
GET /settings	Public	Read idle timer and pan/zoom lock defaults (no PIN hash).
POST /settings	Admin only	Update site-wide idle timer and bounds lock.
POST /pin/verify	Public	Exchange a PIN for a short-lived session token.
GET /allowlist	Public	Approved domain list for the Kiosk PWA's Remote URL mode.
POST /allowlist	Admin only	Replace the approved domain list.

GET /pdf-proxy	Public	Server-side PDF relay for CORS workaround (approved domains only).
GET /pdf-proxy-allowlist	Admin only	Read the PDF proxy domain list.
POST /pdf-proxy-allowlist	Admin only	Replace the PDF proxy domain list.
GET /backup	Protected	Download full consolidated export.
POST /restore	Protected	Destructive full restore from a backup file.
POST /flush	Protected	Wipe all layers, points, and shapes.

5. Kiosk Map PWA (kiosk-map-nt / kiosk-map-sa)

Package: kiosk-map-network **Version:** 2.4.1 **Type:** Progressive Web App (no server required)

The Kiosk Map PWA is a fully self-contained Progressive Web App — a single folder of HTML, CSS, and JavaScript that runs in any modern browser with no server-side component. It is the end-display application for the suite, rendering an interactive Leaflet map with media-rich pins and styled GeoJSON shapes on kiosk touchscreens, desktop PCs, or mobile devices.

5.1 Deployment

13. Copy the kiosk-map-network folder to any web server, USB drive root, or local filesystem accessible by the kiosk device's browser.
14. Open index.html. The Setup screen appears on first launch.
15. Choose a source mode and configure it. The choice is saved and restored automatically on every subsequent load — including after a power cycle.
16. (Optional) Install the PWA from the browser's "Install app" prompt to run fullscreen with its own icon and no browser chrome.

On Apache web servers, the included .htaccess maps the .mjs extension to text/javascript and .wasm to application/wasm, ensuring PDF.js loads correctly as an ES module. Without this, the vendor/pdfjs/ PDF renderer will fail. On other servers (nginx, IIS), add equivalent MIME type rules.

5.2 PWA Variants

The Kiosk Map PWA is distributed in two variants that differ only in how they handle PIN verification on a device that has never been online:

Variant	Package / Use case
kiosk-map-nt (Network-required)	kiosk-map-network — for kiosks that have internet access at least occasionally. PIN verification always requires a live network round-trip. Described throughout this section.
kiosk-map-sa (Standalone / offline)	For kiosks that have NO internet access at all. Includes a one-time PIN bypass for first-time setup only. See the box below.

❑ **kiosk-map-sa — Standalone (Offline) PWA Variant**

Use this variant when the kiosk device has no internet connection at any point.

The standard PIN-verification mechanism requires a live network round-trip to the WordPress MediaMap Kiosk Plugin's `/pin/verify` endpoint every time a source change is made. On a kiosk that is permanently offline this creates an inescapable deadlock:

- First-time setup succeeds — no PIN is required yet, because nothing has been saved to protect.
- The operator then needs to change the source — even to correct a first-day mistake — and is immediately locked out, because the PIN check can never reach the server.
- The kiosk is permanently stuck, with no recovery path short of clearing all browser storage.

How the bypass works

The SA variant tracks whether this specific device has ever successfully completed a PIN verification online (stored in `localStorage` under the key `mediamap_pin_verified_once`). Until that happens, the "Change source" screen shows a clearly-labelled bypass button alongside the normal PIN field:

```
Continue without PIN (first-time setup)
```

The bypass is intentionally limited and self-expiring:

- It appears only while the device is in the "unclaimed" state — i.e. a PIN has never been verified online on this device.
- The moment any PIN is successfully verified online, the bypass is permanently hidden on this device and every future source change requires the real, network-verified PIN — exactly as in the NT variant.
- Physical access to the device is already required to tap the bypass button — the same access that picking a USB folder requires. No new attack surface is introduced.

Which variant to choose: If the kiosk will ever connect to the internet — even briefly during initial commissioning — use `kiosk-map-nt`. Only use `kiosk-map-sa` for permanently air-gapped kiosks running entirely on USB data.

5.3 Source Modes

Remote URL Mode

The PWA displays a remote WordPress page (typically the MediaMap Kiosk Plugin's fullscreen URL) directly inside a sandboxed fullscreen `iframe`. The PWA does not parse or interpret JSON data from the remote page — it simply presents it, as a dedicated kiosk browser pointed at a URL would. Key behaviours:

- If the page fails to load (offline, DNS error, server restart), a retry screen appears automatically and the PWA keeps attempting to reload every 8 seconds until it succeeds.
- The configured URL is saved in `localStorage` and restored on every reload — no re-entry needed after a power cycle.

- Every URL entered is validated against the domain allowlist served by the Kiosk Plugin before being saved. Changing an already-saved source additionally requires the kiosk PIN.
- The allowlist is re-checked periodically while the kiosk is running. A URL removed from the allowlist is revoked on the next recheck, with a brief on-screen countdown warning before disconnecting.

USB Mode

The PWA reads layer data directly from a folder on a USB drive (or any local directory) using the browser's File System Access API. Key behaviours:

- On first use, the user clicks "Select folder..." and grants the browser permission to read the `mediamap-kiosk-data` directory.
- The directory handle (not just the name) is saved in IndexedDB. On subsequent loads, the PWA silently re-opens the saved handle. If the browser has already granted permission, no user interaction is needed.
- If permission was revoked, a "Reconnect to saved USB folder" button appears. Only a single tap is required — not the full folder picker — unless the handle is completely gone.
- Layer data, pins, and shapes are rendered entirely client-side using the PWA's own Leaflet map. Note that basemap tiles (the OpenStreetMap background) still require a network connection; only the layer data itself works fully offline.

5.4 Folder Structure (USB Mode)

The `mediamap-kiosk-data` folder must contain a `settings.json` and one file per layer (JSON or GeoJSON):

```
mediamap-kiosk-data/  
  settings.json           ← required: lists layers and kiosk config  
  heritage-sites.geojson  ← one file per layer (name matches "file" field)  
  river-course.geojson  
  campus-pois.json
```

settings.json Format

```
{  
  "layers": [  
    {  
      "file": "heritage-sites.geojson",  
      "name": "Heritage Sites",  
      "enabled": true  
    },  
    {  
      "file": "river-course.geojson",
```

```

    "name": "River Course",
    "enabled": true,
    "shapeStyle": {
      "fillColor": "#4f46e5",
      "fillOpacity": 0.25,
      "lineColor": "#312e81",
      "lineWeight": 3,
      "label": "Brahmaputra",
      "labelColor": "#1e1b4b",
      "labelSize": 14
    }
  },
  {
    "file": "campus-pois.json",
    "name": "Campus POIs",
    "enabled": true,
    "cluster": false
  }
],
"kiosk": {
  "idle_time_seconds": 90,
  "lock_bounds_to_data": false
}
}

```

Field	Description
layers[].file	Filename of the layer data file in the same directory.
layers[].name	Display name in the layer legend (overrides the file's own name).
layers[].enabled	false hides the layer without removing it from settings.
layers[].shapeStyle	Fill colour, fill opacity, line colour, line weight, label text, label colour, label size. Applied to GeoJSON shape features.
layers[].cluster	Set false to disable marker clustering for this layer (default: true).
kiosk.idle_time_seconds	Seconds of inactivity before the kiosk returns to the default map view.
kiosk.lock_bounds_to_data	If true, the map cannot be panned or zoomed outside the data extent.

5.5 Map Features

Interactive Leaflet Map

A Leaflet 1.9 map with OpenStreetMap tiles (internet required for tiles). Point markers are clustered by default (three size tiers in indigo branding). Clicking a cluster zooms in to reveal individual pins. Clicking a pin opens a media lightbox.

Media Lightbox

The lightbox renders different media types natively:

- Video — embedded player (YouTube, Vimeo, Twitch, TikTok, and others via iframe embed).
- Audio — HTML5 audio player or platform embed (SoundCloud, Spotify).
- Image — full-resolution image display.
- PDF — paginated PDF.js viewer, rendering page-by-page on canvas. The PDF.js library (including the LEGACY build of pdf.min.mjs, the worker, standard fonts, JBIG2/QCMS WASM modules) is vendored locally. This ensures PDF rendering works on a kiosk's first launch without network access. In USB mode, PDF files can be path-referenced relative to the data folder; the PWA resolves them using the File System Access API handle.
- Street View — Google Street View embed inside the lightbox.
- Text — description only, no media area.

GeoJSON Shape Layers

LineString, Polygon, MultiLineString, and MultiPolygon features are rendered as styled overlays with configurable fill colour, fill opacity, line colour, line weight, and an optional label. Style is read from shapeStyle in settings.json (USB mode) or from the layer record in the database (Remote URL mode).

Idle Reset

After the configured idle period of inactivity, the kiosk resets the map view to the default extent, closing any open lightbox. The idle timer is per-device; the site-wide default comes from the Kiosk Plugin's /settings endpoint.

5.6 Vendored Libraries

All libraries are bundled locally so the PWA works correctly on a kiosk's very first launch with zero network connectivity:

Library	Purpose
Leaflet 1.9 (leaflet.js, leaflet.css)	Interactive map rendering and tile loading.
Leaflet.markercluster (leaflet.markercluster.js)	Marker clustering for dense pin layers.

Material Icons (material-icons.woff2)	UI icon glyphs. Vendored so icons render correctly offline.
PDF.js — LEGACY build (pdf.min.mjs, pdf.worker.min.mjs)	Client-side PDF parsing and canvas rendering. LEGACY build used for broadest browser compatibility.
PDF.js standard fonts	Foxit and Liberation fonts for PDF text rendering without network.
PDF.js WASM modules (jbig2.wasm, qcms_bg.wasm)	JBIG2 compressed image decoding and colour management in scanned PDFs.

5.7 Bundled Sample Data

The PWA ships with three demonstration layers pre-configured in `mediamap-kiosk-data/settings.json`, all for the Assam / Northeast India region:

Layer File	Contents
<code>iitg_campus.geojson</code>	IIT Guwahati campus boundary — polygon shape layer with blue fill and label.
<code>kaziranga_area.geojson</code>	Kaziranga National Park area boundary — polygon shape layer with green fill and label.
<code>assam_points_demo.geojson</code>	Points of interest across Assam — pin layer with sample video, audio, image, and text entries.

Replace or supplement these files with your own layer exports for production deployment.

6. Security Architecture

The suite has several overlapping security mechanisms that are worth understanding as a whole, especially for public-facing deployments such as museum kiosks or outdoor information terminals.

6.1 Media Map Plugin — Submission and Access Control

Only logged-in WordPress users can submit content. Viewing the map is public. The admin approval workflow ensures no user-submitted content appears publicly without a human review. Rate limiting (configurable submissions per hour per user) prevents submission flooding. Duplicate URL detection prevents the same URL from being submitted multiple times. URL and description fields are sanitised and HTML-escaped before being written to attributes or rendered in the map panel.

6.2 Kiosk Plugin — Dual Authentication

Protected REST endpoints accept two credential types:

- A logged-in WordPress session with the `manage_mediapmap_kiosk` capability (for remote administration via wp-admin or REST client).
- A kiosk session token obtained by calling `POST /pin/verify` with the correct PIN (for on-device management without a WordPress login).

The PIN is stored as a one-way hash server-side; the plaintext PIN is never stored or compared client-side. Rate limiting is applied to `/pin/verify` to resist brute-force attacks. PIN-holders can manage layers and adjust local settings but cannot change site-wide defaults or the domain allowlists — those require a full WordPress admin session.

6.3 Kiosk PWA — Domain Allowlist

The domain allowlist is the primary integrity control for Remote URL mode, ensuring that a kiosk device can only ever display content from sites explicitly approved by a WordPress administrator.

The allowlist is about integrity, not secrecy. The list is publicly readable via `GET /allowlist`. What it prevents is unauthorized sources being saved or persisted on a kiosk device.

Save-time Validation (Fails Closed)

When a user enters a new URL on the PWA setup screen, the PWA fetches the allowlist from `ALLOWLIST_ENDPOINT` and checks for an exact hostname match. If the endpoint cannot be reached and no cached allowlist exists, the save is blocked — not silently allowed through.

Runtime Re-validation (Fails Open on Network Error)

While the kiosk is running, the allowlist is re-checked periodically (every 5 minutes). If the re-check finds the current source URL is no longer listed, a short countdown warning is shown before the kiosk disconnects. However, if the allowlist endpoint is simply unreachable during a periodic re-check, the running session continues — a network blip must not cause a kiosk outage. Only an explicitly negative allowlist response causes revocation.

PIN Gate on Source Changes

Changing an already-configured source URL (or switching between URL and USB modes) requires both a passing allowlist check and the kiosk PIN, verified via `/pin/verify`. First-ever setup on a fresh kiosk is not PIN-gated — there is nothing yet to protect.

6.4 PDF Proxy — SSRF Defenses

Both the Media Map Plugin and the MediaMap Kiosk Plugin include server-side PDF proxies that fetch a remote PDF on a visitor's behalf to circumvent browser CORS restrictions. Both proxies implement the same defence-in-depth stack:

- Scheme check — only `http://` and `https://` are accepted. `file://`, `gopher://`, and other schemes are rejected.
- Domain allowlist — the target hostname must appear on the admin-managed allowlist. Nothing is fetchable until explicitly approved.
- IP resolution and private-range check — the target hostname is resolved to an IPv4 address, which is then checked against private (RFC 1918), loopback, link-local, and reserved ranges. This catches DNS rebinding attacks and misconfigured domains even after allowlist approval.
- No redirect following — a redirect response is treated as a failure, preventing an allowlisted host from redirecting to a non-allowlisted or internal target.
- Response size cap (50 MB) and timeout — prevents memory exhaustion and hung PHP workers.
- "%PDF-" magic-byte validation — the response must begin with the PDF magic header before being cached or served. Unexpected content from an allowlisted host is not relayed.
- Per-IP rate limiting — limits the outbound work triggered per visitor.
- 24-hour disk cache — successful fetches are cached in `wp-content/uploads/`, so the same PDF is not re-fetched on every visit.

6.5 Kiosk Fullscreen URL — Admin Toolbar Suppression

When the dedicated fullscreen kiosk URL is accessed, the WordPress admin toolbar is suppressed even for logged-in administrators — preventing "Howdy, [name]" and a wp-admin link from appearing on a public-facing kiosk screen. The shortcode embed on a normal themed page retains

the admin toolbar for logged-in users, as this is expected WordPress behaviour outside a kiosk context.

7. Deployment Scenarios

7.1 Museum or Heritage Centre (Full Online Suite)

A museum runs the Media Map Plugin on a community-facing WordPress site. Visitors and community members submit content — videos, audio recordings, photographs, and text notes — pinned to heritage sites on the map. Curators approve submissions from wp-admin. The approved dataset is exported and imported into the MediaMap Kiosk Plugin (on the same or a dedicated WordPress site). Touchscreen kiosks in the museum's galleries run the Kiosk Map PWA in Remote URL mode, pointed at the Kiosk Plugin's fullscreen URL.

- Community site: Media Map Plugin.
- Kiosk backend site: MediaMap Kiosk Plugin.
- Gallery kiosks: Kiosk Map PWA (NT variant) in Remote URL mode.

7.2 Offline / Travelling Exhibition (USB Mode)

A community organisation takes a curated map to rural events without reliable internet. Content is authored and approved via the Media Map Plugin on a connected WordPress site. The Kiosk Plugin's backup is downloaded and processed through Strata to produce a folder of layer files. The folder is copied onto a USB drive. At the event, a laptop or tablet runs the Kiosk Map PWA (SA variant if fully offline, NT variant if briefly commissioning online) in USB mode. Basemap tiles require internet; if no connection is available at the event, a cached or offline tile provider can be substituted in app.js.

- Authoring: Media Map Plugin (online).
- Reformatting: Strata Backup Splitter.
- Event device: Kiosk Map PWA (SA variant) in USB mode.

7.3 Classroom or Library Portal (Embedded Map)

A school adds the MediaMap Kiosk Plugin to its existing WordPress site and imports curated GeoJSON layers (local field trip routes, points of interest, historical sites). The kiosk map is embedded on a page using [mediamap_kiosk]. Students browse from any device on the school network — no dedicated kiosk hardware needed. The Media Map Plugin is optional if content is curated externally.

- WordPress site: MediaMap Kiosk Plugin.
- No separate PWA required.

7.4 Research or Data Visualisation (Plugin Only)

A research team uses the Media Map Plugin standalone: team members submit georeferenced media (audio field recordings, video interviews, PDF reports) via the [mediamap] shortcode page. An admin curates and exports the data as JSON or CSV for further analysis. The kiosk pipeline is not used.

- WordPress site: Media Map Plugin only.
- No Kiosk Plugin, no PWA, no Strata.

8. Quick Reference

8.1 Shortcodes

Shortcode	Effect
[mediamap]	Media Map Plugin — full public map with submission form.
[mediamap height="600"]	Media Map Plugin — map at a custom pixel height.
[mediamap_kiosk]	Kiosk Plugin — kiosk map embedded in a themed page.
[mediamap_kiosk height="800px"]	Kiosk Plugin — kiosk map at a custom height.

8.2 Key URLs (Kiosk Plugin)

URL Pattern	Description
https://yoursite.com/map-kiosk/	Fullscreen kiosk URL (pretty permalink).
https://yoursite.com/?mediamap_kiosk=1	Fullscreen kiosk URL (query string).
https://yoursite.com/wp-json/mediamap-kiosk/v1/layers	REST: list all layers.
https://yoursite.com/wp-json/mediamap-kiosk/v1/allowlist	REST: PWA domain allowlist (public).
https://yoursite.com/wp-json/mediamap-kiosk/v1/backup	REST: full consolidated export (protected).

8.3 Supported Media Types (Both Plugins)

Type	Detection and Display
video	YouTube, Vimeo, Dailymotion, Twitch, TikTok, Facebook, Twitter/X, Reddit, Streamable, Wistia, Loom, TED, Bilibili, Rumble, Odysee, Brightcove, Panopto, and others — embedded via iframe.
audio	Spotify, SoundCloud, Apple Podcasts, Bandcamp, Mixcloud, Audiomack, Buzzsprout, Podbean, Simplecast, Transistor, Audius — embedded player or HTML5 audio.
image	Imgur, Flickr, Unsplash, Pexels, Pixabay, 500px, DeviantArt, Behance, Dribbble, Giphy, Cloudinary, ImgBB, and direct image file URLs.

pdf	.pdf URLs and Google Drive/Docs share links — rendered page-by-page via bundled PDF.js.
streetview	Google Maps embed URLs (maps.google.com/maps/embed) — rendered in an iframe.
text	No URL — description text only.

8.4 File and Directory Reference

Component	Path	Contents
Media Map Plugin	wp-content/plugins/media-map/	Plugin PHP, admin pages, frontend JS/CSS, vendored Leaflet and PDF.js.
Media Map Plugin	wp-content/uploads/mediamap-pdf-cache/	Server-side PDF proxy disk cache (24h TTL).
Kiosk Plugin	wp-content/plugins/mediamap-kiosk/	Plugin PHP, admin pages, kiosk JS/CSS, vendored libraries.
Kiosk Plugin (DB)	wp_mediapmap_layers / _points / _shapes	Custom database tables for all layer, point, and shape data.
Strata Splitter	strata-backup-splitter/index.html	Single-file PWA utility. All processing in-browser.
Kiosk PWA	kiosk-map-network/index.html	PWA entry point.
Kiosk PWA	kiosk-map-network/app.js	All PWA application logic (map, media, security, USB).
Kiosk PWA	kiosk-map-network/sw.js	Service worker for offline app-shell caching.
Kiosk PWA	kiosk-map-network/mediamap-kiosk-data/	USB mode data folder (settings.json + layer GeoJSON files).
Kiosk PWA	kiosk-map-network/vendor/	Leaflet, MarkerCluster, Material Icons, PDF.js — all vendored locally.
Kiosk PWA	kiosk-map-network/.htaccess	Apache MIME type rules for .mjs and .wasm (required for PDF.js).

8.5 Browser Support Notes

Feature	Browser Support
File System Access API (USB mode)	Chrome, Edge, and other Chromium browsers only. Not available in Firefox or Safari.

PDF.js rendering	All modern browsers. Uses LEGACY build for widest compatibility.
Service Worker / PWA install	Chrome, Edge, Firefox, Safari 16.4+.
Marker clustering	All modern browsers.
Leaflet map (tile loading)	All modern browsers. Tiles require internet.
IndexedDB (offline cache / USB handle)	All modern browsers.

9. Troubleshooting

9.1 Media Map Plugin

A submitted PDF shows "open link" instead of rendering in the lightbox

The PDF is hosted on an off-site domain that has not yet been added to the PDF Sources allowlist. Go to Media Map → PDF Sources in wp-admin and add the domain (bare hostname, e.g. example.com). PDFs in the site's own Media Library are always same-origin and never need approval.

Imported CSV has corrupted rows or missing content

Ensure the CSV was exported with proper RFC 4180 quoting, particularly for fields containing commas or line breaks. Versions 1.4.4 and later use full quote-aware CSV parsing. Re-import from a fresh export from a 1.4.4+ site if upgrading from an older version.

Pending marker colour does not change after updating Marker Styles

Ensure you are on version 1.4.4 or later. Earlier versions had a bug where a second set of default marker colours silently overrode the saved Marker Styles settings. After upgrading, save the Marker Styles page once to write the correct values.

9.2 Strata Backup Splitter

"No layers array found" error when loading a file

Strata expects a MediaMap Kiosk Plugin backup (the format produced by GET /backup or the on-screen Backup button). A raw Media Map Plugin JSON export (a flat array of submissions) does not contain a "layers" key and cannot be split by Strata. Import the submission JSON directly into the Kiosk Plugin's Layers page first, then export a consolidated backup from the Kiosk Plugin, then run that through Strata.

Two layers end up with the same output filename

Strata slugifies layer names for filenames and automatically appends _2, _3, etc. if two slugified names would collide (e.g. "Heritage Sites" and "Heritage Sites (2)" both become heritage_sites, so the second becomes heritage_sites_2). The output preview shows the actual filename before you split — check it and rename layers in the Kiosk Plugin if a cleaner filename is needed.

9.3 MediaMap Kiosk Plugin

Layer rename, toggle, or delete does nothing from the on-screen panel

Ensure you are on version 1.0.2 or later. Earlier versions identified layers by name in the REST URL path, which failed for names containing spaces. Version 1.0.2 switched to numeric ID. After upgrading, existing layers and their names are unaffected.

Active checkbox in the on-screen panel is invisible

Ensure you are on version 1.0.1 or later. Earlier versions relied on native browser checkbox theming, which rendered with very low contrast in the dark kiosk admin panel on some browser/OS combinations. Version 1.0.1 applies explicit CSS.

Flush wiped data on all kiosks, not just one device

This is expected behaviour. The Flush action deletes data from the shared WordPress database — the single source of truth for all connected kiosk devices. Per-device local caches (IndexedDB) are stale after a flush and will show empty layers until cleared. Always back up (download a consolidated JSON) before flushing.

9.4 Kiosk Map PWA

PDF.js fails to load — "Failed to load module script: Expected a JavaScript-or-Wasm module"

The web server is not serving .mjs files with the correct MIME type. On Apache servers, the included .htaccess adds the necessary AddType directives for .mjs and .wasm. On nginx, add: `types { text/javascript mjs; application/wasm wasm; }.` On IIS, add the MIME types via the management console. Without this, `vendor/pdfjs/*.mjs` cannot be imported as ES modules and PDF rendering will fail.

"URL not in approved list" when entering a Remote URL

The hostname of the URL entered on the setup screen is not on the domain allowlist served by the configured `ALLOWLIST_ENDPOINT`. Ask the WordPress administrator of the target Kiosk Plugin site to add your domain to MediaMap Kiosk → Approved Kiosk URLs. The check is an exact hostname match — `www.yoursite.com` and `yoursite.com` are treated as different hostnames.

USB folder selection does nothing in the browser

The File System Access API (`showDirectoryPicker`) is only available in Chromium-based browsers (Chrome, Edge). It is not supported in Firefox or Safari. USB mode cannot function in these browsers; use Chrome or Edge.

Map tiles do not appear in USB mode

Basemap tiles (the OpenStreetMap background) are loaded from the internet on demand and are not bundled in the PWA or on the USB drive. USB mode layer data (pins and shapes) works offline, but the basemap always requires a network connection. For a fully offline basemap, replace the tile URL in `app.js` with a local tile server or a file-based MBTiles solution.

10. Changelog

Media Map Plugin

Version 1.5.0 (Current)

- New: PDF support. Submitted .pdf URLs and Google Drive/Docs links are now auto-detected as a new "pdf" media type, with configurable marker colour and icon.
- New: PDF.js viewer bundled — clicking a PDF marker's thumbnail opens it in the lightbox rendered page-by-page rather than linking out.
- New: PDF Sources admin page (Media Map → PDF Sources). Off-site PDFs require their domain to be approved before in-lightbox preview works; PDFs in the site's own Media Library are always same-origin.
- Note: the media_type database column gains a new "pdf" value. New installs pick this up automatically; upgrading from 1.4.x should reinstall fresh (deactivate, delete, reinstall) rather than upgrade in place.

Version 1.4.5

- New: "My Submissions" panel has a checkbox per entry and an Export JSON button. Selected submissions are downloaded in the same format as the admin export.

Version 1.4.4

- Fix: CSV import no longer corrupts rows containing line breaks in descriptions.
- Fix: Edit button on My Submissions now works correctly.
- Fix: Media embeds extended to Twitch, TikTok, Streamable, Loom, and direct media files.
- Fix: Rejected submission URLs no longer permanently block re-submission.
- Fix: Pending marker colour setting on Marker Styles page now takes effect.
- Fix: Bulk-reject now supports an optional rejection note.
- Fix: Rate-limit log table is now pruned daily.
- Multiple additional bug fixes — see readme.txt for the full list.

Version 1.4.3

- Initial public release: interactive Leaflet map, multimedia submission, admin approval workflow, email notifications, import/export, marker clustering, fullscreen support, configurable rate limiting.

MediaMap Kiosk Plugin

Version 2.3.0 (Current)

- New: PDF points supported (`media_type: "pdf"`). Rendered page-by-page in the kiosk lightbox via `PDF.js`.
- New: Server-side PDF proxy (MediaMap Kiosk → PDF Sources) for off-site PDFs blocked by CORS. Approved-domain PDFs are relayed from the WordPress server's origin; 24-hour disk cache.

Version 1.2.0

- New: Lightbox redesigned to match the standalone Kiosk PWA pixel-for-pixel.
- New: Marker clustering for all pin layers (three size tiers in indigo branding). No per-layer setting to disable clustering in this release.

Version 1.0.3

- Fix: Layer active checkbox in on-screen admin panel failed to render its checked state visually until a browser repaint was triggered. Now set as a live DOM property after row insertion.

Version 1.0.2

- Fix: Rename, toggle, restyle, and delete operations silently failed for layer names containing spaces. Now identifies layers by numeric ID instead of name in the REST URL path.

Version 1.0.1

- Fix: Active checkbox in dark on-screen admin panel rendered with very low contrast on some browsers. Now styled with explicit CSS.

Version 1.0.0

- Initial release.

Kiosk Map PWA

Version 2.4.1 (Current)

- Current stable release. Includes domain allowlist re-validation on boot and every 5 minutes, PIN-gated source changes, IndexedDB directory handle persistence for USB mode, `PDF.js` vendor bundle (LEGACY build), and service worker offline app-shell caching.
- SA (standalone) variant adds the first-time PIN bypass for permanently air-gapped kiosks; see Section 5.2.

11. Appendix

A. Minimum Requirements Summary

Component	Requirement	Value
Media Map Plugin	WordPress version	6.2 or later
Media Map Plugin	PHP version	7.4 or later
Media Map Plugin	Database	MySQL 5.7+ / MariaDB 10.3+
MediaMap Kiosk Plugin	WordPress version	6.0 or later
MediaMap Kiosk Plugin	PHP version	7.4 or later
Strata Backup Splitter	Browser	Any modern browser (Chrome, Edge, Firefox, Safari)
Strata Backup Splitter	Server requirement	None — runs entirely in the browser
Kiosk Map PWA — URL mode	Browser	Any modern browser with HTTPS
Kiosk Map PWA — USB mode	Browser	Chromium-based only (Chrome, Edge)
Kiosk Map PWA	Server requirement	None — static files; Apache needs .htaccess for PDF.js

B. Licencing

Component	Licence
Media Map Plugin v1.5.0	GPLv2 or later
MediaMap Kiosk Plugin v2.3.0	GPLv2 or later
Strata Backup Splitter	GPLv2 or later
Kiosk Map PWA v2.4.1 (NT and SA)	GPLv2 or later
Leaflet 1.9 (vendored)	BSD 2-Clause
Leaflet.markercluster (vendored)	MIT
Material Icons (vendored)	Apache 2.0
PDF.js (vendored)	Apache 2.0
JSZip (CDN, Strata only)	MIT

Full GPLv2 text: <https://www.gnu.org/licenses/gpl-2.0.html>

C. Key Links

Resource	URL
Developer / Author	https://bhoomitechfoundation.org
Media Map Plugin	https://bhoomitechfoundation.org/media-map
MediaMap Kiosk Plugin documentation	https://bhoomitechapps.github.io/documentation/mm-k/
GNU GPLv2 Licence	https://www.gnu.org/licenses/gpl-2.0.html