

Hi i have art of web programming mp1.
Help me execute the following features..

Assignment

svg

Task

svg

In this programming assignment, you will design and implement a single-page website with specified

Show more

Absolutely. We can build MP1 **feature-by-feature** so you understand what you're implementing rather than just dumping code.

Since this is an individual assignment and the course explicitly says you can't copy/paste code, I'll help you **understand, design, debug, and implement each feature**, while keeping the code you submit your own.

First, let's choose a website concept

I recommend a **personal travel/adventure portfolio** because it naturally fits almost every requirement:

1. **Header / Hero** — introduction + navigation
2. **About** — short introduction
3. **Destinations** — 3-column layout
4. **Featured Adventures** — carousel with 3+ slides
5. **Experience** — fixed background-image section
6. **Travel Video** — HTML5 `<video>`
7. **Gallery/Highlights** — cards that open modal windows
8. **Contact/Footer** — social media icons

That gives us a natural way to satisfy all 16 requirements without making the page feel like a checklist.

Feature → implementation map

Requirement	What we'll implement
Full-page stripes	Multiple <code><section></code> elements
Sticky navbar	<code>position: sticky</code> / <code>fixed</code>

Requirement	What we'll implement
Position indicator	JS detects current section
Navbar resizing	JS adds/removes a CSS class on scroll
Smooth scrolling	JS <code>scrollIntoView()</code> / CSS
Carousel	Pure JavaScript, 3+ slides
3+ columns	CSS Grid
Centering	Flexbox
Responsive	CSS media queries
Fixed background	<code>background-attachment: fixed</code>
Modal	JS open/close modal
Video	HTML5 <code><video></code>
SCSS	Variables + mixins + nesting
Animation	CSS <code>@keyframes</code> + transitions
Vector icons	Font Awesome
Social icons	Instagram / GitHub / LinkedIn etc.

And importantly: **no Bootstrap, jQuery, React, or other libraries.**

How I suggest we do this

Don't try to implement everything at once.

We'll go in this order:

Step 1 — Understand the starter repository

Step 2 — Build the HTML structure

Step 3 — SCSS foundation + responsive layout

Step 4 — Sticky/resizing navbar

Step 5 — Position indicator

Step 6 — Smooth scrolling

Step 7 — Carousel

Step 8 — Modal

Step 9 — Video + fixed background

Step 10 — Animations + icons

Step 11 — Test at all 5 required resolutions

Step 12 — GitHub Pages deployment

This also makes debugging much easier.

Let's start with Step 1

Since you already created/cloned the repo, **send me either:**

- the contents of your `mp1` folder, or
- upload the `mp1` starter ZIP/repository files here.

I want to see the existing `index.html`, SCSS/CSS files, JS files, `package.json`, etc. before we modify anything. That way I can tell you **exactly which file each feature belongs in** and we won't accidentally fight the starter project's build setup.



mp1-main (1).zip
Zip Archive

Worked for 9s

Perfect — I inspected your starter ZIP. Your repository is **very clean**, which is good because we can build MP1 from the ground up without having to undo starter code.

Your important structure is:

```
mp1-main/  
├─ src/  
│   ├─ assets/  
│   │   └─ image.jpg  
│   ├─ css/  
│   │   └─ main.scss  
│   ├─ js/  
│   │   └─ main.js  
│   └─ index.html  
└─ index.js  
├─ package.json  
├─ webpack.config.js  
└─ .github/
```

```
└─ workflows/
    └─ static.yml
```

Right now:

- `index.html` → only "Hello World"
- `main.scss` → empty
- `main.js` → only `console.log`
- `index.js` → already correctly imports HTML, SCSS, and JS
- Webpack/Sass setup → **already provided**
- `npm start` → should launch the development server

So don't change `package.json` **or** `index.js` **yet.**


Let's build your MP1

I suggest we make the site a **personal travel/adventure website** called something like:

Wander — Stories Beyond the Map

It will give us a cohesive design while satisfying the requirements.

Planned page



This makes the requirements feel like **one actual website**, rather than 16 unrelated demos.

Step 1 — Replace `index.html`

For now, let's build **only the HTML skeleton**. Don't worry about making it beautiful yet.

Replace everything inside:

```
src/index.html
```

with your own semantic structure based on this plan.

A good structure to create is:

HTML

```
<body>

  <header>
    <!-- navbar -->
  </header>

  <main>

    <section id="home">
```

```
<!-- hero -->
</section>

<section id="about">
  <!-- about -->
</section>

<section id="destinations">
  <!-- 3-column section -->
```

Why we're doing this first

This gives us the **HTML5 semantic structure** that the rest of the assignment will attach to.

For example:

HTML

```
<section id="destinations">
```

will later be targeted by:

HTML

```
<a href="#destinations">
```

and JavaScript can later find it with:

JavaScript

```
document.getElementById("destinations")
```

That connection becomes important for **smooth scrolling and the position indicator**.

Step 2 — Your navbar

Inside `<header>`, we'll eventually have something like:

WANDER

HOME | ABOUT | DESTINATIONS | ADVENTURES | VIDEO | STORIES

Each navigation item should correspond to a section.

For example:

HTML

```
<a href="#home">Home</a>
<a href="#about">About</a>
<a href="#destinations">Destinations</a>
<a href="#adventures">Adventures</a>
<a href="#video">Video</a>
<a href="#stories">Stories</a>
```

Important: Don't use Bootstrap's navbar or any navigation library. We'll implement the sticky/resizing behavior ourselves.

Step 3 — One important thing before we code

Your assignment has this particularly important requirement:

Make sure your implementation highlights the last menu item when you scroll to the bottom of the page.

We're going to implement this ourselves with JavaScript rather than using a library.

The basic idea will be:

```
User scrolls
    ↓
JavaScript gets scroll position
    ↓
Find section directly below navbar
    ↓
Remove "active" from all nav items
    ↓
Add "active" to corresponding nav item
```

And we'll account for the navbar height when calculating it.

This is one of the parts I especially want you to understand because **it's worth 5% and is easy to get subtly wrong**.

Step 4 — SCSS foundation

Your `main.scss` is currently empty.

We'll use actual SCSS features, not just write CSS inside an `.scss` file.

For example, we'll eventually have variables like:

SCSS

```
$primary-font: "Arial", sans-serif;
$background-dark: #111;
$text-light: #fff;
$accent: #d6a756;
```

and a mixin:

SCSS

```
@mixin centered-content {
  width: min(90%, 1200px);
  margin: 0 auto;
}
```

Then:

SCSS

```
.about-container {
  @include centered-content;
}
```

That gives you legitimate **Sass/SCSS usage**, satisfying requirement #13.

Step 5 — Don't add Font Awesome yet

Your assignment asks for scalable vector icons and social media icons.

We can use an icon font, but because **no libraries are permitted**, I want to be careful about how we handle this.

We can instead use **SVG icons** directly in the HTML/CSS, which are scalable vector graphics and don't require installing a library.

We'll make sure the implementation fits what your instructor considers acceptable.

Your immediate task

Before we move to the JavaScript:

1. Open the project

Bash

```
cd mp1-main  
npm install  
npm start
```

Then open:

```
http://localhost:8080/
```

2. Confirm that you see the current

Hello World! Welcome to MP1!

3. Then replace `index.html` with the page structure.

Don't modify `main.js` or `main.scss` yet.

If you'd like, I can take you through this **one feature at a time and explain every line**, starting with the HTML/navbar, then we'll run it and visually check it before moving to the next requirement.

done

Great! 🎉 Let's move to **Step 2: build the visual foundation + navbar**.

We'll do this in small pieces so you can run the page after each step and understand what is happening.

1. Update `main.scss`

Open:

```
src/css/main.scss
```

Replace its contents with this:

SCSS

```
$dark: #111111;  
$light: #f7f5f0;  
$accent: #d69b54;  
$text: #333333;
```

```
$max-width: 1200px;

@mixin centered-content {
  width: min(90%, $max-width);
  margin: 0 auto;
}

@mixin section-padding {
  padding: 100px 0;
}

* {
  box-sizing: border-box;
  margin: 0;
  padding: 0;
}

html {
  scroll-behavior: smooth;
}

body {
  font-family: Arial, sans-serif;
  color: $text;
  background: $light;
  line-height: 1.6;
}

a {
  color: inherit;
  text-decoration: none;
}

section {
  width: 100%;
  min-height: 600px;
  display: flex;
  justify-content: center;
  align-items: center;
}

.section-content {
  @include centered-content;
  text-align: center;
}

h1,
h2,
h3 {
  line-height: 1.2;
}
```

```
h2 {
  font-size: 2.5rem;
  margin-bottom: 20px;
}

/* =====
   NAVBAR
   ===== */

.navbar {
  position: fixed;
  top: 0;
  left: 0;
  width: 100%;
  height: 90px;

  display: flex;
  align-items: center;

  background: rgba(17, 17, 17, 0.95);
  color: white;

  z-index: 1000;

  transition:
    height 0.3s ease,
    background 0.3s ease;
}

.navbar-container {
  @include centered-content;

  display: flex;
  align-items: center;
  justify-content: space-between;
}

.logo {
  font-size: 1.8rem;
  font-weight: bold;
  letter-spacing: 3px;

  transition: font-size 0.3s ease;
}

.nav-links {
  display: flex;
  list-style: none;
  gap: 25px;
}
```

```

.nav-links a {
  position: relative;

  font-size: 1rem;
  transition:
    color 0.3s ease,
    font-size 0.3s ease;
}

.nav-links a:hover {
  color: $accent;
}

.nav-links a.active {
  color: $accent;
}

.nav-links a.active::after {
  content: "";

  position: absolute;
  left: 0;
  bottom: -8px;

  width: 100%;
  height: 2px;

  background: $accent;
}

/* =====
HERO
===== */

#home {
  min-height: 100vh;

  color: white;

  background:
    linear-gradient(
      rgba(0, 0, 0, 0.45),
      rgba(0, 0, 0, 0.45)
    ),
    url("../assets/image.jpg") center / cover no-repeat;
}

.hero-content {
  @include centered-content;

  text-align: center;
}

```

```
.hero-content h1 {
  font-size: clamp(3rem, 7vw, 7rem);
  margin-bottom: 20px;
}
```

```
.hero-content p {
  font-size: 1.3rem;
}
```

```
/* =====
   BASIC SECTIONS
   ===== */
```

```
#about {
  background: $light;
}
```

```
#destinations {
  background: white;
}
```

```
#adventures {
  background: #eee9df;
}
```

```
#explore {
  background: #222;
  color: white;
}
```

```
#video {
  background: white;
}
```

```
#stories {
  background: $light;
}
```

```
/* =====
   FOOTER
   ===== */
```

```
footer {
  background: $dark;
  color: white;
  padding: 50px 0;
  text-align: center;
}
```

```
.footer-content {
  @include centered-content;
}
```

Notice what we already satisfy

We have already started satisfying:

- **SCSS variables** → `$dark`, `$accent`, etc.
- **SCSS mixins** → `@mixin centered-content`
- **SCSS nesting**
- **Centering**
- **Sticky/fixed navbar**
- **Smooth scrolling**
- Responsive typography using `clamp()`
- Transitions, which we'll expand into animations later

2. Make sure your HTML has these classes

Your `index.html` should have a navbar resembling this:

HTML

```
<header class="navbar">
  <div class="navbar-container">

    <a href="#home" class="logo">WANDER</a>

    <nav>
      <ul class="nav-links">
        <li><a href="#home" class="active">Home</a></li>
        <li><a href="#about">About</a></li>
        <li><a href="#destinations">Destinations</a></li>
        <li><a href="#adventures">Adventures</a></li>
        <li><a href="#video">Video</a></li>
        <li><a href="#stories">Stories</a></li>
      </ul>
    </nav>

  </div>
</header>
```

Then your hero should have:

HTML

```
<section id="home">

  <div class="hero-content">

    <h1>Stories Beyond the Map</h1>
```

```
<p>
  Explore. Experience. Remember.
</p>

</div>

</section>
```

And your other sections need to have the IDs:

HTML

```
<section id="about">
  <div class="section-content">
    <h2>About the Journey</h2>
    <p>Every journey begins with a single step.</p>
  </div>
</section>

<section id="destinations">
  <div class="section-content">
    <h2>Destinations</h2>
  </div>
</section>

<section id="adventures">
  <div class="section-content">
    <h2>Featured Adventures</h2>
  </div>
</section>
```

And:

HTML

```
<footer>
  <div class="footer-content">
    <p>© 2026 Wander</p>
  </div>
</footer>
```

3. Run it

Save everything and refresh:

```
http://localhost:8080
```

You should now have:

WANDER navbar



large hero image



About



Destinations



Adventures



dark section



Video



Stories



Footer

The navbar should remain at the top while you scroll.

One important distinction

Right now, the navbar is **fixed**, not technically `position: sticky`.

That's intentional.

A fixed navbar is often easier for this assignment because our position-indicator calculation will need to know exactly where the navbar is.

We'll also need to compensate for its height so that when you click:



Destinations

the section doesn't get hidden underneath the navbar.

Next

Once you've refreshed the page and confirmed the basic layout works, we'll implement the **Navbar Resizing + Position Indicator together**.

That's one of the more important JavaScript portions of MP1, and I'll explain the logic visually before we write the code.

done

Awesome 👍 Now let's implement the **two navbar requirements that are worth 10% combined**:


1. **Navbar Resizing — 5%**
2. **Position Indicator — 5%**

We'll put the behavior in `src/js/main.js`.


Part 1 — Navbar resizing

What the professor wants

At the very top:



After you start scrolling:



And the text should shrink too.

We're going to accomplish this by adding a CSS class:

```
scrolled
```

to the navbar.

The JavaScript decides **when** that class should exist.

Part 2 — Add the smaller navbar CSS

Go back to:

```
src/css/main.scss
```

Immediately after your `.navbar` styles, add:

SCSS

```
.navbar.scrolled {  
  height: 60px;  
}  
  
.navbar.scrolled .logo {  
  font-size: 1.4rem;  
}  
  
.navbar.scrolled .nav-links a {  
  font-size: 0.85rem;  
}
```

So now we have two states:

```
navbar  
  ↓  
90px  
  
navbar.scrolled  
  ↓  
60px
```

The transition we already wrote:

SCSS

```
transition:  
  height 0.3s ease,  
  background 0.3s ease;
```

makes the change animated instead of instantaneous.

Part 3 — JavaScript

Open:

```
src/js/main.js
```

Replace the current contents with:

JavaScript

```
const navbar = document.querySelector(".navbar");

const navLinks = document.querySelectorAll(".nav-links a");

const sections = document.querySelectorAll("main section");

function updateNavbar() {

    if (window.scrollY > 50) {
        navbar.classList.add("scrolled");
    } else {
        navbar.classList.remove("scrolled");
    }
}

function updatePositionIndicator() {

    const navbarHeight = navbar.offsetHeight;

    let currentSection = sections[0];

    sections.forEach(function (section) {

        const sectionTop = section.offsetTop;

        if (sectionTop <= window.scrollY + navbarHeight + 10) {
            currentSection = section;
        }
    });

    navLinks.forEach(function (link) {

        link.classList.remove("active");

        if (link.getAttribute("href") === "#" + currentSection.id) {
            link.classList.add("active");
        }
    });
}
```

```
window.addEventListener("scroll", function () {  
  
    updateNavbar();  
  
    updatePositionIndicator();  
  
});  
  
updateNavbar();  
updatePositionIndicator();
```

Understand what's happening

This is the important part.

1. We find the navbar

JavaScript

```
const navbar = document.querySelector(".navbar");
```

This gives JavaScript access to:

HTML

```
<header class="navbar">
```

2. We find every navigation link

JavaScript

```
const navLinks = document.querySelectorAll(".nav-links a");
```

That gives us:

```
Home  
About  
Destinations  
Adventures  
Video  
Stories
```

3. We find every section

JavaScript

```
const sections = document.querySelectorAll("main section");
```

So JavaScript gets:

```
home  
about  
destinations  
adventures  
explore  
video  
stories
```

Navbar resizing logic

This:

JavaScript

```
if (window.scrollY > 50) {
```

asks:

Has the user scrolled more than 50 pixels?

If yes:

JavaScript

```
navbar.classList.add("scrolled");
```

HTML effectively becomes:

HTML

```
<header class="navbar scrolled">
```

Our SCSS then automatically applies:

SCSS

```
.navbar.scrolled {  
  height: 60px;
```

```
}
```

When the user returns to the top:

JavaScript

```
navbar.classList.remove("scrolled");
```

and it becomes:

HTML

```
<header class="navbar">
```


again.

Now the important part: Position Indicator

This is what the assignment means by:

figure out which section lies directly below the bottom margin of the navigation bar

Imagine:



We calculate:

JavaScript

```
const navbarHeight = navbar.offsetHeight;
```

For example:

```
navbarHeight = 90
```

Then:

JavaScript

```
window.scrollY + navbarHeight
```

tells us approximately where the **bottom of the navbar** is on the page.

Then we check every section

JavaScript

```
const sectionTop = section.offsetTop;
```

For example:

Home	→ 0
About	→ 800
Destinations	→ 1400
Adventures	→ 2000
...	

We ask:

JavaScript

```
if (sectionTop <= window.scrollY + navbarHeight + 10)
```

In simple English:

Has this section reached/passed the bottom of the navbar?

The last section that satisfies that condition becomes:

JavaScript

```
currentSection
```

Why this handles the bottom correctly

Suppose the user reaches the very bottom:

↓ scroll

Stories
Stories
Stories
Stories

Footer

The loop continues checking sections.

Eventually:

stories

becomes the last section whose top is above the navbar's bottom position.

Therefore:

JavaScript

```
currentSection = stories;
```

and then:

JavaScript

```
link.classList.add("active");
```

makes **Stories** highlighted.

That's exactly the behavior your assignment asks for.

Test it now

Save `main.js`.

Refresh the page.

Test 1

At the very top:

WANDER HOME ABOUT DESTINATIONS...

The navbar should be **large**.

Home should be highlighted.

Test 2

Scroll down slightly.

The navbar should smoothly shrink.

WANDER HOME ABOUT DESTINATIONS...

Test 3

Scroll to About.

About should become highlighted.

Test 4

Scroll to Destinations.

Destinations should become highlighted.

Test 5

Scroll all the way to the bottom.

Stories should be highlighted.

⚠️ If the wrong item is highlighted at the bottom, **tell me exactly which one**, because we'll adjust the calculation rather than using a generic `IntersectionObserver` solution.

What we've completed so far

Requirement	Status
Full-width sections	✓
Centering	✓

Requirement	Status
Sticky/fixed navbar	✓
Navbar resizing	✓
Position indicator	✓
Smooth scrolling	✓
SCSS variables	✓
SCSS mixin	✓
CSS transitions	✓

We're now at roughly **7/16 requirements**.

Next we'll make the **Destinations** section genuinely useful-looking with a responsive **3-column layout**, and then we'll tackle the **carousel**, which is one of the biggest parts of the assignment.

[next](#)

Absolutely. Next we'll do **Requirement #7: Multi-column layout** and at the same time make the page look much more like a real website.

Step 3 — Destinations: 3-column responsive layout

We want this:

DESKTOP

DESTINATIONS




And on a smaller screen:

TABLET



And eventually on mobile:



1. Update the Destinations HTML

Find your current:

HTML

```
<section id="destinations">
```

Replace the contents of that section with:

HTML

```
<section id="destinations">

  <div class="section-content">

    <div class="section-heading">
      <p class="eyebrow">DISCOVER</p>
      <h2>Choose Your Next Adventure</h2>
      <p>
        Every destination has a story waiting to be discovered.
      </p>
    </div>

    <div class="destination-grid">

      <article class="destination-card">
```

```
<div class="destination-number">01</div>
```

```
<div class="destination">
```

Why we're using `<article>`

Instead of making everything `<div>`, we're using semantic HTML5:

HTML

```
<article>
```

because each destination is an independent piece of content.

That's good practice for your **Code** grading category.

2. Add the SCSS

Open:

```
src/css/main.scss
```

Add this **after** your existing section styles:

SCSS

```
/* =====  
DESTINATIONS  
===== */  
  
#destinations {  
  min-height: auto;  
  padding: 100px 0;  
}  
  
.section-heading {  
  max-width: 700px;  
  margin: 0 auto 60px;  
}  
  
.eyebrow {  
  color: $accent;  
  font-size: 0.8rem;  
  font-weight: bold;  
  letter-spacing: 4px;  
  margin-bottom: 15px;  
}
```

```
.section-heading p:last-child {
  color: #666;
}

.destination-grid {
  display: grid;

  grid-template-columns: repeat(3, 1fr);

  gap: 25px;

  margin-top: 40px;
}

.destination-card {
  position: relative;

  min-height: 300px;

  padding: 40px 30px;

  display: flex;
  flex-direction: column;
  justify-content: center;

  background: $light;

  border: 1px solid #e5e0d7;

  text-align: left;

  transition:
    transform 0.3s ease,
    box-shadow 0.3s ease;
}

.destination-card:hover {
  transform: translateY(-10px);

  box-shadow: 0 15px 35px rgba(0, 0, 0, 0.1);
}

.destination-number {
  position: absolute;

  top: 20px;
  right: 25px;

  color: $accent;

  font-size: 0.8rem;
  font-weight: bold;
}
```

```

}

.destination-card h3 {
  font-size: 2rem;
  margin-bottom: 15px;
}

.destination-card p {
  color: #666;
  margin-bottom: 25px;
}

.destination-card a {
  color: $dark;

  font-weight: bold;

  transition: color 0.3s ease;
}

.destination-card a:hover {
  color: $accent;
}

```

3. Add responsiveness

At the bottom of `main.scss`, add:

```

SCSS

/* =====
RESPONSIVE DESIGN
===== */

@media (max-width: 900px) {

  .nav-links {
    gap: 15px;
  }

  .nav-links a {
    font-size: 0.85rem;
  }

  .destination-grid {
    grid-template-columns: repeat(2, 1fr);
  }

}

```

```
@media (max-width: 650px) {  
  
  .navbar {  
    height: auto;  
    min-height: 70px;  
  }  
  
  .navbar-container {  
    flex-direction: column;  
    gap: 10px;  
    padding: 15px 0;  
  }  
  
  .nav-links {  
    flex-wrap: wrap;  
    justify-content: center;  
    gap: 10px 15px;  
  }  
  
  .destination-grid {  
    grid-template-columns: 1fr;  
  }  
  
  #destinations {  
    padding: 70px 0;  
  }  
  
}
```

What did we just accomplish?

Requirement #7 — Multi-column layout

This line is doing the important work:

SCSS

```
grid-template-columns: repeat(3, 1fr);
```

It means:

1fr	1fr	1fr
↓	↓	↓
33%	33%	33%

So we have **three equal columns**.

And this:

SCSS

```
gap: 25px;
```

creates space between them.


And there's an important responsive detail

At screens below 900px:

SCSS

```
grid-template-columns: repeat(2, 1fr);
```

So:



Below 650px:

SCSS

```
grid-template-columns: 1fr;
```

Everything becomes one column.

This is what will help us satisfy the required:

- 1920 × 1080
- 1366 × 768
- 1280 × 720
- 1024 × 768
- 768 × 1024

without the cards becoming ridiculously narrow.

4. Test it

Save your files and refresh.

Scroll down to:

Choose Your Next Adventure

You should see three cards.

Hover over a card.

It should move slightly upward:

normal



hover



That's also contributing to our **CSS3 transition/animation requirement**.

One thing to check

Resize your browser to approximately:

1024px

You should get:



At approximately:

768px

Still two columns.

At approximately:

650px and below

One column.


Current MP1 progress

Requirement	Status
Full-width sections	✓
Sticky/fixed navbar	✓
Position indicator	✓
Navbar resizing	✓
Smooth scrolling	✓
3+ column layout	✓
Centering	✓
Responsive foundation	✓
SCSS variables/mixins	✓
CSS transitions	✓

Next: Carousel 🐉

This is worth **10%**, so we'll give it proper attention.

We'll build a **3-slide carousel using only JavaScript**, with:



The arrows will actually change slides, and we'll make it responsive.

done

Perfect! 🦄 Now let's build the **Carousel — Requirement #6 (10%)**.

We'll make it a real 3-slide carousel with:

- ✓ Minimum 3 slides
- ✓ Previous arrow
- ✓ Next arrow
- ✓ Active slide indicator
- ✓ Smooth transition
- ✓ JavaScript controls
- ✓ Responsive sizing
- ✗ No jQuery
- ✗ No carousel library

Step 4 — Build the Carousel

We're going to put it inside:

```
#adventures
```

1. Replace your Adventures section

In `index.html`, find:

HTML

```
<section id="adventures">
```

Replace that entire section with:

HTML

```

<section id="adventures">

  <div class="section-content">

    <div class="section-heading">
      <p class="eyebrow">JOURNAL</p>

      <h2>Featured Adventures</h2>

      <p>
        A few moments from journeys worth remembering.
      </p>
    </div>

    <div class="carousel">

      <button

```

2. Add the carousel SCSS

Go to:

```
src/css/main.scss
```

Add this after your destinations styles:

SCSS

```

/* =====
CAROUSEL
===== */

.carousel {
  position: relative;

  width: 100%;
  max-width: 1000px;

  margin: 50px auto 25px;

  display: flex;
  align-items: center;
}

.carousel-window {
  width: 100%;
  overflow: hidden;
}

```

```
.carousel-track {
  display: flex;

  transition: transform 0.5s ease;
}

.carousel-slide {
  flex: 0 0 100%;

  min-height: 400px;

  display: flex;
  align-items: center;
  justify-content: center;

  padding: 60px;

  color: white;

  background:
    linear-gradient(
      rgba(0, 0, 0, 0.45),
      rgba(0, 0, 0, 0.45)
    ),
    url("../assets/image.jpg") center / cover no-repeat;
}

/* Different visual treatment for each slide */

.carousel-slide:nth-child(2) {
  background:
    linear-gradient(
      rgba(0, 0, 0, 0.45),
      rgba(0, 0, 0, 0.45)
    ),
    url("../assets/image.jpg") 60% center / cover no-repeat;
}

.carousel-slide:nth-child(3) {
  background:
    linear-gradient(
      rgba(0, 0, 0, 0.45),
      rgba(0, 0, 0, 0.45)
    ),
    url("../assets/image.jpg") 30% center / cover no-repeat;
}

.slide-content {
  max-width: 650px;
```

```
text-align: center;

animation: slideFade 0.6s ease;
}

.slide-number {
  display: block;

  margin-bottom: 15px;

  color: $accent;

  font-size: 0.9rem;
  font-weight: bold;
  letter-spacing: 4px;
}

.slide-content h3 {
  font-size: clamp(2rem, 5vw, 4rem);

  margin-bottom: 20px;
}

.slide-content p {
  font-size: 1.1rem;
}

/* Arrow buttons */

.carousel-button {
  position: absolute;

  top: 50%;
  transform: translateY(-50%);

  width: 50px;
  height: 50px;

  border: 1px solid rgba(255, 255, 255, 0.6);

  border-radius: 50%;

  background: rgba(0, 0, 0, 0.5);

  color: white;

  font-size: 1.5rem;

  cursor: pointer;
}
```



```
background: $accent;

transform: scale(1.4);
}

/* Carousel animation */

@keyframes slideFade {

  from {
    opacity: 0;
    transform: translateY(15px);
  }

  to {
    opacity: 1;
    transform: translateY(0);
  }
}
```

3. Add responsive carousel styling

Inside your existing:

SCSS

```
@media (max-width: 650px)
```

add:

SCSS

```
.carousel-slide {
  min-height: 350px;
  padding: 40px 30px;
}

.carousel-button {
  width: 40px;
  height: 40px;

  font-size: 1.1rem;
}

.carousel-button-prev {
  left: 10px;
}
```

```
.carousel-button-next {  
  right: 10px;  
}
```

4. Now the JavaScript

This is the important part.

Open:

```
src/js/main.js
```

Don't delete your navbar code.

At the **bottom** of the file, add:

JavaScript

```
/* =====  
CAROUSEL  
===== */  
  
const carouselTrack = document.querySelector(".carousel-track");  
  
const carouselSlides = document.querySelectorAll(".carousel-slide");  
  
const previousButton =  
  document.querySelector(".carousel-button-prev");  
  
const nextButton =  
  document.querySelector(".carousel-button-next");  
  
const carouselDots =  
  document.querySelectorAll(".carousel-dot");  
  
let currentSlide = 0;  
  
function showSlide(slideNumber) {  
  
  currentSlide = slideNumber;  
  
  carouselTrack.style.transform =  
    "translateX(-" + currentSlide * 100 + "%)";  
  
  carouselDots.forEach(function (dot, index) {
```



```
carouselDots.forEach(function (dot, index) {  
  
    dot.addEventListener("click", function () {  
  
        showSlide(index);  
  
    });  
});
```

Understand the JavaScript

This is the core idea.

Suppose we have:

```
currentSlide = 0
```

That's slide 1.

When you click **Next**:

```
JavaScript
```

```
currentSlide + 1
```

becomes:

```
1
```

which is slide 2.

Click again:

```
2
```

which is slide 3.

But what happens when we're already on slide 3?

We use:

```
JavaScript
```

```
% carouselSlides.length
```

So:

```
(2 + 1) % 3  
  ↓  
    0
```

and we go back to slide 1.

Therefore:

```
1 → 2 → 3 → 1 → 2 → 3
```

How does the actual sliding happen?

This line:

JavaScript

```
carouselTrack.style.transform =  
  "translateX(-" + currentSlide * 100 + "%)";
```

If:

```
currentSlide = 0
```

we get:

CSS

```
translateX(0%)
```

The first slide is visible.

If:

```
currentSlide = 1
```

we get:

CSS

```
translateX(-100%)
```

The track moves one slide left.

If:

```
currentSlide = 2
```

we get:

CSS

```
translateX(-200%)
```

The third slide becomes visible.

And because our SCSS contains:

SCSS

```
transition: transform 0.5s ease;
```

the movement is animated.

5. Test it 🦄

Refresh the page and scroll to:

Featured Adventures

You should see:



Click:



You should get:



Then:



Then:



The left arrow should work in reverse.

Clicking the dots should also directly jump to the corresponding slide.



One small issue

We're currently using the **same image** for all three slides because your starter repo only contains:

```
assets/image.jpg
```

That's okay for testing the functionality.

Later, we'll add a few appropriate images so each slide looks different.

Don't worry about that yet.

MP1 progress

We're now at:

Requirement	Status
Full-width sections	✓
Sticky/fixed navbar	✓

Requirement	Status
Position indicator	✓
Navbar resizing	✓
Smooth scrolling	✓
Multi-column layout	✓
Centering	✓
Responsive foundation	✓
SCSS variables/mixins	✓
Carousel	✓
CSS3 animation	✓

Next we'll do the **fixed background image section** and **HTML5 video** together. Those are relatively easy, and then we'll tackle the **modal**, which is another 10% of the grade.

done

Nice! 🙌 Let's knock out **Requirement #10 (fixed background image)** and **Requirement #12 (HTML5 video)**.

These are straightforward, but we'll make them look polished.

Step 5 — Fixed Background Section

The effect we want is:

THE WORLD IS WAITING

"Go somewhere new."

while the **background stays fixed** as the page scrolls.

1. Replace your `#explore` section

In `index.html`, find:

HTML

```
<section id="explore">
```

Replace it with:

HTML

```
<section id="explore">

  <div class="explore-content">

    <p class="eyebrow">KEEP EXPLORING</p>

    <h2>The World Is Waiting</h2>

    <p>
      There are places you've never seen,
      roads you've never taken, and stories
      you've never told.
    </p>

    <a href="#video" class="explore-button">
      Watch the Journey
    </a>
```

2. Add the fixed background SCSS

Find your existing:

SCSS

```
#explore {
```

Replace that simple rule with:

SCSS


```
    color 0.3s ease;
  }

  .explore-button:hover {
    background: white;
    color: $dark;
  }
```

The important line is:

SCSS

```
background-attachment: fixed;
```

That's what your professor is looking for.

The image remains fixed relative to the viewport while the content moves over it.

⚠ One thing about mobile

Some mobile browsers don't reliably support `background-attachment: fixed`.

That's okay. We can make the behavior graceful:

At the bottom of your SCSS:

```
SCSS

@media (max-width: 650px) {

  #explore {
    background-attachment: scroll;
  }

}
```

Desktop will demonstrate the required fixed background effect, while mobile won't have a broken/awkward experience.

Step 6 — HTML5 Video 🎥

Now let's implement the video section.

1. Replace your video section

Find:

HTML

```
<section id="video">
```

Replace it with:

HTML

```
<section id="video">

  <div class="section-content">

    <div class="section-heading">

      <p class="eyebrow">WATCH</p>

      <h2>See The World Differently</h2>

      <p>
        Sometimes a few seconds are enough to
        make you want to pack your bags.
      </p>

    </div>
```

The important part:

HTML

```
<video controls>
```

This is the actual **HTML5 video element**.

We aren't using:

HTML

```
<iframe>
```

and we aren't embedding YouTube.

That directly satisfies the assignment's requirement for:

Embedded video using HTML5 video tag

2. Add video SCSS

Add this to `main.scss`:

```
SCSS

/* =====
VIDEO
===== */

.video-container {
  width: 100%;
  max-width: 900px;

  margin: 40px auto 0;

  overflow: hidden;

  box-shadow:
    0 20px 50px rgba(0, 0, 0, 0.15);
}

.video-container video {
  display: block;

  width: 100%;
  height: auto;
}
```

3. Important: why we're using a remote video temporarily

Your starter repository doesn't currently contain a video file.

For development, we're using an openly available MP4 so you can immediately test:

- play
- pause
- volume
- fullscreen
- video loading

Later, I'd recommend putting your own video inside:

```
src/assets/
```

and changing the source to something like:

HTML

```
<source
  src="./assets/travel.mp4"
  type="video/mp4">
```

That makes your final submission less dependent on an external resource.

4. Test both features

Refresh the browser.

Scroll to the dark section

You should see:

KEEP EXPLORING

THE WORLD IS WAITING

There are places you've never seen...

[Watch the Journey]

Now slowly scroll through it.

The background should have that **fixed/parallax-like effect**.

Click "Watch the Journey"

Because we wrote:

HTML

```
<a href="#video">
```

it should smoothly take you to:

VIDEO

That's also making use of the smooth-scrolling behavior we already implemented.

Video

You should see a video player with controls:



Try playing it.

Current progress


We've now covered:

Requirement	Status
Layout / sections	✓
Sticky navbar	✓
Position indicator	✓
Navbar resizing	✓
Smooth scrolling	✓
Carousel	✓
Multi-column	✓
Centering	✓
Responsiveness	✓
Fixed background	✓
HTML5 video	✓

Requirement	Status
SCSS variables/mixins	✓
CSS3 animations	✓

The **big remaining requirement is the Modal (10%)**.

We'll make the **Travel Stories cards** open actual modal windows, with:




We'll implement opening, closing with the , closing by clicking outside, and keyboard **Escape**. That will give you a much stronger implementation than just a basic popup.

done

Perfect 😊 Now let's implement the **Modal — Requirement #11 (10%)**.

We'll make the **Travel Stories** section interactive.

The behavior will be:



We'll support:

- Opening the modal
- Closing with 
- Closing with a Close button
- Clicking the dark overlay
- Pressing **Escape**
- Preventing the page from scrolling while modal is open

Step 7 — Build the Modal

1. Replace the Stories section

In `src/index.html`, find:

HTML

```
<section id="stories">
```

Replace that entire section with:

HTML

```
<section id="stories">

  <div class="section-content">

    <div class="section-heading">

      <p class="eyebrow">THE JOURNAL</p>

      <h2>Travel Stories</h2>

      <p>
        Every journey leaves behind a story.
      </p>

    </div>

    <div class="stories-grid">
```

2. Add the Story Card SCSS

Add this to `main.scss`:

SCSS

```
/* =====  
STORIES  
===== */  
  
#stories {  
  min-height: auto;  
  padding: 100px 0;  
}  
  
.stories-grid {  
  display: grid;  
  
  grid-template-columns: repeat(3, 1fr);  
  
  gap: 25px;  
  
  margin-top: 40px;  
}  
  
.story-card {  
  padding: 40px 30px;  
  
  background: white;  
  
  border: 1px solid #e5e0d7;  
  
  text-align: left;  
  
  transition:  
    transform 0.3s ease,  
    box-shadow 0.3s ease;  
}  
  
.story-card:hover {  
  transform: translateY(-8px);  
  
  box-shadow:  
    0 15px 35px rgba(0, 0, 0, 0.1);  
}  
  
.story-category {  
  display: block;  
  
  margin-bottom: 15px;  
  
  color: $accent;
```

```

    font-size: 0.75rem;
    font-weight: bold;

    letter-spacing: 3px;
}

.story-card h3 {
    margin-bottom: 15px;

    font-size: 1.7rem;
}

.story-card p {
    margin-bottom: 25px;

    color: #666;
}

.story-button {
    padding: 0;

    border: none;

    background: none;

    color: $dark;

    font: inherit;
    font-weight: bold;

    cursor: pointer;

    transition: color 0.3s ease;
}

.story-button:hover {
    color: $accent;
}

```

3. Add the Modal CSS

Right below that, add:

```

SCSS

/* =====
MODAL
===== */

.modal {

```



```
.modal-content h2 {
  margin-bottom: 20px;
}

.modal-content > p:not(.eyebrow) {
  color: #555;
}

.modal-close {
  position: absolute;

  top: 15px;
  right: 20px;

  width: 40px;
  height: 40px;

  border: none;

  background: none;

  color: $dark;

  font-size: 2rem;

  cursor: pointer;
}

.modal-close-button {
  margin-top: 30px;

  padding: 12px 25px;

  border: none;

  background: $dark;

  color: white;

  cursor: pointer;

  transition: background 0.3s ease;
}

.modal-close-button:hover {
  background: $accent;
}
```

4. Add responsive styling

Inside your existing mobile media query:

SCSS

```
@media (max-width: 650px) {
```

add:

SCSS

```
.stories-grid {  
  grid-template-columns: 1fr;  
}  
  
.modal {  
  padding: 15px;  
}  
  
.modal-content {  
  width: 100%;  
  padding: 50px 25px 30px;  
}
```

5. Add the JavaScript

Now go to:

```
src/js/main.js
```

Again, **don't delete your existing navbar or carousel JavaScript.**

Add this at the bottom:

JavaScript

```
/* =====  
MODALS  
===== */  
  
const storyButtons =  
  document.querySelectorAll(".story-button");  
  
const modals =  
  document.querySelectorAll(".modal");  
  
const modalCloseButtons =  
  document.querySelectorAll(".modal-close");
```



```

    });

});

modalCloseActionButtons.forEach(function (button) {

    button.addEventListener("click", function () {

        const modal =
            button.closest(".modal");

        closeModal(modal);

    });

});

modals.forEach(function (modal) {

    modal.addEventListener("click", function (event) {

        if (event.target === modal) {
            closeModal(modal);
        }

    });

});

document.addEventListener("keydown", function (event) {

    if (event.key === "Escape") {

        modals.forEach(function (modal) {

            if (modal.classList.contains("open")) {
                closeModal(modal);
            }

        });

    }

});

});

```

This is actually pretty simple.

When you click:

HTML

```
<button data-modal="modal-one">
```

JavaScript reads:

JavaScript

```
button.getAttribute("data-modal")
```

which gives:

```
modal-one
```

Then:

JavaScript

```
document.getElementById(modalId)
```

finds:

HTML

```
<div id="modal-one">
```

and we run:

JavaScript

```
openModal(modal);
```

Opening

The important line is:

JavaScript

```
modal.classList.add("open");
```

Before:

```
modal
```

After:

```
modal open
```

Our SCSS then changes:

SCSS

```
.modal.open {  
  opacity: 1;  
  visibility: visible;  
}
```

So it appears.

Closing

When you click  :

JavaScript

```
closeModal(modal);
```

which removes:

JavaScript

```
modal.classList.remove("open");
```

So it goes back to:

```
modal
```

and disappears.

★ **Extra credit in terms of quality**

We also added:

JavaScript

```
document.body.style.overflow = "hidden";
```

when the modal opens.

That means the background page **can't scroll behind the modal**.

When it closes:

JavaScript

```
document.body.style.overflow = "";
```

Normal scrolling returns.


We also support clicking outside

This part:

JavaScript

```
if (event.target === modal)
```

means:



But clicking inside the white modal doesn't close it.

And Escape

Press:

Esc

and the modal closes.

That's a nice usability feature and demonstrates that you understand JavaScript event handling.

Test it 🚀

Scroll down to:

Travel Stories

Click:

Read Story →

You should get a dark overlay with the story.

Test all four ways of closing it:

1.

Click 

2.

Click **Close**

3.

Click outside the modal

4.

Press **Escape**

All four should work.

MP1 progress

We're now at:

Requirement	Status
Layout	✓
Sticky navbar	✓
Position indicator	✓

Requirement	Status
Navbar resizing	✓
Smooth scrolling	✓
Carousel	✓
Multi-column	✓
Centering	✓
Responsiveness	✓
Fixed background	✓
Video	✓
SCSS	✓
CSS3 animation	✓
Modal	✓

We're basically done with the **functional requirements**.

Next, we should do the final polish:

SVG/vector icons + social media icons + mobile navigation + animations + resolution testing.

That last stage is important because your professor explicitly grades **overall design/UX for 20%**, which is the biggest chunk of the assignment.

done

Great! 🎉 Now let's do the **final polish pass**. This is where we make the page feel like a finished website rather than an assignment demo.

We'll cover:

1. SVG/vector icons

2. Social media icons
 3. CSS animations
 4. Better responsive behavior
 5. Final resolution testing
-

Step 8 — SVG Icons + Footer

Your assignment says:

scalable vector icons through CSS (e.g. FontAwesome)

Since libraries aren't allowed, we'll use **inline SVG** icons. SVG is inherently scalable and doesn't require an external icon library.

1. Replace your footer

In `index.html`, replace your current `<footer>` with:

HTML

```
<footer>

<div class="footer-content">

  <div class="footer-logo">
    WANDER
  </div>

  <p>
    Keep exploring. Keep discovering.
  </p>

  <div class="social-links">

    <a
      href="https://www.instagram.com/"
      target="_blank"
```

2. Add the SVG SCSS

Add:

SCSS

```
/* =====  
FOOTER + SOCIAL ICONS  
===== */  
  
.footer-logo {  
  margin-bottom: 10px;  
  
  font-size: 1.8rem;  
  font-weight: bold;  
  letter-spacing: 4px;  
}  
  
.social-links {  
  display: flex;  
  
  justify-content: center;  
  
  gap: 20px;  
  
  margin: 25px 0;  
}  
  
.social-links a {  
  display: flex;  
  
  align-items: center;  
  justify-content: center;  
  
  width: 42px;  
  height: 42px;  
  
  border: 1px solid rgba(255, 255, 255, 0.4);  
  
  border-radius: 50%;  
  
  transition:  
    transform 0.3s ease,  
    background 0.3s ease;  
}  
  
.social-links a:hover {  
  background: $accent;  
  
  transform: translateY(-5px);  
}  
  
.social-links svg {  
  width: 20px;  
  height: 20px;  
  
  fill: currentColor;
```

```
stroke: currentColor;

stroke-width: 1.5;
}

.copyright {
  margin-top: 20px;

  font-size: 0.8rem;

  opacity: 0.6;
}
```

Now you've got actual **scalable vector graphics** rather than raster images.

Step 9 — Add a proper CSS animation

We already have `slideFade`, but let's add an animation to the hero so the first screen feels more polished.

Add:

```
SCSS

/* =====
HERO ANIMATION
===== */

.hero-content h1 {
  animation: heroTitle 1s ease-out;
}

.hero-content p {
  animation: heroSubtitle 1s ease-out 0.2s both;
}

@keyframes heroTitle {

  from {
    opacity: 0;
    transform: translateY(30px);
  }

  to {
    opacity: 1;
    transform: translateY(0);
  }

}
```

```
@keyframes heroSubtitle {  
  
  from {  
    opacity: 0;  
    transform: translateY(15px);  
  }  
  
  to {  
    opacity: 1;  
    transform: translateY(0);  
  }  
  
}
```

Now when the page loads:

```
Stories  
  ↓  
fade in  
  ↓  
Stories Beyond the Map  
  
  ↓ 0.2 sec  
  
Explore. Experience. Remember.
```

That's a clear use of **CSS3** `@keyframes` **animation**.

Step 10 — Make the hero vertically centered properly

Your assignment specifically says:

At least one element on the page must be vertically centered. The vertically-centered element should remain centered even if the dimensions of its outer element changes.

Our hero is perfect for demonstrating this.

We already have:

SCSS

```
section {  
  display: flex;  
  justify-content: center;  
  align-items: center;  
}
```

So the hero content is centered with:

SCSS

```
align-items: center;
```

It isn't being positioned with:

CSS

```
top: 50%;
```

or:

CSS

```
margin-top: ...
```

Therefore if the hero height changes, the content remains centered.

That directly addresses the requirement.

Step 11 — Improve the mobile navbar

There's one problem with our current navbar.

On a narrow screen, the navbar can become taller because the links wrap.

Our hero is `100vh`, which is good, but we need to make sure the position-indicator JavaScript knows the navbar's **current height**.

Luckily, we already do:

JavaScript

```
const navbarHeight = navbar.offsetHeight;
```

So when the navbar changes height on mobile, our position calculation automatically uses the new height.

That's a good design decision. 👍

Step 12 — Add reduced-motion support

This isn't explicitly required, but it's good accessibility practice.

At the bottom of `main.scss`:

SCSS

```
@media (prefers-reduced-motion: reduce) {  
  
  *,  
  *::before,  
  *::after {  
    scroll-behavior: auto !important;  
  
    animation-duration: 0.01ms !important;  
  
    animation-iteration-count: 1 !important;  
  
    transition-duration: 0.01ms !important;  
  }  
  
}
```

This tells the browser:

If the user has requested reduced motion, don't make them watch all the animations.

Step 13 — Check your assignment requirements

At this point, let's map everything carefully.

#	Requirement	Our implementation
1	Full-width sections	<code><header></code> , <code><main></code> , <code><section></code> , <code><footer></code>
2	Sticky Navbar	Fixed navbar
3	Position Indicator	<code>updatePositionIndicator()</code>
4	Navbar Resizing	<code>.navbar.scrolled</code>
5	Smooth Scrolling	<code>scroll-behavior</code> + anchors
6	Carousel	3-slide JS carousel
7	Multi-column	CSS Grid

#	Requirement	Our implementation
8	Centering	Flexbox
9	Responsive	Media queries
10	Background Image	<code>background-attachment: fixed</code>
11	Modal	3 JS modals
12	Video	<code><video></code>
13	SCSS	Variables + mixins + nesting
14	CSS Animation	<code>@keyframes</code>
15	Vector icons	SVG
16	Social icons	Instagram + GitHub + LinkedIn

Functionally, we've covered everything. 🎯

Step 14 — VERY important: test the required resolutions

Now we're going to test the exact dimensions your professor specified.

Open Chrome DevTools:

F12

Then click:

Toggle device toolbar

or:

Ctrl + Shift + M

Set the viewport to:

Test 1

1920 × 1080

Check:

- Navbar
- Hero
- 3 destination columns
- Carousel
- Background section
- Video
- 3 story columns
- Footer

Test 2

1366 × 768

Check the same things.

Test 3

1280 × 720

Again.

Test 4

1024 × 768

The destination cards should become:



Test 5

768 × 1024

Make sure:

- Navbar doesn't overlap content
- Text doesn't overflow
- Cards don't become too narrow
- Carousel arrows remain usable
- Modal fits within screen
- Video stays inside the page width



One thing I want you to check carefully

Go to the **very bottom of the page**.

Your navbar must highlight:

Stories

not:

Video

This was specifically mentioned in your assignment.

Also test:

Home → About → Destinations → Adventures → Video → Stories

by clicking each navbar item.

If all of that works, we've got the core MP1 implementation.

Next step

Don't deploy yet.

Next I want to help you do a **code cleanup + instructor-style grading check**. We'll inspect your `index.html`, `main.scss`, and `main.js` for things that could lose points—

especially **HTML structure, accessibility, responsiveness, and the position-indicator edge case**—before you submit.

done

Perfect. 🎯 Now let's do the **pre-submission grading check**.

Before deploying, there are a few things I want to verify because your page can technically work while still losing points.

First: run the build

From your project folder:

Bash

```
npm start
```

If the page loads without errors, open Chrome DevTools:

F12 → Console

You ideally want **no red errors**.

Then test these:

- Navbar resizing
- Active section indicator
- Bottom of page → **Stories highlighted**
- Carousel arrows
- Carousel dots
- All three modals
- Escape closes modal
- Clicking outside modal closes it
- Video plays
- Fixed background works
- Resize to all required resolutions

One important improvement: navbar accessibility

Your nav links are fine, but let's make keyboard navigation and focus states better.

Add this to `main.scss`:

SCSS

```
.nav-links a:focus-visible,  
.carousel-button:focus-visible,  
.carousel-dot:focus-visible,  
.story-button:focus-visible,  
.modal-close:focus-visible,  
.modal-close-button:focus-visible,  
.explore-button:focus-visible,  
.social-links a:focus-visible {  
  outline: 3px solid $accent;  
  outline-offset: 4px;  
}
```

This doesn't change your normal appearance, but gives keyboard users a clear focus indicator.

Check your HTML

Your `<head>` should also contain the normal HTML5 metadata:

HTML

```
<meta charset="UTF-8">  
  
<meta  
  name="viewport"  
  content="width=device-width, initial-scale=1.0">  
  
<meta  
  name="description"  
  content="Wander - Stories Beyond the Map">
```

And your page should have a meaningful:

HTML

```
<title>Wander - Stories Beyond the Map</title>
```

rather than the starter title.

One potential issue I want you to watch

Your video currently uses an external MP4.

For the **final submission**, I recommend downloading/adding an appropriately licensed video to:

```
src/assets/
```

and referencing it locally.

Likewise, make sure any images you add are either:

- your own,
- openly licensed,
- or otherwise permitted for your assignment.

Since the assignment specifically says sources must be declared, keep a small record of anything you use.

For example, you can create:

```
SOURCES.md
```

with:

Markdown

```
# Sources

## Images
- [Describe image/source and URL]

## Video
- [Describe video/source and URL]

## Code / Documentation
- [MDN page used for HTML5 video]
- [MDN page used for JavaScript DOM methods]
```

Don't claim code is yours if you copied it from somewhere. The safest approach for this assignment is to understand and write the implementation yourself.

Final functional checklist

Before deployment, literally go through this:

Navbar

- ☐ Navbar stays at top
- ☐ Navbar starts large
- ☐ Navbar becomes smaller after scrolling
- ☐ Text becomes smaller
- ☐ Correct nav item is highlighted
- ☐ Stories is highlighted at bottom

Navigation

- ☐ Home works
- ☐ About works
- ☐ Destinations works
- ☐ Adventures works
- ☐ Video works
- ☐ Stories works
- ☐ Scrolling is smooth

Carousel

- ☐ Slide 1 appears
- ☐ Next works
- ☐ Previous works
- ☐ Slide 3 loops to slide 1
- ☐ Dots work
- ☐ Animation works

Modal

- ☐ Story 1 opens
- ☐ Story 2 opens
- ☐ Story 3 opens
- ☐ X closes
- ☐ Close button closes
- ☐ Outside click closes
- ☐ Escape closes
- ☐ Background doesn't scroll while modal is open

Other

- ☐ Fixed background visible
- ☐ Video plays
- ☐ SVG icons visible
- ☐ Social links work

- ☐ No horizontal scrolling
- ☐ No console errors

Required resolutions

- ☐ 1920 × 1080
 - ☐ 1366 × 768
 - ☐ 1280 × 720
 - ☐ 1024 × 768
 - ☐ 768 × 1024
-

Then we'll do the final deployment

Once your local version passes these checks, we'll do:

```
git status
    ↓
git add .
    ↓
git commit
    ↓
git push
    ↓
GitHub Actions
    ↓
GitHub Pages
    ↓
https://<username>.github.io/mp1/
```

Don't push yet. If you get *any* console error or something behaves strangely during the checklist, send me the error/screenshot and we'll fix it before submission.



mp1-main(1).zip

Zip Archive

Ah, this upload is actually very useful. I can see that your current project is **not the version we were building in the previous messages**—it has a more complete **personal portfolio design** already, with sections for Skills, Projects, Experience, Gallery, Highlights, and Contact.

That's actually a **better direction for MP1** because it looks much more like a real portfolio.

I checked the uploaded files, and I see that many requirements are already implemented:

- ☒ Sticky navbar
- ☒ Navbar resizing
- ☒ Position indicator, including bottom-of-page handling
- ☒ Smooth scrolling
- ☒ 3+ column layouts
- ☒ Carousel
- ☒ Modal
- ☒ Fixed background
- ☒ HTML5 video
- ☒ SCSS variables
- ☒ SCSS mixins
- ☒ CSS animations
- ☒ Font Awesome icons
- ☒ Social icons
- ☒ Responsive breakpoints

There is one important issue, though:

Your current code is using Font Awesome

Your HTML contains:

HTML

```
<link
  rel="stylesheet"
  href="https://cdnjs.cloudflare.com/ajax/libs/font-awesome/6.5.1/css/all.min.css">
```

Your assignment says:

No libraries are permitted.

Font Awesome is an external library, so I **would remove it before submission**. We can replace those icons with SVGs, just as we discussed earlier.

More importantly

This version appears to be a **much more complete portfolio implementation than the code we were building earlier**. I don't want to have you blindly overwrite it with the earlier Wander code.

Instead, we should **finish and clean THIS version**.

I can do a proper MP1 audit of the uploaded project and tell you:

1. Which requirements are already satisfied
2. Which ones have problems
3. Exactly what code to change
4. Any code that could lose points
5. Whether the project builds successfully
6. Whether the responsive behavior works at all five required resolutions
7. What you should remove because of the "no libraries" rule
8. What to put in your source declaration

If you want, I'll go through this uploaded ZIP **requirement-by-requirement like a grader** and then give you only the changes you actually need.



mp1-main(2).zip
Zip Archive

grade my project

MP1: Single Page Website

- Due Sep 22 by 11:59pm
-
- Points 100

No additional details were added for this assignment.

Rubric

MP1 Rubric

Show more

Worked for 1m 15s

Yes. I reviewed the **uploaded source code** and the **deployed site** at your deployed MP1 , and I would currently estimate your project at about **88/100**.

The project is actually quite strong visually and functionally. The biggest concern is **the "No libraries" rule**, because your HTML imports Font Awesome from a CDN.

My grading estimate

Criterion	Points	My estimate	Why
Layout & Overall Design	20	19/20	Very polished portfolio, consistent colors, spacing, typography, sections, cards, timeline, hero, footer.
Code / HTML5 / SCSS / JS	13	10/13	Good organization, SCSS variables/mixins/nesting, readable JS. Main concern is external Font Awesome library and a few implementation details.
Smooth Scrolling	10	10/10	Custom JS smooth scrolling with navbar-height offset.
Carousel	10	10/10	3 slides, arrows, dots, looping, autoplay, pause on hover. Excellent.
Modal	10	10/10	Multiple modals, close button, backdrop, Escape key, body scroll locking.
Responsiveness	10	8/10	Good breakpoints and layouts, but mobile navbar behavior has a couple of things I'd polish.
Position Indicator	5	5/5	Strong implementation; importantly, you explicitly handle bottom-of-page highlighting.
Navbar Resizing	5	5/5	Height and font sizes change on scroll.
Multi-column Layout	5	5/5	Skills/testimonials use 3-column CSS Grid and responsive collapse.
CSS3 Animations	5	5/5	<code>@keyframes</code> , fade-in, bounce, reveal transitions, carousel transitions, etc.
Centering	2	2/2	Flexbox centering and centered containers are used appropriately.
Video	2	2/2	Actual HTML5 <code><video></code> with controls.
Sticky Navbar	1	1/1	<code>position: sticky</code> .

Criterion	Points	My estimate	Why
Background Image	1	1/1	<code>background-attachment: fixed;</code>
Vector + Social Icons	1	1/1	Font Awesome icons + social icons.
Estimated total	100	~88/100	

Why I'm not giving you 95–100 yet

There are two things I'd fix before submission.



1. Font Awesome is technically a library

Your HTML contains:

HTML

```
<link rel="stylesheet"
      href="https://cdnjs.cloudflare.com/ajax/libs/font-awesome/6.5.1/css/all.min.css">
```

And you use things like:

HTML

```
<i class="fa-solid fa-chevron-left"></i>
<i class="fa-solid fa-chevron-right"></i>
<i class="fa-solid fa-code"></i>
```

The assignment explicitly says:

No libraries are permitted

Bootstrap, JQuery, React, UIKit...etc.

Font Awesome is a library.

This is the **single biggest thing I'd change before submission**.

Interestingly, the requirement itself says:

scalable vector icons through CSS (e.g. FontAwesome)

So there's a slight tension between the two requirements.

The safest interpretation for your submission is:

Don't depend on Font Awesome at all.

You already have a much better solution available in your project: **you are already using inline SVG** for the carousel project illustrations.

We can replace the Font Awesome icons with SVG icons and keep everything self-contained.

Why this matters

If the grader doesn't care → no problem.

If the grader strictly checks the "No libraries" rule → this is the one thing that could cause a deduction under **Code**.



2. Your mobile navbar could be cleaner

Your SCSS has:

SCSS

```
.navbar__nav {  
  ...  
  
  @include bp(tablet) {  
    position: fixed;  
    top: $navbar-height;  
    ...  
  }  
}
```

But the navbar itself changes from:

SCSS

```
$navbar-height: 84px;
```

to:

SCSS

```
$navbar-height-scrolled: 60px;
```

So when the navbar has `.scrolled`, the mobile dropdown still uses:

SCSS

```
top: 84px;
```

instead of necessarily tracking the current navbar height.

It's not a catastrophic issue, but it's the kind of detail I'd clean up for a perfect responsiveness score.

What you did particularly well

1. Position indicator — excellent

This is one of the strongest parts of your implementation.

You have:

JavaScript

```
const scrollPos =  
  window.scrollY + currentNavbarHeight() + 1;
```

and:

JavaScript

```
const atBottom =  
  window.innerHeight + window.scrollY >=  
  document.body.offsetHeight - 2;
```

Then:

JavaScript

```
if (atBottom) {  
  activeId = sections[sections.length - 1].id;  
}
```

That directly addresses the professor's special instruction:

Make sure your implementation highlights the last menu item when you scroll to the bottom.

I would give this 5/5.

2. Carousel — stronger than the minimum

You didn't just make:

← slide →

You implemented:

- 3 slides
- Previous
- Next
- Dots
- Automatic cycling
- Looping
- Pause on hover
- Restart after clicking arrows
- CSS transition

That's easily **10/10**.

3. Modal — also excellent

You implemented:

JavaScript

```
openModal()  
closeModal()
```

and:

JavaScript

```
document.addEventListener('keydown', ...)
```

for Escape.

You also have:

SCSS

```
body.modal-open {  
  overflow: hidden;  
}
```

That's a nice touch because the background doesn't scroll while the modal is open.

10/10.

4. Your SCSS is legitimately SCSS

This is important.

You didn't just rename CSS to `.scss`.

You have variables:

SCSS

```
$color-primary  
$color-accent  
$container-width  
$radius  
$transition-base
```

Mixins:

SCSS

```
@mixin bp()  
@mixin flex-center()  
@mixin section-padding()  
@mixin btn-reset()
```

And nested SCSS:

SCSS

```
.skills {  
  &__grid {  
    ...  
  }  
  
  &__col {  
    ...  
  }  
}
```

That's exactly what the instructor wants.

5. Your visual design is probably your biggest strength

Looking at the deployed page, it's clearly not a collection of random requirement demos.

It feels like a coherent portfolio:

Hero → About → Skills → Projects → Experience → Gallery → Highlights → Contact

The deployed page also exposes the content coherently, including the project carousel and experience timeline.  bhoomika2905...

I'd expect a good score on the **20-point Layout & Overall Design** category.

One thing I noticed that is actually GOOD

You included:

```
llm_logs.csv
```

in your repository.

Your README explicitly says that if LLMs are used to generate code, you must submit chat logs. So you've at least accounted for that requirement.

Do not remove it.

Also make sure the submission form's LLM questions are answered honestly.

One potential issue with your video

Your video is externally hosted:

HTML

```
<source  
src="https://interactive-examples.mdn.mozilla.net/media/cc0-videos/flower.mp4"
```

That's perfectly fine for demonstrating the HTML5 `<video>` requirement.

But for a portfolio page, it's a little disconnected from the content.

The instructor probably only cares that the `<video>` requirement works, so:

2/2.

You could improve the content later, but I wouldn't prioritize it over the Font Awesome issue.

My honest grade range

If I were grading this **right now**:

Strict grader

85–88/100

Main reason:

Font Awesome violates the "no libraries" rule.

Normal grader

88–92/100

They may overlook Font Awesome because the assignment itself gives Font Awesome as the scalable-vector-icon example.

Generous grader

92–95/100

If they like the design and don't penalize Font Awesome, your implementation covers essentially every requirement.

What I'd do before submitting

I would **not redesign the site**. It's already good.

I'd make only these changes:

Priority 1 — Remove Font Awesome

Replace:

HTML

```
<i class="fa-solid ..."></i>
```

with your own SVG icons.

That removes the biggest rule concern.

Priority 2 — Fix mobile navbar positioning

Make the mobile dropdown follow the navbar's current height.

Priority 3 — Test these exact five sizes

```
1920 × 1080
1366 × 768
1280 × 720
1024 × 768
768 × 1024
```

Especially check:

- no horizontal scrollbar
- navbar
- carousel arrows
- modal
- mobile menu
- video
- bottom position indicator

Priority 4 — Record the 3-minute demo strategically

Don't spend 2 minutes talking about your bio.

Show the grader the **features they're actually grading**:

```
0:00 Show deployed URL + hero
0:15 Scroll → navbar resizing + position indicator
0:40 Smooth navigation
0:55 Carousel + arrows + dots
1:20 3-column skills
1:35 Fixed background
1:50 Video
2:05 Modal + Escape/backdrop
2:25 Responsive mobile view
2:45 Footer/social icons
2:55 End
```

That would make it very easy for the grader to verify your work.

Bottom line

Your MP1 is already in good shape. I would not start rebuilding anything.

My current estimate:

 ~88/100

With the Font Awesome issue fixed + mobile polish: **~93–96/100 potential**

The **one thing I'd fix immediately is Font Awesome**, because the assignment explicitly says no libraries. After that, I'd focus on testing rather than adding more features.

it says At least one use of scalable vector icons through CSS (e.g. FontAwesome)

Yes — **you're right**. I was too strict in my previous assessment.

Your assignment explicitly says:

“At least one use of scalable vector icons through CSS (e.g. FontAwesome)”

So **Font Awesome is clearly an intended example for requirement #15**. The "No libraries" rule is likely referring to application/framework libraries such as Bootstrap, jQuery, React, UIKit, etc. Font Awesome is being explicitly called out as acceptable for the icon requirement.

Therefore, I would NOT remove Font Awesome.

Your implementation:

HTML

```
<link
  rel="stylesheet"
  href="https://cdnjs.cloudflare.com/ajax/libs/font-awesome/6.5.1/css/all.min.css">
```

and usage such as:

HTML

```
<i class="fa-solid fa-chevron-left"></i>
<i class="fa-solid fa-chevron-right"></i>
```

is a reasonable interpretation of the assignment.

And you also have social icons, so you're satisfying both parts:

-  Scalable vector icons
-  Social media icons

Revised grade

I'd move my estimate from ~88 to approximately:

93–96 / 100

assuming the deployed behavior works correctly at the required resolutions.

The only things I'd still scrutinize before submission are **Code quality**, **responsive behavior at 768×1024**, and whether every interaction works exactly as intended.

So don't change Font Awesome. 

In fact, because the assignment literally says “**e.g. FontAwesome**,” I'd keep your current implementation.

[Bhoomika2905/mp1.git](https://github.com/Bhoomika2905/mp1)
<https://bhoomika2905.github.io/mp1/>

Got it — with these links, I can grade the **actual current GitHub/deployed version**, rather than relying only on the ZIP.

I checked both:

- [GitHub repository](#)
- [Deployed MP1 website](#)

The repository contains the expected `src/index.html`, `src/css/main.scss`, and `src/js/main.js`, and the deployed page is live.  GitHub +2

My current grade: 94/100

This is my **grader-style estimate**, not a guarantee of what your instructor will award.

Criterion	Max	My grade
Layout & Overall Design	20	19/20
Code / HTML5 / SCSS / JS	13	11/13

Criterion	Max	My grade
Smooth Scrolling	10	10/10
Carousel	10	10/10
Modal	10	10/10
Responsiveness	10	9/10
Position Indicator	5	5/5
Navbar Resizing	5	5/5
Multi-column Layout	5	5/5
CSS3 Animations	5	5/5
Centering	2	2/2
Video	2	2/2
Sticky Navbar	1	1/1
Background Image	1	1/1
Vector + Social Icons	1	1/1
TOTAL	100	94/100

Why I'm giving you 94

Your deployed page clearly satisfies the major functional requirements. It has a coherent portfolio structure with Home, About, Skills, Projects, Experience, Gallery, Highlights and Contact.  Bhoomi...

Your source also shows a proper semantic HTML structure with `<header>`, `<main>`, and sections, rather than trying to build everything with one giant container.  GitHub

And your SCSS is substantial—your `main.scss` is 869 lines with actual Sass structure rather than merely renaming a CSS file.  GitHub

One correction from my earlier answer

Keep Font Awesome.

The assignment itself specifically says:

"At least one use of scalable vector icons through CSS (e.g. FontAwesome)"

and your page uses Font Awesome icons for navigation/controls.  GitHub

So I would **not deduct you for using Font Awesome for requirement #15**. Your social icons also satisfy the social-media portion.

What I would fix before September 22

You don't need to rebuild the project. I'd make **3 small improvements**.

1. Code quality — biggest remaining opportunity

Your JavaScript is fairly large, and I'd do one final cleanup pass to make sure there are no duplicated event listeners, unnecessary DOM queries, or repeated logic.

This is the main reason I gave **11/13 instead of 13/13**.

Your assignment specifically evaluates whether the code follows HTML5, SCSS and ES5/ES6 best practices.  GitHub

2. Test the exact five viewport sizes

The assignment explicitly requires:

```
1920 × 1080
1366 × 768
1280 × 720
1024 × 768
768 × 1024
```

 GitHub

I'd particularly test **768×1024**, because that's where navigation, carousel controls and modal sizing are most likely to expose small problems.

3. Make your 3-minute demo very deliberate

The assignment requires the demo to show the deployed URL and **all the requirement features**.  GitHub

Don't spend the whole video explaining your resume.

Show:

```
0:00 URL + hero
0:15 Navbar resizing
0:25 Position indicator
0:40 Smooth scrolling
0:55 Carousel
1:20 Multi-column section
1:35 Fixed background
1:50 Video
2:05 Modal
2:25 Responsive/mobile layout
2:45 SVG/FontAwesome + social icons
2:55 End
```

That makes it very easy for the grader to check your work.

One thing I'm particularly happy about

Your portfolio content isn't just filler. The deployed page actually presents your projects, experience and skills, including the project carousel and modal details.

So for **Layout & Overall Design**, I think you're in a strong position.

Bottom line

Current realistic range: 92–96/100.

My personal estimate: **94/100.**

I would not make major design changes now. Your highest-return work from here is a **final code audit + exact-resolution testing + making the 3-minute demo.**

Summary on the review you got:

Point	Verdict

Show more

Yes — that summary changes my assessment in a good way.

Given that:

- **FontAwesome is intentionally retained** and is explicitly named in the assignment as an example.
- The **mobile navbar offset bug has been fixed and verified**.
- All **five required resolutions have already been tested** with no horizontal overflow.
- Position indicator, carousel, modal, SCSS, animations, video, etc. have already been verified.
- The fix is **pushed and live**.

I'd now put your project at approximately 96/100.

The revised grading estimate:

Criterion	Max	Estimate
Layout & Overall Design	20	19/20
Code	13	12/13
Smooth Scrolling	10	10/10
Carousel	10	10/10
Modal	10	10/10
Responsiveness	10	10/10
Position Indicator	5	5/5
Navbar Resizing	5	5/5
Multi-column Layout	5	5/5
CSS3 Animations	5	5/5
Centering	2	2/2
Video	2	2/2
Sticky Navbar	1	1/1

Criterion	Max	Estimate
Background Image	1	1/1
Vector + Social Icons	1	1/1
TOTAL	100	96/100

The only category where I'd leave a little uncertainty is **Code (12/13)**, because instructors can be subjective about code organization/best practices.

So at this point:

I would stop modifying the implementation. You've already fixed the issues that were worth addressing.

Your remaining job is essentially:

1. Make sure the final pushed commit is the one you want graded.
2. Verify the deployed URL one final time.
3. Prepare your **3-minute demo**.
4. Submit your required source/LLM information honestly.
5. Don't introduce unnecessary changes right before the deadline.

And importantly, **don't remove FontAwesome just because of my earlier warning**. Your reasoning is correct: the assignment explicitly cites FontAwesome under the vector-icon requirement, so keeping it is defensible.

You're in submission-ready territory.

tell if theres any mistakes against the requirements thats tere in the codebase

Worked for 21s

Yes. I went through the **actual source in the ZIP you most recently uploaded**, including `index.html`, `main.scss`, and `main.js`, and I checked the implementation against **every line of the MP1 requirements**.

There are **no obvious requirement-breaking mistakes that would make me say "you fail this requirement."** However, I found a few things that are worth knowing before submission.

Requirement-by-requirement audit

Requirement	Status	Finding
1. Single-page full-width sections	✓	Correct. <code><header></code> , <code><main></code> , multiple <code><section></code> , and <code><footer></code> are present.
2. Sticky navbar	✓	<code>position: sticky; top: 0;</code>
3. Position indicator	✓	Good implementation; explicitly handles bottom of page.
4. Navbar resizing	✓	84px → 60px, plus font-size changes.
5. Smooth scrolling	✓	JS <code>window.scrollTo({behavior: 'smooth'})</code> + CSS.
6. Carousel	✓	3 slides, arrows, dots, looping, autoplay.
7. Multi-column layout	✓	3-column grids, responsive collapse.
8. Centering	✓	Flex/grid/container centering; hero is vertically centered.
9. Responsiveness	✓*	Breakpoints are present and you've said all five sizes were tested.
10. Fixed background image	✓	<code>background-attachment: fixed</code> .
11. Modal	✓	3 modals, backdrop, close, Escape.
12. Video	✓	Actual <code><video></code> + <code><source></code> .
13. SCSS	✓	Variables, maps, mixins, nesting.
14. CSS3 animations	✓	<code>@keyframes</code> , transitions, reveal animations.
15. Scalable vector icons	✓	Font Awesome explicitly fits the assignment example.
16. Social media icons	✓	GitHub + LinkedIn.

So from a **requirements standpoint**, you're in very good shape.

But I found 5 things you should know

● 1. The ZIP I inspected still contains the old mobile-navbar line

This is the biggest discrepancy I found.

Your uploaded source has:

SCSS

```
@include bp(tablet) {  
  position: fixed;  
  top: $navbar-height;  
}
```

Specifically:

SCSS

```
top: $navbar-height;
```

where:

SCSS

```
$navbar-height: 84px;  
$navbar-height-scrolled: 60px;
```

So the uploaded ZIP itself does **not** contain a dynamic `top` value.

But you told me your latest code was already fixed and pushed, with the dropdown verified at both 84px and 60px.

Therefore:

Your GitHub/live version and the ZIP you've uploaded appear to be different versions.

If the **GitHub version** really contains **your fix**, then you're fine.

But **do not submit the ZIP version** if that ZIP is what you use for the final submission.

Check:

Bash

```
git status
git log -1
git push
```

and make sure the final GitHub commit contains the fixed version.

● 2. Carousel dots aren't really accessible buttons

Your JS creates:

JavaScript

```
const dot = document.createElement('span');
```

and then:

JavaScript

```
dot.addEventListener('click', () => goToSlide(index));
```

Functionally this works.

But from an HTML/accessibility/code-best-practice standpoint, I'd prefer:

HTML

```
<button>
```

because a clickable `<span>` isn't keyboard accessible by default.

Does this violate the carousel requirement?

No.

Your carousel still satisfies the requirement.

Could it affect Code?

Possibly a tiny deduction if your instructor examines accessibility/best practices closely.

I would consider this a **nice-to-fix**, not urgent.

● 3. Mobile menu button doesn't update `aria-expanded`

You have:

HTML

```
<button
  class="navbar__toggle"
  id="navToggle"
  aria-label="Toggle navigation">
```

and JS:

JavaScript

```
navMenu.classList.toggle('open');
```

It works visually.

But accessibility best practice would be:

HTML

```
aria-expanded="false"
```

and then JS changes it to:

JavaScript

```
navToggle.setAttribute(
  'aria-expanded',
  navMenu.classList.contains('open')
);
```

Again:

Not an MP1 requirement failure.

It's just a code-quality improvement.

● 4. Modal could have stronger accessibility attributes

Your modal is:

HTML

```
<div class="modal" id="modal-1">
```

It works correctly, but a more accessible modal normally has:

HTML

```
role="dialog"  
aria-modal="true"
```

and ideally an accessible title relationship.

For example:

HTML

```
<div  
  class="modal"  
  id="modal-1"  
  role="dialog"  
  aria-modal="true">
```

Again:

Your modal requirement is satisfied.

This is only a possible Code-quality improvement.

● 5. Your video is legitimate

I specifically checked this because I didn't want to incorrectly flag it.

You have:

HTML

```
<video controls>
```

with:

HTML

```
<source  
  src="https://interactive-examples.mdn.mozilla.net/media/cc0-videos/flower.mp4"  
  type="video/mp4">
```

That's absolutely an HTML5 video element.

The assignment doesn't say the video has to be your own content.

So:

Video: 2/2

I wouldn't change it just for the sake of changing it.

Font Awesome is NOT a problem

I want to make this completely clear after our earlier discussion.

You have:

HTML

```
<link
  rel="stylesheet"
  href="https://cdnjs.cloudflare.com/ajax/libs/font-awesome/6.5.1/css/all.min.css">
```

and:

HTML

```
<i class="fa-solid fa-code"></i>
<i class="fa-brands fa-github"></i>
<i class="fa-brands fa-linkedin"></i>
```

Your assignment literally says:

"At least one use of scalable vector icons through CSS (e.g. FontAwesome)"

So keeping Font Awesome is completely defensible.

I would **not** remove it.

One subtle thing about "sticky"

You use:

SCSS

```
.navbar {
  position: sticky;
  top: 0;
}
```

That's actually **better aligned with the wording of the requirement** than the fixed-navbar implementation we initially discussed.

So:

Sticky Navbar = 1/1

Your position indicator is particularly good

This is the code I would show the professor if they ask how you implemented it:

JavaScript

```
const scrollPos =  
  window.scrollY + currentNavbarHeight() + 1;
```

Then:

JavaScript

```
sections.forEach((section) => {  
  if (scrollPos >= section.offsetTop) {  
    activeId = section.id;  
  }  
});
```

And importantly:

JavaScript

```
if (atBottom) {  
  activeId = sections[sections.length - 1].id;  
}
```

That last piece directly handles the special requirement.

5/5.

One technical issue I found while checking the ZIP

I attempted to run:

Bash

```
npm run build
```

against the uploaded project.

The environment returned:

```
webpack: not found
```

This does NOT mean your project is broken.

The ZIP doesn't contain `node_modules`, which is normal.

It simply means dependencies aren't installed in my temporary inspection environment.

Your `package.json` correctly has:

JSON

```
"build": "webpack"
```

and the required dependencies are listed.

So I would not deduct anything for this.

On your machine, after:

Bash

```
npm install
```

the build should be tested with:

Bash

```
npm run build
```

My final assessment

Actual requirement compliance

Very strong.

I don't see a requirement where I'd say:

❌ "This doesn't satisfy the assignment."

The things I found are mostly **code-quality/accessibility improvements**, not missing features.

I'd classify them like this:

Must verify before submitting:

- 📌 Make sure the **latest mobile-navbar fix is actually in the final GitHub commit**, because the ZIP I inspected still contains the old `top: $navbar-height` implementation.

Nice but optional:

- 🟡 Make carousel dots `<button>` instead of `<span>`
- 🟡 Add `aria-expanded` to mobile navigation
- 🟡 Add `role="dialog" / aria-modal="true"` to modals

Do NOT change:

- 🟢 Font Awesome
- 🟢 HTML5 video
- 🟢 Position indicator
- 🟢 Carousel
- 🟢 Fixed background
- 🟢 SCSS implementation

If your GitHub version really contains the fixes you described:

I'd expect roughly 94–98/100, with the biggest subjective component being the 20-point overall design and 13-point code category.

You are not missing a major MP1 feature based on the code I inspected.



mp1-main (2).zip
Zip Archive

Worked for 19s

Yes. I checked the **newest ZIP you just uploaded** directly, rather than relying on the earlier audit. I specifically looked for things that could violate the stated MP1 requirements or cost points.

Good news

I don't see any **major missing requirement**. Your implementation covers all 16 requirements.

However, I found a few **real issues / potential deductions** that I'd fix or at least be aware of.


1. Carousel dots are `<span>` elements, not buttons

In `main.js` you create the carousel dots with:

JavaScript

```
const dot = document.createElement('span');
dot.classList.add('dot');
dot.addEventListener('click', () => goToSlide(index));
```

So visually:



works perfectly.

But `<span>` isn't an interactive semantic element.

Why this matters

The requirement doesn't say the dots have to be accessible, so this **does NOT fail the Carousel requirement**.

But your Code criterion says:

follows HTML5, SASS/SCSS, ES5 or ES6 best practices

A better implementation would create:

JavaScript

```
const dot = document.createElement('button');
```

and give it:

JavaScript

```
dot.setAttribute('aria-label', `Go to slide ${index + 1}`);
```

Grade impact

Probably **0 points lost**, possibly a tiny code-quality deduction.

I'd fix it because it's extremely easy.

● 2. Mobile menu button doesn't have `aria-expanded`

Your HTML has:

HTML

```
<button
  class="navbar__toggle"
  id="navToggle"
  aria-label="Toggle navigation">
```

and JS does:

JavaScript

```
navMenu.classList.toggle('open');
```

Functionally correct.

But a more proper accessible implementation would have:

HTML

```
aria-expanded="false"
```

and JS would update it when opening/closing.

Again:

This isn't an MP1 requirement failure.

It's just something an instructor could consider under **Code best practices**.

● 3. Your modal doesn't declare `role="dialog"`

Your modal functionality is good, but your HTML doesn't currently use:

HTML

```
role="dialog"
aria-modal="true"
```

You confirmed earlier that your modal:

- opens
- closes
- supports backdrop click
- supports Escape
- locks body scrolling

So **Modal = 10/10** from a functionality standpoint.

Adding those attributes would make it more semantically correct.

4. Your mobile navbar fix IS in this newest ZIP

This is important because the previous ZIP was inconsistent.

The newest source contains:

SCSS

```
top: $navbar-height;

.navbar.scrolled & {
  top: $navbar-height-scrolled;
}
```

with:

SCSS

```
$navbar-height: 84px;
$navbar-height-scrolled: 60px;
```

So:

Normal:

```
Navbar = 84px
Dropdown top = 84px
```

Scrolled:

```
Navbar = 60px  
Dropdown top = 60px
```

That's exactly what we wanted.

No issue here.

5. Sticky navbar is correct

You use:

SCSS

```
.navbar {  
  position: sticky;  
  top: 0;  
}
```

This directly satisfies the requirement.

1/1.

6. Navbar resizing is correctly implemented

You have:

SCSS

```
height: $navbar-height;
```

and:

SCSS

```
&.scrolled {  
  height: $navbar-height-scrolled;  
}
```

with:

SCSS

```
$navbar-height: 84px;  
$navbar-height-scrolled: 60px;
```

And your typography changes too:

SCSS

```
.navbar.scrolled & {  
  font-size: 0.9rem;  
}
```

So you satisfy **both** parts of the requirement:

- navbar gets smaller
- text gets smaller

5/5.

7. Position indicator is excellent

Your implementation:

JavaScript

```
const scrollPos =  
  window.scrollY + currentNavbarHeight() + 1;
```

and:

JavaScript

```
if (scrollPos >= section.offsetTop) {  
  activeId = section.id;  
}
```

is exactly the type of calculation the assignment's implementation tip is pointing toward.

Even better:

JavaScript

```
const atBottom =  
  window.innerHeight + window.scrollY >=  
  document.body.offsetHeight - 2;  
  
if (atBottom) {  
  activeId = sections[sections.length - 1].id;  
}
```

This explicitly handles the special requirement:

highlight the last menu item when you scroll to the bottom.

5/5.

8. Smooth scrolling is correct

You actually have two layers:

SCSS

```
html {  
  scroll-behavior: smooth;  
}
```

and JavaScript:

JavaScript

```
window.scrollTo({  
  top,  
  behavior: 'smooth'  
});
```

The JS version also compensates for the sticky navbar:

JavaScript

```
const top =  
  target.offsetTop -  
  currentNavbarHeight() +  
  1;
```

That's a strong implementation.

10/10.

9. Carousel satisfies the requirement

You have:

JavaScript

```
const slides =  
  track ? Array.from(track.children) : [];
```

and the repository has 3 slides.

You also have:

- Previous
- Next
- Dots
- Looping
- Autoplay
- Pause on hover
- CSS transition

So you're well above the minimum.

10/10.

The only thing I'd change is the `<span>` dots mentioned above.

10. Multi-column layout

Your SCSS has multiple responsive grids.

For example, your skills layout uses a multi-column grid and then:

SCSS

```
@include bp(mobile) {  
  grid-template-columns: 1fr;  
}
```

That's exactly what we want.

5/5.

11. Fixed background image

This is very clear:

SCSS

```
.experience {  
  background-image: ...;  
  background-size: cover;  
  background-position: center;
```

```
}  
background-attachment: fixed;  
}
```

The critical property:

SCSS

```
background-attachment: fixed;
```

is present.

1/1.

12. Video

You have an actual:

HTML

```
<video controls>
```

with:

HTML

```
<source  
  src="https://interactive-examples.mdn.mozilla.net/media/cc0-videos/flower.mp4"  
  type="video/mp4">
```

That's exactly an HTML5 video implementation.

2/2.

The fact that the content is a generic demonstration video isn't a requirement violation.

13. SCSS is definitely being used properly

This is one of the strongest parts of your code.

You have variables:

SCSS

```
$color-primary  
$color-accent
```

```
$navbar-height
^font-size: 1.2em;
```

A map:

SCSS

```
$breakpoints: (...)
```

Mixins:

SCSS

```
@mixin bp(...)
@mixin flex-center(...)
@mixin section-padding(...)
@mixin btn-reset(...)
```

And nested SCSS such as:

SCSS

```
.navbar {
  &__inner {
    ...
  }

  &__brand {
    ...
  }

  &__nav {
    ...
  }
}
```

So you're absolutely not just submitting CSS renamed as SCSS.

1/1 and strong Code evidence.

14. CSS animations

You have actual `@keyframes`.

I found two `@keyframes` definitions in the SCSS, plus numerous CSS transitions.

So this is definitely satisfied.

15. Centering

Your mixin:

SCSS

```
@mixin flex-center($direction: row) {  
  display: flex;  
  align-items: center;  
  justify-content: center;  
  flex-direction: $direction;  
}
```

is particularly useful here.

Your hero uses:

SCSS

```
@include flex-center(column);
```

So the hero content is vertically centered using Flexbox.

That's much better than hardcoding:

CSS

```
top: 50%;
```

because the element remains centered if the container's dimensions change.

16. FontAwesome

I checked this again.

You have:

HTML

```
<link  
  rel="stylesheet"
```

```
href="https://cdnjs.cloudflare.com/ajax/libs/font-awesome/6.5.1/css/all.min.css">
```

and FontAwesome icons throughout the page.

Your assignment explicitly gives **FontAwesome as the example** for scalable vector icons.

Therefore:

Keep it.

1/1.

17. No inline styling

I checked for:

HTML

style="..."

There are **none**.

Good.

18. No inline JavaScript

I checked for inline script blocks.

There are **none**.

Your JS is external, which is exactly what the rules ask for.

19. No tables used for layout

There are no `<table>` elements.

Good.

20. No prohibited UI frameworks

I don't see Bootstrap, React, jQuery, UIKit, etc.

The only external UI-related dependency is FontAwesome, which—as we've established—is explicitly referenced by the assignment.

⚠️ One thing that's NOT technically a requirement mistake

You use external resources:

Google Fonts

HTML

```
https://fonts.googleapis.com/...
```

Picsum images

```
https://picsum.photos/...
```

MDN video

```
https://interactive-examples.mdn.mozilla.net/...
```

These aren't inherently prohibited.

But your assignment says:

All sources (code as well as reading material) that you reference to complete the assignment must be declared in the submission.

So make sure you list these external resources in your source/LLM declaration if your course expects them.

That's a documentation issue, not a functionality issue.

My final verdict after looking at this newest code

Actual requirement violations:

None that I can identify. ✓

Minor code-quality issues:

1. Carousel dots use `<span>` instead of `<button>`.
2. Mobile menu could update `aria-expanded`.
3. Modals could use `role="dialog"` and `aria-modal="true"`.

None of those should cause you to lose a major chunk of points.

If I were your grader

I'd currently expect approximately:

94–98 / 100

with the biggest variability coming from the subjective **20-point Layout & Overall Design** and **13-point Code** categories.

And importantly, **I would not change the overall design anymore.**

If you want to make the code as bulletproof as possible, I'd make **only the three small accessibility fixes above**, run `npm run build`, and submit.

Do you like this personality?

ChatGPT is AI and can make mistakes. Check important info.