

## Experiment 01

### Aim:

- Load data in Pandas.
- Description of the dataset.
- Drop columns that aren't useful.
- Drop rows with maximum missing values.
- Take care of missing data.
- Create dummy variables.
- Find out outliers (manually)
- standardization and normalization of columns

### Data preprocessing

Data preprocessing involves transforming raw data into a structured and meaningful format, making it suitable for analysis. It is a crucial step in data mining, as raw data often contains inconsistencies, missing values, or noise. Ensuring data quality is essential before applying machine learning or data mining algorithms to achieve accurate and reliable results.

### **Why is Data Preprocessing Important?**

Data preprocessing is essential for ensuring the quality and reliability of data before analysis. It helps improve the accuracy and efficiency of machine learning and data mining processes. The key aspects of data quality include:

- **Accuracy:** Ensuring the data is correct and free from errors.
- **Completeness:** Checking for missing or unrecorded data.
- **Consistency:** Verifying that data remains uniform across different sources.
- **Timeliness:** Ensuring the data is up-to-date and relevant.
- **Believability:** Assessing whether the data is reliable and trustworthy.
- **Interpretability:** Making sure the data is clear and easy to understand.

Dataset: [Crop Yield Dataset](#)

## 1) Loading Data in Pandas

```
import pandas as pd

file_path = "/content/crop_yield.csv"
df = pd.read_csv(file_path)

print("Dataset Preview:")
print(df.head().to_string(index=False))
```

Dataset Preview:

Crop	Crop_Year	Season	State	Area	Production	Annual_Rainfall	Fertilizer	Pesticide	Yield
Areca nut	1997	Whole Year	Assam	73814.0	56708	2051.4	7024878.38	22882.34	0.796087
Arhar/Tur	1997	Kharif	Assam	6637.0	4685	2051.4	631643.29	2057.47	0.710435
Castor seed	1997	Kharif	Assam	796.0	22	2051.4	75755.32	246.76	0.238333
Coconut	1997	Whole Year	Assam	19656.0	126905000	2051.4	1870661.52	6093.36	5238.051739
cotton(lint)	1997	Kharif	Assam	1739.0	794	2051.4	165500.63	539.09	0.420909

## 2) Description of the dataset.

Attribute/Column Name	Data Type	Description
Crop	String	Name of the crop (e.g., Arecanut, Arhar/Tur, Coconut, etc.).
Crop_Year	Float	The year in which the crop was grown.
Season	String	The season in which the crop was cultivated (e.g., Kharif, Whole Year).
State	String	The state in which the crop was grown.
Area	Float	The total area (in hectares) used for cultivation.
Production	Float	The total production of the crop (in metric tons).
Annual_Rainfall	Float	The annual rainfall (in mm) received in the region.
Fertilizer	Float	The amount of fertilizer (in kg) used.
Pesticide	Float	The amount of pesticide (in kg) used.
Yield	Float	The yield (production per unit area) of the crop.

`df.info()`: Provides an overview of the dataset, including:

- Number of rows and columns.
- Data types of each column (e.g., int, float, object).
- Number of non-null (non-missing) values in each column.

`df.describe()`: Generates summary statistics for numeric columns, such as:

- count: Number of non-missing values.
- mean: Average value.
- std: Standard deviation.

- min, 25%, 50% (median), 75%, and max: Percentile values.

```
import pandas as pd

file_path = "/content/crop_yield.csv"
df = pd.read_csv(file_path)

print(df.info())
print(df.describe().to_string(index=False))
```

```
<class 'pandas.core.frame.DataFrame'>
RangeIndex: 19689 entries, 0 to 19688
Data columns (total 10 columns):
#   Column                Non-Null Count  Dtype
---  ---
0   Crop                   19689 non-null object
1   Crop_Year              19689 non-null int64
2   Season                 19689 non-null object
3   State                  19689 non-null object
4   Area                   19689 non-null float64
5   Production             19689 non-null int64
6   Annual_Rainfall        19689 non-null float64
7   Fertilizer             19689 non-null float64
8   Pesticide              19689 non-null float64
9   Yield                  19689 non-null float64
dtypes: float64(5), int64(2), object(3)
memory usage: 1.5+ MB
None
```

	Crop_Year	Area	Production	Annual_Rainfall	Fertilizer	Pesticide	Yield
19689.000000	1.968900e+04	1.968900e+04	19689.000000	1.968900e+04	1.968900e+04	19689.000000	
2009.127584	1.799266e+05	1.643594e+07	1437.755177	2.410331e+07	4.884835e+04	79.954009	
6.498099	7.328287e+05	2.630568e+08	816.909589	9.494600e+07	2.132874e+05	878.306193	
1997.000000	5.000000e-01	0.000000e+00	301.300000	5.417000e+01	9.000000e-02	0.000000	
2004.000000	1.390000e+03	1.393000e+03	940.700000	1.880146e+05	3.567000e+02	0.600000	
2010.000000	9.317000e+03	1.380400e+04	1247.600000	1.234957e+06	2.421900e+03	1.030000	
2015.000000	7.511200e+04	1.227180e+05	1643.700000	1.000385e+07	2.004170e+04	2.388889	
2020.000000	5.080810e+07	6.326000e+09	6552.700000	4.835407e+09	1.575051e+07	21105.000000	

3) Drop columns that aren't useful: Columns like Invoice ID may not contribute to analysis (it's often just an identifier). Removing irrelevant columns reduces complexity.

```
import pandas as pd

file_path = "/content/crop_yield.csv"
df = pd.read_csv(file_path)

df = df.drop(['Crop_Year'], axis=1)
df.head()
```

	Crop	Season	State	Area	Production	Annual_Rainfall	Fertilizer	Pesticide	Yield
0	Areca nut	Whole Year	Assam	73814.0	56708	2051.4	7024878.38	22882.34	0.796087
1	Arhar/Tur	Kharif	Assam	6637.0	4685	2051.4	631643.29	2057.47	0.710435
2	Castor seed	Kharif	Assam	796.0	22	2051.4	75755.32	246.76	0.238333
3	Coconut	Whole Year	Assam	19656.0	126905000	2051.4	1870661.52	6093.36	5238.051739
4	Cotton(lint)	Kharif	Assam	1739.0	794	2051.4	165500.63	539.09	0.420909

4) Drop rows with maximum missing values.

`df.dropna(thresh=int(0.5 * len(df.columns)))`:

- Drops rows where more than half the columns have missing (NaN) values.
- `thresh=int(0.5 * len(df.columns))`: Ensures that a row must have at least 50% non-null values to remain.

`df = ...`: Updates the DataFrame after dropping rows.

`print(df.info())`: Confirms that rows with excessive missing values have been removed.

```
import pandas as pd

file_path = "/content/crop_yield.csv"
df = pd.read_csv(file_path)

df = df.dropna(thresh=int(0.5 * len(df.columns)))
print(df.info())
```

```
<class 'pandas.core.frame.DataFrame'>
RangeIndex: 19689 entries, 0 to 19688
Data columns (total 10 columns):
 #   Column          Non-Null Count  Dtype
---  -
 0   Crop            19689 non-null object
 1   Crop_Year       19689 non-null int64
 2   Season         19689 non-null object
 3   State          19689 non-null object
 4   Area           19689 non-null float64
 5   Production      19689 non-null int64
 6   Annual_Rainfall 19689 non-null float64
 7   Fertilizer      19689 non-null float64
 8   Pesticide       19689 non-null float64
 9   Yield           19689 non-null float64
dtypes: float64(5), int64(2), object(3)
memory usage: 1.5+ MB
```

5) Take care of missing data.

`df.fillna(df.mean())`: Replaces missing values (NaN) in numeric columns with the mean of that column.

```
import pandas as pd

file_path = "/content/crop_yield.csv"
df = pd.read_csv(file_path)

df = df.dropna(thresh=int(0.5 * len(df.columns)))

numeric_cols = df.select_dtypes(include=['float64', 'int64']).columns
df[numeric_cols] = df[numeric_cols].fillna(df[numeric_cols].mean())

print(df.isnull().sum())
```

Crop	0
Crop_Year	0
Season	0
State	0
Area	0
Production	0
Annual_Rainfall	0
Fertilizer	0
Pesticide	0
Yield	0
dtype: int64	

6) Create dummy variables.

`pd.get_dummies()`: Converts categorical variables into dummy variables (binary indicators: 0 or 1).

- Example: The Gender column becomes Gender\_Male (1 if Male, 0 otherwise).

`columns=['...']`: Specifies which columns to convert.

`drop_first=True`: Avoids the "dummy variable trap" by dropping one dummy variable to prevent multicollinearity.

```
import pandas as pd

file_path = "/content/crop_yield.csv"
df = pd.read_csv(file_path)

df = df.dropna(thresh=int(0.5 * len(df.columns)))

df = pd.get_dummies(df, columns = ['Season'], drop_first = True)
df.head()
```

Crop_Year	State	Area	Production	Annual_Rainfall	Fertilizer	Pesticide	Yield	Season_Kharif	Season_Rabi	Season_Summer	Season_Whole_Year	Season_Winter
1997	Assam	73814.0	56708	2051.4	7024878.38	22882.34	0.796087	False	False	False	True	False
1997	Assam	6637.0	4685	2051.4	631643.29	2057.47	0.710435	True	False	False	False	False
1997	Assam	796.0	22	2051.4	75755.32	246.76	0.238333	True	False	False	False	False
1997	Assam	19656.0	126905000	2051.4	1870661.52	6093.36	5238.051739	False	False	False	True	False
1997	Assam	1739.0	794	2051.4	165500.63	539.09	0.420909	True	False	False	False	False

## 7)Find out outliers (manually)

```
import pandas as pd

file_path = "/content/crop_yield.csv"
df = pd.read_csv(file_path)

def detect_outliers(df, col):
    Q1 = df[col].quantile(0.25) # First quartile (25th percentile)
    Q3 = df[col].quantile(0.75) # Third quartile (75th percentile)
    IQR = Q3 - Q1 # Interquartile range

    lower_bound = Q1 - 1.5 * IQR
    upper_bound = Q3 + 1.5 * IQR

    return df[(df[col] < lower_bound) | (df[col] > upper_bound)]

# Detect outliers in the 'Yield' column
outliers = detect_outliers(df, 'Yield')

print(outliers)

if outliers.empty:
    print("No outliers detected.")
else:
    print(f"Outliers detected:\n{outliers}")

print(f"Number of outliers: {len(outliers)}")
```

Number of outliers: 3065

## 8) standardization and normalization of columns

**Standardization** is another scaling technique where the values are centered around the mean with a unit standard deviation. This means that the mean of the attribute becomes zero and the resultant distribution has a unit standard deviation.

Standardization equation

$$X' = \frac{X - \mu}{\sigma}$$

To standardize your data, we need to import the StandardScaler from the sklearn library and apply it to our dataset.

**Normalization** is a scaling technique in which values are shifted and rescaled so that they end up ranging between 0 and 1. It is also known as Min-Max scaling.

Normalization equation

$$X' = \frac{X - X_{min}}{X_{max} - X_{min}}$$

Here, Xmax and Xmin are the maximum and the minimum values of the feature respectively.

- When the value of X is the minimum value in the column, the numerator will be 0, and hence X' is 0
- On the other hand, when the value of X is the maximum value in the column, the numerator is equal to the denominator and thus the value of X' is 1
- If the value of X is between the minimum and the maximum value, then the value of X' is between 0 and 1

To normalize your data, you need to import the MinMaxScaler from the sklearn library and apply it to our dataset.



```
import pandas as pd
from sklearn.preprocessing import StandardScaler, MinMaxScaler

file_path = "/content/crop_yield.csv"
df = pd.read_csv(file_path)

cols_to_transform = ['Area', 'Production']

standard_scaler = StandardScaler()
minmax_scaler = MinMaxScaler()

df[cols_to_transform] = standard_scaler.fit_transform(df[cols_to_transform])

df[cols_to_transform] = minmax_scaler.fit_transform(df[cols_to_transform])

print(df[cols_to_transform].head())
```

	Area	Production
0	0.001453	8.964274e-06
1	0.000131	7.405944e-07
2	0.000016	3.477711e-09
3	0.000387	2.006086e-02
4	0.000034	1.255138e-07

## **Conclusion:**

Thus we have understood how to perform data preprocessing which can further be taken into exploratory data analysis and further in the Model preparation sequence.