

# TCP: Connection Management

Kameswari Chebrolu

All the figures used as part of the slides are either self created or from the public domain with either 'creative commons' or 'public domain dedication' licensing. The public sites from which some of the figures have been picked include:


<http://commons.wikimedia.org> (Wikipedia, Wikimedia and workbooks); <http://www.sxc.hu> and <http://www.pixabay.com>

# Background




- TCP is a connection oriented protocol
  - Processes can run on any type of machine in the Internet
- Connection establishment helps
  - Exchange and initiate state variables
    - MSS size, initial sequence number, ACK type
  - Allocate resources (buffer space)
    - ↓ send Buffer  
4KB - 1MB
    - ↓ receive Buffer  
8KB

# Connection Setup




# Problem




# Solution


- TCP's famous three-way handshake (idea from Tomlinson)



# Case-1



# Case-2



# Initial Sequence Number (ISN)


- Why not start with Seqno zero?
- Segments from different connections can get mixed up
- Security risk when ISN's are predictable
- Original solution: Use a clock (e.g. increments every 4 microsec) to choose ISN
  - 32 bit sequence number wraps around in 4 hrs
- Current implementations use random ISN

IP → TTL




# Connection Termination

- Asymmetric release (just hang-up) leads to loss of data
- Symmetric release
  - Treat connection as two separate unidirectional connections
  - Each side should be released separately



1. Let's attack on Sun @ 9am, Please ACK
2. OK fine. Let's attack, Please ACK
3. OK fine. ACK CAN IT ATTACK NOW????

# Two Army Problem




NO MATTER HOW MANY U USE, U CNT BE SURE

The attack will succeed *if and only if* both armies attack the enemy at the same time

***What strategy to adopt?***

# Relevance




The attack will succeed *if and only if* both armies attack the enemy at the same time

***What strategy to adopt?***

If neither side is ready to disconnect unless it is sure the other side is ready to disconnect, disconnect will never happen


# Solution

- Follows simple two-way handshake
- Each side independently closes connection



u will still use time-outs and Retransmissions, and  
if u do too many retrans then close()

# TCP State Diagram



# Time-Wait State

- Wait in time-wait for  $2 * \text{MSL}$  (maximum segment lifetime)

- Helps clear out older packets in the network; prevents them from interfering with new connection

- Time spent in time-wait range from 30sec to 2 min



"bind failed"

Conn 1:

same Port #

Src IP, Src Port, Dest IP, Dest Port

data

→ Used.

Conn 2:

Abort

RST

if we establish a new connection with same port,dsp,src ip .. then if prev packet which got delayed reaches now , then seq num not match and it leads to ABORT RST.

so u wait for sometime to all those packets handling... TIMEOUT state.. then release those ports for new connection .... if u try to connect .. it gives BINDING ERROR.

# Summary

- TCP is a connection oriented protocol
- Connection management complicated by the fact that packets can get retransmitted, delayed, delivered out of order etc
- Connection establishment governed by 3-way handshake
- Connection termination is based on symmetric release and managed by 2-way handshake
- Ahead: Sliding window action in the established state