Data Link Layer: Reliable Data Transfer

Kameswari Chebrolu

All the figures used as part of the slides are either self created or from the public domain with either 'creative commons' or 'public domain dedication' licensing. The public sites from which some of the figures have been picked include: http://commons.wikimedia.org (Wikipedia, Wikimedia and workbooks); http://www.sxc.hu and http://www.pixabay.com

Recap

- Frame-by-Frame next-hop delivery
 - Frames can get corrupted or lost
 - Error Detection helps detect corrupted frames
 - What next?
- Recover the corrupted/lost frames → Reliable


 Data Transfer

 Link Layer reliability is handled at both want port Layers.

 Transfer
 - One of the most researched problem in networking

Outline

- Develop a Reliable
 Data Transfer protocol
 (RDT)
 - Unreliable channel with bit errors
 - Unreliable channel with
 bit errors and losses



RDTv1.0: Channel with bit errors

Telephone Analogy

crashed

- Receiver Feedback
 - Positive: aha, ok, hmm → ACK


 acknnowledge
 - Negative: repeat that, didn't follow, what did you say? →
 NACK
 - Do we need both? YESSS
- Sender retransmits on NACK

- Error Detection mechanism
 - Checksum, CRC etc
- •

Automatic Repeat Request (ARQ)

Protocols based on

Feedback and retransmissions



Required Functionality:

- Error Detection mechanism
 - Checksum, CRC etc
- Receiver Feedback
 - ACK + NACK

RDTv1.0

RDTv1.0 has a fatal flaw!

- What if the ACK/NACK got corrupted?
 - What should sender do then?
- Send next packet? If prev.

 pkt is lost, RDT not

 providing reliability

 our goal is reliability... so u have to assume the worst and send againm
- Send previous packet? If prev. pkt is not lost, creates duplicates

- Error Detection mechanism
 - Checksum, CRC etc
- Receiver Feedback
 - -ACK + NACK
- Data Sequence Numbers

- Receiver gives feedback (ACK, NACK)
- Sender retransmits


 'sequenced' packet on
 NACK, garbled
 ACK/NACK
- Receiver discards
 duplicates if any based
 on sequence number

- Error Detection mechanism
 - Checksum, CRC etc
- Receiver Feedback
 - -ACK + NACK
- Data Sequence Numbers

- What is the sequence number space? [0,1,2,3]


 Just two car " "
 - Just two seq #s "0, 1" will suffice 1-bit Keek "K

nums suffice



- Optimization: NACK free operation
 - Convey same information as NACK but through ACK.
 How?
- Instead of NACK, receiver sends ACK of last correctly received packet
 - Receiver must explicitly include seq # of packet being ACKed
- Duplicate ACK at sender results in same action as NACK: retransmit current packet

NACK Free Protocol




- Error Detection mechanism <
 - Checksum, CRC etc
- Receiver Feedback
 - ACK + NACK
- Data Sequence Numbers
- ACK carries sequence number of data packets


RDT: Channel with Errors and Losses

- Will RDTv2.1 work?
- Sender gets no feedback: Need a Timeout mechanism

trigger for a sender to act is the feedback

• How long to wait? bit more than RTT Delay






Packet0

RDTv3.0

- Sender waits
 "Reasonable" amount of
 time for ACK
 - Retransmits if no ACK received in this time
- If pkt (or ACK) just delayed (not lost)
 - Retransmission will be duplicate, seq. #'s help resolve this


- Error Detection mechanism
- Checksum, CRC etc
- Receiver Feedback
 - ACK + NACK
 - Data Sequence Numbers
- ACK carries data seq. No.
- Timeout Timer

RDTv3.0: Stop and Wait Protocol In Action




Also called Alternating Bit Protocol

RDTv3.0: Stop and Wait Protocol



RDTv3.0: Stop and Wait Protocol In Action



but if it was a premature timeout then doing nothing is the right thing to do (d) Premature Timeout

Design of RDT protocols


- Many challenges to handle
 - ACKs/Packet loss, ACKs/Packet delayed,
 - Duplication of packets, Reordering, Incorrect timeout timer settings, Receiver capabilities
 - Protocol has to work <u>correctly and efficiently</u> in spite of all this



- 1 x+1 long time
- Can conclude packet loss on detecting 'holes'
 - Long delay between some packets can slow down recovery
 - What if the last packet in the flow is lost?
 - Receiver doesn't generate NACK, sender assume 'all is well'
- Advantage of NACK: If errors are infrequent, reduces overhead of feedback

Performance of Stop and Wait Protocol

- What is the achieved throughput?
- A 1000 By to
- 10 Mbps link, 10 ms prop. delay, 1KB packet,
 ACK too small (ignore its Transmission time)
- Throughput: 8000 bits / [(8000/10⁷)+2*0.010] = 384.6Kbps
- Utilization = 384.6kbps/10000kbps = 3.8%



Utilization = Transmission time / (Transmission time + RTT)

Summary

- Reliable data transfer protocols provide 'reliable channel' service abstraction to higher layers
- We incrementally determined the required functionality needed in RDT protocols with the second control of the second control of
- The current protocol designed is inefficient
- Future: Build on this framework to design better protocols