

A Brief Understanding of README.md

A Brief Understanding of README.md

Import Libraries

Code Block

Remarks

Load The Dataset

Code Block

Remarks

Preparing Data

Code Block

Remarks

Load 2D Detections

Code Block

Remarks

Code Block

Remarks

Function Fetch()

Code Block

Remarks

Code Block

Remarks

Code Block

Remarks

Code Block

Remarks

Evaluate (本部分不要求理解，只要会用就行)

Code Block

Remarks

Import Libraries

Code Block

```
1 import numpy as np
2
3 from common.arguments import parse_args
4 import torch
5
6 import torch.nn as nn
7 import torch.nn.functional as F
8 import torch.optim as optim
```

```
9 import os
10 import sys
11 import errno
12
13 from common.camera import *
14 from common.model import *
15 from common.loss import *
16 from common.generators import ChunkedGenerator, UnchunkedGenerator
17 from time import time
18 from common.utils import deterministic_random
```

Remarks

- `common.camera` 等引入都是在文件夹 `common` 下的 `.py` 文件，例如 `common.camera == common/camera.py`。
- 对与 `torch` 包中三个函数的名字进行了重载，例如使用 `F` 来代替 `torch.nn.functional` 来节省空间。

Load The Dataset

Code Block

```
1 args = parse_args()
2 print(args)
3
4 try:
5     # Create checkpoint directory if it does not exist
6     os.makedirs(args.checkpoint)
7 except OSError as e:
8     if e.errno != errno.EEXIST:
9         raise RuntimeError('Unable to create checkpoint directory:',
10                             args.checkpoint)
11
12 print('Loading dataset...')
13 dataset_path = 'data/data_3d_' + args.dataset + '.npz'
14 if args.dataset == 'h36m':
15     from common.h36m_dataset import Human36mDataset
16     dataset = Human36mDataset(dataset_path)
17 elif args.dataset.startswith('humaneva'):
18     from common.humaneva_dataset import HumanEvaDataset
19     dataset = HumanEvaDataset(dataset_path)
20 elif args.dataset.startswith('custom'):
21     from common.custom_dataset import CustomDataset
```

```

21     dataset = CustomDataset('data/data_2d_' + args.dataset + '_' +
    args.keypoints + '.npz')
22 else:
23     raise KeyError('Invalid dataset')

```

Remarks

- `Keyerror` 在使用映射中不存在的键时引发
- 先尝试新建 `./checkpoint` 文件夹。如果文件夹已经存在，不再新建；如果还不存在，则新建文件夹。如果不在这两种情况之内，则报错，终止程序。
- 定义变量 `dataset_path` 为数据集路径变量。观察 `data/data_3d` 中我们的数据集：
- 根据 `README.md` 说明，`python run.py -e 80 -k cpn_ft_h36m_dbb -arc 3,3,3,3,3` 是成功运行的解，这说明我们并没有人为输入 `path` 参数，而是在 `run.py` 中已经定义了这个参数。
- 根据 `DATASET.md` 说明，目录结构已经符合如下样式：

```

1  /path/to/dataset/S1/MyPoseFeatures/D3_Positions/Directions 1.cdf
2  /path/to/dataset/S1/MyPoseFeatures/D3_Positions/Directions.cdf
3  ...

```

- 再根据 `DATASET.md` 指出的 `pyscript` 脚本（新版本，不使用 `matlab`）

```

1  cd data
2  python prepare_data_h36m.py --from-source-cdf /path/to/dataset
3  cd ..

```

我们看进 `prepare_data_h36m.py` 的代码：

```

1  import argparse
2  import os
3  import zipfile
4  import numpy as np
5  import h5py
6  from glob import glob
7  from shutil import rmtree
8
9  import sys # 这是system扩展包，用于进行系统的io处理
10 sys.path.append('../')
11 from common.h36m_dataset import Human36mDataset # 引入../common中写好的
    h36m_dataset.py脚本
12 from common.camera import world_to_camera, project_to_2d,
    image_coordinates
13 from common.utils import wrap
14
15 output_filename = 'data_3d_h36m'
16 output_filename_2d = 'data_2d_h36m_gt'
17 subjects = ['S1', 'S5', 'S6', 'S7', 'S8', 'S9', 'S11']
18

```

```

19 if __name__ == '__main__': # execute only if run as a script
20     if os.path.basename(os.getcwd()) != 'data':
21         print('This script must be launched from the "data" directory') #
        必须在给定的文件夹启动本脚本
22         exit(0)
23
24     parser = argparse.ArgumentParser(description='Human3.6M dataset
        downloader/converter')
25
26     # Convert dataset preprocessed by Martinez et al. in
        https://github.com/una-dinosauria/3d-pose-baseline
27     parser.add_argument('--from-archive', default='', type=str,
        metavar='PATH', help='convert preprocessed dataset')
28
29     # Convert dataset from original source, using files converted to .mat
        (the Human3.6M dataset path must be specified manually)
30     # This option requires MATLAB to convert files using the provided
        script
31     parser.add_argument('--from-source', default='', type=str,
        metavar='PATH', help='convert original dataset')
32
33     # Convert dataset from original source, using original .cdf files
        (the Human3.6M dataset path must be specified manually)
34     # This option does not require MATLAB, but the Python library cdflib
        must be installed
35     parser.add_argument('--from-source-cdf', default='', type=str,
        metavar='PATH', help='convert original dataset')
36
37     args = parser.parse_args()
38
39     if args.from_archive and args.from_source:
40         print('Please specify only one argument')
41         exit(0)
42
43     if os.path.exists(output_filename + '.npz'):
44         print('The dataset already exists at', output_filename + '.npz')
45         exit(0)
46
47     if args.from_archive:
48         print('Extracting Human3.6M dataset from', args.from_archive)
49         with zipfile.ZipFile(args.from_archive, 'r') as archive:
50             archive.extractall()
51
52         print('Converting...')
53         output = {}
54         for subject in subjects:
55             output[subject] = {}
56             file_list = glob('h36m/' + subject +
        '/MyPoses/3D_positions/*.h5')

```

```

57         assert len(file_list) == 30, "Expected 30 files for subject "
+ subject + ", got " + str(len(file_list))
58         for f in file_list:
59             action = os.path.splitext(os.path.basename(f))[0]
60
61             if subject == 'S11' and action == 'Directions':
62                 continue # Discard corrupted video
63
64             with h5py.File(f) as hf:
65                 positions = hf['3D_positions'].value.reshape(32, 3,
-1).transpose(2, 0, 1)
66                 positions /= 1000 # Meters instead of millimeters
67                 output[subject][action] = positions.astype('float32')
68
69             print('Saving...')
70             np.savez_compressed(output_filename, positions_3d=output)
71
72             print('Cleaning up...')
73             rmtree('h36m')
74
75             print('Done.')
76
77     elif args.from_source:
78         print('Converting original Human3.6M dataset from',
args.from_source)
79         output = {}
80
81         from scipy.io import loadmat
82
83         for subject in subjects:
84             output[subject] = {}
85             file_list = glob(args.from_source + '/' + subject +
'/MyPoseFeatures/D3_Positions/*.cdf.mat')
86             assert len(file_list) == 30, "Expected 30 files for subject "
+ subject + ", got " + str(len(file_list))
87             for f in file_list:
88                 action =
os.path.splitext(os.path.splitext(os.path.basename(f))[0])[0]
89
90                 if subject == 'S11' and action == 'Directions':
91                     continue # Discard corrupted video
92
93                 # Use consistent naming convention
94                 canonical_name = action.replace('TakingPhoto', 'Photo') \
.replace('WalkingDog', 'WalkDog')
95
96
97                 hf = loadmat(f)
98                 positions = hf['data'][0, 0].reshape(-1, 32, 3)
99                 positions /= 1000 # Meters instead of millimeters

```

```

100         output[subject][canonical_name] =
positions.astype('float32')
101
102         print('Saving...')
103         np.savez_compressed(output_filename, positions_3d=output)
104
105         print('Done.')
106
107     elif args.from_source_cdf:
108         print('Converting original Human3.6M dataset from',
args.from_source_cdf, '(CDF files)')
109         output = {}
110
111         import cdfplib
112
113         for subject in subjects:
114             output[subject] = {}
115             file_list = glob(args.from_source_cdf + '/' + subject +
'/MyPoseFeatures/D3_Positions/*.cdf')
116             assert len(file_list) == 30, "Expected 30 files for subject "
+ subject + ", got " + str(len(file_list))
117             for f in file_list:
118                 action = os.path.splitext(os.path.basename(f))[0]
119
120                 if subject == 'S11' and action == 'Directions':
121                     continue # Discard corrupted video
122
123                 # Use consistent naming convention
124                 canonical_name = action.replace('TakingPhoto', 'Photo') \
.replace('WalkingDog', 'WalkDog')
125
126                 hf = cdfplib.CDF(f)
127                 positions = hf['Pose'].reshape(-1, 32, 3)
128                 positions /= 1000 # Meters instead of millimeters
129                 output[subject][canonical_name] =
positions.astype('float32')
130
131                 print('Saving...')
132                 np.savez_compressed(output_filename, positions_3d=output)
133
134                 print('Done.')
135
136     else:
137         print('Please specify the dataset source')
138         exit(0)
139
140     # Create 2D pose file
141     print('')
142     print('Computing ground-truth 2D poses...')

```

```

144     dataset = Human36mDataset(output_filename + '.npz') # 使用npz文件存储计
算出的2d pose gt文件
145     output_2d_poses = {}
146     for subject in dataset.subjects():
147         output_2d_poses[subject] = {}
148         for action in dataset[subject].keys():
149             anim = dataset[subject][action]
150
151             positions_2d = []
152             for cam in anim['cameras']:
153                 pos_3d = world_to_camera(anim['positions'],
R=cam['orientation'], t=cam['translation'])
154                 pos_2d = wrap(project_to_2d, pos_3d, cam['intrinsic'],
unsqueeze=True)
155                 pos_2d_pixel_space = image_coordinates(pos_2d,
w=cam['res_w'], h=cam['res_h'])
156                 positions_2d.append(pos_2d_pixel_space.astype('float32'))
157                 output_2d_poses[subject][action] = positions_2d
158
159     print('Saving...')
160     metadata = {
161         'num_joints': dataset.skeleton().num_joints(),
162         'keypoints_symmetry': [dataset.skeleton().joints_left(),
dataset.skeleton().joints_right()]
163     }
164     np.savez_compressed(output_filename_2d, positions_2d=output_2d_poses,
metadata=metadata)
165
166     print('Done.')

```

发现最后所有的data都被装进了一个文件 `data/data_3d_h36m.npz` 中。我们跟着看 `README.md` 中剩下的代码：

```

1  dataset_path = 'data/data_3d_' + args.dataset + '.npz'
2  if args.dataset == 'h36m':
3      from common.h36m_dataset import Human36mDataset
4      dataset = Human36mDataset(dataset_path)
5  elif args.dataset.startswith('humaneva'):
6      from common.humaneva_dataset import HumanEvaDataset
7      dataset = HumanEvaDataset(dataset_path)
8  elif args.dataset.startswith('custom'):
9      from common.custom_dataset import CustomDataset
10     dataset = CustomDataset('data/data_2d_' + args.dataset + '_' +
args.keypoints + '.npz')
11 else:
12     raise KeyError('Invalid dataset')

```

- 发现程序已经选择了 `Human36mDataset(dataset_path)` 进行挂载。

Preparing Data

Code Block

```
1 print('Preparing data...')
2 for subject in dataset.subjects():
3     for action in dataset[subject].keys():
4         anim = dataset[subject][action]
5
6         if 'positions' in anim:
7             positions_3d = []
8             for cam in anim['cameras']:
9                 pos_3d = world_to_camera(anim['positions'],
10 R=cam['orientation'], t=cam['translation'])
11                 pos_3d[:, 1:] -= pos_3d[:, :1] # Remove global offset, but
12 keep trajectory in first position
13                 positions_3d.append(pos_3d)
14             anim['positions_3d'] = positions_3d
```

Remarks

- 对于数据集中每一个对象都执行准备（预处理）操作。
- 删除全局偏移，但将轨迹保持在第一位置。

Load 2D Detections

Code Block

```
1 print('Loading 2D detections...')
2 keypoints = np.load('data/data_2d_' + args.dataset + '_' + args.keypoints
3 + '.npz', allow_pickle=True)
4 keypoints_metadata = keypoints['metadata'].item()
5 keypoints_symmetry = keypoints_metadata['keypoints_symmetry']
6 kps_left, kps_right = list(keypoints_symmetry[0]),
7 list(keypoints_symmetry[1])
8 joints_left, joints_right = list(dataset.skeleton().joints_left()),
9 list(dataset.skeleton().joints_right())
10 keypoints = keypoints['positions_2d'].item()
11
12 for subject in dataset.subjects():
13     assert subject in keypoints, 'Subject {} is missing from the 2D
14 detections dataset'.format(subject)
15     for action in dataset[subject].keys():
16         assert action in keypoints[subject], 'Action {} of subject {} is
17 missing from the 2D detections dataset'.format(action, subject)
18         if 'positions_3d' not in dataset[subject][action]:
```



```

14         continue
15
16     for cam_idx in range(len(keypoints[subject][action])):
17
18         # We check for >= instead of == because some videos in H3.6M
19         contain extra frames
20         mocap_length = dataset[subject][action]['positions_3d']
21         [cam_idx].shape[0]
22         assert keypoints[subject][action][cam_idx].shape[0] >=
23         mocap_length
24
25         if keypoints[subject][action][cam_idx].shape[0] >
26         mocap_length:
27             # Shorten sequence
28             keypoints[subject][action][cam_idx] = keypoints[subject]
29             [action][cam_idx][:mocap_length]
30
31         assert len(keypoints[subject][action]) == len(dataset[subject]
32         [action]['positions_3d'])

```

Remarks

- 装载2D探测。根据命令 `keypoints = np.load('data/data_2d_' + args.dataset + '_' + args.keypoints + '.npz', allow_pickle=True)` 推知



主要的变化是 `args.keypoints`，因为custom只在inference in the wild的时候才会用到。对于

Code Block

```

1  for subject in keypoints.keys():
2      for action in keypoints[subject]:
3          for cam_idx, kps in enumerate(keypoints[subject][action]):
4              # Normalize camera frame
5              cam = dataset.cameras()[subject][cam_idx]
6              kps[..., :2] = normalize_screen_coordinates(kps[..., :2],
7              w=cam['res_w'], h=cam['res_h'])
8              keypoints[subject][action][cam_idx] = kps
9
10 subjects_train = args.subjects_train.split(',')
11 subjects_semi = [] if not args.subjects_unlabeled else
12 args.subjects_unlabeled.split(',')
13
14 if not args.render:
15     subjects_test = args.subjects_test.split(',')

```

```

13 else:
14     subjects_test = [args.viz_subject]
15
16 semi_supervised = len(subjects_semi) > 0
17 if semi_supervised and not dataset.supports_semi_supervised():
18     raise RuntimeError('Semi-supervised training is not implemented for
    this dataset')

```

Remarks

- `RuntimeError`



Function Fetch()

Code Block

```

1 def fetch(subjects, action_filter=None, subset=1, parse_3d_poses=True):
2     out_poses_3d = []
3     out_poses_2d = []
4     out_camera_params = []
5     for subject in subjects:
6         for action in keypoints[subject].keys():
7             if action_filter is not None:
8                 found = False
9                 for a in action_filter:
10                     if action.startswith(a):
11                         found = True
12                         break
13                 if not found:
14                     continue
15
16             poses_2d = keypoints[subject][action]
17             for i in range(len(poses_2d)): # Iterate across cameras
18                 out_poses_2d.append(poses_2d[i])
19
20             if subject in dataset.cameras():
21                 cams = dataset.cameras()[subject]
22                 assert len(cams) == len(poses_2d), 'Camera count mismatch'
23                 for cam in cams:
24                     if 'intrinsic' in cam:
25                         out_camera_params.append(cam['intrinsic'])
26
27             if parse_3d_poses and 'positions_3d' in dataset[subject]
    [action]:

```

```

28         poses_3d = dataset[subject][action]['positions_3d']
29         assert len(poses_3d) == len(poses_2d), 'Camera count
mismatch'
30         for i in range(len(poses_3d)): # Iterate across cameras
31             out_poses_3d.append(poses_3d[i])
32
33         if len(out_camera_params) == 0:
34             out_camera_params = None
35         if len(out_poses_3d) == 0:
36             out_poses_3d = None
37
38         stride = args.downsample
39         if subset < 1:
40             for i in range(len(out_poses_2d)):
41                 n_frames = int(round(len(out_poses_2d[i])//stride *
subset)*stride)
42                 start = deterministic_random(0, len(out_poses_2d[i]) -
n_frames + 1, str(len(out_poses_2d[i])))
43                 out_poses_2d[i] = out_poses_2d[i][start:start+n_frames:stride]
44                 if out_poses_3d is not None:
45                     out_poses_3d[i] = out_poses_3d[i]
[start:start+n_frames:stride]
46             elif stride > 1:
47                 # Downsample as requested
48                 for i in range(len(out_poses_2d)):
49                     out_poses_2d[i] = out_poses_2d[i][::stride]
50                     if out_poses_3d is not None:
51                         out_poses_3d[i] = out_poses_3d[i][::stride]
52
53         return out_camera_params, out_poses_3d, out_poses_2d

```

Remarks

Code Block

```

1  action_filter = None if args.actions == '*' else args.actions.split(',')
2  if action_filter is not None:
3      print('Selected actions:', action_filter)
4
5  cameras_valid, poses_valid, poses_valid_2d = fetch(subjects_test,
action_filter)

```

```

6
7 filter_widths = [int(x) for x in args.architecture.split(',')]
8 if not args.disable_optimizations and not args.dense and args.stride == 1:
9     # Use optimized model for single-frame predictions
10    model_pos_train =
TemporalModelOptimized1f(poses_valid_2d[0].shape[-2],
poses_valid_2d[0].shape[-1], dataset.skeleton().num_joints(),
11                        filter_widths=filter_widths,
causal=args.causal, dropout=args.dropout, channels=args.channels)
12 else:
13     # When incompatible settings are detected (stride > 1, dense filters,
or disabled optimization) fall back to normal model
14    model_pos_train = TemporalModel(poses_valid_2d[0].shape[-2],
poses_valid_2d[0].shape[-1],
dataset.skeleton().num_joints(), filter_widths=filter_widths, causal=args.ca
usal, dropout=args.dropout, channels=args.channels, dense=args.dense)

```

Remarks

Code Block

```

1 model_pos = TemporalModel(poses_valid_2d[0].shape[-2],
poses_valid_2d[0].shape[-1], dataset.skeleton().num_joints(),
2                        filter_widths=filter_widths,
causal=args.causal, dropout=args.dropout, channels=args.channels,
3                        dense=args.dense)
4
5 receptive_field = model_pos.receptive_field()
6 print('INFO: Receptive field: {} frames'.format(receptive_field))
7 pad = (receptive_field - 1) // 2 # Padding on each side
8 if args.causal:
9     print('INFO: Using causal convolutions')
10    causal_shift = pad
11 else:
12    causal_shift = 0
13
14 model_params = 0
15 for parameter in model_pos.parameters():
16     model_params += parameter.numel()
17 print('INFO: Trainable parameter count:', model_params)
18
19 if torch.cuda.is_available():
20     model_pos = model_pos.cuda()
21     model_pos_train = model_pos_train.cuda()

```

```

22
23 if args.resume or args.evaluate:
24     chk_filename = os.path.join(args.checkpoint, args.resume if
args.resume else args.evaluate)
25     print('Loading checkpoint', chk_filename)
26     checkpoint = torch.load(chk_filename, map_location=lambda storage,
loc: storage)
27     print('This model was trained for {}
epochs'.format(checkpoint['epoch']))
28     model_pos_train.load_state_dict(checkpoint['model_pos'])
29     model_pos.load_state_dict(checkpoint['model_pos'])
30
31     if args.evaluate and 'model_traj' in checkpoint:
32         # Load trajectory model if it contained in the checkpoint (e.g.
for inference in the wild)
33         model_traj = TemporalModel(poses_valid_2d[0].shape[-2],
poses_valid_2d[0].shape[-1], 1,
34                                     filter_widths=filter_widths,
causal=args.causal, dropout=args.dropout, channels=args.channels,
35                                     dense=args.dense)
36         if torch.cuda.is_available():
37             model_traj = model_traj.cuda()
38         model_traj.load_state_dict(checkpoint['model_traj'])
39     else:
40         model_traj = None

```

Remarks

Code Block

```

1 test_generator = UnchunkedGenerator(cameras_valid, poses_valid,
poses_valid_2d,
2                                     pad=pad, causal_shift=causal_shift,
augment=False,
3                                     kps_left=kps_left,
kps_right=kps_right, joints_left=joints_left, joints_right=joints_right)
4 print('INFO: Testing on {} frames'.format(test_generator.num_frames()))
5
6 if not args.evaluate:
7     cameras_train, poses_train, poses_train_2d = fetch(subjects_train,
action_filter, subset=args.subset)
8
9     lr = args.learning_rate
10    if semi_supervised:

```

```

11     cameras_semi, _, poses_semi_2d = fetch(subjects_semi,
12     action_filter, parse_3d_poses=False)
13
14     if not args.disable_optimizations and not args.dense and
15     args.stride == 1:
16         # Use optimized model for single-frame predictions
17         model_traj_train =
18         TemporalModelOptimized1f(poses_valid_2d[0].shape[-2],
19         poses_valid_2d[0].shape[-1], 1,
20         filter_widths=filter_widths, causal=args.causal,
21         dropout=args.dropout, channels=args.channels)
22     else:
23         # When incompatible settings are detected (stride > 1, dense
24         filters, or disabled optimization) fall back to normal model
25         model_traj_train = TemporalModel(poses_valid_2d[0].shape[-2],
26         poses_valid_2d[0].shape[-1], 1,
27         filter_widths=filter_widths, causal=args.causal,
28         dropout=args.dropout, channels=args.channels,
29         dense=args.dense)
30
31     model_traj = TemporalModel(poses_valid_2d[0].shape[-2],
32     poses_valid_2d[0].shape[-1], 1,
33     filter_widths=filter_widths,
34     causal=args.causal, dropout=args.dropout, channels=args.channels,
35     dense=args.dense)
36
37     if torch.cuda.is_available():
38         model_traj = model_traj.cuda()
39         model_traj_train = model_traj_train.cuda()
40     optimizer = optim.Adam(list(model_pos_train.parameters()) +
41     list(model_traj_train.parameters()),
42     lr=lr, amsgrad=True)
43
44
45     losses_2d_train_unlabeled = []
46     losses_2d_train_labeled_eval = []
47     losses_2d_train_unlabeled_eval = []
48     losses_2d_valid = []
49
50     losses_traj_train = []
51     losses_traj_train_eval = []
52     losses_traj_valid = []
53 else:
54     optimizer = optim.Adam(model_pos_train.parameters(), lr=lr,
55     amsgrad=True)
56
57     lr_decay = args.lr_decay
58
59     losses_3d_train = []
60     losses_3d_train_eval = []
61     losses_3d_valid = []

```

```

48
49     epoch = 0
50     initial_momentum = 0.1
51     final_momentum = 0.001
52
53
54     train_generator = ChunkedGenerator(args.batch_size//args.stride,
cameras_train, poses_train, poses_train_2d, args.stride,
55                                     pad=pad,
causal_shift=causal_shift, shuffle=True, augment=args.data_augmentation,
56                                     kps_left=kps_left,
kps_right=kps_right, joints_left=joints_left, joints_right=joints_right)
57     train_generator_eval = UnchunkedGenerator(cameras_train, poses_train,
poses_train_2d,
58                                             pad=pad,
causal_shift=causal_shift, augment=False)
59     print('INFO: Training on {}
frames'.format(train_generator_eval.num_frames()))
60     if semi_supervised:
61         semi_generator = ChunkedGenerator(args.batch_size//args.stride,
cameras_semi, None, poses_semi_2d, args.stride,
62                                             pad=pad,
causal_shift=causal_shift, shuffle=True,
63                                             random_seed=4321,
augment=args.data_augmentation,
64                                             kps_left=kps_left,
kps_right=kps_right, joints_left=joints_left, joints_right=joints_right,
65                                             endless=True)
66         semi_generator_eval = UnchunkedGenerator(cameras_semi, None,
poses_semi_2d,
67                                             pad=pad,
causal_shift=causal_shift, augment=False)
68         print('INFO: Semi-supervision on {}
frames'.format(semi_generator_eval.num_frames()))
69
70     if args.resume:
71         epoch = checkpoint['epoch']
72         if 'optimizer' in checkpoint and checkpoint['optimizer'] is not
None:
73             optimizer.load_state_dict(checkpoint['optimizer'])
74             train_generator.set_random_state(checkpoint['random_state'])
75         else:
76             print('WARNING: this checkpoint does not contain an optimizer
state. The optimizer will be reinitialized.')
77
78     lr = checkpoint['lr']
79     if semi_supervised:
80         model_traj_train.load_state_dict(checkpoint['model_traj'])
81         model_traj.load_state_dict(checkpoint['model_traj'])

```

```

82     semi_generator.set_random_state(checkpoint['random_state_semi'])
83
84     print('** Note: reported losses are averaged over all frames and
test-time augmentation is not used here.')
85     print('** The final evaluation will be carried out after the last
training epoch.')
86
87     # Pos model only
88     while epoch < args.epochs:
89         start_time = time()
90         epoch_loss_3d_train = 0
91         epoch_loss_traj_train = 0
92         epoch_loss_2d_train_unlabeled = 0
93         N = 0
94         N_semi = 0
95         model_pos_train.train()
96         if semi_supervised:
97             # Semi-supervised scenario
98             model_traj_train.train()
99             for (_, batch_3d, batch_2d), (cam_semi, _, batch_2d_semi) in
\
100                 zip(train_generator.next_epoch(),
semi_generator.next_epoch()):
101
102                 # Fall back to supervised training for the first epoch
(to avoid instability)
103                 skip = epoch < args.warmup
104
105                 cam_semi = torch.from_numpy(cam_semi.astype('float32'))
106                 inputs_3d = torch.from_numpy(batch_3d.astype('float32'))
107                 if torch.cuda.is_available():
108                     cam_semi = cam_semi.cuda()
109                     inputs_3d = inputs_3d.cuda()
110
111                 inputs_traj = inputs_3d[:, :, :1].clone()
112                 inputs_3d[:, :, 0] = 0
113
114                 # Split point between labeled and unlabeled samples in
the batch
115                 split_idx = inputs_3d.shape[0]
116
117                 inputs_2d = torch.from_numpy(batch_2d.astype('float32'))
118                 inputs_2d_semi =
torch.from_numpy(batch_2d_semi.astype('float32'))
119                 if torch.cuda.is_available():
120                     inputs_2d = inputs_2d.cuda()
121                     inputs_2d_semi = inputs_2d_semi.cuda()

```



```

122         inputs_2d_cat = torch.cat((inputs_2d, inputs_2d_semi),
dim=0) if not skip else inputs_2d
123
124         optimizer.zero_grad()
125
126         # Compute 3D poses
127         predicted_3d_pos_cat = model_pos_train(inputs_2d_cat)
128
129         loss_3d_pos = mpjpe(predicted_3d_pos_cat[:split_idx],
inputs_3d)
130         epoch_loss_3d_train +=
inputs_3d.shape[0]*inputs_3d.shape[1] * loss_3d_pos.item()
131         N += inputs_3d.shape[0]*inputs_3d.shape[1]
132         loss_total = loss_3d_pos
133
134         # Compute global trajectory
135         predicted_traj_cat = model_traj_train(inputs_2d_cat)
136         w = 1 / inputs_traj[:, :, :, 2] # Weight inversely
proportional to depth
137         loss_traj =
weighted_mpjpe(predicted_traj_cat[:split_idx], inputs_traj, w)
138         epoch_loss_traj_train +=
inputs_3d.shape[0]*inputs_3d.shape[1] * loss_traj.item()
139         assert inputs_traj.shape[0]*inputs_traj.shape[1] ==
inputs_3d.shape[0]*inputs_3d.shape[1]
140         loss_total += loss_traj
141
142         if not skip:
143             # Semi-supervised loss for unlabeled samples
144             predicted_semi = predicted_3d_pos_cat[split_idx:]
145             if pad > 0:
146                 target_semi = inputs_2d_semi[:, pad:-pad, :,
:2].contiguous()
147             else:
148                 target_semi = inputs_2d_semi[:, :, :,
:2].contiguous()
149
150             projection_func = project_to_2d_linear if
args.linear_projection else project_to_2d
151             reconstruction_semi = projection_func(predicted_semi
+ predicted_traj_cat[split_idx:], cam_semi)
152
153             loss_reconstruction = mpjpe(reconstruction_semi,
target_semi) # On 2D poses
154             epoch_loss_2d_train_unlabeled +=
predicted_semi.shape[0]*predicted_semi.shape[1] *
loss_reconstruction.item()
155             if not args.no_proj:
156                 loss_total += loss_reconstruction

```

```

157
158         # Bone length term to enforce kinematic constraints
159         if args.bone_length_term:
160             dists = predicted_3d_pos_cat[:, :, 1:] -
predicted_3d_pos_cat[:, :, dataset.skeleton().parents()[1:]]
161             bone_lengths = torch.mean(torch.norm(dists,
dim=3), dim=1)
162             penalty =
torch.mean(torch.abs(torch.mean(bone_lengths[:split_idx], dim=0) \
163 -
torch.mean(bone_lengths[split_idx:], dim=0)))
164             loss_total += penalty
165
166
167             N_semi +=
predicted_semi.shape[0]*predicted_semi.shape[1]
168         else:
169             N_semi += 1 # To avoid division by zero
170
171             loss_total.backward()
172
173             optimizer.step()
174             losses_traj_train.append(epoch_loss_traj_train / N)
175
losses_2d_train_unlabeled.append(epoch_loss_2d_train_unlabeled / N_semi)
176     else:
177         # Regular supervised scenario
178         for _, batch_3d, batch_2d in train_generator.next_epoch():
179             inputs_3d = torch.from_numpy(batch_3d.astype('float32'))
180             inputs_2d = torch.from_numpy(batch_2d.astype('float32'))
181             if torch.cuda.is_available():
182                 inputs_3d = inputs_3d.cuda()
183                 inputs_2d = inputs_2d.cuda()
184             inputs_3d[:, :, 0] = 0
185
186             optimizer.zero_grad()
187
188             # Predict 3D poses
189             predicted_3d_pos = model_pos_train(inputs_2d)
190             loss_3d_pos = mpjpe(predicted_3d_pos, inputs_3d)
191             epoch_loss_3d_train +=
inputs_3d.shape[0]*inputs_3d.shape[1] * loss_3d_pos.item()
192             N += inputs_3d.shape[0]*inputs_3d.shape[1]
193
194             loss_total = loss_3d_pos
195             loss_total.backward()
196
197             optimizer.step()
198

```

```

199         losses_3d_train.append(epoch_loss_3d_train / N)
200
201     # End-of-epoch evaluation
202     with torch.no_grad():
203         model_pos.load_state_dict(model_pos_train.state_dict())
204         model_pos.eval()
205         if semi_supervised:
206             model_traj.load_state_dict(model_traj_train.state_dict())
207             model_traj.eval()
208
209         epoch_loss_3d_valid = 0
210         epoch_loss_traj_valid = 0
211         epoch_loss_2d_valid = 0
212         N = 0
213
214         if not args.no_eval:
215             # Evaluate on test set
216             for cam, batch, batch_2d in test_generator.next_epoch():
217                 inputs_3d = torch.from_numpy(batch.astype('float32'))
218                 inputs_2d =
219 torch.from_numpy(batch_2d.astype('float32'))
220                 if torch.cuda.is_available():
221                     inputs_3d = inputs_3d.cuda()
222                     inputs_2d = inputs_2d.cuda()
223                 inputs_traj = inputs_3d[:, :, :1].clone()
224                 inputs_3d[:, :, 0] = 0
225
226                 # Predict 3D poses
227                 predicted_3d_pos = model_pos(inputs_2d)
228                 loss_3d_pos = mpjpe(predicted_3d_pos, inputs_3d)
229                 epoch_loss_3d_valid +=
230 inputs_3d.shape[0]*inputs_3d.shape[1] * loss_3d_pos.item()
231                 N += inputs_3d.shape[0]*inputs_3d.shape[1]
232
233                 if semi_supervised:
234                     cam = torch.from_numpy(cam.astype('float32'))
235                     if torch.cuda.is_available():
236                         cam = cam.cuda()
237
238                     predicted_traj = model_traj(inputs_2d)
239                     loss_traj = mpjpe(predicted_traj, inputs_traj)
240                     epoch_loss_traj_valid +=
241 inputs_traj.shape[0]*inputs_traj.shape[1] * loss_traj.item()
242                     assert inputs_traj.shape[0]*inputs_traj.shape[1]
243 == inputs_3d.shape[0]*inputs_3d.shape[1]
244
245                     if pad > 0:
246                         target = inputs_2d[:, pad:-pad, :,
247 :2].contiguous()

```

```

243         else:
244             target = inputs_2d[:, :, :, :2].contiguous()
245             reconstruction = project_to_2d(predicted_3d_pos +
predicted_traj, cam)
246             loss_reconstruction = mpjpe(reconstruction,
target) # On 2D poses
247             epoch_loss_2d_valid +=
reconstruction.shape[0]*reconstruction.shape[1] *
loss_reconstruction.item()
248             assert
reconstruction.shape[0]*reconstruction.shape[1] ==
inputs_3d.shape[0]*inputs_3d.shape[1]
249
250             losses_3d_valid.append(epoch_loss_3d_valid / N)
251             if semi_supervised:
252                 losses_traj_valid.append(epoch_loss_traj_valid / N)
253                 losses_2d_valid.append(epoch_loss_2d_valid / N)
254
255
256             # Evaluate on training set, this time in evaluation mode
257             epoch_loss_3d_train_eval = 0
258             epoch_loss_traj_train_eval = 0
259             epoch_loss_2d_train_labeled_eval = 0
260             N = 0
261             for cam, batch, batch_2d in
train_generator_eval.next_epoch():
262                 if batch_2d.shape[1] == 0:
263                     # This can only happen when downsampling the
dataset
264                     continue
265
266                 inputs_3d = torch.from_numpy(batch.astype('float32'))
267                 inputs_2d =
torch.from_numpy(batch_2d.astype('float32'))
268                 if torch.cuda.is_available():
269                     inputs_3d = inputs_3d.cuda()
270                     inputs_2d = inputs_2d.cuda()
271                 inputs_traj = inputs_3d[:, :, :1].clone()
272                 inputs_3d[:, :, 0] = 0
273
274                 # Compute 3D poses
275                 predicted_3d_pos = model_pos(inputs_2d)
276                 loss_3d_pos = mpjpe(predicted_3d_pos, inputs_3d)
277                 epoch_loss_3d_train_eval +=
inputs_3d.shape[0]*inputs_3d.shape[1] * loss_3d_pos.item()
278                 N += inputs_3d.shape[0]*inputs_3d.shape[1]
279
280                 if semi_supervised:
281                     cam = torch.from_numpy(cam.astype('float32'))

```

```

282         if torch.cuda.is_available():
283             cam = cam.cuda()
284             predicted_traj = model_traj(inputs_2d)
285             loss_traj = mpjpe(predicted_traj, inputs_traj)
286             epoch_loss_traj_train_eval +=
inputs_traj.shape[0]*inputs_traj.shape[1] * loss_traj.item()
287             assert inputs_traj.shape[0]*inputs_traj.shape[1]
== inputs_3d.shape[0]*inputs_3d.shape[1]
288
289             if pad > 0:
290                 target = inputs_2d[:, pad:-pad, :,
:2].contiguous()
291             else:
292                 target = inputs_2d[:, :, :, :2].contiguous()
293             reconstruction = project_to_2d(predicted_3d_pos +
predicted_traj, cam)
294             loss_reconstruction = mpjpe(reconstruction,
target)
295             epoch_loss_2d_train_labeled_eval +=
reconstruction.shape[0]*reconstruction.shape[1] *
loss_reconstruction.item()
296             assert
reconstruction.shape[0]*reconstruction.shape[1] ==
inputs_3d.shape[0]*inputs_3d.shape[1]
297
298             losses_3d_train_eval.append(epoch_loss_3d_train_eval / N)
299             if semi_supervised:
300
301                 losses_traj_train_eval.append(epoch_loss_traj_train_eval / N)
302
303                 losses_2d_train_labeled_eval.append(epoch_loss_2d_train_labeled_eval /
N)
304
305                 # Evaluate 2D loss on unlabeled training set (in
evaluation mode)
306                 epoch_loss_2d_train_unlabeled_eval = 0
307                 N_semi = 0
308                 if semi_supervised:
309                     for cam, _, batch_2d in
semi_generator_eval.next_epoch():
310                         cam = torch.from_numpy(cam.astype('float32'))
311                         inputs_2d_semi =
torch.from_numpy(batch_2d.astype('float32'))
312                         if torch.cuda.is_available():
313                             cam = cam.cuda()
314                             inputs_2d_semi = inputs_2d_semi.cuda()
315
316                         predicted_3d_pos_semi = model_pos(inputs_2d_semi)
317                         predicted_traj_semi = model_traj(inputs_2d_semi)

```

```

316         if pad > 0:
317             target_semi = inputs_2d_semi[:, pad:-pad, :,
:2].contiguous()
318         else:
319             target_semi = inputs_2d_semi[:, :, :,
:2].contiguous()
320             reconstruction_semi =
project_to_2d(predicted_3d_pos_semi + predicted_traj_semi, cam)
321             loss_reconstruction_semi =
mpjpe(reconstruction_semi, target_semi)
322
323             epoch_loss_2d_train_unlabeled_eval +=
reconstruction_semi.shape[0]*reconstruction_semi.shape[1] \
324                                     *
loss_reconstruction_semi.item()
325             N_semi +=
reconstruction_semi.shape[0]*reconstruction_semi.shape[1]
326
losses_2d_train_unlabeled_eval.append(epoch_loss_2d_train_unlabeled_eval
/ N_semi)
327
328     elapsed = (time() - start_time)/60
329
330     if args.no_eval:
331         print('[%d] time %.2f lr %f 3d_train %f' % (
332             epoch + 1,
333             elapsed,
334             lr,
335             losses_3d_train[-1] * 1000))
336     else:
337         if semi_supervised:
338             print('[%d] time %.2f lr %f 3d_train %f 3d_eval %f
traj_eval %f 3d_valid %f '
339                 'traj_valid %f 2d_train_sup %f 2d_train_unsup %f
2d_valid %f' % (
340                 epoch + 1,
341                 elapsed,
342                 lr,
343                 losses_3d_train[-1] * 1000,
344                 losses_3d_train_eval[-1] * 1000,
345                 losses_traj_train_eval[-1] * 1000,
346                 losses_3d_valid[-1] * 1000,
347                 losses_traj_valid[-1] * 1000,
348                 losses_2d_train_labeled_eval[-1],
349                 losses_2d_train_unlabeled_eval[-1],
350                 losses_2d_valid[-1]))
351         else:
352             print('[%d] time %.2f lr %f 3d_train %f 3d_eval %f
3d_valid %f' % (

```

```

353         epoch + 1,
354         elapsed,
355         lr,
356         losses_3d_train[-1] * 1000,
357         losses_3d_train_eval[-1] * 1000,
358         losses_3d_valid[-1] * 1000))
359
360     # Decay learning rate exponentially
361     lr *= lr_decay
362     for param_group in optimizer.param_groups:
363         param_group['lr'] *= lr_decay
364     epoch += 1
365
366     # Decay BatchNorm momentum
367     momentum = initial_momentum * np.exp(-epoch/args.epochs *
np.log(initial_momentum/final_momentum))
368     model_pos_train.set_bn_momentum(momentum)
369     if semi_supervised:
370         model_traj_train.set_bn_momentum(momentum)
371
372     # Save checkpoint if necessary
373     if epoch % args.checkpoint_frequency == 0:
374         chk_path = os.path.join(args.checkpoint,
'epoch_{}.bin'.format(epoch))
375         print('Saving checkpoint to', chk_path)
376
377         torch.save({
378             'epoch': epoch,
379             'lr': lr,
380             'random_state': train_generator.random_state(),
381             'optimizer': optimizer.state_dict(),
382             'model_pos': model_pos_train.state_dict(),
383             'model_traj': model_traj_train.state_dict() if
semi_supervised else None,
384             'random_state_semi': semi_generator.random_state() if
semi_supervised else None,
385             }, chk_path)
386
387     # Save training curves after every epoch, as .png images (if
requested)
388     if args.export_training_curves and epoch > 3:
389         if 'matplotlib' not in sys.modules:
390             import matplotlib
391             matplotlib.use('Agg')
392             import matplotlib.pyplot as plt
393
394         plt.figure()
395         epoch_x = np.arange(3, len(losses_3d_train)) + 1
396         plt.plot(epoch_x, losses_3d_train[3:], '--', color='C0')

```

```

397         plt.plot(epoch_x, losses_3d_train_eval[3:], color='C0')
398         plt.plot(epoch_x, losses_3d_valid[3:], color='C1')
399         plt.legend(['3d train', '3d train (eval)', '3d valid
(eval)'])
400         plt.ylabel('MPJPE (m)')
401         plt.xlabel('Epoch')
402         plt.xlim((3, epoch))
403         plt.savefig(os.path.join(args.checkpoint, 'loss_3d.png'))
404
405         if semi_supervised:
406             plt.figure()
407             plt.plot(epoch_x, losses_traj_train[3:], '--',
color='C0')
408             plt.plot(epoch_x, losses_traj_train_eval[3:], color='C0')
409             plt.plot(epoch_x, losses_traj_valid[3:], color='C1')
410             plt.legend(['traj. train', 'traj. train (eval)', 'traj.
valid (eval)'])
411             plt.ylabel('Mean distance (m)')
412             plt.xlabel('Epoch')
413             plt.xlim((3, epoch))
414             plt.savefig(os.path.join(args.checkpoint,
'loss_traj.png'))
415
416             plt.figure()
417             plt.plot(epoch_x, losses_2d_train_labeled_eval[3:],
color='C0')
418             plt.plot(epoch_x, losses_2d_train_unlabeled[3:], '--',
color='C1')
419             plt.plot(epoch_x, losses_2d_train_unlabeled_eval[3:],
color='C1')
420             plt.plot(epoch_x, losses_2d_valid[3:], color='C2')
421             plt.legend(['2d train labeled (eval)', '2d train
unlabeled', '2d train unlabeled (eval)', '2d valid (eval)'])
422             plt.ylabel('MPJPE (2D)')
423             plt.xlabel('Epoch')
424             plt.xlim((3, epoch))
425             plt.savefig(os.path.join(args.checkpoint, 'loss_2d.png'))
426         plt.close('all')

```

Remarks

Evaluate（本部分不要求理解，只要会用就行）

Code Block

```
1  # Evaluate
2  def evaluate(test_generator, action=None, return_predictions=False,
   use_trajectory_model=False):
3      epoch_loss_3d_pos = 0
4      epoch_loss_3d_pos_procrustes = 0
5      epoch_loss_3d_pos_scale = 0
6      epoch_loss_3d_vel = 0
7      with torch.no_grad():
8          if not use_trajectory_model:
9              model_pos.eval()
10         else:
11             model_traj.eval()
12         N = 0
13         for _, batch, batch_2d in test_generator.next_epoch():
14             inputs_2d = torch.from_numpy(batch_2d.astype('float32'))
15             if torch.cuda.is_available():
16                 inputs_2d = inputs_2d.cuda()
17
18             # Positional model
19             if not use_trajectory_model:
20                 predicted_3d_pos = model_pos(inputs_2d)
21             else:
22                 predicted_3d_pos = model_traj(inputs_2d)
23
24             # Test-time augmentation (if enabled)
25             if test_generator.augment_enabled():
26                 # Undo flipping and take average with non-flipped version
27                 predicted_3d_pos[1, :, :, 0] *= -1
28                 if not use_trajectory_model:
29                     predicted_3d_pos[1, :, joints_left + joints_right] =
predicted_3d_pos[1, :, joints_right + joints_left]
30                 predicted_3d_pos = torch.mean(predicted_3d_pos, dim=0,
keepdim=True)
31
32             if return_predictions:
33                 return predicted_3d_pos.squeeze(0).cpu().numpy()
34
35             inputs_3d = torch.from_numpy(batch.astype('float32'))
36             if torch.cuda.is_available():
37                 inputs_3d = inputs_3d.cuda()
38             inputs_3d[:, :, 0] = 0
39             if test_generator.augment_enabled():
```

```

40         inputs_3d = inputs_3d[:1]
41
42         error = mpjpe(predicted_3d_pos, inputs_3d)
43         epoch_loss_3d_pos_scale +=
inputs_3d.shape[0]*inputs_3d.shape[1] * n_mpjpe(predicted_3d_pos,
inputs_3d).item()
44
45         epoch_loss_3d_pos += inputs_3d.shape[0]*inputs_3d.shape[1] *
error.item()
46         N += inputs_3d.shape[0] * inputs_3d.shape[1]
47
48         inputs = inputs_3d.cpu().numpy().reshape(-1,
inputs_3d.shape[-2], inputs_3d.shape[-1])
49         predicted_3d_pos = predicted_3d_pos.cpu().numpy().reshape(-1,
inputs_3d.shape[-2], inputs_3d.shape[-1])
50
51         epoch_loss_3d_pos_procrustes +=
inputs_3d.shape[0]*inputs_3d.shape[1] * p_mpjpe(predicted_3d_pos, inputs)
52
53         # Compute velocity error
54         epoch_loss_3d_vel += inputs_3d.shape[0]*inputs_3d.shape[1] *
mean_velocity_error(predicted_3d_pos, inputs)
55
56         if action is None:
57             print('-----')
58         else:
59             print('----'+action+'----')
60         e1 = (epoch_loss_3d_pos / N)*1000
61         e2 = (epoch_loss_3d_pos_procrustes / N)*1000
62         e3 = (epoch_loss_3d_pos_scale / N)*1000
63         ev = (epoch_loss_3d_vel / N)*1000
64         print('Test time augmentation:', test_generator.augment_enabled())
65         print('Protocol #1 Error (MPJPE):', e1, 'mm')
66         print('Protocol #2 Error (P-MPJPE):', e2, 'mm')
67         print('Protocol #3 Error (N-MPJPE):', e3, 'mm')
68         print('Velocity Error (MPJVE):', ev, 'mm')
69         print('-----')
70
71         return e1, e2, e3, ev
72
73
74     if args.render:
75         print('Rendering...')
76
77         input_keypoints = keypoints[args.viz_subject][args.viz_action]
[args.viz_camera].copy()
78         ground_truth = None
79         if args.viz_subject in dataset.subjects() and args.viz_action in
dataset[args.viz_subject]:

```

```

80         if 'positions_3d' in dataset[args.viz_subject][args.viz_action]:
81             ground_truth = dataset[args.viz_subject][args.viz_action]
82             ['positions_3d'][args.viz_camera].copy()
83             if ground_truth is None:
84                 print('INFO: this action is unlabeled. Ground truth will not be
85                 rendered.')
86
87             gen = UnchunkedGenerator(None, None, [input_keypoints],
88                                     pad=pad, causal_shift=causal_shift,
89                                     augment=args.test_time_augmentation,
90                                     kps_left=kps_left, kps_right=kps_right,
91                                     joints_left=joints_left, joints_right=joints_right)
92             prediction = evaluate(gen, return_predictions=True)
93             if model_traj is not None and ground_truth is None:
94                 prediction_traj = evaluate(gen, return_predictions=True,
95                                           use_trajectory_model=True)
96                 prediction += prediction_traj
97
98             if args.viz_export is not None:
99                 print('Exporting joint positions to', args.viz_export)
100                 # Predictions are in camera space
101                 np.save(args.viz_export, prediction)
102
103             if args.viz_output is not None:
104                 if ground_truth is not None:
105                     # Reapply trajectory
106                     trajectory = ground_truth[:, :1]
107                     ground_truth[:, 1:] += trajectory
108                     prediction += trajectory
109
110                     # Invert camera transformation
111                     cam = dataset.cameras()[args.viz_subject][args.viz_camera]
112                     if ground_truth is not None:
113                         prediction = camera_to_world(prediction,
114                                                         R=cam['orientation'], t=cam['translation'])
115                         ground_truth = camera_to_world(ground_truth,
116                                                         R=cam['orientation'], t=cam['translation'])
117                     else:
118                         # If the ground truth is not available, take the camera
119                         extrinsic params from a random subject.
120                         # They are almost the same, and anyway, we only need this for
121                         visualization purposes.
122                         for subject in dataset.cameras():
123                             if 'orientation' in dataset.cameras()[subject]
124                             [args.viz_camera]:
125                                 rot = dataset.cameras()[subject][args.viz_camera]
126                                 ['orientation']
127                                 break
128                         prediction = camera_to_world(prediction, R=rot, t=0)

```



```

160         poses_3d = dataset[subject][action]['positions_3d']
161         assert len(poses_3d) == len(poses_2d), 'Camera count
mismatch'
162         for i in range(len(poses_3d)): # Iterate across cameras
163             out_poses_3d.append(poses_3d[i])
164
165         stride = args.downsample
166         if stride > 1:
167             # Downsample as requested
168             for i in range(len(out_poses_2d)):
169                 out_poses_2d[i] = out_poses_2d[i][::stride]
170                 if out_poses_3d is not None:
171                     out_poses_3d[i] = out_poses_3d[i][::stride]
172
173         return out_poses_3d, out_poses_2d
174
175     def run_evaluation(actions, action_filter=None):
176         errors_p1 = []
177         errors_p2 = []
178         errors_p3 = []
179         errors_vel = []
180
181         for action_key in actions.keys():
182             if action_filter is not None:
183                 found = False
184                 for a in action_filter:
185                     if action_key.startswith(a):
186                         found = True
187                         break
188                 if not found:
189                     continue
190
191             poses_act, poses_2d_act = fetch_actions(actions[action_key])
192             gen = UnchunkedGenerator(None, poses_act, poses_2d_act,
193                                     pad=pad, causal_shift=causal_shift,
194                                     augment=args.test_time_augmentation,
195                                     kps_left=kps_left,
196                                     kps_right=kps_right, joints_left=joints_left, joints_right=joints_right)
197             e1, e2, e3, ev = evaluate(gen, action_key)
198             errors_p1.append(e1)
199             errors_p2.append(e2)
200             errors_p3.append(e3)
201             errors_vel.append(ev)
202
203         print('Protocol #1 (MPJPE) action-wise average:',
204               round(np.mean(errors_p1), 1), 'mm')
205         print('Protocol #2 (P-MPJPE) action-wise average:',
206               round(np.mean(errors_p2), 1), 'mm')

```

```
203         print('Protocol #3 (N-MPJPE) action-wise average:',  
round(np.mean(errors_p3), 1), 'mm')  
204         print('Velocity      (MPJVE) action-wise average:',  
round(np.mean(errors_vel), 2), 'mm')  
205  
206         if not args.by_subject:  
207             run_evaluation(all_actions, action_filter)  
208         else:  
209             for subject in all_actions_by_subject.keys():  
210                 print('Evaluating on subject', subject)  
211                 run_evaluation(all_actions_by_subject[subject],  
action_filter)  
212                 print('')
```

Remarks
