HP3C 2022



Modern Distributed Data-Parallel Large-Scale Pre-training Strategies For NLP models


Hao Bai

Junior, Computer Engineering
National Center For Supercomputing Applications, UIUC
Champaign, Illinois, USA

Author & Supervisor

- AUTHOR | Jack Bai (Junior UG, CompE, UIUC)
 - Take a look at my profile at https://www.jackgethome.com/
 - My paper preprint is on ArXiV: https://arxiv.org/pdf/2206.06356.pdf
- ADVISOR | Volodymyr Kindratenko (Assistant Director at NCSA)
 - Research interests mainly in HPC
 - Take a look at his profile at https://ece.illinois.edu/about/directory/faculty/kindrtnk
 - Has lots of supercomputers, much acknowledge to my prof

Why do we pick an NLP pre-trained model?



Pain...

I'm sure everyone who used PyTorch or TensorFlow experiences this kind of pain.

NVIDIA-SMI 375.66 Driver Version:						ion: 375	75.66			
GPU Fan								Uncorr. ECC Compute M.		
0 30%	GeForce G 53C P		off W / 250W	0000:02 8779M:		0ff 172MiB	 6%	N/A Default		
1 30%	GeForce G 53C P		off W / 250W			Off L172MiB		N/A Default		
2 31%	GeForce G 55C P		off W / 250W			Off L172MiB		N/A Default		
3 28%	GeForce G 50C P			0000:84 8989M:			•	N/A Default		
_								±		
Proc GPU	esses: PID	Туре	Process	name				GPU Memory Usage		
===== 0 1 2 3	85736 85736	C C	python python python python					8777MiB 8661MiB 8661MiB 8661MiB 8987MiB		

Dream?

How to improve the volatile GPU utility like this?

```
kiongyu@ubuntu:~$ watch nvidia-smi
        47741 C ./mtcnn c
                                                           461
Every 2.0s: nvidia-smi
ri Jun 29 11:25:43 2018
 NVIDIA-SMI 390.48
                   Driver Version: 390.48
 GPU Name Persistence-M Bus-Id Disp.A Volatile Uncorr. E
 Fan Temp Perf Pwr:Usage/Cap | Memory-Usage | GPU-Util Compute
  0 Tesla M40
                            00000000:03:00.0 Off
                     On l
  0% 57C P0 217W / 250W | 10806MiB / 11448MiB |
                                                          Defau
  1 Tesla M40
                            00000000:04:00.0 Off
                      On I
                             9992MiB / 11448MiB
           P0 200W / 250W
                                                   99%
                                                          Defau
  2 Tesla M40
                           00000000:84:00.0 Off
  0% 56C P0 222W / 250W | 9955MiB / 11448MiB |
                                                          Defau
  3 Tesla M40
                      On | 00000000:85:00.0 Off |
           P0 203W / 250W
                             9960MiB / 11448MiB
                                                          Defau
                                                        GPU Memo
 Processes:
  GPU
                     Process name
               Type
                                                        Usage
        35346
                  C python2
                                                           110
        55323
                     python
                                                          106731
        55323
                     python
                                                          99701
```

Model Parallel And Data Parallel

Not exactly a dream.


We have model parallel and data parallel to help.

Model parallel: parts of model on different GPUs.

Data parallel: scatter and gather data on different GPUs.

Data Parallel In PyTorch

- Let's take PyTorch for example.
- Who encountered to use nn.DataParallel library?
- I'm sure you're worried about the performance. When you're doing a Kaggle, you get anxious about your code.



Forward and Backward passes with torch.nn.DataParallel

Bottleneck

- It's not exacly your fault. We've got similar results.
- Why? Because it's Single Parameter Server training. Can you get the bottleneck?
- Yes, it's even slower than the baseline with only 1 GPU. Don't use it that way!




Figure 3: Conceptual architecture of Single Parameter Server parallization approach.

Parallel Type	PrmSrv	GPU0	GPU1	GPU2	GPU3	Total
Baseline	0	85%	0	0	0	0.94
SPS	1	17%	13%	11%	14%	0.55

nn.DistributedDataParallel (DPS)

- Distributed Data Parallel (DPS) helps with the problem.
- No surprise. Think about why it's faster. Does it solve the bottleneck here?
- All-reduce algorithm to synchronize the training process.




Figure 4: Conceptual architecture of Distributed Parameter Server parallization approach.

Parallel Type	PrmSrv	GPU0	GPU1	GPU2	GPU3	Total
Baseline	0	85%	0	0	0	0.94
SPS	1	17%	13%	11%	14%	0.55
DPS	4	94%	94%	89%	94%	3.71


Good approches come with price...

- Good on one node, hard on multiple nodes.
- Because you have to launch the script on every node.
- Any frameworks solving this problem?


Horovod

- Yes! Let's use Horovod, a distributed deep learning framework.
- Install it on all the nodes, so they share the same backend (MPI).
- Launch on one node, then all the nodes can work together.
- Ring-allreduce: optimized synchronization strategy.






Comparison of DPS and Horovod on one node



(a) Loss curve for DPS (after adding the memory cleaning code) and Horovod, both with respect to a batch size of 8 and 16.

- Look into source code: Horovod is basically a wrapper around DPS.
- DPS is faster on one node, but allreduce introduces asymmetricity.
- Horovod is slower on one node, but has built-in cache cleaning techniques and ring-allreduce algorithm eliminates asymmetricity.

Big brother: Apex mixed Precision (fp16+fp32)



(d) Loss curve for DPS and Horovod before and after applying Apex fp16-fp32 mixed training.

- Extreme performance boosting: 2x faster for DPS, 4x faster for Horovod (i.e. nice compatibility with Horovod)
- Half the memory used to store batches, so DPS 4*4 can now run!
- Requires TensorCore to use. Try to pursuade your boss to buy one for you!
- V100+ (V100, A100...)
- Details look at the GPU specs page.

Code? Open-source!

```
n_ctx = model_config.n_ctx
if args.bpe_token:
    full_tokenizer = get_encoder(args.encoder_json, args.vocab_bpe)
else:
    full_tokenizer = tokenization_bert.BertTokenizer(vocab_file=args.to
full_tokenizer.max_len = 999999
# construct GPU network
torch.distributed.init_process_group(
    backend='nccl'
local_rank = torch.distributed.get_rank()
torch.cuda.set_device(local_rank)
device = torch.device("cuda", local_rank)
######
print('using device:', device)
```

- Feel free to copy and paste.
- Easy to follow! '#####' is used to mark the parallel code added to the initial code.
- https://github.com/BiEchi/Distri butedTrainingGPT2

Thank you!

+ -	NVID			9 Dri		 rsion: 352.79	+ 	
		Name		Persiste	nce-MI	Bus-Id Disp.A Memory-Usage		
						0000:04:00.0 Off 11769MiB / 12287MiB		
	1 23%					0000:05:00.0 Off 11768MiB / 12287MiB		N/A Default
 - -	2 22%	51 C	P2	227W /	250W I	0000:06:00.0 Off 11768MiB / 12287MiB		N/A Default
	3 29%	GeForce	GTX	TIT	On I	0000:07:00.0 Off 11768MiB / 12287MiB		N/A Default
 - -	4 22%					0000:0A:00.0 Off 11768MiB / 12287MiB		N/A Default
	5 23%					0000:0B:00.0 Off 11768MiB / 12287MiB		N/A Default
- -	6 22%	GeForce 56C				0000:0C:00.0 Off 11769MiB / 12287MiB		N/A Default
	7 22%					0000:0D:00.0 Off 11768MiB / 12287MiB		N/A N/A Default