Caleta: An Evidence-Oriented Trust Layer for Reproducible Local Large Language Model Inference

Technical Preprint — Software Validation Manuscript

Joan-Marc Fisa
BiVelio Inc
jmfisa@bivelio.com

28 October 2026

Copyright © 2026 BiVelio Inc. This manuscript is licensed under Creative Commons Attribution 4.0 International (CC BY 4.0).

Corresponding author: Joan-Marc Fisa (jmfisa@bivelio.com).

Software reference implementation: Caleta v0.1.0, Apache-2.0.

Zenodo DOI: 10.5281/zenodo.23761755.

Status: non-peer-reviewed technical preprint.

Abstract

Local large language model (LLM) inference is frequently described as private, verified, or reproducible without separating the technical claims behind those terms. A local deployment can still execute an unintended artifact, inherit unsafe configuration, expose unnecessary API routes, or publish aggregate performance results that omit failed runs and methodological differences. This paper presents **Caleta**, an Apache-2.0 process supervisor and evidence layer around llama.cpp rather than a new inference engine. Caleta combines versioned model manifests, exact-size and SHA-256 verification, controlled backend construction, a restricted OpenAI-compatible proxy, prompt-free execution records, reproducible benchmark reports, and a small conformance suite. Its research contribution is the composition of these mechanisms into explicit, machine-readable contracts that distinguish integrity from authenticated provenance and privacy controls from operating-system isolation. We evaluate the reference implementation through strict static checks, fifteen unit tests, and a deterministic end-to-end experiment covering verification, process supervision, authentication, model listing, server-sent events, conformance, and benchmarking. The experiment validates software behavior, not model accuracy, inference throughput, or llama.cpp compatibility with real GGUF artifacts. We therefore present no real-model performance claim. The resulting design offers a reproducible foundation for studying trustworthy local inference while making the remaining threats—unsigned manifests, time-of-check/time-of-use replacement, lack of TLS and OS-enforced egress isolation, and incomplete API conformance—explicit subjects for future work.

Keywords: local inference; large language models; reproducibility; software supply chain; privacy engineering; benchmarking; provenance; llama.cpp.

1 Introduction

The deployment of LLMs on local machines is motivated by latency, cost, data-control, availability, and operational-sovereignty requirements. Open-source runtimes such as llama.cpp, MLX-based systems, Ollama, Uzu, and BaseRT address important parts of this problem, including hardware coverage, model packaging, ease of use, and optimized execution [1, 2, 3, 4, 5]. However, the ability to execute a model locally does not by itself answer several operational questions: Which bytes were executed? Which backend and runtime options were active? Which interfaces were exposed? What was measured, and which runs failed? What evidence remains after execution?

These questions are often conflated under broad claims of privacy or verification. A cryptographic digest can establish correspondence between an artifact and an expected value, but not the identity of the publisher who supplied that value. An offline backend flag can request network inactivity, but it is not equivalent to an operating-system firewall. A local HTTP listener can avoid wide-area exposure while remaining reachable by other local processes. Similarly, a throughput number without artifact identity, generation parameters, cold/warm separation, and failed-run accounting is insufficient to reproduce an experiment.

Caleta addresses this narrower but consequential layer around the inference engine. It deliberately does not implement tensor kernels, a model format, or a new serving API. Instead, it wraps llama.cpp's `llama-server` with a small trust boundary and emits versioned evidence. This choice preserves GGUF interoperability [9] and allows the measurement and conformance contracts to be reused independently of the supervisor.

The manuscript makes three deliberate evidentiary restrictions. First, it reports only tests actually executed on the reference implementation. Second, its end-to-end backend is deterministic mock software, not an LLM; it validates orchestration and protocol behavior rather than inference. Third, it treats authenticated provenance, OS-level containment, real-model benchmarking, and broad API compatibility as future experimental work, not implied properties of the current system.

2 Research Questions and Contributions

We organize the work around three research questions:

RQ1:
How can a local inference launcher make artifact integrity and runtime configuration explicit without replacing the inference engine?

RQ2:
Which operational and benchmarking evidence can be emitted without persisting prompts and responses by default?

RQ3:
To what extent can deterministic tests validate the resulting supervisor and proxy while avoiding unsupported claims about real-model execution?

The paper offers four contributions:

1. A composable architecture that combines artifact verification, backend supervision, restricted proxying, execution records, benchmarking, and conformance under explicit security boundaries.
2. Versioned manifest and report contracts that separate declared provenance, observed integrity, runtime configuration, and measurement limitations.
3. Benchmark definitions that preserve raw failures, distinguish cold startup from warm requests, and avoid converting unavailable measurements into zero-valued results.

4. A reproducible software-validation experiment and a threat-to-validity analysis identifying the evidence still required for real-world performance or security claims.

The contribution is therefore not a universal performance improvement or a formal proof of privacy. It is a reference design for bounded, inspectable claims in local inference systems.

3 Background and Related Work

3.1 Local inference runtimes

llama.cpp provides broad GGUF and hardware support and includes an HTTP server with offline, authentication, and cross-origin resource sharing (CORS) options [1]. Caleta does not assume that these upstream controls are absent. Its purpose is to construct a consistent subset of configuration, remove selected inherited overrides, restrict externally reachable routes, and produce execution and measurement evidence around that configuration.

Ollama emphasizes installation and model-distribution ergonomics [3]; MLX LM integrates local inference with Apple Silicon and the Hugging Face ecosystem [2]; Uzu implements a Rust inference engine with platform-specific optimization and a broader application ecosystem [4]. BaseRT demonstrates the importance of native Metal optimization and phase-specific performance evaluation on Apple Silicon [5]. These projects primarily address execution, optimization, packaging, or developer experience. Caleta is complementary: its schemas and conformance checks could be implemented by another runtime without adopting its process supervisor.

The BaseRT preprint also illustrates why performance claims must be scoped by hardware, model family, quantization, and inference phase. Its results concern the configurations evaluated by its authors. They are neither replicated in this study nor used as evidence for Caleta's performance.

3.2 Integrity, provenance, and attestation

Secure software distribution requires more than file hashing. SHA-256 provides a deterministic digest used here to compare artifact contents against a manifest [6]. The security of that comparison depends on how the expected digest was obtained. Supply-chain frameworks such as SLSA distinguish provenance and build properties from the simplified notion that a checksum alone establishes trust [7].

Caleta v0.1.0 implements integrity comparison and provenance declaration. It does not implement signed manifests, transparency logs, remote attestation, or independently signed execution records. We reserve *authenticated provenance* for mechanisms that establish the identity of the party supplying an artifact or manifest through a trusted channel.

3.3 Reproducible performance evaluation

Local inference comprises at least model initialization, prompt processing, and autoregressive decoding. Combining these stages into one number obscures different system behaviors. Meaningful comparisons must hold artifact identity, quantization semantics, prompts, templates, decoding parameters, backend revisions, hardware, and power conditions as constant as practical. They must also distinguish cold starts from warm requests and describe how tokens and timing events are counted.

Caleta operationalizes part of this methodology in JSON. It does not measure output quality, energy, thermal throttling, GPU memory, or pure kernel time. These omissions are represented as limitations rather than estimated values.

4 Design Principles

The architecture follows five principles:

Composition over replacement. The reference backend remains llama.cpp. Caleta does not duplicate its kernels, model conversion, or hardware backends.

Verification before execution. `serve` and `bench` refuse to start after a missing artifact, size mismatch, digest mismatch, or read failure.

Least exposed interface by default. Both the public proxy and backend default to loopback. The backend is never intentionally exposed on a public listener. Only health, model listing, and chat completions are proxied.

Evidence with bounded meaning. Every contract names what it records and what it does not establish. A verification report is labeled `integrity_only`; execution records are unsigned operational evidence, not attestations.

Reproducibility without prompt retention by default. Configuration and measurements are retained, while request and response bodies are not logged. Benchmarks store a prompt digest and length unless the operator explicitly requests prompt inclusion.

5 System Architecture

5.1 Components and data flow

Figure 1 shows the principal boundary. A client communicates with the Caleta proxy. The proxy replaces external authorization with a random per-launch internal credential and forwards only supported requests to llama-server. The backend binds to IPv4 loopback and receives a verified local GGUF path.




Figure 1: Caleta process and evidence boundary. The diagram does not imply OS-level sandboxing.

The implementation separates manifest parsing, verification, backend lifecycle, HTTP serving, execution records, diagnostics, benchmarking, and conformance. This decomposition permits

unit testing without a model and keeps the command-line interface from becoming the sole integration point.

5.2 Manifest and artifact verification

A manifest declares a schema identifier, model identifier, license, source, artifact path, expected digest and size, backend kind, and runtime parameters. Relative artifact and explicit backend paths resolve against the manifest directory rather than the caller's working directory. The source and license are declarations; they are not inferred from file contents.

For artifact bytes a, declared digest h, and declared byte length b, execution proceeds only if

$$|a| = b \quad \wedge \quad \mathrm{SHA256}(a) = h. \tag{1}$$

Verification streams data in 1 MiB blocks, so artifact size does not determine verifier memory usage. When a backend digest is pinned, an explicit backend path is required to avoid treating ambiguous `PATH` resolution as precise provenance.

This check does not establish that the manifest is truthful, that the model is safe to parse, or that the file cannot be replaced between verification and backend loading. Signed manifests and immutable or otherwise protected storage are therefore separate requirements.

5.3 Backend supervision

Before launch, Caleta removes inherited `LLAMA_ARG_*` and `LLAMA_API_KEY` variables that could alter the declared boundary. It generates a fresh 32-byte random internal credential, passes it through the backend environment, and constructs arguments for model, loopback host, ephemeral port, alias, offline mode, disabled Web UI, context size, GPU layers, and optional thread count.

The manifest validator rejects additional arguments that would replace the model or listener, alter credentials, or enable agent tools. This is a reviewed policy for known options, not a universal proof against every future upstream flag. Readiness requires an authenticated health response within a timeout. Premature child exit and readiness timeout are errors. Shutdown terminates and waits for the child, with kill-on-drop as an additional process-lifetime safeguard.

Two residual races remain: another local process may bind a reserved ephemeral port before the child uses it, and an artifact may be replaced after verification. Hostile-local-user deployments require stronger OS-specific mechanisms.

5.4 Restricted HTTP proxy

The public server exposes only `/health`, `/v1/models`, and `/v1/chat/completions`, a deliberately small subset of the OpenAI-compatible API [8]. Non-loopback listeners require a public bearer key of at least sixteen characters, although high-entropy random secrets are recommended. Credential comparison is constant-time. Request bodies are limited to 16 MiB; responses, including server-sent events (SSE), are streamed rather than collected.

The proxy removes hop-by-hop headers and all upstream CORS response headers. Only Caleta's explicit origin allowlist can produce CORS headers. Wildcard origins are rejected. The server provides plain HTTP; remote deployments require a TLS reverse proxy, SSH tunnel, or an appropriately controlled private network. CORS is not an authentication mechanism and does not protect non-browser clients.

6 Operational Evidence and Measurement Contracts

6.1 Execution records

Optional execution records use the schema `caleta.dev/execution/v1`. They capture version, model identity, paths, artifact and backend digests, listener configuration, loopback/offline flags, CORS policy, arguments, and limitations. Prompt and response bodies are excluded. The record is generated by the same process whose behavior it describes and is unsigned; it supports inspection and reproduction but does not prove execution to a third party.

6.2 Benchmark methodology

A benchmark verifies the artifact, starts one backend, measures cold startup to authenticated readiness, executes warm-up requests, and then measures warm requests in that process. Failed measured requests remain in the report and are excluded only from aggregates of successful measurements. Warm-up failures are logged but are not retained as raw per-run records. A report is written even when all measured requests fail.

For a request sent at t_0, the first content-bearing SSE event arrives at t_1, and the last such event arrives at t_n. Time to first token is defined operationally as

$$\mathrm{TTFT} = t_1 - t_0. \tag{2}$$

It includes local HTTP and queueing overhead and ignores empty role-only events. If the backend reports c completion tokens and $c \geq 2$, decode throughput is

$$\mathrm{decode_tps} = \frac{c - 1}{t_n - t_1}. \tag{3}$$

Observed prefill throughput is reported prompt tokens divided by TTFT; it is not a pure kernel measurement. Inter-event latency is computed over arrivals of content-bearing SSE events. Because backend chunking need not map one event to one tokenizer token, this metric is not claimed to be exact per-token latency in all backends.

The schema `caleta.dev/benchmark/v1` stores raw runs, token usage, estimated-token flags, cold startup, configuration, environment, failures, and limitations. On Linux, main-process resident memory is sampled approximately every 50 ms through `/proc/PID/status`; this excludes GPU memory and child processes and can miss short peaks. Missing metrics remain null.

6.3 Conformance

The conformance command checks a deliberately small OpenAI-compatible contract: model listing returns a data array, non-streaming chat contains message content in the expected structure, and streaming chat uses `text/event-stream`, emits deltas, and terminates with `data: [DONE]`. The schema is `caleta.dev/conformance/v1`. Passing does not certify tool calls, structured output, multimodality, cancellation, backpressure, fragmented SSE handling, or complete OpenAI compatibility.

7 Implementation and Reproducibility

The reference implementation is written in Rust and uses Tokio, Axum, Reqwest, Serde, and SHA-2. The package declares Rust 1.88 as its minimum version and Apache-2.0 as its software

license. Model artifacts and llama.cpp retain their respective licenses. Caleta does not bundle a model or llama.cpp binary.

A minimal local workflow is:

```
cargo build --release --locked
caleta doctor --backend /path/to/llama-server
caleta verify model.toml
caleta serve model.toml --record-out execution.json
caleta bench model.toml --output benchmark.json \
  --runs 5 --warmup 1 --max-tokens 64 --seed 42
caleta conformance --url http://127.0.0.1:8080 \
  --output conformance.json
```

The canonical public artifact location is:

https://github.com/BiVelio/caleta

The repository contains the source, lockfile, manifests, and deterministic mock. Future experimental publications must also include raw reports and exact command transcripts.

8 Evaluation

8.1 Experimental scope

The evaluation tests software mechanisms corresponding to RQ1–RQ3. It does not estimate inference quality or performance. The end-to-end backend is a deterministic Python process that accepts the subset of llama-server arguments used by Caleta, requires the internal credential, serves health and model routes, and returns fixed chat and SSE responses. The model artifact is a 45-byte placeholder whose contents are not a valid GGUF model. This design makes protocol and lifecycle behavior repeatable without downloading weights or depending on GPU availability.

The local validation reported here was executed on Windows with rustc 1.94.1, Cargo 1.94.1, and Python 3.14.0. A subsequent hosted CI run on Ubuntu, macOS, and Windows is reported separately below.

8.2 Procedure

The validation sequence was:

```
cargo fmt --all -- --check
cargo clippy --locked --all-targets -- -D warnings
cargo test --locked
cargo build --locked
CALETA_BIN=target/debug/caleta python3 tests/e2e_mock.py
```

The end-to-end scenario constructs a temporary artifact and manifest, computes their digests, and executes verification. It starts the supervised service, checks unauthenticated rejection, performs authorized model listing and streaming chat, and runs the conformance command. It then executes one warm-up and two measured benchmark requests and inspects the resulting JSON. The Unix branch of the scenario validates graceful interruption and the resulting prompt-free execution record; that branch was not executed in the local Windows run. The Windows scenario uses forced process-tree shutdown for the mock and does not claim graceful-shutdown or execution-record coverage.

8.3 Results

All reported checks completed successfully after correcting platform-specific implementation and test issues: an unused non-Linux process identifier in the benchmark module rejected by strict Clippy, and Windows handling of TOML paths, executable mock launching, and mock-process shutdown in the test harness. Table 1 maps outcomes to the claims they support.

Check	Observed result	Supported interpretation
Formatting	Pass	Source conforms to Rust formatting.
Clippy, all targets	Pass with warnings denied	No emitted lint warnings under the configured toolchain.
Unit tests	15 passed, 0 failed	Tested manifest, digest, SSE, percentile, authentication, proxy, and exposure cases behave as expected.
Locked build	Pass	Package builds with the committed dependency resolution.
Verification E2E	Pass	Exact size/digest and pinned mock backend are accepted by the workflow.
Serve/authentication E2E	Pass	Supervised proxy starts; missing public credentials are rejected; authorized models and chat requests succeed.
SSE/conformance E2E	Pass	The tested stream and three conformance contracts pass against the deterministic backend.
Benchmark E2E	2 successful runs	Raw successful-run records and model digest are emitted; no prompt text is stored by default.
Real GGUF inference	Not run	No claim about model loading, output quality, hardware compatibility, or performance.

Table 1: Local software-validation outcomes and their bounded interpretation.

8.4 Hosted multi-platform confirmation

After the local validation, GitHub Actions run 40758287817 completed successfully at source revision `d898dad904ccabbff5af40dd5906e98fd0ee6369`. The Ubuntu, macOS, and Windows test jobs passed, as did the separate formatting and Clippy job. The Ubuntu and macOS end-to-end runs included graceful-shutdown execution records; the Windows run used forced mock-process shutdown. This confirms the same mock-based contracts across the three hosted operating systems, but it does not add real-model evidence.

For RQ1, the implementation demonstrates a concrete composition of manifest validation, streamed integrity verification, controlled backend construction, and restricted proxying. For RQ2, the local Windows experiment validates benchmark output without default prompt persistence, while the hosted Unix runs validate prompt-free execution records. For RQ3, deterministic tests establish the tested software paths while their inability to support real-model claims confirms the need to state evaluation scope explicitly.

No tokens-per-second result from the mock is scientifically meaningful. Mock timing is intentionally excluded from the performance claims.

9 Security and Privacy Analysis

Table 2 summarizes the implemented controls and residual risks. The central analytical requirement is to avoid converting a control in one layer into a guarantee about the whole system.

Threat or ambiguity	Current control	Residual risk or non-claim
Artifact substitution	Exact size and SHA-256 before serve/bench	Trusted digest distribution and post-check replacement remain unresolved.
Backend substitution	Optional explicit-path digest	Unpinned PATH resolution remains possible and is reported as such.
Inherited reconfiguration	Remove selected llama.cpp environment options	Other host variables, drivers, and future upstream options remain relevant.
Unauthorized network API use	Bearer authentication outside loopback	No integrated TLS; secret storage and transport are operator responsibilities.
Permissive upstream CORS	Strip upstream CORS; explicit local allowlist	CORS does not authenticate non-browser clients.
Backend network access	Loopback listener and offline request	No OS-enforced outbound-network denial.
Prompt retention by Caleta	No request/response logs; prompt digest by default	Clients, backend, OS swap, crash reports, and other processes are separate.
Misleading execution evidence	Versioned prompt-free JSON	Records are unsigned and are not remote attestations.

Table 2: Security controls and residual risks in Caleta v0.1.0.

A fully malicious host operating system, privileged local attacker, compromised Caleta binary, or malicious native backend is outside the containment claimed by this version. Model parsing occurs inside llama.cpp, so a matching digest cannot make an untrusted GGUF safe to parse. Loopback also is not a complete security boundary against other local processes.

Accordingly, we define the supported privacy claim narrowly: Caleta adds no telemetry or prompt history, avoids logging request and response bodies, requests offline backend behavior, and limits backend network listening to loopback. It does not claim that the complete host cannot disclose data.

10 Threats to Validity

Construct validity. Integrity, declared provenance, authenticated provenance, privacy, and safety are distinct constructs. The implementation and reports use separate terms, but users could still overinterpret the word "verified." The `integrity_only` label and explicit limitations mitigate rather than eliminate this risk.

Internal validity. The mock backend is deterministic and suitable for orchestration tests, but it does not reproduce llama.cpp argument semantics, GGUF parsing, model initialization, tokenization, or hardware behavior. A defect visible only with a real backend would not be detected. The Windows mock uses forced process-tree shutdown, so graceful-shutdown evidence is platform-specific.

External validity. Local Windows validation and hosted mock-based CI on Ubuntu, macOS, and Windows cannot establish correctness across backend revisions, real model families, hardware accelerators, or adversarial conditions. The hosted run broadens operating-system evidence for the tested contracts, but it does not reduce the need for real-model and adversarial evaluation.

Reliability. The committed lockfile, fixed commands, deterministic responses, and versioned schemas support repetition. Future public artifacts must include exact source revisions, backend builds, manifest files, raw JSON, operating-system details, and hardware metadata.

Performance validity. No real-model performance experiment has been conducted. The current study cannot estimate proxy overhead, cold-start distributions, prefill or decode throughput, memory use, energy, thermal effects, or output quality. No comparative ranking is made.

11 Research Agenda

The next stage must add evidence rather than broaden marketing language. We identify four ordered directions.

11.1 Real-model experimental matrix

A preregistered matrix should pin at least one redistributable GGUF artifact and llama.cpp revision per claimed operating system. Experiments should record model source and digest, quantization, context, prompt template, seed, temperature, hardware, power state, backend options, and Caleta revision. Direct-backend and proxied measurements should estimate overhead with repeated independent runs and uncertainty intervals. Raw successful and failed runs should be published.

11.2 Authenticated provenance and release evidence

Signed manifests, protected update channels, release attestations, and independently reproducible builds should be evaluated as separate mechanisms. Acceptance tests must demonstrate signature verification and failure under modification. A software bill of materials may complement these controls but cannot replace them.

11.3 Operating-system containment

Network and filesystem restrictions require platform-specific enforcement and adversarial tests. A backend flag must not be reported as a sandbox. The acceptance criterion is a demonstrated blocked outbound connection and denied unauthorized resource access under the stated threat model.

11.4 Protocol and measurement robustness

Conformance should expand to fragmented SSE, cancellation, concurrent requests, backpressure, structured outputs, and tool calls only when each contract is implemented and tested. Measurement research should add calibrated energy, GPU and process-tree memory, thermal state, and quantization-quality evaluation without conflating their definitions across platforms.

12 Conclusion

Caleta explores a complementary layer in the local-LLM stack: making artifact identity, runtime configuration, exposed interfaces, and measurement methodology explicit and machine-readable. Its design avoids duplicating optimized runtimes and instead composes integrity checks, supervision, restricted proxying, prompt-free operational evidence, benchmarking, and conformance around llama.cpp.

The local and hosted multi-platform evaluations validate the reference software's tested behavior and identify concrete platform issues that were corrected. They do not validate real-model inference or performance. This distinction is central to the contribution: trustworthy local inference requires claims whose scope is visible in both documentation and artifacts. Caleta provides an initial open implementation of that principle and a concrete basis for future real-model, provenance, containment, and measurement research.

Author and Intellectual Property

Author and corresponding author: Joan-Marc Fisa, BiVelio Inc, jmfisa@bivelio.com.
Manuscript copyright and license: Copyright © 2026 BiVelio Inc. Distributed under CC BY 4.0; attribution must identify Joan-Marc Fisa as author and BiVelio Inc as copyright holder.
Reference software license: Apache License 2.0. Third-party software and model artifacts retain their own licenses. The software license does not grant trademark rights in Caleta or BiVelio.

Data and Code Availability

The reference implementation, test harness, documentation, and release runbook are available in the Caleta repository at https://github.com/BiVelio/caleta. The archival preprint record is assigned DOI 10.5281/zenodo.23761755. Future experimental claims must be accompanied by their raw reports and reproducibility materials.

References

[1] ggml-org. llama.cpp: LLM inference in C/C++. https://github.com/ggml-org/llama.cpp, accessed 28 October 2026.

[2] Apple Machine Learning Research. MLX LM: LLM inference with MLX. https://github.com/ml-explore/mlx-lm, accessed 28 October 2026.

[3] Ollama contributors. Ollama: local model execution and distribution. https://github.com/ollama/ollama, accessed 28 October 2026.

[4] Mirai contributors. Uzu: a Rust large language model inference engine. https://github.com/trymirai/uzu, accessed 28 October 2026.

[5] Prabod Rathnayaka, Fabian Waschkowski, and Lukas Wesemann. BaseRT: Best-in-Class LLM Inference on Apple Silicon via Native Metal. arXiv:2607.00501 [cs.CL], 2026. https://arxiv.org/abs/2607.00501.

[6] National Institute of Standards and Technology. FIPS PUB 180-4: Secure Hash Standard (SHS). 2015. https://csrc.nist.gov/pubs/fips/180-4/upd1/final.

[7] OpenSSF and SLSA contributors. Supply-chain Levels for Software Artifacts (SLSA) Specification. https://slsa.dev/spec/, accessed 28 October 2026.

[8] OpenAI. API Reference: Models and Chat Completions. https://platform.openai.com/docs/api-reference, accessed 28 October 2026.

[9] ggml-org. GGUF model format specification. https://github.com/ggml-org/ggml/blob/master/docs/gguf.md, accessed 28 October 2026.