

Blockchain Security | Smart Contract Audits | KYC



Play Basketball to earn

Audit

Security Assessment 20. May, 2022



Disclaimer	3
Description	5
Project Engagement	5
Logo	5
Contract Link	5
Methodology	7
Used Code from other Frameworks/Smart Contracts (direct imports)	8
Tested Contract Files	9
Source Lines	10
Risk Level	10
Capabilities	11
Inheritance Graph	12
CallGraph	13
Scope of Work/Verify Claims	14
Modifiers and public functions	20
Source Units in Scope	22
Critical issues	23
High issues	23
Medium issues	23
Low issues	23
Informational issues	24
Audit Comments	25
SWC Attacks	26

Disclaimer

<u>SolidProof.io</u> reports are not, nor should be considered, an "endorsement" or "disapproval" of any particular project or team. These reports are not, nor should be considered, an indication of the economics or value of any "product" or "asset" created by any team. SolidProof.io do not cover testing or auditing the integration with external contract or services (such as Unicrypt, Uniswap, PancakeSwap etc'...)

SolidProof.io Audits do not provide any warranty or guarantee regarding the absolute bug- free nature of the technology analyzed, nor do they provide any indication of the technology proprietors. SolidProof Audits should not be used in any way to make decisions around investment or involvement with any particular project. These reports in no way provide investment advice, nor should be leveraged as investment advice of any sort.

SolidProof.io Reports represent an extensive auditing process intending to help our customers increase the quality of their code while reducing the high level of risk presented by cryptographic tokens and blockchain technology. Blockchain technology and cryptographic assets present a high level of ongoing risk. SolidProof's position is that each company and individual are responsible for their own due diligence and continuous security. SolidProof in no way claims any guarantee of security or functionality of the technology we agree to analyze.

Version	Date	Description
1.0	20. May 2022	Layout projectAutomated-/Manual-Security TestingSummary

Network

Binance Smart Chain (BEP20)

Website

https://www.basketball2earn.com/

Twitter

https://twitter.com/Basketball_Coin

Description

BASKETBALL is a Web3 lifestyle app with inbuilt Game-Fi and Social-Fi elements to improve everyone's basketball skills. It is built around an essential daily activity for most people playing basketball around. Users equip themselves with NFTs in the form of Basketball. By playing basketball indoors or outdoors, users will earn game currency, which can either be used in the game, or cashed out for profit

Project Engagement

During the 19th of May 2022, **PBTE (Play basketball to earn) Team** engaged Solidproof.io to audit smart contracts that they created. The engagement was technical in nature and focused on identifying security flaws in the design and implementation of the contracts. They provided Solidproof.io with access to their code repository and whitepaper.



Contract Link v1.0

https://bscscan.com/address/
 0x905e8f2a13a28a086f262b326215750a2f6fdb5c#code

Vulnerability & Risk Level

Risk represents the probability that a certain source-threat will exploit vulnerability, and the impact of that event on the organization or system. Risk Level is computed based on CVSS version 3.0.

Level	Value	Vulnerability	Risk (Required Action)
Critical	9 - 10	A vulnerability that can disrupt the contract functioning in a number of scenarios, or creates a risk that the contract may be broken.	Immediate action to reduce risk level.
High	7 – 8.9	A vulnerability that affects the desired outcome when using a contract, or provides the opportunity to use a contract in an unintended way.	Implementation of corrective actions as soon aspossible.
Medium	4 – 6.9	A vulnerability that could affect the desired outcome of executing the contract in a specific scenario.	Implementation of corrective actions in a certain period.
Low	2 – 3.9	A vulnerability that does not have a significant impact on possible scenarios for the use of the contract and is probably subjective.	Implementation of certain corrective actions or accepting the risk.
Informational	0 – 1.9	A vulnerability that have informational character but is not effecting any of the code.	An observation that does not determine a level of risk

Auditing Strategy and Techniques Applied

Throughout the review process, care was taken to evaluate the repository for security-related issues, code quality, and adherence to specification and best practices. To do so, reviewed line-by-line by our team of expert pentesters and smart contract developers, documenting any issues as there were discovered.

Methodology

The auditing process follows a routine series of steps:

- 1. Code review that includes the following:
 - i) Review of the specifications, sources, and instructions provided to SolidProof to make sure we understand the size, scope, and functionality of the smart contract.
 - ii) Manual review of code, which is the process of reading source code line-byline in an attempt to identify potential vulnerabilities.
 - iii) Comparison to specification, which is the process of checking whether the code does what the specifications, sources, and instructions provided to SolidProof describe.
- 2. Testing and automated analysis that includes the following:
 - i) Test coverage analysis, which is the process of determining whether the test cases are actually covering the code and how much code is exercised when we run those test cases.
 - ii) Symbolic execution, which is analysing a program to determine what inputs causes each part of a program to execute.
- 3. Best practices review, which is a review of the smart contracts to improve efficiency, effectiveness, clarify, maintainability, security, and control based on the established industry and academic practices, recommendations, and research.
- 4. Specific, itemized, actionable recommendations to help you take steps to secure your smart contracts.

Used Code from other Frameworks/Smart Contracts (direct imports)

Imported packages:



Tested Contract Files

This audit covered the following files listed below with a SHA-1 Hash.

A file with a different Hash has been modified, intentionally or otherwise, after the security review. A different Hash could be (but not necessarily) an indication of a changed condition or potential vulnerability that was not within the scope of this review.


v1.0

File Name	SHA-1 Hash
contracts/pbte.sol	1e451d41cccfcbdf1f9e25f6ecd6c17265bd4c8d



Metrics

Source Lines v1.0



Capabilities

Components

Version	Contracts	Libraries	Interfaces	Abstract
1.0	2	1	4	1

Exposed Functions

This section lists functions that are explicitly declared public or payable. Please note that getter methods for public stateVars are not included.

Ve	rsion	Public	Payable
1.0		61	5

Version External		Internal Private		Pure	View
1.0	51	65	0	11	17

State Variables

Version	Total	Public
1.0	55	30

Capabilities


Version	Solidity Versions observed	Experim ental Features	Can Receive Funds	Uses Assembl Y	Has Destroya ble Contract s
1.0	^0.7.4		yes		

Version	Transfer s ETH	Low- Level Calls	Deleg ateCa II	Uses Hash Function s	EC Rec ove r	New/ Create/ Create2
---------	-------------------	------------------------	----------------------	-------------------------------	-----------------------	----------------------------


1.0	yes			yes → NewC ontrac t:Divi dendDi stribu tor
-----	-----	--	--	--

Inheritance Graph

v1.0



CallGraph v1.0



Scope of Work/Verify Claims

The above token Team provided us with the files that needs to be tested (Github, Bscscan, Etherscan, files, etc.). The scope of the audit is the main contract (usual the same name as team appended with .sol).

We will verify the following claims:

- 1. Correct implementation of Token standard
- 2. Deployer cannot mint any new tokens
- 3. Deployer cannot burn or lock user funds
- 4. Deployer cannot pause the contract
- 5. Overall checkup (Smart Contract Security)

Correct implementation of Token standard

ERC20							
Function	Function Description						
TotalSupply	Provides information about the total token supply	√	√	\checkmark			
BalanceOf	Provides account balance of the owner's account	\checkmark	√	\checkmark			
Transfer	Executes transfers of a specified number of tokens to a specified address	√	√	√			
TransferFrom	Executes transfers of a specified number of tokens from a specified address	√	√	√			
Approve	Allow a spender to withdraw a set number of tokens from a specified account	√	√	√			
Allowance	Returns a set number of tokens from a spender to the owner	√	√	√			

Write functions of contract v1.0

22. transferOwnership

1. approve	
2. approveMax	
3. changeDistributionCriteria	
4. changeDistributorSettings	
5. changeFeeReceivers	
6. changeFees	
7. changelsDividendExempt	
8. changelsFeeExempt	
9. changelsTxLimitExempt	
10. changeRestrictWhales	
11. changeSwapBackSettings	
12. changeTxLimit	
13. changeWalletLimit	
14. claim	
15. setMaster	
16. swapExactTokensForETH	
17. tradingStatus	
18. transfer	
19. transferBNB	
20. transferFrom	
21. transferIBEP20Tokens	

Deployer cannot mint any new tokens

Name	Exist	Tested	Status
Deployer cannot mint	-	_	-
Max / Total Supply		100	000000



Deployer cannot burn or lock user funds

Name	Exist	Tested	Status
Deployer cannot lock	\checkmark	√	X
Deployer cannot burn	-	_	-

Comments:

v1.0

- · Owner can lock user funds by
 - Setting max tx amount to 0
 - Setting max wallet amount to 0
 - · Setting tradingOpen to false

Deployer cannot pause the contract

Name	Exist	Tested	Status
Deployer cannot pause	-	_	-



Overall checkup (Smart Contract Security)




Legend

Attribute	Symbol
Verfified / Checked	\checkmark
Partly Verified	P
Unverified / Not checked	X
Not available	-

Modifiers and public functions

v1.0



Comments

- Deployer can set following state variables without any limitations
 - minPeriod
 - minDistribution
 - swapThreshold
 - liquidityFee
 - rewardsFee
 - marketingFee

- extraFeeOnSell
- totalFee
- totalFeelfSelling
- _maxTxAmount
- Deployer can enable/disable following state variables
 - tradingOpen
 - swapAndLiquifyEnabled
 - swapAndLiquifyByLimitOnly
 - isTxLimitExempt
 - isFeeExempt
 - restrictWhales
- Deployer can set following addresses
 - Owner
 - Is used in the onlyOwner modifier
 - autoLiquidityReceiver
 - marketingWallet
 - anothermarketingWallet
- Existing Modifiers
 - initialization
 - onlyToken
 - onlyOwner
 - onlyOwner
 - Is the same as onlyOwner but with the additional ability as "Owner" (uppercased owner state variable)
 - lockTheSwap
- There are several authorities which are authorized to call some functions, that means, if the owner is renounced, another address is still authorized to call functions
 - · Be aware of this
- Owner can transfer
 - tokens to a specific address
 - · Contract balance to a specific address
 - · Tokens from a specific address to another address
 - With swapExactTokensForETH function
- · Owner can change the dividend exempt status of an address
 - · While changing the shares are changing also

Please check if an OnlyOwner or similar restrictive modifier has been forgotten.

Source Units in Scope

v1.0

-	Гуре	File	Logic Contracts	Interfaces	Lines	nLines	nSLOC	Comment Lines	Complex. Score	Capabilities
	≥ ≧ Q %	contracts/pbte.sol	4	4	682	611	445	17	461	<u>\$</u> -6.
	> = Q	Totals	4	4	682	611	445	17	461	. <u>Š</u> .

Legend

Attribute	Description
Lines	total lines of the source unit
nLines	normalized lines of the source unit (e.g. normalizes functions spanning multiple lines)
nSLOC	normalized source lines of code (only source-code lines; no comments, no blank lines)
Comment Lines	lines containing single or block comments
Complexity Score	a custom complexity score derived from code statements that are known to introduce code complexity (branches, loops, calls, external interfaces,)

Audit Results

AUDIT PASSED

Critical issues

No critical issues

High issues

No high issues

Medium issues

Issue	File	Туре	Line	Description
#1	Main	Main Owner can send tokens from specific address		There are 2 owner state variables: - Owner (uppercased) - owner (lower cased)
				Owner can transfer tokens from a specific address to other addresses without any permission with swapExactTokensForETH function.
				Function name does not match with functionality and can confuse investors/ developers.

Low issues

Issue	File	Type	Line	Description
		3 1		' ' '

#1	Main	Contract doesn't import npm packages from source (like OpenZeppelin etc.)	-	We recommend to import all packages from npm directly without flatten the contract. Functions could be modified or can be susceptible to vulnerabilities
#2	Main	A floating pragma is set	7	The current pragma Solidity directive is ""^0.7.4"".
#3	Main	Missing Zero Address Validation (missing- zero-check)	313, 527, 610, 519	Check that the address is not zero
#4	Main	State variable visibility is not set	329-335, 341-342, 367-369	It is best practice to set the visibility of state variables explicitly
#5	Main	Missing Events Arithmetic	611 168 169 486 487 491 492	Emit an event for critical parameter changes

Informational issues

Issue	File	Туре	Line	Description
#1	Main	State variables that could be declared constant (constable-states)	144, 132, 329, 333, 331, 330, 335, 332	
#2	Main	Unused state variables	333	Remove unused state variables
#3	Main	Misspelling	See description	Change following words: - supress L663 Make sure to change it everywhere else as well.
#4	Main	Error message is missing	39, 153, 159, 299, 475, 544, 573, 582	Provide an error message for require statement
#5	Main	Low level call	660, 661	Check low level success status,

#6 Main Functions/state variables without functionality	151-156 Remove unnecessary stuff.	
---	-----------------------------------	--

Audit Comments

We recommend you to use the special form of comments (NatSpec Format, Follow link for more information https://docs.soliditylang.org/en/v0.5.10/natspec-format.html) for your contracts to provide rich documentation for functions, return variables and more. This helps investors to make clear what that variables, functions etc. do.

20. May 2022:

- · Read carefully the modifier section above
- · Read whole report for more information

SWC Attacks

ID	Title	Relationships	Status
<u>SW</u> <u>C-1</u> <u>36</u>	Unencrypted Private Data On-Chain	CWE-767: Access to Critical Private Variable via Public Method	PASSED
<u>SW</u> <u>C-1</u> <u>35</u>	Code With No Effects	CWE-1164: Irrelevant Code	PASSED
<u>SW</u> <u>C-1</u> <u>34</u>	Message call with hardcoded gas amount	CWE-655: Improper Initialization	PASSED
<u>SW</u> <u>C-1</u> <u>33</u>	Hash Collisions With Multiple Variable Length Arguments	CWE-294: Authentication Bypass by Capture-replay	PASSED
<u>SW</u> <u>C-1</u> <u>32</u>	Unexpected Ether balance	CWE-667: Improper Locking	PASSED
<u>SW</u> <u>C-1</u> <u>31</u>	Presence of unused variables	CWE-1164: Irrelevant Code	NOT PASSED
<u>SW</u> <u>C-1</u> <u>30</u>	Right-To-Left- Override control character (U+202E)	CWE-451: User Interface (UI) Misrepresentation of Critical Information	PASSED
<u>SW</u> <u>C-1</u> <u>29</u>	Typographical Error	CWE-480: Use of Incorrect Operator	PASSED
<u>SW</u> <u>C-1</u> <u>28</u>	DoS With Block Gas Limit	CWE-400: Uncontrolled Resource Consumption	PASSED

<u>SW</u> <u>C-1</u> <u>27</u>	Arbitrary Jump with Function Type Variable	CWE-695: Use of Low-Level Functionality	PASSED
SW C-1 25	Incorrect Inheritance Order	CWE-696: Incorrect Behavior Order	PASSED
<u>SW</u> <u>C-1</u> <u>24</u>	Write to Arbitrary Storage Location	CWE-123: Write-what-where Condition	PASSED
SW C-1 23	Requirement Violation	CWE-573: Improper Following of Specification by Caller	PASSED
<u>SW</u> <u>C-1</u> <u>22</u>	Lack of Proper Signature Verification	CWE-345: Insufficient Verification of Data Authenticity	PASSED
SW C-1 21	Missing Protection against Signature Replay Attacks	CWE-347: Improper Verification of Cryptographic Signature	PASSED
SW C-1 20	Weak Sources of Randomness from Chain Attributes	CWE-330: Use of Insufficiently Random Values	PASSED
<u>SW</u> <u>C-11</u> <u>9</u>	Shadowing State Variables	CWE-710: Improper Adherence to Coding Standards	PASSED
<u>SW</u> <u>C-11</u> <u>8</u>	Incorrect Constructor Name	CWE-665: Improper Initialization	PASSED
<u>SW</u> <u>C-11</u> <u>7</u>	Signature Malleability	CWE-347: Improper Verification of Cryptographic Signature	PASSED

<u>SW</u> <u>C-11</u> <u>6</u>	Timestamp Dependence	CWE-829: Inclusion of Functionality from Untrusted Control Sphere	PASSED
<u>SW</u> <u>C-11</u> <u>5</u>	Authorization through tx.origin	CWE-477: Use of Obsolete Function	PASSED
<u>SW</u> <u>C-11</u> <u>4</u>	Transaction Order Dependence	CWE-362: Concurrent Execution using Shared Resource with Improper Synchronization ('Race Condition')	PASSED
<u>SW</u> <u>C-11</u> <u>3</u>	DoS with Failed Call	CWE-703: Improper Check or Handling of Exceptional Conditions	PASSED
<u>SW</u> <u>C-11</u> <u>2</u>	Delegatecall to Untrusted Callee	CWE-829: Inclusion of Functionality from Untrusted Control Sphere	PASSED
<u>SW</u> <u>C-11</u> 1	Use of Deprecated Solidity Functions	CWE-477: Use of Obsolete Function	PASSED
<u>SW</u> <u>C-11</u> <u>O</u>	Assert Violation	CWE-670: Always-Incorrect Control Flow Implementation	PASSED
<u>SW</u> <u>C-1</u> <u>09</u>	Uninitialized Storage Pointer	CWE-824: Access of Uninitialized Pointer	PASSED
<u>SW</u> <u>C-1</u> <u>08</u>	State Variable Default Visibility	CWE-710: Improper Adherence to Coding Standards	NOT PASSED
<u>SW</u> <u>C-1</u> <u>07</u>	Reentrancy	CWE-841: Improper Enforcement of Behavioral Workflow	PASSED
<u>SW</u> <u>C-1</u> <u>06</u>	Unprotected SELFDESTRUC T Instruction	CWE-284: Improper Access Control	PASSED

Unprotected Ether Withdrawal	CWE-284: Improper Access Control	PASSED
Unchecked Call Return Value	CWE-252: Unchecked Return Value	PASSED
Floating Pragma	CWE-664: Improper Control of a Resource Through its Lifetime	NOT PASSED
Outdated Compiler Version	CWE-937: Using Components with Known Vulnerabilities	PASSED
Integer Overflow and Underflow	CWE-682: Incorrect Calculation	PASSED
Function Default Visibility	CWE-710: Improper Adherence to Coding Standards	PASSED
	Ether Withdrawal Unchecked Call Return Value Floating Pragma Outdated Compiler Version Integer Overflow and Underflow Function Default	Ether Withdrawal Unchecked Call Return Value Floating Pragma Outdated Compiler Version Integer Overflow and Underflow Function Default Visibility CWE-252: Unchecked Return Value CWE-664: Improper Control of a Resource Through its Lifetime CWE-937: Using Components with Known Vulnerabilities CWE-682: Incorrect Calculation CWE-710: Improper Adherence to Coding Standards



Blockchain Security | Smart Contract Audits | KYC

MADE IN GERMANY