

Blockchain Security | Smart Contract Audits | KYC

MADE IN GERMANY

Blockdeed

Audit

Security Assessment 11. July, 2022

For

BLOCKDEED





Disclaimer	3
Description	5
Project Engagement	5
Logo	5
Contract Link	5
Methodology	7
Used Code from other Frameworks/Smart Contracts (direct imports)	8
Tested Contract Files	9
Source Lines	10
Risk Level	10
Capabilities	11
Inheritance Graph	12
CallGraph	13
Scope of Work/Verify Claims	14
Modifiers and public functions	22
Source Units in Scope	24
Critical issues	25
High issues	25
Medium issues	25
Low issues	25
Informational issues	26
Commented Code exist	27
Audit Comments	27
SWC Attacks	28

Disclaimer

<u>SolidProof.io</u> reports are not, nor should be considered, an "endorsement" or "disapproval" of any particular project or team. These reports are not, nor should be considered, an indication of the economics or value of any "product" or "asset" created by any team. SolidProof.io do not cover testing or auditing the integration with external contract or services (such as Unicrypt, Uniswap, PancakeSwap etc'...)

SolidProof.io Audits do not provide any warranty or guarantee regarding the absolute bug- free nature of the technology analyzed, nor do they provide any indication of the technology proprietors. SolidProof Audits should not be used in any way to make decisions around investment or involvement with any particular project. These reports in no way provide investment advice, nor should be leveraged as investment advice of any sort.

SolidProof.io Reports represent an extensive auditing process intending to help our customers increase the quality of their code while reducing the high level of risk presented by cryptographic tokens and blockchain technology. Blockchain technology and cryptographic assets present a high level of ongoing risk. SolidProof's position is that each company and individual are responsible for their own due diligence and continuous security. SolidProof in no way claims any guarantee of security or functionality of the technology we agree to analyze.

Version	Date	Description
1.0	11. July 2022	Layout projectAutomated-/Manual-Security TestingSummary

Network

Ethereum (ERC20)

Website

https://www.blockdeed.xyz/

Twitter

https://twitter.com/blockdeed

Instagram

https://www.instagram.com/blockdeed/

Discord

https://discord.gg/Y4ECrdvbZB

LinkedIn

https://www.linkedin.com/company/blockdeed

Description

TBA

Project Engagement

During the 7th of July 2022, **Blockaded Team** engaged Solidproof.io to audit smart contracts that they created. The engagement was technical in nature and focused on identifying security flaws in the design and implementation of the contracts. They provided Solidproof.io with access to their code repository and whitepaper.





Contract Link

v1.0

- Testnet
 - https://ropsten.etherscan.io/address/
 0x67CD3F7006Fc811d8C113eA00D3cF5eA0153A1A6#code

Vulnerability & Risk Level

Risk represents the probability that a certain source-threat will exploit vulnerability, and the impact of that event on the organization or system. Risk Level is computed based on CVSS version 3.0.

Level	Value	Vulnerability	Risk (Required Action)
Critical 9-10		A vulnerability that can disrupt the contract functioning in a number of scenarios, or creates a risk that the contract may be broken.	Immediate action to reduce risk level.
High	7 – 8.9	A vulnerability that affects the desired outcome when using a contract, or provides the opportunity to use a contract in an unintended way.	Implementation of corrective actions as soon aspossible.
Medium	4 – 6.9	A vulnerability that could affect the desired outcome of executing the contract in a specific scenario.	Implementation of corrective actions in a certain period.
Low	2 – 3.9	A vulnerability that does not have a significant impact on possible scenarios for the use of the contract and is probably subjective.	Implementation of certain corrective actions or accepting the risk.
Informational	0 – 1.9	A vulnerability that have informational character but is not effecting any of the code.	An observation that does not determine a level of risk

Auditing Strategy and Techniques Applied

Throughout the review process, care was taken to evaluate the repository for security-related issues, code quality, and adherence to specification and best practices. To do so, reviewed line-by-line by our team of expert pentesters and smart contract developers, documenting any issues as there were discovered.


Methodology

The auditing process follows a routine series of steps:

- 1. Code review that includes the following:
 - i) Review of the specifications, sources, and instructions provided to SolidProof to make sure we understand the size, scope, and functionality of the smart contract.
 - ii) Manual review of code, which is the process of reading source code line-byline in an attempt to identify potential vulnerabilities.
 - iii) Comparison to specification, which is the process of checking whether the code does what the specifications, sources, and instructions provided to SolidProof describe.
- 2. Testing and automated analysis that includes the following:
 - i) Test coverage analysis, which is the process of determining whether the test cases are actually covering the code and how much code is exercised when we run those test cases.
 - ii) Symbolic execution, which is analysing a program to determine what inputs causes each part of a program to execute.
- 3. Best practices review, which is a review of the smart contracts to improve efficiency, effectiveness, clarify, maintainability, security, and control based on the established industry and academic practices, recommendations, and research.
- 4. Specific, itemized, actionable recommendations to help you take steps to secure your smart contracts.

Used Code from other Frameworks/Smart Contracts (direct imports)

Imported packages:



Tested Contract Files

This audit covered the following files listed below with a SHA-1 Hash.


A file with a different Hash has been modified, intentionally or otherwise, after the security review. A different Hash could be (but not necessarily) an indication of a changed condition or potential vulnerability that was not within the scope of this review.

v1.0

File Name	SHA-1 Hash	
contracts/blockdeed.sol	3214fbc41fd3054838be61a7ce28e7b370e52c5a	

Metrics

Source Lines v1.0



Capabilities

Components

Version	Contracts	Libraries	Interfaces	Abstract
1.0	2	3	5	6

Exposed Functions

This section lists functions that are explicitly declared public or payable. Please note that getter methods for public stateVars are not included.

Version		Public	Payable
1.0		53	1

Version	External	Internal	Private	Pure	View
1.0	16	107	1	6	38

State Variables

Version	Total	Public
1.0	23	10

Capabilities

Version	Solidity Versions observed	Experim ental Features	Can Receive Funds	Uses Assembl Y	Has Destroya ble Contract s
1.0	^0.8.0		yes	yes (2 asm blocks)	

Version	Transfer s ETH	Low- Level Calls	Deleg ateCa II	Uses Hash Function s	EC Rec ove r	New/ Create/ Create2
---------	-------------------	------------------------	----------------------	-------------------------------	-----------------------	----------------------------


1.0	yes	yes		
	_	_		

Inheritance Graph v1.0



CallGraph

v1.0



Scope of Work/Verify Claims

The above token Team provided us with the files that needs to be tested (Github, Bscscan, Etherscan, files, etc.). The scope of the audit is the main contract (usual the same name as team appended with .sol).

We will verify the following claims:

- 1. Is contract an upgradeable
- 2. Correct implementation of Token standard
- 3. Deployer cannot mint any new tokens
- 4. Deployer cannot burn or lock user funds
- 5. Deployer cannot pause the contract
- 6. Overall checkup (Smart Contract Security)

Is contract an upgradeable

Name	
Is contract an upgradeable?	No



Correct implementation of Token standard

ERC721					
Function	Description	Exist	Tested	Verified	
BalanceOf	Count all NFTs assigned to an owner	\checkmark	√	\checkmark	
OwnerOf	Find the owner of an NFT	\checkmark	√	\checkmark	
SafeTransferFrom	Transfers the ownership of an NFT from one address to another address	√	√	√	
SafeTransferFrom	See above - Difference is that this function has an extra data parameter	√	√	√	
TransferFrom	Transfer ownership of an NFT		√	\checkmark	
Approve	Change or reaffirm the approved address for an NFT	√	√	√	
SetApprovalForAll	Enable or disable approval for a third party ("operator") to manage all of `msg.sender`'s assets	√	√	√	
GetApproved	Get the approved address for a single NFT	\checkmark	√	√	
IsApprovedForAll	Query if an address is an authorized operator for another address	√	√	√	
SupportsInterface	Query if a contract implements an interface	√	√	√	
Name	Provides information about the name	√	√	√	
Symbol	Provides information about the symbol	√	√	√	
TokenURI	Provides information about the TokenUri	√	1	√	

Write functions of contract v1.0

21. withdrawETH

approve	
burn	
changeOwner	
mint	
pause	
outOnStake	
moveWhitelist	
enounceOwnership	
afeTransferFrom	
safeTransferFrom	
setApprovalForAll	
setBKDPrice	
eetNftPrice	
setWINftPrice	
setstakingPrice	
transferFrom	
transferOwnership	
unpause	
unstake	
whitelis	
mitelis	

Deployer cannot mint any new tokens

Name	Exist	Tested	Status
Deployer cannot mint	\checkmark	√	√

Comments:

v1.0

· Everyone is able to mint new tokens



Deployer cannot burn or lock user funds

Name	Exist	Tested	Status
Deployer cannot lock	\checkmark	√	X
Deployer cannot burn	√	√	\checkmark

Comments:

v1.0

- · Owner can lock user funds by
 - Pausing contract
- Tokens
 - · can be burned by msg.sender

Deployer cannot pause the contract

Name	Exist	Tested	Status
Deployer cannot pause	\checkmark	√	X

Comments:

v1.0

· Owner can pause contract

Overall checkup (Smart Contract Security)




Legend

Attribute	Symbol
Verfified / Checked	\checkmark
Partly Verified	P
Unverified / Not checked	X
Not available	-

Modifiers and public functions

v1.0



Comments

- Deployer can set following state variables without any limitations
 - nftPrice
 - wINftPrice
 - BKDPrice
 - Must not be 0, it causes reverting in "putOnStake" function L1421 because it is not allowed to divide by zero
 - stakingPrice
- Deployer can enable/disable following state variables

- _paused
- whitelisted
- Existing Modifiers
 - onlyOwner
 - whenPaused
 - whenNotPaused
- · Owner can withdraw contract eth balance
- Use Ownable functions instead of implementing ownable functionalities by yourself or remove Ownable contract and implement everything by yourself

Please check if an OnlyOwner or similar restrictive modifier has been forgotten.

Source Units in Scope

v1.0

Туре	File	Logic Contracts	Interfaces	Lines	nLines	nSLOC	Comment Lines	Complex. Score	Capabilities
 	contracts/blockdeed.sol	11	5	1455	1236	569	671	462	™ § ≛11 ☼ 3 Σ
∌≜ Q %	Totals	11	5	1455	1236	569	671	462	

Legend

Attribute	Description
Lines	total lines of the source unit
nLines	normalized lines of the source unit (e.g. normalizes functions spanning multiple lines)
nSLOC	normalized source lines of code (only source-code lines; no comments, no blank lines)
Comment Lines	lines containing single or block comments
Complexity Score	a custom complexity score derived from code statements that are known to introduce code complexity (branches, loops, calls, external interfaces,)

Audit Results

AUDIT PASSED

Critical issues

No critical issues

High issues

No high issues

Medium issues

No medium issues

Low issues

Issue	File	Type	Line	Description
#1	Main	Contract doesn't import npm packages from source (like OpenZeppelin etc.)		We recommend to import all packages from npm directly without flatten the contract. Functions could be modified or can be susceptible to vulnerabilities
#2	Main	A floating pragma is set	5	The current pragma Solidity directive is ""^0.8.0"".
#3	Main	Missing Zero Address Validation (missing- zero-check)	1379, 1310	Check that the address is not zero
#4	Main	State variables shadowing	1297	Rename the state variables that shadow another component

#5 Main Unnecessary require statement	1427	You are looking for history[tokenId] in L1427 but that variable is 0 already. That means, that every tokenId is 0 by default. Remove the "=" sign from the condition
---------------------------------------	------	--

Informational issues

Issue	File	Туре	Line	Description
#1	Main	State variables that could be declared constant (constable-states)	1305	Add the `constant` attributes to state variables that never change
#2	Main	Misspelling	See description	Change following words:whitelis L1364Make sure to change it everywhere else as well.
#3	Main	Error message is missing	1374	Provide an error message for require statement
#4	Main	NatSpec documentation missing		If you started to comment your code, also comment all other functions, variables etc.
#5	Main	Remove owner functionality	1378-1382	If you are using "Ownable" contract for the ownership logic, use its transfer/ renounce ownership function to set another admin for this contract instead of writing it by yourself.
#6	Main	No difference between wINftPrice and nftPrice	See description	To make sure that there is a difference between those variables make sure that the wINftPrice will not become more than nftPrice
#7	Main	Readability	See description	We recommend you to reorder functions state variables etc. to improve the readability of the contract.

Commented Code exist

There are some instances of code being commented out in the following files that should be removed:

File	Line	Comment
Main	1442-1447	<pre>// for(uint256 i;i<stake_holders.length;i++){ _stake="stakes[i];" if(_stake.user="=staker){" memory="" pre="" stake="" stakingsummarys.push(stakingsummary(staker,stakes[i]));="" }="" }<=""></stake_holders.length;i++){></pre>

Recommendation

Remove the commented code, or address them properly.

Audit Comments

We recommend you to use the special form of comments (NatSpec Format, Follow link for more information https://docs.soliditylang.org/en/v0.5.10/natspec-format.html) for your contracts to provide rich documentation for functions, return variables and more. This helps investors to make clear what that variables, functions etc. do.

11. July 2022:

· Read whole report and modifiers section for more information

SWC Attacks

ID	Title	Relationships	Status
<u>SW</u> <u>C-1</u> <u>36</u>	Unencrypted Private Data On-Chain	CWE-767: Access to Critical Private Variable via Public Method	PASSED
<u>SW</u> <u>C-1</u> <u>35</u>	Code With No Effects	CWE-1164: Irrelevant Code	PASSED
<u>SW</u> <u>C-1</u> <u>34</u>	Message call with hardcoded gas amount	CWE-655: Improper Initialization	PASSED
<u>SW</u> <u>C-1</u> <u>33</u>	Hash Collisions With Multiple Variable Length Arguments	CWE-294: Authentication Bypass by Capture-replay	PASSED
<u>SW</u> <u>C-1</u> <u>32</u>	Unexpected Ether balance	CWE-667: Improper Locking	PASSED
<u>SW</u> <u>C-1</u> <u>31</u>	Presence of unused variables	CWE-1164: Irrelevant Code	PASSED
<u>SW</u> <u>C-1</u> <u>30</u>	Right-To-Left- Override control character (U+202E)	CWE-451: User Interface (UI) Misrepresentation of Critical Information	PASSED
<u>SW</u> <u>C-1</u> <u>29</u>	Typographical Error	CWE-480: Use of Incorrect Operator	PASSED
<u>SW</u> <u>C-1</u> <u>28</u>	DoS With Block Gas Limit	CWE-400: Uncontrolled Resource Consumption	PASSED

<u>SW</u> <u>C-1</u> <u>27</u>	Arbitrary Jump with Function Type Variable	CWE-695: Use of Low-Level Functionality	PASSED
<u>SW</u> <u>C-1</u> <u>25</u>	Incorrect Inheritance Order	CWE-696: Incorrect Behavior Order	PASSED
<u>SW</u> <u>C-1</u> <u>24</u>	Write to Arbitrary Storage Location	CWE-123: Write-what-where Condition	PASSED
<u>SW</u> <u>C-1</u> <u>23</u>	Requirement Violation	CWE-573: Improper Following of Specification by Caller	PASSED
<u>SW</u> <u>C-1</u> <u>22</u>	Lack of Proper Signature Verification	CWE-345: Insufficient Verification of Data Authenticity	PASSED
<u>SW</u> <u>C-1</u> <u>21</u>	Missing Protection against Signature Replay Attacks	CWE-347: Improper Verification of Cryptographic Signature	PASSED
<u>SW</u> <u>C-1</u> <u>20</u>	Weak Sources of Randomness from Chain Attributes	CWE-330: Use of Insufficiently Random Values	PASSED
<u>SW</u> <u>C-11</u> <u>9</u>	Shadowing State Variables	CWE-710: Improper Adherence to Coding Standards	NOT PASSED
<u>SW</u> <u>C-11</u> <u>8</u>	Incorrect Constructor Name	CWE-665: Improper Initialization	PASSED
<u>SW</u> <u>C-11</u> <u>7</u>	Signature Malleability	CWE-347: Improper Verification of Cryptographic Signature	PASSED

<u>SW</u> <u>C-11</u> <u>6</u>	Timestamp Dependence	CWE-829: Inclusion of Functionality from Untrusted Control Sphere	PASSED
<u>SW</u> <u>C-11</u> <u>5</u>	Authorization through tx.origin	CWE-477: Use of Obsolete Function	PASSED
<u>SW</u> <u>C-11</u> <u>4</u>	Transaction Order Dependence	CWE-362: Concurrent Execution using Shared Resource with Improper Synchronization ('Race Condition')	PASSED
<u>SW</u> <u>C-11</u> <u>3</u>	DoS with Failed Call	CWE-703: Improper Check or Handling of Exceptional Conditions	PASSED
<u>SW</u> <u>C-11</u> <u>2</u>	Delegatecall to Untrusted Callee	CWE-829: Inclusion of Functionality from Untrusted Control Sphere	PASSED
<u>SW</u> <u>C-11</u> <u>1</u>	Use of Deprecated Solidity Functions	CWE-477: Use of Obsolete Function	PASSED
<u>SW</u> <u>C-11</u> <u>O</u>	Assert Violation	CWE-670: Always-Incorrect Control Flow Implementation	PASSED
SW C-1 09	Uninitialized Storage Pointer	CWE-824: Access of Uninitialized Pointer	PASSED
<u>SW</u> <u>C-1</u> <u>08</u>	State Variable Default Visibility	CWE-710: Improper Adherence to Coding Standards	PASSED
SW C-1 07	Reentrancy	CWE-841: Improper Enforcement of Behavioral Workflow	PASSED
<u>SW</u> <u>C-1</u> <u>06</u>	Unprotected SELFDESTRUC T Instruction	CWE-284: Improper Access Control	PASSED

<u>SW</u> <u>C-1</u> <u>05</u>	Unprotected Ether Withdrawal	CWE-284: Improper Access Control	PASSED
SW C-1 04	Unchecked Call Return Value	CWE-252: Unchecked Return Value	PASSED
SW C-1 03	Floating Pragma	CWE-664: Improper Control of a Resource Through its Lifetime	NOT PASSED
<u>SW</u> <u>C-1</u> <u>02</u>	Outdated Compiler Version	CWE-937: Using Components with Known Vulnerabilities	PASSED
<u>SW</u> <u>C-1</u> <u>01</u>	Integer Overflow and Underflow	CWE-682: Incorrect Calculation	PASSED
<u>SW</u> <u>C-1</u> <u>00</u>	Function Default Visibility	CWE-710: Improper Adherence to Coding Standards	PASSED







Blockchain Security | Smart Contract Audits | KYC

MADE IN GERMANY