

Candidate Report: trainingB5QKYM-XJ2

Check out Codility training tasks

Test Name:

Summary

Timeline

Feedback

Tasks summary

Task	Time spent	Score
FrogRiverOne C#	1 min	54%

Total score

54%

Tasks Details

Easy

1. FrogRiverOne

Find the earliest time when a frog can jump to the other side of a river.

Task Score

54%

Correctness

100%

Performance

0%

Task description

A small frog wants to get to the other side of a river. The frog is initially located on one bank of the river (position 0) and wants to get to the opposite bank (position X+1). Leaves fall from a tree onto the surface of the river.

You are given an array A consisting of N integers representing the falling leaves. A[K] represents the position where one leaf falls at time K, measured in seconds.

The goal is to find the earliest time when the frog can jump to the other side of the river. The frog can cross only when leaves appear at every position across the river from 1 to X (that is, we want to find the earliest moment when all the positions from 1 to X are covered by leaves). You may assume that the speed of the current in the river is negligibly small, i.e. the leaves do not change their positions once they fall in the river.

For example, you are given integer X = 5 and array A such that:

```
A[0] = 1
A[1] = 3
A[2] = 1
A[3] = 4
A[4] = 2
A[5] = 3
```

Solution

Programming language used: C#

Total time used:

1 minutes

?

Effective time used:

1 minutes

?

Notes:

not defined yet

Task timeline

?

15:25:20

15:26:08

Code: 15:26:08 UTC, cs, final,

score: 54

show code in pop-up

```
A[6] = 5
A[7] = 4
```

In second 6, a leaf falls into position 5. This is the earliest time when leaves appear in every position across the river.

Write a function:

```
class Solution { public int solution(int X, int[] A); }
```

that, given a non-empty array A consisting of N integers and integer X, returns the earliest time when the frog can jump to the other side of the river.

If the frog is never able to jump to the other side of the river, the function should return -1.

For example, given X = 5 and array A such that:

```
A[0] = 1
A[1] = 3
A[2] = 1
A[3] = 4
A[4] = 2
A[5] = 3
A[6] = 5
A[7] = 4
```

the function should return 6, as explained above.

Write an **efficient** algorithm for the following assumptions:

- N and X are integers within the range [1..100,000];
- each element of array A is an integer within the range [1..X].

Copyright 2009–2020 by Codility Limited. All Rights Reserved. Unauthorized copying, publication or disclosure prohibited.

```
1 using System;
2 using System.Linq;
3 // you can also use other imports, for example:
4 // using System.Collections.Generic;
5
6 // you can write to stdout for debugging purposes, e.g.
7 // Console.WriteLine("this is a debug message");
8
9 class Solution {
10     public int solution(int X, int[] A)
11     {
12         if (A.Length == 1)
13         {
14             if (A[0] == X)
15             {
16                 return 0;
17             }
18             else
19                 return -1;
20         }
21         bool connected = false;
22         var len = A.Length;
23         int second = 0;
24
25         bool[] visited = new bool[X+1];
26         visited[0] = true;
27         do
28         {
29             visited[A[second]] = true;
30             connected = visited.Count(v=>v==false) == 0;
31             if (!connected && second < len)
32                 ++second;
33         } while (!connected && second < len);
34
35         if (connected)
36             return second;
37         else
38             return -1;
39     }
40 }
```

Analysis summary

The following issues have been detected: timeout errors.

Analysis ?

Detected time complexity: **O(N ** 2)**

expand all	Example tests
▶ example example test	✓ OK
expand all	Correctness tests
▶ simple simple test	✓ OK
▶ single single element	✓ OK
▶ extreme_frog frog never across the river	✓ OK
▶ small_random1 3 random permutation, X = 50	✓ OK
▶ small_random2 5 random permutation, X = 60	✓ OK

<div>▶ extreme_leaves</div> <div>all leaves in the same place</div>	✓ OK
<div>expand all</div> <div>Performance tests</div>	
<div>▶ medium_random</div> <div>6 and 2 random permutations, X = ~5,000</div>	<div>✗ TIMEOUT ERROR</div> <div>running time: 0.644 sec., time limit: 0.100 sec.</div>
<div>▶ medium_range</div> <div>arithmetic sequences, X = 5,000</div>	<div>✗ TIMEOUT ERROR</div> <div>running time: 0.436 sec., time limit: 0.100 sec.</div>
<div>▶ large_random</div> <div>10 and 100 random permutation, X = ~10,000</div>	<div>✗ TIMEOUT ERROR</div> <div>Killed. Hard limit reached: 6.000 sec.</div>
<div>▶ large_permutation</div> <div>permutation tests</div>	<div>✗ TIMEOUT ERROR</div> <div>Killed. Hard limit reached: 6.000 sec.</div>
<div>▶ large_range</div> <div>arithmetic sequences, X = 30,000</div>	<div>✗ TIMEOUT ERROR</div> <div>Killed. Hard limit reached: 6.000 sec.</div>

The PDF version of this report that may be downloaded on top of this site may contain sensitive data including personal information. For security purposes, we recommend you remove it from your system once reviewed.