

AutoPos — 3D Anchor Self-Calibration from Inter-Anchor Ranging Alone

Concept Brief (Paper A: System)

Zekai Xiao

June 2026

*Part of a deliberately split two-paper program. This is the **system** paper (Paper A): the working, ground-truth-validated calibration system and the vertical limit it does not cross. A companion **mechanism** paper (Paper B) explains why that vertical limit exists. The two are non-overlapping by design.*

Why this matters. Anchor-based UWB positioning needs accurately known anchor coordinates, and the systems that reach high accuracy obtain them from external infrastructure — surveyed anchor positions or angle-of-arrival base stations (Zihajehzadeh, 2017; Kok, 2015) — exactly the infrastructure missing in ambulatory, out-of-lab settings. Anchor *self*-calibration breaks that circular dependency. Yet even with anchors in hand the field stays well short of the bar it sets itself — the optical “gold standard” the review ties to clinically-relevant decision-making (~ 1 cm): across 37 UWB+IMU systems the *best* reported accuracy is only ~ 5 cm (most 10–80 cm; only $\sim 19\%$ within 10 cm) (Yogesh, 2023, 2024). The shortfall is sharpest on the vertical: only 5 of the 37 attempt 3D at all (the other 32 stay 2D), and even those five take the vertical from IMU fusion over surveyed anchors (Kok, 2015), several adding a biomechanical-model constraint (Zihajehzadeh, 2017). The industrial, aerial side — which this clinical review excludes — does the same: a flying platform resolves height with an onboard laser rangefinder and barometer (Xiang, 2025). Across both directions the vertical is imported from an external aid, *never* recovered from UWB geometry alone. That is the gap AutoPos targets: a body-worn, clinical tag can carry no such aid, so its usable **vertical must come from the UWB geometry itself**.

Why pure-UWB Z, and why 4+4. A body-worn tag does carry one inertial sensor — but no on-body IMU gives a *drift-free, absolute* vertical on its own: an IMU’s height comes from double-integrating acceleration, so it drifts at a rate set by sensor grade — even a premium unit — and is rescued only by gait/biomechanical assumptions the review notes fail for the individual, non-cyclic movement of patients (Yogesh, 2023); a barometer stays coarse and drifts indoors. Recovering Z from the UWB geometry supplies the missing absolute reference and keeps the vertical in the *same* drift-free error regime that already fixes the horizontal, with no second sensor to register or de-drift. The catch is purely geometric: with a single coplanar layer the vertical is badly ill-conditioned — the height still falls out, just far too inaccurate to use. The minimal remedy is the intuitive one — four anchors is the well-known minimum for a 3D fix, so we take that single, horizontally-complete layer and copy it to a second height offset by a Δz , giving a balanced 4+4: the smallest vertical baseline that makes the vertical usable, not an arbitrary denser array nor a coplanar anchor layer plus a Z sensor on the tag. Forcing UWB onto its weakest axis is also what exposed what we name the *delay-layout coupling* (companion paper).

The gap. Existing self-calibration falls into two clusters. One is inter-anchor-only but *2D/coplanar*, or needs a few surveyed reference anchors (De Preter, 2019; Piavanini, 2022; Corbalan, 2023; Ridolfi, 2021). The other reaches *3D* but only by adding an external sensor or mobile platform — LiDAR, SLAM, or visual-inertial odometry (Nguyen, 2025; Yuan, 2024; Delama, 2025) — effectively replacing manual surveying with a robot-assisted survey. The cell “3D + inter-anchor ranging only + joint antenna-delay + no known reference” is empty. It is empty because it is the ill-conditioned regime the field side-steps: De Preter (2019) call 3D self-calibration “very ill-conditioned” and drop to 2D with tape-measured heights; Corbalan (2023) report poor vertical resolution and measure height independently; and commercial RTLS deployments that raise a few anchors to recover the vertical *survey* those raised positions rather than self-calibrate them. Every escape route imports a measured height — the manual step this work removes.

What AutoPos does. On commodity hardware ($8\times$ DWM1001C at two elevation levels) it takes bidirectional SS-TWR inter-anchor ranging through robust fusion (MAD/MVUE) to a joint solve of 3D anchor coordinates *and* per-device antenna delays — no external sensor, no mobile rig, no surveyed reference — and then validates the layout against optical ground truth. The novelty is a *deployment capability and its honest characterization*, not a new estimator: the numerical components (MDS/SDP initialization, Tukey-IRLS robust fitting, alternating delay estimation) are established, and joint anchor+delay estimation is itself prior art (De Preter, 2019; Shah, 2022). (The deployed firmware applies one generic antenna-delay default to every node with no per-device calibration, so the solver’s delays are the residuals that default leaves — the realistic out-of-the-box condition.) What is new is (i) closing the empty 3D inter-anchor-only cell on cheap single-antenna modules; (ii) a *balanced* two-layer 4+4 array that, *within reference-free self-calibration*, restores the well-conditioned vertical geometry that a single coplanar layer lacks — deployed few-anchor raises avoid that wall only by surveying the raised positions, not self-calibrating

them (a self-calibration Fisher analysis gives a vertical CRLB exactly singular for a coplanar layer and ~ 63 mm for 4+4, at the ~ 60 mm production floor); and (iii) two ground-truth-free deployment diagnostics — that ranging residual is a misleading quality signal under minimal anchor counts, and that dispersion across dynamic anchor selection exposes calibration bias that a fixed anchor set would hide.

Result, by axis (Std vs absolute kept separate). Repeatability ~ 5 cm 3D / ~ 4 cm vertical; absolute (vs Vicon) ~ 7 cm 3D / ~ 6 cm vertical — UWB-only and self-calibrated. The *vertical* is the point: ~ 4 – 6 cm from pure UWB, on an axis 32 of 37 reviewed systems avoid entirely and that the remaining few reach only by importing an external height reference. The defensible claim is a usable vertical recovered from UWB alone under the body-worn constraint that rules out external height aids — not the smallest absolute number (the best fusion-plus-surveyed system still edges the 3D total).

Honest limits. The preliminary ~ 5 cm figures are *repeatability*, not accuracy — only the optical-ground-truth numbers are reported as accuracy. The 4+4 geometry is *necessary but not sufficient* for the vertical: it completes the geometric observability, but a systematic vertical bias remains — a *tag-side delay* aliasing into the vertical, not a geometry deficit — which the companion mechanism paper (Paper B) analyzes as the tag-side face of its delay–layout coupling result. These figures also presuppose the eight-anchor, two-layer **broadcast SS-TWR** acquisition the array is built for: a naive minimal-anchor SS-TWR shortcut, or a single coplanar layer, returns the vertical to its singular regime by construction and will not reproduce them.

Priority and disclosure. To our knowledge this is the first demonstration that the *vertical* axis of a UWB anchor array can be self-calibrated to the centimetre level (~ 59 mm absolute vs Vicon, near a ~ 63 mm inter-anchor Cramér–Rao floor) from inter-anchor ranging alone on commodity single-antenna modules — the number later reference-free pure-UWB vertical self-calibration must beat. For defensive-publication value the manuscript discloses the full enabling combination once (3D self-calibration; inter-anchor ranging only; joint per-device antenna-delay estimation; commodity DWM1001C modules; balanced 4+4 array; optical-ground-truth validation — no survey, no external Z sensor, no mobile platform), and ships the CRLB script and ranging data so the floor is independently reproducible. Publish this system paper first and early (dated, indexed) so it becomes the citable prior work the companion paper builds on.

Venue. IEEE Sensors / IEEE Access / IPIN (full paper); the higher-tier Measurement / IEEE TIM target is reserved for the companion mechanism paper. Paper A first, to establish the validated system as the cited substrate for Paper B.

References

- Corbalan, P. et al., 2023. Self-localization of UWB anchors: From theory to practice. *IEEE Access*, 11, pp.29711–29725.
- De Preter, A. et al., 2019. Range bias modeling and autocalibration of a UWB positioning system. In: *IPIN*, pp.1–8.
- Delama, G. et al., 2025. Real-time initialization of unknown anchors for UWB-aided navigation. In: *IROS*. arXiv:2506.15518.
- Kok, M. et al., 2015. Indoor positioning using ultrawideband and inertial measurements. *IEEE Trans. Veh. Technol.*, 64(4), pp.1293–1303.
- Nguyen, T.-D. et al., 2025. Coordinate-consistent localization via continuous-time calibration and fusion of UWB and SLAM. *arXiv:2510.05992*.
- Piavanini, M. et al., 2022. A self-calibrating localization solution for sport applications with UWB technology. *Sensors*, 22(23), 9363.
- Ridolfi, M. et al., 2021. UWB anchor nodes self-calibration in NLOS conditions. *Wireless Networks*, 27, pp.3007–3023.
- Shah, S. et al., 2022. Node calibration in UWB-based RTLSS using multiple simultaneous ranging. *Sensors*, 22(3), 864.
- Xiang, Z., Chen, L., Wu, Q., Yang, J., Dai, X. and Xie, X., 2025. An improved UWB indoor positioning approach for UAVs based on the dual-anchor model. *Sensors*, 25(4), 1052.
- Yogesh, V. et al., 2023. Integrated UWB/MIMU sensor system for position estimation: A technical review (37 systems). *Sensors*, 23(16), 7277.
- Yogesh, V. et al., 2024. Novel calibration method for improved UWB sensor distance measurement for 3D analysis of human movement. *Eng. Sci. Technol. Int. J.*, 58, 101844.
- Yuan, S. et al., 2024. Large-scale UWB anchor calibration and one-shot localization using Gaussian process. *arXiv:2412.16880*.
- Zihajehzadeh, S. and Park, E.J., 2017. A novel biomechanical model-aided IMU/UWB fusion for magnetometer-free lower body motion capture. *IEEE Trans. Syst. Man Cybern. Syst.*, 47(6), pp.927–938.