Примеры использования команд коннектора

Connect

<command

 $id="connect"><login>userXXXXX</login><password>******</password><host>213.247.141.13\\ 3 </host><port>3900</port><logsdir>D:\\Documents and Settings\\user\\Local Settings\\Application Data\\TSLab\\Logs\\</logsdir><loglevel>0</loglevel><autopos>true</autopos><rqdelay>50\\ 0</rqdelay></command>$

Subscribe / AllTrades / Quotations / Quotes

<command

id="subscribe"><alltrades><secid>5253</secid><secid>4024</secid></alltrades><quotations><secid>5253</secid><secid>4024</secid><secid>6210</secid><secid>21</secid><secid>4784</secid><secid>6248</secid><secid>5178</secid><secid>3888</secid><secid>5818</secid><secid>5818</secid><secid>3936</secid><secid>35</secid><secid>6212</secid><secid>27</secid><secid>6214</secid><secid>6214</secid><secid>5169</secid><secid>6034</secid><secid>5548</secid><secid>6211</secid><secid>6126</secid><secid>3570</secid><secid>4875</secid><secid>4872</secid><secid>3784</secid><secid>3785</secid><secid>3786</secid><secid>3789</secid><secid>3790</secid><secid>3813</secid><secid>5124</secid><<secid>3791</secid><secid>3795</secid><secid>3813</secid><secid>5124</secid></guotations><quotes><secid>5253</secid><secid>4025</secid></guotes></command>

Unsubscribe / AllTrades / Quotes

<command

id="unsubscribe"><alltrades><secid>21</secid></alltrades><quotes><secid>21</secid></quotes></command>

Get_history_data

<command id="gethistorydata" secid="21" period="1" count="125" reset="false" />

NewOrder

<command id="neworder"><secid>752</secid><client>virt/00XX</client><bymarket
/><quantity>39</quantity><buysell>S</buysell><usecredit /></command>

NewCondOrder

<command

id="newcondorder"><secid>3403</secid><client>7600XXX</client><price>158475</price><quantity>1</quantity><buysell>S</buysell><cond_type>AskOrLast</cond_type><cond_value>158555</cond_value><validafter>27.02.2010 22:00:00</validafter><validbefore>01.03.2010

CancelOrder

<command id="cancelorder"><transactionid>617521</transactionid></command>