

★ Get unlimited access to the best of Medium for less than \$1/week. [Become a member](#)



Understanding and Using Services in Android: Background & Foreground Services



Codeible · [Follow](#)

5 min read · Oct 2, 2021



Listen



Share

... More

Hello, in this article, I will show you how to utilize Background and Foreground Services in Android.


Follow on Twitter: [Codeible \(@codeible\)](#) / [Twitter](#).

View article on [Codeible.com](#).

Understanding and Using Services in Android: Background & Foreground Services

Hello, in this tutorial, I will show you how to utilize Background and Foreground Services in Android. There are 3...

[codeible.com](#)



Understanding and Using Services in Android: Background & Foreground ...



There are 3 types of services in Android:

- (1) Background
- (2) Foreground
- (3) Bound

Each of these terms are misleading because it is not describing the behavior of how each service are used, but it is describing how they are terminated.

For Android Developers, a Service is a component that runs on the background to perform long-running tasks.

*A **Background Service** is a service that runs only when the app is running so it'll get terminated when the app is terminated.*

*A **Foreground Service** is a service that stays alive even when the app is terminated.*

*And a **Bound Service** is a service that runs only if the component it is bound to is still active.*

Let's see how we can create a Background Service.

Creating a Background Service

To create a Background Service, (1) create a new Class and have it extend the Service class. (2) Inside the class, override the onBind() and onStartCommand() methods.

```
1  import android.app.Service;
2  import android.content.Intent;
3  import android.os.IBinder;
4
5  import androidx.annotation.Nullable;
6
7  public class MyBackgroundService extends Service {
8      @Override
9      public int onStartCommand(Intent intent, int flags, int startId) {
10
11          return super.onStartCommand(intent, flags, startId);
12      }
13
14      @Nullable
15      @Override
16      public IBinder onBind(Intent intent) {
17          return null;
18      }
19  }
```

MyBackgroundService.java hosted with ❤ by GitHub

[view raw](#)

The onStartCommand() method is called every time we start the service either by calling startService() or startForegroundService(). This is where we want to define what the service will do.

For now, we'll create a thread that'll print a message to the terminal every 2 seconds.

```
1  @Override
2  public int onStartCommand(Intent intent, int flags, int startId) {
3      new Thread(
4          new Runnable() {
5              @Override
6              public void run() {
7                  while (true) {
8                      Log.e("Service", "Service is running...");
9                      try {
10                         Thread.sleep(2000);
11                     } catch (InterruptedException e) {
12                         e.printStackTrace();
13                     }
14                 }
15             }
16         }
17     ).start();
18     return super.onStartCommand(intent, flags, startId);
19 }
```

MyBackgroundService.java hosted with ❤ by GitHub

[view raw](#)

Adding the service to the app

Now that we have our Background Service, we need to let the app know about this service.

Go to the manifests file. Inside the application element, add a service element and use the **android:name** attribute to add the service to the app.

```
1  <?xml version="1.0" encoding="utf-8"?>
2  <manifest xmlns:android="http://schemas.android.com/apk/res/android"
3      package="com.codeible.servicestutorial">
4      <application
5          ...>
6          ...
7      </activity>
8
9      <service android:name=".MyBackgroundService"></service>
10
11  </application>
12
13  </manifest>
```

background-service.xml hosted with ❤ by GitHub

[view raw](#)

Starting the Service

```
@Override
protected void onCreate(Bundle savedInstanceState) {
    super.onCreate(savedInstanceState);
    setContentView(R.layout.activity_main);
    Intent serviceIntent = new Intent(this,
        MyBackgroundService.class);
}
```

Call `startService()` and pass in the intent.

```
startService(serviceIntent);
```

If we run the app and look at the terminal, a message will be displayed every 2 seconds.

If we minimize the app, the service will continue to run.

If we terminate the app, it will stop.

Creating Foreground Services

Now let's see how we create a Foreground Service. Create a new class and have it extend the Service class.

Override the `onBind()` and `onStartCommand()` methods.

```
1  import android.app.Service;
2  import android.content.Intent;
3  import android.os.IBinder;
4  import androidx.annotation.Nullable;
5
6  public class MyForegroundService extends Service {
7      @Override
8      public int onStartCommand(Intent intent, int flags, int startId) {
9          return super.onStartCommand(intent, flags, startId);
10     }
11
12     @Nullable
13     @Override
14     public IBinder onBind(Intent intent) {
15         return null;
16     }
17 }
```

MyForegroundService.java hosted with ❤ by GitHub

[view raw](#)

Inside the `onStartCommand()` method, copy the code from the `BackgroundService` and paste it inside.

```
1  @Override
2  public int onStartCommand(Intent intent, int flags, int startId) {
3      new Thread(
4          new Runnable() {
5              @Override
6              public void run() {
7                  while (true) {
8                      Log.e("Service", "Service is running...");
9                      try {
10                         Thread.sleep(2000);
11                     } catch (InterruptedException e) {
12                         e.printStackTrace();
13                     }
14                 }
15             }
16         }
17     ).start();
18     return super.onStartCommand(intent, flags, startId);
19 }
```

MyBackgroundService.java hosted with ❤ by GitHub

[view raw](#)

Go to the manifests file and add the service to the app.

```
1  <?xml version="1.0" encoding="utf-8"?>
2  <manifest xmlns:android="http://schemas.android.com/apk/res/android"
3      package="com.codeible.servicestutorial">
4      <application
5          ...>
6          ...
7      </activity>
8
9      <service android:name=".MyForegroundService"></service>
10
11  </application>
12
13  </manifest>
```

ForegroundService.xml hosted with ❤ by GitHub

[view raw](#)

In order for us to use Foreground Services, we need to add the `FOREGROUND_SERVICE` permission in the manifests file to enable it.

```
<uses-permission
android:name="android.permission.FOREGROUND_SERVICE"></uses-
permission>
```

Starting the Foreground Service

Now we need to start the service.

Go to the MainActivity file. In the `onCreate()` method, replace the `BackgroundService` class with the `ForegroundService` class for the intent.

Instead of calling `startService()`, call `startForegroundService()`.

```
Intent serviceIntent = new Intent(this, MyForegroundService.class);
startForegroundService(serviceIntent);
```

If we run the app, the service should start. However, if we terminate the app, it will stop.

This is because we have not put the service in the Foreground yet. Calling `startForegroundService()` only starts the service, we still need to put it in the Foreground state.

Go back to the Foreground Service class. In the onStartCommand() method, call startForeground().

```
public int onStartCommand(Intent intent, int flags, int startId) {  
    ...  
    startForeground(ID, NOTIFICATION);  
    return super.onStartCommand(intent, flags, startId);  
}
```

It takes 2 arguments. An id for the notification and the notification itself.

The reason we need to provide a notification for a Foreground Service is because we need to let the user know that there is a service from our app that is running even when the app is terminated. The notification cannot be removed until the service is terminated.


Pass in an ID and a notification object.


```
1  @Override
2  public int onStartCommand(Intent intent, int flags, int startId) {
3      new Thread(
4          new Runnable() {
5              @Override
6              public void run() {
7                  while (true) {
8                      Log.e("Service", "Service is running...");
9                      try {
10                         Thread.sleep(2000);
11                     } catch (InterruptedException e) {
12                         e.printStackTrace();
13                     }
14                 }
15             }
16         ).start();
17
18
19     final String CHANNELID = "Foreground Service ID";
20     NotificationChannel channel = new NotificationChannel(
21         CHANNELID,
22         CHANNELID,
23         NotificationManager.IMPORTANCE_LOW
24     );
25
26     getSystemService(NotificationManager.class).createNotificationChannel(channel);
27     Notification.Builder notification = new Notification.Builder(this, CHANNELID)
28         .setContentText("Service is running")
29         .setContentTitle("Service enabled")
30         .setSmallIcon(R.drawable.ic_launcher_background);
31
32     startForeground(1001, notification.build());
33     return super.onStartCommand(intent, flags, startId);
34 }
```

MyForegroundService.java hosted with ❤ by GitHub

[view raw](#)

If we run the app and terminate the app, the service should still be running and we'll see the notification in the notification tray.



Although it is working as intended, we still need to do one more thing to properly handle Foreground Services. Because they stay alive even after the app is terminated, whenever the app gets relaunched, another service will be created, and we'll end up with multiple of the same service running at the same time.

To stop this from happening, every time we want to start the service, we need to check if it is already running first.

Go back to the MainActivity file. Create a Boolean method call `foregroundServiceRunning()` and have it return false by default.

```
1  public boolean foregroundServiceRunning(){
2      return false;
3  }
```

MainActivity.java hosted with ❤ by GitHub

[view raw](#)

Inside the method get a reference to the ActivityManager using `getSystemService()`.

Then use a For Loop and loop through all the active services that are running for the app.

During each iteration, check if there is a service that matches our Foreground Service. If there is, return true.

```
1 public boolean foregroundServiceRunning(){
2     ActivityManager activityManager = (ActivityManager) getSystemService(Context.ACTIVITY_SERVICE);
3     for(ActivityManager.RunningServiceInfo service: activityManager.getRunningServices(Integer.MAX_VALUE)){
4         if(MyForegroundService.class.getName().equals(service.service.getClassName())) {
5             return true;
6         }
7     }
8     return false;
9 }
```

MainActivity.java hosted with ❤ by GitHub

[view raw](#)

In the onCreate() method, check if the service is not running first. If it is not running, we want to start the service.

```
if(!foregroundServiceRunning()) {
    Intent serviceIntent = new Intent(this,
        MyForegroundService.class);
    startForegroundService(serviceIntent);
}
```

If we run the app, and then terminate it, and then relaunch the app, it'll not start the service again.

Restarting the Foreground Service on Reboot

Sometimes you may want to restart a Foreground Service when the user reboots the system. We can achieve this by using a BroadcastReceiver.

The purpose of the Broadcast Receiver is to send or receive messages from the Android System.

When the user reboots their device, Android will send out a message telling everyone that the system was rebooted. We need to create a BroadcastReceiver to receive that message so we can restart Foreground Service.

To create a BroadcastReceiver, create a new class and have it extend the BroadcastReceiver class.



```
1  import android.content.BroadcastReceiver;
2  import android.content.Context;
3  import android.content.Intent;
4
5  public class MyBroadcastReceiver extends BroadcastReceiver {
6      @Override
7      public void onReceive(Context context, Intent intent) {
8
9      }
10 }
```

MyBroadcastReceiver.java hosted with ❤ by GitHub

[view raw](#)

Now that we have the BroadcastReceiver class, we need to add the BroadcastReceiver in the manifests file to let the app know about it.

Go to the Manifests file.

- (1) Add a receiver element and use the android:name attribute to add the receiver.
- (2) Inside the receiver, add an intent filter element to let the app will know what the receiver will be listening for.
- (3) Add the BOOT_COMPLETED action so it'll listen for when the app is rebooted.
- (4) When that is done, enable the RECEIVE_BOOT_COMPLETE permission.

```
1  <?xml version="1.0" encoding="utf-8"?>
2  <manifest xmlns:android="http://schemas.android.com/apk/res/android"
3      package="com.codeible.servicestutorial">
4      <uses-permission android:name="android.permission.FOREGROUND_SERVICE"></uses-permission>
5      <uses-permission android:name="android.permission.RECEIVE_BOOT_COMPLETED"></uses-permission>
6      <application
7          ...>
8          <activity android:name=".MainActivity">
9              ...
10         </activity>
11         ...
12         <receiver android:name=".MyBroadcastReceiver">
13             <intent-filter>
14                 <action android:name="android.intent.action.BOOT_COMPLETED"></action>
15             </intent-filter>
16         </receiver>
17     </application>
18
19
20 </manifest>
```

broadcast-receiver.xml hosted with ❤ by GitHub

[view raw](#)

Now go back to the BroadcastReceiver class. In the onReceive() method, check if the action we received from the intent is equal to ACTION_BOOT_COMPLETED. If it is, we want to start the Foreground Service.

```
@Override
public void onReceive(Context context, Intent intent) {
    if(intent.getAction().equals(Intent.ACTION_BOOT_COMPLETED)) {
        Intent serviceIntent = new Intent(context,
            MyForegroundService.class);
        context.startForegroundService(serviceIntent);
    }
}
```

If we run the app and then restart the device the service should start up automatically on its own.

[Click here to download the project.](#)



Codeible.com Image

Understanding and Using Services in Android: Background & Foreground Services

Hello, in this tutorial, I will show you how to utilize Background and Foreground Services in Android. There are 3...

codeible.com



Android App Development

AndroidDev

Java

Codeible

Android



Written by Codeible

121 Followers

Spreading Coding Knowledge to Viewers

Follow



More from Codeible



Codeible

Adding, Loading, and Using JavaScript in Angular

Learn how to load and use JavaScript code inside your Angular project

3 min read · Sep 26, 2022



51



2





Codeible

Android Notifications with Firebase Cloud Messaging

By King (Codeible.com)


6 min read · Aug 9, 2021



124



1



Codeible

Swipe or Slide and Drag and Drop items in RecyclerView

Hello, in this tutorial, I'll be showing you how to add swipe and drag gesture events to a RecyclerView.

5 min read · Aug 25, 2022

 37  1



HTTP REQUEST for Blueprints



Codeible

Making a HTTP Request in Unreal Engine Blueprints using One Node

Hello, in this tutorial, I will show you how to make http requests in Unreal Engine using the HTTP Requests for Blueprints plugin with one...

4 min read · Mar 12

 41 



See all from Codeible

Recommended from Medium



WorkManager With Hilt

Without **WorkerFactory**



Abdellah Ibn El Azraq

How to use WorkManager with Hilt in Android

In the fast-paced world of mobile app development, managing background tasks effectively is a crucial aspect of creating robust and...

3 min read · Oct 8



13



Kirill Rozov in ProAndroidDev

What's new in Android 14 for developers

Review of most important changes in API and new features in Android 14 that developers need to adopt

21 min read · Oct 5



1.97K



11



Lists



General Coding Knowledge

20 stories · 645 saves



Medium Publications Accepting Story Submissions

155 stories · 1175 saves



New_Reading_List

174 stories · 215 saves



Staff Picks

529 stories · 494 saves



Manu Aravind

How to secure Api key in Android

Securing API keys in Android is important to prevent unauthorized access to your APIs and sensitive information. Here are some approaches...

1 min read · Aug 24

👏 3 💬 1

🔖⁺ ⋮



Benoit Ruiz in Better Programming

Advice From a Software Engineer With 8 Years of Experience


Practical tips for those who want to advance in their careers

22 min read · Mar 21

👏 12.5K 💬 241

🔖⁺ ⋮

BEST PRACTISES VIEWMODEL



Mukul Jangir in Stackademic

Best Practises In ViewModel

Why do we need ViewModel?

5 min read · Oct 30



452



10



Abhishek Pathak

Secured Shared Preferences in Android

In Android app development, data storage is a crucial aspect to consider. One of the most commonly used methods to store small amounts of...

4 min read · Jul 28



50



See more recommendations