

```
resolve ( did, input-metadata ) -> ( did-document, did-document-metadata, did-resolution-metadata )
```

```
input-metadata = { accept: application/did+ld+json,  
                    version-time: 1570534405 }
```

```
did-document-metadata = { created: 1570534300,  
                           controller: did:example:123 }
```

```
did-resolution-metadata = { content-type: application/did+ld+json,  
                             resolution-time: 1570540333,  
                             cached: false }
```

```
GET /resolve/did HTTP/1.1  
Host: myresolver.com  
Accept: application/did+ld+json  
DID-Version-Time: 1570534405  
[ other input-metadata as HTTP request headers ]
```

->

```
HTTP/1.1 200 OK  
DID-Created: 1570534300  
DID-Controller: did:example:123  
[ other did-document-metadata as HTTP response headers ]  
Content-Type: application/did+ld+json  
DID-Resolution-Time: 1570540333  
[ other did-resolution-metadata as HTTP response headers ]
```

```
{  
  "@context": "https://www.w3.org/ns/did/v1",  
  [ did-document ]  
}
```

```
resolve ( did, input-metadata ) -> ( did-document, did-document-metadata, did-resolution-metadata )
```

```
input-metadata = { accept: application/did+ld+json,  
                    version-time: 1570534405 }
```

```
did-document-metadata = { created: 1570534300,  
                           controller: did:example:123 }
```

```
did-resolution-metadata = { content-type: application/did+ld+json,  
                             resolution-time: 1570540333,  
                             cached: false }
```

```
GET /resolve/did HTTP/1.1  
Host: myresolver.com  
Accept: application/did+ld+json  
DID-Version-Time: 1570534405  
[ other input-metadata as HTTP request headers ]
```

```
->
```

```
HTTP/1.1 200 OK  
Content-Type: application/did+ld+json
```

```
{  
  "@context": "https://www.w3.org/ns/did-resolution/v1 ",  
  "didDocument": {  
    [ did-document ]  
  },  
  "didDocumentMetadata": {  
    [ did-document-metadata ]  
  },  
  "resolutionMetadata": {  
    [ did-resolution-metadata ]  
  }  
}
```

```
resolve ( did, input-metadata ) -> ( did-document, did-document-metadata, did-resolution-metadata )
```

```
input-metadata = { accept: application/did+ld+json,  
                    version-time: 1570534405 }
```

```
did-document-metadata = { created: 1570534300,  
                           controller: did:example:123 }
```

```
did-resolution-metadata = { content-type: application/did+ld+json,  
                             resolution-time: 1570540333,  
                             cached: false }
```

```
GET /resolve/did HTTP/1.1  
Host: myresolver.com  
Accept: application/did+ld+json  
DID-Version-Time: 1570534405  
[ other input-metadata as HTTP request headers ]
```

->

```
HTTP/1.1 200 OK  
Content-Type: application/did+ld+json  
DID-Resolution-Time: 1570540333  
[ other did-resolution-metadata as HTTP response headers ]
```

```
{  
  "@context": "https://www.w3.org/ns/did/v1",  
  [ did-document ],  
  "metadata": {  
    [ did-document-metadata ]  
  }  
}
```