



Executing the dereference() function ...

did:xyz:1234?service=messages&relative-ref=%2Fsome%2Fpath%3Fquery#frag "@context": "https://www.w3.org/ns/did/v1", "id": "did:example:123456789abcdefqhi", "publicKey": [{ "id": "did:example:123456789abcdefghi#keys-1", "type": "RsaVerificationKey2018", "publicKeyPem": "----BEGIN PUB...0101010..END PUB ----\r\n" }], "service": [{ "id": "did:example:123456789abcdefghi#agent", "type": "AgentService", "serviceEndpoint": "https://agent.example.com/8377464" }, { "id": "did:example:123456789abcdefghi#hub", "type": "HubService", "serviceEndpoint": "https://hub.example.com/.identity/did:example:0123456789abcdef/" "id": "did:example:123456789abcdefghi#messages", "type": "MessagingService", "serviceEndpoint": "https://example.com/messages/8377464" }]

(with matrix parameters it would have been like this)

```
did:xvz:1234;service=messages/some/path?query#frag
"@context": "https://www.w3.org/ns/did/v1",
"id": "did:example:123456789abcdefqhi",
"publicKey": [{
  "id": "did:example:123456789abcdefghi#keys-1",
  "type": "RsaVerificationKey2018",
  "publicKeyPem": "----BEGIN PUB...0101010..END PUB ----\r\n"
}],
"service": [{
  "id": "did:example:123456789abcdefghi#agent",
  "type": "AgentService",
  "serviceEndpoint": "https://agent.example.com/8377464"
}, {
  "id": "did:example:123456789abcdefghi#hub",
  "type": "HubService",
  "serviceEndpoint": "https://hub.example.com/.identity/did:example:0123456789abcdef/"
  "id": "did:example:123456789abcdefghi#messages",
  "type": "MessagingService",
  "serviceEndpoint": "https://example.com/messages/8377464"
}]
```

https://example.com/messages/8377464/some/path?query#frag

Executing the dereference() function via HTTP(S) binding...

did:xyz:1234?service=messages&relative-ref=%2Fsome%2Fpath%3Fquery#frag

GET

https://myresolver.io/

did%3Axyz%3A1234%3Fservice%3Dmessages%26relative-ref%3D%252Fsome%252Fpath%253Fquery%23frag?no-cache=1

https://example.com/messages/8377464/some/path?query#frag