

Pointer 1

Computer Science Department
Eastern Washington University
Yun Tian (Tony) Ph.D.

Recall

- C Arrays
- Two types
 - ‘static’ Array
 - Dynamic Array
 - Their differences
- How to use ‘static’ array in C program

Today

- Concept of address
- Concept of pointers
- How to define/declare pointers
- How to use pointers?

Motivation


- Some C programming tasks are performed more easily with pointers.
- Some tasks cannot be performed without using pointers.
 - Dynamic memory allocation.
 - Linked Structures like linked list and Tree
- So it becomes necessary to learn pointers.

Concept of Address

- Every variable needs a memory location(as container),
 - We use the variable name to refer to the value stored in that container.
- Every memory location has its address defined,
 - We can obtain the address by using ampersand (&) operator.
 - `int age = 69;`
 - Age is a variable, we use the variable name to refer to its value.


Concept of Address

- `int age = 69;`
 - age is a variable, we use the variable name to refer to its value,
 - That is, the variable name also refer to the value container.



Memory Allocation

- `int age = 69;` in `main()` or in another function
 - The memory space (the box or the container below) for variable **age** is allocated automatically when system calls that function.
 - It is deallocated automatically once the function returns.



Concept of Address

```
#include <stdio.h>
int main ()
{
    int var1;
    char arr[4];

    printf("Address of var1 variable: %x\n", &var1 );
    printf("Value of arr: %x\n", arr );
    printf("Address of arr[0] variable: %x\n", &arr[0] );
    printf("Address of arr[1] variable: %x\n", &arr[1] );
    printf("Address of arr[2] variable: %x\n", &arr[2] );
    printf("Address of arr[3] variable: %x\n", &arr[3] );
    return 0;
} //Demo pointerArray.c
```


Concept of Address

- Output of the program

```
Address of var1 variable: 5b7b8be8  
Value of arr: 5b7b8be4  
Address of arr[0] variable: 5b7b8be4  
Address of arr[1] variable: 5b7b8be5  
Address of arr[2] variable: 5b7b8be6  
Address of arr[3] variable: 5b7b8be7
```

5b7b8be4	5b7b8be5	5b7b8be6	5b7b8be7
arr[0]	arr[1]	arr[2]	arr[3]

We observe that `&arr[0]` and `arr` return the same value.
That means the array name **arr could be used as the array base address.**

Concept of Address

```
#include <stdio.h>
int main ()
{
    int var1;
    int arr[4];

    printf("Address of var1 variable: %x\n", &var1 );
    printf("Value of arr: %x\n", arr );
    printf("Address of arr[0] variable: %x\n", &arr[0] );
    printf("Address of arr[1] variable: %x\n", &arr[1] );
    printf("Address of arr[2] variable: %x\n", &arr[2] );
    printf("Address of arr[3] variable: %x\n", &arr[3] );
    return 0;
}
```

Concept of Address

- Output of the program

```
Address of var1 variable: 5cc9ebe0  
Value of arr: 5cc9ebd0  
Address of arr[0] variable: 5cc9ebd0  
Address of arr[1] variable: 5cc9ebd4  
Address of arr[2] variable: 5cc9ebd8  
Address of arr[3] variable: 5cc9ebdc
```

5cc9ebd0	5cc9ebd4	5cc9ebd8	5cc9ebdc
arr[0]	arr[1]	arr[2]	arr[3]

We observe that `&arr[0]` and `arr` return the same value.
That means the array name **arr could be used as the array base address.**

Concept of Address


- What are the new output after we change the array type from char array to integer array?
- What changes have you observed ?

Concept of Pointer

- A pointer is a **variable** whose value is the address of another variable.
 - Normally, a regular variable directly contains a specific value.
 - Use variable name to retrieve its value.
 - A pointer, on the other hand, contains an **address** of a variable that contains a specific value.

Concept of Pointer

- In this sense, a variable name **directly** references a value, and a pointer **indirectly** references a value.
- Referencing a value through a pointer is called indirection or **dereferencing a pointer**.



Directly and indirectly referencing a variable.

Define Pointer Variables

- Like any variable or constant, you must define a pointer before you can use it to store any variable address.
- To define/declare a pointer variable,
- `type * ptrName;`
 - **type** is the pointer's base type; it must be a valid C data type
 - **ptrName** is the name of the pointer variable.
 - The asterisk `*` you used to declare a pointer.

Define Pointer Variables

E.g.

```
int *ip;
```

- pointer to an integer, variable **ip** should hold an address of another integer variable.

```
double *dp;
```

- pointer to a double

```
float *fp;
```

- pointer to a float

```
char *ch
```


- pointer to a character

Memory Allocation

- `int * iptr;` in main or in a function,
- The memory space for holding a **memory address** is allocated automatically for variable `iptr`.
- When the function returns, that memory space (the box for `iptr` itself) is deallocated automatically. **But, the memory that `iptr` points to is not included in this deallocation.**

Memory Allocation

- `int * iptr;` in main or in a function,
 - The box on the right, `iptr` is a memory cell, used to hold a memory address of another int variable.
 - The variable **`iptr`** like regular variables in C, has a address associated with it, (shown outside of box)



Memory Allocation

- `int * iptr;` in main or in a function,
- After we create the pointer, before we initialize it, it could contains arbitrary(junk) memory address.
 - In other word, `iptr` right now points to arbitrary memory location.



Initialize Pointer

- `int age=10;` → memory allocated automatically
- `int * iptr;` → in main or in the same function as previous statement.
- `iptr = &age;`
- After this assignment, `iptr` points to variable **age**.



Initialize Pointer

- In C programming, we usually don't care about the specific value that a pointer variable holds(in binary format), but we really care about which variable it currently points to.



- Next class, we will learn this,
 - `int arr[4] = { 1, 2, 4, 9};`
 - `int *iptr = arr;`

Use Pointer

- Typical way to use a pointer variable,
 - (a) we define a pointer variable
 - (b) assign the address of a variable to the pointer
 - (c) finally access the value at the address contained in the pointer variable.
 - We say **‘access the value that the pointer points to’**.

Use Pointer

- Step (c) is done by using unary operator `*` that returns the value of the variable located at the address specified by its operand.
- E.g.
 `int a = 10;`
 `int *ptr = &a;`
 `*ptr = 100; //this changes the value of variable a`
 `int total=3 + *ptr;`
 `*ptr`, return the value of variable **a**, **because ptr points to a**, or **because ptr holds the address of variable a**.

Use Pointer

- ***ptr, is the to dereference pointer ptr.**
 - That is, it returns the value at the memory address stored in variable ptr.
 - More simply, ***ptr**, returns the value that ptr variable points to.



- If you draw this picture above, actually ***ptr** operation, will follow the arrow from ptr box, and return the value in the box to which the arrow points.

Demo

- `pointer1.c`

Summary

- Concept of address
- Concept of pointers
- How to define/declare pointers
- How to use pointers?

Next Class

- Make files and Debug tools