

PDM Professional Web API (REST) — Reference (1/3): g-081b00cf-917a-401f-9276-9f29de5178b5-r-api-{vaultName}-files-{fileId}-bominfo

SOLIDWORKS API Documentation (converted from CHM)

PDM Pro API Web Service

Default Resource Group

Description

URI services. You must send [api/{vaultName}/authenticate](#) before calling these. See [Getting Started](#).

Operations

POST	api/{uri} Uses the specified URI to post information.
PUT	api/{uri} Uses the specified URI to save information.
PATCH	api/{uri} Uses the specified URI to patch information.
DELETE	api/{uri} Uses the specified URI to delete information.

See Also

[PDM Pro API Web Service](#)

PDM Pro API Web Service

User Resource Group

Description

User services. You must send [api/{vaultName}/authenticate](#) before calling these. See [Getting Started](#).

Operations

GET	api/{vaultName}/users/{userId} GET: api/{VaultName}/users/{UserID} or api/{VaultName}/users/{UserID}/info Get user info Gets information about the specified user.
GET	api/{vaultName}/users/{userId}/Extended GET: api/{VaultName}/users/{UserID}/Extended Get user info extended Gets extended information about the specified user.
PUT	api/{vaultName}/users/{userId}/Extended PUT: api/{VaultName}/users/{UserID}/Extended Set user info extended Saves information about the specified user.
GET	api/{vaultName}/users/{userId}/info GET: api/{VaultName}/users/{UserID} or api/{VaultName}/users/{UserID}/info Get user info Gets information about the specified user.
GET	api/{vaultName}/users/{userId}/Picture GET: api/{VaultName}/users/{UserID}/Picture Get user picture Gets the picture of the specified user.
PUT	api/{vaultName}/users/{userId}/Picture PUT: api/{VaultName}/users/{UserID}/Picture Put user picture Saves the picture of the specified user.
DELETE	api/{vaultName}/users/{userId}/Picture DELETE: api/{VaultName}/users/{UserID}/Picture Delete user picture Deletes the picture of the specified user.
GET	api/{vaultName}/users/all GET: api/{VaultName}/users or api/{VaultName}/users/all Get users Gets the users of the specified vault.

See Also

[PDM Pro API Web Service](#)

Description

File services. You must send `api/{vaultName}/authenticate` before calling these. See [Getting Started](#).

Operations

GET	<code>api/{vaultName}/files/{fileId}/{folderId}/history</code> Gets a specified file's history.
GET	<code>api/{vaultName}/files/{fileId}/{folderId}/moves</code> Gets the history of moves for the specified file.
GET	<code>api/{vaultName}/files/{fileId}/{folderId}/versions</code> GET: <code>api/{VaultName}/files/{FileID}/versions</code> Get file version info Gets the specified file's version information.
DELETE	<code>api/{vaultName}/files/{fileId}/{folderId}?destroy={destroy}</code> Deletes the specified file.
GET	<code>api/{vaultName}/files/{fileId}/{version}/{configId}/{folderId}/whereused?anyVersion={anyVersion}</code> GET: <code>api/{VaultName}/files/{FileID}/{Version}/whereused</code> Get file where usedGets the parent files where the specified file is used.
GET	<code>api/{vaultName}/files/{fileId}/{version}/{configId}/whereused?folderId={folderId}&anyVersion={anyVersion}</code> GET: <code>api/{VaultName}/files/{FileID}/{Version}/whereused</code> Get file where usedGets the parent files where the specified file is used.
GET	<code>api/{vaultName}/files/{fileId}/{version}/{folderId}</code> Gets information about the specified file.
GET	<code>api/{vaultName}/files/{fileId}/{version}/{folderId}/ActiveConfig</code> Gets the active configuration for the specified file.
GET	<code>api/{vaultName}/files/{fileId}/{version}/{folderId}/allreferences?configId={configId}&includeSubParents={includeSubParents}</code> GET: <code>api/{VaultName}/files/{FileID}/{Version}/allreferences</code> Get all file references Gets the reference tree of the specified file.
GET	<code>api/{vaultName}/files/{fileId}/{version}/{folderId}/configurations</code> Gets the configurations for the specified file.
GET	<code>api/{vaultName}/files/{fileId}/{version}/{folderId}/download</code> Gets the specified file.
GET	<code>api/{vaultName}/files/{fileId}/{version}/{folderId}/info</code> Gets information about the specified file.
GET	<code>api/{vaultName}/files/{fileId}/{version}/{folderId}/info/extended</code> Gets extended version information for a specified file.
GET	<code>api/{vaultName}/files/{fileId}/{version}/{folderId}/references?configId={configId}</code> GET: <code>api/{VaultName}/files/{FileID}/{Version}/references</code> Get file references Gets the top level file references of the specified file.
GET	<code>api/{vaultName}/files/{fileId}/{version}/{folderId}/thumbnails</code> Gets a specified file's thumbnail.
GET	<code>api/{vaultName}/files/{fileId}/{version}/{folderId}/transitions</code> Gets the file transitions for the specified file.
GET	<code>api/{vaultName}/files/{fileId}/{version}/{folderId}/variables</code> Gets configuration variable information for the specified file.
GET	<code>api/{vaultName}/files/{fileId}/{version}/ActiveConfig?folderId={folderId}</code> Gets the active configuration for the specified file.
GET	<code>api/{vaultName}/files/{fileId}/{version}/allreferences?configId={configId}&folderId={folderId}&includeSubParents={includeSubParents}</code> GET: <code>api/{VaultName}/files/{FileID}/{Version}/allreferences</code> Get all file references

	Gets the reference tree of the specified file.
GET	api/{vaultName}/files/{fileId}/{version}/configurations?folderId={folderId} Gets the configurations for the specified file.
GET	api/{vaultName}/files/{fileId}/{version}/download?folderId={folderId} Gets the specified file.
GET	api/{vaultName}/files/{fileId}/{version}/info/extended?folderId={folderId} Gets extended version information for a specified file.
GET	api/{vaultName}/files/{fileId}/{version}/info?folderId={folderId} Gets information about the specified file.
GET	api/{vaultName}/files/{fileId}/{version}/references?configId={configId}&folderId={folderId} GET: api/{VaultName}/files/{FileID}/{Version}/references Get file references Gets the top level file references of the specified file.
GET	api/{vaultName}/files/{fileId}/{version}/thumbnails?folderId={folderId} Gets a specified file's thumbnail.
GET	api/{vaultName}/files/{fileId}/{version}/transitions?folderId={folderId} Gets the file transitions for the specified file.
GET	api/{vaultName}/files/{fileId}/{version}/variables?folderId={folderId} Gets configuration variable information for the specified file.
GET	api/{vaultName}/files/{fileId}/{version}/whereused?configId={configId}&folderId={folderId}&anyVersion={anyVersion} GET: api/{VaultName}/files/{FileID}/{Version}/whereused Get file where used Gets the parents of the specified file.
GET	api/{vaultName}/files/{fileId}/{version}?folderId={folderId} Gets information about the specified file.
GET	api/{vaultName}/files/{fileId}/bominfo?folderId={folderId} GET: api/{VaultName}/files/{FileID}/bominfo Get file BOM info Gets the BOM information for the specified file.
GET	api/{vaultName}/files/{fileId}/history?folderId={folderId} Gets a specified file's history.
GET	api/{vaultName}/files/{fileId}/info?version={version}&folderId={folderId} Gets information about the specified file.
GET	api/{vaultName}/files/{fileId}/moves?folderId={folderId} Gets the history of moves for the specified file.
GET	api/{vaultName}/files/{fileId}/transitions?version={version}&folderId={folderId} Gets the file transitions for the specified file.
GET	api/{vaultName}/files/{fileId}/versions?folderId={folderId} GET: api/{VaultName}/files/{FileID}/versions Get file version info Gets the specified file's version information.
DELETE	api/{vaultName}/files/{fileId}?folderId={folderId}&destroy={destroy} Deletes the specified file.
GET	api/{vaultName}/files/{fileId}?version={version}&folderId={folderId} Gets information about the specified file.
POST	api/{vaultName}/files/buildtree/checkout POST: api/{VaultName}/files/buildtree/checkout Build checkout references tree Gets the tree of references in the specified file's checkout.
POST	api/{vaultName}/files/buildtree/undo POST: api/{VaultName}/files/buildtree/undo Build undo checkout references tree

	Builds the reference tree to undo the checkout of the specified file.
POST	api/{vaultName}/files/CheckOut POST: api/{VaultName}/files/CheckOut Lock file Checks out the specified file(s).
POST	api/{vaultName}/files/info POST: api/{VaultName}/files/info Gets information about the specified files.
POST	api/{vaultName}/files/infofrompath Gets information about a file in the specified vault.
POST	api/{vaultName}/files/UndoCheckOut POST: api/{VaultName}/files/UndoCheckOut Undo lock file Unlocks the specified file.

See Also

[PDM Pro API Web Service](#)

PDM Pro API Web Service

BOM Resource Group

Description

This resource group consists of BOM HTTP requests. You must send `api/{vaultName}/authenticate` before calling these. See [Getting Started](#).

Operations

GET	<code>api/{vaultName}/bom/{bomTypeId}/{fileId}/{version}/{folderId}/computed?configId={configId}&latest={latest}</code> GET: <code>api/{VaultName}/bom/{BomTypeId}/{FileID}/{Version}/{FolderID}/weldmentcutlist</code> or <code>api/{VaultName}/bom/{BomTypeId}/{FileID}/{Version}/{FolderID}/computed</code> Get computed BOM Gets the computed BOM.
GET	<code>api/{vaultName}/bom/{bomTypeId}/{fileId}/{version}/{folderId}/weldmentcutlist?configId={configId}&latest={latest}</code> GET: <code>api/{VaultName}/bom/{BomTypeId}/{FileID}/{Version}/{FolderID}/weldmentcutlist</code> or <code>api/{VaultName}/bom/{BomTypeId}/{FileID}/{Version}/{FolderID}/computed</code> Get computed BOM Gets the weldment cut list BOM.

See Also

[PDM Pro API Web Service](#)

PDM Pro API Web Service

Progress Resource Group

Description

Progress services. You must send `api/{vaultName}/authenticate` before calling these. See [Getting Started](#).

Operations

GET	<code>api/{vaultName}/progress/{guid}/status</code>
	GET: <code>api/{vaultName}/progress/{guid}/status</code> Get operation status
	Gets the status of the specified operation.

See Also

[PDM Pro API Web Service](#)

PDM Pro API Web Service

Vault Resource Group

Description

Vault services. You must send [api/{vaultName}/authenticate](#) before calling these. See [Getting Started](#).

Operations

POST	api/{vaultName}/delete/computetree POST: api/{VaultName}/delete/computetree Delete compute tree Deletes the specified items in the specified vault.
GET	api/{vaultName}/info GET: api/{VaultName} or api/{VaultName}/info Get vault properties Gets the properties of the specified vault.

See Also

[PDM Pro API Web Service](#)

PDM Pro API Web Service

State Transition Resource Group

Description

State transition services. You must send `api/{vaultName}/authenticate` before calling these. See [Getting Started](#).

Operations

GET	<code>api/{vaultName}/state/{documentId}/{folderId}/transitions</code> Gets the transitions available for the specified file.
GET	<code>api/{vaultName}/state/{documentId}/transitions?folderId={folderId}</code> Gets the transitions available for the specified file.
GET	<code>api/{vaultName}/state/{transitionId}</code> GET: <code>api/{vaultName}/state/{transitionId}</code> Get transition info Gets information about the specified transition.
POST	<code>api/{vaultName}/state/{transitionId}/changestate?revoke={revoke}</code> POST: <code>api/{vaultName}/state/{transitionId}/changestate</code> Change state Changes the state of the specified documents.
POST	<code>api/{vaultName}/state/{transitionId}/DynamicNotificationUsers</code> POST: <code>api/{vaultName}/state/{transitionId}/DynamicNotificationUsers</code> Get dynamic notification users Gets the users to notify when the specified items undergo the specified transition.
POST	<code>api/{vaultName}/state/{transitionId}/HistoryComments</code> POST: <code>api/{vaultName}/state/{transitionId}/HistoryComments</code> Get transition comment history for multiple files Gets the comment histories for specified files that undergo the specified transition.
POST	<code>api/{vaultName}/state/transitions</code> POST: <code>api/{vaultName}/state/transitions</code> Get available transitions for multiple files Gets the transitions available for multiple files.

See Also

[PDM Pro API Web Service](#)

PDM Pro API Web Service

Configuration Resource Group

Description

This resource group consists of one HTTP request that gets all of the vaults in the web server's vault.config.json. It also contains several webhook management endpoints. You must send [api/{vaultName}/authenticate](#) before calling some of these endpoints. See [Getting Started](#) and the individual endpoints for details and JSON examples.

Operations

PUT	api/{vaultName}/configuration/hooks/dll Puts add-in hook DLLs in the specified vault.
DELETE	api/{vaultName}/configuration/hooks/dll Deletes add-in hook DLLs from the specified vault.
GET	api/{vaultName}/configuration/hooks/url Retrieves the list of webhooks configured in the specified vault.
POST	api/{vaultName}/configuration/hooks/url Sets the webhooks for the specified vault.
GET	api/configuration/fileserverroot GET: api/configuration/fileserverroot Get file server root path(WebAPI storage)Gets the file server root path.
POST	api/configuration/fileserverroot POST: api/configuration/fileserverroot Add file server root pathMigrates add-ins from previous file server root to the specified new one and reloads hooks instances.
GET	api/configuration/vaults?vaultName={vaultName} GET: api/configuration/vaults Get all vaults from the config file Gets all vaults from the vault configuration file.

See Also

[PDM Pro API Web Service](#)

PDM Pro API Web Service

Workflow Resource Group

Description

Workflow services. You must send [api/{vaultName}/authenticate](#) before calling these. See [Getting Started](#).

Operations

GET	api/{vaultName}/workflows/icons
	GET: api/{vaultName}/workflows/icons Get state icons
	Gets the workflow state icons in the specified vault.

See Also

[PDM Pro API Web Service](#)

PDM Pro API Web Service

Notification Resource Group

Description

Notification services. You must send [api/{vaultName}/authenticate](#) before calling these. See [Getting Started](#).

Operations

POST	api/{vaultName}/notifications/markRead POST: api/{vaultName}/notifications/markRead Mark message as read Marks a notification as read.
GET	api/{vaultName}/notifications?all={all}&pageNo={pageNo}&pageSize={pageSize} GET: api/{VaultName}/notifications Get user notifications Gets the user notifications.

See Also

[PDM Pro API Web Service](#)

PDM Pro API Web Service

Stage Resource Group

Description

This resource group consists of HTTP requests for uploading and checking in files to your PDM Pro vault. You must send `api/{vaultName}/authenticate` before calling these. See [Getting Started](#).

Operations

PUT	<code>api/{vaultName}/checkin/{changesetId}/{overrideVersion}</code> PUT: <code>api/{vaultName}/checkin/{changesetId}/{overrideVersion=false}</code> Check in files from the changeset Checks in the specified changeset.
PUT	<code>api/{vaultName}/checkin/addfiles/{changesetId}</code> PUT: <code>api/{vaultName}/checkin/addfiles/{changesetId=0}</code> Upload files or document ids to changeset to the check in operation Adds files to a changeset for checkin. (See Remarks)
GET	<code>api/{vaultName}/checkin/buildtree/{changesetId}</code> GET: <code>api/{vaultName}/checkin/buildtree/{changesetId}</code> Get references tree Builds a reference tree of files that are uploaded to the specified changeset.
PUT	<code>api/{vaultName}/files/{changesetId}/finishadd</code> PUT: <code>api/{vaultName}/files/{changesetId}/finishadd</code> Finish of add file operation. This method adds files from changeset to the vault. Adds files in the specified changeset to the vault. (See Remarks)
PUT	<code>api/{vaultName}/files/{changesetId}/upload</code> PUT: <code>api/{vaultName}/files/{changesetId}/upload</code> Upload file to changeset to add files operations Uploads files to the specified changeset. (See Remarks)
PUT	<code>api/stage/{vaultName}/{documentId}?folderId={folderId}&overrideVersion={overrideVersion}</code> Checks in the specified document.

See Also

[PDM Pro API Web Service](#)

PDM Pro API Web Service

Search Resource Group

Description

Search services. You must send [api/{vaultName}/authenticate](#) before calling these. See [Getting Started](#).

Operations

POST	api/{vaultName}/search Gets objects in the vault that contain the specified string.
POST	api/{vaultName}/searchvariables Specifies parameters and variables for a search.

See Also

[PDM Pro API Web Service](#)

PDM Pro API Web Service

Data Card Resource Group

Description

This resource group consists of Data card HTTP requests. You must send `api/{vaultName}/authenticate` before calling these. See [Getting Started](#).

Operations

GET	api/{vaultName}/files/{fileId}/{version}/datacard?folderId={folderId} GET: api/{VaultName}/files/{FileID}/{Version}/datacard Get file data card Gets the data card for the specified file, file version, and vault.
POST	api/{vaultName}/files/{fileId}/datacard?folderId={folderId} Saves the specified data card variables to the specified file.
GET	api/{vaultName}/folders/{folderId}/datacard GET: api/{VaultName}/folders/{FolderID}/datacard Get folder data card Gets the data card for the specified folder and vault.

See Also

[PDM Pro API Web Service](#)

PDM Pro API Web Service
Authentication Resource Group

Description

This resource group consists of an authentication HTTP request which you need to send before all other requests. See [Getting Started](#).

Operations

See Also

[PDM Pro API Web Service](#)

PDM Pro API Web Service

Version Resource Group

Description

Version service. See [Getting Started](#).

Operations

See Also

[PDM Pro API Web Service](#)

PDM Pro API Web Service

Folder Resource Group

Description

Folder services. You must send [api/{vaultName}/authenticate](#) before calling these. See [Getting Started](#).

Operations

GET	api/{vaultName}/folders/{folderId}/browse GET: api/{VaultName}/folders/{FolderID}/browse Get browse folder Gets the files and folders in the specified folder.
GET	api/{vaultName}/folders/{folderId}/info GET: api/{VaultName}/folders/{FolderID} or api/{VaultName}/folders/{FolderID}/info Get folder info Gets information for the specified folder.
DELETE	api/{vaultName}/folders/{folderId}?destroy={destroy} DELETE: api/{VaultName}/folders/{FolderID} Delete folder Deletes the specified folder.
PUT	api/{vaultName}/folders/{parentFolderId} PUT: api/{VaultName}/folders/{ParentFolderID} Add folder Adds a folder to the specified folder.
POST	api/{vaultName}/folders/info POST: api/{VaultName}/folders/info Get folder info Gets information about specified folders in the specified vault.

See Also

[PDM Pro API Web Service](#)

PDM Pro API Web Service

Group Resource Group

Description

User group services. You must send [api/{vaultName}/authenticate](#) before calling these. See [Getting Started](#).

Operations

GET	api/{vaultName}/groups/{groupId} GET: api/{VaultName}/groups/{GroupID} or api/{VaultName}/groups/{GroupID}/info Get group info Gets information about the specified group.
GET	api/{vaultName}/groups/{groupId}/info GET: api/{VaultName}/groups/{GroupID} or api/{VaultName}/groups/{GroupID}/info Get group info Gets information about the specified group.
GET	api/{vaultName}/groups/all GET: api/{VaultName}/groups or api/{VaultName}/groups/all Get groups Gets the groups in the specified vault.

See Also

[PDM Pro API Web Service](#)

PDM Pro API Web Service

GETapi/configuration/fileserverroot

Description

GET: api/configuration/fileserverroot Get file server root path(WebAPI storage)Gets the file server root path.

Response (application/json, text/json)

Sample Data

"sample string 1"

Response (application/xml, text/xml)

Sample Data

<string xmlns="http://schemas.microsoft.com/2003/10/Serialization/">sample string 1</string>

Example

Click and save the following to your computer. Then drag/drop it into Postman:

GetPostFileServerRoot.postman_collection.json

Remarks

See the [PDM Pro Web API Webhooks Programming Guide](#).

See Also

[Configuration Resource Group | PDM Pro API Web Service](#)

PDM Pro API Web Service

POSTapi/configuration/fileserverroot

Description

POST: api/configuration/fileserverroot Add file server root pathMigrates add-ins from previous file server root to the specified new one and reloads hooks instances.

Request (application/json, text/json)

Sample Data

"sample string 1"

Request (application/xml, text/xml)

Sample Data

<string xmlns="http://schemas.microsoft.com/2003/10/Serialization/">sample string 1</string>

Request (application/x-www-form-urlencoded)

Response (application/json, text/json)

Sample Data

true

Response (application/xml, text/xml)

Sample Data

<boolean xmlns="http://schemas.microsoft.com/2003/10/Serialization/">>true</boolean>

Example

Click and save the following to your computer. Then drag/drop it into Postman:

[GetPostFileServerRoot.postman_collection.json](#)

In Postman, modify the Body of fileserverroot (Post) for your file server root location.

Remarks

See the [PDM Pro Web API Webhooks Programming Guide](#).

See Also

[Configuration Resource Group](#) | [PDM Pro API Web Service](#)

GET

api/configuration/vaults?vaultName={vaultName}

Description

GET: api/configuration/vaults Get all vaults from the config file

Gets all vaults from the vault configuration file.

Parameters

vaultName	(URI parameter) Vault name (default is empty string)	string
	(Response) Vault name matching regular expression pattern: <code>^[^\W:]*?"<>]+\$</code>	
Name	Member of VaultProperties model See the Remarks .	string
	(Response) Database name matching regular expression pattern: <code>^[^\W:]*?"<>]+\$</code>	
DatabaseName	Member of VaultProperties model See the Remarks .	string
ArchiveServer	Archive server name Member of VaultProperties model See the Remarks .	string
ArchiveServerPort	Archive server port Member of VaultProperties model See the Remarks .	integer
DatabaseServer	Database server Member of VaultProperties model See the Remarks .	string
CommandTimeOut	Length before time out (seconds) Member of VaultProperties model See the Remarks .	integer
IndexingUserId	Indexing user ID Member of VaultProperties model See the Remarks .	integer

Response (application/json, text/json)

Sample Data

```
[
  {
    "Name": "sample string 1",
    "DatabaseName": "sample string 2",
    "ArchiveServer": "sample string 3",
    "ArchiveServerPort": 4,
    "DatabaseServer": "sample string 5",
    "CommandTimeOut": 6,
    "IndexingUserId": 7
  },
  {
    "Name": "sample string 1",
    "DatabaseName": "sample string 2",
    "ArchiveServer": "sample string 3",
```

```

    "ArchiveServerPort": 4,
    "DatabaseServer": "sample string 5",
    "CommandTimeout": 6,
    "IndexingUserId": 7
  }
}

```

Response (application/xml, text/xml)

Sample Data

```

<ArrayOfVaultProperties xmlns:i="http://www.w3.org/2001/XMLSchema-instance"
  xmlns="http://schemas.datacontract.org/2004/07/SWPDM.Configuration">
  <VaultProperties>
    <ArchiveServer>sample string 3</ArchiveServer>
    <ArchiveServerPort>4</ArchiveServerPort>
    <CommandTimeout>6</CommandTimeout>
    <DatabaseName>sample string 2</DatabaseName>
    <DatabaseServer>sample string 5</DatabaseServer>
    <IndexingUserId>7</IndexingUserId>
    <Name>sample string 1</Name>
  </VaultProperties>
  <VaultProperties>
    <ArchiveServer>sample string 3</ArchiveServer>
    <ArchiveServerPort>4</ArchiveServerPort>
    <CommandTimeout>6</CommandTimeout>
    <DatabaseName>sample string 2</DatabaseName>
    <DatabaseServer>sample string 5</DatabaseServer>
    <IndexingUserId>7</IndexingUserId>
    <Name>sample string 1</Name>
  </VaultProperties>
</ArrayOfVaultProperties>

```

Remarks

This operation can return an array of VaultProperties objects. See the Response samples.

See Also

[Configuration Resource Group | PDM Pro API Web Service](#)

PUT

api/stage/{vaultName}/{documentId}?folderId={folderId}&overrideVersion={overrideVersion}

Description

Checks in the specified document.

Parameters

vaultName	(URI parameter) Vault name (required)	string
documentId	(URI parameter) Document ID (required)	integer
folderId	(URI parameter) Folder ID (default is 0)	integer
overrideVersion	(URI parameter) Whether to override the current versions of files (default value is false)	boolean

Response (application/json, text/json)

True if checkin is successful, false if not

Sample Data

true

Response (application/xml, text/xml)

True if checkin is successful, false if not

Sample Data

<boolean xmlns="http://schemas.microsoft.com/2003/10/Serialization/">true</boolean>

See Also

[Stage Resource Group](#) | [PDM Pro API Web Service](#)

GET

api/version/webapi

Description

GET: api/version/webapi Get version

Gets the version of this web application.

Parameters

SwCompany	(Response) Company Member of WebAPIVersionModel model	string
SWCopyright	(Response) Copyright Member of WebAPIVersionModel model	string
ProdName	(Response) Product name Member of WebAPIVersionModel model	string
ProdAppVersion	(Response) Product application version Member of WebAPIVersionModel model	string
ProdFileVersion	(Response) Product file version Member of WebAPIVersionModel model	string

Response (application/json, text/json)

Sample Data

```
{
  "SwCompany": "sample string 1",
  "SWCopyright": "sample string 2",
  "ProdName": "sample string 3",
  "ProdAppVersion": "sample string 4",
  "ProdFileVersion": "sample string 5"
}
```

Response (application/xml, text/xml)

Sample Data

```
<WebAPIVersionModel xmlns:i="http://www.w3.org/2001/XMLSchema-instance" xmlns="http://schemas.datacontract.org/2004/07/SWPDM.Models">
  <ProdAppVersion>sample string 4</ProdAppVersion>
  <ProdFileVersion>sample string 5</ProdFileVersion>
  <ProdName>sample string 3</ProdName>
  <SWCopyright>sample string 2</SWCopyright>
  <SwCompany>sample string 1</SwCompany>
</WebAPIVersionModel>
```

See Also

[Version Resource Group](#) | [PDM Pro API Web Service](#)

DELETE

api/{uri}

Description

Uses the specified URI to delete information.

Parameters

uri	(URI parameter) Uniform resource identifier (required)	string
-----	--	--------

Response (application/json, text/json, application/xml, text/xml)

See Also

[Default Resource Group](#) | [PDM Pro API Web Service](#)

GET

api/{uri}

Description

Uses the specified URI to get information.

Parameters

uri	(URI parameter) Uniform resource identifier (required)	string
-----	--	--------

Response (application/json, text/json, application/xml, text/xml)

See Also

[Default Resource Group](#) | [PDM Pro API Web Service](#)

PATCH

api/{uri}

Description

Uses the specified URI to patch information.

Parameters

uri	(URI parameter) Uniform resource identifier (required)	string
-----	--	--------

Response (application/json, text/json, application/xml, text/xml)

See Also

[Default Resource Group](#) | [PDM Pro API Web Service](#)

POST

api/{uri}

Description

Uses the specified URI to post information.

Parameters

uri	(URI parameter) Uniform resource identifier (required)	string
-----	--	--------

Response (application/json, text/json, application/xml, text/xml)

See Also

[Default Resource Group](#) | [PDM Pro API Web Service](#)

PDM Pro API Web Service

PUT

api/{uri}

Description

Uses the specified URI to save information.

Parameters

uri	(URI parameter) Uniform resource identifier (required)	string
-----	--	--------

Response (application/json, text/json, application/xml, text/xml)

See Also

[Default Resource Group](#) | [PDM Pro API Web Service](#)

GET

api/**{vaultName}**

Description

GET: api/{VaultName} or api/{VaultName}/info Get vault properties

Gets the properties of the specified vault.

Parameters

vaultName	(URI parameter) Vault name (required)	string
Version	(Response) Vault version	integer
	Member of VaultProp model	
VaultType	(Response) Type of vault	string
	Member of VaultProp model	
ArchiveServer	(Response) Archive server	string
	Member of VaultProp model	
DatabaseName	(Response) Database name	string
	Member of VaultProp model	
DatabaseServer	(Response) Database server	string
	Member of VaultProp model	
VaultID	(Response) Vault ID	globally unique identifier
	Member of VaultProp model	

Response (application/json, text/json)

Sample Data

```
{
  "Version": 1,
  "VaultType": "sample string 2",
  "ArchiveServer": "sample string 3",
  "DatabaseName": "sample string 4",
  "DatabaseServer": "sample string 5",
  "VaultID": "1008dbe9-546b-4727-9f5d-08dabf9a226e"
}
```

Response (application/xml, text/xml)

Sample Data

```
<VaultProp xmlns:i="http://www.w3.org/2001/XMLSchema-instance" xmlns="http://schemas.datacontract.org/2004/07/SWPDM.Models">
  <ArchiveServer>sample string 3</ArchiveServer>
  <DatabaseName>sample string 4</DatabaseName>
  <DatabaseServer>sample string 5</DatabaseServer>
</VaultProp>
```

```
<VaultID>1008dbe9-546b-4727-9f5d-08dabf9a226e</VaultID>  
<VaultType>sample string 2</VaultType>  
<Version>1</Version>  
</VaultProp>
```

See Also

[Vault Resource Group](#) | [PDM Pro API Web Service](#)

Description

POST: api/{VaultName}/authenticate Use for the authenticate to get authentication token

Authenticates the specified login for the specified vault and returns the authentication token and status.

Parameters

vaultName	(URI parameter) Name of the vault (required)	string
Username	(Body) Login name	string
Password	(Body) Password	string
Version	(Response) Software version information: - Major - Minor - Build - Revision - MajorRevision - MinorRevision Member of HttpResponseMessage model	Version
Content	(Response) Authentication token Member of HttpResponseMessage model	HttpContent
StatusCode	(Response) Status code; see https://en.wikipedia.org/wiki/List_of_HTTP_status_codes Member of HttpResponseMessage model	HttpStatusCode
ReasonPhrase	(Response) Reason Member of HttpResponseMessage model	string
Headers	(Response) Collection of headers Member of HttpResponseMessage model	Collection of Object
RequestMessage	(Response) An HttpRequestMessage object that consists of: Version (Version model) Content (HttpContent object consisting of Headers array) Method (HttpMethod object consisting of Method string) RequestUri (URI) Headers (Array of objects) Properties (Dictionary of string [key] and Object [value]) Member of HttpResponseMessage model	HttpRequestMessage
IsSuccessStatusCode	(Response) True if successful, false if not Member of HttpResponseMessage model	boolean

Request (application/json, text/json)

Body parameter is an array of Username and Password.

Sample Data

```
{
  "Username": "sample string 1",
  "Password": "sample string 2"
}
```

Request (application/xml, text/xml)

Body parameter is an array of Username and Password.

Sample Data

```
<UserCredentials xmlns:i="http://www.w3.org/2001/XMLSchema-instance" xmlns="http://schemas.datacontract.org/2004/07/SWPDM.Models">
  <Password>sample string 2</Password>
  <Username>sample string 1</Username>
</UserCredentials>
```

Request (application/x-www-form-urlencoded)

Body parameter is an array of Username and Password.

Example

Python application (*.py):

#Change the basicUri, vaultname, and payload variable assignments below for your system

```
import requests
import json
basicUri = "http://machine_name:port/api"
vaultname = "vault_name"

# Post api/{vaultName}/authenticate
PostAuthenticateurl = basicUri+vaultname+"/"+authenticate"
payload = "{\"Password\":\"\\\", \"Username\":\"Admin\\\"}"
headers = {
  'Content-Type': 'application/json;charset=UTF-8',
  'version': '30.0'
}
response = requests.request(
  "POST", PostAuthenticateurl, headers=headers, data=payload)
jwtToken = json.loads(response.text)
# This token will be used in all the downstream APIs
token = jwtToken["JwtString"]
# GET api/{vaultName}/folders/{folderId}/browse
Getbrowsefolderurl = basicUri+vaultname+"/"+folders/1/browse"
payload = {}
headers = {
  'Authorization': 'Bearer ' + token
}
response = requests.request(
  "GET", Getbrowsefolderurl, headers=headers, data=payload)
data = json.loads(response.text)
print("All the File Names inside the folder Id = 1 are : ")
for item in data:
  if item["Type"] == 1:
    print(" " + item["Name"])
```

C# console application:

```
//=====
// Preconditions:
// 1. A SOLIDWORKS PDM Professional Web Server is running on a host machine web site.
// 2. SOLIDWORKS PDM Professional is installed and configured with a vault, vault view, and Admin user.
// 3. Create a C# console project in Visual Studio.
// 4. Copy the code below into Program.cs.
// 5. Change the namespace as needed. Change "localhost" and the port in this application's Url string to your host machine's name and available port.
// 6. Change the vaultName and loginuser.password assignments to your vault name and Admin password.
// Postconditions:
// 1. Authenticates the logged-in user. Deserializes the authentication result to create a JSON Web Tokens (JWT) Bearer token.
// 2. Sends GET requests with the Bearer token to obtain all folders and all users in the vault.
// 3. Inspect the console.
//=====
using Newtonsoft.Json;
using System;
using System.Collections.Generic;
using System.IO;
using System.Linq;
using System.Net;
using System.Text;
using System.Threading.Tasks;
using System.Web.Script.Serialization;
namespace ConsoleWebAPIClientHTTPWebReq
{
    class Program
    {
        const string Url = "http://localhost:8082/api/";
        static string JwtString = string.Empty;
        static bool Authorized = false;
        const string vaultName = "2_24_2021";
        static void Main(string[] args)
        {
            try
            {
                string urlLogin = Url + vaultName + "/authenticate";
                UserCredentials loginUser = new UserCredentials();
                loginUser.username = "Admin";
                loginUser.password = String.Empty;
            }
        }
    }
}
```

```

string loginResult = AuthenticateRequest(urlLogin, loginUser);
Authorized = AuthorizationCode(loginResult);
if (Authorized)
{
    // Get all the folders in the root folder of the vault
    Console.WriteLine(" All folders : \n");
    string urlBrowseAllFolder = Url + vaultName + "/folders/1/browse";
    List<ObjectInfo> vaultFolderItems = GetVaultItems(urlBrowseAllFolder);
    foreach (var item in vaultFolderItems)
    {
        Console.WriteLine(" Folder Name :"+ item.Name);
    }
    // Get all the users in the vault
    Console.WriteLine("\n Vault Users : \n");
    string urlAllUsers = Url + vaultName + "/users";
    vaultFolderItems = GetVaultItems(urlAllUsers);
    foreach (var item in vaultFolderItems)
    {
        Console.WriteLine(" User Name :"+ item.FullName);
        Console.WriteLine(" User ID :"+ item.UserInfo.UserId.ToString());
    }
}
catch (Exception ex)
{
    Console.WriteLine(ex.ToString());
}
}

private static List<ObjectInfo> GetVaultItems(string Url)
{
    var result = GetResultOfAPI<List<ObjectInfo>>(Url);
    return result ?? new List<ObjectInfo>();
}

public static T GetResultOfAPI<T>(string data)
{
    T model = default(T);
    string result = GetRequest(data, JwtString);
    try
    {
        // Convert the GET returned string to a list
        // of objects of type specified in GetVaultItems
        model = ConvertToType<T>(result);
    }
    catch (Exception ex)
    {
        Console.WriteLine(ex.ToString());
    }
    return model;
}

public static T ConvertToType<T>(string response)
{
    // Deserialize the response and convert it to the specified type
    return JsonConvert.DeserializeObject<T>(response);
}

public static bool AuthorizationCode(string result)
{
    try
    {
        var jsonConvert = new JavaScriptSerializer();
        // Deserialize the authentication result
        // and convert it to a JSON Web Token
        var temp = (Dictionary<string, object>)jsonConvert.DeserializeObject(result);
        JwtString = temp["JwtString"].ToString();
    }
    catch (Exception ex)
    {
        Console.WriteLine(ex.ToString());
    }
    // Authorize, if the Bearer token is not empty of null
    Authorized = !String.IsNullOrEmpty(JwtString);
    return Authorized;
}

public static string AuthenticateRequest(string url, UserCredentials user)
{
    string result = String.Empty;
    var jsonConvert = new JavaScriptSerializer();
    string json = JsonConvert.SerializeObject(user);
    var body = Encoding.UTF8.GetBytes(json);
    HttpWebRequest request = (HttpWebRequest)WebRequest.Create(url);
    request.Method = "POST";
    request.ContentType = "application/json";
    request.ContentLength = body.Length;
    // Get a stream object to send request data
    // using the Stream.Write method
    using (Stream stream = request.GetRequestStream())
    {
        stream.Write(body, 0, body.Length);
        stream.Close();
    }
    try
    {
        // Sends the HttpWebRequest and waits for the response
        using (HttpWebResponse response = (HttpWebResponse)request.GetResponse())
        {
            // Gets the stream associated with the response
            // and pipes it to a higher-level stream reader
            // with the required encoding format
            using (var sr = new StreamReader(response.GetResponseStream()))
            {
                result = sr.ReadToEnd();
            }
            response.Close();
        }
    }
    catch (WebException ex)
    {
        if (ex.Response == null)
            throw;
        using (WebResponse response = ex.Response)
        {
            using (var sr = new StreamReader(response.GetResponseStream()))
            {
                result = sr.ReadToEnd();
            }
        }
    }
    return result;
}

public static string GetRequest(string url, string jwt)
{
    // Initialize an HttpWebRequest
    HttpWebRequest req = (HttpWebRequest)WebRequest.Create(url);
    req.Accept = "application/json";
}

```

```

        req.Headers.Add("Authorization", "Bearer " + jwt);
        string result = String.Empty;
        try
        {
            // Sends the HttpRequest and waits for the response
            HttpResponseMessage resp = (HttpResponseMessage)req.GetResponse();
            // Gets the stream used to read the body of the response
            using (var sr = new StreamReader(resp.GetResponseStream()))
            {
                result = sr.ReadToEnd();
            }
        }
        catch (WebException ex)
        {
            if (ex.Response == null)
            {
                return result;
            }
            using (WebResponse response = ex.Response)
            {
                using (var sr = new StreamReader(response.GetResponseStream()))
                {
                    result = sr.ReadToEnd();
                }
            }
        }
        return result;
    }
}

public struct UserCredentials
{
    public string password;
    public string username;
}

public class ObjectInfo
{
    public int Id { get; set; }
    public string Name { get; set; }
    public long Size { get; set; }
    public DateTime ModifiedDate { get; set; }
    public int Version { get; set; }
    public string State { get; set; }
    public int StateId { get; set; }
    public int ParentFolderId { get; set; }
    public string Path { get; set; }
    public ObjectType Type { get; set; }
    public int IsLocked { get; set; }
    public int IsLockedBy { get; set; }
    public int IsShared { get; set; }
    public int IsToolbox { get; set; }
    public int IsDeleted { get; set; }
    public UserInfo UserInfo { get; set; }
    public string FullName { get; set; }
    public string Initials { get; set; }
}

public enum ObjectType
{
    Folder = 0,
    File = 1,
    Bom = 3
}

public class UserInfo
{
    public string UserName { get; set; }
    public int UserId { get; set; }
}
}

```

Example

[Authentication \(JS\)](#) | [Use Search Variables.postman_collection.json](#) | [Upload SOLIDWORKS Files to PDM Vault.postman_collection.json](#) | [Check in SOLIDWORKS Files in PDM Vault.postman_collection.json](#) | [Check Out Files in PDM Vault.postman_collection.json](#) | [Modify File Datacards.postman_collection.json](#)

Remarks

Read [Getting Started](#).

For more information about the data types used in authentication:

- [HttpContent](#)
- [HttpRequestMessage](#)
- [HttpResponseMessage](#)
- [HttpStatusCode](#) enumerator
- [HttpRequest](#)
- [HttpResponse](#)

See Also

[Authentication Resource Group](#) | [PDM Pro API Web Service](#)

PDM Pro API Web Service

GETapi/{vaultName}/bom/{bomDocumentId}/{version}/{folderId}/named

Description

GET: api/{VaultName}/bom/{BomDocumentId}/{Version}/{FolderID}/named Get named bom

Gets the specified BOM.

Parameters

vaultName	(URI parameter) Vault name (required in URI)	string
bomDocumentId	(URI parameter) BOM ID (required in URI)	integer
version	(URI parameter) Version (required in URI)	integer
folderId	(URI parameter) Folder ID (required in URI)	integer
Columns	(Response) Array of BOMColumns; each BOMColumn consists of: - ColumnNo (integer) - ColumnName (string) Member of NamedBOM model	Collection of BOMColumn
Values	(Response) Array of NamedBOMRows; each NamedBOMRow consists of: - RowNo (integer) - ColumnNo (integer) - Value (string) Member of NamedBOM model	Collection of NamedBOMRow

Response (application/json, text/json)

Sample Data

```
{
  "Columns": [
    {
      "ColumnNo": 1,
      "ColumnName": "sample string 2"
    },
    {
      "ColumnNo": 1,
      "ColumnName": "sample string 2"
    }
  ],
  "Values": [
    {
      "RowNo": 1,
      "ColumnNo": 2,
      "Value": "sample string 3"
    },
    {
      "RowNo": 1,
      "ColumnNo": 2,
      "Value": "sample string 3"
    }
  ]
}
```

Response (application/xml, text/xml)

Sample Data

```
<NamedBOM xmlns:i="http://www.w3.org/2001/XMLSchema-instance" xmlns="http://schemas.datacontract.org/2004/07/SWPDM.Models">
  <Columns>
    <BOMColumn>
      <ColumnName>sample string 2</ColumnName>
      <ColumnNo>1</ColumnNo>
    </BOMColumn>
    <BOMColumn>
      <ColumnName>sample string 2</ColumnName>
      <ColumnNo>1</ColumnNo>
    </BOMColumn>
  </Columns>
  <Values>
    <NamedBOMRow>
```

```
<ColumnNo>2</ColumnNo>
<RowNo>1</RowNo>
<Value>sample string 3</Value>
</NamedBOMRow>
<NamedBOMRow>
  <ColumnNo>2</ColumnNo>
  <RowNo>1</RowNo>
  <Value>sample string 3</Value>
</NamedBOMRow>
</Values>
</NamedBOM>
```

See Also

[BOM Resource Group](#) | [PDM Pro API Web Service](#)

GET

api/{vaultName}/bom/{bomTypeId}/{fileId}/{version}/{folderId}/computed?configId={configId}&latest={latest}

Description

GET: api/{VaultName}/bom/{BomTypeId}/{FileId}/{Version}/{FolderId}/weldmentcutlist or api/{VaultName}/bom/{BomTypeId}/{FileId}/{Version}/{FolderId}/computed
Get computed BOM

Gets the computed BOM.

Parameters

vaultName	(URI parameter) Vault name (required in URI)	string
bomTypeId	(URI parameter) BOM type ID (required in URI)	integer
fileId	(URI parameter) File ID (required in URI)	integer
version	(URI parameter) Version (required in URI)	integer
folderId	(URI parameter) Folder ID (required in URI)	integer
configId	(URI parameter) Configuration ID (default is -1)	integer
latest	(URI parameter) Whether the latest version (default is false)	boolean
Columns	(Response) Array of BOMColumns; each BOMColumn consists of: - ColumnNo (integer) - ColumnName (string) Member of ComputedBOM model	Collection of BOMColumn
File	(Response) BOMRef consists of: - File (BOMRow) - References (Collection of BOMRef) Member of ComputedBOM model	BOMRef

Response (application/json)

Response (text/json)

Response (application/xml)

Response (text/xml)

See Also

PDM Pro API Web Service

GET

api/{vaultName}/bom/{bomTypeId}/{fileId}/{version}/{folderId}/weldmentcutlist?configId={configId}&latest={latest}

Description

GET: api/{VaultName}/bom/{BomTypeId}/{FileID}/{Version}/{FolderID}/weldmentcutlist or api/{VaultName}/bom/{BomTypeId}/{FileID}/{Version}/{FolderID}/computed
Get computed BOM

Gets the weldment cut list BOM.

Parameters

vaultName	(URI parameter) Vault name (required in URI)	string
bomTypeId	(URI parameter) BOM type ID (required in URI)	integer
fileId	(URI parameter) File ID (required in URI)	integer
version	(URI parameter) Version (required in URI)	integer
folderId	(URI parameter) Folder ID (required in URI)	integer
configId	(URI parameter) Configuration ID (default is -1)	integer
latest	(URI parameter) Whether the latest version (default is false)	boolean
Columns	(Response) Array of BOMColumns; each BOMColumn consists of: - ColumnNo (integer) - ColumnName (string) Member of ComputedBOM model	Collection of BOMColumn
File	(Response) BOMRef consists of: - File (BOMRow) - References (Collection of BOMRef) Member of ComputedBOM model	BOMRef

Response (application/json)

Response (text/json)

Response (application/xml)

Response (text/xml)

See Also

GET

api/{vaultName}/changeset/create

Description

GET: api/{vaultName}/changeset/create Generate changesetId
Gets a changeset ID for the specified vault.

Parameters

vaultName	(URI parameter) Vault name (required)	string
-----------	---------------------------------------	--------

Response (application/json, text/json)

Returns the new changeset ID

Sample Data

1

Response (application/xml, text/xml)

Returns the new changeset ID

Sample Data

<int xmlns="http://schemas.microsoft.com/2003/10/Serialization/">1</int>

Example

Upload SOLIDWORKS Files to PDM Vault.postman_collection.json

See Also

Stage Resource Group | PDM Pro API Web Service

PUT

api/{vaultName}/checkin/addfiles/{changesetId}

Description

PUT: api/{vaultname}/checkin/addfiles/{changesetId=0} Upload files or document ids to changeset to the check in operation

Adds files to a changeset for checkin. (See **Remarks**)

Parameters

vaultName	(URI parameter) Vault name (required)	string
changesetId	(URI and Response parameter) Changeset ID = 0 (URI required)	integer
References	(Response) Array of FileInfo objects; each FileInfo consists of: File (File object that consists of: FileId (integer) FileName (string)) Folder (Folder object that consist of: FolderId (integer) FolderPath (string)) Version (integer) Config (Config object that consists of: ConfigurationName (string) ConfigurationId (integer))) Collection of FileInfo	

Response (application/json, text/json)

This request returns a new changeset ID and file references.

Sample Data

```
{
  "ChangesetId": 1,
  "References": [
    {
      "File": {
        "FileId": 1,
        "FileName": "sample string 2"
      },
      "Folder": {
        "FolderId": 1,
        "FolderPath": "sample string 2"
      },
      "Version": 1,
      "Config": {
        "ConfigurationName": "sample string 1",
        "ConfigurationId": 2
      }
    },
    {
      "File": {
        "FileId": 1,
        "FileName": "sample string 2"
      },
      "Folder": {
        "FolderId": 1,
        "FolderPath": "sample string 2"
      },
      "Version": 1,
      "Config": {
        "ConfigurationName": "sample string 1",
        "ConfigurationId": 2
      }
    }
  ]
}
```

Response (application/xml, text/xml)

This request returns a new changeset ID and file references.

Sample Data

```
<UploadModel xmlns:i="http://www.w3.org/2001/XMLSchema-instance" xmlns="http://schemas.datacontract.org/2004/07/SWPDM.Models">
  <ChangesetId>1</ChangesetId>
  <References>
    <FileInfo>
      <Config>
        <ConfigurationId>2</ConfigurationId>
        <ConfigurationName>sample string 1</ConfigurationName>
      </Config>
      <File>
        <FileId>1</FileId>
        <FileName>sample string 2</FileName>
      </File>
      <Folder>
        <FolderId>1</FolderId>
        <FolderPath>sample string 2</FolderPath>
      </Folder>
      <Version>1</Version>
    </FileInfo>
    <FileInfo>
      <Config>
        <ConfigurationId>2</ConfigurationId>
        <ConfigurationName>sample string 1</ConfigurationName>
      </Config>
      <File>
        <FileId>1</FileId>
        <FileName>sample string 2</FileName>
      </File>
      <Folder>
        <FolderId>1</FolderId>
        <FolderPath>sample string 2</FolderPath>
      </Folder>
      <Version>1</Version>
    </FileInfo>
  </References>
</UploadModel>
```

Example

[Check in SOLIDWORKS Files in PDM Vault.postman_collection.json](#) | [Program.cs](#) | [Modify File Datacards.postman_collection.json](#)

Remarks

This request also requires a binary Body that consists of the binary files to add to the changeset. Drag/drop the JSON example to Postman and inspect the Body of the HTTP request. The **Program.cs** example creates the binary file that you can upload using this request.

Send this HTTP request with a changeset ID of 0. If successful, it will return a new changeset ID which you will use in further requests: [api/{vaultName}/checkin/buildtree/{changesetId}](#) (Get) and [api/{vaultName}/checkin/{changesetId}/{overrideVersion}](#) (Put)

See Also

[Stage Resource Group](#) | [PDM Pro API Web Service](#)

GET

api/{{vaultName}}/checkin/buildtree/{{changesetId}}

Description

GET: api/{{vaultName}}/checkin/buildtree/{{changesetId}} Get references tree

Builds a reference tree of files that are uploaded to the specified changeset.

Parameters

vaultName	(URI parameter) Vault name (required)	string
changesetId	(URI parameter) Changeset ID (required)	integer
File	(Response) A FileInfoStageModel object that consists of: File (File object that consists of FileId (integer) and FileName (string)) Folder (Folder object that consists of FolderId (integer) and FolderPath (string)) Version (integer) Quantity (integer) LockedBy (integer) NewVersion (boolean) DocumentType (DocumentType object that contains one of: NoObject = 0 NormalDocument = 1 VirtualComponent = 2 SavedBOM = 3 Item = 4 CutListItem = 5) LockViewId (globally unique identifier) LockProject (integer) ModifiedDate (date)	FileInfoStageModel
IsToolbox	(Response) 1 if a toolbox file, 0 if not	integer
ObjectType	(Response) "Folder", "File", or "Bom"	String

Response (application/json)

Response (text/json)

Response (application/xml)

Response (text/xml)

Example

[Check in SOLIDWORKS Files in PDM Vault.postman_collection.json](#)

See Also

PUT

api/{vaultName}/checkin/{changesetId}/{overrideVersion}

Description

PUT: api/{vaultName}/checkin/{changesetId}/{overrideVersion=false} Check in files from the changeset
Checks in the specified changeset.

Parameters

vaultName	(URI parameter) Vault name (required)	string
changesetId	(URI parameter) Changeset ID (required)	integer
overrideVersion	(URI parameter) Whether to override the current versions of files (required)	boolean
DocumentIds	(Body parameter) Array of document IDs Member of CheckInModel model	Collection of integer
Comments	(Body parameter) Checkin comment Member of CheckInModel model	string
Version	(Response) A Version model that consists of: - Major (integer) - Minor (integer) - Build (integer) - Revision (integer) - MajorRevision (integer) - MinorRevision (integer) Member of HttpResponseMessage model	Version
Content	(Response) GUID of the check-in operation; use the GUID to query for the status of the operation (see api/{vaultName}/progress/{guid}/status) Member of HttpResponseMessage model	HttpContent
StatusCode	(Response) Status code; see https://en.wikipedia.org/wiki/List_of_HTTP_status_codes Member of HttpResponseMessage model	HttpStatusCode
ReasonPhrase	(Response) Reason Member of HttpResponseMessage model	string
Headers	(Response) Collection of objects Member of HttpResponseMessage model	Collection of Object
RequestMessage	(Response) An HttpRequestMessage object that consists of: Version (Version model) Content (HttpContent object consisting of Headers array) Method (HttpMethod object consisting of Method string) RequestUri (URI) Headers (Array of objects) Properties (Dictionary of string [key] and Object [value]) Member of HttpResponseMessage model	HttpRequestMessage
IsSuccessStatusCode	(Response) True if successful, false if not Member of HttpResponseMessage model	boolean

Request (application/json, text/json)

The body parameter includes an array of document IDs and comments.

Sample Data

```
{
  "DocumentIds": [
    1,
    2
  ],
  "Comments": "sample string 1"
}
```

Request (application/xml, text/xml)

The body parameter includes an array of document IDs and comments.

Sample Data

```
<CheckInModel xmlns:i="http://www.w3.org/2001/XMLSchema-instance" xmlns="http://schemas.datacontract.org/2004/07/SWPDM.Models">
  <Comments>sample string 1</Comments>
  <DocumentIds xmlns:d2p1="http://schemas.microsoft.com/2003/10/Serialization/Arrays">
    <d2p1:int>1</d2p1:int>
    <d2p1:int>2</d2p1:int>
  </DocumentIds>
</CheckInModel>
```

Request (application/x-www-form-urlencoded)

The body parameter includes an array of document IDs and comments.

Example

[Modify File Datacards.postman_collection.json](#)

See Also

[Stage Resource Group](#) | [PDM Pro API Web Service](#)

PDM Pro API Web Service

DELETE **api/{vaultName}/configuration/hooks/dll**

Description

Deletes add-in hook DLLs from the specified vault.

Parameters

vaultName	Name of vault to get, put, and delete add-in hook DLLs	string
-----------	--	--------

Response (application/json, text/json, application/xml, text/xml)

Example

Click and save the following to your computer. Then drag/drop it into Postman:

[HooksManagement.postman_collection.json](#)

Remarks

To use this API, you must authenticate this request with a token and select the CanAdministrateAddins permission in the Admin tool.

See the [PDM Pro Web API Webhooks Programming Guide](#).

See Also

[Configuration Resource Group](#) | [PDM Pro API Web Service](#)

PDM Pro API Web Service

GET **api/{vaultName}/configuration/hooks/dll**

Description

Retrieves the list of add-in hooks from the specified vault.

Parameters

vaultName	Name of vault to get, put, and delete add-in hook DLLs	string
-----------	--	--------

Response (application/json, text/json, application/xml, text/xml)

Example

Click and save the following to your computer. Then drag/drop it into Postman:

[HooksManagement.postman_collection.json](#)

Remarks

To use this API, you must create a **storage\addins\vault_name** folder in your file server root directory and add a Header called download to this request.

If download is set to:

- false, you must authenticate this request with a token. A list of relative path filenames is returned.
- true, you must authenticate this request with a token and select the CanAdministrateAddins permission in the Admin tool. A ZIP file containing all of the add-in hooks is downloaded.

See the [PDM Pro Web API Webhooks Programming Guide](#).

See Also

[Configuration Resource Group](#) | [PDM Pro API Web Service](#)

PUT

api/{vaultName}/configuration/hooks/dll

Description

Puts add-in hook DLLs in the specified vault.

Parameters

vaultName	Name of vault to get, put, and delete add-in hook DLLs	string
-----------	--	--------

Response (application/json, text/json, application/xml, text/xml)

Example

Click and save the following to your computer. Then drag/drop it into Postman:

[HooksManagement.postman_collection.json](#)

Remarks

To use this API, you must authenticate this request with a token and select the CanAdministrateAddins permission in the Admin tool.

See the [PDM Pro Web API Webhooks Programming Guide](#).

See Also

[Configuration Resource Group](#) | [PDM Pro API Web Service](#)

PDM Pro API Web Service

GET**api/{vaultName}/configuration/hooks/url**

Description

Retrieves the list of webhooks configured in the specified vault.

Parameters

vaultName	Name of vault to get and set webhooks	string
-----------	---------------------------------------	--------

Response (application/json, text/json, application/xml, text/xml)

Example

Click and save the following to your computer. Then drag/drop it into Postman:

[HooksManagement.postman_collection.json](#)

Remarks

To use this API, you must authenticate this request with a token.

See the [PDM Pro Web API Webhooks Programming Guide](#).

See Also

[Configuration Resource Group](#) | [PDM Pro API Web Service](#)

PDM Pro API Web Service

POST**api/{vaultName}/configuration/hooks/url**

Description

Sets the webhooks for the specified vault.

Parameters

vaultName	Name of vault to get and set webhooks	string
-----------	---------------------------------------	--------

Request (application/json, text/json)

Sample Data

```
{
  "sample string 1": [
    "sample string 1",
    "sample string 2"
  ],
  "sample string 2": [
    "sample string 1",
    "sample string 2"
  ]
}
```

Request (application/xml, text/xml)

Sample Data

```
<ArrayOfKeyValueOfstringArrayOfstringty7Ep6D1 xmlns:i="http://www.w3.org/2001/XMLSchema-instance"
xmlns="http://schemas.microsoft.com/2003/10/Serialization/Arrays">
  <KeyValueOfstringArrayOfstringty7Ep6D1>
    <Key>sample string 1</Key>
    <Value>
      <string>sample string 1</string>
      <string>sample string 2</string>
    </Value>
  </KeyValueOfstringArrayOfstringty7Ep6D1>
  <KeyValueOfstringArrayOfstringty7Ep6D1>
    <Key>sample string 2</Key>
```

```
<Value>
  <string>sample string 1</string>
  <string>sample string 2</string>
</Value>
</KeyValue0fstringArray0fstringty7Ep6D1>
</ArrayOfKeyValue0fstringArray0fstringty7Ep6D1>
```

Request (application/x-www-form-urlencoded)

Response (application/json, text/json, application/xml, text/xml)

Example

Click and save the following to your computer. Then drag/drop it into Postman:

[HooksManagement.postman_collection.json](#)

Remarks

To use this API, you must authenticate this request with a token and select the CanAdministrateAddins permission in the Admin tool.

See the [PDM Pro Web API Webhooks Programming Guide](#).

See Also

[Configuration Resource Group | PDM Pro API Web Service](#)

POST

api/{vaultName}/delete/computetree

Description

POST: api/{VaultName}/delete/computetree Delete compute tree

Deletes the specified items in the specified vault.

Parameters

vaultName	(URI parameter) Vault name (required)	string
FolderIDs	(Body parameter) Array of folder IDs	Collection of integer
	Member of DeleteComputeTree model	
FileIDs	(Body parameter) Array of file IDs	Collection of integer
	Member of DeleteComputeTree model	
Destroy	(Body parameter) Whether to destroy	boolean
	Member of DeleteComputeTree model	
FileCount	(Response) Number of files deleted	integer
	Member of DelResult model	
FolderCount	(Response) Number of folders deleted	integer
	Member of DelResult model	
XRefWarnings	(Response) An XRefWarning object that consists of: ParentProjectID (integer) ObjectType (PweObjectType that is one of: ObjType_NoObject = 0 ObjType_File= 1 ObjType_InternalComponent = 2 ObjType_SavedBOM = 3 ObjType_Item = 4 ObjType_CutListItem = 5) ChildObjectType (PweObjectType; see ObjectType) DocumentID (integer) Version (integer) ChildDocumentID (integer) ChildProjectID (integer) ChildVersion (integer) Member of DelResult model	String

Request (application/json, text/json)

Sample Data

```
{  
  "FolderIDs": [  

```

```

    1,
    2
  ],
  "FileIDs": [
    1,
    2
  ],
  "Destroy": true
}

```

Request (application/xml, text/xml)

Sample Data

```

<DeleteComputeTree xmlns:i="http://www.w3.org/2001/XMLSchema-instance" xmlns="http://schemas.datacontract.org/2004/07/SWPDM.Models">
  <Destroy>true</Destroy>
  <FileIDs xmlns:d2p1="http://schemas.microsoft.com/2003/10/Serialization/Arrays">
    <d2p1:int>1</d2p1:int>
    <d2p1:int>2</d2p1:int>
  </FileIDs>
  <FolderIDs xmlns:d2p1="http://schemas.microsoft.com/2003/10/Serialization/Arrays">
    <d2p1:int>1</d2p1:int>
    <d2p1:int>2</d2p1:int>
  </FolderIDs>
</DeleteComputeTree>

```

Request (application/x-www-form-urlencoded)

Response (application/json, text/json)

Sample Data

```

{
  "FileCount": 1,
  "FolderCount": 2,
  "XRefWarnings": [
    {
      "ParentProjectID": 1,
      "ObjectType": 0,
      "ChildObjectType": 0,
      "DocumentID": 2,
      "Version": 3,
      "ChildDocumentID": 4,
      "ChildProjectID": 5,
      "ChildVersion": 6
    },
    {
      "ParentProjectID": 1,
      "ObjectType": 0,
      "ChildObjectType": 0,
      "DocumentID": 2,
      "Version": 3,
      "ChildDocumentID": 4,
      "ChildProjectID": 5,
      "ChildVersion": 6
    }
  ],
  "BranchRefWarnings": [
    {
      "DocumentID": 1,
      "ProjectID": 2,
      "ObjectType": 0,
      "BranchName": "sample string 3",
      "BranchDeleted": 4
    },
    {
      "DocumentID": 1,
      "ProjectID": 2,
      "ObjectType": 0,
      "BranchName": "sample string 3",
      "BranchDeleted": 4
    }
  ],
  "LockedFiles": [
    {
      "DocumentID": 1,
      "ProjectID": 2,
      "ObjectType": 3,
      "UserID": 4,
      "InUserState": true
    },
    {
      "DocumentID": 1,
      "ProjectID": 2,
      "ObjectType": 3,
      "UserID": 4,
      "InUserState": true
    }
  ],
  "FileNames": {

```

```

    "1": "sample string 2",
    "3": "sample string 4"
  },
  "UserNameMap": {
    "1": "sample string 2",
    "3": "sample string 4"
  },
  "FolderPaths": {
    "1": "sample string 2",
    "3": "sample string 4"
  },
  "LocalFiles": [
    "sample string 1",
    "sample string 2"
  ],
  "LocalFolders": [
    "sample string 1",
    "sample string 2"
  ],
  "VaultItems": [
    {
      "ProjectID": 1,
      "DocumentID": 2,
      "ObjectType": 3,
      "Flags": 4
    },
    {
      "ProjectID": 1,
      "DocumentID": 2,
      "ObjectType": 3,
      "Flags": 4
    }
  ]
}

```

Response (application/xml, text/xml)

Sample Data

```

<DelResult xmlns:i="http://www.w3.org/2001/XMLSchema-instance" xmlns="http://schemas.datacontract.org/2004/07/SWPDM.Repositories.DTO">
  <BranchRefWarnings>
    <BranchRefWarning>
      <BranchDeleted>4</BranchDeleted>
      <BranchName>sample string 3</BranchName>
      <DocumentID>1</DocumentID>
      <ObjectType>ObjType_NoObject</ObjectType>
      <ProjectID>2</ProjectID>
    </BranchRefWarning>
    <BranchRefWarning>
      <BranchDeleted>4</BranchDeleted>
      <BranchName>sample string 3</BranchName>
      <DocumentID>1</DocumentID>
      <ObjectType>ObjType_NoObject</ObjectType>
      <ProjectID>2</ProjectID>
    </BranchRefWarning>
  </BranchRefWarnings>
  <FileCount>1</FileCount>
  <FileNames xmlns:d2p1="http://schemas.microsoft.com/2003/10/Serialization/Arrays">
    <d2p1:KeyValueOflongstring>
      <d2p1:Key>1</d2p1:Key>
      <d2p1:Value>sample string 2</d2p1:Value>
    </d2p1:KeyValueOflongstring>
    <d2p1:KeyValueOflongstring>
      <d2p1:Key>3</d2p1:Key>
      <d2p1:Value>sample string 4</d2p1:Value>
    </d2p1:KeyValueOflongstring>
  </FileNames>
  <FolderCount>2</FolderCount>
  <FolderPaths xmlns:d2p1="http://schemas.microsoft.com/2003/10/Serialization/Arrays">
    <d2p1:KeyValueOflongstring>
      <d2p1:Key>1</d2p1:Key>
      <d2p1:Value>sample string 2</d2p1:Value>
    </d2p1:KeyValueOflongstring>
    <d2p1:KeyValueOflongstring>
      <d2p1:Key>3</d2p1:Key>
      <d2p1:Value>sample string 4</d2p1:Value>
    </d2p1:KeyValueOflongstring>
  </FolderPaths>
  <LocalFiles xmlns:d2p1="http://schemas.microsoft.com/2003/10/Serialization/Arrays">
    <d2p1:string>sample string 1</d2p1:string>
    <d2p1:string>sample string 2</d2p1:string>
  </LocalFiles>
  <LocalFolders xmlns:d2p1="http://schemas.microsoft.com/2003/10/Serialization/Arrays">
    <d2p1:string>sample string 1</d2p1:string>
    <d2p1:string>sample string 2</d2p1:string>
  </LocalFolders>
  <LockedFiles>
    <LockInfo2>
      <DocumentID>1</DocumentID>
      <InUserState>true</InUserState>
      <ObjectType>3</ObjectType>
      <ProjectID>2</ProjectID>
    </LockInfo2>
  </LockedFiles>
</DelResult>

```

```

        <UserID>4</UserID>
    </LockInfo2>
</LockInfo2>
    <DocumentID>1</DocumentID>
    <InUserState>true</InUserState>
    <ObjectType>3</ObjectType>
    <ProjectID>2</ProjectID>
    <UserID>4</UserID>
</LockInfo2>
</LockedFiles>
<UserNameMap xmlns:d2p1="http://schemas.microsoft.com/2003/10/Serialization/Arrays">
    <d2p1:KeyValueOflongstring>
        <d2p1:Key>1</d2p1:Key>
        <d2p1:Value>sample string 2</d2p1:Value>
    </d2p1:KeyValueOflongstring>
    <d2p1:KeyValueOflongstring>
        <d2p1:Key>3</d2p1:Key>
        <d2p1:Value>sample string 4</d2p1:Value>
    </d2p1:KeyValueOflongstring>
</UserNameMap>
<VaultItems>
    <DeleteItem>
        <DocumentID>2</DocumentID>
        <Flags>4</Flags>
        <ObjectType>3</ObjectType>
        <ProjectID>1</ProjectID>
    </DeleteItem>
    <DeleteItem>
        <DocumentID>2</DocumentID>
        <Flags>4</Flags>
        <ObjectType>3</ObjectType>
        <ProjectID>1</ProjectID>
    </DeleteItem>
</VaultItems>
<XRefWarnings>
    <XRefWarning>
        <ChildDocumentID>4</ChildDocumentID>
        <ChildProjectID>5</ChildProjectID>
        <ChildVersion>6</ChildVersion>
        <DocumentID>2</DocumentID>
        <Version>3</Version>
        <ChildObjectType>ObjType_NoObject</ChildObjectType>
        <ObjectType>ObjType_NoObject</ObjectType>
        <ParentProjectID>1</ParentProjectID>
    </XRefWarning>
    <XRefWarning>
        <ChildDocumentID>4</ChildDocumentID>
        <ChildProjectID>5</ChildProjectID>
        <ChildVersion>6</ChildVersion>
        <DocumentID>2</DocumentID>
        <Version>3</Version>
        <ChildObjectType>ObjType_NoObject</ChildObjectType>
        <ObjectType>ObjType_NoObject</ObjectType>
        <ParentProjectID>1</ParentProjectID>
    </XRefWarning>
</XRefWarnings>
</DelResult>

```

Remarks

This operation:

- takes a DeleteComputeTree object as a body parameter.
- returns a DelResult object.

The complete DelResult model consists of:

FileCount (integer)

FolderCount (integer)

XRefWarnings (array of XRefWarning objects; each XRefWarning consists of:

ParentProjectID (integer)

ObjectType (PweObjectType that is one of:

ObjType_NoObject = 0

ObjType_File = 1

ObjType_InternalComponent = 2

ObjType_SavedBOM = 3

ObjType_Item = 4

ObjType_CutListItem = 5

)

ChildObjectType (PweObjectType; see ObjectType)

DocumentID (integer)

Version (integer)

ChildDocumentID (integer)

ChildProjectID (integer)

ChildVersion (integer)

)

BranchRefWarnings (array of BranchRefWarning objects; each BranchRefWarning consists of:

DocumentID (integer)

ProjectID (integer)

ObjectType (PweObjectType; see XRefWarnings)

BranchName (string)

BranchDeleted (integer)

)

LockedFiles (array of LockInfo2 objects; each LockInfo2 consists of:

DocumentID (integer)

```
ProjectID (integer)
ObjectType (integer)
ObjectType (PweObjectType; see BranchRefWarnings)
UserID (integer)
InUserState (boolean)
)
FileNames (dictionary of integer [key] and string [value] pairs)
UserNameMap (dictionary of integer [key] and string [value] pairs)
FolderPaths (dictionary of integer [key] and string [value] pairs)
LocalFiles (array of strings)
LocalFolders (array of strings)
VaultItems (array of Deleteltem objects; each Deleteltem consists of:
  ProjectID (integer)
  DocumentID (integer)
  ObjectType (integer)
  Flags (integer)
)
```

See Also

[Vault Resource Group](#) | [PDM Pro API Web Service](#)

POST

api/{vaultName}/files/buildtree/checkout

Description

POST: api/{VaultName}/files/buildtree/checkout Build checkout references tree

Gets the tree of references in the specified file's checkout.

Parameters

vaultName	(URI parameter) Valut name (required)	string
FileId	(Body parameter) File ID	integer
	Member of CheckOutItem; see Remarks	
FolderId	(Body parameter) Folder ID	integer
	Member of CheckOutItem; see Remarks	
File	(Response) A FileInfoConfigLess object that consists of: File (File object consists of: FileId (integer) FileName (string)) Folder (Folder object consists of: FolderId (integer) FolderPath (string)) Version (integer)	FileInfoConfigLess
	Member of FileRefOfFileInfoConfigLess model; see Remarks	
IsToolbox	(Response) Whether is a toolbox item	integer
	Member of FileRefOfFileInfoConfigLess model; see Remarks	
ObjectType	(Response) PweObjectType model; one of: ObjType_NoObject = 0 ObjType_File = 1 ObjType_InternalComponent = 2 ObjType_SavedBOM = 3 ObjType_Item = 4 ObjType_CutListItem = 5	String
	Member of FileRefOfFileInfoConfigLess model; see Remarks	

Request (application/json, text/json)

Sample Data

```
[
  {
    "FileId": 1,
    "FolderId": 2
  },
  {
    "FileId": 1,
    "FolderId": 2
  }
]
```

Request (application/xml, text/xml)

Sample Data

```
<ArrayOfCheckOutItem xmlns:i="http://www.w3.org/2001/XMLSchema-instance" xmlns="http://schemas.datacontract.org/2004/07/SWPDM.Models">
  <CheckOutItem>
    <FileId>1</FileId>
    <FolderId>2</FolderId>
  </CheckOutItem>
  <CheckOutItem>
    <FileId>1</FileId>
    <FolderId>2</FolderId>
  </CheckOutItem>
</ArrayOfCheckOutItem>
```

Request (application/x-www-form-urlencoded)

Response (application/json)

Response (text/json)

Response (application/xml)

Response (text/xml)

Remarks

This operation can:

- take an array of CheckOutItem objects. Each CheckOutItem consists of FileId and Folder Id.
- return an array of FileRefOfFileInfoConfigLess objects that represent the tree of references to include in the file's checkout.

See Also

[File Resource Group](#) | [PDM Pro API Web Service](#)

POST

api/{vaultName}/files/buildtree/undo

Description

POST: api/{VaultName}/files/buildtree/undo Build undo checkout references tree

Builds the reference tree to undo the checkout of the specified file.

Parameters

vaultName	(URI parameter) Vault name (required)	string
FileId	(Body parameter) File ID	integer
	Member of CheckOutItem; see Remarks	
FolderId	(Body parameter) Folder ID	integer
	Member of CheckOutItem; see Remarks	
File	(Response) A FileInfoConfigLess object that consists of: File (File object consists of: FileId (integer) FileName (string)) Folder (Folder object consists of: FolderId (integer) FolderPath (string)) Version (integer) Member of FileRefOfFileInfoConfigLess model; see Remarks	FileInfoConfigLess
IsToolbox	(Response) Whether is a toolbox item Member of FileRefOfFileInfoConfigLess model; see Remarks	integer
ObjectType	(Response) PweObjectType model; one of: ObjType_NoObject = 0 ObjType_File = 1 ObjType_InternalComponent = 2 ObjType_SavedBOM = 3 ObjType_Item = 4 ObjType_CutListItem = 5 Member of FileRefOfFileInfoConfigLess model; see Remarks	String

Request (application/json, text/json)

Sample Data

```
[
  {
    "FileId": 1,
    "FolderId": 2
  },
  {
    "FileId": 1,
    "FolderId": 2
  }
]
```

Request (application/xml, text/xml)

Sample Data

```
<ArrayOfCheckOutItem xmlns:i="http://www.w3.org/2001/XMLSchema-instance" xmlns="http://schemas.datacontract.org/2004/07/SWPDM.Models">
  <CheckOutItem>
    <FileId>1</FileId>
    <FolderId>2</FolderId>
  </CheckOutItem>
  <CheckOutItem>
    <FileId>1</FileId>
    <FolderId>2</FolderId>
  </CheckOutItem>
</ArrayOfCheckOutItem>
```

Request (application/x-www-form-urlencoded)

Response (application/json)

Response (text/json)

Response (application/xml)

Response (text/xml)

Remarks

This operation can:

- take an array of CheckOutItem objects. Each CheckOutItem consists of FileId and Folder Id.
- return an array of FileRefOfFileInfoConfigLess objects that represent the tree of references to include in the file's undo checkout.

See Also

[File Resource Group | PDM Pro API Web Service](#)

POST

api/{vaultName}/files/CheckOut

Description

POST: api/{VaultName}/files/CheckOut Lock file

Checks out the specified file(s).

Parameters

vaultName	(URI parameter) Vault name (required)	string
FileId	(Body and response parameter) File ID	integer
	Member of CheckOutResultModel model	
FolderId	(Body parameter) Folder ID	integer
IsSuccess	(Response) Whether the check out is successful	boolean
	Member of CheckOutResultModel model	
Warning	(Response) A BaseWarningModel object that consists of:	Collection of BaseWarningModel
	Message (string)	
	IsBlocking (boolean)	
	IsError (boolean)	
	Member of CheckOutResultModel model	

Request (application/json, text/json)

The body parameter consists of arrays of FileId and FolderId.

Sample Data

```
[
  {
    "FileId": 1,
    "FolderId": 2
  },
  {
    "FileId": 1,
    "FolderId": 2
  }
]
```

Request (application/xml, text/xml)

The body parameter consists of arrays of FileId and FolderId.

Sample Data

```
<ArrayOfCheckOutItem xmlns:i="http://www.w3.org/2001/XMLSchema-instance" xmlns="http://schemas.datacontract.org/2004/07/SWPDM.Models">
  <CheckOutItem>
    <FileId>1</FileId>
    <FolderId>2</FolderId>
  </CheckOutItem>
  <CheckOutItem>
    <FileId>1</FileId>
    <FolderId>2</FolderId>
  </CheckOutItem>
</ArrayOfCheckOutItem>
```

Request (application/x-www-form-urlencoded)

The body parameter consists of arrays of FileId and FolderId.

Response (application/json, text/json)

Sample Data

```
[
  {
    "FileId": 1,
    "IsSuccess": true,
    "Warning": null
  },
  {
    "FileId": 1,
    "IsSuccess": true,
    "Warning": null
  }
]
```

Response (application/xml, text/xml)

Sample Data

```
<ArrayOfCheckOutResultModel xmlns:i="http://www.w3.org/2001/XMLSchema-instance"
xmlns="http://schemas.datacontract.org/2004/07/SWPDM.Models">
  <CheckOutResultModel>
    <FileId>1</FileId>
    <IsSuccess>true</IsSuccess>
    <Warning i:nil="true" />
  </CheckOutResultModel>
  <CheckOutResultModel>
    <FileId>1</FileId>
    <IsSuccess>true</IsSuccess>
    <Warning i:nil="true" />
  </CheckOutResultModel>
</ArrayOfCheckOutResultModel>
```

Example

[Check Out Files in PDM Vault.postman_collection.json](#) | [Modify File Datacards.postman_collection.json](#)

Remarks

This operation returns the file ID, IsSuccess, and Warning.

See Also

[File Resource Group](#) | [PDM Pro API Web Service](#)

POST

api/{vaultName}/files/info

Description

POST: api/{VaultName}/files/info

Gets information about the specified files.

Parameters

vaultName	(URI parameter) Vault name (required)	string
Id	(Response) File ID	integer
	Member of ObjectInfo model; see Remarks	
Name	(Response) File name	string
	Member of ObjectInfo model; see Remarks	
Size	(Response) File size	integer
	Member of ObjectInfo model; see Remarks	
ModifiedDate	(Response) Modification date	date
	Member of ObjectInfo model; see Remarks	
Version	(Response) Version	integer
State	(Response) Workflow state	string
	Member of ObjectInfo model; see Remarks	
StateId	(Response) State ID	integer
	Member of ObjectInfo model; see Remarks	
ParentFolderId	(Response) Parent folder ID	integer
	Member of ObjectInfo model; see Remarks	
Path	(Response) Folder path	string
	Member of ObjectInfo model; see Remarks	
Type	(Response) ObjectType model; one of: Folder = 0 File = 1 Bom = 3	ObjectType
	Member of ObjectInfo model; see Remarks	
IsLocked	(Response) Whether the file is checked out	integer
	Member of ObjectInfo model; see Remarks	
LockedBy	(Response) ID of user who checked out the file	integer
	Member of ObjectInfo model; see Remarks	
IsShared	(Response) Whether the file is shared	integer

	Member of ObjectInfo model; see Remarks	
IsToolbox	(Response) Whether the file is a toolbox item	integer
	Member of ObjectInfo model; see Remarks	
IsDeleted	(Response) Whether the file is deleted	integer
	Member of ObjectInfo model; see Remarks	

Request (application/json, text/json)

Array of file IDs as body parameter

Sample Data

```
[
  1,
  2
]
```

Request (application/xml, text/xml)

Array of file IDs as body parameter

Sample Data

```
<ArrayOfint xmlns:i="http://www.w3.org/2001/XMLSchema-instance" xmlns="http://schemas.microsoft.com/2003/10/Serialization/Arrays">
  <int>1</int>
  <int>2</int>
</ArrayOfint>
```

Request (application/x-www-form-urlencoded)

Array of file IDs as body parameter

Response (application/json, text/json)

Sample Data

```
[
  {
    "Id": 1,
    "Name": "sample string 2",
    "Size": 3,
    "ModifiedDate": "2024-11-27T09:52:30.6715765-05:00",
    "Version": 5,
    "State": "sample string 6",
    "StateId": 7,
    "ParentFolderId": 8,
    "Path": "sample string 9",
    "Type": 0,
    "IsLocked": 10,
    "LockedBy": 11,
    "IsShared": 12,
    "IsToolbox": 13,
    "IsDeleted": 14
  },
  {
    "Id": 1,
    "Name": "sample string 2",
    "Size": 3,
    "ModifiedDate": "2024-11-27T09:52:30.6715765-05:00",
    "Version": 5,
    "State": "sample string 6",
    "StateId": 7,
    "ParentFolderId": 8,
    "Path": "sample string 9",
    "Type": 0,
    "IsLocked": 10,
    "LockedBy": 11,
    "IsShared": 12,
    "IsToolbox": 13,
    "IsDeleted": 14
  }
]
```

Response (application/xml, text/xml)

Sample Data

```
<ArrayOfObjectInfo xmlns:i="http://www.w3.org/2001/XMLSchema-instance" xmlns="http://schemas.datacontract.org/2004/07/SWPDM.Models">
  <ObjectInfo>
    <Id>1</Id>
    <IsDeleted>14</IsDeleted>
    <IsLocked>10</IsLocked>
    <IsShared>12</IsShared>
    <IsToolbox>13</IsToolbox>
    <LockedBy>11</LockedBy>
    <ModifiedDate>2024-11-27T09:52:30.6715765-05:00</ModifiedDate>
    <Name>sample string 2</Name>
    <ParentFolderId>8</ParentFolderId>
    <Path>sample string 9</Path>
    <Size>3</Size>
    <State>sample string 6</State>
    <StateId>7</StateId>
    <Type>Folder</Type>
    <Version>5</Version>
  </ObjectInfo>
  <ObjectInfo>
    <Id>1</Id>
    <IsDeleted>14</IsDeleted>
    <IsLocked>10</IsLocked>
    <IsShared>12</IsShared>
    <IsToolbox>13</IsToolbox>
    <LockedBy>11</LockedBy>
    <ModifiedDate>2024-11-27T09:52:30.6715765-05:00</ModifiedDate>
    <Name>sample string 2</Name>
    <ParentFolderId>8</ParentFolderId>
    <Path>sample string 9</Path>
    <Size>3</Size>
    <State>sample string 6</State>
    <StateId>7</StateId>
    <Type>Folder</Type>
    <Version>5</Version>
  </ObjectInfo>
</ArrayOfObjectInfo>
```

Remarks

This operation:

- takes an array of body parameters that are IDs of files for which to get information.
- returns an array of ObjectInfos, one for each file ID.

See Also

[File Resource Group](#) | [PDM Pro API Web Service](#)

POST

api/{vaultName}/files/infofrompath

Description

Gets information about a file in the specified vault.

Parameters

vaultName	(URI parameter) Vault name (required)	string
Id	(Response) File ID	integer
	Member of ObjectInfo model; see Remarks	
Name	(Response) File name	string
	Member of ObjectInfo model; see Remarks	
Size	(Response) File size	integer
	Member of ObjectInfo model; see Remarks	
ModifiedDate	(Response) Modification date	date
	Member of ObjectInfo model; see Remarks	
Version	(Response) Version	integer
State	(Response) Workflow state	string
	Member of ObjectInfo model; see Remarks	
StateId	(Response) State ID	integer
	Member of ObjectInfo model; see Remarks	
ParentFolderId	(Response) Parent folder ID	integer
	Member of ObjectInfo model; see Remarks	
Path	(Response) Folder path	string
	Member of ObjectInfo model; see Remarks	
Type	(Response) ObjectType model; one of: Folder = 0 File = 1 Bom = 3	ObjectType
	Member of ObjectInfo model; see Remarks	
IsLocked	(Response) Whether the file is checked out	integer
	Member of ObjectInfo model; see Remarks	
LockedBy	(Response) ID of user who checked out the file	integer
	Member of ObjectInfo model; see Remarks	
IsShared	(Response) Whether the file is shared	integer
	Member of ObjectInfo model; see Remarks	

IsToolbox	(Response) Whether the file is a toolbox item	integer
	Member of ObjectInfo model; see Remarks	
IsDeleted	(Response) Whether the file is deleted	integer
	Member of ObjectInfo model; see Remarks	

Request (application/json, text/json)

Sample Data

"sample string 1"

Request (application/xml, text/xml)

Sample Data

<string xmlns="http://schemas.microsoft.com/2003/10/Serialization/">sample string 1</string>

Request (application/x-www-form-urlencoded)

Response (application/json, text/json)

Sample Data

```
[
  {
    "Id": 1,
    "Name": "sample string 2",
    "Size": 3,
    "ModifiedDate": "2024-11-27T09:52:30.9629157-05:00",
    "Version": 5,
    "State": "sample string 6",
    "StateId": 7,
    "ParentFolderId": 8,
    "Path": "sample string 9",
    "Type": 0,
    "IsLocked": 10,
    "LockedBy": 11,
    "IsShared": 12,
    "IsToolbox": 13,
    "IsDeleted": 14
  },
  {
    "Id": 1,
    "Name": "sample string 2",
    "Size": 3,
    "ModifiedDate": "2024-11-27T09:52:30.9629157-05:00",
    "Version": 5,
    "State": "sample string 6",
    "StateId": 7,
    "ParentFolderId": 8,
    "Path": "sample string 9",
    "Type": 0,
    "IsLocked": 10,
    "LockedBy": 11,
    "IsShared": 12,
    "IsToolbox": 13,
    "IsDeleted": 14
  }
]
```

Response (application/xml, text/xml)

Sample Data

<ArrayOfObjectInfo xmlns:i="http://www.w3.org/2001/XMLSchema-instance" xmlns="http://schemas.datacontract.org/2004/07/SWPDM.Models">
 <ObjectInfo>
 <Id>1</Id>
 <IsDeleted>14</IsDeleted>
 <IsLocked>10</IsLocked>
 <IsShared>12</IsShared>
 <IsToolbox>13</IsToolbox>
 <LockedBy>11</LockedBy>
 <ModifiedDate>2024-11-27T09:52:30.9629157-05:00</ModifiedDate>
 <Name>sample string 2</Name>
 <ParentFolderId>8</ParentFolderId>
 <Path>sample string 9</Path>
 <Size>3</Size>
 <State>sample string 6</State>
 <StateId>7</StateId>
 <Type>Folder</Type>

```
<Version>5</Version>
</ObjectInfo>
<ObjectInfo>
  <Id>1</Id>
  <IsDeleted>14</IsDeleted>
  <IsLocked>10</IsLocked>
  <IsShared>12</IsShared>
  <IsToolbox>13</IsToolbox>
  <LockedBy>11</LockedBy>
  <ModifiedDate>2024-11-27T09:52:30.9629157-05:00</ModifiedDate>
  <Name>sample string 2</Name>
  <ParentFolderId>8</ParentFolderId>
  <Path>sample string 9</Path>
  <Size>3</Size>
  <State>sample string 6</State>
  <StateId>7</StateId>
  <Type>Folder</Type>
  <Version>5</Version>
</ObjectInfo>
</ArrayOfObjectInfo>
```

Remarks

This operation:

- takes a body parameter that contains a file path relative to the vault root. For example, if you want information about **File1.txt** which is stored in **c:\PDMLocalViews\vault_name\Test1\Test2**, where *vault_name* is the name of the vault, then the body of this API should contain **\\Test1\\Test2\\File1.txt**.
- returns an ObjectInfo for the file.

See Also

[File Resource Group](#) | [PDM Pro API Web Service](#)

POST

api/{vaultName}/files/UndoCheckOut

Description

POST: api/{VaultName}/files/UndoCheckOut Undo lock file

Unlocks the specified file.

Parameters

vaultName	(URI parameter) Vault name (required)	string
FileId	(Body and response parameter) File ID	integer
	Member of CheckOutItem and UnLockResultModel models	
FolderId	(Body parameter) Folder ID	integer
	Member of CheckOutItem model	
IsSuccess	(Response) Whether unlock is successful	boolean
	Member of UndoLockResultModel model	
Warning	(Response) A BaseWarningModel object that consists of:	BaseWarningModel
	Message (string)	
	IsBlocking (boolean)	
	IsError (boolean)	
	Member of UndoLockResultModel model	

Request (application/json, text/json)

Sample Data

```
[
  {
    "FileId": 1,
    "FolderId": 2
  },
  {
    "FileId": 1,
    "FolderId": 2
  }
]
```

Request (application/xml, text/xml)

Sample Data

```
<ArrayOfCheckOutItem xmlns:i="http://www.w3.org/2001/XMLSchema-instance" xmlns="http://schemas.datacontract.org/2004/07/SWPDM.Models">
  <CheckOutItem>
    <FileId>1</FileId>
    <FolderId>2</FolderId>
  </CheckOutItem>
  <CheckOutItem>
    <FileId>1</FileId>
    <FolderId>2</FolderId>
  </CheckOutItem>
</ArrayOfCheckOutItem>
```

Request (application/x-www-form-urlencoded)

Response (application/json, text/json, application/xml, text/xml)

Example

[Check Out Files in PDM Vault.postman_collection.json](#)

Remarks

This operation:

- takes an array of CheckOutItems.
- returns an array of UndoLockResultModels.

See Also

[File Resource Group](#) | [PDM Pro API Web Service](#)

PUT

api/{vaultName}/files/{changesetId}/finishadd

Description

PUT: api/{vaultName}/files/{changesetId}/finishadd Finish of add file operation. This method adds files from changeset to the vault.

Adds files in the specified changeset to the vault. (See **Remarks**)

Parameters

vaultName	(URI parameter) Vault name (required)	string
changesetId	(URI parameter) Changeset ID (required)	integer
Content	(Response) GUID of the add operation; use the GUID to query the progress/status of the add operation (see api/{vaultName}/progress/{guid}/status) Member of HttpResponseMessage model	HttpContent

Example

[Upload SOLIDWORKS Files to PDM Vault.postman_collection.json](#)

Remarks

Before sending this HTTP request you must send [api/{vaultName}/files/{changesetId}/upload \(Put\)](#) to get a changeset ID.

This request returns a GUID that you can use in further calls to check progress: [api/{vaultName}/progress/{guid}/status \(Get\)](#) and [api/{vaultName}/progress/{guid}/result \(Get\)](#)

See Also

[Stage Resource Group](#) | [PDM Pro API Web Service](#)

PDM Pro API Web Service

PUTapi/{vaultName}/files/{changesetId}/upload

Description

PUT: api/{vaultname}/files/{changesetId}/upload Upload file to changeset to add files operations

Uploads files to the specified changeset. (See **Remarks**)

Parameters

vaultName	(URI parameter) Vault name (required)	string
changesetId	(URI parameter) Changeset ID (required) (See Remarks)	integer

Response (application/json, text/json)

Returns a changeset ID

[Sample Data](#)

1

Response (application/xml, text/xml)

Returns the changeset ID

[Sample Data](#)

<int xmlns="http://schemas.microsoft.com/2003/10/Serialization/">1</int>

Example

[Upload SOLIDWORKS Files to PDM Vault.postman_collection.json](#) | [Program.cs](#)

Remarks

This request also requires a binary Body that consists of the binary files to add to the changeset. Drag/drop the JSON example to Postman and inspect the Body of the HTTP request. The **Program.cs** example creates the binary file that you can upload using this request.

You must call [api/{vaultName}/changeset/create](#) to get the changeset ID for this HTTP request.

See Also

[Stage Resource Group](#) | [PDM Pro API Web Service](#)

GET

api/{vaultName}/files/{fileId}/bominfo?folderId={folderId}

Description

GET: api/{VaultName}/files/{FileID}/bominfo Get file BOM info
Gets the BOM information for the specified file.

Parameters

vaultName	(Required URI parameter) Vault name	string
fileId	(Required URI parameter) File ID	integer
folderId	(URI parameter) Folder ID (default value is 0)	integer
NamedBOM	(Response) A NamedBOMInfoList; each NamedBOMInfoList consists of: BOMList (array of NamedBOMInfo objects; each NamedBOMInfo consists of: Folder (Folder object that consists of FolderId (integer) and FolderPath (string)) Config (Config object that consists of ConfigurationName (string) and ConfigurationId (integer)) BOMId (integer) BOMName (string) VersionNo (integer) SavedBOM (boolean) Member of BOMInfo model	NamedBOMInfoList
ComputedBOM	(Response) A ComputedBOMInfoList; each ComputedBOMInfoList consists of: BOMList (array of ComputedBOMInfo objects; each ComputedBOMInfo consists of: Folder (Folder object that consists of FolderId (integer) and FolderPath (string)) Configs (Array of Config objects, each Config object consists of: ConfigurationName (string) ConfigurationId (integer) BOMId (integer) BOMName (string) Member of BOMInfo model	ComputedBOMInfoList
WeldmentCutlistBOM	(Response) A ComputedBOMInfoList; each ComputedBOMInfoList consists of: BOMList (array of ComputedBOMInfo objects; each ComputedBOMInfo consists of: Folder (Folder object that consists of FolderId (integer) and FolderPath (string)) Configs (Array of Config objects, each Config object consists of: ConfigurationName (string) ConfigurationId (integer) BOMId (integer) BOMName (string) Member of BOMInfo model	ComputedBOMInfoList
WeldmentBOM	(Response) A ComputedBOMInfoList; each ComputedBOMInfoList consists of: BOMList (array of ComputedBOMInfo objects; each ComputedBOMInfo consists of: Folder (Folder object that consists of FolderId (integer) and FolderPath (string)) Configs (Array of Config objects, each Config object consists of: ConfigurationName (string) ConfigurationId (integer) BOMId (integer) BOMName (string) Member of BOMInfo model	ComputedBOMInfoList

Response (application/json, text/json)

Sample Data

```
{
  "NamedBOM": {
    "BOMList": [
      {
        "Folder": {
          "FolderId": 1,
          "FolderPath": "sample string 2"
        },
        "Config": {
          "ConfigurationName": "sample string 1",
          "ConfigurationId": 2
        },
        "BOMId": 1,
        "BOMName": "sample string 2",
        "VersionNo": 3,
        "SavedBOM": true
      },
      {
        "Folder": {
          "FolderId": 1,
          "FolderPath": "sample string 2"
        },
        "Config": {
          "ConfigurationName": "sample string 1",
          "ConfigurationId": 2
        },
        "BOMId": 1,
        "BOMName": "sample string 2",
        "VersionNo": 3,
        "SavedBOM": true
      }
    ]
  },
  "ComputedBOM": {
    "BOMList": [
      {
        "Folder": {
          "FolderId": 1,
          "FolderPath": "sample string 2"
        },
        "Configs": [
          {
            "ConfigurationName": "sample string 1",
            "ConfigurationId": 2
          },
          {
            "ConfigurationName": "sample string 1",
            "ConfigurationId": 2
          }
        ],
        "BOMId": 1,
        "BOMName": "sample string 2"
      },
      {
        "Folder": {
          "FolderId": 1,
          "FolderPath": "sample string 2"
        },
        "Configs": [
          {
            "ConfigurationName": "sample string 1",
            "ConfigurationId": 2
          },
          {
            "ConfigurationName": "sample string 1",
            "ConfigurationId": 2
          }
        ],
        "BOMId": 1,
        "BOMName": "sample string 2"
      }
    ]
  },
  "WeldmentCutlistBOM": {
    "BOMList": [
      {
        "Folder": {
          "FolderId": 1,
          "FolderPath": "sample string 2"
        },
        "Configs": [
          {
            "ConfigurationName": "sample string 1",
            "ConfigurationId": 2
          },
          {
            "ConfigurationName": "sample string 1",
            "ConfigurationId": 2
          }
        ]
      }
    ]
  }
}
```

```

    },
    "BOMId": 1,
    "BOMName": "sample string 2"
  },
  {
    "Folder": {
      "FolderId": 1,
      "FolderPath": "sample string 2"
    },
    "Configs": [
      {
        "ConfigurationName": "sample string 1",
        "ConfigurationId": 2
      },
      {
        "ConfigurationName": "sample string 1",
        "ConfigurationId": 2
      }
    ],
    "BOMId": 1,
    "BOMName": "sample string 2"
  }
],
},
"WeldmentBOM": {
  "BOMList": [
    {
      "Folder": {
        "FolderId": 1,
        "FolderPath": "sample string 2"
      },
      "Configs": [
        {
          "ConfigurationName": "sample string 1",
          "ConfigurationId": 2
        },
        {
          "ConfigurationName": "sample string 1",
          "ConfigurationId": 2
        }
      ],
      "BOMId": 1,
      "BOMName": "sample string 2"
    },
    {
      "Folder": {
        "FolderId": 1,
        "FolderPath": "sample string 2"
      },
      "Configs": [
        {
          "ConfigurationName": "sample string 1",
          "ConfigurationId": 2
        },
        {
          "ConfigurationName": "sample string 1",
          "ConfigurationId": 2
        }
      ],
      "BOMId": 1,
      "BOMName": "sample string 2"
    }
  ]
}
}
}

```

Response (application/xml, text/xml)

Sample Data

```

<BOMInfo xmlns:i="http://www.w3.org/2001/XMLSchema-instance" xmlns="http://schemas.datacontract.org/2004/07/SWPDM.Models">
  <ComputedBOM>
    <BOMList>
      <ComputedBOMInfo>
        <BOMId>1</BOMId>
        <BOMName>sample string 2</BOMName>
        <Configs>
          <Config>
            <ConfigurationId>2</ConfigurationId>
            <ConfigurationName>sample string 1</ConfigurationName>
          </Config>
          <Config>
            <ConfigurationId>2</ConfigurationId>
            <ConfigurationName>sample string 1</ConfigurationName>
          </Config>
        </Configs>
        <Folder>
          <FolderId>1</FolderId>
          <FolderPath>sample string 2</FolderPath>
        </Folder>
      </ComputedBOMInfo>
    
```

```

    <ComputedBOMInfo>
      <BOMId>1</BOMId>
      <BOMName>sample string 2</BOMName>
      <Configs>
        <Config>
          <ConfigurationId>2</ConfigurationId>
          <ConfigurationName>sample string 1</ConfigurationName>
        </Config>
        <Config>
          <ConfigurationId>2</ConfigurationId>
          <ConfigurationName>sample string 1</ConfigurationName>
        </Config>
      </Configs>
      <Folder>
        <FolderId>1</FolderId>
        <FolderPath>sample string 2</FolderPath>
      </Folder>
    </ComputedBOMInfo>
  </BOMList>
</ComputedBOM>
<NamedBOM>
  <BOMList>
    <NamedBOMInfo>
      <BOMId>1</BOMId>
      <BOMName>sample string 2</BOMName>
      <Config>
        <ConfigurationId>2</ConfigurationId>
        <ConfigurationName>sample string 1</ConfigurationName>
      </Config>
      <Folder>
        <FolderId>1</FolderId>
        <FolderPath>sample string 2</FolderPath>
      </Folder>
      <SavedBOM>true</SavedBOM>
      <VersionNo>3</VersionNo>
    </NamedBOMInfo>
    <NamedBOMInfo>
      <BOMId>1</BOMId>
      <BOMName>sample string 2</BOMName>
      <Config>
        <ConfigurationId>2</ConfigurationId>
        <ConfigurationName>sample string 1</ConfigurationName>
      </Config>
      <Folder>
        <FolderId>1</FolderId>
        <FolderPath>sample string 2</FolderPath>
      </Folder>
      <SavedBOM>true</SavedBOM>
      <VersionNo>3</VersionNo>
    </NamedBOMInfo>
  </BOMList>
</NamedBOM>
<WeldmentBOM>
  <BOMList>
    <ComputedBOMInfo>
      <BOMId>1</BOMId>
      <BOMName>sample string 2</BOMName>
      <Configs>
        <Config>
          <ConfigurationId>2</ConfigurationId>
          <ConfigurationName>sample string 1</ConfigurationName>
        </Config>
        <Config>
          <ConfigurationId>2</ConfigurationId>
          <ConfigurationName>sample string 1</ConfigurationName>
        </Config>
      </Configs>
      <Folder>
        <FolderId>1</FolderId>
        <FolderPath>sample string 2</FolderPath>
      </Folder>
    </ComputedBOMInfo>
    <ComputedBOMInfo>
      <BOMId>1</BOMId>
      <BOMName>sample string 2</BOMName>
      <Configs>
        <Config>
          <ConfigurationId>2</ConfigurationId>
          <ConfigurationName>sample string 1</ConfigurationName>
        </Config>
        <Config>
          <ConfigurationId>2</ConfigurationId>
          <ConfigurationName>sample string 1</ConfigurationName>
        </Config>
      </Configs>
      <Folder>
        <FolderId>1</FolderId>
        <FolderPath>sample string 2</FolderPath>
      </Folder>
    </ComputedBOMInfo>
  </BOMList>
</WeldmentBOM>
<WeldmentCutlistBOM>
  <BOMList>

```

```

<ComputedBOMInfo>
  <BOMId>1</BOMId>
  <BOMName>sample string 2</BOMName>
  <Configs>
    <Config>
      <ConfigurationId>2</ConfigurationId>
      <ConfigurationName>sample string 1</ConfigurationName>
    </Config>
    <Config>
      <ConfigurationId>2</ConfigurationId>
      <ConfigurationName>sample string 1</ConfigurationName>
    </Config>
  </Configs>
  <Folder>
    <FolderId>1</FolderId>
    <FolderPath>sample string 2</FolderPath>
  </Folder>
</ComputedBOMInfo>
<ComputedBOMInfo>
  <BOMId>1</BOMId>
  <BOMName>sample string 2</BOMName>
  <Configs>
    <Config>
      <ConfigurationId>2</ConfigurationId>
      <ConfigurationName>sample string 1</ConfigurationName>
    </Config>
    <Config>
      <ConfigurationId>2</ConfigurationId>
      <ConfigurationName>sample string 1</ConfigurationName>
    </Config>
  </Configs>
  <Folder>
    <FolderId>1</FolderId>
    <FolderPath>sample string 2</FolderPath>
  </Folder>
</ComputedBOMInfo>
</BOMList>
</WeldmentCutlistBOM>
</BOMInfo>

```

See Also

[File Resource Group | PDM Pro API Web Service](#)