

PDM Professional Web API (REST) — Reference (2/3): r-api- {vaultName}-files-{fileId}-datacar-r-api-{vaultName}-files- {fileId}-versio

SOLIDWORKS API Documentation (converted from CHM)

POST

api/{vaultName}/files/{fileId}/datacard

Description

Save file data card

Saves the data card for the specified file and vault.

Parameters

vaultName	(URI parameter) Vault name (required)	string
fileId	(URI parameter) File ID (required)	integer
Models	(Body) Array of VariableInfo_DataCards; each VariableInfo_DataCard consists of: ReadOnly (boolean) Multiline (boolean) VarId (integer) VarName (string) VarValue (string) VarType (one of: VarTypeNone = 0 VarTypeText = 1 VarTypeInt = 2 VarTypeFloat = 3 VarTypeBool = 4 VarTypeDate = 5 Mandatory (boolean) VersionFree (boolean) Member of ConfigInfo_DataCard model (see Remarks)	Collection of VariableInfo_DataCard
ConfigurationName	(Body) Configuration name Member of ConfigInfo_DataCard model (see Remarks)	string
ConfigurationId	(Body) Configuration ID Member of ConfigInfo_DataCard model (see Remarks)	integer

Request (application/json, text/json)

Body parameter contains multiple arrays, each consisting of variables to modify (Models), configuration name, and configuration ID.

Sample Data

```
[
  {
    "Models": [
      {
        "ReadOnly": true,
        "Multiline": true,
        "VarId": 3,
        "VarName": "sample string 4",
        "VarValue": "sample string 5",
        "VarType": 0,
        "Mandatory": true,
        "VersionFree": true
      },
      {
        "ReadOnly": true,
```

```

        "Multiline": true,
        "VarId": 3,
        "VarName": "sample string 4",
        "VarValue": "sample string 5",
        "VarType": 0,
        "Mandatory": true,
        "VersionFree": true
    }
},
"ConfigurationName": "sample string 1",
"ConfigurationId": 2
},
{
    "Models": [
        {
            "ReadOnly": true,
            "Multiline": true,
            "VarId": 3,
            "VarName": "sample string 4",
            "VarValue": "sample string 5",
            "VarType": 0,
            "Mandatory": true,
            "VersionFree": true
        },
        {
            "ReadOnly": true,
            "Multiline": true,
            "VarId": 3,
            "VarName": "sample string 4",
            "VarValue": "sample string 5",
            "VarType": 0,
            "Mandatory": true,
            "VersionFree": true
        }
    ],
    "ConfigurationName": "sample string 1",
    "ConfigurationId": 2
}
]

```

Request (application/xml, text/xml)

Body parameter contains multiple arrays, each consisting of variables to modify (Models), configuration name, and configuration ID.

Sample Data

```

<ArrayOfConfigInfo_DataCard xmlns:i="http://www.w3.org/2001/XMLSchema-instance"
xmlns="http://schemas.datacontract.org/2004/07/SWPDM.Models">
  <ConfigInfo_DataCard>
    <ConfigurationId>2</ConfigurationId>
    <ConfigurationName>sample string 1</ConfigurationName>
    <Models>
      <VariableInfo_DataCard>
        <Mandatory>true</Mandatory>
        <VarId>3</VarId>
        <VarName>sample string 4</VarName>
        <VarType>VarTypeNone</VarType>
        <VarValue>sample string 5</VarValue>
        <VersionFree>true</VersionFree>
        <Multiline>true</Multiline>
        <ReadOnly>true</ReadOnly>
      </VariableInfo_DataCard>
      <VariableInfo_DataCard>
        <Mandatory>true</Mandatory>
        <VarId>3</VarId>
        <VarName>sample string 4</VarName>
        <VarType>VarTypeNone</VarType>
        <VarValue>sample string 5</VarValue>
        <VersionFree>true</VersionFree>
        <Multiline>true</Multiline>
        <ReadOnly>true</ReadOnly>
      </VariableInfo_DataCard>
    </Models>
  </ConfigInfo_DataCard>
  <ConfigInfo_DataCard>
    <ConfigurationId>2</ConfigurationId>
    <ConfigurationName>sample string 1</ConfigurationName>
    <Models>
      <VariableInfo_DataCard>
        <Mandatory>true</Mandatory>
        <VarId>3</VarId>
        <VarName>sample string 4</VarName>
        <VarType>VarTypeNone</VarType>
        <VarValue>sample string 5</VarValue>

```

```

        <VersionFree>true</VersionFree>
        <Multiline>true</Multiline>
        <ReadOnly>true</ReadOnly>
    </VariableInfo_DataCard>
    <VariableInfo_DataCard>
        <Mandatory>true</Mandatory>
        <VarId>3</VarId>
        <VarName>sample string 4</VarName>
        <VarType>VarTypeNone</VarType>
        <VarValue>sample string 5</VarValue>
        <VersionFree>true</VersionFree>
        <Multiline>true</Multiline>
        <ReadOnly>true</ReadOnly>
    </VariableInfo_DataCard>
    </Models>
</ConfigInfo_DataCard>
</ArrayOfConfigInfo_DataCard>

```

Request (application/x-www-form-urlencoded)

Body parameter contains multiple arrays, each consisting of variables to modify (Models), configuration name, and configuration ID.

Response (application/json, text/json)

Returns the status of the operation.

Sample Data

```
true
```

Response (application/xml, text/xml)

Returns the status of the operation.

Sample Data

```
<boolean xmlns="http://schemas.microsoft.com/2003/10/Serialization/">true</boolean>
```

Example

Remarks

Models, ConfigurationName, and ConfigurationId are all members of ConfigInfo_DataCard. This operation can return an array of ConfigInfo_DataCards. See the Request samples.

See Also

[Data Card Resource Group](#) | [PDM Pro API Web Service](#)

POST

api/{vaultName}/files/{fileId}/datacard?folderId={folderId}

Description

Saves the specified data card variables to the specified file.

Parameters

vaultName	(URI parameter) Name of vault	string
fileId	(URI parameter) File ID	integer
folderId	(URI parameter) Folder ID	integer
Models	(Body parameter) (VariableInfo_DataCard: ReadOnly: boolean Multiline: boolean VarId: integer VarName: string VarValue: string VarType: VarTypeNone = 0 VarTypeText = 1 VarTypeInt = 2 VarTypeFloat = 3 VarTypeBool = 4 VarTypeDate = 5 Mandatory: boolean VersionFree: boolean) (Member of ConfigInfo_DataCard)	Collection of VariableInfo_DataCard
ConfigurationName	(Body parameter) Name of configuration (Member of ConfigInfo_DataCard)	string
ConfigurationId	(Body parameter) Configuration ID (Member of ConfigInfo_DataCard)	integer

Request (application/json, text/json)

Sample Data

```
[
  {
    "Models": [
      {
        "ReadOnly": true,
        "Multiline": true,
        "VarId": 3,
        "VarName": "sample string 4",
        "VarValue": "sample string 5",
        "VarType": 0,
        "Mandatory": true,
        "VersionFree": true
      },
      {
        "ReadOnly": true,
        "Multiline": true,
```

```

        "VarId": 3,
        "VarName": "sample string 4",
        "VarValue": "sample string 5",
        "VarType": 0,
        "Mandatory": true,
        "VersionFree": true
    }
},
"ConfigurationName": "sample string 1",
"ConfigurationId": 2
},
{
    "Models": [
        {
            "ReadOnly": true,
            "Multiline": true,
            "VarId": 3,
            "VarName": "sample string 4",
            "VarValue": "sample string 5",
            "VarType": 0,
            "Mandatory": true,
            "VersionFree": true
        },
        {
            "ReadOnly": true,
            "Multiline": true,
            "VarId": 3,
            "VarName": "sample string 4",
            "VarValue": "sample string 5",
            "VarType": 0,
            "Mandatory": true,
            "VersionFree": true
        }
    ],
    "ConfigurationName": "sample string 1",
    "ConfigurationId": 2
}
}
]

```

Request (application/xml, text/xml)

Sample Data

```

<ArrayOfConfigInfo_DataCard xmlns:i="http://www.w3.org/2001/XMLSchema-instance"
xmlns="http://schemas.datacontract.org/2004/07/SWPDM.Models">
  <ConfigInfo_DataCard>
    <ConfigurationId>2</ConfigurationId>
    <ConfigurationName>sample string 1</ConfigurationName>
    <Models>
      <VariableInfo_DataCard>
        <Mandatory>true</Mandatory>
        <VarId>3</VarId>
        <VarName>sample string 4</VarName>
        <VarType>VarTypeNone</VarType>
        <VarValue>sample string 5</VarValue>
        <VersionFree>true</VersionFree>
        <Multiline>true</Multiline>
        <ReadOnly>true</ReadOnly>
      </VariableInfo_DataCard>
      <VariableInfo_DataCard>
        <Mandatory>true</Mandatory>
        <VarId>3</VarId>
        <VarName>sample string 4</VarName>
        <VarType>VarTypeNone</VarType>
        <VarValue>sample string 5</VarValue>
        <VersionFree>true</VersionFree>
        <Multiline>true</Multiline>
        <ReadOnly>true</ReadOnly>
      </VariableInfo_DataCard>
    </Models>
  </ConfigInfo_DataCard>
  <ConfigInfo_DataCard>
    <ConfigurationId>2</ConfigurationId>
    <ConfigurationName>sample string 1</ConfigurationName>
    <Models>
      <VariableInfo_DataCard>
        <Mandatory>true</Mandatory>
        <VarId>3</VarId>
        <VarName>sample string 4</VarName>
        <VarType>VarTypeNone</VarType>
        <VarValue>sample string 5</VarValue>
        <VersionFree>true</VersionFree>
        <Multiline>true</Multiline>
        <ReadOnly>true</ReadOnly>
      </VariableInfo_DataCard>
    </Models>
  </ConfigInfo_DataCard>
</ArrayOfConfigInfo_DataCard>

```

```
</VariableInfo_DataCard>
<VariableInfo_DataCard>
  <Mandatory>true</Mandatory>
  <VarId>3</VarId>
  <VarName>sample string 4</VarName>
  <VarType>VarTypeNone</VarType>
  <VarValue>sample string 5</VarValue>
  <VersionFree>true</VersionFree>
  <Multiline>true</Multiline>
  <ReadOnly>true</ReadOnly>
</VariableInfo_DataCard>
</Models>
</ConfigInfo_DataCard>
</ArrayOfConfigInfo_DataCard>
```

Request (application/x-www-form-urlencoded)

Response (application/json, text/json)

Sample Data

true

Response (application/xml, text/xml)

Sample Data

```
<boolean xmlns="http://schemas.microsoft.com/2003/10/Serialization/">true</boolean>
```

See Also

[Data Card Resource Group](#) | [PDM Pro API Web Service](#)

DELETE

api/{vaultName}/files/{fileId}?destroy={destroy}

Description

Delete file

Deletes the specified file

Parameters

vaultName	(URI parameter) Vault name (required)	string
fileId	(URI parameter) File ID (required)	integer
destroy	(URI parameter) Whether to delete the file (default value is false)	boolean
Id	(Response) ID of object	integer
	Member of ObjectInfoShort model	
Name	(Response) Name of object	string
	Member of ObjectInfoShort model	
Type	(Response) An ObjectType object; one of: Folder = 0 File = 1 Bom = 3	ObjectType
	Member of ObjectInfoShort model	
Status	(Response) A StatusOperation object; one of: Success = 0 Failure = 1	StatusOperation
	Member of ObjectInfoShort model	
Warning	(Response) A BaseWarningModel object that consists of: Message (string) IsBlocking (boolean) IsError (boolean)	BaseWarningModel
	Member of ObjectInfoShort model	

Response (application/json, text/json)

Sample Data

```
{
  "Id": 1,
  "Name": "sample string 2",
  "Type": 0,
  "Status": 0,
  "Warning": null
}
```

Response (application/xml, text/xml)

Sample Data

```
<ObjectInfoShort xmlns:i="http://www.w3.org/2001/XMLSchema-instance"
xmlns="http://schemas.datacontract.org/2004/07/SWPDM.Models">
  <Id>1</Id>
  <Name>sample string 2</Name>
  <Status>Success</Status>
  <Type>Folder</Type>
  <Warning i:nil="true" />
</ObjectInfoShort>
```

See Also

[File Resource Group](#) | [PDM Pro API Web Service](#)

DELETE**api/{vaultName}/files/{fileId}?folderId={folderId}&destroy={destroy}****Description**

Deletes the specified file.

Parameters

vaultName	(Required URI parameter) Vault name	string
fileId	(Required URI parameter) File ID	integer
folderId	(URI parameter) Folder ID; default is 0	integer
destroy	(URI parameter) True to destroy, false to not	boolean
Id	(Response parameter) File type: Folder = 0 File = 1 Bom = 3 (Member of ObjectInfoShort Model)	integer
Name	(Response parameter) File name	string
Type	(Response parameter) File type Folder = 0 File = 1 Bom = 3	ObjectType
Status	(Response parameter) Status code: Success = 0 Failure = 1 (Member of ObjectInfoShort Model)	StatusOperation
Warning	(Response parameter) Warning: Message: string IsBlocking: boolean IsError: boolean (Member of ObjectInfoShort Model)	BaseWarningModel

Response (application/json, text/json)**Sample Data**

```
{
  "Id": 1,
  "Name": "sample string 2",
  "Type": 0,
  "Status": 0,
  "Warning": null
}
```

Response (application/xml, text/xml)**Sample Data**

```
<ObjectInfoShort xmlns:i="http://www.w3.org/2001/XMLSchema-instance"
xmlns="http://schemas.datacontract.org/2004/07/SWPDM.Models">
  <Id>1</Id>
  <Name>sample string 2</Name>
  <Status>Success</Status>
  <Type>Folder</Type>
  <Warning i:nil="true" />
</ObjectInfoShort>
```

See Also

[File Resource Group](#) | [PDM Pro API Web Service](#)

GET**api/{vaultName}/files/{fileId}/history?folderId={folderId}**

Description

Gets a specified file's history.

Parameters

vaultName	(Required URI Parameter) Vault name	string
fileId	(Required URI Parameter) File ID	integer
folderId	(URI Parameter) Folder ID, default is 0	integer
DocumentId	(Response) Document ID (Member of HistoryBase model)	integer
Version	(Response) File version (Member of HistoryBase model)	integer
User	(Response) UserInfo: UserName: string UserId: integer (Member of HistoryBase model)	UserInfo
Date	(Response) Date (Member of HistoryBase model)	date
HistoryType	(Response) HistoryType: None = 0 Share = 1 Rename = 2 Move = 3 Rollback = 4 Delete = 5 Version = 7 Label = 9 Transition = 10 Revision = 11 ColdStore = 12 VerFreeVar = 18 PendingState = 20 ParallelState = 21 VersionOverwrite = 22 Branch = 23 DocUndoLock = 24 DocBranchMerge = 25 DocLock = 26 DocUndoLock2 = 27 (Member of HistoryBase model)	HistoryType
Event	(Response) Event (Member of HistoryBase model)	string

Comment	(Response) Comment (Member of HistoryBase model)	string
---------	---	--------

Response (application/json, text/json, application/xml, text/xml)

See Also

[File Resource Group](#) | [PDM Pro API Web Service](#)

GET

api/{vaultName}/files/{fileId}/info?version={version}

Description

Get file info

Gets information about the specified file.

Parameters

vaultName	(URI parameter) Vault name (required)	string
fileId	(URI parameter) File ID (required)	integer
version	(URI and Response parameter) Version (default value is 0)	integer
Id	(Response) File ID Member of ObjectInfo model; see Remarks	integer
Name	(Response) File name Member of ObjectInfo model; see Remarks	string
Size	(Response) File size Member of ObjectInfo model; see Remarks	integer
ModifiedDate	(Response) Modification date Member of ObjectInfo model; see Remarks	date
State	(Response) Workflow state Member of ObjectInfo model; see Remarks	string
StateId	(Response) State ID Member of ObjectInfo model; see Remarks	integer
ParentFolderId	(Response) Parent folder ID Member of ObjectInfo model; see Remarks	integer
Path	(Response) Folder path Member of ObjectInfo model; see Remarks	string
Type	(Response) ObjectType model; one of: Folder = 0 File = 1 Bom = 3 Member of ObjectInfo model; see Remarks	ObjectType

IsLocked	(Response) Whether the file is checked out	integer
	Member of ObjectInfo model; see Remarks	
LockedBy	(Response) ID of user who checked out the file	integer
	Member of ObjectInfo model; see Remarks	
IsShared	(Response) Whether the file is shared	integer
	Member of ObjectInfo model; see Remarks	
IsToolbox	(Response) Whether the file is a toolbox item	integer
	Member of ObjectInfo model; see Remarks	
IsDeleted	(Response) Whether the file is deleted	integer
	Member of ObjectInfo model; see Remarks	

Response (application/json, text/json)

Sample Data

```
[
  {
    "Id": 1,
    "Name": "sample string 2",
    "Size": 3,
    "ModifiedDate": "2022-07-25T14:02:49.4594064-04:00",
    "Version": 5,
    "State": "sample string 6",
    "StateId": 7,
    "ParentFolderId": 8,
    "Path": "sample string 9",
    "Type": 0,
    "IsLocked": 10,
    "LockedBy": 11,
    "IsShared": 12,
    "IsToolbox": 13,
    "IsDeleted": 14
  },
  {
    "Id": 1,
    "Name": "sample string 2",
    "Size": 3,
    "ModifiedDate": "2022-07-25T14:02:49.4594064-04:00",
    "Version": 5,
    "State": "sample string 6",
    "StateId": 7,
    "ParentFolderId": 8,
    "Path": "sample string 9",
    "Type": 0,
    "IsLocked": 10,
    "LockedBy": 11,
    "IsShared": 12,
    "IsToolbox": 13,
    "IsDeleted": 14
  }
]
```

Response (application/xml, text/xml)

Sample Data

```
<ArrayOfObjectInfo xmlns:i="http://www.w3.org/2001/XMLSchema-instance"
xmlns="http://schemas.datacontract.org/2004/07/SWPDM.Models">
  <ObjectInfo>
    <Id>1</Id>
    <IsDeleted>14</IsDeleted>
    <IsLocked>10</IsLocked>
    <IsShared>12</IsShared>
    <IsToolbox>13</IsToolbox>
    <LockedBy>11</LockedBy>
    <ModifiedDate>2022-07-25T14:02:49.4594064-04:00</ModifiedDate>
    <Name>sample string 2</Name>
    <ParentFolderId>8</ParentFolderId>
    <Path>sample string 9</Path>
    <Size>3</Size>
    <State>sample string 6</State>
    <StateId>7</StateId>
    <Type>Folder</Type>
    <Version>5</Version>
  </ObjectInfo>
  <ObjectInfo>
    <Id>1</Id>
    <IsDeleted>14</IsDeleted>
    <IsLocked>10</IsLocked>
    <IsShared>12</IsShared>
    <IsToolbox>13</IsToolbox>
    <LockedBy>11</LockedBy>
    <ModifiedDate>2022-07-25T14:02:49.4594064-04:00</ModifiedDate>
    <Name>sample string 2</Name>
    <ParentFolderId>8</ParentFolderId>
    <Path>sample string 9</Path>
    <Size>3</Size>
    <State>sample string 6</State>
    <StateId>7</StateId>
    <Type>Folder</Type>
    <Version>5</Version>
  </ObjectInfo>
</ArrayOfObjectInfo>
```

Remarks

This operation should return one ObjectInfo object for each unique file ID in the request URI.

See Also

[File Resource Group](#) | [PDM Pro API Web Service](#)

GET**api/{vaultName}/files/{fileId}/info?version={version}&folderId={folderId}**

Description

Gets information about the specified file.

Parameters

vaultName	(Required URI Parameter) Vault name	string
fileId	(Required URI Parameter) File ID	integer
version	(URI Parameter) File version, default value is 0	integer
folderId	(URI Parameter) Folder ID, default value is 0	integer
Id	(Response) File ID (Member of ObjectInfo model)	integer
Name	(Response) File name (Member of ObjectInfo model)	string
Size	(Response) File size (Member of ObjectInfo model)	integer
ModifiedDate	(Response) Modified date (Member of ObjectInfo model)	date
State	(Response) File state (Member of ObjectInfo model)	string
StateId	(Response) File state ID (Member of ObjectInfo model)	integer
ParentFolderId	(Response) Parent folder ID (Member of ObjectInfo model)	integer
Path	(Response) Folder path (Member of ObjectInfo model)	string
Type	(Response) Object Type: Folder = 0 File = 1 Bom = 3 (Member of ObjectInfo model)	ObjectType
IsLocked	(Response) Whether file is locked (checked out) (Member of ObjectInfo model)	integer
LockedBy	(Response) ID of user who checked out the file (Member of ObjectInfo model)	integer
IsShared	(Response) Whether the file is shared (Member of ObjectInfo model)	integer
IsToolbox	(Response) 1 if a ToolBox item, 0 if not (Member of ObjectInfo model)	integer

IsDeleted

(Response) Whether file is deleted
(Member of ObjectInfo model)

integer

Response (application/json, text/json)

Sample Data

```
[
  {
    "Id": 1,
    "Name": "sample string 2",
    "Size": 3,
    "ModifiedDate": "2024-11-27T09:52:30.6405732-05:00",
    "Version": 5,
    "State": "sample string 6",
    "StateId": 7,
    "ParentFolderId": 8,
    "Path": "sample string 9",
    "Type": 0,
    "IsLocked": 10,
    "LockedBy": 11,
    "IsShared": 12,
    "IsToolbox": 13,
    "IsDeleted": 14
  },
  {
    "Id": 1,
    "Name": "sample string 2",
    "Size": 3,
    "ModifiedDate": "2024-11-27T09:52:30.6405732-05:00",
    "Version": 5,
    "State": "sample string 6",
    "StateId": 7,
    "ParentFolderId": 8,
    "Path": "sample string 9",
    "Type": 0,
    "IsLocked": 10,
    "LockedBy": 11,
    "IsShared": 12,
    "IsToolbox": 13,
    "IsDeleted": 14
  }
]
```

Response (application/xml, text/xml)

Sample Data

```
<ArrayOfObjectInfo xmlns:i="http://www.w3.org/2001/XMLSchema-instance"
xmlns="http://schemas.datacontract.org/2004/07/SWPDM.Models">
  <ObjectInfo>
    <Id>1</Id>
    <IsDeleted>14</IsDeleted>
    <IsLocked>10</IsLocked>
    <IsShared>12</IsShared>
    <IsToolbox>13</IsToolbox>
    <LockedBy>11</LockedBy>
    <ModifiedDate>2024-11-27T09:52:30.6405732-05:00</ModifiedDate>
    <Name>sample string 2</Name>
    <ParentFolderId>8</ParentFolderId>
    <Path>sample string 9</Path>
    <Size>3</Size>
    <State>sample string 6</State>
    <StateId>7</StateId>
    <Type>Folder</Type>
    <Version>5</Version>
  </ObjectInfo>
  <ObjectInfo>
    <Id>1</Id>
    <IsDeleted>14</IsDeleted>
    <IsLocked>10</IsLocked>
    <IsShared>12</IsShared>
    <IsToolbox>13</IsToolbox>
    <LockedBy>11</LockedBy>
    <ModifiedDate>2024-11-27T09:52:30.6405732-05:00</ModifiedDate>
    <Name>sample string 2</Name>
    <ParentFolderId>8</ParentFolderId>
    <Path>sample string 9</Path>
    <Size>3</Size>
    <State>sample string 6</State>
  </ObjectInfo>
</ArrayOfObjectInfo>
```

```
<StateId>7</StateId>
<Type>Folder</Type>
<Version>5</Version>
</ObjectInfo>
</ArrayOfObjectInfo>
```

See Also

[File Resource Group](#) | [PDM Pro API Web Service](#)

GET

api/{vaultName}/files/{fileId}/moves?folderId={folderId}

Description

Gets the history of moves for the specified file.

Parameters

vaultName	(Required URI Parameter) Vault name	string
fileId	(Required URI Parameter) File ID	integer
folderId	(URI Parameter) Folder ID, default is 0	integer
Source	(Response) Source Folder: FolderId: integer FolderPath: string (Member of HistoryMove)	Folder
Destination	(Response) Destination Folder: FolderId: integer FolderPath: string (Member of HistoryMove)	Folder
Date	(Response) Date (Member of HistoryMove)	date

Response (application/json, text/json)

Sample Data

```
[
  {
    "Source": {
      "FolderId": 1,
      "FolderPath": "sample string 2"
    },
    "Destination": {
      "FolderId": 1,
      "FolderPath": "sample string 2"
    },
    "Date": "2024-11-27T09:52:30.6956057-05:00"
  },
  {
    "Source": {
      "FolderId": 1,
      "FolderPath": "sample string 2"
    },
    "Destination": {
      "FolderId": 1,
      "FolderPath": "sample string 2"
    },
    "Date": "2024-11-27T09:52:30.6956057-05:00"
  }
]
```

Response (application/xml, text/xml)

Sample Data

```
<ArrayOfHistoryMove xmlns:i="http://www.w3.org/2001/XMLSchema-instance"
xmlns="http://schemas.datacontract.org/2004/07/SWPDM.Models">
  <HistoryMove>
    <Date>2024-11-27T09:52:30.6956057-05:00</Date>
    <Destination>
      <FolderId>1</FolderId>
```

```
<FolderPath>sample string 2</FolderPath>
</Destination>
<Source>
  <FolderId>1</FolderId>
  <FolderPath>sample string 2</FolderPath>
</Source>
</HistoryMove>
<HistoryMove>
  <Date>2024-11-27T09:52:30.6956057-05:00</Date>
  <Destination>
    <FolderId>1</FolderId>
    <FolderPath>sample string 2</FolderPath>
  </Destination>
  <Source>
    <FolderId>1</FolderId>
    <FolderPath>sample string 2</FolderPath>
  </Source>
</HistoryMove>
</ArrayOfHistoryMove>
```

See Also

[File Resource Group](#) | [PDM Pro API Web Service](#)

GET

api/{vaultName}/files/{fileId}/transitions?version={version}

Description

Get file transitions

Gets the state transitions for the specified file.

Parameters

vaultName	(URI parameter) Vault name (required)	string
fileId	(URI parameter) File ID (required)	integer
version	(URI parameter) Version (default value is -1)	integer
TransitionId	(Response) Transition ID Member of HistoryTransition model	integer
VersionNo	(Response) Version number Member of HistoryTransition model	integer
Comment	(Response) Comment Member of HistoryTransition model	string
Date	(Response) Date Member of HistoryTransition model	date
SourceState	(Response) A StateInfo object; each StateInfo object consists of: StateId (integer) StateName (string) IgnorePreviousPermissions (integer) Member of HistoryTransition model	StateInfo
DestinationState	(Response) A StateInfo object; each StateInfo object consists of: StateId (integer) StateName (string) IgnorePreviousPermissions (integer) Member of HistoryTransition model	StateInfo
User	(Response) A UserInfo object; each UserInfo object consists of: UserName (string) UserId (integer) Member of HistoryTransition model	UserInfo

Response (application/json, text/json)

Sample Data

```
[
  {
    "TransitionId": 1,
    "VersionNo": 2,
    "Comment": "sample string 3",
    "Date": "2022-07-25T14:02:49.482406-04:00",
    "SourceState": {
      "StateId": 1,
      "StateName": "sample string 2",
      "IgnorePreviousPermissions": 3
    },
    "DestinationState": {
      "StateId": 1,
      "StateName": "sample string 2",
      "IgnorePreviousPermissions": 3
    },
    "User": {
      "UserName": "sample string 1",
      "UserId": 2
    }
  },
  {
    "TransitionId": 1,
    "VersionNo": 2,
    "Comment": "sample string 3",
    "Date": "2022-07-25T14:02:49.482406-04:00",
    "SourceState": {
      "StateId": 1,
      "StateName": "sample string 2",
      "IgnorePreviousPermissions": 3
    },
    "DestinationState": {
      "StateId": 1,
      "StateName": "sample string 2",
      "IgnorePreviousPermissions": 3
    },
    "User": {
      "UserName": "sample string 1",
      "UserId": 2
    }
  }
]
```

Response (application/xml, text/xml)

Sample Data

```
<ArrayOfHistoryTransition xmlns:i="http://www.w3.org/2001/XMLSchema-instance"
  xmlns="http://schemas.datacontract.org/2004/07/SWPDM.Models">
  <HistoryTransition>
    <Comment>sample string 3</Comment>
    <Date>2022-07-25T14:02:49.482406-04:00</Date>
    <DestinationState>
      <IgnorePreviousPermissions>3</IgnorePreviousPermissions>
      <StateId>1</StateId>
      <StateName>sample string 2</StateName>
    </DestinationState>
    <SourceState>
      <IgnorePreviousPermissions>3</IgnorePreviousPermissions>
      <StateId>1</StateId>
      <StateName>sample string 2</StateName>
    </SourceState>
    <TransitionId>1</TransitionId>
    <User>
      <UserId>2</UserId>
      <UserName>sample string 1</UserName>
    </User>
    <VersionNo>2</VersionNo>
  </HistoryTransition>
  <HistoryTransition>
    <Comment>sample string 3</Comment>
    <Date>2022-07-25T14:02:49.482406-04:00</Date>
    <DestinationState>
      <IgnorePreviousPermissions>3</IgnorePreviousPermissions>
      <StateId>1</StateId>
      <StateName>sample string 2</StateName>
    </DestinationState>
    <SourceState>
```

```
<IgnorePreviousPermissions>3</IgnorePreviousPermissions>
<StateId>1</StateId>
<StateName>sample string 2</StateName>
</SourceState>
<TransitionId>1</TransitionId>
<User>
  <UserId>2</UserId>
  <UserName>sample string 1</UserName>
</User>
<VersionNo>2</VersionNo>
</HistoryTransition>
</ArrayOfHistoryTransition>
```

Remarks

This operation returns an array of HistoryTransition objects, one for each transition made by the file.

See Also

[File Resource Group](#) | [PDM Pro API Web Service](#)

GET

api/{vaultName}/files/{fileId}/transitions?version={version}&folderId={folderId}

Description

Gets the file transitions for the specified file.

Parameters

vaultName	(Required URI Parameter) Vault name	string
fileId	(Required URI Parameter) File ID	integer
version	(URI Parameter) File version, default is -1	integer
folderId	(URI Parameter) Folder ID, default is 0	integer
TransitionId	(Response) Transition ID (Member of HistoryTransition Model)	integer
VersionNo	(Response) Version number (Member of HistoryTransition Model)	integer
Comment	(Response) Comment (Member of HistoryTransition Model)	string
Date	(Response) Date (Member of HistoryTransition Model)	date
SourceState	(Response) Source StateInfo: StateId: integer StateName: string IgnorePreviousPermissions: integer (Member of HistoryTransition Model)	StateInfo
DestinationState	(Response) Destination StateInfo: StateId: integer StateName: string IgnorePreviousPermissions: integer (Member of HistoryTransition Model)	StateInfo
User	(Response) UserInfo: UserName: string UserId: integer (Member of HistoryTransition Model)	UserInfo

Response (application/json, text/json)

Sample Data

```
[
  {
    "TransitionId": 1,
    "VersionNo": 2,
    "Comment": "sample string 3",
    "Date": "2024-11-27T09:52:30.6765737-05:00",
    "SourceState": {
      "StateId": 1,
      "StateName": "sample string 2",
      "IgnorePreviousPermissions": 3
    }
  }
]
```

```

    },
    "DestinationState": {
      "StateId": 1,
      "StateName": "sample string 2",
      "IgnorePreviousPermissions": 3
    },
    "User": {
      "UserName": "sample string 1",
      "UserId": 2
    }
  },
  {
    "TransitionId": 1,
    "VersionNo": 2,
    "Comment": "sample string 3",
    "Date": "2024-11-27T09:52:30.6765737-05:00",
    "SourceState": {
      "StateId": 1,
      "StateName": "sample string 2",
      "IgnorePreviousPermissions": 3
    },
    "DestinationState": {
      "StateId": 1,
      "StateName": "sample string 2",
      "IgnorePreviousPermissions": 3
    },
    "User": {
      "UserName": "sample string 1",
      "UserId": 2
    }
  }
]

```

Response (application/xml, text/xml)

Sample Data

```

<ArrayOfHistoryTransition xmlns:i="http://www.w3.org/2001/XMLSchema-instance"
xmlns="http://schemas.datacontract.org/2004/07/SWPDM.Models">
  <HistoryTransition>
    <Comment>sample string 3</Comment>
    <Date>2024-11-27T09:52:30.6765737-05:00</Date>
    <DestinationState>
      <IgnorePreviousPermissions>3</IgnorePreviousPermissions>
      <StateId>1</StateId>
      <StateName>sample string 2</StateName>
    </DestinationState>
    <SourceState>
      <IgnorePreviousPermissions>3</IgnorePreviousPermissions>
      <StateId>1</StateId>
      <StateName>sample string 2</StateName>
    </SourceState>
    <TransitionId>1</TransitionId>
    <User>
      <UserId>2</UserId>
      <UserName>sample string 1</UserName>
    </User>
    <VersionNo>2</VersionNo>
  </HistoryTransition>
  <HistoryTransition>
    <Comment>sample string 3</Comment>
    <Date>2024-11-27T09:52:30.6765737-05:00</Date>
    <DestinationState>
      <IgnorePreviousPermissions>3</IgnorePreviousPermissions>
      <StateId>1</StateId>
      <StateName>sample string 2</StateName>
    </DestinationState>
    <SourceState>
      <IgnorePreviousPermissions>3</IgnorePreviousPermissions>
      <StateId>1</StateId>
      <StateName>sample string 2</StateName>
    </SourceState>
    <TransitionId>1</TransitionId>
    <User>
      <UserId>2</UserId>
      <UserName>sample string 1</UserName>
    </User>
    <VersionNo>2</VersionNo>
  </HistoryTransition>
</ArrayOfHistoryTransition>

```

See Also

GET

api/{vaultName}/files/{fileId}?version={version}

Description

Get file info

Gets information about the specified file.

Parameters

vaultName	(URI parameter) Vault name (required)	string
fileId	(URI parameter) File ID (required)	integer
version	(URI and Response parameter) Version (default value is 0)	integer
Id	(Response) File ID Member of ObjectInfo model; see Remarks	integer
Name	(Response) File name Member of ObjectInfo model; see Remarks	string
Size	(Response) File size Member of ObjectInfo model; see Remarks	integer
ModifiedDate	(Response) Modification date Member of ObjectInfo model; see Remarks	date
State	(Response) Workflow state Member of ObjectInfo model; see Remarks	string
StateId	(Response) State ID Member of ObjectInfo model; see Remarks	integer
ParentFolderId	(Response) Parent folder ID Member of ObjectInfo model; see Remarks	integer
Path	(Response) Folder path Member of ObjectInfo model; see Remarks	string
Type	(Response) ObjectType model; one of: Folder = 0 File = 1	ObjectType

	Bom = 3	
	Member of ObjectInfo model; see Remarks	
IsLocked	(Response) Whether the file is checked out Member of ObjectInfo model; see Remarks	integer
LockedBy	(Response) ID of user who checked out the file Member of ObjectInfo model; see Remarks	integer
IsShared	(Response) Whether the file is shared Member of ObjectInfo model; see Remarks	integer
IsToolbox	(Response) Whether the file is a toolbox item Member of ObjectInfo model; see Remarks	integer
IsDeleted	(Response) Whether the file is deleted Member of ObjectInfo model; see Remarks	integer

Response (application/json, text/json)

Sample Data

```
[
  {
    "Id": 1,
    "Name": "sample string 2",
    "Size": 3,
    "ModifiedDate": "2022-07-25T14:02:49.4464064-04:00",
    "Version": 5,
    "State": "sample string 6",
    "StateId": 7,
    "ParentFolderId": 8,
    "Path": "sample string 9",
    "Type": 0,
    "IsLocked": 10,
    "LockedBy": 11,
    "IsShared": 12,
    "IsToolbox": 13,
    "IsDeleted": 14
  },
  {
    "Id": 1,
    "Name": "sample string 2",
    "Size": 3,
    "ModifiedDate": "2022-07-25T14:02:49.4464064-04:00",
    "Version": 5,
    "State": "sample string 6",
    "StateId": 7,
    "ParentFolderId": 8,
    "Path": "sample string 9",
    "Type": 0,
    "IsLocked": 10,
    "LockedBy": 11,
    "IsShared": 12,
    "IsToolbox": 13,
    "IsDeleted": 14
  }
]
```

Response (application/xml, text/xml)

Sample Data

```
<ArrayOfObjectInfo xmlns:i="http://www.w3.org/2001/XMLSchema-instance"
xmlns="http://schemas.datacontract.org/2004/07/SWPDM.Models">
  <ObjectInfo>
    <Id>1</Id>
    <IsDeleted>14</IsDeleted>
    <IsLocked>10</IsLocked>
    <IsShared>12</IsShared>
    <IsToolbox>13</IsToolbox>
    <LockedBy>11</LockedBy>
    <ModifiedDate>2022-07-25T14:02:49.4464064-04:00</ModifiedDate>
    <Name>sample string 2</Name>
    <ParentFolderId>8</ParentFolderId>
    <Path>sample string 9</Path>
    <Size>3</Size>
    <State>sample string 6</State>
    <StateId>7</StateId>
    <Type>Folder</Type>
    <Version>5</Version>
  </ObjectInfo>
  <ObjectInfo>
    <Id>1</Id>
    <IsDeleted>14</IsDeleted>
    <IsLocked>10</IsLocked>
    <IsShared>12</IsShared>
    <IsToolbox>13</IsToolbox>
    <LockedBy>11</LockedBy>
    <ModifiedDate>2022-07-25T14:02:49.4464064-04:00</ModifiedDate>
    <Name>sample string 2</Name>
    <ParentFolderId>8</ParentFolderId>
    <Path>sample string 9</Path>
    <Size>3</Size>
    <State>sample string 6</State>
    <StateId>7</StateId>
    <Type>Folder</Type>
    <Version>5</Version>
  </ObjectInfo>
</ArrayOfObjectInfo>
```

Remarks

This operation should return one ObjectInfo object for each unique file ID in the request URI.

See Also

[File Resource Group](#) | [PDM Pro API Web Service](#)

GET **api/{vaultName}/files/{fileId}?version={version}&folderId={folderId}****Description**

Gets information about the specified file.

Parameters

vaultName	(Required URI Parameter) Vault name	string
fileId	(Required URI Parameter) File ID	integer
version	(URI Parameter) File version, default value is 0	integer
folderId	(URI Parameter) Folder ID, default value is 0	integer
Id	(Response) File ID (Member of ObjectInfo model)	integer
Name	(Response) File name (Member of ObjectInfo model)	string
Size	(Response) File size (Member of ObjectInfo model)	integer
ModifiedDate	(Response) Modified date (Member of ObjectInfo model)	date
State	(Response) File state (Member of ObjectInfo model)	string
StateId	(Response) File state ID (Member of ObjectInfo model)	integer
ParentFolderId	(Response) Parent folder ID (Member of ObjectInfo model)	integer
Path	(Response) Folder path (Member of ObjectInfo model)	string
Type	(Response) Object Type: Folder = 0 File = 1 Bom = 3 (Member of ObjectInfo model)	ObjectType
IsLocked	(Response) Whether file is locked (checked out) (Member of ObjectInfo model)	integer
LockedBy	(Response) ID of user who checked out the file (Member of ObjectInfo model)	integer
IsShared	(Response) Whether the file is shared (Member of ObjectInfo model)	integer
IsToolbox	(Response) 1 if a Toolbox item, 0 if not (Member of ObjectInfo model)	integer

IsDeleted

(Response) Whether file is deleted
(Member of ObjectInfo model)

integer

Response (application/json, text/json)

Sample Data

```
[
  {
    "Id": 1,
    "Name": "sample string 2",
    "Size": 3,
    "ModifiedDate": "2024-11-27T09:52:30.6345745-05:00",
    "Version": 5,
    "State": "sample string 6",
    "StateId": 7,
    "ParentFolderId": 8,
    "Path": "sample string 9",
    "Type": 0,
    "IsLocked": 10,
    "LockedBy": 11,
    "IsShared": 12,
    "IsToolbox": 13,
    "IsDeleted": 14
  },
  {
    "Id": 1,
    "Name": "sample string 2",
    "Size": 3,
    "ModifiedDate": "2024-11-27T09:52:30.6345745-05:00",
    "Version": 5,
    "State": "sample string 6",
    "StateId": 7,
    "ParentFolderId": 8,
    "Path": "sample string 9",
    "Type": 0,
    "IsLocked": 10,
    "LockedBy": 11,
    "IsShared": 12,
    "IsToolbox": 13,
    "IsDeleted": 14
  }
]
```

Response (application/xml, text/xml)

Sample Data

```
<ArrayOfObjectInfo xmlns:i="http://www.w3.org/2001/XMLSchema-instance"
xmlns="http://schemas.datacontract.org/2004/07/SWPDM.Models">
  <ObjectInfo>
    <Id>1</Id>
    <IsDeleted>14</IsDeleted>
    <IsLocked>10</IsLocked>
    <IsShared>12</IsShared>
    <IsToolbox>13</IsToolbox>
    <LockedBy>11</LockedBy>
    <ModifiedDate>2024-11-27T09:52:30.6345745-05:00</ModifiedDate>
    <Name>sample string 2</Name>
    <ParentFolderId>8</ParentFolderId>
    <Path>sample string 9</Path>
    <Size>3</Size>
    <State>sample string 6</State>
    <StateId>7</StateId>
    <Type>Folder</Type>
    <Version>5</Version>
  </ObjectInfo>
  <ObjectInfo>
    <Id>1</Id>
    <IsDeleted>14</IsDeleted>
    <IsLocked>10</IsLocked>
    <IsShared>12</IsShared>
    <IsToolbox>13</IsToolbox>
    <LockedBy>11</LockedBy>
    <ModifiedDate>2024-11-27T09:52:30.6345745-05:00</ModifiedDate>
    <Name>sample string 2</Name>
    <ParentFolderId>8</ParentFolderId>
    <Path>sample string 9</Path>
    <Size>3</Size>
    <State>sample string 6</State>
  </ObjectInfo>
</ArrayOfObjectInfo>
```

```
<StateId>7</StateId>
<Type>Folder</Type>
<Version>5</Version>
</ObjectInfo>
</ArrayOfObjectInfo>
```

See Also

[File Resource Group](#) | [PDM Pro API Web Service](#)

GET

api/{vaultName}/files/{fileId}/versions?folderId={folderId}

Description

GET: api/{VaultName}/files/{FileID}/versions Get file version info

Gets the specified file's version information.

Parameters

vaultName	(Required URI parameter) Vault name	string
fileId	(Required URI parameter) File ID	integer
folderId	(URI parameter) Folder ID (default value is 0)	integer
InfoType	(Response) Version information type: Version = 0 Revision = 1 Label = 2 Member of FileRevisionInfo model	Type
VersionNumber	(Response) Version; valid only if InfoType is 0 Member of FileRevisionInfo model	integer
Text	(Response) Label; valid only if InfoType is 2 Member of FileRevisionInfo model	string
Revision	(Response) Revision; valid only if InfoType is 1 Member of FileRevisionInfo model	string
FileSize	(Response) Size of file Member of FileRevisionInfo model	integer
VersionDate	(Response) Date of version, revision, or label Member of FileRevisionInfo model	date

Response (application/json, text/json)

Sample Data

```
[
  {
    "InfoType": 0,
    "VersionNumber": 1,
    "Text": "sample string 2",
    "Revision": "sample string 3",
    "FileSize": 4,
    "VersionDate": "2024-11-27T09:52:30.3220305-05:00"
  }
]
```

```

    },
    {
      "InfoType": 0,
      "VersionNumber": 1,
      "Text": "sample string 2",
      "Revision": "sample string 3",
      "FileSize": 4,
      "VersionDate": "2024-11-27T09:52:30.3220305-05:00"
    }
  ]

```

Response (application/xml, text/xml)

Sample Data

```

<ArrayOfFileRevisionInfo xmlns:i="http://www.w3.org/2001/XMLSchema-instance"
xmlns="http://schemas.datacontract.org/2004/07/SWPDM.Models">
  <FileRevisionInfo>
    <FileSize>4</FileSize>
    <InfoType>Version</InfoType>
    <Revision>sample string 3</Revision>
    <Text>sample string 2</Text>
    <VersionDate>2024-11-27T09:52:30.3220305-05:00</VersionDate>
    <VersionNumber>1</VersionNumber>
  </FileRevisionInfo>
  <FileRevisionInfo>
    <FileSize>4</FileSize>
    <InfoType>Version</InfoType>
    <Revision>sample string 3</Revision>
    <Text>sample string 2</Text>
    <VersionDate>2024-11-27T09:52:30.3220305-05:00</VersionDate>
    <VersionNumber>1</VersionNumber>
  </FileRevisionInfo>
</ArrayOfFileRevisionInfo>

```

See Also

[File Resource Group | PDM Pro API Web Service](#)

GET

api/{vaultName}/files/{fileId}/{folderId}/bominfo

Description

GET: api/{VaultName}/files/{FileID}/bominfo Get file BOM infoGets the BOM information for the specified file.

Parameters

vaultName	(Required URI parameter) Vault name	string
fileId	(Required URI parameter) File ID	integer
folderId	(URI parameter) Folder ID (default value is 0)	integer
NamedBOM	(Response) A NamedBOMInfoList; each NamedBOMInfoList consists of: BOMList (array of NamedBOMInfo objects; each NamedBOMInfo consists of: Folder (Folder object that consists of FolderId (integer) and FolderPath (string)) Config (Config object that consists of ConfigurationName (string) and ConfigurationId (integer)) BOMId (integer) BOMName (string) VersionNo (integer) SavedBOM (boolean) Member of BOMInfo model	NamedBOMInfoList
ComputedBOM	(Response) A ComputedBOMInfoList; each ComputedBOMInfoList consists of: BOMList (array of ComputedBOMInfo objects; each ComputedBOMInfo consists of: Folder (Folder object that consists of FolderId (integer) and FolderPath (string)) Configs (Array of Config objects, each Config object consists of: ConfigurationName (string) ConfigurationId (integer) BOMId (integer) BOMName (string) Member of BOMInfo model	ComputedBOMInfoList
WeldmentCutlistBOM	(Response) A ComputedBOMInfoList; each ComputedBOMInfoList consists of: BOMList (array of ComputedBOMInfo objects; each ComputedBOMInfo consists of: Folder (Folder object that consists of FolderId (integer) and FolderPath (string)) Configs (Array of Config objects, each Config object consists of: ConfigurationName (string) ConfigurationId (integer) BOMId (integer) BOMName (string) Member of BOMInfo model	ComputedBOMInfoList
WeldmentBOM	(Response) A ComputedBOMInfoList; each ComputedBOMInfoList consists of: BOMList (array of ComputedBOMInfo objects; each ComputedBOMInfo consists of: Folder (Folder object that consists of FolderId (integer) and FolderPath (string)) Configs (Array of Config objects, each Config object consists of: ConfigurationName (string) ConfigurationId (integer) BOMId (integer) BOMName (string)	ComputedBOMInfoList

Response (application/json, text/json)

Sample Data

```
{
  "NamedBOM": {
    "BOMList": [
      {
        "Folder": {
          "FolderId": 1,
          "FolderPath": "sample string 2"
        },
        "Config": {
          "ConfigurationName": "sample string 1",
          "ConfigurationId": 2
        },
        "BOMId": 1,
        "BOMName": "sample string 2",
        "VersionNo": 3,
        "SavedBOM": true
      },
      {
        "Folder": {
          "FolderId": 1,
          "FolderPath": "sample string 2"
        },
        "Config": {
          "ConfigurationName": "sample string 1",
          "ConfigurationId": 2
        },
        "BOMId": 1,
        "BOMName": "sample string 2",
        "VersionNo": 3,
        "SavedBOM": true
      }
    ]
  },
  "ComputedBOM": {
    "BOMList": [
      {
        "Folder": {
          "FolderId": 1,
          "FolderPath": "sample string 2"
        },
        "Configs": [
          {
            "ConfigurationName": "sample string 1",
            "ConfigurationId": 2
          },
          {
            "ConfigurationName": "sample string 1",
            "ConfigurationId": 2
          }
        ],
        "BOMId": 1,
        "BOMName": "sample string 2"
      },
      {
        "Folder": {
          "FolderId": 1,
          "FolderPath": "sample string 2"
        },
        "Configs": [
          {
            "ConfigurationName": "sample string 1",
            "ConfigurationId": 2
          },
          {
            "ConfigurationName": "sample string 1",
            "ConfigurationId": 2
          }
        ],
        "BOMId": 1,
        "BOMName": "sample string 2"
      }
    ]
  },
  "WeldmentCutlistBOM": {
    "BOMList": [
      {
        "Folder": {

```

```

        "FolderId": 1,
        "FolderPath": "sample string 2"
    },
    "Configs": [
        {
            "ConfigurationName": "sample string 1",
            "ConfigurationId": 2
        },
        {
            "ConfigurationName": "sample string 1",
            "ConfigurationId": 2
        }
    ],
    "BOMId": 1,
    "BOMName": "sample string 2"
},
{
    "Folder": {
        "FolderId": 1,
        "FolderPath": "sample string 2"
    },
    "Configs": [
        {
            "ConfigurationName": "sample string 1",
            "ConfigurationId": 2
        },
        {
            "ConfigurationName": "sample string 1",
            "ConfigurationId": 2
        }
    ],
    "BOMId": 1,
    "BOMName": "sample string 2"
}
],
},
"WeldmentBOM": {
    "BOMList": [
        {
            "Folder": {
                "FolderId": 1,
                "FolderPath": "sample string 2"
            },
            "Configs": [
                {
                    "ConfigurationName": "sample string 1",
                    "ConfigurationId": 2
                },
                {
                    "ConfigurationName": "sample string 1",
                    "ConfigurationId": 2
                }
            ],
            "BOMId": 1,
            "BOMName": "sample string 2"
        },
        {
            "Folder": {
                "FolderId": 1,
                "FolderPath": "sample string 2"
            },
            "Configs": [
                {
                    "ConfigurationName": "sample string 1",
                    "ConfigurationId": 2
                },
                {
                    "ConfigurationName": "sample string 1",
                    "ConfigurationId": 2
                }
            ],
            "BOMId": 1,
            "BOMName": "sample string 2"
        }
    ]
}
}
}

```

Response (application/xml, text/xml)

Sample Data

```

<BOMInfo xmlns:i="http://www.w3.org/2001/XMLSchema-instance" xmlns="http://schemas.datacontract.org/2004/07/SWPDM.Models">
  <ComputedBOM>

```

```

<BOMList>
  <ComputedBOMInfo>
    <BOMId>1</BOMId>
    <BOMName>sample string 2</BOMName>
    <Configs>
      <Config>
        <ConfigurationId>2</ConfigurationId>
        <ConfigurationName>sample string 1</ConfigurationName>
      </Config>
      <Config>
        <ConfigurationId>2</ConfigurationId>
        <ConfigurationName>sample string 1</ConfigurationName>
      </Config>
    </Configs>
    <Folder>
      <FolderId>1</FolderId>
      <FolderPath>sample string 2</FolderPath>
    </Folder>
  </ComputedBOMInfo>
  <ComputedBOMInfo>
    <BOMId>1</BOMId>
    <BOMName>sample string 2</BOMName>
    <Configs>
      <Config>
        <ConfigurationId>2</ConfigurationId>
        <ConfigurationName>sample string 1</ConfigurationName>
      </Config>
      <Config>
        <ConfigurationId>2</ConfigurationId>
        <ConfigurationName>sample string 1</ConfigurationName>
      </Config>
    </Configs>
    <Folder>
      <FolderId>1</FolderId>
      <FolderPath>sample string 2</FolderPath>
    </Folder>
  </ComputedBOMInfo>
</BOMList>
</ComputedBOM>
<NamedBOM>
  <BOMList>
    <NamedBOMInfo>
      <BOMId>1</BOMId>
      <BOMName>sample string 2</BOMName>
      <Config>
        <ConfigurationId>2</ConfigurationId>
        <ConfigurationName>sample string 1</ConfigurationName>
      </Config>
      <Folder>
        <FolderId>1</FolderId>
        <FolderPath>sample string 2</FolderPath>
      </Folder>
      <SavedBOM>true</SavedBOM>
      <VersionNo>3</VersionNo>
    </NamedBOMInfo>
    <NamedBOMInfo>
      <BOMId>1</BOMId>
      <BOMName>sample string 2</BOMName>
      <Config>
        <ConfigurationId>2</ConfigurationId>
        <ConfigurationName>sample string 1</ConfigurationName>
      </Config>
      <Folder>
        <FolderId>1</FolderId>
        <FolderPath>sample string 2</FolderPath>
      </Folder>
      <SavedBOM>true</SavedBOM>
      <VersionNo>3</VersionNo>
    </NamedBOMInfo>
  </BOMList>
</NamedBOM>
<WeldmentBOM>
  <BOMList>
    <ComputedBOMInfo>
      <BOMId>1</BOMId>
      <BOMName>sample string 2</BOMName>
      <Configs>
        <Config>
          <ConfigurationId>2</ConfigurationId>
          <ConfigurationName>sample string 1</ConfigurationName>
        </Config>
        <Config>
          <ConfigurationId>2</ConfigurationId>
          <ConfigurationName>sample string 1</ConfigurationName>
        </Config>
      </Configs>
    </ComputedBOMInfo>
  </BOMList>
</WeldmentBOM>

```

```

    </Configs>
    <Folder>
      <FolderId>1</FolderId>
      <FolderPath>sample string 2</FolderPath>
    </Folder>
  </ComputedBOMInfo>
<ComputedBOMInfo>
  <BOMId>1</BOMId>
  <BOMName>sample string 2</BOMName>
  <Configs>
    <Config>
      <ConfigurationId>2</ConfigurationId>
      <ConfigurationName>sample string 1</ConfigurationName>
    </Config>
    <Config>
      <ConfigurationId>2</ConfigurationId>
      <ConfigurationName>sample string 1</ConfigurationName>
    </Config>
  </Configs>
  <Folder>
    <FolderId>1</FolderId>
    <FolderPath>sample string 2</FolderPath>
  </Folder>
</ComputedBOMInfo>
</BOMList>
</WeldmentBOM>
<WeldmentCutlistBOM>
  <BOMList>
    <ComputedBOMInfo>
      <BOMId>1</BOMId>
      <BOMName>sample string 2</BOMName>
      <Configs>
        <Config>
          <ConfigurationId>2</ConfigurationId>
          <ConfigurationName>sample string 1</ConfigurationName>
        </Config>
        <Config>
          <ConfigurationId>2</ConfigurationId>
          <ConfigurationName>sample string 1</ConfigurationName>
        </Config>
      </Configs>
    </Folder>
    <Folder>
      <FolderId>1</FolderId>
      <FolderPath>sample string 2</FolderPath>
    </Folder>
  </ComputedBOMInfo>
<ComputedBOMInfo>
  <BOMId>1</BOMId>
  <BOMName>sample string 2</BOMName>
  <Configs>
    <Config>
      <ConfigurationId>2</ConfigurationId>
      <ConfigurationName>sample string 1</ConfigurationName>
    </Config>
    <Config>
      <ConfigurationId>2</ConfigurationId>
      <ConfigurationName>sample string 1</ConfigurationName>
    </Config>
  </Configs>
  <Folder>
    <FolderId>1</FolderId>
    <FolderPath>sample string 2</FolderPath>
  </Folder>
</ComputedBOMInfo>
</BOMList>
</WeldmentCutlistBOM>
</BOMInfo>

```

See Also

[File Resource Group](#) | [PDM Pro API Web Service](#)

POST

api/{vaultName}/files/{fileId}/{folderId}/datacard

Description

Saves the data card for the specified file

Parameters

vaultName	(URI parameter) Name of vault	string
fileId	(URI parameter) File ID	integer
folderId	(URI parameter) Folder ID	integer
Models	(Body parameter) (VariableInfo_DataCard: ReadOnly: boolean Multiline: boolean VarId: integer VarName: string VarValue: string VarType: VarTypeNone = 0 VarTypeText = 1 VarTypeInt = 2 VarTypeFloat = 3 VarTypeBool = 4 VarTypeDate = 5 Mandatory: boolean VersionFree: boolean) (Member of ConfigInfo_DataCard)	Collection of VariableInfo_DataCard
ConfigurationName	(Body parameter) Name of configuration (Member of ConfigInfo_DataCard)	string
ConfigurationId	(Body parameter) Configuration ID (Member of ConfigInfo_DataCard)	integer

Request (application/json, text/json)

Sample Data

```
[
  {
    "Models": [
      {
        "ReadOnly": true,
        "Multiline": true,
        "VarId": 3,
        "VarName": "sample string 4",
        "VarValue": "sample string 5",
        "VarType": 0,
        "Mandatory": true,
        "VersionFree": true
      },
      {
        "ReadOnly": true,
        "Multiline": true,
        "VarId": 3,
```

```

        "VarName": "sample string 4",
        "VarValue": "sample string 5",
        "VarType": 0,
        "Mandatory": true,
        "VersionFree": true
    }
},
"ConfigurationName": "sample string 1",
"ConfigurationId": 2
},
{
    "Models": [
        {
            "ReadOnly": true,
            "Multiline": true,
            "VarId": 3,
            "VarName": "sample string 4",
            "VarValue": "sample string 5",
            "VarType": 0,
            "Mandatory": true,
            "VersionFree": true
        },
        {
            "ReadOnly": true,
            "Multiline": true,
            "VarId": 3,
            "VarName": "sample string 4",
            "VarValue": "sample string 5",
            "VarType": 0,
            "Mandatory": true,
            "VersionFree": true
        }
    ],
    "ConfigurationName": "sample string 1",
    "ConfigurationId": 2
}
}
]

```

Request (application/xml, text/xml)

Sample Data

```

<ArrayOfConfigInfo_DataCard xmlns:i="http://www.w3.org/2001/XMLSchema-instance"
xmlns="http://schemas.datacontract.org/2004/07/SWPDM.Models">
  <ConfigInfo_DataCard>
    <ConfigurationId>2</ConfigurationId>
    <ConfigurationName>sample string 1</ConfigurationName>
    <Models>
      <VariableInfo_DataCard>
        <Mandatory>true</Mandatory>
        <VarId>3</VarId>
        <VarName>sample string 4</VarName>
        <VarType>VarTypeNone</VarType>
        <VarValue>sample string 5</VarValue>
        <VersionFree>true</VersionFree>
        <Multiline>true</Multiline>
        <ReadOnly>true</ReadOnly>
      </VariableInfo_DataCard>
      <VariableInfo_DataCard>
        <Mandatory>true</Mandatory>
        <VarId>3</VarId>
        <VarName>sample string 4</VarName>
        <VarType>VarTypeNone</VarType>
        <VarValue>sample string 5</VarValue>
        <VersionFree>true</VersionFree>
        <Multiline>true</Multiline>
        <ReadOnly>true</ReadOnly>
      </VariableInfo_DataCard>
    </Models>
  </ConfigInfo_DataCard>
</ArrayOfConfigInfo_DataCard>
<ConfigInfo_DataCard>
  <ConfigurationId>2</ConfigurationId>
  <ConfigurationName>sample string 1</ConfigurationName>
  <Models>
    <VariableInfo_DataCard>
      <Mandatory>true</Mandatory>
      <VarId>3</VarId>
      <VarName>sample string 4</VarName>
      <VarType>VarTypeNone</VarType>
      <VarValue>sample string 5</VarValue>
      <VersionFree>true</VersionFree>
      <Multiline>true</Multiline>
      <ReadOnly>true</ReadOnly>
    </VariableInfo_DataCard>
  </Models>
</ConfigInfo_DataCard>

```

```
<VariableInfo_DataCard>
  <Mandatory>true</Mandatory>
  <VarId>3</VarId>
  <VarName>sample string 4</VarName>
  <VarType>VarTypeNone</VarType>
  <VarValue>sample string 5</VarValue>
  <VersionFree>true</VersionFree>
  <Multiline>true</Multiline>
  <ReadOnly>true</ReadOnly>
</VariableInfo_DataCard>
</Models>
</ConfigInfo_DataCard>
</ArrayOfConfigInfo_DataCard>
```

Request (application/x-www-form-urlencoded)

Response (application/json, text/json)

Sample Data

true

Response (application/xml, text/xml)

Sample Data

```
<boolean xmlns="http://schemas.microsoft.com/2003/10/Serialization/">true</boolean>
```

Example

[Modify File Datacards.postman_collection.json](#)

See Also

[Data Card Resource Group](#) | [PDM Pro API Web Service](#)

DELETE**api/{vaultName}/files/{fileId}/{folderId}?destroy={destroy}****Description**

Deletes the specified file.

Parameters

vaultName	(Required URI parameter) Vault name	string
fileId	(Required URI parameter) File ID	integer
folderId	(URI parameter) Folder ID; default is 0	integer
destroy	(URI parameter) True to destroy, false to not	boolean
Id	(Response parameter) File type: Folder = 0 File = 1 Bom = 3 (Member of ObjectInfoShort Model)	integer
Name	(Response parameter) File name	string
Type	(Response parameter) File type Folder = 0 File = 1 Bom = 3	ObjectType
Status	(Response parameter) Status code: Success = 0 Failure = 1 (Member of ObjectInfoShort Model)	StatusOperation
Warning	(Response parameter) Warning: Message: string IsBlocking: boolean IsError: boolean (Member of ObjectInfoShort Model)	BaseWarningModel

Response (application/json, text/json)**Sample Data**

```
{
  "Id": 1,
  "Name": "sample string 2",
  "Type": 0,
  "Status": 0,
  "Warning": null
}
```

Response (application/xml, text/xml)**Sample Data**

```
<ObjectInfoShort xmlns:i="http://www.w3.org/2001/XMLSchema-instance"
xmlns="http://schemas.datacontract.org/2004/07/SWPDM.Models">
  <Id>1</Id>
  <Name>sample string 2</Name>
  <Status>Success</Status>
```

```
<Type>Folder</Type>
<Warning i:nil="true" />
</ObjectInfoShort>
```

See Also

[File Resource Group](#) | [PDM Pro API Web Service](#)

GET

api/{vaultName}/files/{fileId}/{folderId}/history

Description

Gets a specified file's history.

Parameters

vaultName	(Required URI Parameter) Vault name	string
fileId	(Required URI Parameter) File ID	integer
folderId	(URI Parameter) Folder ID, default is 0	integer
DocumentId	(Response) Document ID (Member of HistoryBase model)	integer
Version	(Response) File version (Member of HistoryBase model)	integer
User	(Response) UserInfo: UserName: string UserId: integer (Member of HistoryBase model)	UserInfo
Date	(Response) Date (Member of HistoryBase model)	date
HistoryType	(Response) HistoryType: None = 0 Share = 1 Rename = 2 Move = 3 Rollback = 4 Delete = 5 Version = 7 Label = 9 Transition = 10 Revision = 11 ColdStore = 12 VerFreeVar = 18 PendingState = 20 ParallelState = 21 VersionOverwrite = 22 Branch = 23 DocUndoLock = 24 DocBranchMerge = 25 DocLock = 26 DocUndoLock2 = 27 (Member of HistoryBase model)	HistoryType
Event	(Response) Event (Member of HistoryBase model)	string

Comment	(Response) Comment (Member of HistoryBase model)	string
---------	---	--------

Response (application/json, text/json, application/xml, text/xml)

See Also

[File Resource Group](#) | [PDM Pro API Web Service](#)

GET

api/{vaultName}/files/{fileId}/{folderId}/moves

Description

Gets the history of moves for the specified file.

Parameters

vaultName	(Required URI Parameter) Vault name	string
fileId	(Required URI Parameter) File ID	integer
folderId	(URI Parameter) Folder ID, default is 0	integer
Source	(Response) Folder: FolderId: integer FolderPath: string (Member of HistoryMove)	Folder
Destination	(Response) Destination Folder: FolderId: integer FolderPath: string (Member of HistoryMove)	Folder
Date	(Response) Date (Member of HistoryMove)	date

Response (application/json, text/json)

Sample Data

```
[
  {
    "Source": {
      "FolderId": 1,
      "FolderPath": "sample string 2"
    },
    "Destination": {
      "FolderId": 1,
      "FolderPath": "sample string 2"
    },
    "Date": "2024-11-27T09:52:30.7036097-05:00"
  },
  {
    "Source": {
      "FolderId": 1,
      "FolderPath": "sample string 2"
    },
    "Destination": {
      "FolderId": 1,
      "FolderPath": "sample string 2"
    },
    "Date": "2024-11-27T09:52:30.7036097-05:00"
  }
]
```

Response (application/xml, text/xml)

Sample Data

```
<ArrayOfHistoryMove xmlns:i="http://www.w3.org/2001/XMLSchema-instance"
xmlns="http://schemas.datacontract.org/2004/07/SWPDM.Models">
  <HistoryMove>
    <Date>2024-11-27T09:52:30.7036097-05:00</Date>
    <Destination>
      <FolderId>1</FolderId>
```

```
<FolderPath>sample string 2</FolderPath>
</Destination>
<Source>
  <FolderId>1</FolderId>
  <FolderPath>sample string 2</FolderPath>
</Source>
</HistoryMove>
<HistoryMove>
  <Date>2024-11-27T09:52:30.7036097-05:00</Date>
  <Destination>
    <FolderId>1</FolderId>
    <FolderPath>sample string 2</FolderPath>
  </Destination>
  <Source>
    <FolderId>1</FolderId>
    <FolderPath>sample string 2</FolderPath>
  </Source>
</HistoryMove>
</ArrayOfHistoryMove>
```

See Also

[File Resource Group](#) | [PDM Pro API Web Service](#)

GET

api/{vaultName}/files/{fileId}/{folderId}/versions

Description

GET: api/{VaultName}/files/{FileID}/versions Get file version info
Gets the specified file's version information.

Parameters

vaultName	(Required URI parameter) Vault name	string
fileId	(Required URI parameter) File ID	integer
folderId	(URI parameter) Folder ID (default value is 0)	integer
InfoType	(Response) Version information type: Version = 0 Revision = 1 Label = 2 Member of FileRevisionInfo model	Type
VersionNumber	(Response) Version; valid only if InfoType is 0 Member of FileRevisionInfo model	integer
Text	(Response) Label; valid only if InfoType is 2 Member of FileRevisionInfo model	string
Revision	(Response) Revision; valid only if InfoType is 1 Member of FileRevisionInfo model	string
FileSize	(Response) Size of file Member of FileRevisionInfo model	integer
VersionDate	(Response) Date of version, revision, or label Member of FileRevisionInfo model	date

Response (application/json, text/json)

Sample Data

```
[
  {
    "InfoType": 0,
    "VersionNumber": 1,
    "Text": "sample string 2",
    "Revision": "sample string 3",
    "FileSize": 4,
    "VersionDate": "2024-11-27T09:52:30.3340279-05:00"
  },
  {
    "InfoType": 0,
    "VersionNumber": 1,
    "Text": "sample string 2",
    "Revision": "sample string 3",
    "FileSize": 4,
    "VersionDate": "2024-11-27T09:52:30.3340279-05:00"
  }
]
```

```
}  
]
```

Response (application/xml, text/xml)

Sample Data

```
<ArrayOfFileRevisionInfo xmlns:i="http://www.w3.org/2001/XMLSchema-instance"  
xmlns="http://schemas.datacontract.org/2004/07/SWPDM.Models">  
  <FileRevisionInfo>  
    <FileSize>4</FileSize>  
    <InfoType>Version</InfoType>  
    <Revision>sample string 3</Revision>  
    <Text>sample string 2</Text>  
    <VersionDate>2024-11-27T09:52:30.3340279-05:00</VersionDate>  
    <VersionNumber>1</VersionNumber>  
  </FileRevisionInfo>  
  <FileRevisionInfo>  
    <FileSize>4</FileSize>  
    <InfoType>Version</InfoType>  
    <Revision>sample string 3</Revision>  
    <Text>sample string 2</Text>  
    <VersionDate>2024-11-27T09:52:30.3340279-05:00</VersionDate>  
    <VersionNumber>1</VersionNumber>  
  </FileRevisionInfo>  
</ArrayOfFileRevisionInfo>
```

See Also

[File Resource Group](#) | [PDM Pro API Web Service](#)

GET

api/{vaultName}/files/{fileId}/{version}

Description

Get file info

Gets information about the specified file.

Parameters

vaultName	(URI parameter) Vault name (required)	string
fileId	(URI and Response parameter) File ID (required)	integer
version	(URI parameter) Version (default value is 0)	integer
Id	(Response) File ID Member of ObjectInfo model; see Remarks	integer
Name	(Response) File name Member of ObjectInfo model; see Remarks	string
Size	(Response) File size Member of ObjectInfo model; see Remarks	integer
ModifiedDate	(Response) Modification date Member of ObjectInfo model; see Remarks	date
State	(Response) Workflow state Member of ObjectInfo model; see Remarks	string
StateId	(Response) State ID Member of ObjectInfo model; see Remarks	integer
ParentFolderId	(Response) Parent folder ID Member of ObjectInfo model; see Remarks	integer
Path	(Response) Folder path Member of ObjectInfo model; see Remarks	string
Type	(Response) ObjectType model; one of: Folder = 0 File = 1 Bom = 3 Member of ObjectInfo model; see Remarks	ObjectType
IsLocked	(Response) Whether the file is checked out	integer

	Member of ObjectInfo model; see Remarks	
LockedBy	(Response) ID of user who checked out the file Member of ObjectInfo model; see Remarks	integer
IsShared	(Response) Whether the file is shared Member of ObjectInfo model; see Remarks	integer
IsToolbox	(Response) Whether the file is a toolbox item Member of ObjectInfo model; see Remarks	integer
IsDeleted	(Response) Whether the file is deleted Member of ObjectInfo model; see Remarks	integer

Response (application/json, text/json)

Sample Data

```
[
  {
    "Id": 1,
    "Name": "sample string 2",
    "Size": 3,
    "ModifiedDate": "2022-07-25T14:02:49.4654054-04:00",
    "Version": 5,
    "State": "sample string 6",
    "StateId": 7,
    "ParentFolderId": 8,
    "Path": "sample string 9",
    "Type": 0,
    "IsLocked": 10,
    "LockedBy": 11,
    "IsShared": 12,
    "IsToolbox": 13,
    "IsDeleted": 14
  },
  {
    "Id": 1,
    "Name": "sample string 2",
    "Size": 3,
    "ModifiedDate": "2022-07-25T14:02:49.4654054-04:00",
    "Version": 5,
    "State": "sample string 6",
    "StateId": 7,
    "ParentFolderId": 8,
    "Path": "sample string 9",
    "Type": 0,
    "IsLocked": 10,
    "LockedBy": 11,
    "IsShared": 12,
    "IsToolbox": 13,
    "IsDeleted": 14
  }
]
```

Response (application/xml, text/xml)

Sample Data

```
<ArrayOfObjectInfo xmlns:i="http://www.w3.org/2001/XMLSchema-instance"
xmlns="http://schemas.datacontract.org/2004/07/SWPDM.Models">
  <ObjectInfo>
    <Id>1</Id>
```

```
<IsDeleted>14</IsDeleted>
<IsLocked>10</IsLocked>
<IsShared>12</IsShared>
<IsToolbox>13</IsToolbox>
<LockedBy>11</LockedBy>
<ModifiedDate>2022-07-25T14:02:49.4654054-04:00</ModifiedDate>
<Name>sample string 2</Name>
<ParentFolderId>8</ParentFolderId>
<Path>sample string 9</Path>
<Size>3</Size>
<State>sample string 6</State>
<StateId>7</StateId>
<Type>Folder</Type>
<Version>5</Version>
</ObjectInfo>
<ObjectInfo>
  <Id>1</Id>
  <IsDeleted>14</IsDeleted>
  <IsLocked>10</IsLocked>
  <IsShared>12</IsShared>
  <IsToolbox>13</IsToolbox>
  <LockedBy>11</LockedBy>
  <ModifiedDate>2022-07-25T14:02:49.4654054-04:00</ModifiedDate>
  <Name>sample string 2</Name>
  <ParentFolderId>8</ParentFolderId>
  <Path>sample string 9</Path>
  <Size>3</Size>
  <State>sample string 6</State>
  <StateId>7</StateId>
  <Type>Folder</Type>
  <Version>5</Version>
</ObjectInfo>
</ArrayOfObjectInfo>
```

Remarks

This operation should return one ObjectInfo object for each unique file ID in the request URI.

See Also

[File Resource Group](#) | [PDM Pro API Web Service](#)

GET

api/{vaultName}/files/{fileId}/{version}/ActiveConfig

Description

Get active configuration

Gets the active configuration of the specified file.

Parameters

vaultName	(URI parameter) Vault name (required)	string
fileId	(URI parameter) File ID (required)	integer
version	(URI parameter) Version (required)	integer
ConfigurationName	(Response) Active configuration name	string
	Member of Config model	
ConfigurationId	(Response) Active configuration ID	integer
	Member of Config model	

Response (application/json, text/json)

Sample Data

```
{
  "ConfigurationName": "sample string 1",
  "ConfigurationId": 2
}
```

Response (application/xml, text/xml)

Sample Data

```
<Config xmlns:i="http://www.w3.org/2001/XMLSchema-instance" xmlns="http://schemas.datacontract.org/2004/07/SWPDM.Models">
  <ConfigurationId>2</ConfigurationId>
  <ConfigurationName>sample string 1</ConfigurationName>
</Config>
```

See Also

GET

api/{vaultName}/files/{fileId}/{version}/ActiveConfig?folderId={folderId}

Description

Gets the active configuration for the specified file.

Parameters

vaultName	(Required URI Parameter) Vault name	string
fileId	(Required URI Parameter) File ID	integer
version	(Required URI Parameter) File version	integer
folderId	(URI Parameter) Folder ID, default is 0	integer
ConfigurationName	(Response) Name of active configuration (Member of Config Model)	string
ConfigurationId	(Response) ID of active configuration (Member of Config Model)	integer

Response (application/json, text/json)

Sample Data

```
{
  "ConfigurationName": "sample string 1",
  "ConfigurationId": 2
}
```

Response (application/xml, text/xml)

Sample Data

```
<Config xmlns:i="http://www.w3.org/2001/XMLSchema-instance" xmlns="http://schemas.datacontract.org/2004/07/SWPDM.Models">
  <ConfigurationId>2</ConfigurationId>
  <ConfigurationName>sample string 1</ConfigurationName>
</Config>
```

See Also

GET

api/{vaultName}/files/{fileId}/{version}/allreferences?configId={configId}&folderId={folderId}&includeSubParents={includeSubParents}

Description

GET: api/{VaultName}/files/{FileID}/{Version}/allreferences Get all file references

Gets the reference tree of the specified file.

Parameters

vaultName	(Required URI parameter) Vault name	string
fileId	(Required URI parameter) File ID	integer
version	(Required URI parameter) Version	integer
configId	(URI parameter) Config ID (default value is -1)	integer
folderId	(URI parameter) Folder ID (default value is 0)	integer
includeSubParents	(URI parameter) Whether to include sub parents (default value is false)	boolean
File	(Response) A FileInfo object that consists of: File object that consists of: FileId (integer) File Name (string) Folder object that consists of: FolderId (integer) FolderPath Version (integer) Config object that consists of : ConfigurationName (string) ConfigurationId (integer) Member of FileRef model	FileInfo
IsCyclic	(Response) Whether the file reference is self-referential Member of FileRef model	boolean
IsToolbox	(Response) Whether the file reference is a toolbox item Member of FileRef model	integer
ObjectType	(Response) PweObjectType model; one of: ObjType_NoObject = 0 ObjType_File = 1 ObjType_InternalComponent = 2 ObjType_SavedBOM = 3 ObjType_Item = 4 ObjType_CutListItem = 5	PweObjectType

Member of FileRef model		
Warnings	(Response) An array of BaseWarningModels; each BaseWarningModel consists of: - Message (string) - IsBlocking (boolean) - IsError (boolean) Member of FileRef model	Collection of BaseWarningModel
References	(Response) The file reference's references; an array of FileRefs; each FileRef consists of: - File (FileInfo) - IsCyclic (boolean) - IsToolbox (integer) - ObjectType (PweObjectType) - Warnings (Array of BaseWarningModels) - References (Array of FileRefs) Member of FileRef model	Collection of FileRef

Response (application/json)

Response (text/json)

Response (application/xml)

Response (text/xml)

Remarks

This operation can return multiple FileRef objects.

See Also

[File Resource Group](#) | [PDM Pro API Web Service](#)

GET

api/{vaultName}/files/{fileId}/{version}/configurations

Description

Get file configurations

Gets the configurations of the specified file.

Parameters

vaultName	(URI parameter) Vault name (required)	string
fileId	(URI parameter) File ID (required)	integer
version	(URI parameter) Version (required)	integer
ConfigurationName	(Response) Configuration name	string
	Member of Config model	
ConfigurationId	(Response) Configuration ID	integer
	Member of Config model	

Response (application/json, text/json)

Sample Data

```
[
  {
    "ConfigurationName": "sample string 1",
    "ConfigurationId": 2
  },
  {
    "ConfigurationName": "sample string 1",
    "ConfigurationId": 2
  }
]
```

Response (application/xml, text/xml)

Sample Data

```
<ArrayOfConfig xmlns:i="http://www.w3.org/2001/XMLSchema-instance"
xmlns="http://schemas.datacontract.org/2004/07/SWPDM.Models">
  <Config>
    <ConfigurationId>2</ConfigurationId>
    <ConfigurationName>sample string 1</ConfigurationName>
  </Config>
  <Config>
    <ConfigurationId>2</ConfigurationId>
    <ConfigurationName>sample string 1</ConfigurationName>
  </Config>
</ArrayOfConfig>
```

Remarks

This operation returns an array of Config objects.

See Also

GET

api/{vaultName}/files/{fileId}/{version}/configurations?folderId={folderId}

Description

Gets the configurations for the specified file.

Parameters

vaultName	(Required URI Parameter) Vault name	string
fileId	(Required URI Parameter) File ID	integer
version	(Required URI Parameter) File version	integer
folderId	(URI Parameter) Folder ID, default is 0	integer
ConfigurationName	(Response) Configuration name (Member of Config Model)	string
ConfigurationId	(Response) Configuration ID (Member of Config Model)	integer

Response (application/json, text/json)

Sample Data

```
[
  {
    "ConfigurationName": "sample string 1",
    "ConfigurationId": 2
  },
  {
    "ConfigurationName": "sample string 1",
    "ConfigurationId": 2
  }
]
```

Response (application/xml, text/xml)

Sample Data

```
<ArrayOfConfig xmlns:i="http://www.w3.org/2001/XMLSchema-instance"
xmlns="http://schemas.datacontract.org/2004/07/SWPDM.Models">
  <Config>
    <ConfigurationId>2</ConfigurationId>
    <ConfigurationName>sample string 1</ConfigurationName>
  </Config>
  <Config>
    <ConfigurationId>2</ConfigurationId>
    <ConfigurationName>sample string 1</ConfigurationName>
  </Config>
</ArrayOfConfig>
```

See Also

GET `api/{vaultName}/files/{fileId}/{version}/datacard?folderId={folderId}`

Description

GET: `api/{VaultName}/files/{FileID}/{Version}/datacard` Get file data card

Gets the data card for the specified file, file version, and vault.

Parameters

vaultName	(URI parameter) Vault name (required)	string
fileId	(URI parameter) File ID (required)	integer
version	(URI parameter) File version (required)	integer
folderId	(URI parameter) Folder ID (default is 0)	integer
VariablesWithWriteAllConfigs	(Response) Array of IDs of variables with write-all configurations Member of DataCard model	Collection of integer
ConfigVarInfo	(Response) Array of ConfigInfo_DataCards; each ConfigInfo_DataCard consists of: Models (Array of VariableInfo_DataCards; each VariableInfo_DataCard consists of: ReadOnly (boolean) Multiline (boolean) VarId (integer) VarName (string) VarValue (string) VarType (one of: VarTypeNone = 0 VarTypeText = 1 VarTypeInt = 2 VarTypeFloat = 3 VarTypeBool = 4 VarTypeDate = 5) Mandatory (boolean) VersionFree (boolean)) ConfigurationName (string) Configuration Id (integer) Member of DataCard model	Collection of ConfigInfo_DataCard
CardVariableInfo	(Response) Array of VariableExtrInfos; each VariableExtrInfo consists of: Variable Id (integer) VariableValueOptions (array of optional string values) Member of DataCard model	Collection of VariableExtrInfo

Response (application/json, text/json)

Sample Data

```
{
  "VariablesWriteAllConfigs": [
    1,
    2
  ],
  "ConfigVarInfo": [
    {
      "Models": [
        {
          "ReadOnly": true,
          "Multiline": true,
          "VarId": 3,
          "VarName": "sample string 4",
          "VarValue": "sample string 5",
          "VarType": 0,
          "Mandatory": true,
          "VersionFree": true
        },
        {
          "ReadOnly": true,
          "Multiline": true,
          "VarId": 3,
          "VarName": "sample string 4",
          "VarValue": "sample string 5",
          "VarType": 0,
          "Mandatory": true,
          "VersionFree": true
        }
      ],
      "ConfigurationName": "sample string 1",
      "ConfigurationId": 2
    },
    {
      "Models": [
        {
          "ReadOnly": true,
          "Multiline": true,
          "VarId": 3,
          "VarName": "sample string 4",
          "VarValue": "sample string 5",
          "VarType": 0,
          "Mandatory": true,
          "VersionFree": true
        },
        {
          "ReadOnly": true,
          "Multiline": true,
          "VarId": 3,
          "VarName": "sample string 4",
          "VarValue": "sample string 5",
          "VarType": 0,
          "Mandatory": true,
          "VersionFree": true
        }
      ],
      "ConfigurationName": "sample string 1",
      "ConfigurationId": 2
    }
  ],
  "CardVariableInfo": [
    {
      "VariableId": 1,
      "VariableValueOptions": [
        "sample string 1",
        "sample string 2"
      ]
    },
    {
      "VariableId": 1,
      "VariableValueOptions": [
        "sample string 1",
        "sample string 2"
      ]
    }
  ]
}
```

Response (application/xml, text/xml)

Sample Data

```

<DataCard xmlns:i="http://www.w3.org/2001/XMLSchema-instance" xmlns="http://schemas.datacontract.org/2004/07/SWPDM.Models">
  <CardVariableInfo>
    <VariableExtraInfo>
      <VariableId>1</VariableId>
      <VariableValueOptions xmlns:d4p1="http://schemas.microsoft.com/2003/10/Serialization/Arrays">
        <d4p1:string>sample string 1</d4p1:string>
        <d4p1:string>sample string 2</d4p1:string>
      </VariableValueOptions>
    </VariableExtraInfo>
    <VariableExtraInfo>
      <VariableId>1</VariableId>
      <VariableValueOptions xmlns:d4p1="http://schemas.microsoft.com/2003/10/Serialization/Arrays">
        <d4p1:string>sample string 1</d4p1:string>
        <d4p1:string>sample string 2</d4p1:string>
      </VariableValueOptions>
    </VariableExtraInfo>
  </CardVariableInfo>
  <ConfigVarInfo>
    <ConfigInfo_DataCard>
      <ConfigurationId>2</ConfigurationId>
      <ConfigurationName>sample string 1</ConfigurationName>
      <Models>
        <VariableInfo_DataCard>
          <Mandatory>true</Mandatory>
          <VarId>3</VarId>
          <VarName>sample string 4</VarName>
          <VarType>VarTypeNone</VarType>
          <VarValue>sample string 5</VarValue>
          <VersionFree>true</VersionFree>
          <Multiline>true</Multiline>
          <ReadOnly>true</ReadOnly>
        </VariableInfo_DataCard>
        <VariableInfo_DataCard>
          <Mandatory>true</Mandatory>
          <VarId>3</VarId>
          <VarName>sample string 4</VarName>
          <VarType>VarTypeNone</VarType>
          <VarValue>sample string 5</VarValue>
          <VersionFree>true</VersionFree>
          <Multiline>true</Multiline>
          <ReadOnly>true</ReadOnly>
        </VariableInfo_DataCard>
      </Models>
    </ConfigInfo_DataCard>
    <ConfigInfo_DataCard>
      <ConfigurationId>2</ConfigurationId>
      <ConfigurationName>sample string 1</ConfigurationName>
      <Models>
        <VariableInfo_DataCard>
          <Mandatory>true</Mandatory>
          <VarId>3</VarId>
          <VarName>sample string 4</VarName>
          <VarType>VarTypeNone</VarType>
          <VarValue>sample string 5</VarValue>
          <VersionFree>true</VersionFree>
          <Multiline>true</Multiline>
          <ReadOnly>true</ReadOnly>
        </VariableInfo_DataCard>
        <VariableInfo_DataCard>
          <Mandatory>true</Mandatory>
          <VarId>3</VarId>
          <VarName>sample string 4</VarName>
          <VarType>VarTypeNone</VarType>
          <VarValue>sample string 5</VarValue>
          <VersionFree>true</VersionFree>
          <Multiline>true</Multiline>
          <ReadOnly>true</ReadOnly>
        </VariableInfo_DataCard>
      </Models>
    </ConfigInfo_DataCard>
  </ConfigVarInfo>
  <VariablesWithWriteAllConfigs xmlns:d2p1="http://schemas.microsoft.com/2003/10/Serialization/Arrays">
    <d2p1:int>1</d2p1:int>
    <d2p1:int>2</d2p1:int>
  </VariablesWithWriteAllConfigs>
</DataCard>

```

Example

Modify File `Datacards.postman_collection.json`

See Also

GET

api/{vaultName}/files/{fileId}/{version}/download

Description

Get file

Gets the link to download a file.

Parameters

vaultName	(URI parameter) Vault name (required)	string
fileId	(URI parameter) File ID (required)	integer
version	(URI parameter) Version (required)	integer
Location	(Response) URI of file to download Member of RedirectResult model	URI
Request	(Response) An HttpRequestMessage; each HttpRequestMessage consists of: Version (Version object that consists of: Major Minor Build Revision MajorRevision MinorRevision) Content (HttpContent object that consists of an array of headers) Method (HttpMethod object that consists of a method string) RequestUri (URI) Headers (Array of objects) Properties (Dictionary of string [key] and Object [value]) Member of RedirectResult model	HttpRequestMessage

Response (application/json, text/json)

See Also

GET **api/{vaultName}/files/{fileId}/{version}/download?folderId={folderId}**

Description

Gets the specified file.

Parameters

vaultName	(Required URI parameter) Vault name	string
fileId	(Required URI Parameter) File ID	integer
version	(Required URI Parameter) File version	integer
folderId	(URI Parameter) Folder ID, default is 0	integer
Location	(Response) URI location (Member of RedirectResult Model)	URI
Request	(Response) HttpRequestMessage: Version: Major: integer Minor: integer Build: integer Revision: integer MajorRevision: integer MinorRevision: integer Content: HttpContent (array of Headers) Method: HttpMethod (string) RequestUri: URI Headers: array of objects Properties: Dictionary of string/value pairs (Member of RedirectResult Model)	HttpRequestMessage

Response (application/json, text/json)

See Also

[File Resource Group](#) | [PDM Pro API Web Service](#)

GET**api/{vaultName}/files/{fileId}/{version}?folderId={folderId}****Description**

Gets information about the specified file.

Parameters

vaultName	(Required URI Parameter) Vault name	string
fileId	(Required URI Parameter) File ID	integer
version	(URI Parameter) File version, default value is 0	integer
folderId	(URI Parameter) Folder ID, default value is 0	integer
Id	(Response) File ID (Member of ObjectInfo model)	integer
Name	(Response) File name (Member of ObjectInfo model)	string
Size	(Response) File size (Member of ObjectInfo model)	integer
ModifiedDate	(Response) Modified date (Member of ObjectInfo model)	date
State	(Response) File state (Member of ObjectInfo model)	string
StateId	(Response) File state ID (Member of ObjectInfo model)	integer
ParentFolderId	(Response) Parent folder ID (Member of ObjectInfo model)	integer
Path	(Response) Folder path (Member of ObjectInfo model)	string
Type	(Response) Object Type: Folder = 0 File = 1 Bom = 3 (Member of ObjectInfo model)	ObjectType
IsLocked	(Response) Whether file is locked (checked out) (Member of ObjectInfo model)	integer
LockedBy	(Response) ID of user who checked out the file (Member of ObjectInfo model)	integer
IsShared	(Response) Whether the file is shared (Member of ObjectInfo model)	integer
IsToolbox	(Response) 1 if a Toolbox item, 0 if not (Member of ObjectInfo model)	integer

IsDeleted

(Response) Whether file is deleted
(Member of ObjectInfo model)

integer

Response (application/json, text/json)

Sample Data

```
[
  {
    "Id": 1,
    "Name": "sample string 2",
    "Size": 3,
    "ModifiedDate": "2024-11-27T09:52:30.6455738-05:00",
    "Version": 5,
    "State": "sample string 6",
    "StateId": 7,
    "ParentFolderId": 8,
    "Path": "sample string 9",
    "Type": 0,
    "IsLocked": 10,
    "LockedBy": 11,
    "IsShared": 12,
    "IsToolbox": 13,
    "IsDeleted": 14
  },
  {
    "Id": 1,
    "Name": "sample string 2",
    "Size": 3,
    "ModifiedDate": "2024-11-27T09:52:30.6455738-05:00",
    "Version": 5,
    "State": "sample string 6",
    "StateId": 7,
    "ParentFolderId": 8,
    "Path": "sample string 9",
    "Type": 0,
    "IsLocked": 10,
    "LockedBy": 11,
    "IsShared": 12,
    "IsToolbox": 13,
    "IsDeleted": 14
  }
]
```

Response (application/xml, text/xml)

Sample Data

```
<ArrayOfObjectInfo xmlns:i="http://www.w3.org/2001/XMLSchema-instance"
xmlns="http://schemas.datacontract.org/2004/07/SWPDM.Models">
  <ObjectInfo>
    <Id>1</Id>
    <IsDeleted>14</IsDeleted>
    <IsLocked>10</IsLocked>
    <IsShared>12</IsShared>
    <IsToolbox>13</IsToolbox>
    <LockedBy>11</LockedBy>
    <ModifiedDate>2024-11-27T09:52:30.6455738-05:00</ModifiedDate>
    <Name>sample string 2</Name>
    <ParentFolderId>8</ParentFolderId>
    <Path>sample string 9</Path>
    <Size>3</Size>
    <State>sample string 6</State>
    <StateId>7</StateId>
    <Type>Folder</Type>
    <Version>5</Version>
  </ObjectInfo>
  <ObjectInfo>
    <Id>1</Id>
    <IsDeleted>14</IsDeleted>
    <IsLocked>10</IsLocked>
    <IsShared>12</IsShared>
    <IsToolbox>13</IsToolbox>
    <LockedBy>11</LockedBy>
    <ModifiedDate>2024-11-27T09:52:30.6455738-05:00</ModifiedDate>
    <Name>sample string 2</Name>
    <ParentFolderId>8</ParentFolderId>
    <Path>sample string 9</Path>
    <Size>3</Size>
    <State>sample string 6</State>
  </ObjectInfo>
</ArrayOfObjectInfo>
```

```
<StateId>7</StateId>
<Type>Folder</Type>
<Version>5</Version>
</ObjectInfo>
</ArrayOfObjectInfo>
```

See Also

[File Resource Group](#) | [PDM Pro API Web Service](#)

GET

api/{vaultName}/files/{fileId}/{version}/info

Description

Get file info

Gets information about the specified file.

Parameters

vaultName	(URI parameter) Vault name (required)	string
fileId	(URI parameter) File ID (required)	integer
version	(URI and Response parameter) Version (default value is 0)	integer
Id	(Response) File ID Member of ObjectInfo model; see Remarks	integer
Name	(Response) File name Member of ObjectInfo model; see Remarks	string
Size	(Response) File size Member of ObjectInfo model; see Remarks	integer
ModifiedDate	(Response) Modification date Member of ObjectInfo model; see Remarks	date
State	(Response) Workflow state Member of ObjectInfo model; see Remarks	string
StateId	(Response) State ID Member of ObjectInfo model; see Remarks	integer
ParentFolderId	(Response) Parent folder ID Member of ObjectInfo model; see Remarks	integer
Path	(Response) Folder path Member of ObjectInfo model; see Remarks	string
Type	(Response) ObjectType model; one of: Folder = 0 File = 1 Bom = 3 Member of ObjectInfo model; see Remarks	ObjectType
IsLocked	(Response) Whether the file is checked out	integer

	Member of ObjectInfo model; see Remarks	
LockedBy	(Response) ID of user who checked out the file	integer
	Member of ObjectInfo model; see Remarks	
IsShared	(Response) Whether the file is shared	integer
	Member of ObjectInfo model; see Remarks	
IsToolbox	(Response) Whether the file is a toolbox item	integer
	Member of ObjectInfo model; see Remarks	
IsDeleted	(Response) Whether the file is deleted	integer
	Member of ObjectInfo model; see Remarks	

Response (application/json, text/json)

Sample Data

```
[
  {
    "Id": 1,
    "Name": "sample string 2",
    "Size": 3,
    "ModifiedDate": "2022-07-25T14:02:49.4694049-04:00",
    "Version": 5,
    "State": "sample string 6",
    "StateId": 7,
    "ParentFolderId": 8,
    "Path": "sample string 9",
    "Type": 0,
    "IsLocked": 10,
    "LockedBy": 11,
    "IsShared": 12,
    "IsToolbox": 13,
    "IsDeleted": 14
  },
  {
    "Id": 1,
    "Name": "sample string 2",
    "Size": 3,
    "ModifiedDate": "2022-07-25T14:02:49.4694049-04:00",
    "Version": 5,
    "State": "sample string 6",
    "StateId": 7,
    "ParentFolderId": 8,
    "Path": "sample string 9",
    "Type": 0,
    "IsLocked": 10,
    "LockedBy": 11,
    "IsShared": 12,
    "IsToolbox": 13,
    "IsDeleted": 14
  }
]
```

Response (application/xml, text/xml)

Sample Data

```
<ArrayOfObjectInfo xmlns:i="http://www.w3.org/2001/XMLSchema-instance"
xmlns="http://schemas.datacontract.org/2004/07/SWPDM.Models">
  <ObjectInfo>
    <Id>1</Id>
    <IsDeleted>14</IsDeleted>
    <IsLocked>10</IsLocked>
    <IsShared>12</IsShared>
    <IsToolbox>13</IsToolbox>
    <LockedBy>11</LockedBy>
    <ModifiedDate>2022-07-25T14:02:49.4694049-04:00</ModifiedDate>
    <Name>sample string 2</Name>
    <ParentFolderId>8</ParentFolderId>
  </ObjectInfo>
  <ObjectInfo>
    <Id>1</Id>
    <IsDeleted>14</IsDeleted>
    <IsLocked>10</IsLocked>
    <IsShared>12</IsShared>
    <IsToolbox>13</IsToolbox>
    <LockedBy>11</LockedBy>
    <ModifiedDate>2022-07-25T14:02:49.4694049-04:00</ModifiedDate>
    <Name>sample string 2</Name>
    <ParentFolderId>8</ParentFolderId>
  </ObjectInfo>
</ArrayOfObjectInfo>
```

```
<Path>sample string 9</Path>
<Size>3</Size>
<State>sample string 6</State>
<StateId>7</StateId>
<Type>Folder</Type>
<Version>5</Version>
</ObjectInfo>
<ObjectInfo>
  <Id>1</Id>
  <IsDeleted>14</IsDeleted>
  <IsLocked>10</IsLocked>
  <IsShared>12</IsShared>
  <IsToolbox>13</IsToolbox>
  <LockedBy>11</LockedBy>
  <ModifiedDate>2022-07-25T14:02:49.4694049-04:00</ModifiedDate>
  <Name>sample string 2</Name>
  <ParentFolderId>8</ParentFolderId>
  <Path>sample string 9</Path>
  <Size>3</Size>
  <State>sample string 6</State>
  <StateId>7</StateId>
  <Type>Folder</Type>
  <Version>5</Version>
</ObjectInfo>
</ArrayOfObjectInfo>
```

Remarks

This operation should return one ObjectInfo object for each unique file ID in the request URI.

See Also

[File Resource Group](#) | [PDM Pro API Web Service](#)

GET

api/{vaultName}/files/{fileId}/{version}/info/extended

Description

Get file info extended

Gets extended file information.

Parameters

vaultName	(URI parameter) Vault name (required)	string
fileId	(URI parameter) File ID (required)	integer
version	(URI parameter) Version (required)	integer
StateId	(Response) State ID Member of VersionInfoExtended model	integer
State	(Response) State name Member of VersionInfoExtended model	string
Workflow	(Response) Workflow name Member of VersionInfoExtended model	string
Category	(Response) Category Member of VersionInfoExtended model	string
ReplicatedTo	(Response) Replicated to Member of VersionInfoExtended model	string
Branches	(Response) Branches Member of VersionInfoExtended model	string

Response (application/json, text/json)

Sample Data

```
{
  "StateId": 1,
  "State": "sample string 2",
  "Workflow": "sample string 3",
  "Category": "sample string 4",
  "ReplicatedTo": "sample string 5",
  "Branches": "sample string 6"
}
```

Response (application/xml, text/xml)

Sample Data

```
<VersionInfoExtended xmlns:i="http://www.w3.org/2001/XMLSchema-instance"
xmlns="http://schemas.datacontract.org/2004/07/SWPDM.Models">
  <Branches>sample string 6</Branches>
  <Category>sample string 4</Category>
  <ReplicatedTo>sample string 5</ReplicatedTo>
  <State>sample string 2</State>
  <StateId>1</StateId>
  <Workflow>sample string 3</Workflow>
</VersionInfoExtended>
```

See Also

[File Resource Group](#) | [PDM Pro API Web Service](#)

GET

api/{vaultName}/files/{fileId}/{version}/info/extended?folderId={folderId}

Description

Gets extended version information for a specified file.

Parameters

vaultName	(Required URI Parameter) Vault name	string
fileId	(Required URI Parameter) File ID	integer
version	(Required URI Parameter) File version	integer
folderId	(URI Parameter) Folder ID, default is 0	integer
StateId	(Response) State ID (Member of VersionInfoExtended Member)	integer
State	(Response) State name (Member of VersionInfoExtended Member)	string
Workflow	(Response) Workflow (Member of VersionInfoExtended Member)	string
Category	(Response) Category (Member of VersionInfoExtended Member)	string
ReplicatedTo	(Response) Replicated to (Member of VersionInfoExtended Member)	string
Branches	(Response) Branches (Member of VersionInfoExtended Member)	string

Response (application/json, text/json)

Sample Data

```
{
  "StateId": 1,
  "State": "sample string 2",
  "Workflow": "sample string 3",
  "Category": "sample string 4",
  "ReplicatedTo": "sample string 5",
  "Branches": "sample string 6"
}
```

Response (application/xml, text/xml)

Sample Data

```
<VersionInfoExtended xmlns:i="http://www.w3.org/2001/XMLSchema-instance"
xmlns="http://schemas.datacontract.org/2004/07/SWPDM.Models">
  <Branches>sample string 6</Branches>
  <Category>sample string 4</Category>
  <ReplicatedTo>sample string 5</ReplicatedTo>
  <State>sample string 2</State>
  <StateId>1</StateId>
  <Workflow>sample string 3</Workflow>
</VersionInfoExtended>
```

See Also

[File Resource Group](#) | [PDM Pro API Web Service](#)

GET **api/{vaultName}/files/{fileId}/{version}/info?folderId={folderId}****Description**

Gets information about the specified file.

Parameters

vaultName	(Required URI Parameter) Vault name	string
fileId	(Required URI Parameter) File ID	integer
version	(URI Parameter) File version, default value is 0	integer
folderId	(URI Parameter) Folder ID, default value is 0	integer
Id	(Response) File ID (Member of ObjectInfo model)	integer
Name	(Response) File name (Member of ObjectInfo model)	string
Size	(Response) File size (Member of ObjectInfo model)	integer
ModifiedDate	(Response) Modified date (Member of ObjectInfo model)	date
State	(Response) File state (Member of ObjectInfo model)	string
StateId	(Response) File state ID (Member of ObjectInfo model)	integer
ParentFolderId	(Response) Parent folder ID (Member of ObjectInfo model)	integer
Path	(Response) Folder path (Member of ObjectInfo model)	string
Type	(Response) Object Type: Folder = 0 File = 1 Bom = 3 (Member of ObjectInfo model)	ObjectType
IsLocked	(Response) Whether file is locked (checked out) (Member of ObjectInfo model)	integer
LockedBy	(Response) ID of user who checked out the file (Member of ObjectInfo model)	integer
IsShared	(Response) Whether the file is shared (Member of ObjectInfo model)	integer
IsToolbox	(Response) 1 if a Toolbox item, 0 if not (Member of ObjectInfo model)	integer

IsDeleted

(Response) Whether file is deleted
(Member of ObjectInfo model)

integer

Response (application/json, text/json)

Sample Data

```
[
  {
    "Id": 1,
    "Name": "sample string 2",
    "Size": 3,
    "ModifiedDate": "2024-11-27T09:52:30.652577-05:00",
    "Version": 5,
    "State": "sample string 6",
    "StateId": 7,
    "ParentFolderId": 8,
    "Path": "sample string 9",
    "Type": 0,
    "IsLocked": 10,
    "LockedBy": 11,
    "IsShared": 12,
    "IsToolbox": 13,
    "IsDeleted": 14
  },
  {
    "Id": 1,
    "Name": "sample string 2",
    "Size": 3,
    "ModifiedDate": "2024-11-27T09:52:30.652577-05:00",
    "Version": 5,
    "State": "sample string 6",
    "StateId": 7,
    "ParentFolderId": 8,
    "Path": "sample string 9",
    "Type": 0,
    "IsLocked": 10,
    "LockedBy": 11,
    "IsShared": 12,
    "IsToolbox": 13,
    "IsDeleted": 14
  }
]
```

Response (application/xml, text/xml)

Sample Data

```
<ArrayOfObjectInfo xmlns:i="http://www.w3.org/2001/XMLSchema-instance"
xmlns="http://schemas.datacontract.org/2004/07/SWPDM.Models">
  <ObjectInfo>
    <Id>1</Id>
    <IsDeleted>14</IsDeleted>
    <IsLocked>10</IsLocked>
    <IsShared>12</IsShared>
    <IsToolbox>13</IsToolbox>
    <LockedBy>11</LockedBy>
    <ModifiedDate>2024-11-27T09:52:30.652577-05:00</ModifiedDate>
    <Name>sample string 2</Name>
    <ParentFolderId>8</ParentFolderId>
    <Path>sample string 9</Path>
    <Size>3</Size>
    <State>sample string 6</State>
    <StateId>7</StateId>
    <Type>Folder</Type>
    <Version>5</Version>
  </ObjectInfo>
  <ObjectInfo>
    <Id>1</Id>
    <IsDeleted>14</IsDeleted>
    <IsLocked>10</IsLocked>
    <IsShared>12</IsShared>
    <IsToolbox>13</IsToolbox>
    <LockedBy>11</LockedBy>
    <ModifiedDate>2024-11-27T09:52:30.652577-05:00</ModifiedDate>
    <Name>sample string 2</Name>
    <ParentFolderId>8</ParentFolderId>
    <Path>sample string 9</Path>
    <Size>3</Size>
    <State>sample string 6</State>
  </ObjectInfo>
</ArrayOfObjectInfo>
```

```
<StateId>7</StateId>
<Type>Folder</Type>
<Version>5</Version>
</ObjectInfo>
</ArrayOfObjectInfo>
```

See Also

[File Resource Group](#) | [PDM Pro API Web Service](#)

GET

api/{vaultName}/files/{fileId}/{version}/references?configId={configId}&folderId={folderId}

Description

GET: api/{VaultName}/files/{FileID}/{Version}/references Get file references

Gets the top level file references of the specified file.

Parameters

vaultName	(Required URI parameter) Vault name	string
fileId	(Required URI parameter) File ID	integer
version	(Required URI parameter) File version	integer
configId	(URI parameter) Configuration ID (default value is -1)	integer
folderId	(URI parameter) Folder ID (default value is 0)	integer
File	(Response) A FileInfo object that consists of: File object that consists of: FileId (integer) File Name (string) Folder object that consists of: FolderId (integer) FolderPath Version (integer) Config object that consists of : ConfigurationName (string) ConfigurationId (integer) Member of FileRef model	FileInfo
IsCyclic	(Response) Whether the file reference is self-referential Member of FileRef model	boolean
IsToolbox	(Response) Whether the file reference is a toolbox item Member of FileRef model	integer
ObjectType	(Response) PweObjectType model; one of: ObjType_NoObject = 0 ObjType_File = 1 ObjType_InternalComponent = 2 ObjType_SavedBOM = 3 ObjType_Item = 4 ObjType_CutListItem = 5 Member of FileRef model	PweObjectType

Warnings	(Response) An array of BaseWarningModels; each BaseWarningModel consists of: - Message (string) - IsBlocking (boolean) - IsError (boolean) Member of FileRef model	Collection of BaseWarningModel
References	(Response) The file reference's references; an array of FileRefs; each FileRef consists of: - File (FileInfo) - IsCyclic (boolean) - IsToolbox (integer) - ObjectType (PweObjectType) - Warnings (Array of BaseWarningModels) - References (Array of FileRefs) Member of FileRef model; see Remarks	Collection of FileRef

Response (application/json)

Response (text/json)

Response (application/xml)

Response (text/xml)

See Also

GET

api/{vaultName}/files/{fileId}/{version}/thumbnails

Description

Get file thumbnail

Gets the link to download a file thumbnail.

Parameters

vaultName	(URI parameter) Vault name (required)	string
fileId	(URI parameter) File ID (required)	integer
version	(URI parameter) Version (required)	integer
Location	(Response) URI of file to download Member of RedirectResult model	URI
Request	(Response) An HttpRequestMessage; each HttpRequestMessage consists of: Version (Version object that consists of: Major Minor Build Revision MajorRevision MinorRevision) Content (HttpContent object that consists of an array of headers) Method (HttpMethod object that consists of a method string) RequestUri (URI) Headers (Array of objects) Properties (Dictionary of string [key] and Object [value]) Member of RedirectResult model	HttpRequestMessage

Response (application/json, text/json)

See Also

GET **api/{vaultName}/files/{fileId}/{version}/thumbnails?folderId={folderId}**

Description

Gets a specified file's thumbnail.

Parameters

vaultName	(Required URI Parameter) Vault name	string
fileId	(Required URI Parameter) File ID	integer
version	(Required URI Parameter) File version	integer
folderId	(URI Parameter) Folder ID, default is 0	integer
Location	(Response) URI location (Member of RedirectResult Model)	URI
Request	(Response) HttpRequestMessage: Version: Major: integer Minor: integer Build: integer Revision: integer MajorRevision: integer MinorRevision: integer Content: HttpContent: collection of Headers Method HttpMethod: string RequestUri: URI Headers: array Properties: Dictionary of key/value pairs (Member of RedirectResult Model)	HttpRequestMessage

Response (application/json, text/json)

See Also

GET **api/{vaultName}/files/{fileId}/{version}/transitions?folderId={folderId}**

Description

Gets the file transitions for the specified file.

Parameters

vaultName	(Required URI Parameter) Vault name	string
fileId	(Required URI Parameter) File ID	integer
version	(URI Parameter) File version, default is -1	integer
folderId	(URI Parameter) Folder ID, default is 0	integer
TransitionId	(Response) Transition ID (Member of HistoryTransition Model)	integer
VersionNo	(Response) Version number (Member of HistoryTransition Model)	integer
Comment	(Response) Comment (Member of HistoryTransition Model)	string
Date	(Response) Date (Member of HistoryTransition Model)	date
SourceState	(Response) Source StateInfo: StateId: integer StateName: string IgnorePreviousPermissions: integer (Member of HistoryTransition Model)	StateInfo
DestinationState	(Response) Destination StateInfo: StateId: integer StateName: string IgnorePreviousPermissions: integer (Member of HistoryTransition Model)	StateInfo
User	(Response) UserInfo: UserName: string UserId: integer (Member of HistoryTransition Model)	UserInfo

Response (application/json, text/json)

Sample Data

```
[
  {
    "TransitionId": 1,
    "VersionNo": 2,
    "Comment": "sample string 3",
    "Date": "2024-11-27T09:52:30.6865768-05:00",
    "SourceState": {
      "StateId": 1,
      "StateName": "sample string 2",
      "IgnorePreviousPermissions": 3
    },
    "DestinationState": {
```

```

        "StateId": 1,
        "StateName": "sample string 2",
        "IgnorePreviousPermissions": 3
    },
    "User": {
        "UserName": "sample string 1",
        "UserId": 2
    }
},
{
    "TransitionId": 1,
    "VersionNo": 2,
    "Comment": "sample string 3",
    "Date": "2024-11-27T09:52:30.6865768-05:00",
    "SourceState": {
        "StateId": 1,
        "StateName": "sample string 2",
        "IgnorePreviousPermissions": 3
    },
    "DestinationState": {
        "StateId": 1,
        "StateName": "sample string 2",
        "IgnorePreviousPermissions": 3
    },
    "User": {
        "UserName": "sample string 1",
        "UserId": 2
    }
}
]

```

Response (application/xml, text/xml)

Sample Data

```

<ArrayOfHistoryTransition xmlns:i="http://www.w3.org/2001/XMLSchema-instance"
xmlns="http://schemas.datacontract.org/2004/07/SWPDM.Models">
  <HistoryTransition>
    <Comment>sample string 3</Comment>
    <Date>2024-11-27T09:52:30.6865768-05:00</Date>
    <DestinationState>
      <IgnorePreviousPermissions>3</IgnorePreviousPermissions>
      <StateId>1</StateId>
      <StateName>sample string 2</StateName>
    </DestinationState>
    <SourceState>
      <IgnorePreviousPermissions>3</IgnorePreviousPermissions>
      <StateId>1</StateId>
      <StateName>sample string 2</StateName>
    </SourceState>
    <TransitionId>1</TransitionId>
    <User>
      <UserId>2</UserId>
      <UserName>sample string 1</UserName>
    </User>
    <VersionNo>2</VersionNo>
  </HistoryTransition>
  <HistoryTransition>
    <Comment>sample string 3</Comment>
    <Date>2024-11-27T09:52:30.6865768-05:00</Date>
    <DestinationState>
      <IgnorePreviousPermissions>3</IgnorePreviousPermissions>
      <StateId>1</StateId>
      <StateName>sample string 2</StateName>
    </DestinationState>
    <SourceState>
      <IgnorePreviousPermissions>3</IgnorePreviousPermissions>
      <StateId>1</StateId>
      <StateName>sample string 2</StateName>
    </SourceState>
    <TransitionId>1</TransitionId>
    <User>
      <UserId>2</UserId>
      <UserName>sample string 1</UserName>
    </User>
    <VersionNo>2</VersionNo>
  </HistoryTransition>
</ArrayOfHistoryTransition>

```

See Also

[File Resource Group](#) | [PDM Pro API Web Service](#)

GET

api/{vaultName}/files/{fileId}/{version}/variables

Description

Get file variables

Gets the specified file's variables.

Parameters

vaultName	(URI parameter) Vault name (required)	string
fileId	(URI parameter) File ID (required)	integer
version	(URI parameter) File version (required)	integer
ConfigurationName	(Response) Configuration name Member of ConfigInfo model (see Remarks)	string
ConfigurationId	(Response) Configuration ID Member of ConfigInfo model (see Remarks)	integer
Models	(Response) Array of VariableInfos; each VariableInfo consists of: VarId (integer) VarName (string) VarValue (string) VarType (one of: VarTypeNone = 0 VarTypeText = 1 VarTypeInt = 2 VarTypeFloat = 3 VarTypeBool = 4 VarTypeDate = 5 Mandatory (boolean) VersionFree (boolean) Member of ConfigInfo model (see Remarks)	Collection of VariableInfo

Response (application/json, text/json)

Sample Data

```
[
  {
    "Models": [
      {
        "VarId": 1,
        "VarName": "sample string 2",
        "VarValue": "sample string 3",
        "VarType": 0,
        "Mandatory": true,
        "VersionFree": true
      },
      {
        "VarId": 1,
        "VarName": "sample string 2",
```

```

        "VarValue": "sample string 3",
        "VarType": 0,
        "Mandatory": true,
        "VersionFree": true
    }
],
"ConfigurationName": "sample string 1",
"ConfigurationId": 2
},
{
    "Models": [
        {
            "VarId": 1,
            "VarName": "sample string 2",
            "VarValue": "sample string 3",
            "VarType": 0,
            "Mandatory": true,
            "VersionFree": true
        },
        {
            "VarId": 1,
            "VarName": "sample string 2",
            "VarValue": "sample string 3",
            "VarType": 0,
            "Mandatory": true,
            "VersionFree": true
        }
    ],
    "ConfigurationName": "sample string 1",
    "ConfigurationId": 2
}
]

```

Response (application/xml, text/xml)

Sample Data

```

<ArrayOfConfigInfo xmlns:i="http://www.w3.org/2001/XMLSchema-instance"
xmlns="http://schemas.datacontract.org/2004/07/SWPDM.Models">
  <ConfigInfo>
    <ConfigurationId>2</ConfigurationId>
    <ConfigurationName>sample string 1</ConfigurationName>
    <Models>
      <VariableInfo>
        <Mandatory>true</Mandatory>
        <VarId>1</VarId>
        <VarName>sample string 2</VarName>
        <VarType>VarTypeNone</VarType>
        <VarValue>sample string 3</VarValue>
        <VersionFree>true</VersionFree>
      </VariableInfo>
      <VariableInfo>
        <Mandatory>true</Mandatory>
        <VarId>1</VarId>
        <VarName>sample string 2</VarName>
        <VarType>VarTypeNone</VarType>
        <VarValue>sample string 3</VarValue>
        <VersionFree>true</VersionFree>
      </VariableInfo>
    </Models>
  </ConfigInfo>
  <ConfigInfo>
    <ConfigurationId>2</ConfigurationId>
    <ConfigurationName>sample string 1</ConfigurationName>
    <Models>
      <VariableInfo>
        <Mandatory>true</Mandatory>
        <VarId>1</VarId>
        <VarName>sample string 2</VarName>
        <VarType>VarTypeNone</VarType>
        <VarValue>sample string 3</VarValue>
        <VersionFree>true</VersionFree>
      </VariableInfo>
      <VariableInfo>
        <Mandatory>true</Mandatory>
        <VarId>1</VarId>
        <VarName>sample string 2</VarName>
        <VarType>VarTypeNone</VarType>
        <VarValue>sample string 3</VarValue>
        <VersionFree>true</VersionFree>
      </VariableInfo>
    </Models>
  </ConfigInfo>
</ArrayOfConfigInfo>

```

Remarks

This operation can return an array of ConfigInfos. See the Response examples.

See Also

[File Resource Group](#) | [PDM Pro API Web Service](#)

GET **api/{vaultName}/files/{fileId}/{version}/variables?folderId={folderId}**

Description

Gets configuration variable information for the specified file.

Parameters

vaultName	(Required URI Parameter) Vault name	string
fileId	(Required URI Parameter) File ID	integer
version	(Required URI Parameter) File version	integer
folderId	(URI Parameter) Folder ID, default is 0	integer
ConfigurationName	(Response) Name of configuration (Member of ConfigInfo Model)	string
ConfigurationId	(Response) ID of configuration (Member of ConfigInfo Model)	integer
Models	(Response) Collection of VariableInfo: VarId: integer VarName: string VarValue: string VarType: VarTypeNone = 0 VarTypeText = 1 VarTypeInt = 2 VarTypeFloat = 3 VarTypeBool = 4 VarTypeDate = 5 Mandatory: boolean VersionFree: boolean (Member of ConfigInfo Model)	Collection of VariableInfo

Response (application/json, text/json)

Sample Data

```
[
  {
    "Models": [
      {
        "VarId": 1,
        "VarName": "sample string 2",
        "VarValue": "sample string 3",
        "VarType": 0,
        "Mandatory": true,
        "VersionFree": true
      },
      {
        "VarId": 1,
        "VarName": "sample string 2",
        "VarValue": "sample string 3",
        "VarType": 0,
        "Mandatory": true,
        "VersionFree": true
      }
    ],
    "ConfigurationName": "sample string 1",
    "ConfigurationId": 2
  }
]
```

```

},
{
  "Models": [
    {
      "VarId": 1,
      "VarName": "sample string 2",
      "VarValue": "sample string 3",
      "VarType": 0,
      "Mandatory": true,
      "VersionFree": true
    },
    {
      "VarId": 1,
      "VarName": "sample string 2",
      "VarValue": "sample string 3",
      "VarType": 0,
      "Mandatory": true,
      "VersionFree": true
    }
  ],
  "ConfigurationName": "sample string 1",
  "ConfigurationId": 2
}
]

```

Response (application/xml, text/xml)

Sample Data

```

<ArrayOfConfigInfo xmlns:i="http://www.w3.org/2001/XMLSchema-instance"
xmlns="http://schemas.datacontract.org/2004/07/SWPDM.Models">
  <ConfigInfo>
    <ConfigurationId>2</ConfigurationId>
    <ConfigurationName>sample string 1</ConfigurationName>
    <Models>
      <VariableInfo>
        <Mandatory>true</Mandatory>
        <VarId>1</VarId>
        <VarName>sample string 2</VarName>
        <VarType>VarTypeNone</VarType>
        <VarValue>sample string 3</VarValue>
        <VersionFree>true</VersionFree>
      </VariableInfo>
      <VariableInfo>
        <Mandatory>true</Mandatory>
        <VarId>1</VarId>
        <VarName>sample string 2</VarName>
        <VarType>VarTypeNone</VarType>
        <VarValue>sample string 3</VarValue>
        <VersionFree>true</VersionFree>
      </VariableInfo>
    </Models>
  </ConfigInfo>
  <ConfigInfo>
    <ConfigurationId>2</ConfigurationId>
    <ConfigurationName>sample string 1</ConfigurationName>
    <Models>
      <VariableInfo>
        <Mandatory>true</Mandatory>
        <VarId>1</VarId>
        <VarName>sample string 2</VarName>
        <VarType>VarTypeNone</VarType>
        <VarValue>sample string 3</VarValue>
        <VersionFree>true</VersionFree>
      </VariableInfo>
      <VariableInfo>
        <Mandatory>true</Mandatory>
        <VarId>1</VarId>
        <VarName>sample string 2</VarName>
        <VarType>VarTypeNone</VarType>
        <VarValue>sample string 3</VarValue>
        <VersionFree>true</VersionFree>
      </VariableInfo>
    </Models>
  </ConfigInfo>
</ArrayOfConfigInfo>

```

See Also

[File Resource Group](#) | [PDM Pro API Web Service](#)

GET

api/{vaultName}/files/{fileId}/{version}/whereused?configId={configId}&folderId={folderId}&anyVersion={anyVersion}

Description

GET: api/{VaultName}/files/{FileID}/{Version}/whereused Get file where used

Gets the parents of the specified file.

Parameters

vaultName	(URI parameter) Vault name (required)	string
fileId	(URI parameter) File ID (required)	integer
version	(URI parameter) Version (required)	integer
configId	(URI parameter) Configuration ID (default value is -1)	integer
folderId	(URI parameter) Folder ID (default value is 0)	integer
anyVersion	(URI parameter) Whether to get any parent version (default value is false)	boolean
File	(Response) A FileInfo object that consists of: File object that consists of: FileId (integer) File Name (string) Folder object that consists of: FolderId (integer) FolderPath Version (integer) Config object that consists of : ConfigurationName (string) ConfigurationId (integer) Member of FileRef model	FileInfo
IsCyclic	(Response) Whether the file reference is self-referential Member of FileRef model	boolean
IsToolbox	(Response) Whether the file reference is a toolbox item Member of FileRef model	integer
ObjectType	(Response) A PweObjectType model; one of: ObjType_NoObject = 0 ObjType_File = 1 ObjType_InternalComponent = 2 ObjType_SavedBOM = 3 ObjType_Item = 4 ObjType_CutListItem = 5 Member of FileRef model	PweObjectType

Warnings	(Response) An array of BaseWarningModels; each BaseWarningModel consists of: Message (string) IsBlocking (boolean) IsError (boolean) Member of FileRef model	Collection of BaseWarningModel
References	(Response) The file reference's references; an array of FileRefs; each FileRef consists of: File (FileInfo) IsCyclic (boolean) IsToolbox (integer) ObjectType (PweObjectType) Warnings (Array of BaseWarningModels) References (Array of FileRefs) Member of FileRef model; see Remarks	Collection of FileRef

Response (application/json)

Response (text/json)

Response (application/xml)

Response (text/xml)

Remarks

This operation can return an array of FileRef objects that represent the parents of the file. References should be empty in the response of this operation.

See Also

[File Resource Group](#) | [PDM Pro API Web Service](#)

GET

api/{vaultName}/files/{fileId}/{version}/{configId}/whereused?folderId={folderId}&anyVersion={anyVersion}

Description

GET: api/{VaultName}/files/{FileID}/{Version}/whereused Get file where usedGets the parent files where the specified file is used.

Parameters

vaultName	(Required URI Parameter) Vault name	string
fileId	(Required URI Parameter) File ID	integer
version	(Required URI Parameter) File version	integer
configId	(URI Parameter) Config ID, default value is -1	integer
folderId	(URI Parameter) Folder ID, default value is 0	integer
anyVersion	(URI Parameter) Whether any version, default value is false	boolean
File	(Response) FileInfo object: File object: FileID: integer FileName: string Folder object: FolderID: integer FolderPath: string Version: integer Config object: ConfigurationName: string ConfigurationId: integer (Member of FileRef Model)	FileInfo
IsCyclic	(Response) Whether is self-referential (Member of FileRef Model)	boolean
IsToolbox	(Response) 1 if a Toolbox file, 0 if not (Member of FileRef Model)	integer
ObjectType	(Response) Object type: ObjType_NoObject = 0 ObjType_File = 1 ObjType_InternalComponent = 2 ObjType_SavedBOM = 3 ObjType_Item = 4 ObjType_CutListItem = 5 (Member of FileRef model)	PweObjectType
Warnings	(Response) An array of BaseWarningModels, each containing: Message = string IsBlocking = boolean IsError = boolean (Member of FileRef model)	Collection of BaseWarningModel

References

(Response) An array of FileRefs, each containing:

File Info:

File:

- FileId = integer
- FileName = string

Folder:

- FolderId = integer
- FolderPath = string

Version = integer

Config:

- ConfigurationName = string
- ConfigurationId = integer

IsCyclic: whether self-referential

IsToolbox: 1 if in Toolbox, 0 if not

ObjectType: PweObjectType containing one of:

- ObjType_NoObject = 0
- ObjType_File = 1
- ObjType_InternalComponent = 2
- ObjType_SavedBOM = 3
- ObjType_Item = 4
- ObjType_CutListItem = 5

Warnings: Array of BaseWarningModels, each containing:

- Message = string
- IsBlocking = boolean
- IsError = boolean

References: Array of FileRefs, each containing (see above for details):

- FileInfo
- IsCyclic
- IsToolbox
- ObjectType
- Warnings
- References

Collection of FileRef

Response (application/json)

Response (text/json)

Response (application/xml)

Response (text/xml)

See Also

[File Resource Group](#) | [PDM Pro API Web Service](#)

GET `api/{vaultName}/files/{fileId}/{version}/{configId}/{folderId}/whereused?anyVersion={anyVersion}`

Description

GET: `api/{VaultName}/files/{FileID}/{Version}/whereused` Get file where used Gets the parent files where the specified file is used.

Parameters

vaultName	(Required URI Parameter) Vault name	string
fileId	(Required URI Parameter) File ID	integer
version	(Required URI Parameter) File version	integer
configId	(URI Parameter) Config ID, default value is -1	integer
folderId	(URI Parameter) Folder ID, default value is 0	integer
anyVersion	(URI Parameter) Whether any version, default value is false	boolean
File	(Response) FileInfo object: File object: FileID: integer FileName: string Folder object: FolderID: integer FolderPath: string Version: integer Config object: ConfigurationName: string ConfigurationId: integer (Member of FileRef Model)	FileInfo
IsCyclic	(Response) Whether is self-referential (Member of FileRef Model)	boolean
IsToolbox	(Response) 1 if a Toolbox file, 0 if not (Member of FileRef Model)	integer
ObjectType	(Response) Object type: ObjType_NoObject = 0 ObjType_File = 1 ObjType_InternalComponent = 2 ObjType_SavedBOM = 3 ObjType_Item = 4 ObjType_CutListItem = 5 (Member of FileRef model)	PweObjectType
Warnings	(Response) An array of BaseWarningModels, each containing: Message = string IsBlocking = boolean IsError = boolean (Member of FileRef model)	Collection of BaseWarningModel

References

(Response) An array of FileRefs, each containing:

File Info:

File:

- FileId = integer
- FileName = string

Folder:

- FolderId = integer
- FolderPath = string

Version = integer

Config:

- ConfigurationName = string
- ConfigurationId = integer

IsCyclic: whether self-referential

IsToolbox: 1 if in Toolbox, 0 if not

ObjectType: PweObjectType containing one of:

- ObjType_NoObject = 0
- ObjType_File = 1
- ObjType_InternalComponent = 2
- ObjType_SavedBOM = 3
- ObjType_Item = 4
- ObjType_CutListItem = 5

Warnings: Array of BaseWarningModels, each containing:

- Message = string
- IsBlocking = boolean
- IsError = boolean

References: Array of FileRefs, each containing (see above for details):

- FileInfo
- IsCyclic
- IsToolbox
- ObjectType
- Warnings
- References

Collection of FileRef

Response (application/json)

Response (text/json)

Response (application/xml)

Response (text/xml)

See Also

[File Resource Group](#) | [PDM Pro API Web Service](#)