

PDM Professional Web API (REST) — Reference (3/3): r-api- {vaultName}-files-{fileId}-{version}-r-api-{vaultName}-workflows- icons

SOLIDWORKS API Documentation (converted from CHM)

GET**api/{vaultName}/files/{fileId}/{version}/{folderId}****Description**

Gets information about the specified file.

Parameters

vaultName	(Required URI Parameter) Vault name	string
fileId	(Required URI Parameter) File ID	integer
version	(URI Parameter) File version, default value is 0	integer
folderId	(URI Parameter) Folder ID, default value is 0	integer
Id	(Response) File ID (Member of ObjectInfo model)	integer
Name	(Response) File name (Member of ObjectInfo model)	string
Size	(Response) File size (Member of ObjectInfo model)	integer
ModifiedDate	(Response) Modified date (Member of ObjectInfo model)	date
State	(Response) File state (Member of ObjectInfo model)	string
StateId	(Response) File state ID (Member of ObjectInfo model)	integer
ParentFolderId	(Response) Parent folder ID (Member of ObjectInfo model)	integer
Path	(Response) Folder path (Member of ObjectInfo model)	string
Type	(Response) Object Type: Folder = 0 File = 1 Bom = 3 (Member of ObjectInfo model)	ObjectType
IsLocked	(Response) Whether file is locked (checked out) (Member of ObjectInfo model)	integer
LockedBy	(Response) ID of user who checked out the file (Member of ObjectInfo model)	integer
IsShared	(Response) Whether the file is shared (Member of ObjectInfo model)	integer
IsToolbox	(Response) 1 if a Toolbox item, 0 if not (Member of ObjectInfo model)	integer

IsDeleted

(Response) Whether file is deleted
(Member of ObjectInfo model)

integer

Response (application/json, text/json)

Sample Data

```
[
  {
    "Id": 1,
    "Name": "sample string 2",
    "Size": 3,
    "ModifiedDate": "2024-11-27T09:52:30.6575844-05:00",
    "Version": 5,
    "State": "sample string 6",
    "StateId": 7,
    "ParentFolderId": 8,
    "Path": "sample string 9",
    "Type": 0,
    "IsLocked": 10,
    "LockedBy": 11,
    "IsShared": 12,
    "IsToolbox": 13,
    "IsDeleted": 14
  },
  {
    "Id": 1,
    "Name": "sample string 2",
    "Size": 3,
    "ModifiedDate": "2024-11-27T09:52:30.6575844-05:00",
    "Version": 5,
    "State": "sample string 6",
    "StateId": 7,
    "ParentFolderId": 8,
    "Path": "sample string 9",
    "Type": 0,
    "IsLocked": 10,
    "LockedBy": 11,
    "IsShared": 12,
    "IsToolbox": 13,
    "IsDeleted": 14
  }
]
```

Response (application/xml, text/xml)

Sample Data

```
<ArrayOfObjectInfo xmlns:i="http://www.w3.org/2001/XMLSchema-instance"
xmlns="http://schemas.datacontract.org/2004/07/SWPDM.Models">
  <ObjectInfo>
    <Id>1</Id>
    <IsDeleted>14</IsDeleted>
    <IsLocked>10</IsLocked>
    <IsShared>12</IsShared>
    <IsToolbox>13</IsToolbox>
    <LockedBy>11</LockedBy>
    <ModifiedDate>2024-11-27T09:52:30.6575844-05:00</ModifiedDate>
    <Name>sample string 2</Name>
    <ParentFolderId>8</ParentFolderId>
    <Path>sample string 9</Path>
    <Size>3</Size>
    <State>sample string 6</State>
    <StateId>7</StateId>
    <Type>Folder</Type>
    <Version>5</Version>
  </ObjectInfo>
  <ObjectInfo>
    <Id>1</Id>
    <IsDeleted>14</IsDeleted>
    <IsLocked>10</IsLocked>
    <IsShared>12</IsShared>
    <IsToolbox>13</IsToolbox>
    <LockedBy>11</LockedBy>
    <ModifiedDate>2024-11-27T09:52:30.6575844-05:00</ModifiedDate>
    <Name>sample string 2</Name>
    <ParentFolderId>8</ParentFolderId>
    <Path>sample string 9</Path>
    <Size>3</Size>
    <State>sample string 6</State>
  </ObjectInfo>
</ArrayOfObjectInfo>
```

```
<StateId>7</StateId>
<Type>Folder</Type>
<Version>5</Version>
</ObjectInfo>
</ArrayOfObjectInfo>
```

See Also

[File Resource Group](#) | [PDM Pro API Web Service](#)

GET **api/{vaultName}/files/{fileId}/{version}/{folderId}/ActiveConfig**

Description

Gets the active configuration for the specified file.

Parameters

vaultName	(Required URI Parameter) Vault name	string
fileId	(Required URI Parameter) File ID	integer
version	(Required URI Parameter) File version	integer
folderId	(URI Parameter) Folder ID, default is 0	integer
ConfigurationName	(Response) Name of active configuration (Member of Config Model)	string
ConfigurationId	(Response) ID of active configuration (Member of Config Model)	integer

Response (application/json, text/json)

Sample Data

```
{
  "ConfigurationName": "sample string 1",
  "ConfigurationId": 2
}
```

Response (application/xml, text/xml)

Sample Data

```
<Config xmlns:i="http://www.w3.org/2001/XMLSchema-instance" xmlns="http://schemas.datacontract.org/2004/07/SWPDM.Models">
  <ConfigurationId>2</ConfigurationId>
  <ConfigurationName>sample string 1</ConfigurationName>
</Config>
```

See Also

[File Resource Group](#) | [PDM Pro API Web Service](#)

GET

**api/{vaultName}/files/{fileId}/{version}/{folderId}/allreferences?
configId={configId}&includeSubParents={includeSubParents}**

Description

GET: api/{VaultName}/files/{FileID}/{Version}/allreferences Get all file references
Gets the reference tree of the specified file.

Parameters

vaultName	(Required URI parameter) Vault name	string
fileId	(Required URI parameter) File ID	integer
version	(Required URI parameter) Version	integer
folderId	(URI parameter) Folder ID (default value is 0)	integer
configId	(URI parameter) Config ID (default value is -1)	integer
includeSubParents	(URI parameter) Whether to include sub parents (default value is false)	boolean
File	(Response) A FileInfo object that consists of: File object that consists of: FileId (integer) File Name (string) Folder object that consists of: FolderId (integer) FolderPath Version (integer) Config object that consists of : ConfigurationName (string) ConfigurationId (integer) Member of FileRef model	FileInfo
IsCyclic	(Response) Whether the file reference is self-referential Member of FileRef model	boolean
IsToolbox	(Response) Whether the file reference is a toolbox item Member of FileRef model	integer
ObjectType	(Response) PweObjectType model; one of: ObjType_NoObject = 0 ObjType_File = 1 ObjType_InternalComponent = 2 ObjType_SavedBOM = 3 ObjType_Item = 4 ObjType_CutListItem = 5 Member of FileRef model	PweObjectType

Warnings	(Response) An array of BaseWarningModels; each BaseWarningModel consists of: Message (string) IsBlocking (boolean) IsError (boolean) Member of FileRef model	Collection of BaseWarningModel
References	(Response) The file reference's references; an array of FileRefs; each FileRef consists of: File (FileInfo) IsCyclic (boolean) IsToolbox (integer) ObjectType (PweObjectType) Warnings (Array of BaseWarningModels) References (Array of FileRefs) Member of FileRef model	Collection of FileRef

Response (application/json)

Response (text/json)

Response (application/xml)

Response (text/xml)

See Also

[File Resource Group](#) | [PDM Pro API Web Service](#)

GET **api/{vaultName}/files/{fileId}/{version}/{folderId}/configurations**

Description

Gets the configurations for the specified file.

Parameters

vaultName	(Required URI Parameter) Vault name	string
fileId	(Required URI Parameter) File ID	integer
version	(Required URI Parameter) File version	integer
folderId	(URI Parameter) Folder ID, default is 0	integer
ConfigurationName	(Response) Configuration name (Member of Config Model)	string
ConfigurationId	(Response) Configuration ID (Member of Config Model)	integer

Response (application/json, text/json)

Sample Data

```
[
  {
    "ConfigurationName": "sample string 1",
    "ConfigurationId": 2
  },
  {
    "ConfigurationName": "sample string 1",
    "ConfigurationId": 2
  }
]
```

Response (application/xml, text/xml)

Sample Data

```
<ArrayOfConfig xmlns:i="http://www.w3.org/2001/XMLSchema-instance"
xmlns="http://schemas.datacontract.org/2004/07/SWPDM.Models">
  <Config>
    <ConfigurationId>2</ConfigurationId>
    <ConfigurationName>sample string 1</ConfigurationName>
  </Config>
  <Config>
    <ConfigurationId>2</ConfigurationId>
    <ConfigurationName>sample string 1</ConfigurationName>
  </Config>
</ArrayOfConfig>
```

See Also

[File Resource Group](#) | [PDM Pro API Web Service](#)

GET

api/{vaultName}/files/{fileId}/{version}/{folderId}/download

Description

Gets the specified file.

Parameters

vaultName	(Required URI parameter) Vault name	string
fileId	(Required URI Parameter) File ID	integer
version	(Required URI Parameter) File version	integer
folderId	(URI Parameter) Folder ID, default is 0	integer
Location	(Response) URI location (Member of RedirectResult Model)	URI
Request	(Response) HttpRequestMessage: Version: Major: integer Minor: integer Build: integer Revision: integer MajorRevision: integer MinorRevision: integer Content: HttpContent (array of Headers) Method: HttpMethod (string) RequestUri: URI Headers: array of objects Properties: Dictionary of string/value pairs (Member of RedirectResult Model)	HttpRequestMessage

Response (application/json, text/json)

See Also

GET

api/{vaultName}/files/{fileId}/{version}/{folderId}/info

Description

Gets information about the specified file.

Parameters

vaultName	(Required URI Parameter) Vault name	string
fileId	(Required URI Parameter) File ID	integer
version	(URI Parameter) File version, default value is 0	integer
folderId	(URI Parameter) Folder ID, default value is 0	integer
Id	(Response) File ID (Member of ObjectInfo model)	integer
Name	(Response) File name (Member of ObjectInfo model)	string
Size	(Response) File size (Member of ObjectInfo model)	integer
ModifiedDate	(Response) Modified date (Member of ObjectInfo model)	date
State	(Response) File state (Member of ObjectInfo model)	string
StateId	(Response) File state ID (Member of ObjectInfo model)	integer
ParentFolderId	(Response) Parent folder ID (Member of ObjectInfo model)	integer
Path	(Response) Folder path (Member of ObjectInfo model)	string
Type	(Response) Object Type: Folder = 0 File = 1 Bom = 3 (Member of ObjectInfo model)	ObjectType
IsLocked	(Response) Whether file is locked (checked out) (Member of ObjectInfo model)	integer
LockedBy	(Response) ID of user who checked out the file (Member of ObjectInfo model)	integer
IsShared	(Response) Whether the file is shared (Member of ObjectInfo model)	integer
IsToolbox	(Response) 1 if a Toolbox item, 0 if not (Member of ObjectInfo model)	integer

IsDeleted

(Response) Whether file is deleted
(Member of ObjectInfo model)

integer

Response (application/json, text/json)

Sample Data

```
[
  {
    "Id": 1,
    "Name": "sample string 2",
    "Size": 3,
    "ModifiedDate": "2024-11-27T09:52:30.6655761-05:00",
    "Version": 5,
    "State": "sample string 6",
    "StateId": 7,
    "ParentFolderId": 8,
    "Path": "sample string 9",
    "Type": 0,
    "IsLocked": 10,
    "LockedBy": 11,
    "IsShared": 12,
    "IsToolbox": 13,
    "IsDeleted": 14
  },
  {
    "Id": 1,
    "Name": "sample string 2",
    "Size": 3,
    "ModifiedDate": "2024-11-27T09:52:30.6655761-05:00",
    "Version": 5,
    "State": "sample string 6",
    "StateId": 7,
    "ParentFolderId": 8,
    "Path": "sample string 9",
    "Type": 0,
    "IsLocked": 10,
    "LockedBy": 11,
    "IsShared": 12,
    "IsToolbox": 13,
    "IsDeleted": 14
  }
]
```

Response (application/xml, text/xml)

Sample Data

```
<ArrayOfObjectInfo xmlns:i="http://www.w3.org/2001/XMLSchema-instance"
xmlns="http://schemas.datacontract.org/2004/07/SWPDM.Models">
  <ObjectInfo>
    <Id>1</Id>
    <IsDeleted>14</IsDeleted>
    <IsLocked>10</IsLocked>
    <IsShared>12</IsShared>
    <IsToolbox>13</IsToolbox>
    <LockedBy>11</LockedBy>
    <ModifiedDate>2024-11-27T09:52:30.6655761-05:00</ModifiedDate>
    <Name>sample string 2</Name>
    <ParentFolderId>8</ParentFolderId>
    <Path>sample string 9</Path>
    <Size>3</Size>
    <State>sample string 6</State>
    <StateId>7</StateId>
    <Type>Folder</Type>
    <Version>5</Version>
  </ObjectInfo>
  <ObjectInfo>
    <Id>1</Id>
    <IsDeleted>14</IsDeleted>
    <IsLocked>10</IsLocked>
    <IsShared>12</IsShared>
    <IsToolbox>13</IsToolbox>
    <LockedBy>11</LockedBy>
    <ModifiedDate>2024-11-27T09:52:30.6655761-05:00</ModifiedDate>
    <Name>sample string 2</Name>
    <ParentFolderId>8</ParentFolderId>
    <Path>sample string 9</Path>
    <Size>3</Size>
    <State>sample string 6</State>
  </ObjectInfo>
</ArrayOfObjectInfo>
```

```
<StateId>7</StateId>
<Type>Folder</Type>
<Version>5</Version>
</ObjectInfo>
</ArrayOfObjectInfo>
```

See Also

[File Resource Group](#) | [PDM Pro API Web Service](#)

GET **api/{vaultName}/files/{fileId}/{version}/{folderId}/info/extended**

Description

Gets extended version information for a specified file.

Parameters

vaultName	(Required URI Parameter) Vault name	string
fileId	(Required URI Parameter) File ID	integer
version	(Required URI Parameter) File version	integer
folderId	(URI Parameter) Folder ID, default is 0	integer
StateId	(Response) State ID (Member of VersionInfoExtended Member)	integer
State	(Response) State name (Member of VersionInfoExtended Member)	string
Workflow	(Response) Workflow (Member of VersionInfoExtended Member)	string
Category	(Response) Category (Member of VersionInfoExtended Member)	string
ReplicatedTo	(Response) Replicated to (Member of VersionInfoExtended Member)	string
Branches	(Response) Branches (Member of VersionInfoExtended Member)	string

Response (application/json, text/json)

Sample Data

```
{
  "StateId": 1,
  "State": "sample string 2",
  "Workflow": "sample string 3",
  "Category": "sample string 4",
  "ReplicatedTo": "sample string 5",
  "Branches": "sample string 6"
}
```

Response (application/xml, text/xml)

Sample Data

```
<VersionInfoExtended xmlns:i="http://www.w3.org/2001/XMLSchema-instance"
xmlns="http://schemas.datacontract.org/2004/07/SWPDM.Models">
  <Branches>sample string 6</Branches>
  <Category>sample string 4</Category>
  <ReplicatedTo>sample string 5</ReplicatedTo>
  <State>sample string 2</State>
  <StateId>1</StateId>
  <Workflow>sample string 3</Workflow>
</VersionInfoExtended>
```

See Also

GET `api/{vaultName}/files/{fileId}/{version}/{folderId}/references?configId={configId}`

Description

GET: `api/{VaultName}/files/{FileID}/{Version}/references` Get file references
Gets the top level file references of the specified file.

Parameters

vaultName	(Required URI parameter) Vault name	string
fileId	(Required URI parameter) File ID	integer
version	(Required URI parameter) File version	integer
folderId	(URI parameter) Folder ID (default value is 0)	integer
configId	(URI parameter) Configuration ID (default value is -1)	integer
File	(Response) A FileInfo object that consists of: File object that consists of: FileId (integer) FileName (string) Folder object that consists of: FolderId (integer) FolderPath Version (integer) Config object that consists of : ConfigurationName (string) ConfigurationId (integer) Member of FileRef model	FileInfo
IsCyclic	(Response) Whether the file reference is self-referential Member of FileRef model	boolean
IsToolbox	(Response) Whether the file reference is a toolbox item Member of FileRef model	integer
ObjectType	(Response) PweObjectType model; one of: ObjType_NoObject = 0 ObjType_File = 1 ObjType_InternalComponent = 2 ObjType_SavedBOM = 3 ObjType_Item = 4 ObjType_CutListItem = 5 Member of FileRef model	PweObjectType
Warnings	(Response) An array of BaseWarningModels; each BaseWarningModel consists of: Message (string) IsBlocking (boolean) IsError (boolean)	Collection of BaseWarningModel

Member of FileRef model		
References	(Response) The file reference's references; an array of FileRefs; each FileRef consists of:	
	File (FileInfo)	
	IsCyclic (boolean)	
	IsToolbox (integer)	
	ObjectType (PweObjectType)	
	Warnings (Array of BaseWarningModels)	
	References (Array of FileRefs)	Collection of FileRef
Member of FileRef model; see Remarks		

Response (application/json)

Response (text/json)

Response (application/xml)

Response (text/xml)

See Also

[File Resource Group](#) | [PDM Pro API Web Service](#)

GET

api/{vaultName}/files/{fileId}/{version}/{folderId}/thumbnails

Description

Gets a specified file's thumbnail.

Parameters

vaultName	(Required URI Parameter) Vault name	string
fileId	(Required URI Parameter) File ID	integer
version	(Required URI Parameter) File version	integer
folderId	(URI Parameter) Folder ID, default is 0	integer
Location	(Response) URI location (Member of RedirectResult Model)	URI
Request	(Response) HttpRequestMessage: Version: Major: integer Minor: integer Build: integer Revision: integer MajorRevision: integer MinorRevision: integer Content: HttpContent: collection of Headers Method HttpMethod: string RequestUri: URI Headers: array Properties: Dictionary of key/value pairs (Member of RedirectResult Model)	HttpRequestMessage

Response (application/json, text/json)

See Also

GET

api/{vaultName}/files/{fileId}/{version}/{folderId}/transitions

Description

Gets the file transitions for the specified file.

Parameters

vaultName	(Required URI Parameter) Vault name	string
fileId	(Required URI Parameter) File ID	integer
version	(URI Parameter) File version, default is -1	integer
folderId	(URI Parameter) Folder ID, default is 0	integer
TransitionId	(Response) Transition ID (Member of HistoryTransition Model)	integer
VersionNo	(Response) Version number (Member of HistoryTransition Model)	integer
Comment	(Response) Comment (Member of HistoryTransition Model)	string
Date	(Response) Date (Member of HistoryTransition Model)	date
SourceState	(Response) Source StateInfo: StateId: integer StateName: string IgnorePreviousPermissions: integer (Member of HistoryTransition Model)	StateInfo
DestinationState	(Response) Destination StateInfo: StateId: integer StateName: string IgnorePreviousPermissions: integer (Member of HistoryTransition Model)	StateInfo
User	(Response) UserInfo: UserName: string UserId: integer (Member of HistoryTransition Model)	UserInfo

Response (application/json, text/json)

Sample Data

```
[
  {
    "TransitionId": 1,
    "VersionNo": 2,
    "Comment": "sample string 3",
    "Date": "2024-11-27T09:52:30.6915737-05:00",
    "SourceState": {
      "StateId": 1,
      "StateName": "sample string 2",
      "IgnorePreviousPermissions": 3
    },
  },
]
```

```

    "DestinationState": {
      "StateId": 1,
      "StateName": "sample string 2",
      "IgnorePreviousPermissions": 3
    },
    "User": {
      "UserName": "sample string 1",
      "UserId": 2
    }
  },
  {
    "TransitionId": 1,
    "VersionNo": 2,
    "Comment": "sample string 3",
    "Date": "2024-11-27T09:52:30.6915737-05:00",
    "SourceState": {
      "StateId": 1,
      "StateName": "sample string 2",
      "IgnorePreviousPermissions": 3
    },
    "DestinationState": {
      "StateId": 1,
      "StateName": "sample string 2",
      "IgnorePreviousPermissions": 3
    },
    "User": {
      "UserName": "sample string 1",
      "UserId": 2
    }
  }
}
]

```

Response (application/xml, text/xml)

Sample Data

```

<ArrayOfHistoryTransition xmlns:i="http://www.w3.org/2001/XMLSchema-instance"
xmlns="http://schemas.datacontract.org/2004/07/SWPDM.Models">
  <HistoryTransition>
    <Comment>sample string 3</Comment>
    <Date>2024-11-27T09:52:30.6915737-05:00</Date>
    <DestinationState>
      <IgnorePreviousPermissions>3</IgnorePreviousPermissions>
      <StateId>1</StateId>
      <StateName>sample string 2</StateName>
    </DestinationState>
    <SourceState>
      <IgnorePreviousPermissions>3</IgnorePreviousPermissions>
      <StateId>1</StateId>
      <StateName>sample string 2</StateName>
    </SourceState>
    <TransitionId>1</TransitionId>
    <User>
      <UserId>2</UserId>
      <UserName>sample string 1</UserName>
    </User>
    <VersionNo>2</VersionNo>
  </HistoryTransition>
  <HistoryTransition>
    <Comment>sample string 3</Comment>
    <Date>2024-11-27T09:52:30.6915737-05:00</Date>
    <DestinationState>
      <IgnorePreviousPermissions>3</IgnorePreviousPermissions>
      <StateId>1</StateId>
      <StateName>sample string 2</StateName>
    </DestinationState>
    <SourceState>
      <IgnorePreviousPermissions>3</IgnorePreviousPermissions>
      <StateId>1</StateId>
      <StateName>sample string 2</StateName>
    </SourceState>
    <TransitionId>1</TransitionId>
    <User>
      <UserId>2</UserId>
      <UserName>sample string 1</UserName>
    </User>
    <VersionNo>2</VersionNo>
  </HistoryTransition>
</ArrayOfHistoryTransition>

```

See Also

GET

api/{vaultName}/files/{fileId}/{version}/{folderId}/variables

Description

Gets configuration variable information for the specified file.

Parameters

vaultName	(Required URI Parameter) Vault name	string
fileId	(Required URI Parameter) File ID	integer
version	(Required URI Parameter) File version	integer
folderId	(URI Parameter) Folder ID, default is 0	integer
ConfigurationName	(Response) Name of configuration (Member of ConfigInfo Model)	string
ConfigurationId	(Response) ID of configuration (Member of ConfigInfo Model)	integer
Models	(Response) Collection of VariableInfo: VarId: integer VarName: string VarValue: string VarType: VarTypeNone = 0 VarTypeText = 1 VarTypeInt = 2 VarTypeFloat = 3 VarTypeBool = 4 VarTypeDate = 5 Mandatory: boolean VersionFree: boolean (Member of ConfigInfo Model)	Collection of VariableInfo

Response (application/json, text/json)

Sample Data

```
[
  {
    "Models": [
      {
        "VarId": 1,
        "VarName": "sample string 2",
        "VarValue": "sample string 3",
        "VarType": 0,
        "Mandatory": true,
        "VersionFree": true
      },
      {
        "VarId": 1,
        "VarName": "sample string 2",
        "VarValue": "sample string 3",
        "VarType": 0,
        "Mandatory": true,
        "VersionFree": true
      }
    ],
    "ConfigurationName": "sample string 1",
    "ConfigurationId": 2
  }
]
```

```

},
{
  "Models": [
    {
      "VarId": 1,
      "VarName": "sample string 2",
      "VarValue": "sample string 3",
      "VarType": 0,
      "Mandatory": true,
      "VersionFree": true
    },
    {
      "VarId": 1,
      "VarName": "sample string 2",
      "VarValue": "sample string 3",
      "VarType": 0,
      "Mandatory": true,
      "VersionFree": true
    }
  ],
  "ConfigurationName": "sample string 1",
  "ConfigurationId": 2
}
]

```

Response (application/xml, text/xml)

Sample Data

```

<ArrayOfConfigInfo xmlns:i="http://www.w3.org/2001/XMLSchema-instance"
xmlns="http://schemas.datacontract.org/2004/07/SWPDM.Models">
  <ConfigInfo>
    <ConfigurationId>2</ConfigurationId>
    <ConfigurationName>sample string 1</ConfigurationName>
    <Models>
      <VariableInfo>
        <Mandatory>true</Mandatory>
        <VarId>1</VarId>
        <VarName>sample string 2</VarName>
        <VarType>VarTypeNone</VarType>
        <VarValue>sample string 3</VarValue>
        <VersionFree>true</VersionFree>
      </VariableInfo>
      <VariableInfo>
        <Mandatory>true</Mandatory>
        <VarId>1</VarId>
        <VarName>sample string 2</VarName>
        <VarType>VarTypeNone</VarType>
        <VarValue>sample string 3</VarValue>
        <VersionFree>true</VersionFree>
      </VariableInfo>
    </Models>
  </ConfigInfo>
  <ConfigInfo>
    <ConfigurationId>2</ConfigurationId>
    <ConfigurationName>sample string 1</ConfigurationName>
    <Models>
      <VariableInfo>
        <Mandatory>true</Mandatory>
        <VarId>1</VarId>
        <VarName>sample string 2</VarName>
        <VarType>VarTypeNone</VarType>
        <VarValue>sample string 3</VarValue>
        <VersionFree>true</VersionFree>
      </VariableInfo>
      <VariableInfo>
        <Mandatory>true</Mandatory>
        <VarId>1</VarId>
        <VarName>sample string 2</VarName>
        <VarType>VarTypeNone</VarType>
        <VarValue>sample string 3</VarValue>
        <VersionFree>true</VersionFree>
      </VariableInfo>
    </Models>
  </ConfigInfo>
</ArrayOfConfigInfo>

```

See Also

[File Resource Group](#) | [PDM Pro API Web Service](#)

POST

api/{vaultName}/folders/info

Description

POST: api/{VaultName}/folders/info Get folder info

Gets information about specified folders in the specified vault.

Parameters

vaultName	(URI parameter) Name of vault	string
WarningMessage	(Response) Warning message	string
	Member of FolderInfoExtended model	
Folder	(Response) Folder model that consists of:	Folder
	- Folder ID - Folder path Member of FolderInfoExtended model	
FolderName	(Response) Folder name	string
	Member of FolderInfoExtended model	
ParentFolderId	(Response) ID of parent folder	integer
	Member of FolderInfoExtended model	

Request (application/json, text/json)

Array of folder IDs as body parameter

Sample Data

```
[
  1,
  2
]
```

Request (application/xml, text/xml)

Array of folder IDs as body parameter

Sample Data

```
<ArrayOfint xmlns:i="http://www.w3.org/2001/XMLSchema-instance"
xmlns="http://schemas.microsoft.com/2003/10/Serialization/Arrays">
  <int>1</int>
  <int>2</int>
</ArrayOfint>
```

Request (application/x-www-form-urlencoded)

Array of folder IDs as body parameter

Response (application/json, text/json)

Sample Data

```
[
  {
    "WarningMessage": "sample string 1",
    "Folder": {
      "FolderId": 1,
      "FolderPath": "sample string 2"
    },
    "FolderName": "sample string 2",
    "ParentFolderId": 3
  },
  {
    "WarningMessage": "sample string 1",
    "Folder": {
      "FolderId": 1,
      "FolderPath": "sample string 2"
    },
    "FolderName": "sample string 2",
    "ParentFolderId": 3
  }
]
```

Response (application/xml, text/xml)

Sample Data

```
<ArrayOfFolderInfoExtended xmlns:i="http://www.w3.org/2001/XMLSchema-instance"
xmlns="http://schemas.datacontract.org/2004/07/SWPDM.Models">
  <FolderInfoExtended>
    <Folder>
      <FolderId>1</FolderId>
      <FolderPath>sample string 2</FolderPath>
    </Folder>
    <FolderName>sample string 2</FolderName>
    <ParentFolderId>3</ParentFolderId>
    <WarningMessage>sample string 1</WarningMessage>
  </FolderInfoExtended>
  <FolderInfoExtended>
    <Folder>
      <FolderId>1</FolderId>
      <FolderPath>sample string 2</FolderPath>
    </Folder>
    <FolderName>sample string 2</FolderName>
    <ParentFolderId>3</ParentFolderId>
    <WarningMessage>sample string 1</WarningMessage>
  </FolderInfoExtended>
</ArrayOfFolderInfoExtended>
```

See Also

[Folder Resource Group](#) | [PDM Pro API Web Service](#)

GET

api/{vaultName}/folders/{folderId}

Description

GET: api/{VaultName}/folders/{FolderID} or api/{VaultName}/folders/{FolderID}/info Get folder info

Gets information for the specified folder.

Parameters

vaultName	(URI parameter) Vault name (required)	string
folderId	(URI parameter) Folder ID (required)	integer
Folder	(Response) A Folder object that consists of: FolderId (integer) FolderPath (string) Member of FolderInfo model	Folder
FolderName	(Response) Folder name Member of FolderInfo model	string
ParentFolderId	(Response) Parent folder ID Member of FolderInfo model	integer

Response (application/json, text/json)

Sample Data

```
{
  "Folder": {
    "FolderId": 1,
    "FolderPath": "sample string 2"
  },
  "FolderName": "sample string 1",
  "ParentFolderId": 2
}
```

Response (application/xml, text/xml)

Sample Data

```
<FolderInfo xmlns:i="http://www.w3.org/2001/XMLSchema-instance"
xmlns="http://schemas.datacontract.org/2004/07/SWPDM.Models">
  <Folder>
    <FolderId>1</FolderId>
    <FolderPath>sample string 2</FolderPath>
  </Folder>
  <FolderName>sample string 1</FolderName>
  <ParentFolderId>2</ParentFolderId>
</FolderInfo>
```

See Also

GET

api/{vaultName}/folders/{folderId}/browse

Description

GET: api/{VaultName}/folders/{FolderID}/browse Get browse folder

Gets the files and folders in the specified folder.

Parameters

vaultName	(URI parameter) Vault name (required)	string
folderId	(URI parameter) ID of folder in which to browse (required)	integer
Id	(Response) ID of object	integer
	Member of ObjectInfo model	
Name	(Response) Name of object	string
	Member of ObjectInfo model	
Size	(Response) Size of object	integer
	Member of ObjectInfo model	
ModifiedDate	(Response) Modification date	date
	Member of ObjectInfo model	
Version	(Response) Version	integer
	Member of ObjectInfo model	
State	(Response) State	string
	Member of ObjectInfo model	
StateId	(Response) State ID	integer
	Member of ObjectInfo model	
ParentFolderId	(Response) Parent folder ID	integer
	Member of ObjectInfo model	
Path	(Response) Folder path	string
	Member of ObjectInfo model	

Type	(Response) An ObjectType; one of: Folder = 0 File = 1 Bom = 3 Member of ObjectInfo model	ObjectType
IsLocked	(Response) Whether the object is locked Member of ObjectInfo model	integer
LockedBy	(Response) Locked by user Member of ObjectInfo model	integer
IsShared	(Response) Whether the object is shared Member of ObjectInfo model	integer
IsToolbox	(Response) Whether the object is in the toolbox Member of ObjectInfo model	integer
IsDeleted	(Response) Whether the object is deleted Member of ObjectInfo model	integer

Response (application/json, text/json)

Sample Data

```
[
  {
    "Id": 1,
    "Name": "sample string 2",
    "Size": 3,
    "ModifiedDate": "2024-11-27T09:52:31.3283221-05:00",
    "Version": 5,
    "State": "sample string 6",
    "StateId": 7,
    "ParentFolderId": 8,
    "Path": "sample string 9",
    "Type": 0,
    "IsLocked": 10,
    "LockedBy": 11,
    "IsShared": 12,
    "IsToolbox": 13,
    "IsDeleted": 14
  },
  {
    "Id": 1,
    "Name": "sample string 2",
    "Size": 3,
    "ModifiedDate": "2024-11-27T09:52:31.3283221-05:00",
    "Version": 5,
    "State": "sample string 6",
    "StateId": 7,
    "ParentFolderId": 8,
    "Path": "sample string 9",
    "Type": 0,
    "IsLocked": 10,
    "LockedBy": 11,
    "IsShared": 12,
```

```
    "IsToolbox": 13,  
    "IsDeleted": 14  
  }  
]
```

Response (application/xml, text/xml)

Sample Data

```
<ArrayOfObjectInfo xmlns:i="http://www.w3.org/2001/XMLSchema-instance"  
xmlns="http://schemas.datacontract.org/2004/07/SWPDM.Models">  
  <ObjectInfo>  
    <Id>1</Id>  
    <IsDeleted>14</IsDeleted>  
    <IsLocked>10</IsLocked>  
    <IsShared>12</IsShared>  
    <IsToolbox>13</IsToolbox>  
    <LockedBy>11</LockedBy>  
    <ModifiedDate>2024-11-27T09:52:31.3283221-05:00</ModifiedDate>  
    <Name>sample string 2</Name>  
    <ParentFolderId>8</ParentFolderId>  
    <Path>sample string 9</Path>  
    <Size>3</Size>  
    <State>sample string 6</State>  
    <StateId>7</StateId>  
    <Type>Folder</Type>  
    <Version>5</Version>  
  </ObjectInfo>  
  <ObjectInfo>  
    <Id>1</Id>  
    <IsDeleted>14</IsDeleted>  
    <IsLocked>10</IsLocked>  
    <IsShared>12</IsShared>  
    <IsToolbox>13</IsToolbox>  
    <LockedBy>11</LockedBy>  
    <ModifiedDate>2024-11-27T09:52:31.3283221-05:00</ModifiedDate>  
    <Name>sample string 2</Name>  
    <ParentFolderId>8</ParentFolderId>  
    <Path>sample string 9</Path>  
    <Size>3</Size>  
    <State>sample string 6</State>  
    <StateId>7</StateId>  
    <Type>Folder</Type>  
    <Version>5</Version>  
  </ObjectInfo>  
</ArrayOfObjectInfo>
```

Example

See the examples for [api/{vaultName}/authenticate](#).

Example

[Modify File Datacards.postman_collection.json](#)

Remarks

This operation returns an array of ObjectInfo objects.

See Also

[Folder Resource Group](#) | [PDM Pro API Web Service](#)

GET

api/{vaultName}/folders/{folderId}/datacard

Description

GET: api/{VaultName}/folders/{FolderID}/datacard Get folder data card

Gets the data card for the specified folder and vault.

Parameters

vaultName	(URI parameter) Vault name (required)	string
folderId	(URI parameter) Folder ID (required)	integer
VariablesWithWriteAllConfigs	(Response) Array of IDs of variables with write-all configurations Member of DataCard model	Collection of integer
ConfigVarInfo	(Response) Array of ConfigInfo_DataCards; each ConfigInfo_DataCard consists of: Models (Array of VariableInfo_DataCards; each VariableInfo_DataCard consists of: ReadOnly (boolean) Multiline (boolean) VarId (integer) VarName (string) VarValue (string) VarType (one of: VarTypeNone = 0 VarTypeText = 1 VarTypeInt = 2 VarTypeFloat = 3 VarTypeBool = 4 VarTypeDate = 5) Mandatory (boolean) VersionFree (boolean)) ConfigurationName (string) Configuration Id (integer) Member of DataCard model	Collection of ConfigInfo_DataCard
CardVariableInfo	(Response) Array of VariableExtraInfos; each VariableExtraInfo consists of: Variable Id (integer) VariableValueOptions (array of optional string values) Member of DataCard model	Collection of VariableExtraInfo

Response (application/json, text/json)

Sample Data

```

{
  "VariablesWithWriteAllConfigs": [
    1,
    2
  ],
  "ConfigVarInfo": [
    {
      "Models": [
        {
          "ReadOnly": true,
          "Multiline": true,
          "VarId": 3,
          "VarName": "sample string 4",
          "VarValue": "sample string 5",
          "VarType": 0,
          "Mandatory": true,
          "VersionFree": true
        },
        {
          "ReadOnly": true,
          "Multiline": true,
          "VarId": 3,
          "VarName": "sample string 4",
          "VarValue": "sample string 5",
          "VarType": 0,
          "Mandatory": true,
          "VersionFree": true
        }
      ],
      "ConfigurationName": "sample string 1",
      "ConfigurationId": 2
    },
    {
      "Models": [
        {
          "ReadOnly": true,
          "Multiline": true,
          "VarId": 3,
          "VarName": "sample string 4",
          "VarValue": "sample string 5",
          "VarType": 0,
          "Mandatory": true,
          "VersionFree": true
        },
        {
          "ReadOnly": true,
          "Multiline": true,
          "VarId": 3,
          "VarName": "sample string 4",
          "VarValue": "sample string 5",
          "VarType": 0,
          "Mandatory": true,
          "VersionFree": true
        }
      ],
      "ConfigurationName": "sample string 1",
      "ConfigurationId": 2
    }
  ],
  "CardVariableInfo": [
    {
      "VariableId": 1,
      "VariableValueOptions": [
        "sample string 1",
        "sample string 2"
      ]
    },
    {
      "VariableId": 1,
      "VariableValueOptions": [
        "sample string 1",
        "sample string 2"
      ]
    }
  ]
}

```

Response (application/xml, text/xml)

Sample Data

```

<DataCard xmlns:i="http://www.w3.org/2001/XMLSchema-instance"
xmlns="http://schemas.datacontract.org/2004/07/SWPDM.Models">

```

```

<CardVariableInfo>
  <VariableExtraInfo>
    <VariableId>1</VariableId>
    <VariableValueOptions xmlns:d4p1="http://schemas.microsoft.com/2003/10/Serialization/Arrays">
      <d4p1:string>sample string 1</d4p1:string>
      <d4p1:string>sample string 2</d4p1:string>
    </VariableValueOptions>
  </VariableExtraInfo>
  <VariableExtraInfo>
    <VariableId>1</VariableId>
    <VariableValueOptions xmlns:d4p1="http://schemas.microsoft.com/2003/10/Serialization/Arrays">
      <d4p1:string>sample string 1</d4p1:string>
      <d4p1:string>sample string 2</d4p1:string>
    </VariableValueOptions>
  </VariableExtraInfo>
</CardVariableInfo>
<ConfigVarInfo>
  <ConfigInfo_DataCard>
    <ConfigurationId>2</ConfigurationId>
    <ConfigurationName>sample string 1</ConfigurationName>
    <Models>
      <VariableInfo_DataCard>
        <Mandatory>true</Mandatory>
        <VarId>3</VarId>
        <VarName>sample string 4</VarName>
        <VarType>VarTypeNone</VarType>
        <VarValue>sample string 5</VarValue>
        <VersionFree>true</VersionFree>
        <Multiline>true</Multiline>
        <ReadOnly>true</ReadOnly>
      </VariableInfo_DataCard>
      <VariableInfo_DataCard>
        <Mandatory>true</Mandatory>
        <VarId>3</VarId>
        <VarName>sample string 4</VarName>
        <VarType>VarTypeNone</VarType>
        <VarValue>sample string 5</VarValue>
        <VersionFree>true</VersionFree>
        <Multiline>true</Multiline>
        <ReadOnly>true</ReadOnly>
      </VariableInfo_DataCard>
    </Models>
  </ConfigInfo_DataCard>
  <ConfigInfo_DataCard>
    <ConfigurationId>2</ConfigurationId>
    <ConfigurationName>sample string 1</ConfigurationName>
    <Models>
      <VariableInfo_DataCard>
        <Mandatory>true</Mandatory>
        <VarId>3</VarId>
        <VarName>sample string 4</VarName>
        <VarType>VarTypeNone</VarType>
        <VarValue>sample string 5</VarValue>
        <VersionFree>true</VersionFree>
        <Multiline>true</Multiline>
        <ReadOnly>true</ReadOnly>
      </VariableInfo_DataCard>
      <VariableInfo_DataCard>
        <Mandatory>true</Mandatory>
        <VarId>3</VarId>
        <VarName>sample string 4</VarName>
        <VarType>VarTypeNone</VarType>
        <VarValue>sample string 5</VarValue>
        <VersionFree>true</VersionFree>
        <Multiline>true</Multiline>
        <ReadOnly>true</ReadOnly>
      </VariableInfo_DataCard>
    </Models>
  </ConfigInfo_DataCard>
</ConfigVarInfo>
<VariablesWithWriteAllConfigs xmlns:d2p1="http://schemas.microsoft.com/2003/10/Serialization/Arrays">
  <d2p1:int>1</d2p1:int>
  <d2p1:int>2</d2p1:int>
</VariablesWithWriteAllConfigs>
</DataCard>

```

See Also

[Data Card Resource Group](#) | [PDM Pro API Web Service](#)

DELETE

api/{vaultName}/folders/{folderId}?destroy={destroy}

Description

DELETE: api/{VaultName}/folders/{FolderID} Delete folder

Deletes the specified folder.

Parameters

vaultName	(URI parameter) Vault name (required)	string
folderId	(URI parameter) Folder ID (required)	integer
destroy	(URI parameter) Whether to delete the folder (default value is false)	boolean
Id	(Response) Deleted folder ID	integer
	Member of ObjectInfoShort model	
Name	(Response) Deleted folder name	string
	Member of ObjectInfoShort model	
Type	(Response) An ObjectType object; one of: Folder = 0 File = 1 Bom = 3	ObjectType
	Member of ObjectInfoShort model	
Status	(Response) A StatusOperation object; one of: Success = 0 Failure = 1	StatusOperation
	Member of ObjectInfoShort model	
Warning	(Response) A BaseWarningModel object that consists of: Message (string) IsBlocking (boolean) IsError (boolean)	BaseWarningModel
	Member of ObjectInfoShort model	

Response (application/json, text/json)

Sample Data

```
{
  "Id": 1,
  "Name": "sample string 2",
  "Type": 0,
  "Status": 0,
  "Warning": null
}
```

Response (application/xml, text/xml)

Sample Data

```
<ObjectInfoShort xmlns:i="http://www.w3.org/2001/XMLSchema-instance"
xmlns="http://schemas.datacontract.org/2004/07/SWPDM.Models">
  <Id>1</Id>
  <Name>sample string 2</Name>
  <Status>Success</Status>
  <Type>Folder</Type>
  <Warning i:nil="true" />
</ObjectInfoShort>
```

See Also

[Folder Resource Group](#) | [PDM Pro API Web Service](#)

GET

api/{vaultName}/folders/{folderId}/info

Description

GET: api/{VaultName}/folders/{FolderID} or api/{VaultName}/folders/{FolderID}/info Get folder info

Gets information for the specified folder.

Parameters

vaultName	(URI parameter) Vault name (required)	string
folderId	(URI parameter) Folder ID (required)	integer
Folder	(Response) A Folder object that consists of: FolderId (integer) FolderPath (string) Member of FolderInfo model	Folder
FolderName	(Response) Folder name Member of FolderInfo model	string
ParentFolderId	(Response) Parent folder ID Member of FolderInfo model	integer

Response (application/json, text/json)

Sample Data

```
{
  "Folder": {
    "FolderId": 1,
    "FolderPath": "sample string 2"
  },
  "FolderName": "sample string 1",
  "ParentFolderId": 2
}
```

Response (application/xml, text/xml)

Sample Data

```
<FolderInfo xmlns:i="http://www.w3.org/2001/XMLSchema-instance"
xmlns="http://schemas.datacontract.org/2004/07/SWPDM.Models">
  <Folder>
    <FolderId>1</FolderId>
    <FolderPath>sample string 2</FolderPath>
  </Folder>
  <FolderName>sample string 1</FolderName>
  <ParentFolderId>2</ParentFolderId>
</FolderInfo>
```

See Also

PUT

api/{vaultName}/folders/{parentFolderId}

Description

PUT: api/{VaultName}/folders/{ParentFolderID} Add folder

Adds a folder to the specified folder.

Parameters

vaultName	(URI parameter) Vault name (required)	string
parentFolderId	(URI parameter) Parent folder ID (required)	integer
Id	(Response) Created folder ID	integer
	Member of ObjectInfoShort model	
Name	(Response) Created folder name	string
	Member of ObjectInfoShort model	
Type	(Response) An ObjectType object; one of: Folder = 0 File = 1 Bom = 3	ObjectType
	Member of ObjectInfoShort model	
Status	(Response) A StatusOperation object; one of: Success = 0 Failure = 1	StatusOperation
	Member of ObjectInfoShort model	
Warning	(Response) A BaseWarningModel object that consists of: Message (string) IsBlocking (boolean) IsError (boolean)	BaseWarningModel
	Member of ObjectInfoShort model	

Request (application/json, text/json)

Sample Data

"sample string 1"

Request (application/xml, text/xml)

Sample Data

```
<string xmlns="http://schemas.microsoft.com/2003/10/Serialization/">sample string 1</string>
```

Request (application/x-www-form-urlencoded)

Response (application/json, text/json)

Sample Data

```
{
  "Id": 1,
  "Name": "sample string 2",
  "Type": 0,
  "Status": 0,
  "Warning": null
}
```

Response (application/xml, text/xml)

Sample Data

```
<ObjectInfoShort xmlns:i="http://www.w3.org/2001/XMLSchema-instance"
xmlns="http://schemas.datacontract.org/2004/07/SWPDM.Models">
  <Id>1</Id>
  <Name>sample string 2</Name>
  <Status>Success</Status>
  <Type>Folder</Type>
  <Warning i:nil="true" />
</ObjectInfoShort>
```

Remarks

This operation takes a string body parameter that is the name of the folder to add.

See Also

[Folder Resource Group](#) | [PDM Pro API Web Service](#)

GET

api/{vaultName}/groups

Description

GET: api/{VaultName}/groups or api/{VaultName}/groups/all Get groups

Gets the groups in the specified vault.

Parameters

vaultName	(URI parameter) Vault name (required)	string
GroupId	(Response) Group ID	integer
	Member of GroupInfo model	
GroupName	(Response) Group name	string
	Member of GroupInfo model	

Response (application/json, text/json)

Sample Data

```
[
  {
    "GroupId": 1,
    "GroupName": "sample string 2"
  },
  {
    "GroupId": 1,
    "GroupName": "sample string 2"
  }
]
```

Response (application/xml, text/xml)

Sample Data

```
<ArrayOfGroupInfo xmlns:i="http://www.w3.org/2001/XMLSchema-instance"
xmlns="http://schemas.datacontract.org/2004/07/SWPDM.Models">
  <GroupInfo>
    <GroupId>1</GroupId>
    <GroupName>sample string 2</GroupName>
  </GroupInfo>
  <GroupInfo>
    <GroupId>1</GroupId>
    <GroupName>sample string 2</GroupName>
  </GroupInfo>
</ArrayOfGroupInfo>
```

Remarks

This operation returns an array of GroupInfo objects.

See Also

GET

api/{vaultName}/groups/all

Description

GET: api/{VaultName}/groups or api/{VaultName}/groups/all Get groups

Gets the groups in the specified vault.

Parameters

vaultName	(URI parameter) Vault name (required)	string
GroupId	(Response) Group ID	integer
	Member of GroupInfo model	
GroupName	(Response) Group name	string
	Member of GroupInfo model	

Response (application/json, text/json)

Sample Data

```
[
  {
    "GroupId": 1,
    "GroupName": "sample string 2"
  },
  {
    "GroupId": 1,
    "GroupName": "sample string 2"
  }
]
```

Response (application/xml, text/xml)

Sample Data

```
<ArrayOfGroupInfo xmlns:i="http://www.w3.org/2001/XMLSchema-instance"
xmlns="http://schemas.datacontract.org/2004/07/SWPDM.Models">
  <GroupInfo>
    <GroupId>1</GroupId>
    <GroupName>sample string 2</GroupName>
  </GroupInfo>
  <GroupInfo>
    <GroupId>1</GroupId>
    <GroupName>sample string 2</GroupName>
  </GroupInfo>
</ArrayOfGroupInfo>
```

Remarks

This operation returns an array of GroupInfo objects.

See Also

[Group Resource Group](#) | [PDM Pro API Web Service](#)

GET

api/{vaultName}/groups/{groupId}

Description

GET: api/{VaultName}/groups/{GroupID} or api/{VaultName}/groups/{GroupID}/info Get group info

Gets information about the specified group.

Parameters

vaultName	(URI parameter) Vault name (required)	string
groupId	(URI and response parameter) Group ID (URI required)	integer
	Member of GroupInfo model	
GroupName	(Response) Group name	string
	Member of GroupInfo model	

Response (application/json, text/json)

Sample Data

```
{
  "GroupId": 1,
  "GroupName": "sample string 2"
}
```

Response (application/xml, text/xml)

Sample Data

```
<GroupInfo xmlns:i="http://www.w3.org/2001/XMLSchema-instance"
xmlns="http://schemas.datacontract.org/2004/07/SWPDM.Models">
  <GroupId>1</GroupId>
  <GroupName>sample string 2</GroupName>
</GroupInfo>
```

See Also

[Group Resource Group](#) | [PDM Pro API Web Service](#)

GET

api/{vaultName}/groups/{groupId}/info

Description

GET: api/{VaultName}/groups/{GroupID} or api/{VaultName}/groups/{GroupID}/info Get group info

Gets information about the specified group.

Parameters

vaultName	(URI parameter) Vault name (required)	string
groupId	(URI and response parameter) Group ID (URI required) Member of GroupInfo model	integer
GroupName	(Response) Group name Member of GroupInfo model	string

Response (application/json, text/json)

Sample Data

```
{
  "GroupId": 1,
  "GroupName": "sample string 2"
}
```

Response (application/xml, text/xml)

Sample Data

```
<GroupInfo xmlns:i="http://www.w3.org/2001/XMLSchema-instance"
xmlns="http://schemas.datacontract.org/2004/07/SWPDM.Models">
  <GroupId>1</GroupId>
  <GroupName>sample string 2</GroupName>
</GroupInfo>
```

See Also

[Group Resource Group](#) | [PDM Pro API Web Service](#)

GET

api/{vaultName}/info

Description

GET: api/{VaultName} or api/{VaultName}/info Get vault properties

Gets the properties of the specified vault.

Parameters

vaultName	(URI parameter) Vault name (required)	string
Version	(Response) Vault version	integer
	Member of VaultProp model	
VaultType	(Response) Type of vault	string
	Member of VaultProp model	
ArchiveServer	(Response) Archive server	string
	Member of VaultProp model	
DatabaseName	(Response) Database name	string
	Member of VaultProp model	
DatabaseServer	(Response) Database server	string
	Member of VaultProp model	
VaultID	(Response) Vault ID	globally unique identifier
	Member of VaultProp model	

Response (application/json, text/json)

Sample Data

```
{
  "Version": 1,
  "VaultType": "sample string 2",
  "ArchiveServer": "sample string 3",
  "DatabaseName": "sample string 4",
  "DatabaseServer": "sample string 5",
  "VaultID": "e2a87d6d-8f9f-4c1c-a40c-39b81d9f9f56"
}
```

Response (application/xml, text/xml)

Sample Data

```
<VaultProp xmlns:i="http://www.w3.org/2001/XMLSchema-instance"
xmlns="http://schemas.datacontract.org/2004/07/SWPDM.Models">
```

```
<ArchiveServer>sample string 3</ArchiveServer>  
<DatabaseName>sample string 4</DatabaseName>  
<DatabaseServer>sample string 5</DatabaseServer>  
<VaultID>e2a87d6d-8f9f-4c1c-a40c-39b81d9f9f56</VaultID>  
<VaultType>sample string 2</VaultType>  
<Version>1</Version>  
</VaultProp>
```

See Also

[Vault Resource Group](#) | [PDM Pro API Web Service](#)

POST

api/{vaultName}/notifications

Description

POST: api/{VaultName}/notifications Send message

Sends the specified message.

Parameters

vaultName	(URI parameter) Vault name (required)	string
RecipientId	(Body parameter) Recipient user ID	integer
	Member of MsgInfo model	
Subject	(Body parameter) Subject text	string
	Member of MsgInfo model	
Message	(Body parameter) Message text	string
	Member of MsgInfo model	
Password	(Body parameter) Password	string
	Member of MsgInfo model	

Request (application/json, text/json)

Sample Data

```
{
  "RecipientId": 1,
  "Subject": "sample string 2",
  "Message": "sample string 3",
  "Password": "sample string 4"
}
```

Request (application/xml, text/xml)

Sample Data

```
<MsgInfo xmlns:i="http://www.w3.org/2001/XMLSchema-instance" xmlns="http://schemas.datacontract.org/2004/07/SWPDM.Models">
  <Message>sample string 3</Message>
  <Password>sample string 4</Password>
  <RecipientId>1</RecipientId>
  <Subject>sample string 2</Subject>
</MsgInfo>
```

Request (application/x-www-form-urlencoded)

Response (application/json, text/json)

Returns the status of the operation; true if successful, false if not

Sample Data

true

Response (application/xml, text/xml)

Returns the status of the operation; true if successful, false if not

Sample Data

```
<boolean xmlns="http://schemas.microsoft.com/2003/10/Serialization/">true</boolean>
```

Remarks

This operation:

- takes MsgInfo body parameters.
- returns a boolean status.

See Also

[Notification Resource Group](#) | [PDM Pro API Web Service](#)

GET **api/{vaultName}/notifications?all={all}&pageNo={pageNo}&pageSize={pageSize}****Description**

GET: api/{VaultName}/notifications Get user notifications

Gets the user notifications.

Parameters

vaultName	(URI parameter) Vault name (required)	string
all	(URI parameter) Whether to retrieve all notifications (default value is true)	boolean
pageNo	(URI parameter) Page number (default value is 0)	integer
pageSize	(URI parameter) Page size (default value is 0)	integer
MessageId	(Response) Message ID Member of Messages model	integer
Type	(Response) MsgType object; one of: Msgt_All = 0 Msgt_UserMsg = 1 Msgt_NotificationFile = 2 Msgt_NotificationFolder = 3 Msgt_NotificationErp = 4 Msgt_NotificationItem = 5 Msgt_NotificationTask = 6 Msgt_NotificationUpgr = 7 Member of Messages model	MsgType
Subject	(Response) Subject text Member of Messages model	string
Message	(Response) Message text Member of Messages model	string
Time	(Response) Date Member of Messages model	date

Sender	(Response) A UserInfo object that consists of:	UserInfo
	UserName (string)	
	UserId (integer)	
	Member of Messages model	
New	(Response) Whether the notification is new	boolean
	Member of Messages model	

Response (application/json, text/json)

Sample Data

```
[
  {
    "MessageId": 1,
    "Type": 0,
    "Subject": "sample string 2",
    "Message": "sample string 3",
    "Time": "2024-11-27T09:52:31.0644265-05:00",
    "Sender": {
      "UserName": "sample string 1",
      "UserId": 2
    },
    "New": true
  },
  {
    "MessageId": 1,
    "Type": 0,
    "Subject": "sample string 2",
    "Message": "sample string 3",
    "Time": "2024-11-27T09:52:31.0644265-05:00",
    "Sender": {
      "UserName": "sample string 1",
      "UserId": 2
    },
    "New": true
  }
]
```

Response (application/xml, text/xml)

Sample Data

```
<ArrayOfMessages xmlns:i="http://www.w3.org/2001/XMLSchema-instance"
xmlns="http://schemas.datacontract.org/2004/07/SWPDM.Models">
  <Messages>
    <Message>sample string 3</Message>
    <MessageId>1</MessageId>
    <New>true</New>
    <Sender>
      <UserId>2</UserId>
      <UserName>sample string 1</UserName>
    </Sender>
    <Subject>sample string 2</Subject>
    <Time>2024-11-27T09:52:31.0644265-05:00</Time>
    <Type>Msgt_All</Type>
  </Messages>
  <Messages>
    <Message>sample string 3</Message>
    <MessageId>1</MessageId>
    <New>true</New>
    <Sender>
      <UserId>2</UserId>
      <UserName>sample string 1</UserName>
    </Sender>
    <Subject>sample string 2</Subject>
    <Time>2024-11-27T09:52:31.0644265-05:00</Time>
    <Type>Msgt_All</Type>
  </Messages>
</ArrayOfMessages>
```

Remarks

This operation can return an array of Message objects.

See Also

[Notification Resource Group](#) | [PDM Pro API Web Service](#)

POST

api/{vaultName}/notifications/markRead

Description

POST: api/{vaultName}/notifications/markRead Mark message as read

Marks a notification as read.

Parameters

vaultName	(URI parameter) Vault name (required)	string
IsValid	(Response) Whether the mark is valid Member of ValidationOptionOfint32	boolean
Warning	(Response) A BaseWarningModel object that consists of: Message (string) IsBlocking (boolean) IsError (boolean) Member of ValidationOptionOfint32	BaseWarningModel
Value	(Response) Value of response Member of ValidationOptionOfint32	integer

Request (application/json, text/json)

Sample Data

```
[
  1,
  2
]
```

Request (application/xml, text/xml)

Sample Data

```
<ArrayOfint xmlns:i="http://www.w3.org/2001/XMLSchema-instance"
xmlns="http://schemas.microsoft.com/2003/10/Serialization/Arrays">
  <int>1</int>
  <int>2</int>
</ArrayOfint>
```

Request (application/x-www-form-urlencoded)

Response (application/json, text/json)

Sample Data

```
[
  {
    "IsValid": false,
    "Warning": null,
    "Value": 0
  },
  {
    "IsValid": false,
```

```
    "Warning": null,  
    "Value": 0  
  }  
]
```

Response (application/xml, text/xml)

Sample Data

```
<ArrayOfValidationOptionOfint xmlns:i="http://www.w3.org/2001/XMLSchema-instance"  
xmlns="http://schemas.datacontract.org/2004/07/SWPDM.Models">  
  <ValidationOptionOfint />  
  <ValidationOptionOfint />  
</ArrayOfValidationOptionOfint>
```

Remarks

This operation:

- takes a body parameter array of integers that are notification IDs.
- returns an array of ValidationOptionOfint objects.

See Also

[Notification Resource Group](#) | [PDM Pro API Web Service](#)

GET

api/{vaultName}/progress/{guid}/result

Description

GET: api/{vaultName}/progress/{guid}/result

Gets the result of the specified operation.

Parameters

vaultName	(URI parameter) Vault name (required)	string
guid	(URI parameter) Operation GUID (required) (see Remarks)	string

Response (application/json, text/json)

Sample Data

{}

Response (application/xml, text/xml)

Sample Data

<z:anyType xmlns:i="http://www.w3.org/2001/XMLSchema-instance" xmlns:z="http://schemas.microsoft.com/2003/10/Serialization/" />

Example

[Upload SOLIDWORKS Files to PDM Vault.postman_collection.json](#) | [Check in SOLIDWORKS Files in PDM Vault.postman_collection.json](#)

Remarks

The operation GUID can be found in the response of [api/{vaultName}/files/{changesetId}/finishadd \(Put\)](#).

See Also

[Progress Resource Group](#) | [PDM Pro API Web Service](#)

GET

api/{vaultName}/progress/{guid}/status

Description

GET: api/{vaultName}/progress/{guid}/status Get operation status

Gets the status of the specified operation.

Parameters

vaultName	(URI parameter) Vault name (required)	string
guid	(URI parameter) Operation GUID (required) (See Remarks)	string
Version	(Response) A Version model that consists of: - Major (integer) - Minor (integer) - Build (integer) - Revision (integer) - MajorRevision (integer) - MinorRevision (integer) Member of HttpResponseMessage model	Version
Content	(Response) Entity body and content headers Member of HttpResponseMessage model	HttpContent
StatusCode	(Response) Status code; see https://en.wikipedia.org/wiki/List_of_HTTP_status_codes Member of HttpResponseMessage model	HttpStatusCode
ReasonPhrase	(Response) Reason Member of HttpResponseMessage model	string
Headers	(Response) Array of headers Member of HttpResponseMessage model	Collection of Object
RequestMessage	(Response) An HttpRequestMessage object that consists of: Version (Version model) Content (HttpContent object consisting of Headers array) Method (HttpMethod object consisting of Method string) RequestUri (URI) Headers (array of objects) Properties (Dictionary of string [key] and Object [value]) Member of HttpResponseMessage model	HttpRequestMessage
IsSuccessStatusCode	(Response) True if successful, false if not Member of HttpResponseMessage model	boolean

Example

[Upload SOLIDWORKS Files to PDM Vault.postman_collection.json](#) | [Check in SOLIDWORKS Files in PDM Vault.postman_collection.json](#)

Remarks

The operation GUID can be found in the response of [api/{vaultName}/files/{changesetId}/finishadd \(Put\)](#).

See Also

[Progress Resource Group](#) | [PDM Pro API Web Service](#)

GET

api/{vaultName}/search

Description

Gets objects in the specified vault.

Parameters

vaultName	(Required URI parameter) Vault name	string
Id	(Response) ID of vault object	integer
	Member of VaultObject model	
Type	(Response) An ObjectType; one of: Folder = 0 File = 1 Bom = 3 Member of VaultObject model	ObjectType

Response (application/json, text/json)

Sample Data

```
[
  {
    "Id": 1,
    "Type": 0
  },
  {
    "Id": 1,
    "Type": 0
  }
]
```

Response (application/xml, text/xml)

Sample Data

```
<ArrayOfVaultObject xmlns:i="http://www.w3.org/2001/XMLSchema-instance"
xmlns="http://schemas.datacontract.org/2004/07/SWPDM.Models">
  <VaultObject>
    <Id>1</Id>
    <Type>Folder</Type>
  </VaultObject>
  <VaultObject>
    <Id>1</Id>
    <Type>Folder</Type>
  </VaultObject>
</ArrayOfVaultObject>
```

See Also

[Search Resource Group](#) | [PDM Pro API Web Service](#)

POST

api/{vaultName}/search

Description

Gets objects in the vault that contain the specified string.

Parameters

vaultName	(Required URI parameter) Vault name	string
Id	(Response) ID of vault object	integer
	Member of VaultObject model	
Type	(Response) An ObjectType; one of: Folder = 0 File = 1 Bom = 3	ObjectType
	Member of VaultObject model	

Request (application/json, text/json)

Body parameter contains the string to search the vault for

Sample Data

```
"sample string 1"
```

Request (application/xml, text/xml)

Body parameter contains the string to search the vault for

Sample Data

```
<string xmlns="http://schemas.microsoft.com/2003/10/Serialization/">sample string 1</string>
```

Request (application/x-www-form-urlencoded)

Response (application/json, text/json)

Sample Data

```
[
  {
    "Id": 1,
    "Type": 0
  },
  {
    "Id": 1,
    "Type": 0
  }
]
```

Response (application/xml, text/xml)

Sample Data

```
<ArrayOfVaultObject xmlns:i="http://www.w3.org/2001/XMLSchema-instance"
xmlns="http://schemas.datacontract.org/2004/07/SWPDM.Models">
  <VaultObject>
    <Id>1</Id>
    <Type>Folder</Type>
  </VaultObject>
  <VaultObject>
    <Id>1</Id>
    <Type>Folder</Type>
  </VaultObject>
</ArrayOfVaultObject>
```

Remarks

This operation:

- takes a body parameter that contains the string to search the vault for.
- returns an array of VaultObjects.

See Also

[Search Resource Group](#) | [PDM Pro API Web Service](#)

POST

api/{vaultName}/searchvariables

Description

Specifies parameters and variables for a search.

Parameters

vaultName	(Required URI parameter) Name of vault	string
Name	(Body and Response parameter) File name or folder name or empty; supports "%" wildcard search (Member of SearchVariables Model) (See Remarks)	string
ObjectTypeCriteria	(Body parameter) Files = 1, Folders = 2, or Files and folders = 3 (Member of SearchVariables Model)	SearchObjectTypeCriteria
StartPath	(Body parameter) Relative folder path where the search begins; if empty, search starts at vault root (Member of SearchVariables Model)	string
PathCriteria	(Body parameter) Current folder = 1, Current folder and subfolders = 2, All folders = 3 (Member of SearchVariables Model)	SearchPathCriteria
VersionCriteria	(Body parameter) Search in latest version of files = 1 Search in all versions of files = 2 (Member of SearchVariables Model)	SearchVersionCriteria
SearchOperand	(Body parameter) None = 0 AND = 1 OR = 2 (Member of SearchVariables Model)	SearchOperand
Variables	(Body parameter) List of variables to search for; can be empty (Member of SearchVariables Model) (See Remarks)	Collection of SearchVariable
Id	(Response) File ID (Member of ObjectInfo Model)	integer
Size	(Response) File size (Member of ObjectInfo Model)	integer
ModifiedDate	(Response) Modification date (Member of ObjectInfo Model)	date

Version	(Response) File version (Member of ObjectInfo Model)	integer
State	(Response) Workflow state (Member of ObjectInfo Model)	string
StateId	(Response) Workflow state ID (Member of ObjectInfo Model)	integer
ParentFolderId	(Response) Parent folder ID (Member of ObjectInfo Model)	integer
Path	(Response) Folder path (Member of ObjectInfo Model)	string
Type	(Response) Folder = 0 File = 1 Bom = 3 (Member of ObjectInfo Model)	ObjectType
IsLocked	(Response) Whether the file is checked out (Member of ObjectInfo Model)	integer
LockedBy	(Response) ID of user who checked out the file (Member of ObjectInfo Model)	integer
IsShared	(Response) Whether the file is shared (Member of ObjectInfo Model)	integer
IsToolbox	(Response) Whether the file is a toolbox item (Member of ObjectInfo Model)	integer
IsDeleted	(Response) Whether the file is deleted (Member of ObjectInfo Model)	integer

Request (application/json, text/json)

Sample Data

```
{
  "Name": "sample string 1",
  "ObjectTypeCriteria": 1,
  "StartPath": "sample string 2",
  "PathCriteria": 1,
  "VersionCriteria": 1,
  "SearchOperand": 0,
  "Variables": [
    {
      "VariableName": "sample string 1",
      "SearchValue": "sample string 2"
    },
    {
      "VariableName": "sample string 1",
      "SearchValue": "sample string 2"
    }
  ]
}
```

Request (application/xml, text/xml)

Sample Data

```
<SearchVariablesModel xmlns:i="http://www.w3.org/2001/XMLSchema-instance"
xmlns="http://schemas.datacontract.org/2004/07/SWPDM.Models">
  <Name>sample string 1</Name>
  <ObjectTypeCriteria>File</ObjectTypeCriteria>
```

```

<PathCriteria>CurrentFolder</PathCriteria>
<SearchOperand>NONE</SearchOperand>
<StartPath>sample string 2</StartPath>
<Variables>
  <SearchVariable>
    <SearchValue>sample string 2</SearchValue>
    <VariableName>sample string 1</VariableName>
  </SearchVariable>
  <SearchVariable>
    <SearchValue>sample string 2</SearchValue>
    <VariableName>sample string 1</VariableName>
  </SearchVariable>
</Variables>
<VersionCriteria>LatestVersion</VersionCriteria>
</SearchVariablesModel>

```

Request (application/x-www-form-urlencoded)

Response (application/json, text/json)

Sample Data

```

[
  {
    "Id": 1,
    "Name": "sample string 2",
    "Size": 3,
    "ModifiedDate": "2024-11-27T09:51:59.716492-05:00",
    "Version": 5,
    "State": "sample string 6",
    "StateId": 7,
    "ParentFolderId": 8,
    "Path": "sample string 9",
    "Type": 0,
    "IsLocked": 10,
    "LockedBy": 11,
    "IsShared": 12,
    "IsToolbox": 13,
    "IsDeleted": 14
  },
  {
    "Id": 1,
    "Name": "sample string 2",
    "Size": 3,
    "ModifiedDate": "2024-11-27T09:51:59.716492-05:00",
    "Version": 5,
    "State": "sample string 6",
    "StateId": 7,
    "ParentFolderId": 8,
    "Path": "sample string 9",
    "Type": 0,
    "IsLocked": 10,
    "LockedBy": 11,
    "IsShared": 12,
    "IsToolbox": 13,
    "IsDeleted": 14
  }
]

```

Response (application/xml, text/xml)

Sample Data

```

<ArrayOfObjectInfo xmlns:i="http://www.w3.org/2001/XMLSchema-instance"
xmlns="http://schemas.datacontract.org/2004/07/SWPDM.Models">
  <ObjectInfo>
    <Id>1</Id>
    <IsDeleted>14</IsDeleted>
    <IsLocked>10</IsLocked>
    <IsShared>12</IsShared>
    <IsToolbox>13</IsToolbox>
    <LockedBy>11</LockedBy>
    <ModifiedDate>2024-11-27T09:51:59.716492-05:00</ModifiedDate>
    <Name>sample string 2</Name>
    <ParentFolderId>8</ParentFolderId>
    <Path>sample string 9</Path>
    <Size>3</Size>
    <State>sample string 6</State>
    <StateId>7</StateId>
    <Type>Folder</Type>
    <Version>5</Version>
  </ObjectInfo>
  <ObjectInfo>
    <Id>1</Id>
    <IsDeleted>14</IsDeleted>
    <IsLocked>10</IsLocked>
    <IsShared>12</IsShared>
    <IsToolbox>13</IsToolbox>
    <LockedBy>11</LockedBy>
    <ModifiedDate>2024-11-27T09:51:59.716492-05:00</ModifiedDate>
    <Name>sample string 2</Name>
    <ParentFolderId>8</ParentFolderId>
    <Path>sample string 9</Path>
    <Size>3</Size>
    <State>sample string 6</State>
    <StateId>7</StateId>
    <Type>Folder</Type>
    <Version>5</Version>
  </ObjectInfo>
</ArrayOfObjectInfo>

```

```
</ObjectInfo>
<ObjectInfo>
  <Id>1</Id>
  <IsDeleted>14</IsDeleted>
  <IsLocked>10</IsLocked>
  <IsShared>12</IsShared>
  <IsToolbox>13</IsToolbox>
  <LockedBy>11</LockedBy>
  <ModifiedDate>2024-11-27T09:51:59.716492-05:00</ModifiedDate>
  <Name>sample string 2</Name>
  <ParentFolderId>8</ParentFolderId>
  <Path>sample string 9</Path>
  <Size>3</Size>
  <State>sample string 6</State>
  <StateId>7</StateId>
  <Type>Folder</Type>
  <Version>5</Version>
</ObjectInfo>
</ArrayOfObjectInfo>
```

Example

[Use Search Variables.postman_collection.json](#)

Remarks

If Name and Variables are provided, search returns all items matching variables and name (+ other criteria).

If Name is empty and Variables are provided, search returns all items matching the variables (+ other criteria).

If Variables are empty and only Name is provided, search returns all items matching the name (+ other criteria).

If Name and Variables are empty, search returns all items based on other criteria.

See Also

[Search Resource Group | PDM Pro API Web Service](#)

POST

api/{vaultName}/state/transitions

Description

POST: api/{vaultName}/state/transitions Get available transitions for multiple files

Gets the transitions available for multiple files.

Parameters

vaultName	(URI parameter) Vault name (required)	string
TransitionId	(Response) Transition ID Member of AvailableTransition model	integer
TransitionName	(Response) Transition name Member of AvailableTransition model	string
Revoke	(Response) Whether revokable Member of AvailableTransition model	boolean
Commits	(Response) Number of users who have performed this parallel transition; Commits <= Required Member of AvailableTransition model	integer
Required	(Response) Number of users required to perform this parallel transition Member of AvailableTransition model	integer
MustEnterComments	(Response) Whether must enter comments Member of AvailableTransition model	boolean

Request (application/json, text/json)

Body parameter array of file IDs

Sample Data

```
[  
  1,  
  2  
]
```

Request (application/xml, text/xml)

Body parameter array of file IDs

Sample Data

```
<ArrayOfint xmlns:i="http://www.w3.org/2001/XMLSchema-instance"  
xmlns="http://schemas.microsoft.com/2003/10/Serialization/Arrays">  
  <int>1</int>
```

```
<int>2</int>
</ArrayOfint>
```

Request (application/x-www-form-urlencoded)

Body parameter array of file IDs

Response (application/json, text/json)

Sample Data

```
[
  {
    "TransitionId": 1,
    "TransitionName": "sample string 2",
    "Revoke": true,
    "Commits": 4,
    "Required": 5,
    "MustEnterComments": true
  },
  {
    "TransitionId": 1,
    "TransitionName": "sample string 2",
    "Revoke": true,
    "Commits": 4,
    "Required": 5,
    "MustEnterComments": true
  }
]
```

Response (application/xml, text/xml)

Sample Data

```
<ArrayOfAvailableTransition xmlns:i="http://www.w3.org/2001/XMLSchema-instance"
xmlns="http://schemas.datacontract.org/2004/07/SWPDM.Models">
  <AvailableTransition>
    <Commits>4</Commits>
    <MustEnterComments>true</MustEnterComments>
    <Required>5</Required>
    <Revoke>true</Revoke>
    <TransitionId>1</TransitionId>
    <TransitionName>sample string 2</TransitionName>
  </AvailableTransition>
  <AvailableTransition>
    <Commits>4</Commits>
    <MustEnterComments>true</MustEnterComments>
    <Required>5</Required>
    <Revoke>true</Revoke>
    <TransitionId>1</TransitionId>
    <TransitionName>sample string 2</TransitionName>
  </AvailableTransition>
</ArrayOfAvailableTransition>
```

Remarks

This operation:

- takes an array of body parameters that are file IDs.
- returns an array of AvailableTransition objects.

See Also

[State Transition Resource Group](#) | [PDM Pro API Web Service](#)

GET

api/{vaultName}/state/{documentId}/transitions

Description

Get available transitions for single file

Gets the transitions available for the specified file.

Parameters

vaultName	(URI parameter) Vault name (required)	string
documentId	(URI parameter) Document ID (required)	integer
TransitionId	(Response) Transition ID Member of AvailableTransition model	integer
TransitionName	(Response) Transition name Member of AvailableTransition model	string
Revoke	(Response) 1 if the parallel transition's approval is revokable, 0 if not Member of AvailableTransition model	boolean
Commits	(Response) Whether commits Member of AvailableTransition model	integer
Required	(Response) Whether required Member of AvailableTransition model	integer
MustEnterComments	(Response) Whether must enter comments Member of AvailableTransition model	boolean

Response (application/json, text/json)

Sample Data

```
[
  {
    "TransitionId": 1,
    "TransitionName": "sample string 2",
    "Revoke": true,
    "Commits": 4,
    "Required": 5,
    "MustEnterComments": true
  },
  {
    "TransitionId": 1,
    "TransitionName": "sample string 2",
    "Revoke": true,
    "Commits": 4,
```

```
    "Required": 5,  
    "MustEnterComments": true  
  }  
]
```

Response (application/xml, text/xml)

Sample Data

```
<ArrayOfAvailableTransition xmlns:i="http://www.w3.org/2001/XMLSchema-instance"  
xmlns="http://schemas.datacontract.org/2004/07/SWPDM.Models">  
  <AvailableTransition>  
    <Commits>4</Commits>  
    <MustEnterComments>true</MustEnterComments>  
    <Required>5</Required>  
    <Revoke>true</Revoke>  
    <TransitionId>1</TransitionId>  
    <TransitionName>sample string 2</TransitionName>  
  </AvailableTransition>  
  <AvailableTransition>  
    <Commits>4</Commits>  
    <MustEnterComments>true</MustEnterComments>  
    <Required>5</Required>  
    <Revoke>true</Revoke>  
    <TransitionId>1</TransitionId>  
    <TransitionName>sample string 2</TransitionName>  
  </AvailableTransition>  
</ArrayOfAvailableTransition>
```

Remarks

This operation can return an array of AvailableTransition objects.

See Also

[State Transition Resource Group](#) | [PDM Pro API Web Service](#)

GET `api/{vaultName}/state/{documentId}/transitions?folderId={folderId}`

Description

Gets the transitions available for the specified file.

Parameters

vaultName	(Required URI parameter) Name of vault	string
documentId	(Required URI parameter) File ID	integer
folderId	(URI parameter) Folder ID, default is 0	integer
TransitionId	(Response) Transition ID (Member of AvailableTransition Model)	integer
TransitionName	(Response) Transition name (Member of AvailableTransition Model)	string
Revoke	(Response) Whether a revoke (Member of AvailableTransition Model)	boolean
Commits	(Response) Number of users who have performed this parallel transition; Commits <= Required (Member of AvailableTransition Model)	integer
Required	(Response) Number of required (Member of AvailableTransition Model)	integer
MustEnterComments	(Response) Whether must enter comments (Member of AvailableTransition Model)	boolean

Response (application/json, text/json)

Sample Data

```
[
  {
    "TransitionId": 1,
    "TransitionName": "sample string 2",
    "Revoke": true,
    "Commits": 4,
    "Required": 5,
    "MustEnterComments": true
  },
  {
    "TransitionId": 1,
    "TransitionName": "sample string 2",
    "Revoke": true,
    "Commits": 4,
    "Required": 5,
    "MustEnterComments": true
  }
]
```

Response (application/xml, text/xml)

Sample Data

```
<ArrayOfAvailableTransition xmlns:i="http://www.w3.org/2001/XMLSchema-instance"
xmlns="http://schemas.datacontract.org/2004/07/SWPDM.Models">
  <AvailableTransition>
    <Commits>4</Commits>
    <MustEnterComments>true</MustEnterComments>
  </AvailableTransition>
  <AvailableTransition>
    <Commits>4</Commits>
    <MustEnterComments>true</MustEnterComments>
  </AvailableTransition>
</ArrayOfAvailableTransition>
```

```
<Required>5</Required>
<Revoke>true</Revoke>
<TransitionId>1</TransitionId>
<TransitionName>sample string 2</TransitionName>
</AvailableTransition>
<AvailableTransition>
  <Commits>4</Commits>
  <MustEnterComments>true</MustEnterComments>
  <Required>5</Required>
  <Revoke>true</Revoke>
  <TransitionId>1</TransitionId>
  <TransitionName>sample string 2</TransitionName>
</AvailableTransition>
</ArrayOfAvailableTransition>
```

See Also

[State Transition Resource Group](#) | [PDM Pro API Web Service](#)

GET

api/{vaultName}/state/{documentId}/{folderId}/transitions

Description

Gets the transitions available for the specified file.

Parameters

vaultName	(Required URI parameter) Name of vault	string
documentId	(Required URI parameter) File ID	integer
folderId	(URI parameter) Folder ID, default is 0	integer
TransitionId	(Response) Transition ID (Member of AvailableTransition Model)	integer
TransitionName	(Response) Transition name (Member of AvailableTransition Model)	string
Revoke	(Response) Whether a revoke (Member of AvailableTransition Model)	boolean
Commits	(Response) Number of users who have performed this parallel transition; Commits <= Required (Member of AvailableTransition Model)	integer
Required	(Response) Number of required (Member of AvailableTransition Model)	integer
MustEnterComments	(Response) Whether must enter comments (Member of AvailableTransition Model)	boolean

Response (application/json, text/json)

Sample Data

```
[
  {
    "TransitionId": 1,
    "TransitionName": "sample string 2",
    "Revoke": true,
    "Commits": 4,
    "Required": 5,
    "MustEnterComments": true
  },
  {
    "TransitionId": 1,
    "TransitionName": "sample string 2",
    "Revoke": true,
    "Commits": 4,
    "Required": 5,
    "MustEnterComments": true
  }
]
```

Response (application/xml, text/xml)

Sample Data

```
<ArrayOfAvailableTransition xmlns:i="http://www.w3.org/2001/XMLSchema-instance"
xmlns="http://schemas.datacontract.org/2004/07/SWPDM.Models">
  <AvailableTransition>
    <Commits>4</Commits>
    <MustEnterComments>true</MustEnterComments>
    <Required>5</Required>
    <Revoke>true</Revoke>
    <TransitionId>1</TransitionId>
    <TransitionName>sample string 2</TransitionName>
  </AvailableTransition>
  <AvailableTransition>
    <Commits>4</Commits>
    <MustEnterComments>true</MustEnterComments>
    <Required>5</Required>
    <Revoke>true</Revoke>
    <TransitionId>1</TransitionId>
    <TransitionName>sample string 2</TransitionName>
  </AvailableTransition>
</ArrayOfAvailableTransition>
```

See Also

[State Transition Resource Group](#) | [PDM Pro API Web Service](#)

GET **api/{vaultName}/state/{documentId}/{folderId}/{transitionId}/references**

Description

GET: api/{vaultName}/state/{documentId}/{folderId}/{transitionId}/references Get all references

Gets all references for the specified file and transition.

Parameters

vaultName	(URI parameter) Vault name (required)	string
documentId	(URI parameter) Document ID (required)	integer
folderId	(URI parameter) Folder ID (required)	integer
transitionId	(URI parameter) Transition ID (required)	integer
File	(Response) A FileInfoConfigLess object that consists of: File (File object that consists of FileId (integer) and FileName (string)) Folder (Folder object that consists of FolderId (integer) and FolderPath (string)) Version Member of FileRefOfFileInfoConfigLess model	FileInfoConfigLess
IsToolbox	(Response) Whether in toolbox Member of FileRefOfFileInfoConfigLess model	integer
ObjectType	(Response) "File", "Folder", or "Bom" Member of FileRefOfFileInfoConfigLess model	String

Response (application/json)

Array of FileRefOfFileInfoConfigLess objects

Response (text/json)

Array of FileRefOfFileInfoConfigLess objects

Response (application/xml)

Array of FileRefOfFileInfoConfigLess objects

Response (text/xml)

Array of FileRefOfFileInfoConfigLess objects

See Also

GET

api/{vaultName}/state/{transitionId}

Description

GET: api/{vaultName}/state/{transitionId} Get transition info

Gets information about the specified transition.

Parameters

vaultName	(URI parameter) Vault name (required)	string
transitionId	(URI and response parameter) Transition ID (URI required) Member of TransitionInfo model	integer
TransitionName	(Response) Transition name Member of TransitionInfo model	string
Type	(Response) A TransitionType; one of: Normal = 0 Automatic = 1 Parallel = 2 Member of TransitionInfo model	TransitionType
Authentication	(Response) Whether authentication is required Member of TransitionInfo model	boolean

Response (application/json, text/json)

Sample Data

```
{
  "TransitionName": "sample string 1",
  "TransitionId": 2,
  "Type": 0,
  "Authentication": true
}
```

Response (application/xml, text/xml)

Sample Data

```
<TransitionInfo xmlns:i="http://www.w3.org/2001/XMLSchema-instance"
xmlns="http://schemas.datacontract.org/2004/07/SWPDM.Models">
  <Authentication>true</Authentication>
  <TransitionId>2</TransitionId>
  <TransitionName>sample string 1</TransitionName>
  <Type>Normal</Type>
</TransitionInfo>
```

See Also

POST api/{vaultName}/state/{transitionId}/changestate?revoke={revoke}

Description

POST: api/{vaultName}/state/{transitionId}/changestate Change state

Changes the state of the specified documents.

Parameters

vaultName	(URI parameter) Vault name (required)	string
transitionId	(URI parameter) Transition ID (required)	integer
revoke	(URI parameter) Whether a revoke (default value is false)	boolean
Comment	(Body parameter) Comment	string
NotificationComment	(Body parameter) Notification comment	string
Documents	(Body parameter) Array of file IDs	Collection of integer
NotifyUsers	(Body parameter) Array of user IDs	Collection of integer
Password	(Body parameter) Password	string
Id	(Response) File ID	integer
IsSuccess	(Response) Whether transition is successful	boolean
Warning	(Response) A BaseWarningModel object that consists of: Message (string) IsBlocking (boolean) IsError (boolean)	BaseWarningModel

Request (application/json, text/json)

Sample Data

```
{
  "Comment": "sample string 1",
  "NotificationComment": "sample string 2",
  "Documents": [
    1,
    2
  ],
  "NotifyUsers": [
    1,
    2
  ],
  "Password": "sample string 3"
}
```

Request (application/xml, text/xml)

Sample Data

```
<TransitionModel xmlns:i="http://www.w3.org/2001/XMLSchema-instance"
xmlns="http://schemas.datacontract.org/2004/07/SWPDM.Models">
  <Comment>sample string 1</Comment>
  <Documents xmlns:d2p1="http://schemas.microsoft.com/2003/10/Serialization/Arrays">
    <d2p1:int>1</d2p1:int>
  </Documents>
  <NotifyUsers>
    <d2p1:int>1</d2p1:int>
    <d2p1:int>2</d2p1:int>
  </NotifyUsers>
  <Password>sample string 3</Password>
</TransitionModel>
```

```

    <d2p1:int>2</d2p1:int>
  </Documents>
  <NotificationComment>sample string 2</NotificationComment>
  <NotifyUsers xmlns:d2p1="http://schemas.microsoft.com/2003/10/Serialization/Arrays">
    <d2p1:int>1</d2p1:int>
    <d2p1:int>2</d2p1:int>
  </NotifyUsers>
  <Password>sample string 3</Password>
</TransitionModel>

```

Request (application/x-www-form-urlencoded)

Response (application/json, text/json)

Sample Data

```

[
  {
    "Id": 1,
    "IsSuccess": true,
    "Warning": null
  },
  {
    "Id": 1,
    "IsSuccess": true,
    "Warning": null
  }
]

```

Response (application/xml, text/xml)

Sample Data

```

<ArrayOfTransitionResultModel xmlns:i="http://www.w3.org/2001/XMLSchema-instance"
xmlns="http://schemas.datacontract.org/2004/07/SWPDM.Models">
  <TransitionResultModel>
    <Id>1</Id>
    <IsSuccess>true</IsSuccess>
    <Warning i:nil="true" />
  </TransitionResultModel>
  <TransitionResultModel>
    <Id>1</Id>
    <IsSuccess>true</IsSuccess>
    <Warning i:nil="true" />
  </TransitionResultModel>
</ArrayOfTransitionResultModel>

```

Remarks

This operation:

- takes TransitionModel body parameters.
- returns an array of TransitionResultModels.

See Also

[State Transition Resource Group](#) | [PDM Pro API Web Service](#)

POST **api/{vaultName}/state/{transitionId}/DynamicNotificationUsers****Description**

POST: api/{vaultName}/state/{transitionId}/DynamicNotificationUsers Get dynamic notification users

Gets the users to notify when the specified items undergo the specified transition.

Parameters

vaultName	(URI parameter) Vault name (required)	string
transitionId	(URI parameter) Transition ID (required)	integer
FolderId	(Response) ID folder for which notifications are enabled Member of NotificationInfo model	integer
Users	(Response) Array of UserInfo objects; each UserInfo consists of: UserName (string) UserId (integer) Member of NotificationInfo model	Collection of UserInfo

Request (application/json, text/json)

Array of file IDs is passed as a body parameter

Sample Data

```
[  
  1,  
  2  
]
```

Request (application/xml, text/xml)

Array of file IDs is passed as a body parameter

Sample Data

```
<ArrayOfint xmlns:i="http://www.w3.org/2001/XMLSchema-instance"  
xmlns="http://schemas.microsoft.com/2003/10/Serialization/Arrays">  
  <int>1</int>  
  <int>2</int>  
</ArrayOfint>
```

Request (application/x-www-form-urlencoded)

Array of file IDs is passed as a body parameter

Response (application/json, text/json)**Sample Data**

```
[  
  {  
    "FolderId": 1,  
    "Users": [  
      {  
        "UserName": "sample string 1",  
        "UserId": 2  
      }  
    ],  
  },  
]
```

```

        {
            "UserName": "sample string 1",
            "UserId": 2
        }
    ]
},
{
    "FolderId": 1,
    "Users": [
        {
            "UserName": "sample string 1",
            "UserId": 2
        },
        {
            "UserName": "sample string 1",
            "UserId": 2
        }
    ]
}
]

```

Response (application/xml, text/xml)

Sample Data

```

<ArrayOfNotificationInfo xmlns:i="http://www.w3.org/2001/XMLSchema-instance"
xmlns="http://schemas.datacontract.org/2004/07/SWPDM.Models">
  <NotificationInfo>
    <FolderId>1</FolderId>
    <Users>
      <UserInfo>
        <UserId>2</UserId>
        <UserName>sample string 1</UserName>
      </UserInfo>
      <UserInfo>
        <UserId>2</UserId>
        <UserName>sample string 1</UserName>
      </UserInfo>
    </Users>
  </NotificationInfo>
  <NotificationInfo>
    <FolderId>1</FolderId>
    <Users>
      <UserInfo>
        <UserId>2</UserId>
        <UserName>sample string 1</UserName>
      </UserInfo>
      <UserInfo>
        <UserId>2</UserId>
        <UserName>sample string 1</UserName>
      </UserInfo>
    </Users>
  </NotificationInfo>
</ArrayOfNotificationInfo>

```

Remarks

This operation:

- takes an array of body parameter integers that are file IDs.
- returns an array of NotificationInfos.

See Also

[State Transition Resource Group](#) | [PDM Pro API Web Service](#)

POST**api/{vaultName}/state/{transitionId}/HistoryComments****Description**

POST: api/{vaultName}/state/{transitionId}/HistoryComments Get transition comment history for multiple files

Gets the comment histories for specified files that undergo the specified transition.

Parameters

vaultName	(URI parameter) Vault name (required)	string
transitionId	(URI parameter) Transition ID (required)	integer
Comments	(Response) Array of history comments Member of HistoryTransitionComment model	Collection of string

Request (application/json, text/json)

Array of file IDs passed in the body parameter

Sample Data

```
[  
  1,  
  2  
]
```

Request (application/xml, text/xml)

Array of file IDs passed in a body parameter

Sample Data

```
<ArrayOfint xmlns:i="http://www.w3.org/2001/XMLSchema-instance"  
xmlns="http://schemas.microsoft.com/2003/10/Serialization/Arrays">  
  <int>1</int>  
  <int>2</int>  
</ArrayOfint>
```

Request (application/x-www-form-urlencoded)**Response (application/json, text/json)****Sample Data**

```
{  
  "Comments": [  
    "sample string 1",  
    "sample string 2"  
  ]  
}
```

Response (application/xml, text/xml)**Sample Data**

```
<HistoryTransitionComment xmlns:i="http://www.w3.org/2001/XMLSchema-instance"  
xmlns="http://schemas.datacontract.org/2004/07/SWPDM.Models">  
  <Comments xmlns:d2p1="http://schemas.microsoft.com/2003/10/Serialization/Arrays">  
    <d2p1:string>sample string 1</d2p1:string>  
    <d2p1:string>sample string 2</d2p1:string>  
  </Comments>  
</HistoryTransitionComment>
```

Remarks

This operation:

- takes a body parameter array of integers that are file IDs.
- returns an array of HistoryTransitionComments.

See Also

[State Transition Resource Group](#) | [PDM Pro API Web Service](#)

GET

api/{vaultName}/users

Description

GET: api/{VaultName}/users or api/{VaultName}/users/all Get users

Gets the users of the specified vault.

Parameters

vaultName	(URI parameter) Vault name (required)	string
UserInfo	(Response) A UserInfo object that consists of: UserName (string) UserId (integer) Member of UserInfoFull model	UserInfo
FullName	(Response) User name Member of UserInfoFull model	string
Initials	(Response) User initials Member of UserInfoFull model	string

Response (application/json, text/json)

Sample Data

```
[
  {
    "UserInfo": {
      "UserName": "sample string 1",
      "UserId": 2
    },
    "FullName": "sample string 1",
    "Initials": "sample string 2"
  },
  {
    "UserInfo": {
      "UserName": "sample string 1",
      "UserId": 2
    },
    "FullName": "sample string 1",
    "Initials": "sample string 2"
  }
]
```

Response (application/xml, text/xml)

Sample Data

```
<ArrayOfUserInfoFull xmlns:i="http://www.w3.org/2001/XMLSchema-instance"
xmlns="http://schemas.datacontract.org/2004/07/SWPDM.Models">
  <UserInfoFull>
    <FullName>sample string 1</FullName>
    <Initials>sample string 2</Initials>
    <UserInfo>
      <UserId>2</UserId>
      <UserName>sample string 1</UserName>
    </UserInfo>
  </UserInfoFull>

```

```
<UserInfoFull>
  <FullName>sample string 1</FullName>
  <Initials>sample string 2</Initials>
  <UserInfo>
    <UserId>2</UserId>
    <UserName>sample string 1</UserName>
  </UserInfo>
</UserInfoFull>
</ArrayOfUserInfoFull>
```

Example

See the example for [api/{vaultName}/authenticate](#).

See Also

[User Resource Group](#) | [PDM Pro API Web Service](#)

GET

api/{vaultName}/users/all

Description

GET: api/{VaultName}/users or api/{VaultName}/users/all Get users

Gets the users of the specified vault.

Parameters

vaultName	(URI parameter) Vault name (required)	string
UserInfo	(Response) A UserInfo object that consists of: UserName (string) UserId (integer) Member of UserInfoFull model	UserInfo
FullName	(Response) User name Member of UserInfoFull model	string
Initials	(Response) User initials Member of UserInfoFull model	string

Response (application/json, text/json)

Sample Data

```
[
  {
    "UserInfo": {
      "UserName": "sample string 1",
      "UserId": 2
    },
    "FullName": "sample string 1",
    "Initials": "sample string 2"
  },
  {
    "UserInfo": {
      "UserName": "sample string 1",
      "UserId": 2
    },
    "FullName": "sample string 1",
    "Initials": "sample string 2"
  }
]
```

Response (application/xml, text/xml)

Sample Data

```
<ArrayOfUserInfoFull xmlns:i="http://www.w3.org/2001/XMLSchema-instance"
xmlns="http://schemas.datacontract.org/2004/07/SWPDM.Models">
  <UserInfoFull>
    <FullName>sample string 1</FullName>
    <Initials>sample string 2</Initials>
    <UserInfo>
      <UserId>2</UserId>
      <UserName>sample string 1</UserName>
    </UserInfo>
  </UserInfoFull>
  <UserInfoFull>
    <FullName>sample string 1</FullName>
    <Initials>sample string 2</Initials>
```

```
<UserInfo>
  <UserId>2</UserId>
  <UserName>sample string 1</UserName>
</UserInfo>
</UserInfoFull>
</ArrayOfUserInfoFull>
```

See Also

[User Resource Group](#) | [PDM Pro API Web Service](#)

GET

api/{vaultName}/users/{userId}

Description

GET: api/{VaultName}/users/{UserID} or api/{VaultName}/users/{UserID}/info Get user info

Gets information about the specified user.

Parameters

vaultName	(URI parameter) Vault name (required)	string
userId	(URI parameter) User ID (required)	integer
UserInfo	(Response) A UserInfo object that consists of: UserName (string) UserId (integer) Member of UserInfoFull model	UserInfo
FullName	(Response) User name Member of UserInfoFull model	string
Initials	(Response) User initials Member of UserInfoFull model	string

Response (application/json, text/json)

Sample Data

```
{
  "UserInfo": {
    "UserName": "sample string 1",
    "UserId": 2
  },
  "FullName": "sample string 1",
  "Initials": "sample string 2"
}
```

Response (application/xml, text/xml)

Sample Data

```
<UserInfoFull xmlns:i="http://www.w3.org/2001/XMLSchema-instance"
xmlns="http://schemas.datacontract.org/2004/07/SWPDM.Models">
  <FullName>sample string 1</FullName>
  <Initials>sample string 2</Initials>
  <UserInfo>
    <UserId>2</UserId>
    <UserName>sample string 1</UserName>
  </UserInfo>
</UserInfoFull>
```

See Also

GET

api/{vaultName}/users/{userId}/Extended

Description

GET: api/{VaultName}/users/{UserID}/Extended Get user info extended

Gets extended information about the specified user.

Parameters

vaultName	(URI parameter) Vault name (required)	string
userId	(URI parameter) User ID (required)	integer
UserInfo	(Body parameter) A UserInfo object that consists of: UserName (string) UserId (integer)	UserInfo
	Member of UserInfoExtended model	
	(Response) A UserInfo object that consists of: UserName (string) UserId (integer)	
	Member of UserInfoExtended model	
Email	(Body parameter) (Response) User email	string
	Member of UserInfoExtended model	
FullName	(Body parameter)	string
	Member of UserInfoExtended model	
	(Response) User full name	
Initials	Member of UserInfoExtended model	string
	(Response) User initials	
	Member of UserInfoExtended model	
	Member of UserInfoExtended model	
Phone	(Body parameter)	string
	Member of UserInfoExtended model	
	(Response) User phone	

	Member of UserInfoExtended model	
	(Body parameter) Mobile phone	
Cellphone	Member of UserInfoExtended model (Response) User mobile phone	string
	Member of UserInfoExtended model	

Response (application/json, text/json)

Sample Data

```
{
  "UserInfo": {
    "UserName": "sample string 1",
    "UserId": 2
  },
  "Email": "sample string 1",
  "FullName": "sample string 2",
  "Initials": "sample string 3",
  "Phone": "sample string 4",
  "Cellphone": "sample string 5"
}
```

Response (application/xml, text/xml)

Sample Data

```
<UserInfoExtended xmlns:i="http://www.w3.org/2001/XMLSchema-instance"
xmlns="http://schemas.datacontract.org/2004/07/SWPDM.Models">
  <Cellphone>sample string 5</Cellphone>
  <Email>sample string 1</Email>
  <FullName>sample string 2</FullName>
  <Initials>sample string 3</Initials>
  <Phone>sample string 4</Phone>
  <UserInfo>
    <UserId>2</UserId>
    <UserName>sample string 1</UserName>
  </UserInfo>
</UserInfoExtended>
```

See Also

[User Resource Group](#) | [PDM Pro API Web Service](#)

PDM Pro API Web Service

PUT

api/{vaultName}/users/{userId}/Extended

Description

PUT: api/{VaultName}/users/{UserID}/Extended Set user info extended

Saves information about the specified user.

Parameters

vaultName	(URI parameter) Vault name (required)	string
userId	(URI parameter) User ID (required)	integer
UserInfo	(Response) A UserInfo object that consists of: UserName (string) UserId (integer) Member of UserInfoExtended model	UserInfo

	(Body parameter) A UserInfo object that consists of: UserName (string) UserId (integer) Member of UserInfoExtended model	
Email	(Response) User email Member of UserInfoExtended model (Body parameter)	string
FullName	(Response) User full name Member of UserInfoExtended model (Body parameter) Member of UserInfoExtended model	string
Initials	(Response) User initials Member of UserInfoExtended model (Body parameter) Member of UserInfoExtended model	string
Phone	(Response) User phone Member of UserInfoExtended model (Body parameter) Member of UserInfoExtended model	string
Cellphone	(Response) User mobile phone Member of UserInfoExtended model (Body parameter) Mobile phone Member of UserInfoExtended model	string

Request (application/json, text/json)

Sample Data

```
{
  "UserInfo": {
    "UserName": "sample string 1",
    "UserId": 2
  },
  "Email": "sample string 1",
  "FullName": "sample string 2",
  "Initials": "sample string 3",
  "Phone": "sample string 4",
  "Cellphone": "sample string 5"
}
```

Request (application/xml, text/xml)

Sample Data

```
<UserInfoExtended xmlns:i="http://www.w3.org/2001/XMLSchema-instance"
xmlns="http://schemas.datacontract.org/2004/07/SWPDM.Models">
  <Cellphone>sample string 5</Cellphone>
  <Email>sample string 1</Email>
  <FullName>sample string 2</FullName>
  <Initials>sample string 3</Initials>
  <Phone>sample string 4</Phone>
  <UserInfo>
    <UserId>2</UserId>
    <UserName>sample string 1</UserName>
  </UserInfo>
</UserInfoExtended>
```

Request (application/x-www-form-urlencoded)

Response (application/json, text/json)

Sample Data

```
true
```

Response (application/xml, text/xml)

Sample Data

```
<boolean xmlns="http://schemas.microsoft.com/2003/10/Serialization/">true</boolean>
```

See Also

[User Resource Group](#) | [PDM Pro API Web Service](#)

GET

api/{vaultName}/users/{userId}/info

Description

GET: api/{VaultName}/users/{UserID} or api/{VaultName}/users/{UserID}/info Get user info

Gets information about the specified user.

Parameters

vaultName	(URI parameter) Vault name (required)	string
userId	(URI parameter) User ID (required)	integer
UserInfo	(Response) A UserInfo object that consists of: UserName (string) UserId (integer) Member of UserInfoFull model	UserInfo
FullName	(Response) User name Member of UserInfoFull model	string
Initials	(Response) User initials Member of UserInfoFull model	string

Response (application/json, text/json)

Sample Data

```
{
  "UserInfo": {
    "UserName": "sample string 1",
    "UserId": 2
  },
  "FullName": "sample string 1",
  "Initials": "sample string 2"
}
```

Response (application/xml, text/xml)

Sample Data

```
<UserInfoFull xmlns:i="http://www.w3.org/2001/XMLSchema-instance"
xmlns="http://schemas.datacontract.org/2004/07/SWPDM.Models">
  <FullName>sample string 1</FullName>
  <Initials>sample string 2</Initials>
  <UserInfo>
    <UserId>2</UserId>
    <UserName>sample string 1</UserName>
  </UserInfo>
</UserInfoFull>
```

See Also

DELETE

api/{vaultName}/users/{userId}/Picture

Description

DELETE: api/{VaultName}/users/{UserID}/Picture Delete user picture

Deletes the picture of the specified user.

Parameters

vaultName	(URI parameter) Vault name (required)	string
userId	(URI parameter) User ID (required)	integer

Response (application/json, text/json)

Returns true if picture deleted, false if not

Sample Data

true

Response (application/xml, text/xml)

Returns true if picture deleted, false if not

Sample Data

<boolean xmlns="http://schemas.microsoft.com/2003/10/Serialization/">true</boolean>

See Also

User Resource Group | PDM Pro API Web Service

GET

api/{vaultName}/users/{userId}/Picture

Description

GET: api/{VaultName}/users/{UserID}/Picture Get user picture

Gets the picture of the specified user.

Parameters

vaultName	(URI parameter) Vault name (required)	string
userId	(URI parameter) User ID (required)	integer
Version	(Response) A Version model that consists of: - Major (integer) - Minor (integer) - Build (integer) - Revision (integer) - MajorRevision (integer) - MinorRevision (integer) Member of FileHttpResponseMessage model	Version
Content	(Response) Entity body and content headers	HttpContent

	Member of FileHttpResponseMessage model	
StatusCode	(Response) Status code; see https://en.wikipedia.org/wiki/List_of_HTTP_status_codes Member of FileHttpResponseMessage model	HttpStatusCode
ReasonPhrase	(Response) Reason Member of FileHttpResponseMessage model	string
Headers	(Response) Collection of objects Member of FileHttpResponseMessage model	Collection of Object
RequestMessage	(Response) An HttpRequestMessage object that consists of: Version (Version model) Content (HttpContent object consisting of Headers array of objects) Method (HttpMethod object consisting of Method string) RequestUri (URI) Headers (Array of objects) Properties (Dictionary of string [key] and Object [value]) Member of FileHttpResponseMessage model	HttpRequestMessage
IsSuccessStatusCode	(Response) True if successful, false if not Member of FileHttpResponseMessage model	boolean

See Also

[User Resource Group](#) | [PDM Pro API Web Service](#)

PDM Pro API Web Service

PUT `api/{vaultName}/users/{userId}/Picture`

Description

PUT: `api/{VaultName}/users/{UserID}/Picture` Put user picture

Saves the picture of the specified user.

Parameters

vaultName	(URI parameter) Vault name (required)	string
userId	(URI parameter) User ID (required)	integer

Response (application/json, text/json)

Returns true if picture saved, false if not

Sample Data

```
true
```

Response (application/xml, text/xml)

Returns true if picture saved, false if not

Sample Data

```
<boolean xmlns="http://schemas.microsoft.com/2003/10/Serialization/">true</boolean>
```

See Also

[User Resource Group](#) | [PDM Pro API Web Service](#)

GET

api/{vaultName}/workflows

Description

GET: api/{VaultName}/workflows Get workflows

Gets the workflows in the specified vault.

Parameters

vaultName	(URI parameter) Vault name (required)	string
Workflows	(Response) Array of Workflow objects; each Workflow consists of: WorkflowId (integer) WorkflowName (string) States (array of StateInfo objects; each StateInfo consists of: StateId (integer) StateName (string) IgnorePreviousPermissions (integer: 1 to ignore previous permission, 0 to not)) Member of WorkflowList model	Collection of Workflow

Response (application/json, text/json)

Sample Data

```
{
  "Workflows": [
    {
      "WorkflowId": 1,
      "WorkflowName": "sample string 2",
      "States": [
        {
          "StateId": 1,
          "StateName": "sample string 2",
          "IgnorePreviousPermissions": 3
        },
        {
          "StateId": 1,
          "StateName": "sample string 2",
          "IgnorePreviousPermissions": 3
        }
      ]
    },
    {
      "WorkflowId": 1,
      "WorkflowName": "sample string 2",
      "States": [
        {
          "StateId": 1,
          "StateName": "sample string 2",
          "IgnorePreviousPermissions": 3
        },
        {
          "StateId": 1,
          "StateName": "sample string 2",
          "IgnorePreviousPermissions": 3
        }
      ]
    }
  ]
}
```

Response (application/xml, text/xml)

Sample Data

```

<WorkflowList xmlns:i="http://www.w3.org/2001/XMLSchema-instance"
xmlns="http://schemas.datacontract.org/2004/07/SWPDM.Models">
  <Workflows>
    <Workflow>
      <States>
        <StateInfo>
          <IgnorePreviousPermissions>3</IgnorePreviousPermissions>
          <StateId>1</StateId>
          <StateName>sample string 2</StateName>
        </StateInfo>
        <StateInfo>
          <IgnorePreviousPermissions>3</IgnorePreviousPermissions>
          <StateId>1</StateId>
          <StateName>sample string 2</StateName>
        </StateInfo>
      </States>
      <WorkflowId>1</WorkflowId>
      <WorkflowName>sample string 2</WorkflowName>
    </Workflow>
    <Workflow>
      <States>
        <StateInfo>
          <IgnorePreviousPermissions>3</IgnorePreviousPermissions>
          <StateId>1</StateId>
          <StateName>sample string 2</StateName>
        </StateInfo>
        <StateInfo>
          <IgnorePreviousPermissions>3</IgnorePreviousPermissions>
          <StateId>1</StateId>
          <StateName>sample string 2</StateName>
        </StateInfo>
      </States>
      <WorkflowId>1</WorkflowId>
      <WorkflowName>sample string 2</WorkflowName>
    </Workflow>
  </Workflows>
</WorkflowList>

```

See Also

[Workflow Resource Group](#) | [PDM Pro API Web Service](#)

GET

api/{vaultName}/workflows/icons

Description

GET: api/{vaultName}/workflows/icons Get state icons

Gets the workflow state icons in the specified vault.

Parameters

vaultName	(URI parameter) Vault name (required)	string
Item1	(Response) ID of icon	integer
	Member of TupleOfint32AndString model	
Item2	(Response) Name of icon	string
	Member of TupleOfint32AndString model	

Response (application/json, text/json)

Sample Data

```
[
  {
    "m_Item1": 1,
    "m_Item2": "sample string 2"
  },
  {
    "m_Item1": 1,
    "m_Item2": "sample string 2"
  }
]
```

Response (application/xml, text/xml)

Sample Data

```
<ArrayOfTupleOfintstring xmlns:i="http://www.w3.org/2001/XMLSchema-instance"
xmlns="http://schemas.datacontract.org/2004/07/System">
  <TupleOfintstring>
    <m_Item1>1</m_Item1>
    <m_Item2>sample string 2</m_Item2>
  </TupleOfintstring>
  <TupleOfintstring>
    <m_Item1>1</m_Item1>
    <m_Item2>sample string 2</m_Item2>
  </TupleOfintstring>
</ArrayOfTupleOfintstring>
```

See Also