

# SOLIDWORKS API (.NET, VBA, C#) — Reference

## DSldWorksEvents\_BeginRecordNotifyEventHa-

### DTaskpaneViewEvents\_TaskPaneToolBarButto

SOLIDWORKS API Documentation (converted from CHM)

## DSldWorksEvents\_BeginRecordNotifyEventHandler (Type)

SOLIDWORKS API Help

[Send comments on this topic.](#)

DSldWorksEvents\_BeginRecordNotifyEventHandler Delegate (SolidWorks.Interop.sldworks)

[See Also](#) [Example](#)



[SolidWorks.Interop.sldworks Namespace](#) : DSldWorksEvents\_BeginRecordNotifyEventHandler Delegate (SolidWorks.Interop.sldworks)

Notifies the user program when a macro recording has started.

### .NET Syntax

Visual Basic (Declaration)

```
Public Delegate Function DSldWorksEvents_BeginRecordNotifyEventHandler() As System.Integer
```

Visual Basic (Usage)



```
Dim instance As New DSldWorksEvents\_BeginRecordNotifyEventHandler(AddressOf HandlerMethod)
```

C#

```
public delegate System.int DSldWorksEvents_BeginRecordNotifyEventHandler()
```

C++/CLI

```
public delegate System.int DSldWorksEvents_BeginRecordNotifyEventHandler();
```

**NOTE:** See [Differences Between Unmanaged C++ and C++/CLI Code](#).

### Visual Basic for Applications (VBA) Syntax

See [BeginRecordNotify Event \(SldWorks\)](#).

### Example

[Record Macros \(C#\)](#)  
[Record Macros \(VB.NET\)](#)  
[Record Macros \(VBA\)](#)

### Remarks

This event informs the user program when a macro recording has started so that the add-in can add its own initialization code to a macro using [ISldWorks::RecordLine](#), [ISldWorks::RecordLineCSharp](#), or [ISldWorks::RecordLineVBnet](#). This is useful if the add-in is recording its own lines of code to the macro and needs to declare and initialize variables.

The SOLIDWORKS event [EndRecordNotify](#) is sent when the macro recording is stopping.

These events are not sent when the macro is paused and restarted. ISldWorks::RecordLine, ISldWorks::RecordLineCSharp, or ISldWorks::RecordLineVBnet can be used at any time, regardless of whether a macro is currently recording or not. Even if no macro is running, writing to the SOLIDWORKS journal file occurs.

If developing a C++ application, use [swAppBeginRecordNotify](#) to register for this notification.

### Availability

SOLIDWORKS 2006 FCS, Revision Number 14.0

# DSldWorksEvents\_BeginTranslationNotifyEventHandler (Type)

DSldWorksEvents\_BeginTranslationNotifyEventHandler Delegate (SolidWorks.Interop.sldworks)

[See Also](#)



[SolidWorks.Interop.sldworks Namespace](#) : DSldWorksEvents\_BeginTranslationNotifyEventHandler Delegate (SolidWorks.Interop.sldworks)

Notifies the user program when the SOLIDWORKS application starts to import a file.

## .NET Syntax

### Visual Basic (Declaration)

```
Public Delegate Function DSldWorksEvents_BeginTranslationNotifyEventHandler( _  
    ByVal FileName As System.String, _  
    ByVal Options As System.Integer _  
) As System.Integer
```

### Visual Basic (Usage)



```
Dim instance As New DSldWorksEvents\_BeginTranslationNotifyEventHandler(AddressOf HandlerMethod)
```

### C#

```
public delegate System.int DSldWorksEvents_BeginTranslationNotifyEventHandler(  
    System.string FileName,  
    System.int Options  
)
```

### C++/CLI

```
public delegate System.int DSldWorksEvents_BeginTranslationNotifyEventHandler(  
& System.String^ FileName,  
& System.int Options  
)
```

**NOTE:** See [Differences Between Unmanaged C++ and C++/CLI Code](#).

### Parameters

- FileName*  
Name of imported file
- Options*  
Option as defined in [swTranslationNotifyOptions\\_e](#)

## Visual Basic for Applications (VBA) Syntax

See [BeginTranslationNotify\\_Event \(SldWorks\)](#).

## Remarks

If developing a C++ application, use [swAppBeginTranslationNotify](#) to register for this notification.

## Availability

SOLIDWORKS 2001Plus SP3, Revision Number 10.3

## DSldWorksEvents\_CommandCloseNotifyEventHandler (Type)

SOLIDWORKS API Help

[Send comments](#) on this topic.

DSldWorksEvents\_CommandCloseNotifyEventHandler Delegate (SolidWorks.Interop.sldworks)

[See Also](#) [Example](#)



[SolidWorks.Interop.sldworks Namespace](#) : DSldWorksEvents\_CommandCloseNotifyEventHandler Delegate (SolidWorks.Interop.sldworks)

Fired when a command, including a PropertyManager page, is okay'd or canceled by a user.

### .NET Syntax

#### Visual Basic (Declaration)

```
Public Delegate Function DSldWorksEvents_CommandCloseNotifyEventHandler( _  
    ByVal Command As System.Integer, _  
    ByVal reason As System.Integer _  
) As System.Integer
```

#### Visual Basic (Usage)



```
Dim instance As New DSldWorksEvents\_CommandCloseNotifyEventHandler(AddressOf HandlerMethod)
```

#### C#

```
public delegate System.int DSldWorksEvents_CommandCloseNotifyEventHandler(  
    System.int Command,  
    System.int reason  
)
```

#### C++/CLI

```
public delegate System.int DSldWorksEvents_CommandCloseNotifyEventHandler(  
& System.int Command,  
& System.int reason  
)
```

**NOTE:** See [Differences Between Unmanaged C++ and C++/CLI Code](#).

#### Parameters

*Command*

Command as defined in [swCommands\\_e](#)

*reason*

Reason as defined by:

- swCommands\_e.swCommands\_PmOK or swCommands\_e.swCommands\_PmCancel (for PropertyManager page closures)
- swCommands\_e.swCommands\_Exit\_Measure (for Measure dialog closures)
- swCommands\_Comp\_Isolate\_Exit (for Isolate dialog closures)

### Visual Basic for Applications (VBA) Syntax

See [CommandCloseNotify\\_Event \(SldWorks\)](#).

### Example

[Fire Events When PropertyManager Page Opened and Canceled \(VBA\)](#)

[Fire Events When PropertyManager Page Opened and Canceled \(VB.NET\)](#)

[Fire Events When PropertyManager Page Opened and Canceled \(C#\)](#)

### Remarks

If developing a C++ application, use [swAppCommandCloseNotify](#) to register for this notification.

You can combine:

- the IAssemblyDoc [FeatureEditPreNotify](#) event or the IPartDoc [FeatureEditPreNotify](#) event with the ISldWorks CommandCloseNotify event and swCommands\_e.swCommands\_EditFeature.
- the IAssemblyDoc [FeatureSketchEditPreNotify](#) event or the IPartDoc [FeatureSketchEditPreNotify](#) event with the ISldWorks CommandCloseNotify event and swCommands\_e.swCommands\_Sketch.

Call [CommandOpenPreNotify](#) to fire an event before a command executes or a PropertyManager page opens.



## DSldWorksEvents\_CommandOpenPreNotifyEventHandler (Type)

SOLIDWORKS API Help

[Send comments](#) on this topic.

DSldWorksEvents\_CommandOpenPreNotifyEventHandler Delegate (SolidWorks.Interop.sldworks)

[See Also](#) [Example](#)



[SolidWorks.Interop.sldworks Namespace](#) : DSldWorksEvents\_CommandOpenPreNotifyEventHandler Delegate (SolidWorks.Interop.sldworks)

Fired before a command, including a PropertyManager page, executes or opens.

### .NET Syntax

#### Visual Basic (Declaration)

```
Public Delegate Function DSldWorksEvents_CommandOpenPreNotifyEventHandler( _  
    ByVal Command As System.Integer, _  
    ByVal UserCommand As System.Integer _  
) As System.Integer
```

#### Visual Basic (Usage)



```
Dim instance As New DSldWorksEvents\_CommandOpenPreNotifyEventHandler(AddressOf HandlerMethod)
```

#### C#

```
public delegate System.int DSldWorksEvents_CommandOpenPreNotifyEventHandler(  
    System.int Command,  
    System.int UserCommand  
)
```

#### C++/CLI

```
public delegate System.int DSldWorksEvents_CommandOpenPreNotifyEventHandler(  
& System.int Command,  
& System.int UserCommand  
)
```

**NOTE:** See [Differences Between Unmanaged C++ and C++/CLI Code](#).

#### Parameters

*Command*

SOLIDWORKS command ID as defined in [swCommands\\_e](#)

*UserCommand*

Third-party application's command item's ID (see **Remarks**)

#### Return Value

0 to execute the command or open a PropertyManager page, 1 to not

### Visual Basic for Applications (VBA) Syntax

See [CommandOpenPreNotify Event \(SldWorks\)](#).

### Example

[Fire Events When PropertyManager Page Opened and Canceled \(VBA\)](#)

[Fire Events When PropertyManager Page Opened and Canceled \(VB.NET\)](#)

[Fire Events When PropertyManager Page Opened and Canceled \(C#\)](#)

### Remarks

If developing a C++ application, use [swAppCommandOpenPreNotify](#) to register for this notification.

The UserCommand argument is the ID assigned to your application's command item when it was added to a CommandGroup. For example:

```
cmdIndex0 = cmdGroup.AddCommandItem("CreateCube", -1, "Create a cube", "Create cube", 0,  
"CreateCube", "", 0);  
cmdIds[0] = cmdGroup.get_CommandID(cmdIndex0);
```

Selecting the **Create cube** command in the user interface causes the CommandOpenPreNotify event to fire. The Command parameter is swCommands\_e.swCommands\_User\_Toolbar\_Min, and the userCommand parameter is cmdIDs[0].

Call [CommandCloseNotify](#) to fire an event when the PropertyManager page is okay'd or canceled.

## Availability

SOLIDWORKS 2011 FCS, Revision Number 19.0

# DSldWorksEvents\_DestroyNotifyEventHandler (Type)

SOLIDWORKS API Help

[Send comments](#) on this topic.

DSldWorksEvents\_DestroyNotifyEventHandler Delegate (SolidWorks.Interop.sldworks)

[See Also](#)



[SolidWorks.Interop.sldworks Namespace](#) : DSldWorksEvents\_DestroyNotifyEventHandler Delegate (SolidWorks.Interop.sldworks)

Sent to an MFC-based or a COM-based DLL add-in when the SOLIDWORKS session is about to be destroyed.

## .NET Syntax

### Visual Basic (Declaration)

```
Public Delegate Function DSldWorksEvents_DestroyNotifyEventHandler() As System.Integer
```

### Visual Basic (Usage)



```
Dim instance As New DSldWorksEvents\_DestroyNotifyEventHandler(AddressOf HandlerMethod)
```

### C#

```
public delegate System.int DSldWorksEvents_DestroyNotifyEventHandler()
```

### C++/CLI

```
public delegate System.int DSldWorksEvents_DestroyNotifyEventHandler();
```

**NOTE:** See [Differences Between Unmanaged C++ and C++/CLI Code](#).

## Visual Basic for Applications (VBA) Syntax

See [DestroyNotify\\_Event \(SldWorks\)](#).

## Remarks

This is a pre-notification. Add-ins should not perform any cleanup inside this event.

Use [ISwAddin::DisconnectFromSw](#) to perform any cleanup of COM-based DLL add-ins.

If developing a C++ application, use [swAppDestroyNotify](#) to register for this notification.

## Availability

SOLIDWORKS 2001Plus FCS, Revision Number 10.0

# DSldWorksEvents\_DisplayPaneActivationNotifyEventHandler (Type)

DSldWorksEvents\_DisplayPaneActivationNotifyEventHandler Delegate (SolidWorks.Interop.sldworks)

[See Also](#) [Example](#)



[SolidWorks.Interop.sldworks Namespace](#) : DSldWorksEvents\_DisplayPaneActivationNotifyEventHandler Delegate (SolidWorks.Interop.sldworks)

Fired when the Display Pane is activated.

## .NET Syntax

### Visual Basic (Declaration)

```
Public Delegate Function DSldWorksEvents_DisplayPaneActivationNotifyEventHandler( _  
    ByVal ActivePaneIndex As System.Integer _  
) As System.Integer
```

### Visual Basic (Usage)



```
Dim instance As New DSldWorksEvents\_DisplayPaneActivationNotifyEventHandler(AddressOf  
HandlerMethod)
```

### C#

```
public delegate System.int DSldWorksEvents_DisplayPaneActivationNotifyEventHandler(  
    System.int ActivePaneIndex  
)
```

### C++/CLI

```
public delegate System.int DSldWorksEvents_DisplayPaneActivationNotifyEventHandler(  
& System.int ActivePaneIndex  
)
```

**NOTE:** See [Differences Between Unmanaged C++ and C++/CLI Code](#).

### Parameters

*ActivePaneIndex*  
Display Pane as defined by [swDisplayPaneIndex\\_e](#)

## Visual Basic for Applications (VBA) Syntax

See [DisplayPaneActivationNotify Event \(SldWorks\)](#).

## Example

[Create Task Pane View Add-in \(C#\)](#)

## Remarks

If developing a C++ application, use [swAppDisplayPaneActivationNotify](#) to register for this notification.

## Availability

# DSldWorksEvents\_DocumentConversionNotifyEventHandler (Type)

SOLIDWORKS API Help

[Send comments on this topic.](#)

DSldWorksEvents\_DocumentConversionNotifyEventHandler Delegate (SolidWorks.Interop.sldworks)

[See Also](#)



[SolidWorks.Interop.sldworks Namespace](#) : DSldWorksEvents\_DocumentConversionNotifyEventHandler Delegate (SolidWorks.Interop.sldworks)

Post-notifies the user program that a file has been converted from an older version of SOLIDWORKS during the open operation.

## .NET Syntax

### Visual Basic (Declaration)

```
Public Delegate Function DSldWorksEvents_DocumentConversionNotifyEventHandler( _  
    ByVal FileName As System.String _  
) As System.Integer
```

### Visual Basic (Usage)



```
Dim instance As New DSldWorksEvents\_DocumentConversionNotifyEventHandler(AddressOf HandlerMethod)
```

### C#

```
public delegate System.int DSldWorksEvents_DocumentConversionNotifyEventHandler(  
    System.string FileName  
)
```

### C++/CLI

```
public delegate System.int DSldWorksEvents_DocumentConversionNotifyEventHandler(  
    & System.String^ FileName  
)
```

**NOTE:** See [Differences Between Unmanaged C++ and C++/CLI Code](#).

### Parameters

*FileName*  
Name of the converted file

## Visual Basic for Applications (VBA) Syntax

See [DocumentConversionNotify Event \(SldWorks\)](#).

## Remarks

Any number of these notifications may be sent at the end of an open operation because an open operation of an assembly or drawing may cause multiple files to open. In this scenario, all of the opened files may have been converted.

If developing a C++ application, use [swAppDocumentConversionNotify](#) to register for this notification.

## DSldWorksEvents\_DocumentLoadNotify2EventHandler (Type)

SOLIDWORKS API Help

[Send comments on this topic.](#)

DSldWorksEvents\_DocumentLoadNotify2EventHandler Delegate (SolidWorks.Interop.sldworks)

[See Also](#) [Example](#)



[SolidWorks.Interop.sldworks Namespace](#) : DSldWorksEvents\_DocumentLoadNotify2EventHandler Delegate (SolidWorks.Interop.sldworks)

Post-notifies the user program when a SOLIDWORKS document is loaded.

### .NET Syntax

Visual Basic (Declaration)

```
Public Delegate Function DSldWorksEvents_DocumentLoadNotify2EventHandler( _  
    ByVal docTitle As System.String, _  
    ByVal docPath As System.String _  
) As System.Integer
```

Visual Basic (Usage)



```
Dim instance As New DSldWorksEvents\_DocumentLoadNotify2EventHandler(AddressOf HandlerMethod)
```

C#

```
public delegate System.int DSldWorksEvents_DocumentLoadNotify2EventHandler(  
    System.string docTitle,  
    System.string docPath  
)
```

C++/CLI

```
public delegate System.int DSldWorksEvents_DocumentLoadNotify2EventHandler(  
& System.String^ docTitle,  
& System.String^ docPath  
)
```

**NOTE:** See [Differences Between Unmanaged C++ and C++/CLI Code](#).

#### Parameters

*docTitle*  
Document title  
*docPath*  
Document path

### Visual Basic for Applications (VBA) Syntax

See [DocumentLoadNotify2 Event \(SldWorks\)](#).

### Example

[Create CommandManager Tab and Tab Boxes \(VB.NET\)](#)

### Remarks

This event is fired for documents referenced by assemblies and drawings. Client code should expect multiple calls to this event handler when an assembly or drawing is loaded.

If developing a C++ application, use [swAppDocumentLoadNotify2](#) to register for this notification.

### Availability

SOLIDWORKS 2008 FCS, Revision Number 16.0

# DSldWorksEvents\_DocumentLoadNotifyEventHandler (Type)

SOLIDWORKS API Help

[Send comments](#) on this topic.

DSldWorksEvents\_DocumentLoadNotifyEventHandler Delegate (SolidWorks.Interop.sldworks)

[See Also](#)



[SolidWorks.Interop.sldworks Namespace](#) : DSldWorksEvents\_DocumentLoadNotifyEventHandler Delegate (SolidWorks.Interop.sldworks)

Obsolete. Superseded by [DSldWorksEvents\\_DocumentLoadNotify2EventHandler](#).

## .NET Syntax

Visual Basic (Declaration)

```
Public Delegate Function DSldWorksEvents_DocumentLoadNotifyEventHandler( _  
    ByVal docTitle As System.String, _  
    ByVal docPath As System.String _  
) As System.Integer
```

Visual Basic (Usage)



```
Dim instance As New DSldWorksEvents\_DocumentLoadNotifyEventHandler(AddressOf HandlerMethod)
```

C#

```
public delegate System.int DSldWorksEvents_DocumentLoadNotifyEventHandler(  
    System.string docTitle,  
    System.string docPath  
)
```

C++/CLI

```
public delegate System.int DSldWorksEvents_DocumentLoadNotifyEventHandler(  
& System.String^ docTitle,  
& System.String^ docPath  
)
```

**NOTE:** See [Differences Between Unmanaged C++ and C++/CLI Code](#).

### Parameters

*docTitle*

*docPath*

## Visual Basic for Applications (VBA) Syntax

See [DocumentLoadNotify Event \(SldWorks\)](#).

## Availability

# DSldWorksEvents\_End3DInterconnectTranslationNotifyEventHandler (Type)

SOLIDWORKS API Help

[Send comments on this topic.](#)

DSldWorksEvents\_End3DInterconnectTranslationNotifyEventHandler Delegate (SolidWorks.Interop.sldworks)

[See Also](#)



[SolidWorks.Interop.sldworks Namespace](#) : DSldWorksEvents\_End3DInterconnectTranslationNotifyEventHandler Delegate (SolidWorks.Interop.sldworks)

Notifies the user program when the SOLIDWORKS application is finished importing or exporting a third-party native CAD file.

## .NET Syntax

### Visual Basic (Declaration)

```
Public Delegate Function DSldWorksEvents_End3DInterconnectTranslationNotifyEventHandler( _  
    ByVal FileName As System.String _  
) As System.Integer
```

### Visual Basic (Usage)



```
Dim instance As New DSldWorksEvents\_End3DInterconnectTranslationNotifyEventHandler(AddressOf  
HandlerMethod)
```

### C#

```
public delegate System.int DSldWorksEvents_End3DInterconnectTranslationNotifyEventHandler(  
    System.string FileName  
)
```

### C++/CLI

```
public delegate System.int DSldWorksEvents_End3DInterconnectTranslationNotifyEventHandler(  
& System.String^ FileName  
)
```

**NOTE:** See [Differences Between Unmanaged C++ and C++/CLI Code](#).

### Parameters

*FileName*

Name of imported or exported third-party native CAD file

## Visual Basic for Applications (VBA) Syntax

See [End3DInterconnectTranslationNotify Event \(SldWorks\)](#).

## Example

See the [IImport3DInterconnectData](#) examples.

## Remarks

If developing a C++ application, use [swAppEnd3DInterconnectTranslationNotify](#) to register for this notification.

## Availability

SOLIDWORKS 2020 FCS, Revision Number 28.0

## DSldWorksEvents\_EndRecordNotifyEventHandler (Type)

SOLIDWORKS API Help

[Send comments on this topic.](#)

DSldWorksEvents\_EndRecordNotifyEventHandler Delegate (SolidWorks.Interop.sldworks)

[See Also](#) [Example](#)



[SolidWorks.Interop.sldworks Namespace](#) : DSldWorksEvents\_EndRecordNotifyEventHandler Delegate (SolidWorks.Interop.sldworks)

Notifies the user program when a macro recording has ended, including if the user cancels the recording (i.e., the user cancels out of the **Save As** dialog and says **No** to the **Continue recording?** dialog).

### .NET Syntax

Visual Basic (Declaration)

```
Public Delegate Function DSldWorksEvents_EndRecordNotifyEventHandler() As System.Integer
```

Visual Basic (Usage)



```
Dim instance As New DSldWorksEvents\_EndRecordNotifyEventHandler(AddressOf HandlerMethod)
```

C#

```
public delegate System.int DSldWorksEvents_EndRecordNotifyEventHandler()
```

C++/CLI

```
public delegate System.int DSldWorksEvents_EndRecordNotifyEventHandler();
```

**NOTE:** See [Differences Between Unmanaged C++ and C++/CLI Code](#).

### Visual Basic for Applications (VBA) Syntax

See [EndRecordNotify\\_Event \(SldWorks\)](#).

### Example

[Record Macros \(C#\)](#)  
[Record Macros \(VB.NET\)](#)  
[Record Macros \(VBA\)](#)

### Remarks

This event informs the user program when a macro recording has stopped so that the add-in can add its own cleanup code to a macro using [ISldWorks::RecordLine](#), [ISldWorks::RecordLineCSharp](#), or [ISldWorks::RecordLineVBnet](#). This is useful if the add-in has been recording its own lines of code to the macro and needs to clean up variables that have been used.

The SOLIDWORKS event [BeginRecordNotify](#) is sent when the macro recording is starting.

These events are not sent when the macro is paused and restarted. SldWorks::RecordLine, ISldWorks::RecordLineCSharp, or ISldWorks::RecordLineVBnet can be used at any time, regardless of whether a macro is currently recording or not. Even if no macro is running, writing to the journal file occurs.

If developing a C++ application, use [swAppEndRecordNotify](#) to register for this notification.

### Availability

SOLIDWORKS 2006 FCS, Revision Number 14.0

# DSldWorksEvents\_EndTranslationNotifyEventHandler (Type)

DSldWorksEvents\_EndTranslationNotifyEventHandler Delegate (SolidWorks.Interop.sldworks)

[See Also](#)



[SolidWorks.Interop.sldworks Namespace](#) : DSldWorksEvents\_EndTranslationNotifyEventHandler Delegate (SolidWorks.Interop.sldworks)

Notifies the user program when the SOLIDWORKS application is finished importing a file.

## .NET Syntax

### Visual Basic (Declaration)

```
Public Delegate Function DSldWorksEvents_EndTranslationNotifyEventHandler( _  
    ByVal FileName As System.String, _  
    ByVal Options As System.Integer _  
) As System.Integer
```

### Visual Basic (Usage)



```
Dim instance As New DSldWorksEvents\_EndTranslationNotifyEventHandler(AddressOf HandlerMethod)
```

### C#

```
public delegate System.int DSldWorksEvents_EndTranslationNotifyEventHandler(  
    System.string FileName,  
    System.int Options  
)
```

### C++/CLI

```
public delegate System.int DSldWorksEvents_EndTranslationNotifyEventHandler(  
& System.String^ FileName,  
& System.int Options  
)
```

**NOTE:** See [Differences Between Unmanaged C++ and C++/CLI Code](#).

### Parameters

- FileName*  
Name of imported file
- Options*  
Option as defined in [swTranslationNotifyOptions\\_e](#)

## Visual Basic for Applications (VBA) Syntax

See [EndTranslationNotify Event \(SldWorks\)](#).

## Remarks

This event occurs after automatic healing if it is enabled. To enable automatic healing, set swImportAutoRunImportDiagnosticsPersist and swImportAutoRunImportDiagnostics to True. See [swUserPreferenceToggle\\_e](#), **Import** for details about these two enumerators.

If developing a C++ application, use [swAppEndTranslationNotify](#) to register for this notification.

## Availability

SOLIDWORKS 2001Plus SP3, Revision Number 10.3

# DSldWorksEvents\_FileCloseNotifyEventHandler (Type)

SOLIDWORKS API Help

[Send comments](#) on this topic.

DSldWorksEvents\_FileCloseNotifyEventHandler Delegate (SolidWorks.Interop.sldworks)

[See Also](#)



[SolidWorks.Interop.sldworks Namespace](#) : DSldWorksEvents\_FileCloseNotifyEventHandler Delegate (SolidWorks.Interop.sldworks)

Notifies the user program when SOLIDWORKS is finished closing a file.

## .NET Syntax

### Visual Basic (Declaration)

```
Public Delegate Function DSldWorksEvents_FileCloseNotifyEventHandler( _  
    ByVal FileName As System.String, _  
    ByVal reason As System.Integer _  
) As System.Integer
```

### Visual Basic (Usage)



```
Dim instance As New DSldWorksEvents\_FileCloseNotifyEventHandler(AddressOf HandlerMethod)
```

### C#

```
public delegate System.int DSldWorksEvents_FileCloseNotifyEventHandler(  
    System.string FileName,  
    System.int reason  
)
```

### C++/CLI

```
public delegate System.int DSldWorksEvents_FileCloseNotifyEventHandler(  
& System.String^ FileName,  
& System.int reason  
)
```

**NOTE:** See [Differences Between Unmanaged C++ and C++/CLI Code](#).

### Parameters

*FileName*

Name of closed file

*reason*

Reason for closing as defined in [swFileCloseNotifyReason\\_e](#)

## Visual Basic for Applications (VBA) Syntax

See [FileCloseNotify\\_Event \(SldWorks\)](#).

## Example

Contact SOLIDWORKS API Support to obtain **Close and Reopen a Drawing Document (VBA, VB.NET, C#)**.

## Remarks

This event occurs after a drawing document is closed using [ISldWorks::CloseAndReopen](#).  
If developing a C++ application, use [swAppFileCloseNotify](#) to register for this notification.

## Availability

SOLIDWORKS 2012 FCS, Revision Number 20.0

## DSldWorksEvents\_FileNewNotify2EventHandler (Type)

SOLIDWORKS API Help

[Send comments](#) on this topic.

DSldWorksEvents\_FileNewNotify2EventHandler Delegate (SolidWorks.Interop.sldworks)

[See Also](#) [Example](#)



[SolidWorks.Interop.sldworks Namespace](#) : DSldWorksEvents\_FileNewNotify2EventHandler Delegate (SolidWorks.Interop.sldworks)

Post-notifies the user program when a new file is created.

### .NET Syntax

Visual Basic (Declaration)

```
Public Delegate Function DSldWorksEvents_FileNewNotify2EventHandler( _  
    ByVal NewDoc As System.Object, _  
    ByVal DocType As System.Integer, _  
    ByVal TemplateName As System.String _  
) As System.Integer
```

Visual Basic (Usage)



```
Dim instance As New DSldWorksEvents\_FileNewNotify2EventHandler(AddressOf HandlerMethod)
```

C#

```
public delegate System.int DSldWorksEvents_FileNewNotify2EventHandler(  
    System.object NewDoc,  
    System.int DocType,  
    System.string TemplateName  
)
```

C++/CLI

```
public delegate System.int DSldWorksEvents_FileNewNotify2EventHandler(  
& System.Object^ NewDoc,  
& System.int DocType,  
& System.String^ TemplateName  
)
```

**NOTE:** See [Differences Between Unmanaged C++ and C++/CLI Code](#).

#### Parameters

*NewDoc*

New document

*DocType*

Type of document as defined in [swDocumentTypes\\_e](#)

*TemplateName*

Template name of the new document

### Visual Basic for Applications (VBA) Syntax

See [FileNewNotify2 Event \(SldWorks\)](#).

### Example

[Create CommandManager Tab and Tab Boxes \(VB.NET\)](#)

### Remarks

If your add-in wants to use the Dispatch pointer to the new document, then your add-in must increment the reference count using AddRef. When your add-in is done with the new document, it must decrement the reference count using Release.

If developing a C++ application, use [swAppFileNewNotify2](#) to register for this notification.

### Availability

# DSldWorksEvents\_FileNewNotifyEventHandler (Type)

DSldWorksEvents\_FileNewNotifyEventHandler Delegate (SolidWorks.Interop.sldworks)

[See Also](#)



[SolidWorks.Interop.sldworks Namespace](#) : DSldWorksEvents\_FileNewNotifyEventHandler Delegate (SolidWorks.Interop.sldworks)

Obsolete. Superseded by [DSldWorksEvents\\_FileNewNotify2EventHandler](#).

## .NET Syntax

### Visual Basic (Declaration)

```
Public Delegate Function DSldWorksEvents_FileNewNotifyEventHandler( _  
    ByVal NewDoc As System.Object, _  
    ByVal DocType As System.Integer _  
) As System.Integer
```

### Visual Basic (Usage)



```
Dim instance As New DSldWorksEvents\_FileNewNotifyEventHandler(AddressOf HandlerMethod)
```

### C#

```
public delegate System.int DSldWorksEvents_FileNewNotifyEventHandler(  
    System.object NewDoc,  
    System.int DocType  
)
```

### C++/CLI

```
public delegate System.int DSldWorksEvents_FileNewNotifyEventHandler(  
& System.Object^ NewDoc,  
& System.int DocType  
)
```

**NOTE:** See [Differences Between Unmanaged C++ and C++/CLI Code](#).

### Parameters

*NewDoc*

*DocType*

## Visual Basic for Applications (VBA) Syntax

See [FileNewNotify Event \(SldWorks\)](#).

## Availability

## DSldWorksEvents\_FileNewPreNotifyEventHandler (Type)

SOLIDWORKS API Help

[Send comments on this topic.](#)

DSldWorksEvents\_FileNewPreNotifyEventHandler Delegate (SolidWorks.Interop.sldworks)

[See Also](#)



[SolidWorks.Interop.sldworks Namespace](#) : DSldWorksEvents\_FileNewPreNotifyEventHandler Delegate (SolidWorks.Interop.sldworks)

Fired before a new document is created using either the SOLIDWORKS API or the SOLIDWORKS application.

### .NET Syntax

Visual Basic (Declaration)

```
Public Delegate Function DSldWorksEvents_FileNewPreNotifyEventHandler( _  
    ByVal DocType As System.Integer, _  
    ByVal TemplateName As System.String _  
) As System.Integer
```

Visual Basic (Usage)



```
Dim instance As New DSldWorksEvents\_FileNewPreNotifyEventHandler(AddressOf HandlerMethod)
```

C#

```
public delegate System.int DSldWorksEvents_FileNewPreNotifyEventHandler(  
    System.int DocType,  
    System.string TemplateName  
)
```

C++/CLI

```
public delegate System.int DSldWorksEvents_FileNewPreNotifyEventHandler(  
& System.int DocType,  
& System.String^ TemplateName  
)
```

**NOTE:** See [Differences Between Unmanaged C++ and C++/CLI Code](#).

#### Parameters

*DocType*

Document type as defined by [swDocumentTypes](#) e

*TemplateName*

Template path name or file extension

### Visual Basic for Applications (VBA) Syntax

See [FileNewPreNotify Event \(SldWorks\)](#).

### Remarks

Creating a new document using SOLIDWORKS includes:

- Clicking a document-type button on the **New SOLIDWORKS Document** dialog.
- Inserting a new component (part or assembly).

**NOTE:** This event is not raised when creating split parts.

You can cancel the creation of a new document by returning S\_FALSE(1) from the event handler.

If developing a C++ application, use [swAppFileNewPreNotify](#) to register for this notification.

### Availability

SOLIDWORKS 2007 SP4, Revision Number 15.4

# DSldWorksEvents\_FileOpenNotify2EventHandler (Type)

SOLIDWORKS API Help

[Send comments on this topic.](#)

DSldWorksEvents\_FileOpenNotify2EventHandler Delegate (SolidWorks.Interop.sldworks)

[See Also](#)



[SolidWorks.Interop.sldworks Namespace](#) : DSldWorksEvents\_FileOpenNotify2EventHandler Delegate (SolidWorks.Interop.sldworks)

Post-notifies the user program when an existing file has been opened.

## .NET Syntax

Visual Basic (Declaration)

```
Public Delegate Function DSldWorksEvents_FileOpenNotify2EventHandler( _  
    ByVal FileName As System.String _  
) As System.Integer
```

Visual Basic (Usage)



```
Dim instance As New DSldWorksEvents\_FileOpenNotify2EventHandler(AddressOf HandlerMethod)
```

C#

```
public delegate System.int DSldWorksEvents_FileOpenNotify2EventHandler(  
    System.string FileName  
)
```

C++/CLI

```
public delegate System.int DSldWorksEvents_FileOpenNotify2EventHandler(  
& System.String^ FileName  
)
```

**NOTE:** See [Differences Between Unmanaged C++ and C++/CLI Code](#).

### Parameters

*FileName*  
Name of the opened file

## Visual Basic for Applications (VBA) Syntax

See [FileOpenNotify2 Event \(SldWorks\)](#).

## Remarks

You can use [ISldWorks::GetOpenDocumentByName](#) or [ISldWorks::IGetOpenDocumentByName2](#) with *FileName* to get a pointer to the newly opened document. Because it is possible to have a NULL active document when an add-in is notified by `swAppFileOpenNotify2`, use [ISldWorks::IGetOpenDocumentByName2](#) instead of [ISldWorks::IActiveDoc2](#).

This event is very similar to the now obsolete SldWorks events [FileOpenNotify](#) event. The difference is that the SOLIDWORKS event `FileOpenNotify2` is fired later in the process than the SOLIDWORKS event `FileOpenNotify`, so that if end-users respond to the event by opening new part, then `NewDocument`, `NewPart`, `NewAssembly`, or `NewDrawing2` is successful.

This event is sent to any application when a file is opened programmatically using [ISldWorks::OpenDoc6](#). Your application can detect the newly opened document by watching the the SOLIDWORKS events [ActiveModelDocChangeNotify](#) event.

With the exception of Parasolid files (that is, \*.x\_t, \*.x\_b), this event is not sent for the opening of non-native SOLIDWORKS files (that is, \*.igs, \*.dxf, and so on). Opening non-native files is typically handled with the creation of a new SOLIDWORKS file (that is, \*.sldprt, \*.sldasm, \*.slddrw) and the subsequent construction of the foreign geometry within that file.

If developing a C++ application, use [swAppFileOpenNotify2](#) to register for this notification.

## Availability

SOLIDWORKS 2001Plus SP1, Revision Number 10.1

# DSldWorksEvents\_FileOpenNotifyEventHandler (Type)

SOLIDWORKS API Help

[Send comments](#) on this topic.

DSldWorksEvents\_FileOpenNotifyEventHandler Delegate (SolidWorks.Interop.sldworks)

[See Also](#)



[SolidWorks.Interop.sldworks Namespace](#) : DSldWorksEvents\_FileOpenNotifyEventHandler Delegate (SolidWorks.Interop.sldworks)

Obsolete. Superseded by [DSldWorksEvents\\_FileOpenNotify2EventHandler](#).

## .NET Syntax

### Visual Basic (Declaration)

```
Public Delegate Function DSldWorksEvents_FileOpenNotifyEventHandler( _  
    ByVal FileName As System.String _  
) As System.Integer
```

### Visual Basic (Usage)



```
Dim instance As New DSldWorksEvents\_FileOpenNotifyEventHandler(AddressOf HandlerMethod)
```

### C#

```
public delegate System.int DSldWorksEvents_FileOpenNotifyEventHandler(  
    System.string FileName  
)
```

### C++/CLI

```
public delegate System.int DSldWorksEvents_FileOpenNotifyEventHandler(  
& System.String^ FileName  
)
```

**NOTE:** See [Differences Between Unmanaged C++ and C++/CLI Code](#).

### Parameters

*FileName*

## Visual Basic for Applications (VBA) Syntax

See [FileOpenNotify\\_Event \(SldWorks\)](#).

# DSldWorksEvents\_FileOpenPostNotifyEventHandler (Type)

SOLIDWORKS API Help

[Send comments on this topic.](#)

DSldWorksEvents\_FileOpenPostNotifyEventHandler Delegate (SolidWorks.Interop.sldworks)

[See Also](#)



[SolidWorks.Interop.sldworks Namespace](#) : DSldWorksEvents\_FileOpenPostNotifyEventHandler Delegate (SolidWorks.Interop.sldworks)

Post-notifies the user program when a file has been opened.

## .NET Syntax

### Visual Basic (Declaration)

```
Public Delegate Function DSldWorksEvents_FileOpenPostNotifyEventHandler( _  
    ByVal FileName As System.String _  
) As System.Integer
```

### Visual Basic (Usage)



```
Dim instance As New DSldWorksEvents\_FileOpenPostNotifyEventHandler(AddressOf HandlerMethod)
```

### C#

```
public delegate System.int DSldWorksEvents_FileOpenPostNotifyEventHandler(  
    System.string FileName  
)
```

### C++/CLI

```
public delegate System.int DSldWorksEvents_FileOpenPostNotifyEventHandler(  
& System.String^ FileName  
)
```

**NOTE:** See [Differences Between Unmanaged C++ and C++/CLI Code](#).

### Parameters

*FileName*

Name of the opened file

## Visual Basic for Applications (VBA) Syntax

See [FileOpenPostNotify Event \(SldWorks\)](#).

## Remarks

This is the last event fired before control returns to the user. This event indicates that methods that modify references, [reload documents](#), or close documents can be called.

If developing a C++ application, use [swAppFileOpenPostNotify](#) to register for this notification.

## Availability

SOLIDWORKS 2004 SP4, Revision Number 12.4

# DSldWorksEvents\_FileOpenPreNotifyEventHandler (Type)

SOLIDWORKS API Help

[Send comments on this topic.](#)

DSldWorksEvents\_FileOpenPreNotifyEventHandler Delegate (SolidWorks.Interop.sldworks)

[See Also](#)



[SolidWorks.Interop.sldworks Namespace](#) : DSldWorksEvents\_FileOpenPreNotifyEventHandler Delegate (SolidWorks.Interop.sldworks)

Pre-notifies the user program of a [FileOpenNotify2](#) event.

## .NET Syntax

### Visual Basic (Declaration)

```
Public Delegate Function DSldWorksEvents_FileOpenPreNotifyEventHandler( _  
    ByVal FileName As System.String _  
) As System.Integer
```

### Visual Basic (Usage)



```
Dim instance As New DSldWorksEvents\_FileOpenPreNotifyEventHandler(AddressOf HandlerMethod)
```

### C#

```
public delegate System.int DSldWorksEvents_FileOpenPreNotifyEventHandler(  
    System.string FileName  
)
```

### C++/CLI

```
public delegate System.int DSldWorksEvents_FileOpenPreNotifyEventHandler(  
& System.String^ FileName  
)
```

**NOTE:** See [Differences Between Unmanaged C++ and C++/CLI Code](#).

### Parameters

*FileName*

Full path and name of file to open

## Visual Basic for Applications (VBA) Syntax

See [FileOpenPreNotify\\_Event \(SldWorks\)](#).

## Remarks

This event is only fired when opening these SOLIDWORKS files: parts, drawings, and assemblies. It is not fired when opening files like templates, translator files, and so on.

This event is fired before SOLIDWORKS begins loading the file. A SOLIDWORKS file can be opened in many ways; for example, **File, Open** in the user interface, [ISldWorks::OpenDoc6](#) in the API, Load Model from a Detached drawing, Lightweight component being resolved, and so on. This event is fired in all of these cases.

If you want to allow SOLIDWORKS to open the file, return S\_OK (or 0) from the handler. If you do not want to allow SOLIDWORKS to open the file, return S\_false (or any code other than S\_OK) from the handler.

The event that occurs after this event is [DocumentLoadNotify](#).

If developing a C++ application, use [swAppFileOpenPreNotify](#) to register for this notification.

## Availability

SOLIDWORKS 2004 SP4, Revision Number 12.4

# DSldWorksEvents\_InterfaceBrightnessThemeChangeNotifyEventHandler (Type)

SOLIDWORKS API Help

[Send comments on this topic.](#)

DSldWorksEvents\_InterfaceBrightnessThemeChangeNotifyEventHandler Delegate (SolidWorks.Interop.sldworks)

[See Also](#) [Example](#)



[SolidWorks.Interop.sldworks Namespace](#) : DSldWorksEvents\_InterfaceBrightnessThemeChangeNotifyEventHandler Delegate (SolidWorks.Interop.sldworks)

Notifies an add-in when the SOLIDWORKS background changes.

## .NET Syntax

### Visual Basic (Declaration)

```
Public Delegate Function DSldWorksEvents_InterfaceBrightnessThemeChangeNotifyEventHandler( _  
    ByVal ThemeType As System.Integer, _  
    ByRef Colors As System.Object _  
) As System.Integer
```

### Visual Basic (Usage)



```
Dim instance As New DSldWorksEvents\_InterfaceBrightnessThemeChangeNotifyEventHandler(AddressOf  
HandlerMethod)
```

### C#

```
public delegate System.int DSldWorksEvents_InterfaceBrightnessThemeChangeNotifyEventHandler(  
    System.int ThemeType,  
    ref System.object Colors  
)
```

### C++/CLI

```
public delegate System.int DSldWorksEvents_InterfaceBrightnessThemeChangeNotifyEventHandler(  
& System.int ThemeType,  
& System.Object^% Colors  
)
```

**NOTE:** See [Differences Between Unmanaged C++ and C++/CLI Code](#).

### Parameters

*ThemeType*

SOLIDWORKS background as defined in [swInterfaceBrightnessTheme](#) e

*Colors*

Array of RGB (Red, Green, Blue) decimal values (see **Remarks**)

## Visual Basic for Applications (VBA) Syntax

See [InterfaceBrightnessThemeChangeNotify\\_Event \(SldWorks\)](#).

## Example

[Add Shortcut Menus to Add-ins \(VB.NET\)](#)

[Add Shortcut Menus to Add-ins \(C#\)](#)

## Remarks

The Colors array is indexed by [swInterfaceBrightnessColor](#) e.

To get the SOLIDWORKS background:

- theme, use [ISwHtmlInterface::GetInterfaceBrightnessTheme](#).
- theme and colors, [ISldWorks::GetInterfaceBrightnessThemeColors](#).

If developing a C++ application, use [swAppInterfaceBrightnessThemeChangeNotify](#) to register for this notification.

## Availability

SOLIDWORKS 2016 SP1, Revision Number 24.1

# DSldWorksEvents\_LightSheetCreateNotifyEventHandler (Type)

DSldWorksEvents\_LightSheetCreateNotifyEventHandler Delegate (SolidWorks.Interop.sldworks)

[See Also](#)



[SolidWorks.Interop.sldworks Namespace](#) : DSldWorksEvents\_LightSheetCreateNotifyEventHandler Delegate (SolidWorks.Interop.sldworks)

Fired when a lighting sheet has been created.

## .NET Syntax

### Visual Basic (Declaration)

```
Public Delegate Function DSldWorksEvents_LightSheetCreateNotifyEventHandler( _  
    ByVal NewSheet As System.Object, _  
    ByVal sheetType As System.Integer, _  
    ByVal LightId As System.Integer _  
) As System.Integer
```

### Visual Basic (Usage)



```
Dim instance As New DSldWorksEvents\_LightSheetCreateNotifyEventHandler(AddressOf HandlerMethod)
```

### C#

```
public delegate System.int DSldWorksEvents_LightSheetCreateNotifyEventHandler(  
    System.object NewSheet,  
    System.int sheetType,  
    System.int LightId  
)
```

### C++/CLI

```
public delegate System.int DSldWorksEvents_LightSheetCreateNotifyEventHandler(  
& System.Object^ NewSheet,  
& System.int sheetType,  
& System.int LightId  
)
```

**NOTE:** See [Differences Between Unmanaged C++ and C++/CLI Code](#).

### Parameters

- NewSheet*  
New lighting sheet
- sheetType*  
Type of the new lighting sheet
- LightId*  
Light sheet ID

## Visual Basic for Applications (VBA) Syntax

See [LightSheetCreateNotify Event \(SldWorks\)](#).

## Remarks

If developing a C++ application, use [swApplLightSheetCreateNotify](#) to register for this notification.

## Availability

SOLIDWORKS 2001Plus FCS, Revision Number 10.0

## DSldWorksEvents\_NonNativeFileOpenNotifyEventHandler (Type)

SOLIDWORKS API Help

[Send comments on this topic.](#)

DSldWorksEvents\_NonNativeFileOpenNotifyEventHandler Delegate (SolidWorks.Interop.sldworks)

[See Also](#)



[SolidWorks.Interop.sldworks Namespace](#) : DSldWorksEvents\_NonNativeFileOpenNotifyEventHandler Delegate (SolidWorks.Interop.sldworks)

Fired when non-native SOLIDWORKS files are opened.

### .NET Syntax

#### Visual Basic (Declaration)

```
Public Delegate Function DSldWorksEvents_NonNativeFileOpenNotifyEventHandler( _  
    ByVal FileName As System.String _  
) As System.Integer
```

#### Visual Basic (Usage)



```
Dim instance As New DSldWorksEvents\_NonNativeFileOpenNotifyEventHandler(AddressOf HandlerMethod)
```

#### C#

```
public delegate System.int DSldWorksEvents_NonNativeFileOpenNotifyEventHandler(  
    System.string FileName  
)
```

#### C++/CLI

```
public delegate System.int DSldWorksEvents_NonNativeFileOpenNotifyEventHandler(  
& System.String^ FileName  
)
```

**NOTE:** See [Differences Between Unmanaged C++ and C++/CLI Code](#).

#### Parameters

*FileName*  
Name of the opened file

### Visual Basic for Applications (VBA) Syntax

See [NonNativeFileOpenNotify\\_Event \(SldWorks\)](#).

### Remarks

This event occurs after automatic healing if it is enabled. To enable automatic healing, set swlImportAutoRunlImportDiagnosticsPersist and swlImportAutoRunlImportDiagnostics to True. See [swUserPreferenceToggle\\_e](#), Import for details about these two enumerators.

The file types handled include files with these extensions: .dxf, .dwg, .igs, .sat, .step, .vda, .wrl, and .dll.

On receiving this event, you can call [ISldWorks::ActiveDoc](#) or [ISldWorks::IActiveDoc2](#) to get the active [IModelDoc2](#) pointer.

In an environment when multiple applications are simultaneously loaded and have access to the SOLIDWORKS application through its APIs, exercise caution when this notification is processed. The active IModelDoc2 may not be the one that corresponds to the FileName argument. For example, this can occur when one of the translator DLL's receives this event and picks up the non-native file and generates a new SOLIDWORKS document. This could happen prior to your application receiving this event.

If developing a C++ application, use [swAppNonNativeFileOpenNotify](#) to register for this notification.

### Availability

SOLIDWORKS 2001Plus FCS, Revision Number 10.0

# DSldWorksEvents\_On3DExperienceStateChangeNotifyEventHandler (Type)

SOLIDWORKS API Help

[Send comments on this topic.](#)

DSldWorksEvents\_On3DExperienceStateChangeNotifyEventHandler Delegate (SolidWorks.Interop.sldworks)

[See Also](#)



[SolidWorks.Interop.sldworks Namespace](#) : DSldWorksEvents\_On3DExperienceStateChangeNotifyEventHandler Delegate (SolidWorks.Interop.sldworks)

Fired when 3DExperience changes state.

## .NET Syntax

### Visual Basic (Declaration)

```
Public Delegate Function DSldWorksEvents_On3DExperienceStateChangeNotifyEventHandler( _  
    ByVal newState As System.Integer _  
) As System.Integer
```

### Visual Basic (Usage)



```
Dim instance As New DSldWorksEvents\_On3DExperienceStateChangeNotifyEventHandler(AddressOf  
HandlerMethod)
```

### C#

```
public delegate System.int DSldWorksEvents_On3DExperienceStateChangeNotifyEventHandler(  
    System.int newState  
)
```

### C++/CLI

```
public delegate System.int DSldWorksEvents_On3DExperienceStateChangeNotifyEventHandler(  
& System.int newState  
)
```

**NOTE:** See [Differences Between Unmanaged C++ and C++/CLI Code](#).

### Parameters

*newState*  
New state as defined by [sw3DExperienceState\\_e](#)

## Visual Basic for Applications (VBA) Syntax

See [On3DExperienceStateChangeNotify Event \(SldWorks\)](#).

## Remarks

If developing a C++ application, use [swAppOn3DExperienceStateChangeNotify](#) to register for this notification.

## Availability

SOLIDWORKS 2025 SP01, Revision Number 33.1

# DSldWorksEvents\_OnIdleNotifyEventHandler (Type)

DSldWorksEvents\_OnIdleNotifyEventHandler Delegate (SolidWorks.Interop.sldworks)

[See Also](#)



[SolidWorks.Interop.sldworks Namespace](#) : DSldWorksEvents\_OnIdleNotifyEventHandler Delegate (SolidWorks.Interop.sldworks)

Fired after all of the messages have been processed, included posted repaints; therefore, eliminating the need to call [IModelDoc2::GraphicsRedraw2](#).

## .NET Syntax

Visual Basic (Declaration)

```
Public Delegate Function DSldWorksEvents_OnIdleNotifyEventHandler() As System.Integer
```

Visual Basic (Usage)



```
Dim instance As New DSldWorksEvents\_OnIdleNotifyEventHandler(AddressOf HandlerMethod)
```

C#

```
public delegate System.int DSldWorksEvents_OnIdleNotifyEventHandler()
```

C++/CLI

```
public delegate System.int DSldWorksEvents_OnIdleNotifyEventHandler();
```

**NOTE:** See [Differences Between Unmanaged C++ and C++/CLI Code](#).

## Visual Basic for Applications (VBA) Syntax

See [OnIdleNotify\\_Event \(SldWorks\)](#).

## Remarks

If developing a C++ application, use [swAppOnIdleNotify](#) to register for this notification.

## Availability

SOLIDWORKS 2004 SP4, Revision Number 12.4

## DSldWorksEvents\_PromptForFilenameNotifyEventHandler (Type)

SOLIDWORKS API Help

[Send comments](#) on this topic.

DSldWorksEvents\_PromptForFilenameNotifyEventHandler Delegate (SolidWorks.Interop.sldworks)

[See Also](#)



[SolidWorks.Interop.sldworks Namespace](#) : DSldWorksEvents\_PromptForFilenameNotifyEventHandler Delegate (SolidWorks.Interop.sldworks)

Fired when a dependent document is missing from the file being opened.

### .NET Syntax

Visual Basic (Declaration)

```
Public Delegate Function DSldWorksEvents_PromptForFilenameNotifyEventHandler( _  
    ByVal openOrSave As System.Integer, _  
    ByVal suggestedFileName As System.String, _  
    ByVal DocType As System.Integer, _  
    ByVal cause As System.Integer _  
) As System.Integer
```

Visual Basic (Usage)



```
Dim instance As New DSldWorksEvents\_PromptForFilenameNotifyEventHandler(AddressOf HandlerMethod)
```

C#

```
public delegate System.int DSldWorksEvents_PromptForFilenameNotifyEventHandler(  
    System.int openOrSave,  
    System.string suggestedFileName,  
    System.int DocType,  
    System.int cause  
)
```

C++/CLI

```
public delegate System.int DSldWorksEvents_PromptForFilenameNotifyEventHandler(  
& System.int openOrSave,  
& System.String^ suggestedFileName,  
& System.int DocType,  
& System.int cause  
)
```

**NOTE:** See [Differences Between Unmanaged C++ and C++/CLI Code](#).

#### Parameters

*openOrSave*

- 0 = save
- 1 = open

*suggestedFileName*

Name of the missing SOLIDWORKS document

*DocType*

Type of the missing document as defined in [swDocumentTypes\\_e](#)

*cause*

Cause as defined in [swPromptForFilenameCause\\_e](#)

### Visual Basic for Applications (VBA) Syntax

See [PromptForFilenameNotify Event \(SldWorks\)](#).

### Remarks

Use this event with the [ISldWorks::SetPromptFilename2](#) method, not with the [ISldWorks::SetMissingReferencePathName](#) method.

An example of a good use for this event is when you are mirroring an assembly. If you want to create new files for the mirrored components, use this notification to specify the new filename. This is useful when you want to choose filenames for the newly created components during the mirroring process.

If developing a C++ application, use [swAppPromptForFileNameNotify](#) to register for this notification.



## DSldWorksEvents\_PromptForMultipleFileNamesNotifyEventHandler (Type)

SOLIDWORKS API Help

[Send comments](#) on this topic.

DSldWorksEvents\_PromptForMultipleFileNamesNotifyEventHandler Delegate (SolidWorks.Interop.sldworks)

[See Also](#)



[SolidWorks.Interop.sldworks Namespace](#) : DSldWorksEvents\_PromptForMultipleFileNamesNotifyEventHandler Delegate (SolidWorks.Interop.sldworks)

Fired when any dependent documents are missing from the file being opened.

### .NET Syntax

Visual Basic (Declaration)

```
Public Delegate Function DSldWorksEvents_PromptForMultipleFileNamesNotifyEventHandler( _  
    ByVal openOrSave As System.Integer, _  
    ByRef suggestedFileNames As System.Object, _  
    ByRef DocTypes As System.Object, _  
    ByVal cause As System.Integer _  
) As System.Integer
```

Visual Basic (Usage)



```
Dim instance As New DSldWorksEvents\_PromptForMultipleFileNamesNotifyEventHandler(AddressOf  
HandlerMethod)
```

C#

```
public delegate System.int DSldWorksEvents_PromptForMultipleFileNamesNotifyEventHandler(  
    System.int openOrSave,  
    ref System.object suggestedFileNames,  
    ref System.object DocTypes,  
    System.int cause  
)
```

C++/CLI

```
public delegate System.int DSldWorksEvents_PromptForMultipleFileNamesNotifyEventHandler(  
& System.int openOrSave,  
& System.Object^% suggestedFileNames,  
& System.Object^% DocTypes,  
& System.int cause  
)
```

**NOTE:** See [Differences Between Unmanaged C++ and C++/CLI Code](#).

### Parameters

*openOrSave*

- 0 = save
- 1 = open

*suggestedFileNames*

Array of names of the missing SOLIDWORKS documents

*DocTypes*

Types of the missing documents as defined in [swDocumentTypes\\_e](#)

*cause*

Cause as defined in [swPromptForFilenameCause\\_e](#)

### Visual Basic for Applications (VBA) Syntax

See [PromptForMultipleFileNamesNotify\\_Event \(SldWorks\)](#).

### Remarks

Use this event with the [ISldWorks::SetMultipleFileNamesPrompt](#) method.

If developing a C++ application, use [swAppPromptForMultipleFileNameNotify](#) to register for this notification.

### Availability

SOLIDWORKS 2008 SP1, Revision Number 16.1

# DSldWorksEvents\_PropertySheetCreateNotifyEventHandler (Type)

DSldWorksEvents\_PropertySheetCreateNotifyEventHandler Delegate (SolidWorks.Interop.sldworks)

[See Also](#)



[SolidWorks.Interop.sldworks Namespace](#) : DSldWorksEvents\_PropertySheetCreateNotifyEventHandler Delegate (SolidWorks.Interop.sldworks)

Notifies the user program when an exported [ISWPropertySheet](#) is created so that the application can add pages to it.

## .NET Syntax

Visual Basic (Declaration)

```
Public Delegate Function DSldWorksEvents_PropertySheetCreateNotifyEventHandler( _  
    ByVal Sheet As System.Object, _  
    ByVal sheetType As System.Integer _  
) As System.Integer
```

Visual Basic (Usage)



```
Dim instance As New DSldWorksEvents\_PropertySheetCreateNotifyEventHandler(AddressOf HandlerMethod)
```

C#

```
public delegate System.int DSldWorksEvents_PropertySheetCreateNotifyEventHandler(  
    System.object Sheet,  
    System.int sheetType  
)
```

C++/CLI

```
public delegate System.int DSldWorksEvents_PropertySheetCreateNotifyEventHandler(  
& System.Object^ Sheet,  
& System.int sheetType  
)
```

**NOTE:** See [Differences Between Unmanaged C++ and C++/CLI Code](#).

### Parameters

*Sheet*  
[Property sheet](#)  
*sheetType*  
Type of the property sheet as defined in [swPropSheetType\\_e](#)

## Visual Basic for Applications (VBA) Syntax

See [PropertySheetCreateNotify Event \(SldWorks\)](#).

## Remarks

If developing a C++ application, use [swAppPropertySheetCreateNotify](#) to register for this notification.

## Availability

SOLIDWORKS 2001Plus FCS, Revision Number 10.0

# DSldWorksEvents\_ReferencedFilePreNotify2EventHandler (Type)

SOLIDWORKS API Help

[Send comments on this topic.](#)

DSldWorksEvents\_ReferencedFilePreNotify2EventHandler Delegate (SolidWorks.Interop.sldworks)

[See Also](#)



[SolidWorks.Interop.sldworks Namespace](#) : DSldWorksEvents\_ReferencedFilePreNotify2EventHandler Delegate (SolidWorks.Interop.sldworks)

Notifies the user program before SOLIDWORKS opens the specified file with the specified status.

## .NET Syntax

Visual Basic (Declaration)

```
Public Delegate Function DSldWorksEvents_ReferencedFilePreNotify2EventHandler( _  
    ByVal FileName As System.String, _  
    ByVal FileStatus As System.Integer _  
) As System.Integer
```

Visual Basic (Usage)



```
Dim instance As New DSldWorksEvents\_ReferencedFilePreNotify2EventHandler(AddressOf HandlerMethod)
```

C#

```
public delegate System.int DSldWorksEvents_ReferencedFilePreNotify2EventHandler(  
    System.string FileName,  
    System.int FileStatus  
)
```

C++/CLI

```
public delegate System.int DSldWorksEvents_ReferencedFilePreNotify2EventHandler(  
& System.String^ FileName,  
& System.int FileStatus  
)
```

**NOTE:** See [Differences Between Unmanaged C++ and C++/CLI Code](#).

### Parameters

*FileName*

Path and filename of file to open

*FileStatus*

Open status as defined in [swReferencedFileStatus\\_e](#)

## Visual Basic for Applications (VBA) Syntax

See [ReferencedFilePreNotify2 Event \(SldWorks\)](#).

## Remarks

If developing a C++ application, use [swAppReferencedFilePreNotify2](#) to register for this notification.

## Availability

SOLIDWORKS 2019 FCS, Revision Number 27.0

# DSldWorksEvents\_ReferencedFilePreNotifyEventHandler (Type)

DSldWorksEvents\_ReferencedFilePreNotifyEventHandler Delegate (SolidWorks.Interop.sldworks)

[See Also](#)



[SolidWorks.Interop.sldworks Namespace](#) : DSldWorksEvents\_ReferencedFilePreNotifyEventHandler Delegate (SolidWorks.Interop.sldworks)

Obsolete. Superseded by [DSldWorksEvents\\_ReferencedFilePreNotify2EventHandler](#).

## .NET Syntax

### Visual Basic (Declaration)

```
Public Delegate Function DSldWorksEvents_ReferencedFilePreNotifyEventHandler( _  
    ByVal FileName As System.String _  
) As System.Integer
```

### Visual Basic (Usage)



```
Dim instance As New DSldWorksEvents\_ReferencedFilePreNotifyEventHandler(AddressOf HandlerMethod)
```

### C#

```
public delegate System.int DSldWorksEvents_ReferencedFilePreNotifyEventHandler(  
    System.string FileName  
)
```

### C++/CLI

```
public delegate System.int DSldWorksEvents_ReferencedFilePreNotifyEventHandler(  
& System.String^ FileName  
)
```

**NOTE:** See [Differences Between Unmanaged C++ and C++/CLI Code](#).

### Parameters

*FileName*  
Path and filename of referenced file

## Visual Basic for Applications (VBA) Syntax

See [ReferencedFilePreNotify Event \(SldWorks\)](#).

## Remarks

If developing a C++ application, use [swAppReferencedFilePreNotify](#) to register for this notification.

## Availability

SOLIDWORKS 2005 SP1, Revision Number 13.1

## DSldWorksEvents\_ReferenceNotFoundNotifyEventHandler (Type)

SOLIDWORKS API Help

[Send comments on this topic.](#)

DSldWorksEvents\_ReferenceNotFoundNotifyEventHandler Delegate (SolidWorks.Interop.sldworks)

[See Also](#)



[SolidWorks.Interop.sldworks Namespace](#) : DSldWorksEvents\_ReferenceNotFoundNotifyEventHandler Delegate (SolidWorks.Interop.sldworks)

Notifies the user program before SOLIDWORKS displays a dialog box prompting the end-user to browse for the referenced file.

### .NET Syntax

Visual Basic (Declaration)

```
Public Delegate Function DSldWorksEvents_ReferenceNotFoundNotifyEventHandler( _  
    ByVal FileName As System.String _  
) As System.Integer
```

Visual Basic (Usage)



```
Dim instance As New DSldWorksEvents\_ReferenceNotFoundNotifyEventHandler(AddressOf HandlerMethod)
```

C#

```
public delegate System.int DSldWorksEvents_ReferenceNotFoundNotifyEventHandler(  
    System.string FileName  
)
```

C++/CLI

```
public delegate System.int DSldWorksEvents_ReferenceNotFoundNotifyEventHandler(  
& System.String^ FileName  
)
```

**NOTE:** See [Differences Between Unmanaged C++ and C++/CLI Code](#).

#### Parameters

*FileName*

Path and filename of the referenced file

### Visual Basic for Applications (VBA) Syntax

See [ReferenceNotFoundNotify\\_Event \(SldWorks\)](#).

### Example

This code illustrates the proper use of this event:

```
HRESULT swAppEvents::AppReferenceNotFoundNotify (BSTR FileName)  
{  
  
    static bool test = true;  
    TRACE( _T(" TestbedEvents - SldWorks.swAppReferenceNotFoundNotify event fired\n"));  
    if( test)  
    {  
        LPSLDWORKS pSldWorks = NULL;  
        m_lpObject->QueryInterface(IID_ISldWorks, (void*)&pSldWorks);  
        pSldWorks->SetMissingReferencePathName( FileName);  
        pSldWorks->Release();  
        return S_false;  
    }  
    else  
        return S_OK;
```

}

#### Remarks

Use this event with [ISldWorks::SetMissingReferencePathName](#). Returning S\_false from your event handler successfully replaces the specified fileName with the filename specified in the call to ISldWorks::SetMissingReferencePathName.

This event is generated when a document is opened and one of its dependencies is not found.

If developing a C++ application, use [swAppReferenceNotFoundNotify](#) to register for this notification.

#### Availability

SOLIDWORKS 2001Plus FCS, Revision Number 10.0

# DSldWorksEvents\_TaskPaneCollapseNotifyEventHandler (Type)

DSldWorksEvents\_TaskPaneCollapseNotifyEventHandler Delegate (SolidWorks.Interop.sldworks)

[See Also](#) [Example](#)



[SolidWorks.Interop.sldworks Namespace](#) : DSldWorksEvents\_TaskPaneCollapseNotifyEventHandler Delegate (SolidWorks.Interop.sldworks)

Fired when the Task Pane collapses.

## .NET Syntax

### Visual Basic (Declaration)

```
Public Delegate Function DSldWorksEvents_TaskPaneCollapseNotifyEventHandler() As System.Integer
```

### Visual Basic (Usage)



```
Dim instance As New DSldWorksEvents\_TaskPaneCollapseNotifyEventHandler(AddressOf HandlerMethod)
```

### C#

```
public delegate System.int DSldWorksEvents_TaskPaneCollapseNotifyEventHandler()
```

### C++/CLI

```
public delegate System.int DSldWorksEvents_TaskPaneCollapseNotifyEventHandler();
```

**NOTE:** See [Differences Between Unmanaged C++ and C++/CLI Code](#).

## Visual Basic for Applications (VBA) Syntax

See [TaskPaneCollapseNotify Event \(SldWorks\)](#).

## Example

[Create Task Pane View Add-in \(C#\)](#).

## Remarks

If developing a C++ application, use [swAppTaskPaneCollapseNotify](#) to register for this notification.

## Availability

SOLIDWORKS 2024 SP02, Revision Number 32.2

# DSldWorksEvents\_TaskPaneExpandNotifyEventHandler (Type)

SOLIDWORKS API Help

[Send comments on this topic.](#)

DSldWorksEvents\_TaskPaneExpandNotifyEventHandler Delegate (SolidWorks.Interop.sldworks)

[See Also](#) [Example](#)



[SolidWorks.Interop.sldworks Namespace](#) : DSldWorksEvents\_TaskPaneExpandNotifyEventHandler Delegate (SolidWorks.Interop.sldworks)

Fired when the Task Pane expands.

## .NET Syntax

Visual Basic (Declaration)

Public Delegate Function DSldWorksEvents\_TaskPaneExpandNotifyEventHandler() As System.Integer

Visual Basic (Usage)

 Copy Code

Dim instance As New [DSldWorksEvents\\_TaskPaneExpandNotifyEventHandler](#)(AddressOf HandlerMethod)

C#

public delegate System.int DSldWorksEvents\_TaskPaneExpandNotifyEventHandler()

C++/CLI

public delegate System.int DSldWorksEvents\_TaskPaneExpandNotifyEventHandler();

**NOTE:** See [Differences Between Unmanaged C++ and C++/CLI Code](#).

## Visual Basic for Applications (VBA) Syntax

See [TaskPaneExpandNotify Event \(SldWorks\)](#).

## Example

[Create Task Pane View Add-in \(C#\)](#).

## Remarks

If developing a C++ application, use [swAppTaskPaneExpandNotify](#) to register for this notification.

## Availability

SOLIDWORKS 2024 SP02, Revision Number 32.2

# DSldWorksEvents\_TaskPaneHideNotifyEventHandler (Type)

DSldWorksEvents\_TaskPaneHideNotifyEventHandler Delegate (SolidWorks.Interop.sldworks)

[See Also](#) [Example](#)



[SolidWorks.Interop.sldworks Namespace](#) : DSldWorksEvents\_TaskPaneHideNotifyEventHandler Delegate (SolidWorks.Interop.sldworks)

Fired when the Task Pane hides.

## .NET Syntax

### Visual Basic (Declaration)

```
Public Delegate Function DSldWorksEvents_TaskPaneHideNotifyEventHandler() As System.Integer
```

### Visual Basic (Usage)



```
Dim instance As New DSldWorksEvents\_TaskPaneHideNotifyEventHandler(AddressOf HandlerMethod)
```

### C#

```
public delegate System.int DSldWorksEvents_TaskPaneHideNotifyEventHandler()
```

### C++/CLI

```
public delegate System.int DSldWorksEvents_TaskPaneHideNotifyEventHandler();
```

**NOTE:** See [Differences Between Unmanaged C++ and C++/CLI Code](#).

## Visual Basic for Applications (VBA) Syntax

See [TaskPaneHideNotify Event \(SldWorks\)](#).

## Example

[Create Task Pane View Add-in \(C#\)](#).

## Remarks

If developing a C++ application, use [swAppTaskPaneHideNotify](#) to register for this notification.

## Availability

SOLIDWORKS 2024 SP02, Revision Number 32.2

# DSldWorksEvents\_TaskPanePinnedNotifyEventHandler (Type)

DSldWorksEvents\_TaskPanePinnedNotifyEventHandler Delegate (SolidWorks.Interop.sldworks)

[See Also](#) [Example](#)



[SolidWorks.Interop.sldworks Namespace](#) : DSldWorksEvents\_TaskPanePinnedNotifyEventHandler Delegate (SolidWorks.Interop.sldworks)

Fired when the Task Pane is pinned.

## .NET Syntax

### Visual Basic (Declaration)

```
Public Delegate Function DSldWorksEvents_TaskPanePinnedNotifyEventHandler() As System.Integer
```

### Visual Basic (Usage)

```
Dim instance As New DSldWorksEvents\_TaskPanePinnedNotifyEventHandler(AddressOf HandlerMethod)
```

### C#

```
public delegate System.int DSldWorksEvents_TaskPanePinnedNotifyEventHandler()
```

### C++/CLI

```
public delegate System.int DSldWorksEvents_TaskPanePinnedNotifyEventHandler();
```

**NOTE:** See [Differences Between Unmanaged C++ and C++/CLI Code](#).

## Visual Basic for Applications (VBA) Syntax

See [TaskPanePinnedNotify\\_Event \(SldWorks\)](#).

## Example

[Create Task Pane View Add-in \(C#\)](#).

## Remarks

If developing a C++ application, use [swAppTaskPanePinnedNotify](#) to register for this notification.

## Availability

SOLIDWORKS 2024 SP02, Revision Number 32.2

# DSldWorksEvents\_TaskPaneShowNotifyEventHandler (Type)

DSldWorksEvents\_TaskPaneShowNotifyEventHandler Delegate (SolidWorks.Interop.sldworks)

[See Also](#) [Example](#)



[SolidWorks.Interop.sldworks Namespace](#) : DSldWorksEvents\_TaskPaneShowNotifyEventHandler Delegate (SolidWorks.Interop.sldworks)

Fired when the Task Pane displays.

## .NET Syntax

### Visual Basic (Declaration)

```
Public Delegate Function DSldWorksEvents_TaskPaneShowNotifyEventHandler() As System.Integer
```

### Visual Basic (Usage)



```
Dim instance As New DSldWorksEvents\_TaskPaneShowNotifyEventHandler(AddressOf HandlerMethod)
```

### C#

```
public delegate System.int DSldWorksEvents_TaskPaneShowNotifyEventHandler()
```

### C++/CLI

```
public delegate System.int DSldWorksEvents_TaskPaneShowNotifyEventHandler();
```

**NOTE:** See [Differences Between Unmanaged C++ and C++/CLI Code](#).

## Visual Basic for Applications (VBA) Syntax

See [TaskPaneShowNotify\\_Event \(SldWorks\)](#).

## Example

[Create Task Pane View Add-in \(C#\)](#).

## Remarks

If developing a C++ application, use [swAppTaskPaneShowNotify](#) to register for this notification.

## Availability

SOLIDWORKS 2024 SP02, Revision Number 32.2

# DSldWorksEvents\_TaskPaneUnpinnedNotifyEventHandler (Type)

DSldWorksEvents\_TaskPaneUnpinnedNotifyEventHandler Delegate (SolidWorks.Interop.sldworks)

[See Also](#) [Example](#)



[SolidWorks.Interop.sldworks Namespace](#) : DSldWorksEvents\_TaskPaneUnpinnedNotifyEventHandler Delegate (SolidWorks.Interop.sldworks)

Fired when the Task Pane is unpinned.

## .NET Syntax

### Visual Basic (Declaration)

```
Public Delegate Function DSldWorksEvents_TaskPaneUnpinnedNotifyEventHandler() As System.Integer
```

### Visual Basic (Usage)

```
Dim instance As New DSldWorksEvents\_TaskPaneUnpinnedNotifyEventHandler(AddressOf HandlerMethod)
```

### C#

```
public delegate System.int DSldWorksEvents_TaskPaneUnpinnedNotifyEventHandler()
```

### C++/CLI

```
public delegate System.int DSldWorksEvents_TaskPaneUnpinnedNotifyEventHandler();
```

**NOTE:** See [Differences Between Unmanaged C++ and C++/CLI Code](#).

## Visual Basic for Applications (VBA) Syntax

See [TaskPaneUnpinnedNotify\\_Event \(SldWorks\)](#).

## Example

[Create Task Pane View Add-in \(C#\)](#).

## Remarks

If developing a C++ application, use [swAppTaskPaneUnpinnedNotify](#) to register for this notification.

## Availability

# DSWPropertySheetEvents\_CreateControlNotifyEventHandler (Type)

DSWPropertySheetEvents\_CreateControlNotifyEventHandler Delegate (SolidWorks.Interop.sldworks)

[See Also](#)



[SolidWorks.Interop.sldworks Namespace](#) : DSWPropertySheetEvents\_CreateControlNotifyEventHandler Delegate (SolidWorks.Interop.sldworks)

Fired when the ActiveX control is created on the property page.

## .NET Syntax

### Visual Basic (Declaration)

```
Public Delegate Function DSWPropertySheetEvents_CreateControlNotifyEventHandler( _  
    ByVal PageIndex As System.Integer, _  
    ByVal ControlDispatch As System.Object _  
) As System.Integer
```

### Visual Basic (Usage)



```
Dim instance As New DSWPropertySheetEvents\_CreateControlNotifyEventHandler(AddressOf  
HandlerMethod)
```

### C#

```
public delegate System.int DSWPropertySheetEvents_CreateControlNotifyEventHandler(  
    System.int PageIndex,  
    System.object ControlDispatch  
)
```

### C++/CLI

```
public delegate System.int DSWPropertySheetEvents_CreateControlNotifyEventHandler(  
& System.int PageIndex,  
& System.Object^ ControlDispatch  
)
```

**NOTE:** See [Differences Between Unmanaged C++ and C++/CLI Code](#).

### Parameters

*PageIndex*  
Index of property page within the property sheet for the add-in (see **Remarks**)  
*ControlDispatch*  
ActiveX control

### Return Value

ActiveX control

## Visual Basic for Applications (VBA) Syntax

See [CreateControlNotify Event \(SldWorks\)](#).

## Remarks

If PageIndex is the same index as returned by [ISWPropertySheet::AddActivePage](#), then ControlDispatch will contain the Dispatch pointer of the ActiveX control.

If developing a C++ application, use [swPropertySheetCreateControlNotify](#) to register for this notification.

## Availability

# DSWPropertySheetEvents\_DestroyNotifyEventHandler (Type)

DSWPropertySheetEvents\_DestroyNotifyEventHandler Delegate (SolidWorks.Interop.sldworks)

[See Also](#)



[SolidWorks.Interop.sldworks Namespace](#) : DSWPropertySheetEvents\_DestroyNotifyEventHandler Delegate (SolidWorks.Interop.sldworks)

Fired when the property sheet is in the process of being destroyed.

## .NET Syntax

Visual Basic (Declaration)

```
Public Delegate Function DSWPropertySheetEvents_DestroyNotifyEventHandler() As System.Integer
```

Visual Basic (Usage)



```
Dim instance As New DSWPropertySheetEvents\_DestroyNotifyEventHandler(AddressOf HandlerMethod)
```

C#

```
public delegate System.int DSWPropertySheetEvents_DestroyNotifyEventHandler()
```

C++/CLI

```
public delegate System.int DSWPropertySheetEvents_DestroyNotifyEventHandler();
```

**NOTE:** See [Differences Between Unmanaged C++ and C++/CLI Code](#).

## Visual Basic for Applications (VBA) Syntax

See [DestroyNotify Event \(SWPropertySheet\)](#).

## Remarks

When this event is fired, the window associated with the destroyed property sheet is still alive, but any API pages have already been removed.

If developing a C++ application, use [swPropertySheetDestroyNotify](#) to register for this notification.

## Availability

SOLIDWORKS 2001Plus FCS, Revision Number 10.0

# DSWPropertySheetEvents\_HelpNotifyEventHandler (Type)

DSWPropertySheetEvents\_HelpNotifyEventHandler Delegate (SolidWorks.Interop.sldworks)

[See Also](#)



[SolidWorks.Interop.sldworks Namespace](#) : DSWPropertySheetEvents\_HelpNotifyEventHandler Delegate (SolidWorks.Interop.sldworks)

Fired when the Help button is clicked on a property sheet.

## .NET Syntax

### Visual Basic (Declaration)

```
Public Delegate Function DSWPropertySheetEvents_HelpNotifyEventHandler( _  
    ByVal PageIndex As System.Integer _  
) As System.Integer
```

### Visual Basic (Usage)



```
Dim instance As New DSWPropertySheetEvents\_HelpNotifyEventHandler(AddressOf HandlerMethod)
```

### C#

```
public delegate System.int DSWPropertySheetEvents_HelpNotifyEventHandler(  
    System.int PageIndex  
)
```

### C++/CLI

```
public delegate System.int DSWPropertySheetEvents_HelpNotifyEventHandler(  
& System.int PageIndex  
)
```

**NOTE:** See [Differences Between Unmanaged C++ and C++/CLI Code](#).

### Parameters

*PageIndex*  
Page index of the add-in's Help

## Visual Basic for Applications (VBA) Syntax

See [HelpNotify\\_Event \(SWPropertySheet\)](#).

## Remarks

Your application should only display Help if you have added a Help page.

For add-ins, if PageIndex is the same as the value returned by [ISWPropertySheet::AddActivePage](#), then the add-in can display its Help.

If developing a C++ application, use [swPropertySheetHelpNotify](#) to register for this notification.

## Availability

SOLIDWORKS 2001Plus FCS, Revision Number 10.0

# DSWPropertySheetEvents\_OnCancelNotifyEventHandler (Type)

DSWPropertySheetEvents\_OnCancelNotifyEventHandler Delegate (SolidWorks.Interop.sldworks)

[See Also](#)



[SolidWorks.Interop.sldworks Namespace](#) : DSWPropertySheetEvents\_OnCancelNotifyEventHandler Delegate (SolidWorks.Interop.sldworks)

Fired when the Cancel button on the property sheet is clicked. Your add-in can perform clean-up activities in this event.

## .NET Syntax

Visual Basic (Declaration)

```
Public Delegate Function DSWPropertySheetEvents_OnCancelNotifyEventHandler() As System.Integer
```

Visual Basic (Usage)

```
Dim instance As New DSWPropertySheetEvents\_OnCancelNotifyEventHandler(AddressOf HandlerMethod)
```

C#

```
public delegate System.int DSWPropertySheetEvents_OnCancelNotifyEventHandler()
```

C++/CLI

```
public delegate System.int DSWPropertySheetEvents_OnCancelNotifyEventHandler();
```

**NOTE:** See [Differences Between Unmanaged C++ and C++/CLI Code](#).

## Visual Basic for Applications (VBA) Syntax

See [OnCancelNotify Event \(SWPropertySheet\)](#).

## Remarks

If developing a C++ application, use [swPropertySheetOnCancelNotify](#) to register for this notification.

## Availability

SOLIDWORKS 2004 SP4, Revision Number 12.4

# DSWPropertySheetEvents\_OnOKNotifyEventHandler (Type)

SOLIDWORKS API Help

[Send comments on this topic.](#)

DSWPropertySheetEvents\_OnOKNotifyEventHandler Delegate (SolidWorks.Interop.sldworks)

[See Also](#)



[SolidWorks.Interop.sldworks Namespace](#) : DSWPropertySheetEvents\_OnOKNotifyEventHandler Delegate (SolidWorks.Interop.sldworks)

Fired when the OK button on the property sheet is clicked.

## .NET Syntax

Visual Basic (Declaration)

```
Public Delegate Function DSWPropertySheetEvents_OnOKNotifyEventHandler() As System.Integer
```

Visual Basic (Usage)



```
Dim instance As New DSWPropertySheetEvents\_OnOKNotifyEventHandler(AddressOf HandlerMethod)
```

C#

```
public delegate System.int DSWPropertySheetEvents_OnOKNotifyEventHandler()
```

C++/CLI

```
public delegate System.int DSWPropertySheetEvents_OnOKNotifyEventHandler();
```

**NOTE:** See [Differences Between Unmanaged C++ and C++/CLI Code](#).

## Visual Basic for Applications (VBA) Syntax

See [OnOKNotify Event \(SWPropertySheet\)](#).

## Remarks

Your add-in can perform clean-up activities in this event. Typically, this event calls [ISWPropertySheet::GetControl](#) to retrieve data from your ActiveX control.

If developing a C++ application, use [swPropertySheetOnOKNotify](#) to register for this notification.

## Availability

SOLIDWORKS 2004 SP4, Revision Number 12.4

# DTaskpaneViewEvents\_TaskPaneActivateNotifyEventHandler (Type)

SOLIDWORKS API Help

[Send comments](#) on this topic.

DTaskpaneViewEvents\_TaskPaneActivateNotifyEventHandler Delegate (SolidWorks.Interop.sldworks)

[See Also](#) [Example](#)



[SolidWorks.Interop.sldworks Namespace](#) : DTaskpaneViewEvents\_TaskPaneActivateNotifyEventHandler Delegate (SolidWorks.Interop.sldworks)

Post-notifies the user program when an application-level Task Pane view is activated.

## .NET Syntax

### Visual Basic (Declaration)

```
Public Delegate Function DTaskpaneViewEvents_TaskPaneActivateNotifyEventHandler() As System.Integer
```

### Visual Basic (Usage)



```
Dim instance As New DTaskpaneViewEvents\_TaskPaneActivateNotifyEventHandler(AddressOf HandlerMethod)
```

### C#

```
public delegate System.int DTaskpaneViewEvents_TaskPaneActivateNotifyEventHandler()
```

### C++/CLI

```
public delegate System.int DTaskpaneViewEvents_TaskPaneActivateNotifyEventHandler();
```

**NOTE:** See [Differences Between Unmanaged C++ and C++/CLI Code](#).

## Visual Basic for Applications (VBA) Syntax

See [TaskPaneActivateNotify Event \(TaskpaneView\)](#).

## Example

[Add Buttons to Task Pane \(VBA\)](#)  
[Add Buttons to Task Pane \(VB.NET\)](#)  
[Add Buttons to Task Pane \(C#\)](#)

## Remarks

If developing a C++ application, use [swAppTaskPaneActivateNotify](#) to register for this notification.

## Availability

SOLIDWORKS 2006 FCS, Revision Number 14.0

# DTaskpaneViewEvents\_TaskPaneDeactivateNotifyEventHandler (Type)

SOLIDWORKS API Help

[Send comments on this topic.](#)

DTaskpaneViewEvents\_TaskPaneDeactivateNotifyEventHandler Delegate (SolidWorks.Interop.sldworks)

[See Also](#)



[SolidWorks.Interop.sldworks Namespace](#) : DTaskpaneViewEvents\_TaskPaneDeactivateNotifyEventHandler Delegate (SolidWorks.Interop.sldworks)

Post-notifies the user program when an application-level Task Pane view is deactivated.

## .NET Syntax

Visual Basic (Declaration)

```
Public Delegate Function DTaskpaneViewEvents_TaskPaneDeactivateNotifyEventHandler() As System.Integer
```

Visual Basic (Usage)

```
Dim instance As New DTaskpaneViewEvents\_TaskPaneDeactivateNotifyEventHandler(AddressOf HandlerMethod)
```

C#

```
public delegate System.int DTaskpaneViewEvents_TaskPaneDeactivateNotifyEventHandler()
```

C++/CLI

```
public delegate System.int DTaskpaneViewEvents_TaskPaneDeactivateNotifyEventHandler();
```

**NOTE:** See [Differences Between Unmanaged C++ and C++/CLI Code](#).

## Visual Basic for Applications (VBA) Syntax

See [TaskPaneDeactivateNotify\\_Event \(TaskpaneView\)](#).

## Remarks

If developing a C++ application, use [swAppTaskPaneDeactivateNotify](#) to register for this notification.

## Availability

SOLIDWORKS 2006 FCS, Revision Number 14.0

# DTaskpaneViewEvents\_TaskPaneDestroyNotifyEventHandler (Type)

SOLIDWORKS API Help

[Send comments on this topic.](#)

DTaskpaneViewEvents\_TaskPaneDestroyNotifyEventHandler Delegate (SolidWorks.Interop.sldworks)

[See Also](#) [Example](#)



[SolidWorks.Interop.sldworks Namespace](#) : DTaskpaneViewEvents\_TaskPaneDestroyNotifyEventHandler Delegate (SolidWorks.Interop.sldworks)

Pre-notifies the user program when an application-level Task Pane view is about to be destroyed.

## .NET Syntax

Visual Basic (Declaration)

```
Public Delegate Function DTaskpaneViewEvents_TaskPaneDestroyNotifyEventHandler() As System.Integer
```

Visual Basic (Usage)



```
Dim instance As New DTaskpaneViewEvents\_TaskPaneDestroyNotifyEventHandler(AddressOf HandlerMethod)
```

C#

```
public delegate System.int DTaskpaneViewEvents_TaskPaneDestroyNotifyEventHandler()
```

C++/CLI

```
public delegate System.int DTaskpaneViewEvents_TaskPaneDestroyNotifyEventHandler();
```

**NOTE:** See [Differences Between Unmanaged C++ and C++/CLI Code](#).

## Visual Basic for Applications (VBA) Syntax

See [TaskPaneDestroyNotify Event \(TaskpaneView\)](#).

## Example

[Add Buttons to Task Pane \(VBA\)](#)  
[Add Buttons to Task Pane \(VB.NET\)](#)  
[Add Buttons to Task Pane \(C#\)](#)

## Remarks

If developing a C++ application, use [swAppTaskPaneDestroyNotify](#) to register for this notification.

## Availability

SOLIDWORKS 2006 FCS, Revision Number 14.0

# DTaskpaneViewEvents\_TaskPaneToolBarButtonClickedEventHandler (Type)

SOLIDWORKS API Help

[Send comments](#) on this topic.

DTaskpaneViewEvents\_TaskPaneToolBarButtonClickedEventHandler Delegate (SolidWorks.Interop.sldworks)

[See Also](#) [Example](#)



[SolidWorks.Interop.sldworks Namespace](#) : DTaskpaneViewEvents\_TaskPaneToolBarButtonClickedEventHandler Delegate (SolidWorks.Interop.sldworks)

Fired when a toolbar button on the Task Pane is clicked.

## .NET Syntax

### Visual Basic (Declaration)

```
Public Delegate Function DTaskpaneViewEvents_TaskPaneToolBarButtonClickedEventHandler( _  
    ByVal ButtonIndex As System.Integer _  
) As System.Integer
```

### Visual Basic (Usage)



```
Dim instance As New DTaskpaneViewEvents\_TaskPaneToolBarButtonClickedEventHandler(AddressOf  
HandlerMethod)
```

### C#

```
public delegate System.int DTaskpaneViewEvents_TaskPaneToolBarButtonClickedEventHandler(  
    System.int ButtonIndex  
)
```

### C++/CLI

```
public delegate System.int DTaskpaneViewEvents_TaskPaneToolBarButtonClickedEventHandler(  
& System.int ButtonIndex  
)
```

**NOTE:** See [Differences Between Unmanaged C++ and C++/CLI Code](#).

### Parameters

*ButtonIndex*

Index of the toolbar button on the Task Pane that was clicked

## Visual Basic for Applications (VBA) Syntax

See [TaskPaneToolBarButtonClicked Event \(TaskpaneView\)](#).

## Example

[Add Buttons to Task Pane \(VBA\)](#)  
[Add Buttons to Task Pane \(VB.NET\)](#)  
[Add Buttons to Task Pane \(C#\)](#)

## Remarks

If developing a C++ application, use [swAppTaskPaneToolBarButtonClicked](#) to register for this notification.

## Availability

SOLIDWORKS 2011 FCS, Revision Number 19.0