

SOLIDWORKS API (.NET VBA C#) — Reference (45/337): ICommandManager-ICommandTabBox

SOLIDWORKS API Documentation (converted from CHM)

ICommandManager (Type)

ICommandManager Interface

[See Also](#) [Members](#) [Example](#)



[SolidWorks.Interop.sldworks Namespace](#) : ICommandManager Interface

Allows add-in applications to add and remove [CommandGroups](#) (menus and toolbars) to the CommandManager.
NOTE: Click the **Members** link, located near the top of the topic, to see this interface's methods and properties.

.NET Syntax

Visual Basic (Declaration)

```
Public Interface ICommandManager
```

Visual Basic (Usage)

```
Dim instance As ICommandManager
```

C#

```
public interface ICommandManager
```

C++/CLI

```
public interface class ICommandManager
```

Visual Basic for Applications (VBA) Syntax

See [CommandManager](#).

Example

[Create Flyouts in the CommandManager \(C#\)](#)
[Create Flyouts in the CommandManager \(VB.NET\)](#)
[Create Submenus in the CommandManager \(C#\)](#)

Remarks

Only one CommandManager can exist in an add-in application.
See [CommandManager and CommandGroups](#) to learn how to create a CommandManager and add and remove CommandGroups.

Accessors

[ISldWorks::GetCommandManager](#)

Access Diagram

[CommandManager](#)

See Also

[ICommandManager Members](#)
[SolidWorks.Interop.sldworks Namespace](#)

ICommandManager Interface Members

[See Also](#) [Properties](#) [Methods](#)



[SolidWorks.Interop.sldworks Namespace](#) : ICommandManager Interface

The following tables list the members exposed by [ICommandManager](#).

Public Properties

Name	Description
 NumberOfFlyoutGroups	Gets the number of flyouts in the CommandManager.
 NumberOfGroups	Gets the number of CommandGroups.

[Top](#)

Public Methods

Name	Description
 AddCommandTab	Adds a tab to the CommandManager for the specified document type.
 AddContextMenu	Adds a new context-sensitive menu to the CommandManager.
 CommandTabs	Gets all of the add-in CommandManager tabs for the specified document type.
 CreateCommandGroup	Obsolete. Superseded by ICommandManager.CreateCommandGroup2 .
 CreateCommandGroup2	Creates a new CommandGroup in the CommandManager.
 CreateFlyoutGroup	Obsolete. Superseded by ICommandManager.CreateFlyoutGroup2 .
 CreateFlyoutGroup2	Creates a new flyout in the CommandManager and context-sensitive menus.
 GetCommandGroup	Gets the CommandGroup using the specified ID.
 GetCommandIDsCount	Gets the number of command IDs for the given command group.
 GetCommandTab	Gets the specified CommandManager tab for the specified document type.
 GetCommandTabCount	Gets the number of tabs on the CommandManager for the specified document type.
 GetFlyoutGroup	Gets the flyout with the specified ID.
 GetFlyoutGroups	Gets the flyouts in the CommandManager.
 GetGroupDataFromRegistry	Gets the command IDs of the given command group from the registry.
 GetGroups	Gets the CommandGroups in the CommandManager.
 IGetCommandTabs	Gets the CommandManager tabs for the specified document type.
 IGroupDataFromRegistry	Gets the command IDs of the given command group from the registry.
 IGetGroups	Gets the CommandGroups in the CommandManager.
 RemoveCommandGroup	Obsolete. Superseded by ICommandManager.RemoveCommandGroup2 .
 RemoveCommandGroup2	Removes the specified CommandGroup from the CommandManager.
 RemoveCommandTab	Removes the specified CommandManager tab, including its tab boxes and buttons, from the CommandManager.
 RemoveFlyoutGroup	Removes the specified flyout from the CommandManager.

[Top](#)

See Also

[ICommandManager Interface](#)
[SolidWorks.Interop.sldworks Namespace](#)

SOLIDWORKS API Help

[Send comments](#) on this topic.

ICommandManager Interface Methods

[See Also](#)



[SolidWorks.Interop.sldworks Namespace](#) : ICommandManager Interface

For a list of all members of this type, see [ICommandManager members](#).

Public Methods

Name	Description
 AddCommandTab	Adds a tab to the CommandManager for the specified document type.

	AddContextMenu	Adds a new context-sensitive menu to the CommandManager.
	CommandTabs	Gets all of the add-in CommandManager tabs for the specified document type.
	CreateCommandGroup	Obsolete. Superseded by ICommandManager.CreateCommandGroup2 .
	CreateCommandGroup2	Creates a new CommandGroup in the CommandManager.
	CreateFlyoutGroup	Obsolete. Superseded by ICommandManager.CreateFlyoutGroup2 .
	CreateFlyoutGroup2	Creates a new flyout in the CommandManager and context-sensitive menus.
	GetCommandGroup	Gets the CommandGroup using the specified ID.
	GetCommandIdsCount	Gets the number of command IDs for the given command group.
	GetCommandTab	Gets the specified CommandManager tab for the specified document type.
	GetCommandTabCount	Gets the number of tabs on the CommandManager for the specified document type.
	GetFlyoutGroup	Gets the flyout with the specified ID.
	GetFlyoutGroups	Gets the flyouts in the CommandManager.
	GetGroupDataFromRegistry	Gets the command IDs of the given command group from the registry.
	GetGroups	Gets the CommandGroups in the CommandManager.
	IGetCommandTabs	Gets the CommandManager tabs for the specified document type.
	IGetGroupDataFromRegistry	Gets the command IDs of the given command group from the registry.
	IGetGroups	Gets the CommandGroups in the CommandManager.
	RemoveCommandGroup	Obsolete. Superseded by ICommandManager.RemoveCommandGroup2 .
	RemoveCommandGroup2	Removes the specified CommandGroup from the CommandManager.
	RemoveCommandTab	Removes the specified CommandManager tab, including its tab boxes and buttons, from the CommandManager.
	RemoveFlyoutGroup	Removes the specified flyout from the CommandManager.

[Top](#)

 See Also

[ICommandManager Interface](#)
[SolidWorks.Interop.sldworks Namespace](#)

SOLIDWORKS API Help

[Send comments on this topic.](#)

CommandManager Interface Properties

[See Also](#)



[SolidWorks.Interop.sldworks Namespace](#) : ICommandManager Interface

For a list of all members of this type, see [ICommandManager members](#).

 Public Properties

Name	Description
 NumberOfFlyoutGroups	Gets the number of flyouts in the CommandManager.
 NumberOfGroups	Gets the number of CommandGroups.

[Top](#)

 See Also

[ICommandManager Interface](#)
[SolidWorks.Interop.sldworks Namespace](#)

SOLIDWORKS API Help

[Send comments on this topic.](#)

AddCommandTab Method (ICommandManager)

[See Also](#) [Example](#)



[SolidWorks.Interop.sldworks Namespace](#) > [ICommandManager Interface](#) : AddCommandTab Method (ICommandManager)

Adds a tab to the CommandManager for the specified document type.

.NET Syntax

Visual Basic (Declaration)

```
Function AddCommandTab( _  
    ByVal DocumentType As System.Integer, _  
    ByVal TabName As System.String _  
) As CommandTab
```

Visual Basic (Usage)



```
Dim instance As ICommandManager  
Dim DocumentType As System.Integer  
Dim TabName As System.String  
Dim value As CommandTab  
  
value = instance.AddCommandTab(DocumentType, TabName)
```

C#

```
CommandTab AddCommandTab(  
    System.int DocumentType,  
    System.string TabName  
)
```

C++/CLI

```
CommandTab^ AddCommandTab(  
& System.int DocumentType,  
& System.String^ TabName  
)
```

NOTE: See [Differences Between Unmanaged C++ and C++/CLI Code](#).

Parameters

DocumentType
Document type as defined in [swDocumentTypes_e](#)
TabName
Name of CommandManager tab (see **Remarks**)

Return Value

[CommandManager tab](#)

Visual Basic for Applications (VBA) Syntax

See [CommandManager::AddCommandTab](#).

Example

[Create CommandManager Tab and Tab Boxes \(VB.NET\)](#)

Remarks

The CommandManager tab is always created in the last position on the CommandManager. If another CommandManager tab exists with the same name, then another CommandManager tab is still created because CommandManager tab names are not unique.

See Also

[ICommandManager Interface](#)
[ICommandManager Members](#)
[ICommandManager::CommandTabs Method](#)
[ICommandManager::GetCommandTab Method](#)
[ICommandManager::GetCommandTabCount Method](#)
[ICommandManager::IGetCommandTabs Method](#)
[ICommandManager::RemoveCommandTab Method](#)

Availability

AddContextMenu Method (ICommandManager)

[See Also](#)



[SolidWorks.Interop.sldworks Namespace](#) > [ICommandManager Interface](#) : AddContextMenu Method (ICommandManager)

Adds a new context-sensitive menu to the CommandManager.

.NET Syntax

Visual Basic (Declaration)

```
Function AddContextMenu( _
    ByVal UserID As System.Integer, _
    ByVal Title As System.String _
) As CommandGroup
```

Visual Basic (Usage)



```
Dim instance As ICommandManager
Dim UserID As System.Integer
Dim Title As System.String
Dim value As CommandGroup

value = instance.AddContextMenu(UserID, Title)
```

C#

```
CommandGroup AddContextMenu(
    System.int UserID,
    System.string Title
)
```

C++/CLI

```
CommandGroup^ AddContextMenu(
    & System.int UserID,
    & System.String^ Title
)
```

NOTE: See [Differences Between Unmanaged C++ and C++/CLI Code](#).

Parameters

UserID

User-defined ID for this context-sensitive menu

Title

Name of the context-sensitive menu to add to the CommandManager

Return Value

Pointer to [ICommandGroup](#) object

Visual Basic for Applications (VBA) Syntax

See [CommandManager::AddContextMenu](#).

Remarks

A context-sensitive menu is a pop-up menu that is displayed when a user right-clicks a selectable object type defined by [ICommandGroup::SelectType](#) and, if the object type is a custom feature, [ICommandGroup::CustomNames](#).

You can turn off all menus or all toolbars for a CommandGroup. See [ICommandGroup::HasMenu](#) and [ICommandGroup::HasToolbar](#) for details.

See Also

[ICommandManager Interface](#)
[ICommandManager Members](#)
[ICommandGroup::Name Property](#)
[ICommandGroup::SelectType Property](#)
[ICommandManager::RemoveCommandGroup Method](#)

Availability

SOLIDWORKS 2006 FCS, Revision Number 14

SOLIDWORKS API Help

[Send comments on this topic.](#)

CommandTabs Method (ICommandManager)

[See Also](#)



[SolidWorks.Interop.sldworks Namespace](#) > [ICommandManager Interface](#) : CommandTabs Method (ICommandManager)

Gets all of the add-in CommandManager tabs for the specified document type.

.NET Syntax

Visual Basic (Declaration)

```
Function CommandTabs( _  
    ByVal DocumentType As System.Integer _  
) As System.Object
```

Visual Basic (Usage)



```
Dim instance As ICommandManager  
Dim DocumentType As System.Integer  
Dim value As System.Object  
  
value = instance.CommandTabs(DocumentType)
```

C#

```
System.object CommandTabs(  
    System.int DocumentType  
)
```

C++/CLI

```
System.Object^ CommandTabs(  
& System.int DocumentType  
)
```

NOTE: See [Differences Between Unmanaged C++ and C++/CLI Code](#).

Parameters

DocumentType
Document type as defined in [swDocumentTypes_e](#)

Return Value

Array of [CommandManager tabs](#)

Visual Basic for Applications (VBA) Syntax

See [CommandManager::CommandTabs](#).

Remarks

To activate and query native SOLIDWORKS CommandManager tabs, call [IModelDocExtension::GetCommandTabs](#).

See Also

[ICommandManager Interface](#)
[ICommandManager Members](#)
[ICommandManager::IGetCommandTabs Method](#)
[ICommandManager::GetCommandTab Method](#)
[ICommandManager::AddCommandTab Method](#)
[ICommandManager::RemoveCommandTab Method](#)
[ICommandManager::GetCommandTabCount Method](#)

Availability

CreateCommandGroup Method (ICommandManager)

[See Also](#)[SolidWorks.Interop.sldworks Namespace](#) > [ICommandManager Interface](#) : CreateCommandGroup Method (ICommandManager)Obsolete. Superseded by [ICommandManager::CreateCommandGroup2](#). .NET Syntax

Visual Basic (Declaration)

```
Function CreateCommandGroup( _
    ByVal UserID As System.Integer, _
    ByVal Title As System.String, _
    ByVal ToolTip As System.String, _
    ByVal Hint As System.String, _
    ByVal Position As System.Integer _
) As CommandGroup
```

Visual Basic (Usage)



```
Dim instance As ICommandManager
Dim UserID As System.Integer
Dim Title As System.String
Dim ToolTip As System.String
Dim Hint As System.String
Dim Position As System.Integer
Dim value As CommandGroup

value = instance.CreateCommandGroup(UserID, Title, ToolTip, Hint, Position)
```

C#

```
CommandGroup CreateCommandGroup(
    System.int UserID,
    System.string Title,
    System.string ToolTip,
    System.string Hint,
    System.int Position
)
```

C++/CLI

```
CommandGroup^ CreateCommandGroup(
    & System.int UserID,
    & System.String^ Title,
    & System.String^ ToolTip,
    & System.String^ Hint,
    & System.int Position
)
```

NOTE: See [Differences Between Unmanaged C++ and C++/CLI Code](#).**Parameters***UserID*

Unique user-defined ID for this CommandGroup

*Title*Name of the CommandGroup to create (see **Remarks**)*ToolTip*

ToolTip for this CommandGroup

Hint

Text displayed in SOLIDWORKS status bar when a user's mouse pointer is over this CommandGroup

*Position*Position of the CommandGroup in the CommandManager for all document templates (see **Remarks**)**NOTE:** Specify 0 to add the CommandGroup to the beginning of the CommandManager, or specify -1 to add it to the end of the CommandManager.**Return Value**

Pointer to [ICommandGroup](#) object

Visual Basic for Applications (VBA) Syntax

See [CommandManager::CreateCommandGroup](#).

Remarks

You can also use [ICommandGroup::MenuPosition](#) to control the position of the CommandGroup in specific document templates.

If you change the definition of an existing CommandGroup (i.e., add or remove toolbar buttons), you must assign a new unique user-defined UserID to that CommandGroup. You must perform this action to avoid conflicts with any previously existing CommandGroupa and to allow for backward and forward compatibility of the CommandGroups in your application.

To add a CommandGroup to an existing SOLIDWORKS menu, specify the name of a parent menu in Title. For example, to add a CommandGroup to the Help menu, specify:

Visual Basic: "&He lp/MyApp He lp"
Visual C++ or C#: "&He lp\\MyApp He lp"

NOTE: If you do not specify the name of a parent menu in Title, then the menu item appears on the Tools menu below the **Xpress Products** menu item.

You can turn off all menus or all toolbars for a CommandGroup . See [ICommandGroup::HasMenu](#) and [ICommandGroup::HasToolbar](#) for details.

See Also

[ICommandManager Interface](#)
[ICommandManager Members](#)
[ICommandManager::RemoveCommandGroup Method](#)
[ICommandManager::GetCommandGroup Method](#)
[ICommandManager::GetGroups Method](#)
[ICommandManager::!GetGroups Method](#)
[ICommandManager::NumberOfGroups Property](#)

Availability

SOLIDWORKS 2006 FCS, Revision Number 14

SOLIDWORKS API Help

[Send comments on this topic.](#)

CreateCommandGroup2 Method (ICommandManager)

[See Also](#) [Example](#)



[SolidWorks.Interop.sldworks Namespace](#) > [ICommandManager Interface](#) : CreateCommandGroup2 Method (ICommandManager)

Creates a new CommandGroup in the CommandManager.

.NET Syntax

Visual Basic (Declaration)

```
Function CreateCommandGroup2( _  
    ByVal UserID As System.Integer, _  
    ByVal Title As System.String, _  
    ByVal ToolTip As System.String, _  
    ByVal Hint As System.String, _  
    ByVal Position As System.Integer, _  
    ByVal IgnorePreviousVersion As System.Boolean, _  
    ByRef Errors As System.Integer _  
) As CommandGroup
```

Visual Basic (Usage)

```
Dim instance As ICommandManager  
Dim UserID As System.Integer  
Dim Title As System.String  
Dim ToolTip As System.String  
Dim Hint As System.String
```



```

Dim Position As System.Integer
Dim IgnorePreviousVersion As System.Boolean
Dim Errors As System.Integer
Dim value As CommandGroup

value = instance.CreateCommandGroup2(UserID, Title, ToolTip, Hint, Position,
IgnorePreviousVersion, Errors)

```

C#

```

CommandGroup CreateCommandGroup2(
    System.int UserID,
    System.string Title,
    System.string ToolTip,
    System.string Hint,
    System.int Position,
    System.bool IgnorePreviousVersion,
    out System.int Errors
)

```

C++/CLI

```

CommandGroup^ CreateCommandGroup2(
    & System.int UserID,
    & System.String^ Title,
    & System.String^ ToolTip,
    & System.String^ Hint,
    & System.int Position,
    & System.bool IgnorePreviousVersion,
    [Out] System.int Errors
)

```

NOTE: See [Differences Between Unmanaged C++ and C++/CLI Code](#).

Parameters

UserID

Unique user-defined ID for the new CommandGroup

Title

Name of the CommandGroup to create (see **Remarks**)

ToolTip

Tool tip for the CommandGroup

Hint

Text displayed in SOLIDWORKS status bar when a user's mouse pointer is over the CommandGroup

Position

Position of the CommandGroup in the CommandManager for all document templates (see **Remarks**)

NOTE: Specify 0 to add the CommandGroup to the beginning of the CommandManager, or specify -1 to add it to the end of the CommandManager.

IgnorePreviousVersion

True to remove all previously saved customization and toolbar information before creating a new CommandGroup, false to not (see **Remarks**)

Errors

Error code as defined in [swCreateCommandGroupErrors](#)

Return Value

[ICommandGroup](#)

Visual Basic for Applications (VBA) Syntax

See [CommandManager::CreateCommandGroup2](#).

Example

[Create Flyouts in the CommandManager \(C#\)](#)

[Create Flyouts in the CommandManager \(VB.NET\)](#)

Remarks

Call [ICommandManager::GetGroupDataFromRegistry](#) or [ICommandManager::IGetGroupDataFromRegistry](#) before calling this method to determine how to set IgnorePreviousVersion. Set IgnorePreviousVersion to true to prevent SOLIDWORKS from saving the current toolbar settings to the registry, even if there is no previous version.

You can also use [ICommandGroup::MenuPosition](#) to control the position of the CommandGroup in specific document templates.

If you change the definition of an existing CommandGroup (i.e., add or remove toolbar buttons), you must assign a new unique user-defined UserID to that CommandGroup. You must perform this action to avoid conflicts with any previously existing CommandGroups and to allow for backward and forward compatibility of the CommandGroups in your application.

To add a menu item for a CommandGroup to an existing SOLIDWORKS menu, specify the name of a parent menu in Title. For example, to add CommandGroup to the Help menu, specify:

Visual Basic: "&Help/MyApp Help"
Visual C++ or C#: "&Help\\MyApp Help"

NOTE: If you do not specify the name of a parent menu in Title, then the menu item for the CommandGroup appears on the Tools menu below the **Xpress Products** menu item.

You can turn off all menus or all toolbars for a CommandGroup. See [ICommandGroup::HasMenu](#) and [ICommandGroup::HasToolbar](#) for details.

See Also

[ICommandManager Interface](#)
[ICommandManager Members](#)
[ICommandManager::RemoveCommandGroup2 Method](#)
[ICommandManager::GetCommandGroup Method](#)
[ICommandManager::GetGroups Method](#)
[ICommandManager::IGetGroups Method](#)
[ICommandManager::NumberOfGroups Property](#)

Availability

SOLIDWORKS 2011 FCS, Revision Number 19.0

SOLIDWORKS API Help

[Send comments on this topic.](#)

CreateFlyoutGroup Method (ICommandManager)

[See Also](#)



[SolidWorks.Interop.sldworks Namespace](#) > [ICommandManager Interface](#) : CreateFlyoutGroup Method (ICommandManager)

Obsolete. Superseded by [ICommandManager::CreateFlyoutGroup2](#).

.NET Syntax

Visual Basic (Declaration)

```
Function CreateFlyoutGroup( _  
    ByVal UserID As System.Integer, _  
    ByVal Title As System.String, _  
    ByVal ToolTip As System.String, _  
    ByVal Hint As System.String, _  
    ByVal SmallIcon As System.String, _  
    ByVal LargeIcon As System.String, _  
    ByVal SmallImageList As System.String, _  
    ByVal LargeImageList As System.String, _  
    ByVal CallbackFunction As System.String, _  
    ByVal UpdateCallbackFunction As System.String _  
) As FlyoutGroup
```

Visual Basic (Usage)

```
Dim instance As ICommandManager  
Dim UserID As System.Integer  
Dim Title As System.String  
Dim ToolTip As System.String  
Dim Hint As System.String  
Dim SmallIcon As System.String  
Dim LargeIcon As System.String  
Dim SmallImageList As System.String  
Dim LargeImageList As System.String  
Dim CallbackFunction As System.String  
Dim UpdateCallbackFunction As System.String  
Dim value As FlyoutGroup
```



```
value = instance.CreateFlyoutGroup(UserID, Title, ToolTip, Hint, SmallIcon, LargeIcon, SmallImageList, LargeImageList, CallbackFunction, UpdateCallbackFunction)
```

C#

```
FlyoutGroup CreateFlyoutGroup(  
    System.int UserID,  
    System.string Title,  
    System.string ToolTip,  
    System.string Hint,  
    System.string SmallIcon,  
    System.string LargeIcon,  
    System.string SmallImageList,  
    System.string LargeImageList,  
    System.string CallbackFunction,  
    System.string UpdateCallbackFunction  
)
```

C++/CLI

```
FlyoutGroup^ CreateFlyoutGroup(  
& System.int UserID,  
& System.String^ Title,  
& System.String^ ToolTip,  
& System.String^ Hint,  
& System.String^ SmallIcon,  
& System.String^ LargeIcon,  
& System.String^ SmallImageList,  
& System.String^ LargeImageList,  
& System.String^ CallbackFunction,  
& System.String^ UpdateCallbackFunction  
)
```

NOTE: See [Differences Between Unmanaged C++ and C++/CLI Code](#).

Parameters

UserID
Unique, user-defined ID for the new flyout

Title
Name of the flyout to create

ToolTip
ToolTip for the new flyout

Hint
Text displayed in SOLIDWORKS Design status bar when a user's mouse pointer is over the flyout

SmallIcon
Path to the small bitmap or PNG used in the flyout

LargeIcon
Path to the large bitmap or PNG used in the flyout

SmallImageList
Path to the bitmap or PNG containing all of the small button and separator images for this flyout

LargeImageList
Path to the bitmap or PNG containing all of the large button and separator images for this flyout

CallbackFunction
Function to call when the flyout is selected

UpdateCallbackFunction
Optional update function that controls the state of the item; if specified, then SOLIDWORKS Design calls this function before displaying the item (see **Remarks**)

If this update function returns...	Then the SOLIDWORKS Design...
0	Disables the item
1	Enables the item; this is the default state if no update function is specified

Return Value

[IFlyoutGroup](#)

Remarks

After creating the flyout, display it on a CommandManager tab by calling [ICommandTabBox::AddCommands](#). Call [IFlyoutGroup::AddContextMenuFlyout](#) to add it to context menus. Call [IFlyoutGroup::AddCommandItem](#) to add menu items to the flyout group.

If any flyout menu items are enabled, then the flyout button cannot be disabled by the flyout group's UpdateCallbackFunction. The sensitivity of the top-level flyout button is always determined by its enabled menu items. Disabled flyout menu items do not appear in the flyout menu. If there are no flyout menu items, then control of the top-level flyout button is returned to the flyout group's UpdateCallbackFunction.

See Also

[ICommandManager Interface](#)
[ICommandManager Members](#)
[ICommandManager::GetFlyoutGroup Method](#)
[ICommandManager::GetFlyoutGroups Method](#)
[ICommandManager::RemoveFlyoutGroup Method](#)
[ICommandManager::NumberOfFlyoutGroups Property](#)

Availability

SOLIDWORKS 2011 FCS, Revision Number 19.0

SOLIDWORKS API Help

[Send comments on this topic.](#)

CreateFlyoutGroup2 Method (ICommandManager)

[See Also](#) [Example](#)



[SolidWorks.Interop.sldworks Namespace](#) > [ICommandManager Interface](#) : CreateFlyoutGroup2 Method (ICommandManager)

Creates a new flyout in the CommandManager and context-sensitive menus.

.NET Syntax

Visual Basic (Declaration)

```
Function CreateFlyoutGroup2( _  
    ByVal UserID As System.Integer, _  
    ByVal Title As System.String, _  
    ByVal ToolTip As System.String, _  
    ByVal Hint As System.String, _  
    ByVal MainIconList As System.Object, _  
    ByVal IconList As System.Object, _  
    ByVal CallbackFunction As System.String, _  
    ByVal UpdateCallbackFunction As System.String _  
) As FlyoutGroup
```

Visual Basic (Usage)



```
Dim instance As ICommandManager  
Dim UserID As System.Integer  
Dim Title As System.String  
Dim ToolTip As System.String  
Dim Hint As System.String  
Dim MainIconList As System.Object  
Dim IconList As System.Object  
Dim CallbackFunction As System.String  
Dim UpdateCallbackFunction As System.String  
Dim value As FlyoutGroup
```

```
value = instance.CreateFlyoutGroup2(UserID, Title, ToolTip, Hint, MainIconList, IconList,  
    CallbackFunction, UpdateCallbackFunction)
```

C#

```
FlyoutGroup CreateFlyoutGroup2(  
    System.int UserID,  
    System.string Title,  
    System.string ToolTip,  
    System.string Hint,  
    System.object MainIconList,
```

```

System.object IconList,
System.string CallbackFunction,
System.string UpdateCallbackFunction
)

```

C++/CLI

```

FlyoutGroup^ CreateFlyoutGroup2(
& System.int UserID,
& System.String^ Title,
& System.String^ ToolTip,
& System.String^ Hint,
& System.Object^ MainIconList,
& System.Object^ IconList,
& System.String^ CallbackFunction,
& System.String^ UpdateCallbackFunction
)

```

NOTE: See [Differences Between Unmanaged C++ and C++/CLI Code](#).

Parameters

UserID

Unique user-defined ID for the new flyout

Title

Name of the flyout to create

ToolTip

ToolTip for the new flyout

Hint

Text displayed in SOLIDWORKS Design status bar when a user's mouse pointer is over the flyout

MainIconList

Array of strings for the paths to the image files for this flyout button (see **Remarks**)

IconList

Array of strings for the paths to the image files containing all of the flyout toolbar buttons and separators (see **Remarks**)

CallbackFunction

Function to call when the flyout is selected

UpdateCallbackFunction

Optional update function that controls the state of the item; if specified, then SOLIDWORKS calls this function before displaying the item (see **Remarks**)

If the update function returns...	Then SOLIDWORKS...
0	Disables the item
1	Enables the item; this is the default state if no update function is specified

Return Value

[IFlyoutGroup](#)

Visual Basic for Applications (VBA) Syntax

See [CommandManager::CreateFlyoutGroup2](#).

Example

[Create Flyouts in the CommandManager \(C#\)](#)

[Create Flyouts in the CommandManager \(VB.NET\)](#)

Remarks

After creating the flyout, display it on a CommandManager tab by calling [ICommandTabBox::AddCommands](#). Call:

- [IFlyoutGroup::AddContextMenuFlyout](#) to add the flyout to context menus.
- [IFlyoutGroup::AddCommandItem](#) to add menu items to the flyout group.

If any flyout menu items are enabled, then the flyout button cannot be disabled by the flyout group's UpdateCallbackFunction. The sensitivity of the top-level flyout button is always determined by its enabled menu items. Disabled flyout menu items do not appear in the flyout menu. If there are no flyout menu items, then control of the top-level flyout button is returned to the flyout group's UpdateCallbackFunction.

This method supports scaling for high resolution screens with high resolution operating system scaling options.

The array of strings for the paths to the image files for MainIconList and IconList can contain images of the following sizes:

- 20 x 20 pixels
- 32 x 32 pixels
- 40 x 40 pixels
- 64 x 64 pixels
- 96 x 96 pixels
- 128 x 128 pixels

The order in which you specify the image files must be the same for MainIconList and IconList. For example, if you specify an array of paths to 20 x 20 pixels, 32 x 32 pixels, and 40 x 40 pixels images for MainIconList, then you must specify an array of paths to 20 x 20 pixels, 32 x 32 pixels, and 40 x 40 pixels images for IconList. The images should use a 256-color palette.

See Also

[ICommandManager Interface](#)
[ICommandManager Members](#)
[ICommandManager::GetFlyoutGroup Method \(\)](#)
[ICommandManager::GetFlyoutGroups Method \(\)](#)
[ICommandManager::RemoveFlyoutGroup Method \(\)](#)
[ICommandManager::NumberOfFlyoutGroups Property \(\)](#)
[ISldWorks::GetImageSize Method \(\)](#)

Availability

SOLIDWORKS 2016 FCS, Revision Number 24.0

SOLIDWORKS API Help

[Send comments on this topic.](#)

GetCommandGroup Method (ICommandManager)

[See Also](#)



[SolidWorks.Interop.sldworks Namespace](#) > [ICommandManager Interface](#) : GetCommandGroup Method (ICommandManager)

Gets the CommandGroup using the specified ID.

.NET Syntax

Visual Basic (Declaration)

```
Function GetCommandGroup(  
    ByVal UserID As System.Integer _  
) As CommandGroup
```

Visual Basic (Usage)



```
Dim instance As ICommandManager  
Dim UserID As System.Integer  
Dim value As CommandGroup  
  
value = instance.GetCommandGroup(UserID)
```

C#

```
CommandGroup GetCommandGroup(  
    System.int UserID  
)
```

C++/CLI

```
CommandGroup^ GetCommandGroup(  
& System.int UserID  
)
```

NOTE: See [Differences Between Unmanaged C++ and C++/CLI Code](#).

Parameters

UserID

User-defined ID for this CommandGroup

Return Value

Pointer to [ICommandGroup](#) object

Visual Basic for Applications (VBA) Syntax

See [CommandManager::GetCommandGroup](#).

See Also

[ICommandManager Interface](#)
[ICommandManager Members](#)
[ICommandManager::GetGroups Method](#)
[ICommandManager::IGetGroups Method](#)

Availability

SOLIDWORKS 2006 FCS, Revision Number 14

SOLIDWORKS API Help

[Send comments on this topic.](#)

GetCommandIDsCount Method (ICommandManager)

[See Also](#)



[SolidWorks.Interop.sldworks Namespace](#) > [ICommandManager Interface](#) : GetCommandIDsCount Method (ICommandManager)

Gets the number of command IDs for the given command group.

.NET Syntax

Visual Basic (Declaration)

```
Function GetCommandIDsCount( _  
    ByVal UserGroupId As System.Integer _  
) As System.Integer
```

Visual Basic (Usage)



```
Dim instance As ICommandManager  
Dim UserGroupId As System.Integer  
Dim value As System.Integer  
  
value = instance.GetCommandIDsCount(UserGroupId)
```

C#

```
System.int GetCommandIDsCount(  
    System.int UserGroupId  
)
```

C++/CLI

```
System.int GetCommandIDsCount(  
& System.int UserGroupId  
)
```

NOTE: See [Differences Between Unmanaged C++ and C++/CLI Code](#).

Parameters

UserGroupId
User-defined ID of a command group

Return Value

Number of command IDs in the given command group

Visual Basic for Applications (VBA) Syntax

See [CommandManager::GetCommandIDsCount](#).

Remarks

Call this method before calling [ICommandManager::IGetGroupDataFromRegistry](#) to determine the size of the array for that method.

See Also

[ICommandManager Interface](#)
[ICommandManager Members](#)

Availability

SOLIDWORKS 2011 FCS, Revision Number 19.0

GetCommandTab Method (ICommandManager)

[See Also](#) [Example](#)



[SolidWorks.Interop.sldworks Namespace](#) > [ICommandManager Interface](#) : GetCommandTab Method (ICommandManager)

Gets the specified CommandManager tab for the specified document type.

.NET Syntax

Visual Basic (Declaration)

```
Function GetCommandTab( _
    ByVal DocumentType As System.Integer, _
    ByVal TabName As System.String _
) As CommandTab
```

Visual Basic (Usage)



```
Dim instance As ICommandManager
Dim DocumentType As System.Integer
Dim TabName As System.String
Dim value As CommandTab

value = instance.GetCommandTab(DocumentType, TabName)
```

C#

```
CommandTab GetCommandTab(
    System.int DocumentType,
    System.string TabName
)
```

C++/CLI

```
CommandTab^ GetCommandTab(
    & System.int DocumentType,
    & System.String^ TabName
)
```

NOTE: See [Differences Between Unmanaged C++ and C++/CLI Code](#).

Parameters

DocumentType

Document type as defined in [swDocumentTypes_e](#)

TabName

Name of CommandManager tab

Return Value

[CommandManager tab](#)

Visual Basic for Applications (VBA) Syntax

See [CommandManager::GetCommandTab](#).

Example

[Create CommandManager Tab and Tab Boxes \(VB.NET\)](#)

Remarks

The names of CommandManager tabs are not unique. If multiple CommandManager tabs exists with the same name for the specified document type, then the first matching tab is returned. If no tabs match the specified name for the specified document type, then NULL is returned.

See Also

[ICommandManager Interface](#)

[ICommandManager Members](#)

[ICommandManager::AddCommandTab Method](#)

[ICommandManager::CommandTabs Method](#)
[ICommandManager::GetCommandTabCount Method](#)
[ICommandManager::!GetCommandTabs Method](#)
[ICommandManager::RemoveCommandTab Method](#)

Availability

SOLIDWORKS 2008 FCS, Revision Number 16.0

SOLIDWORKS API Help

[Send comments on this topic.](#)

GetCommandTabCount Method (ICommandManager)

[See Also](#)



[SolidWorks.Interop.sldworks Namespace](#) > [ICommandManager Interface](#) : GetCommandTabCount Method (ICommandManager)

Gets the number of tabs on the CommandManager for the specified document type.

.NET Syntax

Visual Basic (Declaration)

```
Function GetCommandTabCount( _  
    ByVal DocumentType As System.Integer _  
) As System.Integer
```

Visual Basic (Usage)



```
Dim instance As ICommandManager  
Dim DocumentType As System.Integer  
Dim value As System.Integer  
  
value = instance.GetCommandTabCount(DocumentType)
```

C#

```
System.int GetCommandTabCount(  
    System.int DocumentType  
)
```

C++/CLI

```
System.int GetCommandTabCount(  
& System.int DocumentType  
)
```

NOTE: See [Differences Between Unmanaged C++ and C++/CLI Code](#).

Parameters

DocumentType
Document type as defined in [swDocumentTypes_e](#)

Return Value

Number of tabs on the CommandManager

Visual Basic for Applications (VBA) Syntax

See [CommandManager::GetCommandTabCount](#).

Remarks

Call this method before [ICommandManager::!GetCommandTabs](#) to get the size of the array for that method.
All CommandManager tabs are returned. Some CommandManager tabs may not be active or visible.

See Also

[ICommandManager Interface](#)
[ICommandManager Members](#)
[ICommandManager::AddCommandTab Method](#)
[ICommandManager::CommandTabs Method](#)

Availability

SOLIDWORKS 2008 FCS, Revision Number 16.0

SOLIDWORKS API Help

[Send comments](#) on this topic.

GetFlyoutGroup Method (ICommandManager)

See Also [Example](#)



[SolidWorks.Interop.sldworks Namespace](#) > [ICommandManager Interface](#) : GetFlyoutGroup Method (ICommandManager)

Gets the flyout with the specified ID.

.NET Syntax

Visual Basic (Declaration)

```
Function GetFlyoutGroup( _  
    ByVal UserID As System.Integer _  
) As FlyoutGroup
```

Visual Basic (Usage)



```
Dim instance As ICommandManager  
Dim UserID As System.Integer  
Dim value As FlyoutGroup  
  
value = instance.GetFlyoutGroup(UserID)
```

C#

```
FlyoutGroup GetFlyoutGroup(  
    System.int UserID  
)
```

C++/CLI

```
FlyoutGroup^ GetFlyoutGroup(  
& System.int UserID  
)
```

NOTE: See [Differences Between Unmanaged C++ and C++/CLI Code](#).

Parameters

UserID

User-defined ID for the flyout

Return Value

[IFlyoutGroup](#)

Visual Basic for Applications (VBA) Syntax

See [CommandManager::GetFlyoutGroup](#).

Example

[Create Flyouts in the CommandManager \(C#\)](#)
[Create Flyouts in the CommandManager \(VB.NET\)](#)

See Also

[ICommandManager Interface](#)
[ICommandManager Members](#)
[ICommandManager::CreateFlyoutGroup Method](#)
[ICommandManager::GetFlyoutGroups Method](#)
[ICommandManager::RemoveFlyoutGroup Method](#)
[ICommandManager::NumberOfFlyoutGroups Property](#)

Availability

SOLIDWORKS 2011 FCS, Revision Number 19.0

SOLIDWORKS API Help

[Send comments on this topic.](#)

GetFlyoutGroups Method (ICommandManager)

[See Also](#) [Example](#)



[SolidWorks.Interop.sldworks Namespace](#) > [ICommandManager Interface](#) : GetFlyoutGroups Method (ICommandManager)

Gets the flyouts in the CommandManager.

.NET Syntax

Visual Basic (Declaration)

```
Function GetFlyoutGroups() As System.Object
```

Visual Basic (Usage)



```
Dim instance As ICommandManager
Dim value As System.Object

value = instance.GetFlyoutGroups()
```

C#

```
System.Object GetFlyoutGroups()
```

C++/CLI

```
System.Object^ GetFlyoutGroups();
```

NOTE: See [Differences Between Unmanaged C++ and C++/CLI Code](#).

Return Value

Array of the [IFlyoutGroups](#) in the CommandManager

Visual Basic for Applications (VBA) Syntax

See [CommandManager::GetFlyoutGroups](#).

Example

[Create Flyouts in the CommandManager \(C#\)](#)
[Create Flyouts in the CommandManager \(VB.NET\)](#)

See Also

[ICommandManager Interface](#)
[ICommandManager Members](#)
[ICommandManager::CreateFlyoutGroup Method](#)
[ICommandManager::GetFlyoutGroup Method](#)
[ICommandManager::RemoveFlyoutGroup Method](#)
[ICommandManager::NumberOfFlyoutGroups Property](#)

Availability

SOLIDWORKS 2011 FCS, Revision Number 19.0

SOLIDWORKS API Help

[Send comments on this topic.](#)

GetGroupDataFromRegistry Method (ICommandManager)

[See Also](#) [Example](#)



[SolidWorks.Interop.sldworks Namespace](#) > [ICommandManager Interface](#) : GetGroupDataFromRegistry Method (ICommandManager)

Gets the command IDs of the given command group from the registry.

.NET Syntax

Visual Basic (Declaration)

```
Function GetGroupDataFromRegistry( _  
    ByVal UserGroupId As System.Integer, _  
    ByRef UserIDs As System.Object _  
) As System.Boolean
```

Visual Basic (Usage)



```
Dim instance As ICommandManager  
Dim UserGroupId As System.Integer  
Dim UserIDs As System.Object  
Dim value As System.Boolean  
  
value = instance.GetGroupDataFromRegistry(UserGroupId, UserIDs)
```

C#

```
System.bool GetGroupDataFromRegistry(  
    System.int UserGroupId,  
    out System.object UserIDs  
)
```

C++/CLI

```
System.bool GetGroupDataFromRegistry(  
& System.int UserGroupId,  
& [Out] System.Object^ UserIDs  
)
```

NOTE: See [Differences Between Unmanaged C++ and C++/CLI Code](#).

Parameters

UserGroupId

User-defined ID of a command group

UserIDs

Array of command IDs for the given command group

Return Value

True if successful, false if not

Visual Basic for Applications (VBA) Syntax

See [CommandManager::GetGroupDataFromRegistry](#).

Example

[Create Flyouts in the CommandManager \(VB.NET\)](#)

[Create Flyouts in the CommandManager \(C#\)](#)

Remarks

Call this API before calling [ICommandManager::CreateCommandGroup2](#). The array of command IDs returned by this method helps you decide how to set the IgnorePreviousVersion parameter of ICommandManager::CreateCommandGroup2.

See Also

[ICommandManager Interface](#)

[ICommandManager Members](#)

[ICommandManager::IGetGroupDataFromRegistry](#)

Availability

SOLIDWORKS 2011 FCS, Revision Number 19.0



Gets the CommandGroups in the CommandManager.

.NET Syntax

Visual Basic (Declaration)

```
Function GetGroups() As System.Object
```

Visual Basic (Usage)



```
Dim instance As ICommandManager  
Dim value As System.Object
```

```
value = instance.GetGroups()
```

C#

```
System.Object GetGroups()
```

C++/CLI

```
System.Object^ GetGroups();
```

NOTE: See [Differences Between Unmanaged C++ and C++/CLI Code](#).

Return Value

Array of the [ICommandGroups](#) in the CommandManager

Visual Basic for Applications (VBA) Syntax

See [CommandManager::GetGroups](#).

See Also

[ICommandManager Interface](#)
[ICommandManager Members](#)
[ICommandManager::IGetGroups Method](#)
[ICommandManager::GetCommandGroup Method](#)
[ICommandManager::RemoveCommandGroup Method](#)
[ICommandManager::NumberOfGroups Property](#)

Availability

SOLIDWORKS 2006 FCS, Revision Number 14

SOLIDWORKS API Help

[Send comments](#) on this topic.

IGetCommandTabs Method (ICommandManager)

[See Also](#)



SolidWorks.Interop.sldworks Namespace > ICommandManager Interface : IGetCommandTabs Method (ICommandManager)

Gets the CommandManager tabs for the specified document type.

.NET Syntax

Visual Basic (Declaration)

```
Function IGetCommandTabs(  
    ByVal DocumentType As System.Integer, _  
    ByVal CommandTabCount As System.Integer _  
) As CommandTab
```

Visual Basic (Usage)



```
Dim instance As ICommandManager  
Dim DocumentType As System.Integer  
Dim CommandTabCount As System.Integer  
Dim value As CommandTab
```

```
value = instance.IGetCommandTabs(DocumentType, CommandTabCount)
```

C#

```
CommandTab IGetCommandTabs(  
    System.int DocumentType,  
    System.int CommandTabCount  
)
```

C++/CLI

```
CommandTab^ IGetCommandTabs(  
& System.int DocumentType,  
& System.int CommandTabCount  
)
```

NOTE: See [Differences Between Unmanaged C++ and C++/CLI Code](#).

Parameters

DocumentType

Document type as defined in [swDocumentTypes](#) e

CommandTabCount

Number of CommandManager tabs for DocumentType

Return Value

- in-process, unmanaged C++: Pointer to an array of [CommandManager tabs](#)
 - VBA, VB.NET, C#, and C++/CLI: Not supported
- See [In-process Methods](#) for details about this type of method.

Remarks

Before calling this method, call [ICommandManager::GetCommandTabCount](#) to get the size of the array for this method.

See Also

[ICommandManager Interface](#)

[ICommandManager Members](#)

[ICommandManager::AddCommandTab Method](#)

[ICommandManager::CommandTabs Method](#)

[ICommandManager::GetCommandTab Method](#)

[ICommandManager::RemoveCommandTab Method](#)

Availability

SOLIDWORKS 2008 FCS, Revision Number 16.0

SOLIDWORKS API Help

[Send comments on this topic.](#)

IGetGroupDataFromRegistry Method (ICommandManager)

[See Also](#)



[SolidWorks.Interop.sldworks Namespace](#) > [ICommandManager Interface](#) : IGetGroupDataFromRegistry Method (ICommandManager)

Gets the command IDs of the given command group from the registry.

.NET Syntax

Visual Basic (Declaration)

```
Function IGetGroupDataFromRegistry( _  
    ByVal UserGroupId As System.Integer, _  
    ByVal Count As System.Integer, _  
    ByRef UserIDs As System.Integer _  
) As System.Boolean
```

Visual Basic (Usage)



```
Dim instance As ICommandManager  
Dim UserGroupId As System.Integer  
Dim Count As System.Integer  
Dim UserIDs As System.Integer
```

```
Dim value As System.Boolean
```

```
value = instance.IGetGroupDataFromRegistry(UserGroupId, Count, UserIDs)
```

C#

```
System.bool IGetGroupDataFromRegistry(  
    System.int UserGroupId,  
    System.int Count,  
    out System.int UserIDs  
)
```

C++/CLI

```
System.bool IGetGroupDataFromRegistry(  
    & System.int UserGroupId,  
    & System.int Count,  
    & [Out] System.int UserIDs  
)
```

NOTE: See [Differences Between Unmanaged C++ and C++/CLI Code](#).

Parameters

UserGroupId

User-defined ID of a command group

Count

Number of command IDs in the given command group

UserIDs

- in-process, unmanaged C++: Pointer to an array of integer IDs

- VBA, VB.NET, C#, and C++/CLI: Not supported

See [In-process Methods](#) for details about this type of method.

Return Value

True if successful, false if not

Remarks

Before calling this method call [ICommandManager::GetCommandIDsCount](#) to populate Count.

Use this method to compare command group IDs obtained through the user interface with those stored in the registry.

See Also

[ICommandManager Interface](#)

[ICommandManager Members](#)

[ICommandManager::GetGroupDataFromRegistry Method](#)

Availability

SOLIDWORKS 2011 FCS, Revision Number 19.0

SOLIDWORKS API Help

[Send comments on this topic.](#)

IGetGroups Method (ICommandManager)

[See Also](#)



[SolidWorks.Interop.sldworks Namespace](#) > [ICommandManager Interface](#) : IGetGroups Method (ICommandManager)

Gets the CommandGroups in the CommandManager.

.NET Syntax

Visual Basic (Declaration)

```
Function IGetGroups( _  
    ByVal Count As System.Integer _  
) As System.IntPtr
```

Visual Basic (Usage)

Copy Code

```
Dim instance As ICommandManager
Dim Count As System.Integer
Dim value As System.IntPtr

value = instance.IGetGroups(Count)
```

C#

```
System.IntPtr IGetGroups(
    System.int Count
)
```

C++/CLI

```
System.IntPtr IGetGroups(
    & System.int Count
)
```

NOTE: See [Differences Between Unmanaged C++ and C++/CLI Code](#).

Parameters

Count

Number of CommandGroups in this CommandManager

Return Value

- in-process, unmanaged C++: Pointer to an array of [ICommandGroup](#) objects in the CommandManager
 - VBA, VB.NET, C#, and C++/CLI: Not supported
- See [In-process Methods](#) for details about this type of method.

Remarks

Before calling this method, call [ICommandManager::NumberOfGroups](#) to determine the size of the array.

See Also

[ICommandManager Interface](#)
[ICommandManager Members](#)
[ICommandManager::GetGroups Method](#)
[ICommandManager::GetCommandGroup Method](#)
[ICommandManager::RemoveCommandGroup Method](#)
[ICommandManager::NumberOfGroups Property](#)

Availability

SOLIDWORKS 2006 FCS, Revision Number 14

SOLIDWORKS API Help

[Send comments on this topic.](#)

NumberOfFlyoutGroups Property (ICommandManager)

[See Also](#) [Example](#)



[SolidWorks.Interop.sldworks Namespace](#) > [ICommandManager Interface](#) : NumberOfFlyoutGroups Property (ICommandManager)

Gets the number of flyouts in the CommandManager.

.NET Syntax

Visual Basic (Declaration)

```
ReadOnly Property NumberOfFlyoutGroups As System.Integer
```

Visual Basic (Usage)



```
Dim instance As ICommandManager
Dim value As System.Integer

value = instance.NumberOfFlyoutGroups
```

C#

```
System.int NumberOfFlyoutGroups {get;}
```

C++/CLI

```
property System.int NumberOfFlyoutGroups {  
    System.int get();  
}
```

NOTE: See [Differences Between Unmanaged C++ and C++/CLI Code](#).

Property Value

Number of flyouts

Visual Basic for Applications (VBA) Syntax

See [CommandManager::NumberOfFlyoutGroups](#).

Example

[Create Flyouts in the CommandManager \(C#\)](#)
[Create Flyouts in the CommandManager \(VB.NET\)](#)

See Also

[ICommandManager Interface](#)
[ICommandManager Members](#)
[ICommandManager::CreateFlyoutGroup Method](#)
[ICommandManager::GetFlyoutGroup Method](#)
[ICommandManager::GetFlyoutGroups Method](#)
[ICommandManager::RemoveFlyoutGroup Method](#)

Availability

SOLIDWORKS 2011 FCS, Revision Number 19.0

SOLIDWORKS API Help

[Send comments on this topic.](#)

NumberOfGroups Property (ICommandManager)

[See Also](#)



[SolidWorks.Interop.sldworks Namespace](#) > [ICommandManager Interface](#) : NumberOfGroups Property (ICommandManager)

Gets the number of CommandGroups.

.NET Syntax

Visual Basic (Declaration)

```
ReadOnly Property NumberOfGroups As System.Integer
```

Visual Basic (Usage)



```
Dim instance As ICommandManager  
Dim value As System.Integer
```

```
value = instance.NumberOfGroups
```

C#

```
System.int NumberOfGroups {get;}
```

C++/CLI

```
property System.int NumberOfGroups {  
    System.int get();  
}
```

NOTE: See [Differences Between Unmanaged C++ and C++/CLI Code](#).

Property Value

Number of CommandGroups

Visual Basic for Applications (VBA) Syntax

See [CommandManager::NumberOfGroups](#).

Remarks

Call this method before calling [ICommandManager::IGetGroups](#) to determine the size of the array for that method.

See Also

[ICommandManager Interface](#)
[ICommandManager Members](#)
[ICommandManager::GetGroups Method](#)

Availability

SOLIDWORKS 2006 FCS, Revision Number 14

SOLIDWORKS API Help

[Send comments on this topic.](#)

RemoveCommandGroup Method (ICommandManager)

[See Also](#)



[SolidWorks.Interop.sldworks Namespace](#) > [ICommandManager Interface](#) : RemoveCommandGroup Method (ICommandManager)

Obsolete. Superseded by [ICommandManager::RemoveCommandGroup2](#).

.NET Syntax

Visual Basic (Declaration)

```
Function RemoveCommandGroup( _  
    ByVal UserID As System.Integer _  
) As System.Boolean
```

Visual Basic (Usage)



```
Dim instance As ICommandManager  
Dim UserID As System.Integer  
Dim value As System.Boolean  
  
value = instance.RemoveCommandGroup(UserID)
```

C#

```
System.bool RemoveCommandGroup(  
    System.int UserID  
)
```

C++/CLI

```
System.bool RemoveCommandGroup(  
& System.int UserID  
)
```

NOTE: See [Differences Between Unmanaged C++ and C++/CLI Code](#).

Parameters

UserID
User-defined ID for this CommandGroup

Return Value

True if the CommandGroup is removed, false if not

Visual Basic for Applications (VBA) Syntax

See [CommandManager::RemoveCommandGroup](#).

Remarks

This method removes CommandGroups created using [ICommandManager::AddContextMenu](#) and [ICommandManager::CreateCommandGroup](#)

See Also

[ICommandManager Interface](#)
[ICommandManager Members](#)
[ICommandManager::GetCommandGroup Method](#)
[ICommandManager::GetGroups Method](#)
[ICommandManager::IGetGroups Method](#)
[ICommandManager::NumberOfGroups Property](#)

Availability

SOLIDWORKS 2006 FCS, Revision Number 14

SOLIDWORKS API Help

[Send comments](#) on this topic.

RemoveCommandGroup2 Method (ICommandManager)

[See Also](#)



[SolidWorks.Interop.sldworks Namespace](#) > [ICommandManager Interface](#) : RemoveCommandGroup2 Method (ICommandManager)

Removes the specified CommandGroup from the CommandManager.

Visual Basic Syntax

Visual Basic (Declaration)

```
Function RemoveCommandGroup2( _  
    ByVal UserID As System.Integer, _  
    ByVal RuntimeOnly As System.Boolean _  
) As System.Integer
```

Visual Basic (Usage)



```
Dim instance As ICommandManager  
Dim UserID As System.Integer  
Dim RuntimeOnly As System.Boolean  
Dim value As System.Integer  
  
value = instance.RemoveCommandGroup2(UserID, RuntimeOnly)
```

C#

```
System.int RemoveCommandGroup2(  
    System.int UserID,  
    System.bool RuntimeOnly  
)
```

C++/CLI

```
System.int RemoveCommandGroup2(  
& System.int UserID,  
& System.bool RuntimeOnly  
)
```

NOTE: See [Differences Between Unmanaged C++ and C++/CLI Code](#).

Parameters

UserID

User-defined ID of the CommandGroup to remove

RuntimeOnly

True to remove the CommandGroup, saving its toolbar information in the registry; false to remove both the CommandGroup and its toolbar information in the registry

Return Value

Error code as defined in [swRemoveCommandGroupErrors](#)

Visual Basic for Applications (VBA) Syntax

See [CommandManager::RemoveCommandGroup2](#).

Remarks

This method removes CommandGroups created using [ICommandManager::AddContextMenu](#) and [ICommandManager::CreateCommandGroup2](#).

See Also

[ICommandManager Interface](#)
[ICommandManager Members](#)

Availability

SOLIDWORKS 2011 FCS, Revision Number 19.0

SOLIDWORKS API Help

[Send comments on this topic.](#)

RemoveCommandTab Method (ICommandManager)

[See Also](#)



[SolidWorks.Interop.sldworks Namespace](#) > [ICommandManager Interface](#) : RemoveCommandTab Method (ICommandManager)

Removes the specified CommandManager tab, including its tab boxes and buttons, from the CommandManager.

.NET Syntax

Visual Basic (Declaration)

```
Function RemoveCommandTab( _  
    ByVal TabToRemove As CommandTab _  
) As System.Boolean
```

Visual Basic (Usage)



```
Dim instance As ICommandManager  
Dim TabToRemove As CommandTab  
Dim value As System.Boolean
```

```
value = instance.RemoveCommandTab(TabToRemove)
```

C#

```
System.bool RemoveCommandTab(  
    CommandTab TabToRemove  
)
```

C++/CLI

```
System.bool RemoveCommandTab(  
& CommandTab^ TabToRemove  
)
```

NOTE: See [Differences Between Unmanaged C++ and C++/CLI Code](#).

Parameters

TabToRemove
[CommandManager tab](#), including its tab boxes and buttons, to remove

Return Value

True if the CommandManager tab is removed, false if not

Visual Basic for Applications (VBA) Syntax

See [CommandManager::RemoveCommandTab](#).

See Also

[ICommandManager Interface](#)
[ICommandManager Members](#)
[ICommandManager::AddCommandTab Method](#)
[ICommandManager::CommandTabs Method](#)
[ICommandManager::GetCommandTab Method](#)
[ICommandManager::GetCommandTabCount Method](#)
[ICommandManager::IGetCommandTabs Method](#)

Availability

SOLIDWORKS 2008 FCS, Revision Number 16.0

SOLIDWORKS API Help

[Send comments on this topic.](#)

RemoveFlyoutGroup Method (ICommandManager)

[See Also](#) [Example](#)



[SolidWorks.Interop.sldworks Namespace](#) > [ICommandManager Interface](#) : RemoveFlyoutGroup Method (ICommandManager)

Removes the specified flyout from the CommandManager.

.NET Syntax

Visual Basic (Declaration)

```
Function RemoveFlyoutGroup( _  
    ByVal UserID As System.Integer _  
) As System.Boolean
```

Visual Basic (Usage)



```
Dim instance As ICommandManager  
Dim UserID As System.Integer  
Dim value As System.Boolean  
  
value = instance.RemoveFlyoutGroup(UserID)
```

C#

```
System.bool RemoveFlyoutGroup(  
    System.int UserID  
)
```

C++/CLI

```
System.bool RemoveFlyoutGroup(  
& System.int UserID  
)
```

NOTE: See [Differences Between Unmanaged C++ and C++/CLI Code](#).

Parameters

UserID

User-defined ID of the flyout to remove

Return Value

True if removal successful, false if not

Visual Basic for Applications (VBA) Syntax

See [CommandManager::RemoveFlyoutGroup](#).

Example

[Create Flyouts in the CommandManager \(C#\)](#)
[Create Flyouts in the CommandManager \(VB.NET\)](#)

See Also

[ICommandManager Interface](#)
[ICommandManager Members](#)
[ICommandManager::CreateFlyoutGroup Method](#)
[ICommandManager::GetFlyoutGroup Method](#)
[ICommandManager::GetFlyoutGroups Method](#)
[ICommandManager::NumberOfFlyoutGroups Property](#)

Availability

SOLIDWORKS 2011 FCS, Revision Number 19.0

ICommandTab (Type)

ICommandTab Interface

[See Also](#) [Members](#) [Example](#)



[SolidWorks.Interop.sldworks Namespace](#) : ICommandTab Interface

Allows add-in applications to create tabs and add them to the [CommandManager](#). The add-in application must create and clean up its own tabs.

NOTE: Click the **Members** link, located near the top of the topic, to see this interface's methods and properties.

.NET Syntax

Visual Basic (Declaration)

```
Public Interface ICommandTab
```

Visual Basic (Usage)

```
Dim instance As ICommandTab
```

C#

```
public interface ICommandTab
```

C++/CLI

```
public interface class ICommandTab
```

Visual Basic for Applications (VBA) Syntax

See [CommandTab](#).

Example

[Create CommandManager Tab and Tab Boxes \(VB.NET\)](#)

Remarks

Your add-in must check to see if the tab already exists. If the tab already exists, then you should use that tab instead of creating a new tab. If your add-in does not check for an existing tab, then SOLIDWORKS will create a new tab each time it starts up.

Users can add buttons to and remove buttons from your CommandManager tab. However, if your add-in removes the CommandManager tab upon exiting SOLIDWORKS, then any customizations made by users will be lost.

Accessors

[ICommandManager::AddCommandTab](#)

[ICommandManager::CommandTabs](#)

[ICommandManager::GetCommandTab](#)

[ICommandManager::IGetCommandTabs](#)

[IModelDocExtension::GetCommandTabs](#)

Access Diagram

[CommandTab](#)

See Also

[ICommandTab Members](#)

[SolidWorks.Interop.sldworks Namespace](#)

[ICommandTabBox Interface](#)

ICommandTab Interface Methods

[See Also](#)

[SolidWorks.Interop.sldworks Namespace](#) : ICommandTab Interface

For a list of all members of this type, see [ICommandTab members](#).

Public Methods

Name	Description
AddCommandTabBox	Adds a tab box to this CommandManager tab.
AddSeparator	Adds a separator to this CommandManager tab.
CommandTabBoxes	Gets the tab boxes on this CommandManager tab.
GetCommandTabBoxCount	Gets the number of tab boxes on this CommandManager tab.
IGetCommandTabBoxes	Gets the CommandManager tab boxes on this CommandManager tab.
RemoveCommandTabBox	Removes the specified tab box and its buttons from this CommandManager tab.

[Top](#)

See Also

[ICommandTab Interface](#)
[SolidWorks.Interop.sldworks Namespace](#)
[ICommandTabBox Interface](#)

ICommandTab Interface Members

[See Also](#) [Properties](#) [Methods](#)

[SolidWorks.Interop.sldworks Namespace](#) : ICommandTab Interface

The following tables list the members exposed by [ICommandTab](#).

Public Properties

Name	Description
Active	Gets or sets whether this CommandManager tab is active.
Name	Gets or sets the name of this CommandManager tab.
Visible	Gets or sets whether to show or hide this CommandManager tab.

[Top](#)

Public Methods

Name	Description
AddCommandTabBox	Adds a tab box to this CommandManager tab.
AddSeparator	Adds a separator to this CommandManager tab.
CommandTabBoxes	Gets the tab boxes on this CommandManager tab.
GetCommandTabBoxCount	Gets the number of tab boxes on this CommandManager tab.
IGetCommandTabBoxes	Gets the CommandManager tab boxes on this CommandManager tab.
RemoveCommandTabBox	Removes the specified tab box and its buttons from this CommandManager tab.

[Top](#)

See Also

[ICommandTab Interface](#)
[SolidWorks.Interop.sldworks Namespace](#)
[ICommandTabBox Interface](#)

ICommandTab Interface Properties

[See Also](#)



[SolidWorks.Interop.sldworks Namespace](#) : ICommandTab Interface

For a list of all members of this type, see [ICommandTab members](#).

Public Properties

Name	Description
Active	Gets or sets whether this CommandManager tab is active.
Name	Gets or sets the name of this CommandManager tab.
Visible	Gets or sets whether to show or hide this CommandManager tab.

[Top](#)

See Also

[ICommandTab Interface](#)
[SolidWorks.Interop.sldworks Namespace](#)
[ICommandTabBox Interface](#)

SOLIDWORKS API Help

[Send comments on this topic.](#)

Active Property (ICommandTab)

[See Also](#)



[SolidWorks.Interop.sldworks Namespace](#) > [ICommandTab Interface](#) : Active Property (ICommandTab)

Gets or sets whether this CommandManager tab is active.

Visual Basic Syntax

Visual Basic (Declaration)

Property Active As System.Boolean

Visual Basic (Usage)



```
Dim instance As ICommandTab  
Dim value As System.Boolean
```

```
instance.Active = value
```

```
value = instance.Active
```

C#

```
System.bool Active {get; set;}
```

C++/CLI

```
property System.bool Active {  
    System.bool get();  
    void set ( & System.bool value);  
}
```

NOTE: See [Differences Between Unmanaged C++ and C++/CLI Code](#).

Property Value

True if this CommandManager tab is active, false if not

Visual Basic for Applications (VBA) Syntax

See [CommandTab.Active](#).

See Also

[ICommandTab Interface](#)
[ICommandTab Members](#)

Availability

SOLIDWORKS 2008 FCS, Revision Number 16.0

SOLIDWORKS API Help

[Send comments on this topic.](#)

AddCommandTabBox Method (ICommandTab)

[See Also](#) [Example](#)



[SolidWorks.Interop.sldworks Namespace](#) > [ICommandTab Interface](#) : AddCommandTabBox Method (ICommandTab)

Adds a tab box to this CommandManager tab.

.NET Syntax

Visual Basic (Declaration)

```
Function AddCommandTabBox() As CommandTabBox
```

Visual Basic (Usage)



```
Dim instance As ICommandTab
Dim value As CommandTabBox

value = instance.AddCommandTabBox()
```

C#

```
CommandTabBox AddCommandTabBox()
```

C++/CLI

```
CommandTabBox^ AddCommandTabBox();
```

NOTE: See [Differences Between Unmanaged C++ and C++/CLI Code](#).

Return Value

[CommandManager tab box](#)

Visual Basic for Applications (VBA) Syntax

See [CommandTab::AddCommandTabBox](#).

Example

[Create CommandManager Tab and Tab Boxes \(VB.NET\)](#)

Remarks

The CommandManager tab box is always added to the end of the CommandManager tab, unless it is the first CommandManager tab box added to this CommandManager tab. If so, then this CommandManager tab box is placed at the beginning of the CommandManager tab.

The CommandManager tab box is not immediately visible. You must first [add buttons](#) to the CommandManager tab box.

See Also

[ICommandTab Interface](#)
[ICommandTab Members](#)

Availability

SOLIDWORKS 2008 FCS, Revision Number 16.0

SOLIDWORKS API Help

[Send comments on this topic.](#)

AddSeparator Method (ICommandTab)

[See Also](#) [Example](#)



Adds a separator to this CommandManager tab.

.NET Syntax

Visual Basic (Declaration)

```
Function AddSeparator( _  
    ByVal CommandTabBoxIn As CommandTabBox, _  
    ByVal CommandID As System.Integer _  
) As CommandTabBox
```

Visual Basic (Usage)



```
Dim instance As ICommandTab  
Dim CommandTabBoxIn As CommandTabBox  
Dim CommandID As System.Integer  
Dim value As CommandTabBox
```

```
value = instance.AddSeparator(CommandTabBoxIn, CommandID)
```

C#

```
CommandTabBox AddSeparator(  
    CommandTabBox CommandTabBoxIn,  
    System.int CommandID  
)
```

C++/CLI

```
CommandTabBox^ AddSeparator(  
& CommandTabBox^ CommandTabBoxIn,  
& System.int CommandID  
)
```

NOTE: See [Differences Between Unmanaged C++ and C++/CLI Code](#).

Parameters

CommandTabBoxIn

[CommandManager tab box](#) to which to add the separator

CommandID

Button before which to place the separator (see **Remarks**)

Return Value

New [CommandManager tab box](#)

Visual Basic for Applications (VBA) Syntax

See [CommandTab::AddSeparator](#).

Example

[Create CommandManager Tab and Tab Boxes \(VB.NET\)](#)

Remarks

The specified CommandManager tab is split into two. The left side is the original CommandManager tab box, and the right side is the new CommandManager tab box. The first button on the new CommandManager tab box is the button specified by CommandID.

If the CommandManager tab box has multiple commands with the same CommandID, then a separator is added before the first matching CommandID.

You can get the CommandID using [ICommandGroup::CommandID](#) or [ICommandGroup::ToolBarId](#) after calling [ICommandGroup::Activate](#).

See Also

[ICommandTab Interface](#)
[ICommandTab Members](#)

Availability

SOLIDWORKS 2008 FCS, Revision Number 16.0

SOLIDWORKS API Help

[Send comments on this topic.](#)

CommandTabBoxes Method (ICommandTab)

[See Also](#)



[SolidWorks.Interop.sldworks Namespace](#) > [ICommandTab Interface](#) : CommandTabBoxes Method (ICommandTab)

Gets the tab boxes on this CommandManager tab.

.NET Syntax

Visual Basic (Declaration)

```
Function CommandTabBoxes() As System.Object
```

Visual Basic (Usage)



```
Dim instance As ICommandTab
Dim value As System.Object

value = instance.CommandTabBoxes()
```

C#

```
System.object CommandTabBoxes()
```

C++/CLI

```
System.Object^ CommandTabBoxes();
```

NOTE: See [Differences Between Unmanaged C++ and C++/CLI Code](#).

Return Value

Array of [CommandManager tab boxes](#) on this CommandManager tab

Visual Basic for Applications (VBA) Syntax

See [CommandTab::CommandTabBoxes](#).

See Also

[ICommandTab Interface](#)
[ICommandTab Members](#)
[ICommandTab::GetCommandTabBoxCount Method](#)
[ICommandTab::IGetCommandTabBoxes Method](#)
[ICommandTab::RemoveCommandTabBox Method](#)

Availability

SOLIDWORKS 2008 FCS, Revision Number 16.0

SOLIDWORKS API Help

[Send comments on this topic.](#)

GetCommandTabBoxCount Method (ICommandTab)

[See Also](#)



[SolidWorks.Interop.sldworks Namespace](#) > [ICommandTab Interface](#) : GetCommandTabBoxCount Method (ICommandTab)

Gets the number of tab boxes on this CommandManager tab.

.NET Syntax

Visual Basic (Declaration)

```
Function GetCommandTabBoxCount() As System.Integer
```

Visual Basic (Usage)



```
Dim instance As ICommandTab
Dim value As System.Integer

value = instance.GetCommandTabBoxCount()
```

C#

```
System.int GetCommandTabBoxCount()
```

C++/CLI

```
System.int GetCommandTabBoxCount();
```

NOTE: See [Differences Between Unmanaged C++ and C++/CLI Code](#).

Return Value

Number of CommandManager tab boxes on this CommandManager tab

Visual Basic for Applications (VBA) Syntax

See [CommandTab::GetCommandTabBoxCount](#).

Remarks

Call this method before calling [ICommandTab::IGetCommandTabBoxes](#) to get the size of the array for that method.

See Also

[ICommandTab Interface](#)
[ICommandTab Members](#)
[ICommandTab::AddCommandTabBox Method](#)
[ICommandTab::CommandTabBoxes Method](#)
[ICommandTab::RemoveCommandTabBox Method](#)

Availability

SOLIDWORKS 2008 FCS, Revision Number 16.0

SOLIDWORKS API Help

[Send comments on this topic.](#)

IGetCommandTabBoxes Method (ICommandTab)

[See Also](#)



[SolidWorks.Interop.sldworks Namespace](#) > [ICommandTab Interface](#) : IGetCommandTabBoxes Method (ICommandTab)

Gets the CommandManager tab boxes on this CommandManager tab.

.NET Syntax

Visual Basic (Declaration)

```
Function IGetCommandTabBoxes( _
    ByVal TabBoxCount As System.Integer _
) As CommandTabBox
```

Visual Basic (Usage)



```
Dim instance As ICommandTab
Dim TabBoxCount As System.Integer
Dim value As CommandTabBox
```

```
value = instance.IGetCommandTabBoxes(TabBoxCount)
```

C#

```
CommandTabBox IGetCommandTabBoxes(
    System.int TabBoxCount
)
```

```
CommandTabBox^ IGetCommandTabBoxes(
& System.int TabBoxCount
)
```

NOTE: See [Differences Between Unmanaged C++ and C++/CLI Code](#).

Parameters

TabBoxCount

Number of CommandManager tab boxes on this CommandManager tab

Return Value

- in-process, unmanaged C++: Pointer to an array of [CommandManager tab boxes](#) on this CommandManager tab
 - VBA, VB.NET, C#, and C++/CLI: Not supported
- See [In-process Methods](#) for details about this type of method.

Remarks

Call [ICommandTab::GetCommandTabBoxCount](#) before calling this method to get the value of TabBoxCount.

See Also

[ICommandTab Interface](#)

[ICommandTab Members](#)

[ICommandTab::AddCommandTabBox Method](#)

[ICommandTab::CommandTabBoxes Method](#)

[ICommandTab::RemoveCommandTabBox Method](#)

Availability

SOLIDWORKS 2008 FCS, Revision Number 16.0

SOLIDWORKS API Help

[Send comments on this topic.](#)

Name Property (ICommandTab)

[See Also](#)



[SolidWorks.Interop.sldworks Namespace](#) > [ICommandTab Interface](#) : Name Property (ICommandTab)

Gets or sets the name of this CommandManager tab.

.NET Syntax

Visual Basic (Declaration)

```
Property Name As System.String
```

Visual Basic (Usage)



```
Dim instance As ICommandTab
```

```
Dim value As System.String
```

```
instance.Name = value
```

```
value = instance.Name
```

C#

```
System.string Name {get; set;}
```

C++/CLI

```
property System.String^ Name {
    System.String^ get();
    void set ( & System.String^ value);
}
```

NOTE: See [Differences Between Unmanaged C++ and C++/CLI Code](#).

Property Value

Name of this CommandManager tab

Visual Basic for Applications (VBA) Syntax

See [CommandTab::Name](#).

See Also

[ICommandTab Interface](#)
[ICommandTab Members](#)

Availability

SOLIDWORKS 2008 FCS, Revision Number 16.0

SOLIDWORKS API Help

[Send comments on this topic.](#)

RemoveCommandTabBox Method (ICommandTab)

[See Also](#)



[SolidWorks.Interop.sldworks Namespace](#) > [ICommandTab Interface](#) : RemoveCommandTabBox Method (ICommandTab)

Removes the specified tab box and its buttons from this CommandManager tab.

.NET Syntax

Visual Basic (Declaration)

```
Sub RemoveCommandTabBox( _  
    ByVal CommandTabBox As CommandTabBox _  
)
```

Visual Basic (Usage)



```
Dim instance As ICommandTab  
Dim CommandTabBox As CommandTabBox  
  
instance.RemoveCommandTabBox(CommandTabBox)
```

C#

```
void RemoveCommandTabBox(  
    CommandTabBox CommandTabBox  
)
```

C++/CLI

```
void RemoveCommandTabBox(  
& CommandTabBox^ CommandTabBox  
)
```

NOTE: See [Differences Between Unmanaged C++ and C++/CLI Code](#).

Parameters

CommandTabBox
[CommandManager tab box](#) and its buttons to remove

Visual Basic for Applications (VBA) Syntax

See [CommandTab::RemoveCommandTabBox](#).

See Also

[ICommandTab Interface](#)
[ICommandTab Members](#)
[ICommandTab::AddCommandTabBox Method](#)
[ICommandTab::CommandTabBoxes Method](#)
[ICommandTab::GetCommandTabBoxCount Method](#)
[ICommandTab::IGetCommandTabBoxes Method](#)

Availability

Visible Property (ICommandTab)

[See Also](#)



[SolidWorks.Interop.sldworks Namespace](#) > [ICommandTab Interface](#) : Visible Property (ICommandTab)

Gets or sets whether to show or hide this CommandManager tab.

.NET Syntax

Visual Basic (Declaration)

Property Visible As System.Boolean

Visual Basic (Usage)



```
Dim instance As ICommandTab  
Dim value As System.Boolean
```

```
instance.Visible = value
```

```
value = instance.Visible
```

C#

```
System.bool Visible {get; set;}
```

C++/CLI

```
property System.bool Visible {  
    System.bool get();  
    void set ( & System.bool value);  
}
```

NOTE: See [Differences Between Unmanaged C++ and C++/CLI Code](#).

Visual Basic for Applications (VBA) Syntax

See [CommandTab.Visible](#).

See Also

[ICommandTab Interface](#)
[ICommandTab Members](#)

Availability

ICommandTabBox (Type)

ICommandTabBox Interface

[See Also](#) [Members](#) [Example](#)



[SolidWorks.Interop.sldworks Namespace](#) : ICommandTabBox Interface

Allows add-in applications to create CommandManager tab boxes and add them to a CommandManager tab. The add-in application must create and clean-up its own tab boxes.

NOTE: Click the **Members** link, located near the top of the topic, to see this interface's methods and properties.

.NET Syntax

Visual Basic (Declaration)

```
Public Interface ICommandTabBox
```

Visual Basic (Usage)



```
Dim instance As ICommandTabBox
```

C#

```
public interface ICommandTabBox
```

C++/CLI

```
public interface class ICommandTabBox
```

Visual Basic for Applications (VBA) Syntax

See [CommandTabBox](#).

Example

[Create CommandManager Tab and Tab Boxes \(VB.NET\)](#)
[Create CommandManager Tab and Tab Boxes \(C#\)](#)

Accessors

[ICommandTab::AddCommandTabBox](#)
[ICommandTab::CommandTabBoxes](#)
[ICommandTab::IGetCommandTabBoxes](#)

Access Diagram

[CommandTabBox](#)

See Also

[ICommandTabBox Members](#)
[SolidWorks.Interop.sldworks Namespace](#)
[ICommandTab Interface](#)

ICommandTabBox Interface Methods

[See Also](#)



[SolidWorks.Interop.sldworks Namespace](#) : ICommandTabBox Interface

For a list of all members of this type, see [ICommandTabBox members](#).

Public Methods

Name	Description
AddCommands	Adds buttons to this CommandManager tab box.

		
	GetCommands	Gets the buttons' command IDs, text display styles, and number of commands on the CommandManager tab box.
	IAddCommands	Adds buttons to this CommandManager tab box.
	IGetCommands	Gets the buttons' Command IDs, text display styles, and number of commands on the CommandManager tab box.
	IRemoveCommands	Removes the specified buttons from this CommandManager tab box.
	RemoveCommands	Removes the specified buttons from this CommandManager tab box.

[Top](#)

See Also

[ICommandTabBox Interface](#)
[SolidWorks.Interop.sldworks Namespace](#)
[ICommandTab Interface](#)

SOLIDWORKS API Help

[Send comments on this topic.](#)

ICommandTabBox Interface Members

[See Also](#) [Methods](#)

 [SolidWorks.Interop.sldworks Namespace](#) : ICommandTabBox Interface

The following tables list the members exposed by [ICommandTabBox](#).

Public Methods

Name	Description
 AddCommands	Adds buttons to this CommandManager tab box.
 GetCommands	Gets the buttons' command IDs, text display styles, and number of commands on the CommandManager tab box.
 IAddCommands	Adds buttons to this CommandManager tab box.
 IGetCommands	Gets the buttons' Command IDs, text display styles, and number of commands on the CommandManager tab box.
 IRemoveCommands	Removes the specified buttons from this CommandManager tab box.
 RemoveCommands	Removes the specified buttons from this CommandManager tab box.

[Top](#)

See Also

[ICommandTabBox Interface](#)
[SolidWorks.Interop.sldworks Namespace](#)
[ICommandTab Interface](#)

SOLIDWORKS API Help

[Send comments on this topic.](#)

AddCommands Method (ICommandTabBox)

[See Also](#) [Example](#)

  [SolidWorks.Interop.sldworks Namespace](#) > [ICommandTabBox Interface](#) : AddCommands Method (ICommandTabBox)

Adds buttons to this CommandManager tab box.

.NET Syntax

Visual Basic (Declaration)

```
Function AddCommands( _  
    ByVal CommandIDs As System.Object, _  
    ByVal TextDisplayStyles As System.Object _  
    ) As System.Boolean
```

Visual Basic (Usage)



```
Dim instance As ICommandTabBox  
Dim CommandIDs As System.Object  
Dim TextDisplayStyles As System.Object  
Dim value As System.Boolean
```

```
value = instance.AddCommands(CommandIDs, TextDisplayStyles)
```

C#

```
System.bool AddCommands(  
    System.object CommandIDs,  
    System.object TextDisplayStyles  
)
```

C++/CLI

```
System.bool AddCommands(  
& System.Object^ CommandIDs,  
& System.Object^ TextDisplayStyles  
)
```

NOTE: See [Differences Between Unmanaged C++ and C++/CLI Code](#).

Parameters

CommandIDs

Array of command IDs for the buttons (see **Remarks**)

TextDisplayStyles

Array of the text display styles for the buttons as defined in [swCommandTabButtonTextDisplay_e](#)

Return Value

True if the buttons are added to the CommandManager tab box, false if not

Visual Basic for Applications (VBA) Syntax

See [CommandTabBox::AddCommands](#).

Example

[Create CommandManager Tab and Tab Boxes \(VB.NET\)](#)
[Create CommandManager Tab and Tab Boxes \(C#\)](#)

Remarks

You can add both CommandGroup and FlyoutGroup items to CommandManager. Populate CommandIDs by calling [IFlyoutGroup::CmdID](#) for FlyoutGroups and [ICommandGroup::CommandID](#) or [ICommandGroup::ToolBarId](#) after calling [ICommandGroup::Activate](#) for CommandGroups.

See Also

[ICommandTabBox Interface](#)
[ICommandTabBox Members](#)
[ICommandTabBox::IAddCommands Method](#)

Availability

SOLIDWORKS 2008 FCS, Revision Number 16.0

SOLIDWORKS API Help

[Send comments on this topic.](#)

GetCommands Method (ICommandTabBox)

[See Also](#) [Example](#)



[SolidWorks.Interop.sldworks Namespace](#) > [ICommandTabBox Interface](#) : GetCommands Method (ICommandTabBox)

Gets the buttons' command IDs, text display styles, and number of commands on the CommandManager tab box.

.NET Syntax

Visual Basic (Declaration)

```
Function GetCommands(  
    ByRef CommandIDs As System.Object, _  
    ByRef TextDisplayStyles As System.Object _  
) As System.Integer
```

```
Dim instance As ICommandTabBox
Dim CommandIDs As System.Object
Dim TextDisplayStyles As System.Object
Dim value As System.Integer

value = instance.GetCommands(CommandIDs, TextDisplayStyles)
```

C#

```
System.int GetCommands(
    out System.object CommandIDs,
    out System.object TextDisplayStyles
)
```

C++/CLI

```
System.int GetCommands(
    & [Out] System.Object^ CommandIDs,
    & [Out] System.Object^ TextDisplayStyles
)
```

NOTE: See [Differences Between Unmanaged C++ and C++/CLI Code](#).

Parameters

CommandIDs

Array of command IDs for the buttons

TextDisplayStyles

Array of the text display styles for the buttons as defined in [swCommandTabButtonTextDisplay_e](#)

Return Value

Number of buttons on this CommandManager tab box

Visual Basic for Applications (VBA) Syntax

See [CommandTabBox::GetCommands](#).

Example

[Create CommandManager Tab and Tab Boxes \(C#\)](#)

[Create CommandManager Tab and Tab Boxes \(VB.NET\)](#)

See Also

[ICommandTabBox Interface](#)

[ICommandTabBox Members](#)

[ICommandTabBox::IGetCommands Method](#)

Availability

SOLIDWORKS 2010 FCS, Revision Number 18.0

SOLIDWORKS API Help

[Send comments](#) on this topic.

IAddCommands Method (ICommandTabBox)

[See Also](#)



[SolidWorks.Interop.sldworks Namespace](#) > [ICommandTabBox Interface](#) : IAddCommands Method (ICommandTabBox)

Adds buttons to this CommandManager tab box.

.NET Syntax

Visual Basic (Declaration)

```
Function IAddCommands( _
    ByVal CommandIDCount As System.Integer, _
    ByRef CommandIDs As System.Integer, _
```

```
ByRef TextDisplayStyles As System.Integer _  
) As System.Boolean
```

Visual Basic (Usage)



```
Dim instance As ICommandTabBox  
Dim CommandIDCount As System.Integer  
Dim CommandIDs As System.Integer  
Dim TextDisplayStyles As System.Integer  
Dim value As System.Boolean  
  
value = instance.IAddCommands(CommandIDCount, CommandIDs, TextDisplayStyles)
```

C#

```
System.bool IAddCommands(  
    System.int CommandIDCount,  
    ref System.int CommandIDs,  
    ref System.int TextDisplayStyles  
)
```

C++/CLI

```
System.bool IAddCommands(  
& System.int CommandIDCount,  
& System.int% CommandIDs,  
& System.int% TextDisplayStyles  
)
```

NOTE: See [Differences Between Unmanaged C++ and C++/CLI Code](#).

Parameters

CommandIDCount

Number of buttons to add

CommandIDs

- in-process, unmanaged C++: Pointer to an array of command IDs (see **Remarks**)
- VBA, VB.NET, C#, and C++/CLI: Not supported

See [In-process Methods](#) for details about this type of method.

TextDisplayStyles

- in-process, unmanaged C++: Pointer to an array the text display styles for the buttons as defined in [swCommandTabButtonTextDisplay_e](#)

- VBA, VB.NET, C#, and C++/CLI: Not supported

See [In-process Methods](#) for details about this type of method.

Return Value

True if the buttons are added to the CommandManager tab box, false if not

Remarks

You can get the CommandID values using [ICommandGroup::CommandID](#) or [ICommandGroup::ToolBarId](#) after calling [ICommandGroup::Activate](#).

See Also

[ICommandTabBox Interface](#)

[ICommandTabBox Members](#)

[ICommandTabBox::AddCommands Method](#)

Availability

SOLIDWORKS 2008 FCS, Revision Number 16.0

SOLIDWORKS API Help

[Send comments on this topic.](#)

IGetCommands Method (ICommandTabBox)

[See Also](#)



[SolidWorks.Interop.sldworks Namespace](#) > [ICommandTabBox Interface](#) : IGetCommands Method (ICommandTabBox)

Gets the buttons' Command IDs, text display styles, and number of commands on the CommandManager tab box.

.NET Syntax

Visual Basic (Declaration)

```
Function IGetCommands( _  
    ByRef CommandIDs As System.Integer, _  
    ByRef TextDisplayStyles As System.Integer _  
    ) As System.Integer
```

Visual Basic (Usage)



```
Dim instance As ICommandTabBox  
Dim CommandIDs As System.Integer  
Dim TextDisplayStyles As System.Integer  
Dim value As System.Integer  
  
value = instance.IGetCommands(CommandIDs, TextDisplayStyles)
```

C#

```
System.int IGetCommands(  
    out System.int CommandIDs,  
    out System.int TextDisplayStyles  
)
```

C++/CLI

```
System.int IGetCommands(  
& [Out] System.int CommandIDs,  
& [Out] System.int TextDisplayStyles  
)
```

NOTE: See [Differences Between Unmanaged C++ and C++/CLI Code](#).

Parameters

CommandIDs

- in-process, unmanaged C++: Pointer to an array of command IDs (see **Remarks**)
- VBA, VB.NET, C#, and C++/CLI: Not supported

See [In-process Methods](#) for details about this type of method.

TextDisplayStyles

- in-process, unmanaged C++: Pointer to an array the text display styles for the buttons as defined in [swCommandTabButtonTextDisplay_e](#)
- VBA, VB.NET, C#, and C++/CLI: Not supported

See [In-process Methods](#) for details about this type of method

Return Value

Number of buttons on this CommandManager tab box

Visual Basic for Applications (VBA) Syntax

See [CommandTabBox::IGetCommands](#).

See Also

[ICommandTabBox Interface](#)
[ICommandTabBox Members](#)
[ICommandTabBox::GetCommands Method](#)

Availability

SOLIDWORKS 2010 FCS, Revision Number 18.0

SOLIDWORKS API Help

[Send comments on this topic.](#)

IRemoveCommands Method (ICommandTabBox)

[See Also](#)



[SolidWorks.Interop.sldworks Namespace](#) > [ICommandTabBox Interface](#) : IRemoveCommands Method (ICommandTabBox)

Removes the specified buttons from this CommandManager tab box.

.NET Syntax

Visual Basic (Declaration)

```
Function IRemoveCommands( _  
    ByVal CommandIDCount As System.Integer, _  
    ByRef CommandIDs As System.Integer _  
) As System.Boolean
```

Visual Basic (Usage)



```
Dim instance As ICommandTabBox  
Dim CommandIDCount As System.Integer  
Dim CommandIDs As System.Integer  
Dim value As System.Boolean  
  
value = instance.IRemoveCommands(CommandIDCount, CommandIDs)
```

C#

```
System.bool IRemoveCommands(  
    System.int CommandIDCount,  
    ref System.int CommandIDs  
)
```

C++/CLI

```
System.bool IRemoveCommands(  
& System.int CommandIDCount,  
& System.int% CommandIDs  
)
```

NOTE: See [Differences Between Unmanaged C++ and C++/CLI Code](#).

Parameters

CommandIDCount

Number of buttons to remove from this CommandManager tab box

CommandIDs

- in-process, unmanaged C++: Pointer to an array of the command IDs for the buttons you want removed from this CommandManager tab box (see **Remarks**)

- VBA, VB.NET, C#, and C++/CLI: Not supported

See [In-process Methods](#) for details about this type of method.

Return Value

True if the specified buttons are removed, false if not

Remarks

You can get the CommandID values using [ICommandGroup::CommandID](#) or [ICommandGroup::ToolBarId](#) after calling [ICommandGroup::Activate](#).

See Also

[ICommandTabBox Interface](#)

[ICommandTabBox Members](#)

[ICommandTabBox::RemoveCommands Method](#)

Availability

SOLIDWORKS 2008 FCS, Revision Number 16.0

SOLIDWORKS API Help

[Send comments on this topic.](#)

RemoveCommands Method (ICommandTabBox)

[See Also](#)



[SolidWorks.Interop.sldworks Namespace](#) > [ICommandTabBox Interface](#) : RemoveCommands Method (ICommandTabBox)

Removes the specified buttons from this CommandManager tab box.

.NET Syntax

Visual Basic (Declaration)

```
Function RemoveCommands( _  
    ByVal CommandIDs As System.Object _  
) As System.Boolean
```

Visual Basic (Usage)



```
Dim instance As ICommandTabBox  
Dim CommandIDs As System.Object  
Dim value As System.Boolean  
  
value = instance.RemoveCommands(CommandIDs)
```

C#

```
System.bool RemoveCommands(  
    System.object CommandIDs  
)
```

C++/CLI

```
System.bool RemoveCommands(  
& System.Object^ CommandIDs  
)
```

NOTE: See [Differences Between Unmanaged C++ and C++/CLI Code](#).

Parameters

CommandIDs

Array of command IDs for the buttons you want removed from this CommandManager tab box (see **Remarks**)

Return Value

True if the specified buttons are removed, false if not

Visual Basic for Applications (VBA) Syntax

See [CommandTabBox::RemoveCommands](#).

Remarks

You can get the CommandID values using [ICommandGroup::CommandID](#) or [ICommandGroup::ToolbarId](#) after calling [ICommandGroup::Activate](#).

See Also

[ICommandTabBox Interface](#)
[ICommandTabBox Members](#)
[ICommandTabBox::IRemoveCommands Method](#)

Availability

SOLIDWORKS 2008 FCS, Revision Number 16.0