

SOLIDWORKS API (.NET VBA C#) — Reference (250/337): ISelectionMgr (part 2 of 2)

SOLIDWORKS API Documentation (converted from CHM)

ISelectionMgr (part 2 of 2) (Type)

SOLIDWORKS API Help

[Send comments](#) on this topic.

IGetSelectedObjectsComponent Method (ISelectionMgr)

[See Also](#)



[SolidWorks.Interop.sldworks Namespace](#) > [ISelectionMgr Interface](#) : IGetSelectedObjectsComponent Method (ISelectionMgr)

Obsolete. Superseded by [ISelectionMgr::GetSelectedObjectsComponent3](#).

.NET Syntax

Visual Basic (Declaration)

```
Function IGetSelectedObjectsComponent( _  
    ByVal AtIndex As System.Integer _  
) As Component
```

Visual Basic (Usage)



```
Dim instance As ISelectionMgr  
Dim AtIndex As System.Integer  
Dim value As Component  
  
value = instance.IGetSelectedObjectsComponent(AtIndex)
```

C#

```
Component IGetSelectedObjectsComponent(  
    System.int AtIndex  
)
```

C++/CLI

```
Component^ IGetSelectedObjectsComponent(  
& System.int AtIndex  
)
```

NOTE: See [Differences Between Unmanaged C++ and C++/CLI Code](#).

Parameters

AtIndex

Visual Basic for Applications (VBA) Syntax

See [SelectionMgr.IGetSelectedObjectsComponent](#).

See Also

[ISelectionMgr Interface](#)
[ISelectionMgr Members](#)

SOLIDWORKS API Help

[Send comments](#) on this topic.

IGetSelectedObjectsComponent2 Method (ISelectionMgr)

[See Also](#)



[SolidWorks.Interop.sldworks Namespace](#) > [ISelectionMgr Interface](#) : IGetSelectedObjectsComponent2 Method (ISelectionMgr)

Obsolete. Superseded by [ISelectionMgr::GetSelectedObjectsComponent3](#).

.NET Syntax

Visual Basic (Declaration)

```
Function IGetSelectedObjectsComponent2( _  
    ByVal AtIndex As System.Integer _  
) As Component2
```

```
Dim instance As ISelectionMgr
Dim AtIndex As System.Integer
Dim value As Component2

value = instance.IGetSelectedObjectsComponent2(AtIndex)
```

C#

```
Component2 IGetSelectedObjectsComponent2(
    System.int AtIndex
)
```

C++/CLI

```
Component2^ IGetSelectedObjectsComponent2(
    & System.int AtIndex
)
```

NOTE: See [Differences Between Unmanaged C++ and C++/CLI Code](#).

Parameters

AtIndex

Visual Basic for Applications (VBA) Syntax

See [SelectionMgr.IGetSelectedObjectsComponent2](#).

See Also

[ISelectionMgr Interface](#)
[ISelectionMgr Members](#)

SOLIDWORKS API Help

[Send comments](#) on this topic.

IGetSelectionPoint Method (ISelectionMgr)

[See Also](#)



[SolidWorks.Interop.sldworks Namespace](#) > [ISelectionMgr Interface](#) : IGetSelectionPoint Method (ISelectionMgr)

Obsolete. Superseded by [ISelectionMgr.IGetSelectionPoint2](#).

.NET Syntax

Visual Basic (Declaration)

```
Function IGetSelectionPoint( _
    ByVal AtIndex As System.Integer _
) As System.Double
```

Visual Basic (Usage)

Copy Code

```
Dim instance As ISelectionMgr
Dim AtIndex As System.Integer
Dim value As System.Double

value = instance.IGetSelectionPoint(AtIndex)
```

C#

```
System.double IGetSelectionPoint(
    System.int AtIndex
)
```

C++/CLI

```
System.double IGetSelectionPoint(
    & System.int AtIndex
)
```

)

NOTE: See [Differences Between Unmanaged C++ and C++/CLI Code](#).

Parameters

AtIndex

Visual Basic for Applications (VBA) Syntax

See [SelectionMgr::IGetSelectionPoint](#).

See Also

[ISelectionMgr Interface](#)
[ISelectionMgr Members](#)

SOLIDWORKS API Help

[Send comments](#) on this topic.

IGetSelectionPoint2 Method (ISelectionMgr)

[See Also](#)



[SolidWorks.Interop.sldworks Namespace](#) > [ISelectionMgr Interface](#) : IGetSelectionPoint2 Method (ISelectionMgr)

Gets the selected point in model space coordinates from the currently selected object.

.NET Syntax

Visual Basic (Declaration)

```
Function IGetSelectionPoint2( _  
    ByVal Index As System.Integer, _  
    ByVal Mark As System.Integer _  
) As System.Double
```

Visual Basic (Usage)



```
Dim instance As ISelectionMgr  
Dim Index As System.Integer  
Dim Mark As System.Integer  
Dim value As System.Double
```

```
value = instance.IGetSelectionPoint2(Index, Mark)
```

C#

```
System.double IGetSelectionPoint2(  
    System.int Index,  
    System.int Mark  
)
```

C++/CLI

```
System.double IGetSelectionPoint2(  
& System.int Index,  
& System.int Mark  
)
```

NOTE: See [Differences Between Unmanaged C++ and C++/CLI Code](#).

Parameters

Index

Index position with in the current list of selected items, where AtIndex ranges from 1 to [ISelectionMgr::GetSelectedObjectCount2](#) (see **Remarks**).

Mark

- -1 = All selections regardless of marks
- 0 = only the selections without marks
- Any other value = Value that was used to mark and select an object

Return Value

Array of 3 doubles (x,y,z)

Visual Basic for Applications (VBA) Syntax

See [SelectionMgr::IGetSelectionPoint2](#).

Remarks

The index starts at 1, even when using C++. However, if you specify -1 for the Index argument, then the Mark argument is ignored and the dynamically highlighted view is selected if dynamic highlighting is turned on. See also IAssemblyDoc event [DynamicHighlightNotify](#), IDrawingDoc event [DynamicHighlightNotify](#), and IPartDoc event [DynamicHighlightNotify](#).

The point returned from [ISelectionMgr::GetSelectionPoint2](#) or ISelectionMgr::IGetSelectionPoint2 cannot lie on the object that was selected. For example, the user can select an edge when the edge is within the pick radius of their mouse cursor. However, to get a point on a face, edge, or vertex, use that object's GetClosestPointOn method.

To do this, get the [IFace2](#), [IEdge](#), or [IVertex](#) object using the [ISelectionMgr::GetSelectedObject6](#) method, and then use that object to call GetClosestPointOn. Pass the X,Y,Z values returned from ISelectionMgr::GetSelectionPoint2 or ISelectionMgr::IGetSelectionPoint2, and the GetClosestPointOn method will return the closest X,Y,Z point that is on the face, edge, or vertex.

If the selected object is sketch geometry, then the coordinates returned are in sketch space. The coordinates are 2D and related to the origin of the sketch that owns the selected geometry.

See Also

[ISelectionMgr Interface](#)
[ISelectionMgr Members](#)
[ISelectionMgr::DeSelect2 Method](#)
[ISelectionMgr::GetSelectedObjectCount2 Method](#)
[ISelectionMgr::GetSelectedObjectLoop2 Method](#)
[ISelectionMgr::GetSelectedObjectMark Method](#)
[ISelectionMgr::GetSelectedObjectsComponent3 Method](#)
[ISelectionMgr::GetSelectedObjectsDrawingView2 Method](#)
[ISelectionMgr::GetSelectedObjectType3 Method](#)
[ISelectionMgr::IDeSelect2 Method](#)
[ISelectionMgr::SetSelectionPoint2 Method](#)

Availability

SOLIDWORKS 2006 FCS, Revision Number 14.0

SOLIDWORKS API Help

[Send comments on this topic.](#)

IGetSelectionPointInSketchSpace Method (ISelectionMgr)

[See Also](#)



[SolidWorks.Interop.sldworks Namespace](#) > [ISelectionMgr Interface](#) : IGetSelectionPointInSketchSpace Method (ISelectionMgr)

Obsolete. Superseded by [ISelectionMgr::IGetSelectionPointInSketchSpace2](#).

.NET Syntax

Visual Basic (Declaration)

```
Function IGetSelectionPointInSketchSpace( _  
    ByVal AtIndex As System.Integer _  
) As System.Double
```

Visual Basic (Usage)



```
Dim instance As ISelectionMgr  
Dim AtIndex As System.Integer  
Dim value As System.Double
```

```
value = instance.IGetSelectionPointInSketchSpace(AtIndex)
```

C#

```
System.double IGetSelectionPointInSketchSpace(  
    System.int AtIndex  
)
```

C++/CLI

```
System.double IGetSelectionPointInSketchSpace(  
& System.int AtIndex  
)
```

NOTE: See [Differences Between Unmanaged C++ and C++/CLI Code](#).

Parameters

AtIndex

Visual Basic for Applications (VBA) Syntax

See [SelectionMgr::IGetSelectionPointInSketchSpace](#).

See Also

[ISelectionMgr Interface](#)
[ISelectionMgr Members](#)

SOLIDWORKS API Help

[Send comments](#) on this topic.

IGetSelectionPointInSketchSpace2 Method (ISelectionMgr)

[See Also](#)



[SolidWorks.Interop.sldworks Namespace](#) > [ISelectionMgr Interface](#) : IGetSelectionPointInSketchSpace2 Method (ISelectionMgr)

Gets the selection point projected on to the active sketch and returned in sketch space.

.NET Syntax

Visual Basic (Declaration)

```
Function IGetSelectionPointInSketchSpace2( _  
    ByVal Index As System.Integer, _  
    ByVal Mark As System.Integer _  
) As System.Double
```

Visual Basic (Usage)



```
Dim instance As ISelectionMgr  
Dim Index As System.Integer  
Dim Mark As System.Integer  
Dim value As System.Double
```

```
value = instance.IGetSelectionPointInSketchSpace2(Index, Mark)
```

C#

```
System.double IGetSelectionPointInSketchSpace2(  
    System.int Index,  
    System.int Mark  
)
```

C++/CLI

```
System.double IGetSelectionPointInSketchSpace2(  
& System.int Index,  
& System.int Mark  
)
```

NOTE: See [Differences Between Unmanaged C++ and C++/CLI Code](#).

Parameters

Index

Index position with in the current list of selected items, where AtIndex ranges from 1 to [ISelectionMgr::GetSelectedObjectCount2](#) (see **Remarks**)

Mark

- 1 = All selections regardless of marks
- 0 = only the selections without marks
- Any other value that was used to mark and select an object

Return Value

- in-process, unmanaged C++: Pointer to an array of 3 doubles (see **Remarks**)
- VBA, VB.NET, C#, and C++/CLI: Not supported

See [In-process Methods](#) for details about this type of method.

Visual Basic for Applications (VBA) Syntax

See [SelectionMgr::IGetSelectionPointInSketchSpace2](#).

Remarks

The selection point is projected on to the currently active sketch, resulting in a z value of 0.00.

If a sketch is not currently active, then the return value is the same as that returned by [ISelectionMgr::GetSelectionPoint2](#) or [ISelectionMgr::IGetSelectionPoint2](#). You can determine if a sketch is active by checking for a null return value from [IModelDoc2::GetActiveSketch2](#) or [IModelDoc2::IGetActiveSketch2](#).

The index starts at 1. However, if you specify -1 for the Index argument, then the Mark argument is ignored and the dynamically highlighted view is selected if dynamic highlighting is turned on. See also IAssemblyDoc event [DynamicHighlightNotify](#), IDrawingDoc event [DynamicHighlightNotify](#), and IPartDoc event [DynamicHighlightNotify](#).

See Also

[ISelectionMgr Interface](#)
[ISelectionMgr Members](#)
[ISelectionMgr::GetSelectionPointInSketchSpace2 Method](#)
[ISelectionMgr::DeSelect2 Method](#)
[ISelectionMgr::GetSelectedObject6 Method](#)
[ISelectionMgr::GetSelectedObjectLoop2 Method](#)
[ISelectionMgr::GetSelectedObjectMark Method](#)
[ISelectionMgr::GetSelectedObjectsComponent3 Method](#)
[ISelectionMgr::GetSelectedObjectsDrawingView2 Method](#)
[ISelectionMgr::GetSelectedObjectType3 Method](#)
[ISelectionMgr::IDeSelect2 Method](#)

Availability

SOLIDWORKS 2006 FCS, Revision Number 14.0

SOLIDWORKS API Help

[Send comments on this topic.](#)

IsCoordSysElementSelected Method (ISelectionMgr)

[See Also](#)



[SolidWorks.Interop.sldworks Namespace](#) > [ISelectionMgr Interface](#) : IsCoordSysElementSelected Method (ISelectionMgr)

Gets whether the selection is a coordinate system element.

.NET Syntax

Visual Basic (Declaration)

```
Function IsCoordSysElementSelected( _
    ByVal Index As System.Integer, _
    ByVal Mark As System.Integer _
) As System.Boolean
```

Visual Basic (Usage)



```
Dim instance As ISelectionMgr
Dim Index As System.Integer
Dim Mark As System.Integer
Dim value As System.Boolean
```

```
value = instance.IsCoordSysElementSelected(Index, Mark)
```

C#

```
System.bool IsCoordSysElementSelected(
    System.int Index,
    System.int Mark
)
```

C++/CLI

```
System.bool IsCoordSysElementSelected(  
& System.int Index,  
& System.int Mark  
)
```

NOTE: See [Differences Between Unmanaged C++ and C++/CLI Code](#).

Parameters

Index

Index position within the current list of selected items, where Index ranges from 1 to [ISelectionMgr::GetSelectedObjectCount2](#) (see **Remarks**)

Mark

- -1 = All selections regardless of marks
- 0 = only the selections without marks

Any other value = Value that was used to mark and select an object

Return Value

True if coordinate system element selected, false if not

Visual Basic for Applications (VBA) Syntax

See [SelectionMgr::IsCoordSysElementSelected](#).

Example

See the [ICoordinateSystemElement](#) examples.

Remarks

Call this method after calling [ISelectionMgr::GetSelectedCoordSysElement](#) to confirm that a coordinate system element is retrieved.

See Also

[ISelectionMgr Interface](#)
[ISelectionMgr Members](#)

Availability

SOLIDWORKS 2025 SP01, Revision Number 33.1

SOLIDWORKS API Help

[Send comments](#) on this topic.

IsInEditTarget Method (ISelectionMgr)

[See Also](#)



[SolidWorks.Interop.sldworks Namespace](#) > [ISelectionMgr Interface](#) : IsInEditTarget Method (ISelectionMgr)

Obsolete. Superseded by [ISelectionMgr::IsInEditTarget2](#).

.NET Syntax

Visual Basic (Declaration)

```
Function IsInEditTarget( _  
    ByVal AtIndex As System.Integer _  
) As System.Boolean
```

Visual Basic (Usage)



```
Dim instance As ISelectionMgr  
Dim AtIndex As System.Integer  
Dim value As System.Boolean
```

```
value = instance.IsInEditTarget(AtIndex)
```

C#

```
System.bool IsInEditTarget(  
    System.int AtIndex
```

)

C++/CLI

```
System.bool IsInEditTarget(  
& System.int AtIndex  
)
```

NOTE: See [Differences Between Unmanaged C++ and C++/CLI Code](#).

Parameters

AtIndex

Visual Basic for Applications (VBA) Syntax

See [SelectionMgr::IsInEditTarget](#).

See Also

[ISelectionMgr Interface](#)
[ISelectionMgr Members](#)

SOLIDWORKS API Help

[Send comments on this topic.](#)

IsInEditTarget2 Method (ISelectionMgr)

[See Also](#)



[SolidWorks.Interop.sldworks Namespace](#) > [ISelectionMgr Interface](#) : IsInEditTarget2 Method (ISelectionMgr)

Gets whether the selected object is in the edit target.

.NET Syntax

Visual Basic (Declaration)

```
Function IsInEditTarget2( _  
    ByVal Index As System.Integer, _  
    ByVal Mark As System.Integer _  
) As System.Boolean
```

Visual Basic (Usage)



```
Dim instance As ISelectionMgr  
Dim Index As System.Integer  
Dim Mark As System.Integer  
Dim value As System.Boolean
```

```
value = instance.IsInEditTarget2(Index, Mark)
```

C#

```
System.bool IsInEditTarget2(  
    System.int Index,  
    System.int Mark  
)
```

C++/CLI

```
System.bool IsInEditTarget2(  
& System.int Index,  
& System.int Mark  
)
```

NOTE: See [Differences Between Unmanaged C++ and C++/CLI Code](#).

Parameters

Index

Index position with in the current list of selected items, where AtIndex ranges from 1 to [ISelectionMgr::GetSelectedObjectCount2](#) (see **Remarks**)

Mark

- 1 = All selections regardless of marks
- 0 = only the selections without marks

Any other value = Value that was used to mark and select an object

Return Value

True if the selected item specified by AtIndex belongs to a model that is the current edit target, false if not

Visual Basic for Applications (VBA) Syntax

See [SelectionMgr::IsInEditTarget2](#).

Remarks

Calling this method is necessary in assemblies when the end-user performs in-context editing of a part. This method allows you to determine if a selected item belongs to the model that is the current edit target.

The index starts at 1, even when using C++. However, if you specify -1 for the Index argument, then the Mark argument is ignored and the dynamically highlighted view is selected if dynamic highlighting is turned on. See also IAssemblyDoc event [DynamicHighlightNotify](#), IDrawingDoc event [DynamicHighlightNotify](#), and IPartDoc event [DynamicHighlightNotify](#).

See Also

[ISelectionMgr Interface](#)
[ISelectionMgr Members](#)

Availability

SOLIDWORKS 2006 FCS, Revision Number 14.0

SOLIDWORKS API Help

[Send comments on this topic.](#)

ResumeSelectionList Method (ISelectionMgr)

[See Also](#) [Example](#)



[SolidWorks.Interop.sldworks Namespace](#) > [ISelectionMgr Interface](#) : ResumeSelectionList Method (ISelectionMgr)

Obsolete. Superseded by [ISelectionMgr::ResumeSelectionList2](#)

.NET Syntax

Visual Basic (Declaration)

```
Sub ResumeSelectionList()
```

Visual Basic (Usage)



```
Dim instance As ISelectionMgr  
instance.ResumeSelectionList()
```

C#

```
void ResumeSelectionList()
```

C++/CLI

```
void ResumeSelectionList();
```

NOTE: See [Differences Between Unmanaged C++ and C++/CLI Code](#).

Visual Basic for Applications (VBA) Syntax

See [SelectionMgr::ResumeSelectionList](#).

Example

[Get Objects in Selection List \(C#\)](#)
[Get Objects in Selection List \(VB.NET\)](#)
[Get Objects in Selection List \(VBA\)](#)

Remarks

To add objects to a selection list without preselecting the objects in the user interface:

1. Call [ISelectionMgr::SuspendSelectionList](#) to suspend the current selection list, preserving its contents and starting a new selection list.
2. To populate a new selection list, call [ISelectionMgr::AddSelectionListObject](#) or [ISelectionMgr::AddSelectionListObjects](#).

NOTE: To add objects in a [selection set](#) in a new selection list, call [ISelectionSet::Select](#).

3. Process the objects in the new selection list.
4. Call [ISelectionMgr::ResumeSelectionList](#) to reinstate the suspended selection list.

To programmatically preselect objects in the user interface and add them to a selection list, use [IModelDocExtension::SelectByID2](#).

See Also

[ISelectionMgr Interface](#)
[ISelectionMgr Members](#)

Availability

SOLIDWORKS 2012 FCS, Revision Number 20.0

SOLIDWORKS API Help

[Send comments on this topic.](#)

ResumeSelectionList2 Method (ISelectionMgr)

[See Also](#) [Example](#)



[SolidWorks.Interop.sldworks Namespace](#) > [ISelectionMgr Interface](#) : ResumeSelectionList2 Method (ISelectionMgr)

Reinstates the previously suspended selection list.

.NET Syntax

Visual Basic (Declaration)

```
Sub ResumeSelectionList2( _  
    ByVal Append As System.Boolean _  
)
```

Visual Basic (Usage)



```
Dim instance As ISelectionMgr  
Dim Append As System.Boolean  
  
instance.ResumeSelectionList2(Append)
```

C#

```
void ResumeSelectionList2(  
    System.bool Append  
)
```

C++/CLI

```
void ResumeSelectionList2(  
& System.bool Append  
)
```

NOTE: See [Differences Between Unmanaged C++ and C++/CLI Code](#).

Parameters

Append

True to append the new selection list to the suspended selection list and resume the combined selection list, false to just resume the suspended selection list

Visual Basic for Applications (VBA) Syntax

See [SelectionMgr::ResumeSelectionList2](#).

Example

[Add Objects to Selection List \(VBA\)](#)
[Add Objects to Selection List \(VB.NET\)](#)

Remarks

To add objects to a selection list without pre-selecting the objects in the user interface:

1. Call [ISelectionMgr::SuspendSelectionList](#) to suspend the current selection list, preserving its contents and starting a new selection list.
 2. To populate the new selection list, call [ISelectionMgr::AddSelectionListObject](#), [ISelectionMgr::AddSelectionListObjects](#), or [IModelDocExtension::SelectByID2](#).
- NOTE:** To add objects in a [selection set](#) to a new selection list, call [ISelectionSet::Select](#).
3. Process the objects in the new selection list.
 4. Call this method to reinstate the suspended selection list, setting Append to true to append the new selection list.

See Also

[ISelectionMgr Interface](#)
[ISelectionMgr Members](#)

Availability

SOLIDWORKS 2020 FCS, Revision Number 28.0

SOLIDWORKS API Help

[Send comments on this topic.](#)

SelectionColor Property (ISelectionMgr)

[See Also](#)



[SolidWorks.Interop.sldworks Namespace](#) > [ISelectionMgr Interface](#) : SelectionColor Property (ISelectionMgr)

Gets or sets the selection color.

.NET Syntax

Visual Basic (Declaration)

```
Property SelectionColor(  
    ByVal Mark As System.Integer _  
) As System.Integer
```

Visual Basic (Usage)



```
Dim instance As ISelectionMgr  
Dim Mark As System.Integer  
Dim value As System.Integer  
  
instance.SelectionColor(Mark) = value  
  
value = instance.SelectionColor(Mark)
```

C#

```
System.int SelectionColor(  
    System.int Mark  
) {get; set;}
```

C++/CLI

```
property System.int SelectionColor {  
    System.int get(System.int Mark);  
    void set (System.int Mark, System.int value);  
}
```

NOTE: See [Differences Between Unmanaged C++ and C++/CLI Code](#).

Parameters

Mark
Mark value (see **Remarks**)

Property Value

Value indicating the color to use for a selection as defined by swSystemColors; these values are from [swUserPreferenceIntegerValue_e](#) (see **Remarks**)

Visual Basic for Applications (VBA) Syntax

See [SelectionMgr::SelectionColor](#).

Remarks

You should have a set of marks that you want to apply to selected objects. These marks are application specific and should be designed to present to the user a visual collection of like objects.

The values that SOLIDWORKS internal dialogs typically use for selection colors are:

- swSystemColorsSelectedItem1
- swSystemColorsSelectedItem2
- swSystemColorsSelectedItem3

You can also specify any of the following values:

- swSystemColorsViewportBackground
- swSystemColorsTopGradientColor
- swSystemColorsBottomGradientColor
- swSystemColorsDynamicHighlight
- swSystemColorsHighlight
- swSystemColorsSelectedItemFaceShaded
- swSystemColorsDrawingsVisibleModelEdge
- swSystemColorsDrawingsHiddenModelEdge

See Also

[ISelectionMgr Interface](#)
[ISelectionMgr Members](#)
[ISelectionMgr::ClearSelectionColors Method](#)

Availability

SOLIDWORKS 2005 FCS, Revision Number 13.0

SOLIDWORKS API Help

[Send comments on this topic.](#)

SetCallout Method (ISelectionMgr)

[See Also](#)



[SolidWorks.Interop.sldworks Namespace](#) > [ISelectionMgr Interface](#) : SetCallout Method (ISelectionMgr)

Adds a callout to the currently selected object.

.NET Syntax

Visual Basic (Declaration)

```
Function SetCallout( _  
    ByVal Index As System.Integer, _  
    ByVal PCallout As Callout _  
) As System.Boolean
```

Visual Basic (Usage)

```
Dim instance As ISelectionMgr  
Dim Index As System.Integer  
Dim PCallout As Callout  
Dim value As System.Boolean
```

```
value = instance.SetCallout(Index, PCallout)
```

C#

```
System.bool SetCallout(  
    System.int Index,
```



```
    Callout PCallout
)
```

C++/CLI

```
System.bool SetCallout(
& System.int Index,
& Callout^ PCallout
)
```

NOTE: See [Differences Between Unmanaged C++ and C++/CLI Code](#).

Parameters

Index
Index number of the selected object
PCallout
[Callout](#) (see **Remarks**)

Return Value

True if the callout is added to the selected object, false if not

Visual Basic for Applications (VBA) Syntax

See [SelectionMgr::SetCallout](#).

Remarks

Use [ISelectionMgr::CreateCallout2](#) to set the properties of the callout. Then use ISelectionMgr::SetCallout to add the callout to an already selected object.

See Also

[ISelectionMgr Interface](#)
[ISelectionMgr Members](#)

Availability

SOLIDWORKS 2006 FCS, Revision number 14.0

SOLIDWORKS API Help

[Send comments on this topic.](#)

SetSelectedObjectMark Method (ISelectionMgr)

[See Also](#) [Example](#)



[SolidWorks.Interop.sldworks Namespace](#) > [ISelectionMgr Interface](#) : SetSelectedObjectMark Method (ISelectionMgr)

Sets the mark value for the specified selection.

.NET Syntax

Visual Basic (Declaration)

```
Function SetSelectedObjectMark( _
    ByVal AtIndex As System.Integer, _
    ByVal Mark As System.Integer, _
    ByVal Action As System.Integer _
) As System.Boolean
```

Visual Basic (Usage)



```
Dim instance As ISelectionMgr
Dim AtIndex As System.Integer
Dim Mark As System.Integer
Dim Action As System.Integer
Dim value As System.Boolean
```

```
value = instance.SetSelectedObjectMark(AtIndex, Mark, Action)
```

C#

```
System.bool SetSelectedObjectMark(  
    System.int AtIndex,  
    System.int Mark,  
    System.int Action  
)
```

C++/CLI

```
System.bool SetSelectedObjectMark(  
& System.int AtIndex,  
& System.int Mark,  
& System.int Action  
)
```

NOTE: See [Differences Between Unmanaged C++ and C++/CLI Code](#).

Parameters

AtIndex

1 <= Index position within the current list of selected items <= [ISelectionMgr::GetSelectedObjectCount2](#)

Mark

Number to use as a mark for the selected item; this number is used by certain API functions that require ordered entity selection

Action

Action to take as defined in [swSelectionMarkAction_e](#)

Return Value

True if the selection is successfully set, false if not

Visual Basic for Applications (VBA) Syntax

See [SelectionMgr::SetSelectedObjectMark](#).

Example

[Thicken Surface and Generate Boss \(VBA\)](#)

[Thicken Surface and Generate Boss \(VB.NET\)](#)

[Thicken Surface and Generate Boss \(C#\)](#)

See Also

[ISelectionMgr Interface](#)

[ISelectionMgr Members](#)

[ISelectionMgr::GetSelectedObjectMark Method](#)

[ISelectionMgr::GetSelectedObject6 Method](#)

[ISelectionMgr::GetSelectedObjectCount2 Method](#)

[ISelectionMgr::GetSelectedObjectLoop2 Method](#)

[ISelectionMgr::GetSelectedObjectsComponent3 Method](#)

[ISelectionMgr::GetSelectedObjectsDrawingView2 Method](#)

[ISelectionMgr::GetSelectedObjectType3 Method](#)

[ISelectionMgr::GetSelectionPoint2 Method](#)

[ISelectionMgr::GetSelectionPointInSketchSpace2 Method](#)

[ISelectionMgr::IGetSelectedObjectsComponent2 Method](#)

[ISelectionMgr::IGetSelectionPointInSketchSpace2 Method](#)

[ISelectionMgr::SetSelectionPoint2 Method](#)

[ISelectionMgr::DeSelect2 Method](#)

[ISelectionMgr::IDeSelect2 Method](#)

[ISelectionMgr::GetSelectByIdSpecification Method](#)

[ISelectionMgr::GetSelectionSpecification Method](#)

Availability

SOLIDWORKS 2001 FCS, Revision Number 9.0

SOLIDWORKS API Help

[Send comments on this topic.](#)

SetSelectionPoint Method (ISelectionMgr)

[See Also](#)



[SolidWorks.Interop.sldworks Namespace](#) > [ISelectionMgr Interface](#) : SetSelectionPoint Method (ISelectionMgr)

Obsolete. Superseded by [ISelectionMgr::SetSelectionPoint2](#).

.NET Syntax

Visual Basic (Declaration)

```
Function SetSelectionPoint( _  
    ByVal AtIndex As System.Integer, _  
    ByVal X As System.Double, _  
    ByVal Y As System.Double, _  
    ByVal Z As System.Double _  
) As System.Boolean
```

Visual Basic (Usage)



```
Dim instance As ISelectionMgr  
Dim AtIndex As System.Integer  
Dim X As System.Double  
Dim Y As System.Double  
Dim Z As System.Double  
Dim value As System.Boolean  
  
value = instance.SetSelectionPoint(AtIndex, X, Y, Z)
```

C#

```
System.bool SetSelectionPoint(  
    System.int AtIndex,  
    System.double X,  
    System.double Y,  
    System.double Z  
)
```

C++/CLI

```
System.bool SetSelectionPoint(  
& System.int AtIndex,  
& System.double X,  
& System.double Y,  
& System.double Z  
)
```

NOTE: See [Differences Between Unmanaged C++ and C++/CLI Code](#).

Parameters

AtIndex

X

Y

Z

Visual Basic for Applications (VBA) Syntax

See [SelectionMgr::SetSelectionPoint](#).

See Also

[ISelectionMgr Interface](#)
[ISelectionMgr Members](#)

SOLIDWORKS API Help

[Send comments on this topic.](#)

SetSelectionPoint2 Method (ISelectionMgr)

[See Also](#)



[SolidWorks.Interop.sldworks Namespace](#) > [ISelectionMgr Interface](#) : SetSelectionPoint2 Method (ISelectionMgr)

Sets the selection point in model space.

.NET Syntax

Visual Basic (Declaration)

```

Function SetSelectionPoint2( _
    ByVal Index As System.Integer, _
    ByVal Mark As System.Integer, _
    ByVal X As System.Double, _
    ByVal Y As System.Double, _
    ByVal Z As System.Double _
) As System.Boolean

```

Visual Basic (Usage)



```

Dim instance As ISelectionMgr
Dim Index As System.Integer
Dim Mark As System.Integer
Dim X As System.Double
Dim Y As System.Double
Dim Z As System.Double
Dim value As System.Boolean

```

```
value = instance.SetSelectionPoint2(Index, Mark, X, Y, Z)
```

C#

```

System.bool SetSelectionPoint2(
    System.int Index,
    System.int Mark,
    System.double X,
    System.double Y,
    System.double Z
)

```

C++/CLI

```

System.bool SetSelectionPoint2(
    & System.int Index,
    & System.int Mark,
    & System.double X,
    & System.double Y,
    & System.double Z
)

```

NOTE: See [Differences Between Unmanaged C++ and C++/CLI Code](#).

Parameters

Index

Index position with in the current list of selected items, where AtIndex ranges from 1 to [ISelectionMgr::GetSelectedObjectCount2](#) (see **Remarks**)

Mark

- -1 = All selections regardless of marks
- 0 = only the selections without marks
- Any other value = Value that was used to mark and select an object

X

x coordinate of the selection point

Y

y coordinate of the selection point

Z

z coordinate of the selection point

Return Value

True if the position of the selection point is set, false if not

Visual Basic for Applications (VBA) Syntax

See [SelectionMgr::SetSelectionPoint2](#).

Remarks

This method allows an application to provide an XYZ position to a selected object at the given index in the [ISelectionMgr](#) object. This XYZ position represents a world-coordinate location in the context of that ISelectionMgr object.

The index starts at 1, even when using C++. However, if you specify -1 for the Index argument, then the Mark argument is ignored and the dynamically highlighted view is selected if dynamic highlighting is turned on. See also IAssemblyDoc event [DynamicHighlightNotify](#), IDrawingDoc

event [DynamicHighlightNotify](#), and IPartDoc event [DynamicHighlightNotify](#).

See Also

[ISelectionMgr Interface](#)
[ISelectionMgr Members](#)
[ISelectionMgr::GetSelectionPoint2 Method](#)
[ISelectionMgr::GetSelectionPointInSketchSpace2 Method](#)
[ISelectionMgr::IGetSelectionPoint2 Method](#)
[ISelectionMgr::IGetSelectionPointInSketchSpace2 Method](#)
[ISelectionMgr::GetSelectByIdSpecification Method](#)
[ISelectionMgr::GetSelectionSpecification Method](#)

Availability

SOLIDWORKS 2006 FCS, Revision Number 14.0

SOLIDWORKS API Help

[Send comments](#) on this topic.

SuspendSelectionList Method (ISelectionMgr)

[See Also](#) [Example](#)



[SolidWorks.Interop.sldworks Namespace](#) > [ISelectionMgr Interface](#) : SuspendSelectionList Method (ISelectionMgr)

Suspends the current selection list.

.NET Syntax

Visual Basic (Declaration)

```
Function SuspendSelectionList() As System.Integer
```

Visual Basic (Usage)



```
Dim instance As ISelectionMgr  
Dim value As System.Integer  
  
value = instance.SuspendSelectionList()
```

C#

```
System.int SuspendSelectionList()
```

C++/CLI

```
System.int SuspendSelectionList();
```

NOTE: See [Differences Between Unmanaged C++ and C++/CLI Code](#).

Return Value

0 if the suspended list is empty, 1 if not

Visual Basic for Applications (VBA) Syntax

See [SelectionMgr::SuspendSelectionList](#).

Example

[Add Objects to Selection List \(C#\)](#)
[Add Objects to Selection List \(VB.NET\)](#)
[Add Objects to Selection List \(VBA\)](#)
[Get Objects in Selection List \(C#\)](#)
[Get Objects in Selection List \(VB.NET\)](#)
[Get Objects in Selection List \(VBA\)](#)

Remarks

To add objects to a selection list without preselecting the objects in the user interface:

1. Call [ISelectionMgr::SuspendSelectionList](#) to suspend the current selection list, preserving its contents and starting a new selection list.
2. To populate a new selection list, call [ISelectionMgr::AddSelectionListObject](#) or [ISelectionMgr::AddSelectionListObjects](#).

NOTE: To add objects in a [selection set](#) to a new selection list, call [ISelectionSet::Select](#).
3. Call [ISelectionMgr::ResumeSelectionList](#) to reinstate the suspended selection list.

To programmatically preselect objects in the user interface and add them to a selection list, use [IModelDocExtension::SelectByID2](#).

[IModelDoc2::ClearSelection2](#) works like ISelectionMgr::SuspendSelectionList to clear the selection list. Unlike IModelDoc2::ClearSelection2, this method preserves the list for future reinstatement.

See Also

[ISelectionMgr Interface](#)
[ISelectionMgr Members](#)

Availability

SOLIDWORKS 2012 FCS, Revision Number 20.0