

SOLIDWORKS API (.NET, VBA, C#) — Reference (281/337): ISldWorks (part 1 of 8)

SOLIDWORKS API Documentation (converted from CHM)

ISldWorks (part 1 of 8) (Type)

ISldWorks Interface

[See Also](#) [Members](#) [Example](#)



[SolidWorks.Interop.sldworks Namespace](#) : ISldWorks Interface

Provides direct and indirect access to all other interfaces exposed in the SOLIDWORKS API.

NOTE: Click the **Members** link, located near the top of the topic, to see this interface's methods and properties.

.NET Syntax

Visual Basic (Declaration)

Public Interface ISldWorks

Visual Basic (Usage)



Dim instance As [ISldWorks](#)

C#

public interface ISldWorks

C++/CLI

public interface class ISldWorks

Visual Basic for Applications (VBA) Syntax

See [SldWorks](#).

Example

[Get Spline Points \(C++\)](#)
[Get Names of Creators of Features \(C++\)](#)
[Traverse Bodies \(C++\)](#)
[Manage Drawing Document Line Styles \(C#\)](#)
[Manage Drawing Document Line Styles \(VB.NET\)](#)
[Manage Drawing Document Line Styles \(VBA\)](#)

Remarks

This interface is the highest-level object in the SOLIDWORKS API. This interface provides a general set of functions that allow application-level operations such as create, open, close, and quit documents, arrange icons and windows, change the active document, and create attribute definitions.

Use CreateObject, GetObject, New, or similar functions to obtain the ISldWorks object from a Dispatch application (Visual Basic or C++ Dispatch). Standalone .exe C++ COM applications can use CoCreateInstance. All of the SOLIDWORKS API add-in wizards automatically create the ISldWorks object for you.

Events are implemented with delegates in the Microsoft .NET Framework. See the [Overview](#) topic for a list of delegates for this interface.

Access Diagram

[SldWorks](#)

See Also

[ISldWorks Members](#)
[SolidWorks.Interop.sldworks Namespace](#)
[IAssemblyDoc Interface](#)
[IDrawingDoc Interface](#)
[IModelDoc2 Interface](#)
[IModelDocExtension Interface](#)
[IPartDoc Interface](#)

ISldWorks Interface Methods

[See Also](#)



[SolidWorks.Interop.sldworks Namespace](#) : ISldWorks Interface

For a list of all members of this type, see [ISldWorks members](#).

Public Methods

Name	Description
 ActivateDoc	Obsolete. Superseded by ISldWorks::ActivateDoc2 and ISldWorks::IActivateDoc3 .
 ActivateDoc2	Obsolete. Superseded by ISldWorks::ActivateDoc3 .
 ActivateDoc3	Activates a loaded document and rebuilds it as specified.
 ActivateTaskPane	Activates the specified task pane.
 AddCallback	Registers a general purpose callback handler.
 AddFileOpenItem	Obsolete. Superseded by ISldWorks::AddFileOpenItem3 .
 AddFileOpenItem2	Obsolete. Superseded by ISldWorks::AddFileOpenItem3 .
 AddFileOpenItem3	Adds file types to the File > Open dialog box.
 AddFileSaveAsItem	Obsolete. Superseded by ISldWorks::AddFileSaveAsItem2 .
 AddFileSaveAsItem2	Adds a file type to the SOLIDWORKS File > Save As dialog box.
 AddItemToThirdPartyPopupMenu	Adds menu items to a pop-up (shortcut) menu in a C++ SOLIDWORKS add-in.
 AddItemToThirdPartyPopupMenu2	Adds menu items to a pop-up (shortcut) menu in a SOLIDWORKS add-in.
 AddMenu	Adds a menu item to a SOLIDWORKS menu for DLL applications.
 AddMenuItem	Obsolete. Superseded by ISldWorks::AddMenuItem3 .
 AddMenuItem2	Obsolete. Superseded by ISldWorks::AddMenuItem3 .
 AddMenuItem3	Obsolete. Superseded by ISldWorks::AddMenuItem4 .
 AddMenuItem4	Obsolete. Superseded by ISldWorks::AddMenuItem5 .
 AddMenuItem5	Adds a menu item and image to the SOLIDWORKS Design user interface.
 AddMenuPopupItem	Obsolete. Superseded by ISldWorks::AddMenuPopupItem2 .
 AddMenuPopupItem2	Obsolete. Superseded by ISldWorks::AddMenuPopupItem3 and ISldWorks::AddMenuPopupItem4 .
 AddMenuPopupItem3	Adds a menu item and zero or more submenus to shortcut menus of entities of the specified type in documents of the specified type.
 AddMenuPopupItem4	Adds a menu item and zero or more submenus to shortcut menus of features of the specified type in documents of the specified type.
 AddToolbar	Obsolete. Superseded by ISldWorks::AddToolbar4 .
 AddToolbar2	Obsolete. Superseded by ISldWorks::AddToolbar4 .
 AddToolbar3	Obsolete. Superseded by ISldWorks::AddToolbar4 .
 AddToolbar4	Obsolete. Superseded by ISldWorks::AddToolbar5 .
 AddToolbar5	Creates a Windows-style dockable toolbar.
 AddToolbarCommand	Obsolete. Superseded by ISldWorks::AddToolbarCommand2 .
 AddToolbarCommand2	Specifies the application functions to call when a toolbar button is clicked or sets a separator.
 AllowFailedFeatureCreation	Sets whether to allow the creation of a feature that has rebuild errors.
 ArrangeIcons	Arranges the icons in SOLIDWORKS.
 ArrangeWindows	Arranges the open windows in SOLIDWORKS.
 BlockSkinning	Blocks skinning a window, which prevents a window from looking like a SOLIDWORKS window.
 CallBack	Allows an out-of-process executable or a SOLIDWORKS macro to call back a function in a SOLIDWORKS add-in DLL.
 CheckpointConvertedDocument	Saves the specified open document if its version is older than the version of the SOLIDWORKS Design product being used.
 CloseAllDocuments	Closes all open documents in the SOLIDWORKS Design session.
 CloseAndReopen	Closes and reopens the specified drawing document without unloading its references from memory.

	CloseAndReopen2	Closes and reopens the specified drawing document without unloading its references from memory.
	CloseDoc	Closes the specified document.
	CloseUserNotification	Closes the specified user notification.
	Command	Opens the specified dialog or file.
	CopyAppearance	Copies the appearance of the specified entity to the clipboard.
	CopyDocument	Copies a document and optionally updates references to it.
	CreateNewWindow	Creates a client window containing the active document.
	CreatePropertyManagerPage	Creates a PropertyManager page.
	CreateTaskpaneView	Obsolete. Superseded by ISldWorks::CreateTaskpaneView2
	CreateTaskpaneView2	Obsolete. Superseded by ISldWorks::CreateTaskpaneView3
	CreateTaskpaneView3	Creates an application-level Task Pane view.
	DateCode	Obsolete. Superseded by ISldWorks::RevisionNumber .
	DefineAttribute	Creates an attribute definition, which is the first step in generating attributes.
	DefineMessageBar	Called by a SOLIDWORKS add-in, creates a message bar definition object.
	DefineUserNotification	Called by a SOLIDWORKS add-in, creates a user notification definition object.
	DisplayStatusBar	Sets whether to display the status bar.
	DocumentVisible	Allows the application to control the display of a document in a window upon creation or retrieval.
	DownloadFromMySolidWorksSettings	Downloads the specified SOLIDWORKS Design connected to the 3DEXPERIENCE platform settings to SOLIDWORKS Design.
	DragToolBarButton	Copies the specified toolbar button from the specified native SOLIDWORKS toolbar or ICommandGroup toolbar to the specified native SOLIDWORKS toolbar or ICommandGroup toolbar.
	DragToolBarButtonFromCommandID	Copies a button to a toolbar using a command ID.
	EnablePhotoWorksProgressiveRender	Obsolete. Not superseded.
	EnableStereoDisplay	Obsolete and not superseded. Functionality no longer implemented.
	EnumDocuments	Obsolete. Superseded by ISldWorks::EnumDocuments2
	EnumDocuments2	Gets a list of documents currently open in the application.
	ExitApp	Shuts down SOLIDWORKS Design.
	ExportHoleWizardItem	Exports data for the specified Hole Wizard standard.
	ExportToolboxItem	Exports data for the specified Toolbox standard.
	Frame	Gets the SOLIDWORKS main frame.
	Get3DExperienceState	Gets the current state of SOLIDWORKS Design connected to the 3DEXPERIENCE platform .
	GetActiveConfigurationName	Gets the name of the active configuration in the specified SOLIDWORKS document.
	GetActiveDisplayPane	Gets the active Display Pane.
	GetAddInObject	Gets an add-in object for the specified SOLIDWORKS add-in.
	GetApplySelectionFilter	Gets the current state of the selection filter.
	GetBatchUploadedFilesInfo	Gets the files uploaded to 3DEXPERIENCE during a batch process.
	GetBuildNumbers	Obsolete. Superseded by ISldWorks::GetBuildNumbers2
	GetBuildNumbers2	Gets the build, major revision, and hot fix numbers of the SOLIDWORKS Design application.
	GetButtonPosition	Gets the center coordinates of the specified SOLIDWORKS toolbar button.
	GetCollisionDetectionManager	Gets the collision detection manager.
	GetColorTable	Gets a color table from the SOLIDWORKS Design application.
	GetCommandID	Gets the SOLIDWORKS command ID for an instance of an add-in's control (e.g., an add-in's toolbar button).
	GetCommandManager	Gets the CommandManager for the specified add-in.
	GetConfigurationCount	Gets the number of configurations in the SOLIDWORKS document, whether the document is opened or closed.
	GetConfigurationNames	Gets the names of the configuration in this SOLIDWORKS Design document, whether the document is opened or closed.

		
	GetCurrentFileUser	Gets the name of the user who has the specified document open.
	GetCurrentLanguage	Gets the current language used by SOLIDWORKS Design.
	GetCurrentLicenseType	Gets the type of license for the current SOLIDWORKS Design session.
	GetCurrentMacroPathFolder	Gets the name of the folder where the macro resides.
	GetCurrentMacroPathName	Gets the path name for the macro currently running.
	GetCurrentWorkingDirectory	Gets the current working directory being used by the SOLIDWORKS Design application.
	GetDataFolder	Gets the data directory name currently used by SOLIDWORKS Design.
	GetDocumentCount	Gets the number of open documents in the current SOLIDWORKS Design session.
	GetDocumentDependencies	Obsolete. Superseded by ISldWorks::GetDocumentDependencies2 .
	GetDocumentDependencies2	Gets all of the model dependencies for a document.
	GetDocumentDependenciesCount	Obsolete. Superseded by ISldWorks::IGetDocumentDependenciesCount2 .
	GetDocuments	Gets the open documents in this SOLIDWORKS Design session.
	GetDocumentTemplate	Gets the name of document template that can be used in ISldWorks::NewDocument or ISldWorks::INewDocument2 .
	GetDocumentVisible	Gets the visibility of the document to open.
	GetEnvironment	Gets the IEnvironment object.
	GetErrorMessage	Gets the last 20 messages issued in the current SOLIDWORKS Design session.
	GetExecutablePath	Gets the path to the SOLIDWORKS Design executable, sldworks.exe .
	GetExportFileData	Gets the data interface for the specified file type to which to export one or more drawing sheets.
	GetFilePLMID	Gets the Product Lifecycle Management (PLM) ID of the specified file stored in 3DEXPERIENCE.
	GetFirstDocument	Gets the document opened first in this SOLIDWORKS Design session.
	GetGtolFormatData	Gets the Gtol format and XML schema versions supported by this version of SOLIDWORKS.
	GetGtolFrameXMLSchema	Gets the XML schema for Gtol frame symbol XML.
	GetHoleStandardsData	Gets the hole standards for the specified hole type.
	GetImageSize	Gets: • small, medium, and large image sizes suitable for the current DPI setting of the display device. • default image size for the current DPI setting of the display device for images that are not based on the SOLIDWORKS icon size setting.
	GetImportFileData	Gets the IGES or DXF/DWG import data for the specified file.
	GetInterfaceBrightnessThemeColors	Gets the theme and colors of the SOLIDWORKS background.
	GetLastSaveError	Gets the last save error issued by Microsoft in the current session.
	GetLastToolBarID	Gets the ID of the last toolbar added to the CommandManager .
	GetLatestSupportedFileVersion	Gets the version number that this instance of SOLIDWORKS reads and writes.
	GetLineStyle	Gets all of the line styles in the specified file.
	GetLocalizedMenuName	Gets a localized menu name for the specified menu ID.
	GetMacroMethods	Gets the names of the modules in the specified macro.
	GetMassProperties	Obsolete. Superseded by ISldWorks::GetMassProperties2 and ISldWorks::IGetMassProperties2 .
	GetMassProperties2	Gets the mass properties from the specified document for the specified configuration.
	GetMaterialDatabaseCount	Gets the number of material databases.
	GetMaterialDatabases	Gets the names of the material databases.
	GetMaterialSchemaPathName	Gets the path for the XML material schema file.
	GetMathUtility	Gets IMathUtility .
	GetMenuStrings	Gets the name of the parent menu of the specified menu command.
	GetModeler	Gets the IModeler interface.
	GetMouseDragMode	Gets whether the specified command-mouse mode is in effect.

		
	GetOpenDocSpec	Gets the specifications to use when opening a model document.
	GetOpenDocument	Gets the open document with the specified name.
	GetOpenDocumentByName	Gets the open document with the specified name.
	GetOpenedFileInfo	Gets the name of the last model successfully opened by SOLIDWORKS and the options that were in effect when it opened.
	GetOpenFileName	Obsolete. Superseded by ISidWorks::GetOpenFileName2 .
	GetOpenFileName2	Prompts the user for the name of the file to open.
	GetPreviewBitmap	Gets the preview bitmap (.bmp) for the specified configuration, regardless if the SOLIDWORKS document is open or closed.
	GetPreviewBitmapFile	Gets the specified preview bitmap of a document and saves it as a Windows bitmap file (.bmp) using the specified filename.
	GetProcessID	Gets the process ID for the current SOLIDWORKS Design session.
	GetRayTraceRenderer	Get a ray-trace rendering engine.
	GetRecentFiles	Gets a list of the most recently used files.
	GetRoutingSettings	Gets routing settings.
	GetRunningCommandInfo	Get a command's ID or PropertyManager page's command ID, title, and whether it is active in the user-interface.
	GetSafeArrayUtility	Gets the ISafeArrayUtility object.
	GetSaveTo3DEXperienceOptions	Initializes save options for a SOLIDWORKS Design connected to the 3DEXPERIENCE platform document.
	GetSearchFolders	Gets the current folder search path as shown in Tools > Options > System Options > File Locations > Show folders for > Referenced Documents .
	GetSelectionFilter	Gets the current selection filter settings for the specified item type.
	GetSelectionFilters	Gets all active selection filters.
	GetSSOFormattedURL	Formats the specified URL for single sign-on.
	GetTemplateSizes	Gets the sheet properties from a template document.
	GetToolBarDock	Obsolete. Superseded by ISidWorks::GetToolBarDock2 .
	GetToolBarDock2	Gets the docking state of the toolbar.
	GetToolBarState	Obsolete. Superseded by ISidWorks::GetToolBarState2 .
	GetToolBarState2	Gets the state of the toolbar.
	GetToolBarVisibility	Gets whether this toolbar is visible.
	GetUserPreferenceDoubleValue	Gets system default user preference values.
	GetUserPreferenceIntegerValue	Gets system default user preference values.
	GetUserPreferenceStringListValue	Gets the name of the DXF mapping file.
	GetUserPreferenceStringValue	Gets system default user preference values.
	GetUserPreferenceToggle	Gets document default user preference values.
	GetUserProgressBar	Gets a progress indicator.
	GetUserTypeLibReferenceCount	Gets the number of user-specified type library references.
	GetUserUnit	Gets an empty IUserUnit object of the specified type.
	HideBubbleTooltip	Hides the bubble ToolTip displayed by ISidWorks::ShowBubbleTooltipA12 .
	HideToolBar	Obsolete. Superseded by ISidWorks::HideToolBar2 .
	HideToolBar2	Hides a toolbar created with ISidWorks::AddToolBar5 .
	IActivateDoc	Obsolete. Superseded by ISidWorks::ActivateDoc2 and ISidWorks::IActivateDoc3 .
	IActivateDoc2	Obsolete. Superseded by ISidWorks::ActivateDoc2 and ISidWorks::IActivateDoc3 .
	IActivateDoc3	Activates a document that has already been loaded. This file becomes the active document, and this method returns a pointer to that document object.
	ICopyDocument	Copies a document and optionally updates references to it.
	ICreatePropertyManagerPage	Creates a PropertyManager page.
	IDefineAttribute	Creates an attribute definition, which is the first step in generating attributes.

		
	IEnableStereoDisplay	Obsolete and not superseded. Functionality no longer implemented.
	IGetColorTable	Gets a color table from the SOLIDWORKS Design application.
	IGetConfigurationNames	Gets the names of the configuration in this SOLIDWORKS document, whether the document is opened or closed.
	IGetDocumentDependencies	Obsolete. Superseded by ISldWorks::IGetDocumentDependencies2 .
	IGetDocumentDependencies2	Gets all of the model dependencies for a document.
	IGetDocumentDependenciesCount2	Gets the size of the array needed for a call to ISldWorks::IGetDocumentDependencies2 .
	IGetDocuments	Gets the open documents in this SOLIDWORKS Design session.
	IGetEnvironment	Gets the IEnvironment object.
	IGetFirstDocument	Obsolete. Superseded by ISldWorks::IGetFirstDocument2 .
	IGetFirstDocument2	Gets the document opened first in this SOLIDWORKS Design session.
	IGetMassProperties	Obsolete. Superseded by ISldWorks::GetMassProperties2 and ISldWorks::IGetMassProperties2 .
	IGetMassProperties2	Gets the mass properties from the specified document for the specified configuration.
	IGetMaterialDatabases	Gets the names of the material databases.
	IGetMathUtility	Gets the IMathUtility interface.
	IGetModeler	Gets the IModeler interface.
	IGetOpenDocumentByName	Obsolete. Superseded by ISldWorks::IGetOpenDocumentByName2 .
	IGetOpenDocumentByName2	Gets the open document with the specified name.
	IGetRayTraceRenderer	Get a ray-trace rendering engine.
	IGetSelectionFilters	Gets all active selection filters.
	IGetSelectionFiltersCount	Gets the number of active selection filters.
	IGetTemplateSizes	Gets the sheet properties from a template document.
	IGetUserTypeLibReferences	Gets the specified user-specified type library references.
	IGetUserUnit	Gets an empty IUserUnit object of the specified type.
	IGetVersionHistoryCount	Gets the size of the array required to hold data returned by ISldWorks::IVersionHistory .
	IMoveDocument	Moves a document and optionally updates references to it.
	ImportHoleWizardItem	Imports data for the specified Hole Wizard standard.
	ImportToolboxItem	Imports data for the specified Toolbox standard.
	INewAssembly	Obsolete. Superseded by ISldWorks::NewDocument and ISldWorks::INewDocument2 .
	INewDocument	Obsolete. Superseded by ISldWorks::INewDocument2 .
	INewDocument2	Creates a new document based on the specified template.
	INewDrawing	Obsolete. Superseded by ISldWorks::NewDocument and ISldWorks::INewDocument2 .
	INewDrawing2	Obsolete. Superseded by ISldWorks::NewDocument and ISldWorks::INewDocument2 .
	INewPart	Obsolete. Superseded by ISldWorks::NewDocument and ISldWorks::INewDocument2 .
	InstallQuickTipGuide	Implements your add-in's copy of the Quick Tips .
	IOpenDoc	Obsolete. Superseded by ISldWorks::OpenDoc6 .
	IOpenDoc2	Obsolete. Superseded by ISldWorks::OpenDoc6 .
	IOpenDoc3	Obsolete. Superseded by ISldWorks::OpenDoc6 .
	IOpenDoc4	Obsolete. Superseded by ISldWorks::OpenDoc6 .
	IOpenDoc5	Obsolete. Superseded by ISldWorks::OpenDoc6 .
	IOpenDocSilent	Obsolete. Superseded by ISldWorks::OpenDoc6 .
	IRemoveUserTypeLibReferences	Removes the user-specified type library references.
	IsBackgroundProcessingCompleted	Gets whether SOLIDWORKS has finished background processing a drawing document that requires a lot of CPU time to open.

		
	IsCommandEnabled	Gets whether the specified command is enabled.
	IsSelectionFilters	Sets the status for multiple selection filters.
	IsUserTypeLibReferences	Sets the user-specified type library references.
	IsRapidDraft	Gets whether the specified drawing file is in SOLIDWORKS Detached format.
	IsSame	Gets whether the two specified objects are the same object.
	IsTaskPaneExpanded	Gets whether the Task Pane is expanded.
	IsTaskPaneVisible	Gets whether the Task Pane is visible.
	IVersionHistory	Gets a list of strings indicating the versions in which a model was saved.
	LoadAddIn	Loads the specified add-in in SOLIDWORKS.
	LoadAdminSettingsFile	Loads the specified *.sldsettings file into SOLIDWORKS Design connected to the 3DEXPERIENCE platform .
	LoadFile	Obsolete. Superseded by ISldWorks::LoadFile4 .
	LoadFile2	Obsolete. Superseded by ISldWorks::LoadFile4 .
	LoadFile3	Obsolete. Superseded by ISldWorks::LoadFile4 .
	LoadFile4	Loads a third-party native CAD file into a new SOLIDWORKS document using 3D Interconnect.
	MoveDocument	Moves a document and optionally updates references to it.
	NewAssembly	Obsolete. Superseded by ISldWorks::NewDocument and ISldWorks::NewDocument2 .
	NewDocument	Creates a new document based on the specified template.
	NewDrawing	Obsolete. Superseded by ISldWorks::NewDocument and ISldWorks::NewDocument2 .
	NewDrawing2	Obsolete. Superseded by ISldWorks::NewDocument and ISldWorks::NewDocument2 .
	NewPart	Obsolete. Superseded by ISldWorks::NewDocument and ISldWorks::NewDocument2 .
	OpenDoc	Obsolete. Superseded by ISldWorks::OpenDoc6 .
	OpenDoc2	Obsolete. Superseded by ISldWorks::OpenDoc6 .
	OpenDoc3	Obsolete. Superseded by ISldWorks::OpenDoc6 .
	OpenDoc4	Obsolete. Superseded by ISldWorks::OpenDoc6 .
	OpenDoc6	Opens an existing document and returns a pointer to the document object.
	OpenDoc7	Opens an existing document and returns a pointer to the document object.
	OpenDocSilent	Obsolete. Superseded by ISldWorks::OpenDoc6 .
	PasteAppearance	Applies to the specified entity an appearance that has been copied to the clipboard.
	PostMessageToApplication	Obsolete. Superseded by ISldWorks::PostMessageToApplicationx64. This method is unsafe to use with 64-bit SOLIDWORKS, i.e. all versions since SOLIDWORKS 2016. The 32-bit integer returned may be too small to contain the 64-bit window handle/pointer, and will be truncated silently. A critical exception will occur sometime later, when the truncated handle/pointer is used. Posts a message to the application that invoked this method.
	PostMessageToApplicationx64	Posts a message to the application that invoked this method in 64-bit applications.
	PreSelectDwgTemplateSize	Establishes which template to use when creating a drawing.
	PresetNewDrawingParameters	Presets the drawing template and sheet size parameters to avoid showing the Sheet Format/Size dialog when creating a new drawing document in the user-interface.
	PreviewDoc	Obsolete. Superseded by ISldWorks::PreviewDocx64. This method is unsafe to use with 64-bit SOLIDWORKS, i.e. all versions since SOLIDWORKS 2016. The 32-bit integer returned may be too small to contain the 64-bit window handle/pointer, and will be truncated silently. A critical exception will occur sometime later, when the truncated handle/pointer is used. Displays a preview of a document to the specified window.
	PreviewDocx64	Displays a preview of a document to the specified window in 64-bit applications.
	QuitDoc	Closes the specified document without saving changes.

		
	RecordLine	Adds a line of code to a VBA macro and the SOLIDWORKS journal file.
	RecordLineCSharp	Adds a line of code to a C# macro and the SOLIDWORKS journal file.
	RecordLineVBNet	Adds a line of code to a VB.NET macro and the SOLIDWORKS journal file.
	RefreshQuickTipWindow	Tells the SOLIDWORKS Design application that your add-in's state has changed and triggers a query for the current URL page.
	RefreshTaskpaneContent	Refreshes the view of the Design Library tab in the Task Pane.
	RegisterThirdPartyPopupMenu	Registers a third-party pop-up (shortcut) menu.
	RegisterTrackingDefinition	Registers a tracking definition.
	RemoveCallback	Unregisters a general purpose callback handler.
	RemoveFileOpenItem	Obsolete. Superseded by ISldWorks.RemoveFileOpenItem2 .
	RemoveFileOpenItem2	Removes a file type from the File > Open dialog box that was added using ISldWorks.AddFileOpenItem3 .
	RemoveFileSaveAsItem	Obsolete. Superseded by ISldWorks.RemoveFileSaveAsItem2 .
	RemoveFileSaveAsItem2	Removes a file type from the File > Save As dialog box that was added using ISldWorks.AddFileSaveAsItem2 .
	RemoveFromMenu	Removes: - the specified command from all main frame menus or a toolbar or both - the specified command's parent menus
	RemoveFromPopupMenu	Removes the specified menu item from one or all specified context-sensitive menus (also called shortcut menus and pop-up menus) for the specified document types.
	RemoveItemFromThirdPartyPopupMenu	Removes a menu item and icon from a third-party pop-up (shortcut) menu.
	RemoveMenu	Removes a menu item from the specified document frame.
	RemoveMenuPopupItem	Obsolete. Superseded by ISldWorks.RemoveMenuPopupItem2 .
	RemoveMenuPopupItem2	Removes an item on a pop-up (shortcut) menu.
	RemoveToolbar	Obsolete. Superseded by ISldWorks.RemoveToolbar2 .
	RemoveToolbar2	Removes a toolbar created with ISldWorks.AddToolbar5 .
	RemoveUserMenu	Obsolete. Superseded by ISldWorks.RemoveMenu .
	RemoveUserTypeLibReferences	Removes the user-specified type library references.
	ReplaceReferencedDocument	Replaces a referenced document.
	ResetPresetDrawingParameters	Resets SOLIDWORKS back to its default behavior after calling ISldWorks.PresetNewDrawingParameters (i.e., display Sheet Format/Size dialog when opening a new drawing document).
	ResetUntitledCount	Resets the index of untitled documents.
	RestoreSettings	Restores the specified SOLIDWORKS settings from the specified *.sldreg file.
	ResumeSkinning	Resumes skinning windows.
	RevisionNumber	Gets the version number of this SOLIDWORKS Design installation.
	RunAttachedMacro	Runs the specified attached macro, module, and procedure.
	RunBatchSaveProcess	Batch saves files to 3DEXPERIENCE.
	RunCommand	Runs the specified SOLIDWORKS command.
	RunJournalCmd	Do not use.
	RunMacro	Obsolete. Superseded by ISldWorks.RunMacro2 .
	RunMacro2	Runs a macro from a project file.
	SaveSettings	Saves the specified SOLIDWORKS settings to the specified *.sldreg file.
	SendMsgToUser	Obsolete. Superseded by ISldWorks.SendMsgToUser2 .
	SendMsgToUser2	Displays a message box containing a message to the user, who is required to interact with it before continuing.
	SetAddinCallbackInfo	Obsolete. Superseded by ISldWorks.SetAddinCallbackInfo2 .
	SetAddinCallbackInfo2	Sets add-in callback commands.
	SetApplySelectionFilter	Sets the current state of the selection filter.

	SetCurrentWorkingDirectory	Sets the current working directory to be used by SOLIDWORKS.
	SetMissingReferencePathName	Sets the missing reference file name. Use with the SOLIDWORKS event ReferenceNotFoundNotify .
	SetMouseDragMode	Sets the command-mouse mode.
	SetMultipleFileNamesPrompt	Sets the new filenames to open in response to the ISldWorks PromptForMultipleFileNamesNotify event.
	SetNewFilename	Sets the name of the new SOLIDWORKS file.
	SetPromptFilename	Obsolete. Superseded by ISldWorks::SetPromptFilename2
	SetPromptFilename2	Sets the file to open in response to a SOLIDWORKS event.
	SetSearchFolders	Sets the current folder search path as shown in Tools > Options > System Options > File Locations > Show folders for > Referenced Documents .
	SetSelectionFilter	Sets the current selection filter values for the specified item type.
	SetSelectionFilters	Sets the status for multiple selection filters.
	SetThirdPartyPopupMenuState	Sets whether to show or hide a third-party popup (shortcut) menu.
	SetToolbarDock	Obsolete. Superseded by ISldWorks::SetToolbarDock2
	SetToolbarDock2	Sets the docking state of the toolbar.
	SetToolbarVisibility	Sets whether the specified toolbar is visible.
	SetUserPreferenceDoubleValue	Sets system default user preference values.
	SetUserPreferenceIntegerValue	Sets system default user preference values.
	SetUserPreferenceStringListValue	Sets the name of the DXF mapping files.
	SetUserPreferenceStringValue	Sets system default user preference values.
	SetUserPreferenceToggle	Sets system default user preference values.
	ShowBatchSaveTo3DEXperienceDlg	Opens a dialog to save files in the specified folder to 3DEXPERIENCE.
	ShowBubbleToolTip	Displays a bubble ToolTip and flashes the specified toolbar button.
	ShowBubbleToolTipAt	Obsolete. Superseded by ISldWorks::ShowBubbleToolTipAt2
	ShowBubbleToolTipAt2	Displays a bubble ToolTip at the specified location.
	ShowHelp	Displays the specified Help topic.
	ShowThirdPartyPopupMenu	Sets where to show a third-party pop-up (shortcut) menu.
	ShowToolbar	Obsolete. Superseded by ISldWorks::ShowToolbar2
	ShowToolbar2	Obsolete. Not superseded.
	ShowUserNotification	Shows the specified user notification for a SOLIDWORKS add-in.
	SolidWorksExplorer	Starts SOLIDWORKS Explorer.
	UninstallQuickTipGuide	Uninstalls your add-in's Quick Tips
	UnloadAddIn	Unloads the specified add-in from SOLIDWORKS.
	UploadToMySolidWorksSettings	Uploads the specified SOLIDWORKS Design settings to SOLIDWORKS Design connected to the 3DEXPERIENCE platform .
	VersionHistory	Gets a list of strings indicating the versions in which a model was saved.

[Top](#)

 See Also

- [ISldWorks Interface](#)
- [SolidWorks.Interop.sldworks Namespace](#)
- [IAssemblyDoc Interface](#)
- [IDrawingDoc Interface](#)
- [IModelDoc2 Interface](#)
- [IModelDocExtension Interface](#)
- [IPartDoc Interface](#)

ISldWorks Interface Members

[See Also](#) [Properties](#) [Methods](#)



[SolidWorks.Interop.sldworks Namespace](#) : ISldWorks Interface

The following tables list the members exposed by [ISldWorks](#).

Public Properties

Name	Description
 ActiveDoc	Gets the currently active document.
 ActivePrinter	Obsolete. Superseded by IModelDoc2::Printer .
 ApplicationType	Gets the type of this SOLIDWORKS application.
 CommandInProgress	Improves performance of out-of-process applications by informing SOLIDWORKS that a sequence of API calls will be made by the out-of-process application.
 EnableBackgroundProcessing	Gets or sets whether to enable background processing.
 EnableFileMenu	Gets or sets whether to enable file-related menus and toolbars.
 FrameHeight	Get or sets the height of the SOLIDWORKS window.
 FrameLeft	Gets or sets the left position of the SOLIDWORKS window.
 FrameState	Gets or sets the window state (minimum, maximum, or normal) for the SOLIDWORKS window.
 FrameTop	Gets or sets the top position of the SOLIDWORKS window.
 FrameWidth	Gets or sets the width of the frame of the SOLIDWORKS window.
 IActiveDoc	Obsolete. Superseded by ISldWorks::IActiveDoc2 .
 IActiveDoc2	Gets the currently active document.
 ShadedEdgeThickness	Gets or sets the edge thickness when the display style is "Shaded with Edges".
 StartupProcessCompleted	Gets whether the SOLIDWORKS startup process, including loading all startup add-ins, has completed.
 TaskPanelsPinned	Gets or sets whether the SOLIDWORKS Task Pane is pinned.
 UserControl	Gets and sets whether the user has control over the application.
 UserControlBackground	Gets and sets whether the user has control over the application.
 UserTypeLibReferences	Gets and sets the user-specified type library references.
 Visible	Gets and sets the visibility property of the SOLIDWORKS Design application.

[Top](#)

Public Methods

Name	Description
 ActivateDoc	Obsolete. Superseded by ISldWorks::ActivateDoc2 and ISldWorks::IActiveDoc3 .
 ActivateDoc2	Obsolete. Superseded by ISldWorks::ActivateDoc3 .
 ActivateDoc3	Activates a loaded document and rebuilds it as specified.
 ActivateTaskPane	Activates the specified task pane.
 AddCallback	Registers a general purpose callback handler.
 AddFileOpenItem	Obsolete. Superseded by ISldWorks::AddFileOpenItem3 .
 AddFileOpenItem2	Obsolete. Superseded by ISldWorks::AddFileOpenItem3 .
 AddFileOpenItem3	Adds file types to the File > Open dialog box.
 AddFileSaveAsItem	Obsolete. Superseded by ISldWorks::AddFileSaveAsItem2 .
 AddFileSaveAsItem2	Adds a file type to the SOLIDWORKS File > Save As dialog box.
 AddItemToThirdPartyPopupMenu	Adds menu items to a pop-up (shortcut) menu in a C++ SOLIDWORKS add-in.
 AddItemToThirdPartyPopupMenu2	Adds menu items to a pop-up (shortcut) menu in a SOLIDWORKS add-in.
 AddMenu	Adds a menu item to a SOLIDWORKS menu for DLL applications.
 AddMenuItem	Obsolete. Superseded by ISldWorks::AddMenuItem3 .
 AddMenuItem2	Obsolete. Superseded by ISldWorks::AddMenuItem3 .
 AddMenuItem3	Obsolete. Superseded by ISldWorks::AddMenuItem4 .

		
	AddMenuItem4	Obsolete. Superseded by ISldWorks:AddMenuItem5 .
	AddMenuItem5	Adds a menu item and image to the SOLIDWORKS Design user interface.
	AddMenuPopUpItem	Obsolete. Superseded by ISldWorks:AddMenuPopUpItem2 .
	AddMenuPopUpItem2	Obsolete. Superseded by ISldWorks:AddMenuPopUpItem3 and ISldWorks:AddMenuPopUpItem4 .
	AddMenuPopUpItem3	Adds a menu item and zero or more submenus to shortcut menus of entities of the specified type in documents of the specified type.
	AddMenuPopUpItem4	Adds a menu item and zero or more submenus to shortcut menus of features of the specified type in documents of the specified type.
	AddToolBar	Obsolete. Superseded by ISldWorks:AddToolBar4 .
	AddToolBar2	Obsolete. Superseded by ISldWorks:AddToolBar4 .
	AddToolBar3	Obsolete. Superseded by ISldWorks:AddToolBar4 .
	AddToolBar4	Obsolete. Superseded by ISldWorks:AddToolBar5 .
	AddToolBar5	Creates a Windows-style dockable toolbar.
	AddToolBarCommand	Obsolete. Superseded by ISldWorks:AddToolBarCommand2 .
	AddToolBarCommand2	Specifies the application functions to call when a toolbar button is clicked or sets a separator.
	AllowFailedFeatureCreation	Sets whether to allow the creation of a feature that has rebuild errors.
	ArrangeIcons	Arranges the icons in SOLIDWORKS.
	ArrangeWindows	Arranges the open windows in SOLIDWORKS.
	BlockSkinning	Blocks skinning a window, which prevents a window from looking like a SOLIDWORKS window.
	CallBack	Allows an out-of-process executable or a SOLIDWORKS macro to call back a function in a SOLIDWORKS add-in DLL.
	CheckpointConvertedDocument	Saves the specified open document if its version is older than the version of the SOLIDWORKS Design product being used.
	CloseAllDocuments	Closes all open documents in the SOLIDWORKS Design session.
	CloseAndReopen	Closes and reopens the specified drawing document without unloading its references from memory.
	CloseAndReopen2	Closes and reopens the specified drawing document without unloading its references from memory.
	CloseDoc	Closes the specified document.
	CloseUserNotification	Closes the specified user notification.
	Command	Opens the specified dialog or file.
	CopyAppearance	Copies the appearance of the specified entity to the clipboard.
	CopyDocument	Copies a document and optionally updates references to it.
	CreateNewWindow	Creates a client window containing the active document.
	CreatePropertyManagerPage	Creates a PropertyManager page.
	CreateTaskpaneView	Obsolete. Superseded by ISldworks:CreateTaskpaneView2 .
	CreateTaskpaneView2	Obsolete. Superseded by ISldworks:CreateTaskpaneView3 .
	CreateTaskpaneView3	Creates an application-level Task Pane view.
	DateCode	Obsolete. Superseded by ISldWorks:RevisionNumber .
	DefineAttribute	Creates an attribute definition, which is the first step in generating attributes.
	DefineMessageBar	Called by a SOLIDWORKS add-in, creates a message bar definition object.
	DefineUserNotification	Called by a SOLIDWORKS add-in, creates a user notification definition object.
	DisplayStatusBar	Sets whether to display the status bar.
	DocumentVisible	Allows the application to control the display of a document in a window upon creation or retrieval.
	DownloadFromMySolidWorksSettings	Downloads the specified SOLIDWORKS Design connected to the 3DEXPERIENCE platform settings to SOLIDWORKS Design.
	DragToolBarButton	Copies the specified toolbar button from the specified native SOLIDWORKS toolbar or ICommandGroup toolbar to the specified native SOLIDWORKS toolbar or ICommandGroup toolbar.
	DragToolBarButtonFromCommandID	Copies a button to a toolbar using a command ID.
	EnablePhotoWorksProgressiveRender	Obsolete. Not superseded.

		
	EnableStereoDisplay	Obsolete and not superseded. Functionality no longer implemented.
	EnumDocuments	Obsolete. Superseded by ISldWorks::EnumDocuments2 .
	EnumDocuments2	Gets a list of documents currently open in the application.
	ExitApp	Shuts down SOLIDWORKS Design.
	ExportHoleWizardItem	Exports data for the specified Hole Wizard standard.
	ExportToolboxItem	Exports data for the specified Toolbox standard.
	Frame	Gets the SOLIDWORKS main frame.
	Get3DEXperienceState	Gets the current state of SOLIDWORKS Design connected to the 3DEXPERIENCE platform .
	GetActiveConfigurationName	Gets the name of the active configuration in the specified SOLIDWORKS document.
	GetActiveDisplayPane	Gets the active Display Pane.
	GetAddInObject	Gets an add-in object for the specified SOLIDWORKS add-in.
	GetApplySelectionFilter	Gets the current state of the selection filter.
	GetBatchUploadedFilesInfo	Gets the files uploaded to 3DEXPERIENCE during a batch process.
	GetBuildNumbers	Obsolete. Superseded by ISldWorks::GetBuildNumbers2 .
	GetBuildNumbers2	Gets the build, major revision, and hot fix numbers of the SOLIDWORKS Design application.
	GetButtonPosition	Gets the center coordinates of the specified SOLIDWORKS toolbar button.
	GetCollisionDetectionManager	Gets the collision detection manager.
	GetColorTable	Gets a color table from the SOLIDWORKS Design application.
	GetCommandID	Gets the SOLIDWORKS command ID for an instance of an add-in's control (e.g., an add-in's toolbar button).
	GetCommandManager	Gets the CommandManager for the specified add-in.
	GetConfigurationCount	Gets the number of configurations in the SOLIDWORKS document, whether the document is opened or closed.
	GetConfigurationNames	Gets the names of the configuration in this SOLIDWORKS Design document, whether the document is opened or closed.
	GetCurrentFileUser	Gets the name of the user who has the the specified document open.
	GetCurrentLanguage	Gets the current language used by SOLIDWORKS Design.
	GetCurrentLicenseType	Gets the type of license for the current SOLIDWORKS Design session.
	GetCurrentMacroPathFolder	Gets the name of the folder where the macro resides.
	GetCurrentMacroPathName	Gets the path name for the macro currently running.
	GetCurrentWorkingDirectory	Gets the current working directory being used by the SOLIDWORKS Design application.
	GetDataFolder	Gets the data directory name currently used by SOLIDWORKS Design.
	GetDocumentCount	Gets the number of open documents in the current SOLIDWORKS Design session.
	GetDocumentDependencies	Obsolete. Superseded by ISldWorks::GetDocumentDependencies2 .
	GetDocumentDependencies2	Gets all of the model dependencies for a document.
	GetDocumentDependenciesCount	Obsolete. Superseded by ISldWorks::GetDocumentDependenciesCount2 .
	GetDocuments	Gets the open documents in this SOLIDWORKS Design session.
	GetDocumentTemplate	Gets the name of document template that can be used in ISldWorks::NewDocument or ISldWorks::INewDocument2 .
	GetDocumentVisible	Gets the visibility of the document to open.
	GetEnvironment	Gets the IEnvironment object.
	GetErrorMessage	Gets the last 20 messages issued in the current SOLIDWORKS Design session.
	GetExecutablePath	Gets the path to the SOLIDWORKS Design executable, sldworks.exe .
	GetExportFileData	Gets the data interface for the specified file type to which to export one or more drawing sheets.
	GetFilePLMID	Gets the Product Lifecycle Management (PLM) ID of the specified file stored in 3DEXPERIENCE.
	GetFirstDocument	Gets the document opened first in this SOLIDWORKS Design session.

		
	GetGtolFormatData	Gets the Gtol format and XML schema versions supported by this version of SOLIDWORKS.
	GetGtolFrameXMLSchema	Gets the XML schema for Gtol frame symbol XML.
	GetHoleStandardsData	Gets the hole standards for the specified hole type.
	GetImageSize	Gets: • small, medium, and large image sizes suitable for the current DPI setting of the display device. • default image size for the current DPI setting of the display device for images that are not based on the SOLIDWORKS icon size setting.
	GetImportFileData	Gets the IGES or DXF/DWG import data for the specified file.
	GetInterfaceBrightnessThemeColors	Gets the theme and colors of the SOLIDWORKS background.
	GetLastSaveError	Gets the last save error issued by Microsoft in the current session.
	GetLastToolbarID	Gets the ID of the last toolbar added to the CommandManager .
	GetLatestSupportedFileVersion	Gets the version number that this instance of SOLIDWORKS reads and writes.
	GetLineStyle	Gets all of the line styles in the specified file.
	GetLocalizedMenuName	Gets a localized menu name for the specified menu ID.
	GetMacroMethods	Gets the names of the modules in the specified macro.
	GetMassProperties	Obsolete. Superseded by ISldWorks::GetMassProperties2 and ISldWorks::IGetMassProperties2
	GetMassProperties2	Gets the mass properties from the specified document for the specified configuration.
	GetMaterialDatabaseCount	Gets the number of material databases.
	GetMaterialDatabases	Gets the names of the material databases.
	GetMaterialSchemaPathName	Gets the path for the XML material schema file.
	GetMathUtility	Gets IMathUtility .
	GetMenuStrings	Gets the name of the parent menu of the specified menu command.
	GetModeler	Gets the IModeler interface.
	GetMouseDragMode	Gets whether the specified command-mouse mode is in effect.
	GetOpenDocSpec	Gets the specifications to use when opening a model document.
	GetOpenDocument	Gets the open document with the specified name.
	GetOpenDocumentByName	Gets the open document with the specified name.
	GetOpenedFileInfo	Gets the name of the last model successfully opened by SOLIDWORKS and the options that were in effect when it opened.
	GetOpenFileName	Obsolete. Superseded by ISldWorks::GetOpenFileName2 .
	GetOpenFileName2	Prompts the user for the name of the file to open.
	GetPreviewBitmap	Gets the preview bitmap (.bmp) for the specified configuration, regardless if the SOLIDWORKS document is open or closed.
	GetPreviewBitmapFile	Gets the specified preview bitmap of a document and saves it as a Windows bitmap file (.bmp) using the specified filename.
	GetProcessID	Gets the process ID for the current SOLIDWORKS Design session.
	GetRayTraceRenderer	Get a ray-trace rendering engine.
	GetRecentFiles	Gets a list of the most recently used files.
	GetRoutingSettings	Gets routing settings.
	GetRunningCommandInfo	Get a command's ID or PropertyManager page's command ID, title, and whether it is active in the user-interface.
	GetSafeArrayUtility	Gets the ISafeArrayUtility object.
	GetSaveTo3DEXperienceOptions	Initializes save options for a SOLIDWORKS Design connected to the 3DEXPERIENCE platform document.
	GetSearchFolders	Gets the current folder search path as shown in Tools > Options > System Options > File Locations > Show folders for > Referenced Documents .
	GetSelectionFilter	Gets the current selection filter settings for the specified item type.
	GetSelectionFilters	Gets all active selection filters.
	GetSSOFormattedURL	Formats the specified URL for single sign-on.
	GetTemplateSizes	Gets the sheet properties from a template document.

		
	GetToolBarDock	Obsolete. Superseded by ISldWorks::GetToolBarDock2 .
	GetToolBarDock2	Gets the docking state of the toolbar.
	GetToolBarState	Obsolete. Superseded by ISldWorks::GetToolBarState2 .
	GetToolBarState2	Gets the state of the toolbar.
	GetToolBarVisibility	Gets whether this toolbar is visible.
	GetUserPreferenceDoubleValue	Gets system default user preference values.
	GetUserPreferenceIntegerValue	Gets system default user preference values.
	GetUserPreferenceStringListValue	Gets the name of the DXF mapping file.
	GetUserPreferenceStringValue	Gets system default user preference values.
	GetUserPreferenceToggle	Gets document default user preference values.
	GetUserProgressBar	Gets a progress indicator.
	GetUserTypeLibReferenceCount	Gets the number of user-specified type library references.
	GetUserUnit	Gets an empty IUserUnit object of the specified type.
	HideBubbleTooltip	Hides the bubble ToolTip displayed by ISldWorks::ShowBubbleTooltipAt2 .
	HideToolBar	Obsolete. Superseded by ISldWorks::HideToolBar2 .
	HideToolBar2	Hides a toolbar created with ISldWorks::AddToolBar5 .
	IActivateDoc	Obsolete. Superseded by ISldWorks::ActivateDoc2 and ISldWorks::IActivateDoc3 .
	IActivateDoc2	Obsolete. Superseded by ISldWorks::ActivateDoc2 and ISldWorks::IActivateDoc3 .
	IActivateDoc3	Activates a document that has already been loaded. This file becomes the active document, and this method returns a pointer to that document object.
	ICopyDocument	Copies a document and optionally updates references to it.
	ICreatePropertyManagerPage	Creates a PropertyManager page.
	IDefineAttribute	Creates an attribute definition, which is the first step in generating attributes.
	IEnableStereoDisplay	Obsolete and not superseded. Functionality no longer implemented.
	IGetColorTable	Gets a color table from the SOLIDWORKS Design application.
	IGetConfigurationNames	Gets the names of the configuration in this SOLIDWORKS document, whether the document is opened or closed.
	IGetDocumentDependencies	Obsolete. Superseded by ISldWorks::IGetDocumentDependencies2 .
	IGetDocumentDependencies2	Gets all of the model dependencies for a document.
	IGetDocumentDependenciesCount2	Gets the size of the array needed for a call to ISldWorks::IGetDocumentDependencies2 .
	IGetDocuments	Gets the open documents in this SOLIDWORKS Design session.
	IGetEnvironment	Gets the IEnvironment object.
	IGetFirstDocument	Obsolete. Superseded by ISldWorks::IGetFirstDocument2 .
	IGetFirstDocument2	Gets the document opened first in this SOLIDWORKS Design session.
	IGetMassProperties	Obsolete. Superseded by ISldWorks::GetMassProperties2 and ISldWorks::IGetMassProperties2 .
	IGetMassProperties2	Gets the mass properties from the specified document for the specified configuration.
	IGetMaterialDatabases	Gets the names of the material databases.
	IGetMathUtility	Gets the IMathUtility interface.
	IGetModeler	Gets the IModeler interface.
	IGetOpenDocumentByName	Obsolete. Superseded ISldWorks::IGetOpenDocumentByName2 .
	IGetOpenDocumentByName2	Gets the open document with the specified name.
	IGetRayTraceRenderer	Get a ray-trace rendering engine.
	IGetSelectionFilters	Gets all active selection filters.
	IGetSelectionFiltersCount	Gets the number of active selection filters.

		
	IGetTemplateSizes	Gets the sheet properties from a template document.
	IGetUserTypeLibReferences	Gets the specified user-specified type library references.
	IGetUserUnit	Gets an empty IUserUnit object of the specified type.
	IGetVersionHistoryCount	Gets the size of the array required to hold data returned by ISldWorks::IVersionHistory .
	IMoveDocument	Moves a document and optionally updates references to it.
	ImportHoleWizardItem	Imports data for the specified Hole Wizard standard.
	ImportToolboxItem	Imports data for the specified Toolbox standard.
	INewAssembly	Obsolete. Superseded by ISldWorks::NewDocument and ISldWorks::NewDocument2 .
	INewDocument	Obsolete. Superseded by ISldWorks::NewDocument2 .
	INewDocument2	Creates a new document based on the specified template.
	INewDrawing	Obsolete. Superseded by ISldWorks::NewDocument and ISldWorks::NewDocument2 .
	INewDrawing2	Obsolete. Superseded by ISldWorks::NewDocument and ISldWorks::NewDocument2 .
	INewPart	Obsolete. Superseded by ISldWorks::NewDocument and ISldWorks::NewDocument2 .
	InstallQuickTipGuide	Implements your add-in's copy of the Quick Tips .
	IOpenDoc	Obsolete. Superseded by ISldWorks::OpenDoc6 .
	IOpenDoc2	Obsolete. Superseded by ISldWorks::OpenDoc6 .
	IOpenDoc3	Obsolete. Superseded by ISldWorks::OpenDoc6 .
	IOpenDoc4	Obsolete. Superseded by ISldWorks::OpenDoc6 .
	IOpenDoc5	Obsolete. Superseded by ISldWorks::OpenDoc6 .
	IOpenDocSilent	Obsolete. Superseded by ISldWorks::OpenDoc6 .
	IRemoveUserTypeLibReferences	Removes the user-specified type library references.
	IsBackgroundProcessingCompleted	Gets whether SOLIDWORKS has finished background processing a drawing document that requires a lot of CPU time to open.
	IsCommandEnabled	Gets whether the specified command is enabled.
	ISetSelectionFilters	Sets the status for multiple selection filters.
	ISetUserTypeLibReferences	Sets the user-specified type library references.
	IsRapidDraft	Gets whether the specified drawing file is in SOLIDWORKS Detached format.
	IsSame	Gets whether the two specified objects are the same object.
	IsTaskPaneExpanded	Gets whether the Task Pane is expanded.
	IsTaskPaneVisible	Gets whether the Task Pane is visible.
	IVersionHistory	Gets a list of strings indicating the versions in which a model was saved.
	LoadAddIn	Loads the specified add-in in SOLIDWORKS.
	LoadAdminSettingsFile	Loads the specified *.sldsettings file into SOLIDWORKS Design connected to the 3DEXPERIENCE platform .
	LoadFile	Obsolete. Superseded by ISldWorks::LoadFile4 .
	LoadFile2	Obsolete. Superseded by ISldWorks::LoadFile4 .
	LoadFile3	Obsolete. Superseded by ISldWorks::LoadFile4 .
	LoadFile4	Loads a third-party native CAD file into a new SOLIDWORKS document using 3D Interconnect.
	MoveDocument	Moves a document and optionally updates references to it.
	NewAssembly	Obsolete. Superseded by ISldWorks::NewDocument and ISldWorks::NewDocument2 .
	NewDocument	Creates a new document based on the specified template.
	NewDrawing	Obsolete. Superseded by ISldWorks::NewDocument and ISldWorks::NewDocument2 .
	NewDrawing2	Obsolete. Superseded by ISldWorks::NewDocument and ISldWorks::NewDocument2 .
	NewPart	Obsolete. Superseded by ISldWorks::NewDocument and ISldWorks::NewDocument2 .

		
	OpenDoc	Obsolete. Superseded by ISldWorks::OpenDoc6 .
	OpenDoc2	Obsolete. Superseded by ISldWorks::OpenDoc6 .
	OpenDoc3	Obsolete. Superseded by ISldWorks::OpenDoc6 .
	OpenDoc4	Obsolete. Superseded by ISldWorks::OpenDoc6 .
	OpenDoc6	Opens an existing document and returns a pointer to the document object.
	OpenDoc7	Opens an existing document and returns a pointer to the document object.
	OpenDocSilent	Obsolete. Superseded by ISldWorks::OpenDoc6 .
	PasteAppearance	Applies to the specified entity an appearance that has been copied to the clipboard.
	PostMessageToApplication	Obsolete. Superseded by ISldWorks::PostMessageToApplicationx64. This method is unsafe to use with 64-bit SOLIDWORKS, i.e. all versions since SOLIDWORKS 2016. The 32-bit integer returned may be too small to contain the 64-bit window handle/pointer, and will be truncated silently. A critical exception will occur sometime later, when the truncated handle/pointer is used. Posts a message to the application that invoked this method.
	PostMessageToApplicationx64	Posts a message to the application that invoked this method in 64-bit applications.
	PreSelectDwgTemplateSize	Establishes which template to use when creating a drawing.
	PresetNewDrawingParameters	Presets the drawing template and sheet size parameters to avoid showing the Sheet Format/Size dialog when creating a new drawing document in the user-interface.
	PreviewDoc	Obsolete. Superseded by ISldWorks::PreviewDocx64. This method is unsafe to use with 64-bit SOLIDWORKS, i.e. all versions since SOLIDWORKS 2016. The 32-bit integer returned may be too small to contain the 64-bit window handle/pointer, and will be truncated silently. A critical exception will occur sometime later, when the truncated handle/pointer is used. Displays a preview of a document to the specified window.
	PreviewDocx64	Displays a preview of a document to the specified window in 64-bit applications.
	QuitDoc	Closes the specified document without saving changes.
	RecordLine	Adds a line of code to a VBA macro and the SOLIDWORKS journal file.
	RecordLineCSharp	Adds a line of code to a C# macro and the SOLIDWORKS journal file.
	RecordLineVBnet	Adds a line of code to a VB.NET macro and the SOLIDWORKS journal file.
	RefreshQuickTipWindow	Tells the SOLIDWORKS Design application that your add-in's state has changed and triggers a query for the current URL page.
	RefreshTaskpaneContent	Refreshes the view of the Design Library tab in the Task Pane.
	RegisterThirdPartyPopupMenu	Registers a third-party pop-up (shortcut) menu.
	RegisterTrackingDefinition	Registers a tracking definition.
	RemoveCallback	Unregisters a general purpose callback handler.
	RemoveFileOpenItem	Obsolete. Superseded by ISldWorks::RemoveFileOpenItem2 .
	RemoveFileOpenItem2	Removes a file type from the File > Open dialog box that was added using ISldWorks::AddFileOpenItem3 .
	RemoveFileSaveAsItem	Obsolete. Superseded by ISldWorks::RemoveFileSaveAsItem2 .
	RemoveFileSaveAsItem2	Removes a file type from the File > Save As dialog box that was added using ISldWorks::AddFileSaveAsItem2 .
	RemoveFromMenu	Removes: - the specified command from all main frame menus or a toolbar or both - the specified command's parent menus
	RemoveFromPopupMenu	Removes the specified menu item from one or all specified context-sensitive menus (also called shortcut menus and pop-up menus) for the specified document types.
	RemoveItemFromThirdPartyPopupMenu	Removes a menu item and icon from a third-party pop-up (shortcut) menu.
	RemoveMenu	Removes a menu item from the specified document frame.
	RemoveMenuPopupItem	Obsolete. Superseded by ISldWorks::RemoveMenuPopupItem2 .
	RemoveMenuPopupItem2	Removes an item on a pop-up (shortcut) menu.

	RemoveToolBar	Obsolete. Superseded by ISldWorks::RemoveToolBar2 .
	RemoveToolBar2	Removes a toolbar created with ISldWorks::AddToolBar5 .
	RemoveUserMenu	Obsolete. Superseded by ISldWorks::RemoveMenu .
	RemoveUserTypeLibReferences	Removes the user-specified type library references.
	ReplaceReferencedDocument	Replaces a referenced document.
	ResetPresetDrawingParameters	Resets SOLIDWORKS back to its default behavior after calling ISldWorks::PresetNewDrawingParameters (i.e., display Sheet Format/Size dialog when opening a new drawing document).
	ResetUntitledCount	Resets the index of untitled documents.
	RestoreSettings	Restores the specified SOLIDWORKS settings from the specified *.sldreg file.
	ResumeSkinning	Resumes skinning windows.
	RevisionNumber	Gets the version number of this SOLIDWORKS Design installation.
	RunAttachedMacro	Runs the specified attached macro, module, and procedure.
	RunBatchSaveProcess	Batch saves files to 3DEXPERIENCE.
	RunCommand	Runs the specified SOLIDWORKS command.
	RunJournalCmd	Do not use.
	RunMacro	Obsolete. Superseded by ISldWorks::RunMacro2 .
	RunMacro2	Runs a macro from a project file.
	SaveSettings	Saves the specified SOLIDWORKS settings to the specified *.sldreg file.
	SendMsgToUser	Obsolete. Superseded by ISldWorks::SendMsgToUser2 .
	SendMsgToUser2	Displays a message box containing a message to the user, who is required to interact with it before continuing.
	SetAddinCallbackInfo	Obsolete. Superseded by ISldWorks::SetAddinCallbackInfo2 .
	SetAddinCallbackInfo2	Sets add-in callback commands.
	SetApplySelectionFilter	Sets the current state of the selection filter.
	SetCurrentWorkingDirectory	Sets the current working directory to be used by SOLIDWORKS.
	SetMissingReferencePathName	Sets the missing reference file name. Use with the SOLIDWORKS event ReferenceNotFoundNotify .
	SetMouseDragMode	Sets the command-mouse mode.
	SetMultipleFileNamesPrompt	Sets the new filenames to open in response to the ISldWorks::PromptForMultipleFileNamesNotify event.
	SetNewFilename	Sets the name of the new SOLIDWORKS file.
	SetPromptFilename	Obsolete. Superseded by ISldWorks::SetPromptFilename2 .
	SetPromptFilename2	Sets the file to open in response to a SOLIDWORKS event.
	SetSearchFolders	Sets the current folder search path as shown in Tools > Options > System Options > File Locations > Show folders for > Referenced Documents .
	SetSelectionFilter	Sets the current selection filter values for the specified item type.
	SetSelectionFilters	Sets the status for multiple selection filters.
	SetThirdPartyPopupMenuState	Sets whether to show or hide a third-party popup (shortcut) menu.
	SetToolBarDock	Obsolete. Superseded by ISldWorks::SetToolBarDock2 .
	SetToolBarDock2	Sets the docking state of the toolbar.
	SetToolBarVisibility	Sets whether the specified toolbar is visible.
	SetUserPreferenceDoubleValue	Sets system default user preference values.
	SetUserPreferenceIntegerValue	Sets system default user preference values.
	SetUserPreferenceStringListValue	Sets the name of the DXF mapping files.
	SetUserPreferenceStringValue	Sets system default user preference values.
	SetUserPreferenceToggle	Sets system default user preference values.
	ShowBatchSaveTo3DEXperienceDlg	Opens a dialog to save files in the specified folder to 3DEXPERIENCE.
	ShowBubbleToolTip	Displays a bubble ToolTip and flashes the specified toolbar button.

		
	ShowBubbleToolTipAt	Obsolete. Superseded by ISldWorks.ShowBubbleToolTipAt2
	ShowBubbleToolTipAt2	Displays a bubble ToolTip at the specified location.
	ShowHelp	Displays the specified Help topic.
	ShowThirdPartyPopUpMenu	Sets where to show a third-party pop-up (shortcut) menu.
	ShowToolbar	Obsolete. Superseded by ISldWorks.ShowToolbar2
	ShowToolbar2	Obsolete. Not superseded.
	ShowUserNotification	Shows the specified user notification for a SOLIDWORKS add-in.
	SolidWorksExplorer	Starts SOLIDWORKS Explorer.
	UninstallQuickTipGuide	Uninstalls your add-in's Quick Tips
	UnloadAddIn	Unloads the specified add-in from SOLIDWORKS.
	UploadToMySolidWorksSettings	Uploads the specified SOLIDWORKS Design settings to SOLIDWORKS Design connected to the 3DEXPERIENCE platform .
	VersionHistory	Gets a list of strings indicating the versions in which a model was saved.

[Top](#)

See Also

[ISldWorks Interface](#)
[SolidWorks.Interop.sldworks Namespace](#)
[IAssemblyDoc Interface](#)
[IDrawingDoc Interface](#)
[IModelDoc2 Interface](#)
[IModelDocExtension Interface](#)
[IPartDoc Interface](#)

SOLIDWORKS API Help

[Send comments on this topic.](#)

ISldWorks Interface Properties

[See Also](#)

[SolidWorks.Interop.sldworks Namespace](#) : ISldWorks Interface

For a list of all members of this type, see [ISldWorks members](#).

Public Properties

Name	Description
 ActiveDoc	Gets the currently active document.
 ActivePrinter	Obsolete. Superseded by IModelDoc2.Printer
 ApplicationType	Gets the type of this SOLIDWORKS application.
 CommandInProgress	Improves performance of out-of-process applications by informing SOLIDWORKS that a sequence of API calls will be made by the out-of-process application.
 EnableBackgroundProcessing	Gets or sets whether to enable background processing.
 EnableFileMenu	Gets or sets whether to enable file-related menus and toolbars.
 FrameHeight	Get or sets the height of the SOLIDWORKS window.
 FrameLeft	Gets or sets the left position of the SOLIDWORKS window.
 FrameState	Gets or sets the window state (minimum, maximum, or normal) for the SOLIDWORKS window.
 FrameTop	Gets or sets the top position of the SOLIDWORKS window.
 FrameWidth	Gets or sets the width of the frame of the SOLIDWORKS window.
 IActiveDoc	Obsolete. Superseded by ISldWorks.IActiveDoc2
 IActiveDoc2	Gets the currently active document.
 ShadedEdgeThickness	Gets or sets the edge thickness when the display style is "Shaded with Edges".
 StartupProcessCompleted	Gets whether the SOLIDWORKS startup process, including loading all startup add-ins, has completed.
 TaskPanelsPinned	Gets or sets whether the SOLIDWORKS Task Pane is pinned.

	UserControl	Gets and sets whether the user has control over the application.
	UserControlBackground	Gets and sets whether the user has control over the application.
	UserTypeLibReferences	Gets and sets the user-specified type library references.
	Visible	Gets and sets the visibility property of the SOLIDWORKS Design application.

[Top](#)

See Also

[ISldWorks Interface](#)
[SolidWorks.Interop.sldworks Namespace](#)
[IAssemblyDoc Interface](#)
[IDrawingDoc Interface](#)
[IModelDoc2 Interface](#)
[IModelDocExtension Interface](#)
[IPartDoc Interface](#)

SOLIDWORKS API Help

[Send comments on this topic.](#)

ActivateDoc Method (ISldWorks)

[See Also](#)



[SolidWorks.Interop.sldworks Namespace](#) > [ISldWorks Interface](#) : ActivateDoc Method (ISldWorks)

Obsolete. Superseded by [ISldWorks::ActivateDoc2](#) and [ISldWorks::IActivateDoc3](#).

.NET Syntax

Visual Basic (Declaration)

```
Function ActivateDoc( _
    ByVal Name As System.String _
) As System.Object
```

Visual Basic (Usage)



```
Dim instance As ISldWorks
Dim Name As System.String
Dim value As System.Object

value = instance.ActivateDoc(Name)
```

C#

```
System.object ActivateDoc(
    System.string Name
)
```

C++/CLI

```
System.Object^ ActivateDoc(
    & System.String^ Name
)
```

NOTE: See [Differences Between Unmanaged C++ and C++/CLI Code](#).

Parameters

Name

Visual Basic for Applications (VBA) Syntax

See [SldWorks::ActivateDoc](#).

See Also

[ISldWorks Interface](#)
[ISldWorks Members](#)

SOLIDWORKS API Help

[Send comments on this topic.](#)

ActivateDoc2 Method (ISldWorks)

[See Also](#) [Example](#)



[SolidWorks.Interop.sldworks Namespace](#) > [ISldWorks Interface](#) : ActivateDoc2 Method (ISldWorks)

Obsolete. Superseded by [ISldWorks::ActivateDoc3](#).

.NET Syntax

Visual Basic (Declaration)

```
Function ActivateDoc2( _  
    ByVal Name As System.String, _  
    ByVal Silent As System.Boolean, _  
    ByRef Errors As System.Integer _  
) As System.Object
```

Visual Basic (Usage)



```
Dim instance As ISldWorks  
Dim Name As System.String  
Dim Silent As System.Boolean  
Dim Errors As System.Integer  
Dim value As System.Object  
  
value = instance.ActivateDoc2(Name, Silent, Errors)
```

C#

```
System.object ActivateDoc2(  
    System.string Name,  
    System.bool Silent,  
    out System.int Errors  
)
```

C++/CLI

```
System.Object^ ActivateDoc2(  
& System.String^ Name,  
& System.bool Silent,  
& [Out] System.int Errors  
)
```

NOTE: See [Differences Between Unmanaged C++ and C++/CLI Code](#).

Parameters

Name

Name of document to activate

Silent

True if dialogs and warning messages should be avoided, false if dialogs and warning messages should be displayed to the user

Errors

Status of the document activate operation as defined in [swActivateDocError e](#); if no errors or warnings are encountered, then this value is set to 0

Return Value

[Model document](#)

Visual Basic for Applications (VBA) Syntax

See [SldWorks::ActivateDoc2](#).

Example

[Add Component and Mate \(VBA\)](#)
[Get Corresponding Note in Assembly \(VBA\)](#)
[Get Corresponding Note in Part \(VBA\)](#)
[Open Part From Assembly \(VBA\)](#)

Remarks

This file becomes the active document, and this method returns a pointer to that document object.

If you do not specify a file extension in the name parameter, the document activated is based on its name and ignores the file extension. This can cause problems if you have two different document types with the same name loaded; for example, 12345.sldprt and 12345.sldasm.

If you do not specify the filename extension in your call to this method, then you cannot be sure which document is activated. To avoid this problem, you can specify the file name extension in the name parameter or you can check the document type after it is activated using [IModelDoc2::GetType](#).

In some instances, a document requires a rebuild when it is activated. If this is the case and you have passed True for the silent argument, then the activated document is not rebuilt and swDocNeedsRebuildWarning is returned in the errors argument. You can then programmatically rebuild the document using the [IModelDoc2::EditRebuild3](#) method.

If the document needs a rebuild upon activation and you have passed false for the Silent argument, then a dialog is displayed to the users asking them if they want to rebuild the document.

If the user answers...	Then the activated document is...
No	Not rebuilt and swDocNeedsRebuildWarning is returned in the errors argument.
Yes	Rebuilt immediately and this warning is not returned.

See Also

[ISldWorks Interface](#)
[ISldWorks Members](#)
[ISldWorks::IActivateDoc3 Method](#)
[ISldWorks::ActiveDoc Property](#)
[ISldWorks::IActiveDoc2 Property](#)
[ISldWorks::CloseAllDocuments Method](#)
[ISldWorks::CloseDoc Method](#)
[ISldWorks::GetFirstDocument Method](#)
[ISldWorks::GetOpenDocument Method](#)
[ISldWorks::GetOpenDocumentByName Method](#)
[ISldWorks::GetOpenFileName Method](#)
[ISldWorks::IGetFirstDocument2 Method](#)
[ISldWorks::IGetOpenDocumentByName2 Method](#)
[ISldWorks::LoadFile4 Method](#)
[ISldWorks::OpenDoc6 Method](#)

Availability

SOLIDWORKS 99, datecode 1999207

SOLIDWORKS API Help

[Send comments on this topic.](#)

ActivateDoc3 Method (ISldWorks)

[See Also](#) [Example](#)



[SolidWorks.Interop.sldworks Namespace](#) > [ISldWorks Interface](#) : ActivateDoc3 Method (ISldWorks)

Activates a loaded document and rebuilds it as specified.

.NET Syntax

Visual Basic (Declaration)

```
Function ActivateDoc3( _  
    ByVal Name As System.String, _  
    ByVal UseUserPreferences As System.Boolean, _  
    ByVal Option As System.Integer, _  
    ByRef Errors As System.Integer _  
) As System.Object
```

Visual Basic (Usage)



```
Dim instance As ISldWorks  
Dim Name As System.String  
Dim UseUserPreferences As System.Boolean  
Dim Option As System.Integer  
Dim Errors As System.Integer  
Dim value As System.Object
```

```
value = instance.ActivateDoc3(Name, UseUserPreferences, Option, Errors)
```

C#

```
System.object ActivateDoc3(  
    System.string Name,  
    System.bool UseUserPreferences,  
    System.int Option,  
    out System.int Errors  
)
```

C++/CLI

```
System.Object^ ActivateDoc3(  
    & System.String^ Name,  
    & System.bool UseUserPreferences,  
    & System.int Option,  
    & [Out] System.int Errors  
)
```

NOTE: See [Differences Between Unmanaged C++ and C++/CLI Code](#).

Parameters

Name

Name of the loaded document to activate (see **Remarks**)

UseUserPreferences

True to rebuild as per the [swRebuildOnActivation](#) system option; false to rebuild as per Option

Option

Rebuild option as defined in [swRebuildOnActivation_e](#) (see **Remarks**)

Errors

Status of the activate operation as defined in [swActivateDocError_e](#); if no errors or warnings are encountered, then this value is 0 (see **Remarks**)

Return Value

[Model document](#)

Visual Basic for Applications (VBA) Syntax

See [SldWorks::ActivateDoc3](#).

Example

[Rebuild Document on Activation \(VBA\)](#)

[Rebuild Document on Activation \(VB.NET\)](#)

[Rebuild Document on Activation \(C#\)](#)

Remarks

This method brings the document specified in Name to the foreground of SOLIDWORKS and returns a pointer to the document.

If you do not specify a file extension in Name, the document activated is based on its filename without the file extension. This can cause problems if you have loaded two different document types with the same name (e.g., **12345.sldprt** and **12345.sldasm**). To avoid this problem, specify the file extension in Name or check the document type after it is activated using [IModelDoc2::GetType](#).

If the document needs a rebuild upon activation, and you have specified Option with [swRebuildOnActivation_e.swDontRebuildActiveDoc](#), then the activated document is not rebuilt, and Errors contains [swActivateDocError_e.swDocNeedsRebuildWarning](#). You can then rebuild the document using [IModelDoc2::EditRebuild3](#).

If the document needs a rebuild upon activation, and you have specified Option with [swRebuildOnActivation_e.swUserDecision](#), then a dialog displays asking whether to rebuild the document.

If the user answers...	Then the activated document is...
No	Not rebuilt, and Errors contains swActivateDocError_e.swDocNeedsRebuildWarning
Yes	Rebuilt immediately

See Also

[ISldWorks Interface](#)
[ISldWorks Members](#)
[ISldWorks::!ActivateDoc3 Method](#)
[ISldWorks::!ActiveDoc Property](#)
[ISldWorks::!ActiveDoc2 Property](#)
[ISldWorks::CloseAllDocuments Method](#)
[ISldWorks::CloseDoc Method](#)
[ISldWorks::CloseAndReopen Method](#)
[ISldWorks::GetFirstDocument Method](#)
[ISldWorks::GetOpenDocument Method](#)
[ISldWorks::GetOpenDocumentByName Method](#)
[ISldWorks::GetOpenFileName Method](#)
[ISldWorks::!GetFirstDocument2 Method](#)
[ISldWorks::!GetOpenDocumentByName2 Method](#)
[ISldWorks::LoadFile4 Method](#)
[ISldWorks::OpenDoc7 Method](#)

Availability

SOLIDWORKS 2012 FCS, Revision Number 20.0

SOLIDWORKS API Help

[Send comments on this topic.](#)

ActivateTaskPane Method (ISldWorks)

[See Also](#)



[SolidWorks.Interop.sldworks Namespace](#) > [ISldWorks Interface](#) : ActivateTaskPane Method (ISldWorks)

Activates the specified task pane.

.NET Syntax

Visual Basic (Declaration)

```
Function ActivateTaskPane( _  
    ByVal TaskPaneID As System.Integer _  
) As System.Boolean
```

Visual Basic (Usage)



```
Dim instance As ISldWorks  
Dim TaskPaneID As System.Integer  
Dim value As System.Boolean  
  
value = instance.ActivateTaskPane(TaskPaneID)
```

C#

```
System.bool ActivateTaskPane(  
    System.int TaskPaneID  
)
```

C++/CLI

```
System.bool ActivateTaskPane(  
&    System.int TaskPaneID  
)
```

NOTE: See [Differences Between Unmanaged C++ and C++/CLI Code](#).

Parameters

TaskPaneID

ID of task pane as defined in [swTaskPaneTab_e](#)

Return Value

True if the specified task pane is activated, false if not

Visual Basic for Applications (VBA) Syntax

See [SldWorks::ActivateTaskPane](#).

See Also

[ISldWorks Interface](#)
[ISldWorks Members](#)
[ISldWorks::CreateTaskpaneView2 Method](#)
[ISldWorks::RefreshTaskpaneContent Method](#)
[ISldWorks::TaskPanelsPinned Property](#)
[ITaskpaneView Interface](#)

Availability

SOLIDWORKS 2007 FCS, Revision Number 15.0

SOLIDWORKS API Help

[Send comments on this topic.](#)

ActiveDoc Property (ISldWorks)

[See Also](#) [Example](#)



[SolidWorks.Interop.sldworks Namespace](#) > [ISldWorks Interface](#) : ActiveDoc Property (ISldWorks)

Gets the currently active document.

.NET Syntax

Visual Basic (Declaration)

ReadOnly Property ActiveDoc As System.Object

Visual Basic (Usage)



```
Dim instance As ISldWorks  
Dim value As System.Object  
  
value = instance.ActiveDoc
```

C#

```
System.object ActiveDoc {get;}
```

C++/CLI

```
property System.Object^ ActiveDoc {  
    System.Object^ get();  
}
```

NOTE: See [Differences Between Unmanaged C++ and C++/CLI Code](#).

Property Value

[Model document](#) or Nothing or null if the operation fails

Visual Basic for Applications (VBA) Syntax

See [SldWorks::ActiveDoc](#).

Example

[Create Equation-driven Curve \(C#\)](#)
[Create Equation-driven Curve \(VB.NET\)](#)
[Create Equation-driven Curve \(VBA\)](#)

Remarks

If no document is active, then Nothing or null is returned. This is a read-only property.

The currently active document cannot be the document that is being edited by the end-user. For example, you can use in-context editing to modify an assembly component. The currently active document is the assembly, but the edit target is the assembly component. For assemblies, you can determine the edit target by using the [IAssemblyDoc::GetEditTarget](#) or [IAssemblyDoc::IGetEditTarget2](#) method.

See Also

[ISldWorks Interface](#)
[ISldWorks Members](#)
[ISldWorks::IActiveDoc2 Property](#)
[ISldWorks::ActivateDoc2 Method](#)
[ISldWorks::EnumDocuments2 Method](#)
[ISldWorks::GetFirstDocument Method](#)
[ISldWorks::GetOpenDocument Method](#)
[ISldWorks::GetOpenDocumentByName Method](#)
[ISldWorks::GetOpenedFileInfo Method](#)
[ISldWorks::GetOpenFileName Method](#)
[ISldWorks::IActivateDoc3 Method](#)
[ISldWorks::IGetFirstDocument2 Method](#)
[ISldWorks::IGetOpenDocumentByName2 Method](#)
[ISldWorks::OpenDoc6 Method](#)

SOLIDWORKS API Help

[Send comments on this topic.](#)

ActivePrinter Property (ISldWorks)

[See Also](#)



[SolidWorks.Interop.sldworks Namespace](#) > [ISldWorks Interface](#) : ActivePrinter Property (ISldWorks)

Obsolete. Superseded by [IModelDoc2::Printer](#).

.NET Syntax

Visual Basic (Declaration)

```
Property ActivePrinter As System.String
```

Visual Basic (Usage)



```
Dim instance As ISldWorks  
Dim value As System.String  
  
instance.ActivePrinter = value  
  
value = instance.ActivePrinter
```

C#

```
System.string ActivePrinter {get; set;}
```

C++/CLI

```
property System.String^ ActivePrinter {  
    System.String^ get();  
    void set ( & System.String^ value);  
}
```

NOTE: See [Differences Between Unmanaged C++ and C++/CLI Code](#).

Visual Basic for Applications (VBA) Syntax

See [SldWorks::ActivePrinter](#).

See Also

[ISldWorks Interface](#)
[ISldWorks Members](#)

SOLIDWORKS API Help

[Send comments on this topic.](#)

AddCallback Method (ISldWorks)

[See Also](#)



[SolidWorks.Interop.sldworks Namespace](#) > [ISldWorks Interface](#) : AddCallback Method (ISldWorks)

Registers a general purpose callback handler.

.NET Syntax

Visual Basic (Declaration)

```
Sub AddCallback( _  
    ByVal Cookie As System.Integer, _
```

```
ByVal CallbackFunction As System.String _  
)
```

Visual Basic (Usage)



```
Dim instance As ISldWorks  
Dim Cookie As System.Integer  
Dim CallbackFunction As System.String  
  
instance.AddCallback(Cookie, CallbackFunction)
```

C#

```
void AddCallback(  
    System.int Cookie,  
    System.string CallbackFunction  
)
```

C++/CLI

```
void AddCallback(  
& System.int Cookie,  
& System.String^ CallbackFunction  
)
```

NOTE: See [Differences Between Unmanaged C++ and C++/CLI Code](#).

Parameters

Cookie

Cookie specified in [ISwAddin::ConnectToSW](#)

CallbackFunction

Name of the function to call (see **Remarks**)

Visual Basic for Applications (VBA) Syntax

See [SldWorks::AddCallback](#).

Remarks

The callback function has three arguments:

Callback function parameter name in example	Data Type	Description
cmd	Integer	Command ID as defined in swAppCallBackCmd_e
data	Integer	Data related to the event
dsp	LPDISPATCH	Not currently used

See Also

[ISldWorks Interface](#)

[ISldWorks Members](#)

[ISldWorks::CallBack Method](#)

[ISldWorks::RemoveCallback Method](#)

[ISldWorks::SetAddinCallbackInfo Method](#)

[ISldWorks::PostMessageToApplication Method](#)

Availability

SOLIDWORKS 2006 FCS, Revision Number 14.0



[SolidWorks.Interop.sldworks Namespace](#) > [ISldWorks Interface](#) : AddFileOpenItem Method (ISldWorks)

Obsolete. Superseded by [ISldWorks::AddFileOpenItem3](#).

.NET Syntax

Visual Basic (Declaration)

```
Function AddFileOpenItem( _  
    ByVal CallbackFcnAndModule As System.String, _  
    ByVal Description As System.String _  
) As System.Boolean
```

Visual Basic (Usage)



```
Dim instance As ISldWorks  
Dim CallbackFcnAndModule As System.String  
Dim Description As System.String  
Dim value As System.Boolean  
  
value = instance.AddFileOpenItem(CallbackFcnAndModule, Description)
```

C#

```
System.bool AddFileOpenItem(  
    System.string CallbackFcnAndModule,  
    System.string Description  
)
```

C++/CLI

```
System.bool AddFileOpenItem(  
& System.String^ CallbackFcnAndModule,  
& System.String^ Description  
)
```

NOTE: See [Differences Between Unmanaged C++ and C++/CLI Code](#).

Parameters

CallbackFcnAndModule

Description

Visual Basic for Applications (VBA) Syntax

See [SldWorks::AddFileOpenItem](#).

See Also

[ISldWorks Interface](#)
[ISldWorks Members](#)

SOLIDWORKS API Help

[Send comments](#) on this topic.

AddFileOpenItem2 Method (ISldWorks)

[See Also](#)



[SolidWorks.Interop.sldworks Namespace](#) > [ISldWorks Interface](#) : AddFileOpenItem2 Method (ISldWorks)

Obsolete. Superseded by [ISldWorks::AddFileOpenItem3](#).

.NET Syntax

Visual Basic (Declaration)

```
Function AddFileOpenItem2( _  
    ByVal Cookie As System.Integer, _  
    ByVal MethodName As System.String, _  
    ByVal Description As System.String, _
```

```
ByVal Extension As System.String _  
) As System.Boolean
```

Visual Basic (Usage)



```
Dim instance As ISldWorks  
Dim Cookie As System.Integer  
Dim MethodName As System.String  
Dim Description As System.String  
Dim Extension As System.String  
Dim value As System.Boolean  
  
value = instance.AddFileOpenItem2(Cookie, MethodName, Description, Extension)
```

C#

```
System.bool AddFileOpenItem2(  
    System.int Cookie,  
    System.string MethodName,  
    System.string Description,  
    System.string Extension  
)
```

C++/CLI

```
System.bool AddFileOpenItem2(  
& System.int Cookie,  
& System.String^ MethodName,  
& System.String^ Description,  
& System.String^ Extension  
)
```

NOTE: See [Differences Between Unmanaged C++ and C++/CLI Code](#).

Parameters

Cookie

MethodName

Description

Extension

Visual Basic for Applications (VBA) Syntax

See [SldWorks::AddFileOpenItem2](#).

See Also

[ISldWorks Interface](#)
[ISldWorks Members](#)

SOLIDWORKS API Help

[Send comments on this topic.](#)

AddFileOpenItem3 Method (ISldWorks)

[See Also](#) [Example](#)



[SolidWorks.Interop.sldworks Namespace](#) > [ISldWorks Interface](#) : AddFileOpenItem3 Method (ISldWorks)

Adds file types to the **File > Open** dialog box.

.NET Syntax

Visual Basic (Declaration)

```
Function AddFileOpenItem3( _  
    ByVal Cookie As System.Integer, _  
    ByVal MethodName As System.String, _  
    ByVal Description As System.String, _  
    ByVal Extension As System.String, _  
    ByVal OptionLabel As System.String, _
```

```
ByVal OptionMethodName As System.String _  
) As System.Boolean
```

Visual Basic (Usage)



```
Dim instance As ISldWorks  
Dim Cookie As System.Integer  
Dim MethodName As System.String  
Dim Description As System.String  
Dim Extension As System.String  
Dim OptionLabel As System.String  
Dim OptionMethodName As System.String  
Dim value As System.Boolean
```

```
value = instance.AddFileOpenItem3(Cookie, MethodName, Description, Extension, OptionLabel,  
OptionMethodName)
```

C#

```
System.bool AddFileOpenItem3(  
    System.int Cookie,  
    System.string MethodName,  
    System.string Description,  
    System.string Extension,  
    System.string OptionLabel,  
    System.string OptionMethodName  
)
```

C++/CLI

```
System.bool AddFileOpenItem3(  
& System.int Cookie,  
& System.String^ MethodName,  
& System.String^ Description,  
& System.String^ Extension,  
& System.String^ OptionLabel,  
& System.String^ OptionMethodName  
)
```

NOTE: See [Differences Between Unmanaged C++ and C++/CLI Code](#).

Parameters

Cookie

Cookie specified in [ISwAddin::ConnectToSW](#)

MethodName

Name of the application function used to open the file (see **Remarks**)

Description

File description displayed in the **Save as type** list

Extension

File name extensions separated by semicolons

OptionLabel

Label for your options button or an empty string

OptionMethodName

Name of the callback method to display a dialog box, which appears when a user clicks your options button or an empty string

Return Value

True if the file types are added to the **Save as type** list, false if not

Visual Basic for Applications (VBA) Syntax

See [SldWorks::AddFileOpenItem3](#).

Example

[Add and Remove Items to File Save As and Open Menus \(VB.NET\)](#)

[Add and Remove Items to File Save As and Open Menus \(C#\)](#)

Remarks

Call this method in your add-in's ConnectToSW method.

Implement the function specified by MethodName with a string parameter that is the file name.

If your application is unloaded using an add-in, then you must remove any file types added with this method. See [ISldWorks::RemoveFileOpenItem2](#).

The callback is called one time if the user:

- Presses the Shift or Ctrl key and selects multiple files to open in the **File > Open** Dialog.
- Drags-and-drops files into SOLIDWORKS from either File Explorer or the File Explorer tab in the TaskPane.

See Also

[ISldWorks Interface](#)
[ISldWorks Members](#)
[ISldWorks::RemoveFileOpenItem2 Method](#)
[ISldWorks::RemoveFileSaveAsItem2 Method](#)
[ISldWorks::AddFileSaveAsItem2 Method](#)

Availability

SOLIDWORKS 2007 FCS, Revision Number 15.0

SOLIDWORKS API Help

[Send comments on this topic.](#)

AddFileSaveAsItem Method (ISldWorks)

[See Also](#)



[SolidWorks.Interop.sldworks Namespace](#) > [ISldWorks Interface](#) : AddFileSaveAsItem Method (ISldWorks)

Obsolete. Superseded by [ISldWorks::AddFileSaveAsItem2](#).

.NET Syntax

Visual Basic (Declaration)

```
Function AddFileSaveAsItem( _  
    ByVal CallbackFcnAndModule As System.String, _  
    ByVal Description As System.String, _  
    ByVal Type As System.Integer _  
) As System.Boolean
```

Visual Basic (Usage)



```
Dim instance As ISldWorks  
Dim CallbackFcnAndModule As System.String  
Dim Description As System.String  
Dim Type As System.Integer  
Dim value As System.Boolean
```

```
value = instance.AddFileSaveAsItem(CallbackFcnAndModule, Description, Type)
```

C#

```
System.bool AddFileSaveAsItem(  
    System.string CallbackFcnAndModule,  
    System.string Description,  
    System.int Type  
)
```

C++/CLI

```
System.bool AddFileSaveAsItem(  
& System.String^ CallbackFcnAndModule,  
& System.String^ Description,  
& System.int Type  
)
```

NOTE: See [Differences Between Unmanaged C++ and C++/CLI Code](#).

Parameters

CallbackFcnAndModule

Description

Type

Visual Basic for Applications (VBA) Syntax

See [SldWorks::AddFileSaveAsItem](#).

See Also

[ISldWorks Interface](#)
[ISldWorks Members](#)

SOLIDWORKS API Help

[Send comments](#) on this topic.

AddFileSaveAsItem2 Method (ISldWorks)

[See Also](#) [Example](#)



[SolidWorks.Interop.sldworks Namespace](#) > [ISldWorks Interface](#) : AddFileSaveAsItem2 Method (ISldWorks)

Adds a file type to the SOLIDWORKS **File > Save As** dialog box.

.NET Syntax

Visual Basic (Declaration)

```
Function AddFileSaveAsItem2( _  
    ByVal Cookie As System.Integer, _  
    ByVal MethodName As System.String, _  
    ByVal Description As System.String, _  
    ByVal Extension As System.String, _  
    ByVal DocumentType As System.Integer _  
) As System.Boolean
```

Visual Basic (Usage)



```
Dim instance As ISldWorks  
Dim Cookie As System.Integer  
Dim MethodName As System.String  
Dim Description As System.String  
Dim Extension As System.String  
Dim DocumentType As System.Integer  
Dim value As System.Boolean
```

```
value = instance.AddFileSaveAsItem2(Cookie, MethodName, Description, Extension, DocumentType)
```

C#

```
System.bool AddFileSaveAsItem2(  
    System.int Cookie,  
    System.string MethodName,  
    System.string Description,  
    System.string Extension,  
    System.int DocumentType  
)
```

C++/CLI

```
System.bool AddFileSaveAsItem2(  
& System.int Cookie,  
& System.String^ MethodName,  
& System.String^ Description,  
& System.String^ Extension,  
& System.int DocumentType  
)
```

NOTE: See [Differences Between Unmanaged C++ and C++/CLI Code](#).

Parameters

Cookie

Cookie specified in [ISwAddin::ConnectToSW](#)

MethodName

Name of the application function used to save the file (see **Remarks**)

Description

File description in the **Save as type** list

Extension

File name extension

DocumentType

Type of document to save as defined in [swDocumentTypes_e](#)

Return Value

True if the file type is added to the **Save as type** list, false if not

Visual Basic for Applications (VBA) Syntax

See [ISldWorks::AddFileSaveAsItem2](#).

Example

[Add and Remove Items to File Save As and Open Menus \(VB.NET\)](#)
[Add and Remove Items to File Save As and Open Menus \(C#\)](#)

Remarks

Call this method in your add-in's ConnectToSW method.

Implement the function specified by MethodName with a string parameter that is the file name.

If your application is unloaded using the Add-In Manager, then you must remove any file types added with this method using [ISldWorks::RemoveFileSaveAsItem2](#).

See Also

[ISldWorks Interface](#)
[ISldWorks Members](#)
[ISldWorks::AddFileOpenItem3 Method](#)
[ISldWorks::RemoveFileOpenItem2 Method](#)

Availability

SOLIDWORKS 2003 FCS, Revision Number 11.0

SOLIDWORKS API Help

[Send comments on this topic.](#)

AddItemToThirdPartyPopupMenu Method (ISldWorks)

[See Also](#)



[SolidWorks.Interop.sldworks Namespace](#) > [ISldWorks Interface](#) : AddItemToThirdPartyPopupMenu Method (ISldWorks)

Adds menu items to a pop-up (shortcut) menu in a C++ SOLIDWORKS add-in.

.NET Syntax

Visual Basic (Declaration)

```
Function AddItemToThirdPartyPopupMenu( _  
    ByVal RegisterId As System.Integer, _  
    ByVal DocType As System.Integer, _  
    ByVal Item As System.String, _  
    ByVal CallbackFcnAndModule As System.String, _  
    ByVal CustomName As System.String, _  
    ByVal HintString As System.String, _  
    ByVal BitmapFileName As System.String, _  
    ByVal MenuItemTypeOption As System.Integer _  
) As System.Boolean
```

Visual Basic (Usage)

```
Dim instance As ISldWorks  
Dim RegisterId As System.Integer
```



```

Dim DocType As System.Integer
Dim Item As System.String
Dim CallbackFcnAndModule As System.String
Dim CustomName As System.String
Dim HintString As System.String
Dim BitmapFileName As System.String
Dim MenuItemTypeOption As System.Integer
Dim value As System.Boolean

```

```

value = instance.AddItemToThirdPartyPopupMenu(RegisterId, DocType, Item, CallbackFcnAndModule,
CustomName, HintString, BitmapFileName, MenuItemTypeOption)

```

C#

```

System.bool AddItemToThirdPartyPopupMenu(
    System.int RegisterId,
    System.int DocType,
    System.string Item,
    System.string CallbackFcnAndModule,
    System.string CustomName,
    System.string HintString,
    System.string BitmapFileName,
    System.int MenuItemTypeOption
)

```

C++/CLI

```

System.bool AddItemToThirdPartyPopupMenu(
    & System.int RegisterId,
    & System.int DocType,
    & System.String^ Item,
    & System.String^ CallbackFcnAndModule,
    & System.String^ CustomName,
    & System.String^ HintString,
    & System.String^ BitmapFileName,
    & System.int MenuItemTypeOption
)

```

NOTE: See [Differences Between Unmanaged C++ and C++/CLI Code](#).

Parameters

RegisterId

ID of shortcut menu from [ISldWorks::RegisterThirdPartyPopupMenu](#)

DocType

Document type where to display shortcut menu, as defined in [swDocumentTypes_e](#)

Item

Name of shortcut menu item (see **Remarks**)

CallbackFcnAndModule

Function called when user clicks the shortcut menu item (see **Remarks**)

CustomName

Empty string

HintString

Text to display in the SOLIDWORKS status bar when users move the mouse over this shortcut menu item

BitmapFileName

Path and filename of the bitmap

MenuItemTypeOption

Menu item as defined in [swMenuItemType_e](#)

Return Value

True if the shortcut menu item is added, false if not

Example

C++



To add a section title or **break** to the shortcut menu:

```

iSwApp->AddItemToThirdPartyPopupMenu
(
    registerIdPMenu1,
    swDocPART,
    CComBSTR(_T("Menu Break")),
    CComBSTR(_T("")),
    CComBSTR(_T("")),

```

```

CComBSTR(_T("")),
CComBSTR(_T("")),
swMenuItemType_Break,
&itemAdded
);

```

To add an icon to a menu bar above the shortcut menu:

```

iSwApp->AddItemToThirdPartyPopupMenu
(
    registerIdPMenu1,
    swDocPART,
    CComBSTR(_T("")),
    CComBSTR(_T("UserPopupMenu.dll@UserItem1_Menu1_Callback")),
    CComBSTR(_T("")),
    CComBSTR(_T("UserItem1_Menu1_Callback_hint")),
    UserItem1_Menu1_bitmapFile,
    swMenuItemType_Default,
    &itemAdded
);

```

To add an actionable item to the shortcut menu:

```

iSwApp->AddItemToThirdPartyPopupMenu
(
    registerIdPMenu1,
    swDocPART,
    CComBSTR(_T("UserItem1_Menu1_Callback")),
    CComBSTR(_T("UserPopupMenu.dll@UserItem1_Menu1_Callback")),
    CComBSTR(_T("")),
    CComBSTR(_T("UserItem1_Menu1_Callback_hint")),
    UserItem1_Menu1_bitmapFile,
    swMenuItemType_Default,
    &itemAdded
);

```

To add a separator bar to the shortcut menu:

```

iSwApp->AddItemToThirdPartyPopupMenu
(
    registerIdPMenu1,
    swDocPART,
    CComBSTR(_T("")),
    CComBSTR(_T("")),
    CComBSTR(_T("")),
    CComBSTR(_T("")),
    CComBSTR(_T("")),
    CComBSTR(_T("")),
    swMenuItemType_Separator,
    &itemAdded
);

```

Remarks

This method is supported in C++ applications only, and it only works in C++ applications implemented as DLLs, not as EXEs.

Read about [Add-in Shortcut Menus](#).

The CallbackFcnAndModule argument specifies which function to call when this shortcut menu item is selected by the user. The syntax is as follows:

"dllname@function@updatefunction"

where:

dllname	Name of your library as specified in the project .def file. The actual DLL filename and the definition in the .def file must be the same.
function	Name of the function that gets called when the user clicks the shortcut menu item. This function must also be declared as an EXPORT in your .def file. See Add-in Callback and Enable Methods to learn how to implement your function.

updatefunction

Optional argument that controls the state of the shortcut menu item. If specified, then SOLIDWORKS calls this function before the shortcut menu item is displayed. Define your updatefunction to return an integer and declare it as an EXPORT or included in your .def file.

The display of the third-party shortcut menu item is controlled by the return value of the function as follows:

- return 0 - Unchecked and disabled.
- return 1 - Unchecked and enabled. This is the default menu state if no updatefunction is specified.
- return 2 - Checked and disabled.
- return 3 - Checked and enabled.

See [Add-in Callback and Enable Methods](#) to learn how to implement your updatefunction.

See Also

[ISldWorks Interface](#)
[ISldWorks Members](#)
[ISldWorks::AddItemToThirdPartyPopupMenu2 Method](#)

Availability

SOLIDWORKS 2010 FCS, Revision Number 18.0

SOLIDWORKS API Help

[Send comments on this topic.](#)

AddItemToThirdPartyPopupMenu2 Method (ISldWorks)

[See Also](#) [Example](#)



[SolidWorks.Interop.sldworks Namespace](#) > [ISldWorks Interface](#) : AddItemToThirdPartyPopupMenu2 Method (ISldWorks)

Adds menu items to a pop-up (shortcut) menu in a SOLIDWORKS add-in.

.NET Syntax

Visual Basic (Declaration)

```
Function AddItemToThirdPartyPopupMenu2( _  
    ByVal RegisterId As System.Integer, _  
    ByVal DocType As System.Integer, _  
    ByVal Item As System.String, _  
    ByVal Identifier As System.Integer, _  
    ByVal CallbackFunction As System.String, _  
    ByVal EnableFunction As System.String, _  
    ByVal CustomName As System.String, _  
    ByVal HintString As System.String, _  
    ByVal BitmapFileName As System.String, _  
    ByVal MenuItemTypeOption As System.Integer _  
) As System.Boolean
```

Visual Basic (Usage)

```
Dim instance As ISldWorks  
Dim RegisterId As System.Integer  
Dim DocType As System.Integer  
Dim Item As System.String  
Dim Identifier As System.Integer  
Dim CallbackFunction As System.String  
Dim EnableFunction As System.String  
Dim CustomName As System.String  
Dim HintString As System.String  
Dim BitmapFileName As System.String  
Dim MenuItemTypeOption As System.Integer  
Dim value As System.Boolean
```

```
value = instance.AddItemToThirdPartyPopupMenu2(RegisterId, DocType, Item, Identifier,  
CallbackFunction, EnableFunction, CustomName, HintString, BitmapFileName, MenuItemTypeOption)
```

C#

```
System.bool AddItemToThirdPartyPopupMenu2(  
    System.int RegisterId,  
    System.int DocType,
```

```

System.string Item,
System.int Identifier,
System.string CallbackFunction,
System.string EnableFunction,
System.string CustomName,
System.string HintString,
System.string BitmapFileName,
System.int MenuItemTypeOption
)

```

C++/CLI

```

System.bool AddItemToThirdPartyPopupMenu2(
& System.int RegisterId,
& System.int DocType,
& System.String^ Item,
& System.int Identifier,
& System.String^ CallbackFunction,
& System.String^ EnableFunction,
& System.String^ CustomName,
& System.String^ HintString,
& System.String^ BitmapFileName,
& System.int MenuItemTypeOption
)

```

NOTE: See [Differences Between Unmanaged C++ and C++/CLI Code](#).

Parameters

RegisterId

ID of shortcut menu from [ISldWorks::RegisterThirdPartyPopupMenu](#)

DocType

Document type where to display shortcut menu, as defined in [swDocumentTypes_e](#)

Item

Unique display name of shortcut menu item (see **Remarks**); specify an empty string if adding an icon to the menu bar

Identifier

ID of the add-in; value of the Cookie argument passed by [ISwAddin::ConnectToSW](#)

CallbackFunction

Function called when user clicks the shortcut menu item; specify an empty string if MenuItemTypeOption is:

- [swMenuItemType_e.swMenuItemType_Break](#)
- [swMenuItemType_e.swMenuItemType_Separator](#)

(see **Remarks**)

EnableFunction

Optional function that controls the state of the shortcut menu item

If specified, SOLIDWORKS:

1. calls this function before displaying the menu
2. displays the menu item according to the return value of this function

If EnableFunction returns...	Then SOLIDWORKS...
0	Deselects and disables the menu item
1	Deselects and enables the menu item; this is the default menu state if EnableFunction is not specified
2	Selects and disables the menu item
3	Selects and enables the menu item

Specify an empty string if MenuItemTypeOption is:

- [swMenuItemType_e.swMenuItemType_Break](#)
- [swMenuItemType_e.swMenuItemType_Separator](#)

(see **Remarks**)

CustomName

Empty string

HintString

Text to display in the SOLIDWORKS status bar when users move the mouse over this shortcut menu item

BitmapFileName

Path and filename of bitmap for icons (menu bar or menu item)

Specify an empty string if MenuItemTypeOption is:

- [swMenuItemType_e.swMenuItemType_Break](#)
- [swMenuItemType_e.swMenuItemType_Separator](#)

MenuItemTypeOption

Type of menu item as defined in [swMenuItemType_e](#)

Return Value

True if the shortcut menu item is added, false if not

Example

VB.NET



```
'To create and register a shortcut menu:
registerID = SwApp.RegisterThirdPartyPopupMenu()

'To add an actionable menu item to a shortcut menu:
resultCode = SwApp.AddItemToThirdPartyPopupMenu2(
    registerID,
    CInt(swDocumentTypes_e.swDocPART),
    "Test1",
    addinID,
    "TestCallback",
    "EnableTest",
    "",
    "Test1",
    cmdGroup.SmallMainIcon,
    CInt(swMenuItemType_e.swMenuItemType_Default))

'To add a separator bar to a shortcut menu
resultCode = SwApp.AddItemToThirdPartyPopupMenu2(
    registerID,
    CInt(swDocumentTypes_e.swDocPART),
    "Separator1",
    addinID
    "",
    "",
    "",
    "",
    "",
    CInt(swMenuItemType_e.swMenuItemType_Separator))

'To add a section title or break to a shortcut menu:
resultCode = SwApp.AddItemToThirdPartyPopupMenu2(
    registerID,
    CInt(swDocumentTypes_e.swDocPART),
    "Menu Break",
    addinID,
    "",
    "",
    "",
    "",
    "",
    CInt(swMenuItemType_e.swMenuItemType_Break))

'To add an icon to the menu bar above a shortcut menu:
resultCode = SwApp.AddItemToThirdPartyPopupMenu2(
    registerID,
    CInt(swDocumentTypes_e.swDocPART),
    "",
    addinID,
    "TestCallback",
    "EnableTest",
    "",
    "NoOp",
    cmdGroup.SmallMainIcon,
    CInt(swMenuItemType_e.swMenuItemType_Default))
```

Example

[Add Shortcut Menus to Add-ins \(VB.NET\)](#)
[Add Shortcut Menus to Add-ins \(C#\)](#)

Remarks

See [Add-in Callback and Enable Methods](#) to learn how to specify CallbackFunction and EnableFunction.

Read about [Add-in Shortcut Menus](#).

See Also

[ISldWorks Interface](#)
[ISldWorks Members](#)
[ISldWorks::AddItemToThirdPartyPopupMenu Method](#)

Availability

SOLIDWORKS 2011 FCS, Revision Number 19.0

SOLIDWORKS API Help

[Send comments on this topic.](#)

AddMenu Method (ISldWorks)

[See Also](#) [Example](#)



[SolidWorks.Interop.sldworks Namespace](#) > [ISldWorks Interface](#) : AddMenu Method (ISldWorks)

Adds a menu item to a SOLIDWORKS menu for DLL applications.

.NET Syntax

Visual Basic (Declaration)

```
Function AddMenu( _  
    ByVal DocType As System.Integer, _  
    ByVal Menu As System.String, _  
    ByVal Position As System.Integer _  
) As System.Integer
```

Visual Basic (Usage)



```
Dim instance As ISldWorks  
Dim DocType As System.Integer  
Dim Menu As System.String  
Dim Position As System.Integer  
Dim value As System.Integer  
  
value = instance.AddMenu(DocType, Menu, Position)
```

C#

```
System.int AddMenu(  
    System.int DocType,  
    System.string Menu,  
    System.int Position  
)
```

C++/CLI

```
System.int AddMenu(  
& System.int DocType,  
& System.String^ Menu,  
& System.int Position  
)
```

NOTE: See [Differences Between Unmanaged C++ and C++/CLI Code](#).

Parameters

DocType

Document type to add the menu item as defined by [swDocumentTypes_e](#)

Menu

Name of menu item to add, including any parent menu names, e.g., subMenuString@menuString

Position

Specifies the position where to add the new menu item; 0 = first position and 1 = end of the parent menu (see **Remarks**)

Return Value

1 if menu item is added successfully added or 0 if adding the menu item failed

Visual Basic for Applications (VBA) Syntax

See [SldWorks::AddMenu](#).

Example

[Add Menu and Menu Item \(C#\)](#)
[Add Menu and Menu Item \(VB.NET\)](#)

Remarks

If the name of a parent menu is not specified in Menu, then:

- the menu item appears on the **Tools** menu below the **XPress products** menu item.
- Position is ignored.

Menus items are automatically created at the end of the parent menu when using [ISldWorks::AddMenuItem5](#). Therefore, if your menu structure is created using sequential calls to SldWorks::AddMenuItem5, then all the menu items are positioned based on their order of creation.

This method is only required when a menu needs to be placed into an existing menu at a specific position.

Read about [Add-in Shortcut Menus](#).

See Also

[ISldWorks Interface](#)
[ISldWorks Members](#)
[ISldWorks::AddMenuPopupItem2 Method](#)
[ISldWorks::AddToolBar4 Method](#)
[ISldWorks::AddToolBarCommand2 Method](#)
[ISldWorks::RemoveFromMenu Method](#)
[ISldWorks::RemoveFromPopupMenu Method](#)
[ISldWorks::RemoveMenu Method](#)
[ISldWorks::RemoveMenuPopupItem2 Method](#)
[ISldWorks::RemoveToolBar2 Method](#)
[ISldWorks::GetLocalizedMenuName Method](#)

Availability

SOLIDWORKS 99, datecode 1999207

SOLIDWORKS API Help

[Send comments on this topic.](#)

AddMenuItem Method (ISldWorks)

[See Also](#)



[SolidWorks.Interop.sldworks Namespace](#) > [ISldWorks Interface](#) : AddMenuItem Method (ISldWorks)

Obsolete. Superseded by [ISldWorks::AddMenuItem3](#).

.NET Syntax

Visual Basic (Declaration)

```
Function AddMenuItem( _  
    ByVal DocType As System.Integer, _  
    ByVal Menu As System.String, _  
    ByVal Postion As System.Integer, _  
    ByVal CallbackModuleAndFcn As System.String _  
) As System.Integer
```

Visual Basic (Usage)



```
Dim instance As ISldWorks  
Dim DocType As System.Integer  
Dim Menu As System.String  
Dim Postion As System.Integer  
Dim CallbackModuleAndFcn As System.String  
Dim value As System.Integer  
  
value = instance.AddMenuItem(DocType, Menu, Postion, CallbackModuleAndFcn)
```

C#

```
System.int AddMenuItem(  
    System.int DocType,  
    System.string Menu,  
    System.int Postion,  
    System.string CallbackModuleAndFcn  
)
```

C++/CLI

```
System.int AddMenuItem(  
& System.int DocType,  
& System.String^ Menu,  
& System.int Postion,  
& System.String^ CallbackModuleAndFcn  
)
```

NOTE: See [Differences Between Unmanaged C++ and C++/CLI Code](#).

Parameters

DocType

Menu

Postion

CallbackModuleAndFcn

Visual Basic for Applications (VBA) Syntax

See [SldWorks::AddMenuItem](#).

See Also

[ISldWorks Interface](#)
[ISldWorks Members](#)

SOLIDWORKS API Help

[Send comments](#) on this topic.

AddMenuItem2 Method (ISldWorks)

[See Also](#)



[SolidWorks.Interop.sldworks Namespace](#) > [ISldWorks Interface](#) : AddMenuItem2 Method (ISldWorks)

Obsolete. Superseded by [ISldWorks::AddMenuItem3](#).

.NET Syntax

Visual Basic (Declaration)

```
Function AddMenuItem2(  
    ByVal DocumentType As System.Integer, _  
    ByVal Cookie As System.Integer, _  
    ByVal MenuItem As System.String, _  
    ByVal Position As System.Integer, _  
    ByVal MenuCallback As System.String, _  
    ByVal MenuEnableMethod As System.String, _  
    ByVal HintString As System.String _  
) As System.Boolean
```

Visual Basic (Usage)



```
Dim instance As ISldWorks  
Dim DocumentType As System.Integer  
Dim Cookie As System.Integer  
Dim MenuItem As System.String  
Dim Position As System.Integer  
Dim MenuCallback As System.String  
Dim MenuEnableMethod As System.String  
Dim HintString As System.String  
Dim value As System.Boolean
```

```
value = instance.AddMenuItem2(DocumentType, Cookie, MenuItem, Position, MenuCallback,
MenuEnableMethod, HintString)
```

C#

```
System.bool AddMenuItem2(
    System.int DocumentType,
    System.int Cookie,
    System.string MenuItem,
    System.int Position,
    System.string MenuCallback,
    System.string MenuEnableMethod,
    System.string HintString
)
```

C++/CLI

```
System.bool AddMenuItem2(
    & System.int DocumentType,
    & System.int Cookie,
    & System.String^ MenuItem,
    & System.int Position,
    & System.String^ MenuCallback,
    & System.String^ MenuEnableMethod,
    & System.String^ HintString
)
```

NOTE: See [Differences Between Unmanaged C++ and C++/CLI Code](#).

Parameters

DocumentType

Cookie

MenuItem

Position

MenuCallback

MenuEnableMethod

HintString

Visual Basic for Applications (VBA) Syntax

See [SldWorks::AddMenuItem2](#).

See Also

[ISldWorks Interface](#)
[ISldWorks Members](#)

SOLIDWORKS API Help

[Send comments on this topic.](#)

AddMenuItem3 Method (ISldWorks)

[See Also](#)



[SolidWorks.Interop.sldworks Namespace](#) > [ISldWorks Interface](#) : AddMenuItem3 Method (ISldWorks)

Obsolete. Superseded by [ISldWorks::AddMenuItem4](#).

.NET Syntax

Visual Basic (Declaration)

```
Function AddMenuItem3( _
    ByVal DocumentType As System.Integer, _
    ByVal Cookie As System.Integer, _
    ByVal MenuItem As System.String, _
    ByVal Position As System.Integer, _
    ByVal MenuCallback As System.String, _
    ByVal MenuEnableMethod As System.String, _
```

```

    ByVal HintString As System.String, _
    ByVal BitmapFilePath As System.String _
) As System.Boolean

```

Visual Basic (Usage)



```

Dim instance As ISldWorks
Dim DocumentType As System.Integer
Dim Cookie As System.Integer
Dim MenuItem As System.String
Dim Position As System.Integer
Dim MenuCallback As System.String
Dim MenuEnableMethod As System.String
Dim HintString As System.String
Dim BitmapFilePath As System.String
Dim value As System.Boolean

value = instance.AddMenuItem3(DocumentType, Cookie, MenuItem, Position, MenuCallback,
MenuEnableMethod, HintString, BitmapFilePath)

```

C#

```

System.bool AddMenuItem3(
    System.int DocumentType,
    System.int Cookie,
    System.string MenuItem,
    System.int Position,
    System.string MenuCallback,
    System.string MenuEnableMethod,
    System.string HintString,
    System.string BitmapFilePath
)

```

C++/CLI

```

System.bool AddMenuItem3(
    & System.int DocumentType,
    & System.int Cookie,
    & System.String^ MenuItem,
    & System.int Position,
    & System.String^ MenuCallback,
    & System.String^ MenuEnableMethod,
    & System.String^ HintString,
    & System.String^ BitmapFilePath
)

```

NOTE: See [Differences Between Unmanaged C++ and C++/CLI Code](#).

Parameters

DocumentType

Document type to add the menu item as defined by [swDocumentTypes_e](#)

Cookie

Cookie specified as defined in [ISwAddin::ConnectToSW](#)

MenuItem

Menu string ("menulitem@menuString"); SOLIDWORKS Design creates menu items only if they do not already exist

NOTE:

- If you do not specify menuString, then the menu item appears on the Tools menu below the **Xpress Products** menu item.
- Use the & symbol to include an accelerator key, e.g., "MyItem@&File" adds MyItem to the File menu with an accelerator key. To display the accelerator key, press the Alt key in SOLIDWORKS Design. The accelerator key is underlined.

Position

Position at which to add the new menu item

The first item is at position 0; if Position is -1, then the new menu item is added to the bottom of the list; this argument specifies the position of the menu item in relation to its immediate parent menu

MenuCallback

Function to call when this menu item is selected

MenuEnableMethod

Optional function that controls the state of the menu item

If specified:

- SOLIDWORKS Design calls this function before displaying the menu.

- Display of the menu item is controlled by the return value of MenuEnableMethod.

If your method returns...	Then SOLIDWORKS Design...
0	Deselects and disables the menu item
1	Deselects and enables the menu item; this is the default menu state if no update function is specified
2	Selects and disables the menu item
3	Selects and enables the menu item

HintString

Text to show in the SOLIDWORKS Design status bar when the user moves their mouse over this menu item; if you specify HintString, then it must be preceded by a comma

BitmapFilePath

Path and filename of bitmap

Return Value

True if menu item and bitmap are added, false if not

Visual Basic for Applications (VBA) Syntax

See [ISldWorks::AddMenuItem3](#).

Example

Adding a menu separator:

```
' Adds a menu separator to a menu (strings not shown as BSTR for clarity)
bRet = iSldWorks.AddMenuItem3(swDocNONE, iCookie, "@subMenuString@menuString", -1,
"ExistingCallBackThatDoesNothing", "", "", "", "")
```

Remarks

For information about using this method with the [ISwAddin](#) object, see [Using ISwAddin to Create a SOLIDWORKS Add-in](#).

The bitmap must be 16w x 16h x 256 colors.

You can add a new menu to any one of the four frames (main, part, assembly, or drawing). To do this, call this method with the appropriate argument in the DocumentType parameter. For example, if you want your menu to be available when a part document is active, then call this method and pass swDocPART as the first argument. After you have added your menu to the part frame, you do not need to do it again during the current SOLIDWORKS Design session. Once a part document is activated by the user, SOLIDWORKS Design automatically displays your menu item.

To add a menu separator:

- leave the text for the menu item blank, so that the menu string for the MenuItem argument starts with the at-sign symbol (@):

"@subMenuString@menuString"

- specify an existing method for the MenuCallback argument. This method is never called, so its implementation can be empty.
- specify empty strings for the MenuEnableMethod, HintString, and bitmapFilePath arguments.

See Also

[ISldWorks Interface](#)
[ISldWorks Members](#)
[ISldWorks::AddMenu Method](#)
[ISldWorks::AddMenuItem2 Method](#)
[ISldWorks::AddToolBar4 Method](#)
[ISldWorks::RemoveMenu Method](#)
[ISldWorks::RemoveFromMenu Method](#)
[ISldWorks::RemoveFromPopupMenu Method](#)
[ISldWorks::RemoveMenuItem2 Method](#)
[ISldWorks::RemoveToolBar2 Method](#)
[ISldWorks::GetLocalizedMenuName Method](#)

Availability

AddMenuItem4 Method (ISldWorks)

[See Also](#)[SolidWorks.Interop.sldworks Namespace](#) > [ISldWorks Interface](#) : AddMenuItem4 Method (ISldWorks)**Obsolete.** Superseded by [ISldWorks::AddMenuItem5](#).

.NET Syntax

Visual Basic (Declaration)

```

Function AddMenuItem4( _
    ByVal DocumentType As System.Integer, _
    ByVal Cookie As System.Integer, _
    ByVal MenuItem As System.String, _
    ByVal Position As System.Integer, _
    ByVal MenuCallback As System.String, _
    ByVal MenuEnableMethod As System.String, _
    ByVal HintString As System.String, _
    ByVal BitmapFilePath As System.String _
) As System.Integer

```

Visual Basic (Usage)



```

Dim instance As ISldWorks
Dim DocumentType As System.Integer
Dim Cookie As System.Integer
Dim MenuItem As System.String
Dim Position As System.Integer
Dim MenuCallback As System.String
Dim MenuEnableMethod As System.String
Dim HintString As System.String
Dim BitmapFilePath As System.String
Dim value As System.Integer

```

```

value = instance.AddMenuItem4(DocumentType, Cookie, MenuItem, Position, MenuCallback,
MenuEnableMethod, HintString, BitmapFilePath)

```

C#

```

System.int AddMenuItem4(
    System.int DocumentType,
    System.int Cookie,
    System.string MenuItem,
    System.int Position,
    System.string MenuCallback,
    System.string MenuEnableMethod,
    System.string HintString,
    System.string BitmapFilePath
)

```

C++/CLI

```

System.int AddMenuItem4(
    & System.int DocumentType,
    & System.int Cookie,
    & System.String^ MenuItem,
    & System.int Position,
    & System.String^ MenuCallback,
    & System.String^ MenuEnableMethod,
    & System.String^ HintString,
    & System.String^ BitmapFilePath
)

```

NOTE: See [Differences Between Unmanaged C++ and C++/CLI Code](#).

Parameters

*DocumentType*Document type to add the menu item as defined by [swDocumentTypes_e](#)

Cookie
Cookie as defined in [ISwAddin::ConnectToSW](#)
MenuItem

Menu string ("menuItem@menuString"); SOLIDWORKS Design creates menu items only if they do not already exist

NOTES:

- If you do not specify menuString, then the menu item appears on the Tools menu below the **Xpress Products** menu item.
- Use the & symbol to include an accelerator key, e.g., "MyItem@&File" adds MyItem to the File menu with an accelerator key. To display the accelerator key, press the Alt key. The accelerator key is underlined.

Position
Position where to add the new menu item; the first item is at position 0; if -1 is specified for Position, then the new menu item is added to the bottom of the list; this argument specifies the position of the menu item in relation to its immediate parent menu.

MenuCallback
Function to call when this menu item is selected (see **Remarks**)

MenuEnableMethod
Optional function that controls the state of the menu item (See **Remarks**)

- If specified:
- SOLIDWORKS Design calls this function before displaying the menu.
 - Display of the menu item is controlled by the return value of MenuEnableMethod.

If MenuEnableMethod returns...	Then SOLIDWORKS Design...
0	Deselects and disables the menu item
1	Deselects and enables the menu item; this is the default menu state if no update function is specified
2	Selects and disables the menu item
3	Selects and enables the menu item

HintString
Text to show in the SOLIDWORKS Design status bar when the user moves the pointer over this menu item; if you specify HintString, then it must be preceded by a comma

BitmapFilePath
Path and filename of bitmap

Return Value
Runtime command ID if successful, -1 if unsuccessful

 Visual Basic for Applications (VBA) Syntax

See [SldWorks::AddMenuItem4](#).

 Remarks

See [Add-in Callback and Enable Methods](#) to learn how to specify MenuCallback and MenuEnableMethod.
For information about using this method with the [ISwAddin](#) object, see [Using ISwAddin to Create a SOLIDWORKS Add-in](#).
The bitmap must be 16w x 16h x 256 colors.

You can add a new menu item to any one of the four frames (main, part, assembly, or drawing). To do this, call this method with the appropriate argument in the DocumentType parameter. For example, if you want your menu item to be available when a part document is active, then call this method and pass swDocPART as the first argument. After you have added your menu item to the part frame, you do not need to do it again during the current SOLIDWORKS Design session. Once a part document is activated by the user, SOLIDWORKS Design automatically displays your menu item.

- To add a menu separator:
- leave the text for the menu item blank, so that the menu string for the MenuItem argument starts with the at-sign symbol (@):

"[@subMenuString@menuString](#)"
 - specify an existing method for the MenuCallback argument. This method is never called, so its implementation can be empty.
 - specify empty strings for the MenuEnableMethod, HintString, and bitmapFilePath arguments.

Read about [Add-in Shortcut Menus](#).

 See Also

[ISldWorks Interface](#)
[ISldWorks Members](#)
[ISldWorks::AddMenu Method](#)
[ISldWorks::AddMenuPopupMenu3 Method](#)

[ISldWorks::AddToolBar4 Method](#)
[ISldWorks::RemoveMenu Method](#)
[ISldWorks::RemoveFromMenu Method](#)
[ISldWorks::RemoveMenuPopupItem2 Method](#)
[ISldWorks::RemoveToolBar2 Method](#)
[ISldWorks::GetLocalizedMenuName Method](#)
[ISldWorks::RemoveFromPopupMenu Method](#)

Availability

SOLIDWORKS 2009 FCS, Revision Number 17.0

SOLIDWORKS API Help

[Send comments on this topic.](#)

AddMenuItem5 Method (ISldWorks)

[See Also](#) [Example](#)



[SolidWorks.Interop.sldworks Namespace](#) > [ISldWorks Interface](#) : AddMenuItem5 Method (ISldWorks)

Adds a menu item and image to the SOLIDWORKS Design user interface.

.NET Syntax

Visual Basic (Declaration)

```
Function AddMenuItem5( _  
    ByVal DocumentType As System.Integer, _  
    ByVal Cookie As System.Integer, _  
    ByVal MenuItem As System.String, _  
    ByVal Position As System.Integer, _  
    ByVal MenuCallback As System.String, _  
    ByVal MenuEnableMethod As System.String, _  
    ByVal HintString As System.String, _  
    ByVal ImageList As System.Object _  
    ) As System.Integer
```

Visual Basic (Usage)



```
Dim instance As ISldWorks  
Dim DocumentType As System.Integer  
Dim Cookie As System.Integer  
Dim MenuItem As System.String  
Dim Position As System.Integer  
Dim MenuCallback As System.String  
Dim MenuEnableMethod As System.String  
Dim HintString As System.String  
Dim ImageList As System.Object  
Dim value As System.Integer
```

```
value = instance.AddMenuItem5(DocumentType, Cookie, MenuItem, Position, MenuCallback,  
MenuEnableMethod, HintString, ImageList)
```

C#

```
System.int AddMenuItem5(  
    System.int DocumentType,  
    System.int Cookie,  
    System.string MenuItem,  
    System.int Position,  
    System.string MenuCallback,  
    System.string MenuEnableMethod,  
    System.string HintString,  
    System.object ImageList  
)
```

C++/CLI

```
System.int AddMenuItem5(  
& System.int DocumentType,  
& System.int Cookie,  
& System.String^ MenuItem,  
& System.int Position,
```

```
& System.String^ MenuCallback,
& System.String^ MenuEnableMethod,
& System.String^ HintString,
& System.Object^ ImageList
)
```

NOTE: See [Differences Between Unmanaged C++ and C++/CLI Code](#).

Parameters

DocumentType

Document type to which to add the menu item as defined by [swDocumentTypes_e](#)

Cookie

Cookie as defined in [ISwAddin::ConnectToSW](#)

MenuItem

Menu item string (e.g., "menuItem@menuString"); SOLIDWORKS Design creates menu items only if they do not already exist

NOTES:

- Specify the name of the menu for menuString (e.g., File, View, etc.) where you want your menu item to appear. If you do not specify menu string, then the menu item appears on the **Tools** menu below the **Xpress Products** menu item.
- To add your own menu to which to add this menu item, call [ISldWorks::AddMenu](#) and substitute the name of your menu for menuString.
- Use the & symbol to include an accelerator key, e.g., MyItem@, adds MyItem to the File menu with an accelerator key. To display the accelerator key, press the Alt key. The accelerator key is underlined.

Position

Position where to add the new menu item; the first item is position 0; if -1 is specified for Position, then the new menu item is added to the bottom of the list; this argument specifies the position of the menu item in relation to its immediate parent menu

MenuCallback

Function to call when this menu item is selected (see **Remarks**)

MenuEnableMethod

Optional function that controls the state of the menu item (See **Remarks**)

If specified:

- SOLIDWORKS Design calls this function before displaying the menu item
- display of the menu item is controlled by the return value of MenuEnableMethod

If MenuEnableMethod returns...	Then SOLIDWORKS Design...
0	Deselects and disables the menu item
1	Deselects and enables the menu item; this is the default menu state if no update function is specified
2	Selects and disables the menu item
3	Selects and enables the menu item

HintString

Text to show in the SOLIDWORKS Design status bar when the user moves the pointer over this menu item; if you specify HintString, then it must be preceded by a comma

ImageList

Array of strings for the paths for the image files for the menu item (see **Remarks**)

Return Value

Runtime command ID if successful or -1 if unsuccessful

Visual Basic for Applications (VBA) Syntax

See [SldWorks::AddMenuItem5](#).

Example

[Add Menu and Menu Item \(C#\)](#)

[Add Menu and Menu Item \(VB.NET\)](#)

Remarks

See [Add-in Callback and Enable Methods](#) to learn how to specify MenuCallback and MenuEnableMethod.

For information about using this method with the [ISwAddin](#) object, see [Using ISwAddin to Create a SOLIDWORKS Add-in](#).

You can add a new menu item to any one of the four frames (main, part, assembly, or drawing). To do this, call this method with the appropriate argument in the swDocumentTypes_e.DocumentType parameter. For example, if you want your menu item to be available when a part document is active, then call this method and pass swDocumentTypes_e.swDocPART as the first argument. After you adding your menu item to the part frame, you do not need to do it again during the current SOLIDWORKS Design session. Once a part document is activated by the user, SOLIDWORKS Design automatically displays your menu item.

This method supports scaling for high resolution screens with high resolution operating system scaling options.

ImageList images can be:

- 20 x 20 pixels
- 32 x 32 pixels
- 40 x 40 pixels
- 64 x 64 pixels
- 96 x 96 pixels
- 128 x128 pixels

Images should use 256-color palette.

To add a menu item separator:

- leave the text for the menu item blank, so that the menu string for the MenuItem argument starts with the at-sign symbol (@):

"@submenuString@menuString"

- specify an existing method for the MenuCallback argument. This method is never called, so its implementation can be empty.
- specify empty strings for MenuEnableMethod and HintString.
- specify Nothing or null for ImageList.

Read [Add-in Shortcut Menus](#) for more information.

See Also

[ISldWorks Interface](#)
[ISldWorks Members](#)
[ISldWorks::AddMenuPopupItem4 Method \(\)](#)
[ISldWorks::AddToolBar5 Method \(\)](#)
[ISldWorks::GetLocalizedMenuName Method \(\)](#)
[ISldWorks::RemoveFromMenu Method \(\)](#)
[ISldWorks::RemoveFromPopupMenu Method \(\)](#)
[ISldWorks::RemoveItemFromThirdPartyPopupMenu Method \(\)](#)
[ISldWorks::RemoveMenu Method \(\)](#)
[ISldWorks::RemoveMenuPopupItem2 Method \(\)](#)
[ISldWorks::RemoveToolBar2 Method \(\)](#)
[ISldWorks::GetImageSize Method \(\)](#)

Availability

SOLIDWORKS 2016 FCS, Revision Number 24.0

SOLIDWORKS API Help

[Send comments on this topic.](#)

AddMenuPopupItem Method (ISldWorks)

[See Also](#)



[SolidWorks.Interop.sldworks Namespace](#) > [ISldWorks Interface](#) : AddMenuPopupItem Method (ISldWorks)

Obsolete. Superseded by [ISldWorks::AddMenuPopupItem2](#).

.NET Syntax

Visual Basic (Declaration)

```
Function AddMenuPopupItem( _  
    ByVal DocType As System.Integer, _  
    ByVal SelType As System.Integer, _  
    ByVal Item As System.String, _  
    ByVal CallbackFcnAndModule As System.String, _  
    ByVal CustomNames As System.String _  
    ) As System.Integer
```

Visual Basic (Usage)

```
Dim instance As ISldWorks  
Dim DocType As System.Integer  
Dim SelType As System.Integer  
Dim Item As System.String  
Dim CallbackFcnAndModule As System.String  
Dim CustomNames As System.String  
Dim value As System.Integer  
  
value = instance.AddMenuPopupItem(DocType, SelType, Item, CallbackFcnAndModule, CustomNames)
```

C#

```
System.int AddMenuPopupItem(  
    System.int DocType,  
    System.int SelType,  
    System.string Item,  
    System.string CallbackFcnAndModule,  
    System.string CustomNames  
)
```

C++/CLI

```
System.int AddMenuPopupItem(  
& System.int DocType,  
& System.int SelType,  
& System.String^ Item,  
& System.String^ CallbackFcnAndModule,  
& System.String^ CustomNames  
)
```

NOTE: See [Differences Between Unmanaged C++ and C++/CLI Code](#).

Parameters

DocType

SelType

Item

CallbackFcnAndModule

CustomNames

Visual Basic for Applications (VBA) Syntax

See [SldWorks::AddMenuPopupItem](#).

See Also

[ISldWorks Interface](#)
[ISldWorks Members](#)