

# SOLIDWORKS API (.NET, VBA, C#) — Reference

## (282/337): ISldWorks (part 2 of 8)

SOLIDWORKS API Documentation (converted from CHM)

## ISldWorks (part 2 of 8) (Type)

SOLIDWORKS API Help

[Send comments](#) on this topic.

### AddMenuPopupItem2 Method (ISldWorks)

[See Also](#)



[SolidWorks.Interop.sldworks Namespace](#) > [ISldWorks Interface](#) : AddMenuPopupItem2 Method (ISldWorks)

Obsolete. Superseded by [ISldWorks::AddMenuPopupItem3](#) and [ISldWorks::AddMenuPopupItem4](#).

#### .NET Syntax

##### Visual Basic (Declaration)

```
Function AddMenuPopupItem2( _  
    ByVal DocumentType As System.Integer, _  
    ByVal Cookie As System.Integer, _  
    ByVal SelectType As System.Integer, _  
    ByVal PopupItemName As System.String, _  
    ByVal MenuCallback As System.String, _  
    ByVal MenuEnableMethod As System.String, _  
    ByVal HintString As System.String, _  
    ByVal CustomNames As System.String _  
) As System.Boolean
```

##### Visual Basic (Usage)



```
Dim instance As ISldWorks  
Dim DocumentType As System.Integer  
Dim Cookie As System.Integer  
Dim SelectType As System.Integer  
Dim PopupItemName As System.String  
Dim MenuCallback As System.String  
Dim MenuEnableMethod As System.String  
Dim HintString As System.String  
Dim CustomNames As System.String  
Dim value As System.Boolean
```

```
value = instance.AddMenuPopupItem2(DocumentType, Cookie, SelectType, PopupItemName, MenuCallback,  
MenuEnableMethod, HintString, CustomNames)
```

##### C#

```
System.bool AddMenuPopupItem2(  
    System.int DocumentType,  
    System.int Cookie,  
    System.int SelectType,  
    System.string PopupItemName,  
    System.string MenuCallback,  
    System.string MenuEnableMethod,  
    System.string HintString,  
    System.string CustomNames  
)
```

##### C++/CLI

```
System.bool AddMenuPopupItem2(  
& System.int DocumentType,  
& System.int Cookie,  
& System.int SelectType,  
& System.String^ PopupItemName,  
& System.String^ MenuCallback,  
& System.String^ MenuEnableMethod,  
& System.String^ HintString,  
& System.String^ CustomNames  
)
```

**NOTE:** See [Differences Between Unmanaged C++ and C++/CLI Code](#).

Parameters

*DocumentType*  
Document type as defined by [swDocumentTypes\\_e](#)

*Cookie*  
Cookie specified as defined in [ISwAddin::ConnectToSW](#)

*SelectType*  
Selection type as defined in [swSelectType\\_e](#)

*PopuPltemName*  
Description displayed on the shortcut menu

*MenuCallback*  
Function to be called when the user clicks your menu item (see description in [ISldWorks::AddMenuItem3](#))

*MenuEnableMethod*  
Optional function that controls the state of the menu item

If specified:

- SOLIDWORKS calls this function before displaying the menu
- Display of the menu item is controlled by the return value of MenuEnableMethod

| If your method returns... | Then SOLIDWORKS...                                                                                      |
|---------------------------|---------------------------------------------------------------------------------------------------------|
| 0                         | Deselects and disables the menu item.                                                                   |
| 1                         | Deselects and enables the menu item (this is the default menu state if no update function is specified) |
| 2                         | Selects and disables the menu item                                                                      |
| 3                         | Selects and enables the menu item                                                                       |
| 4                         | Hides the menu item                                                                                     |

*HintString*  
Text to show in the SOLIDWORKS status bar when the user moves their mouse over this menu item; if you specify a HintString, it must be preceded by a comma

*CustomNames*  
Semi-colon separated list of the names of the custom feature types; this argument is applicable only if SelectType is a custom feature type (like swSelATTRIBUTES); in the case of swSelATTRIBUTES, set this field to the name of the attribute definition

Return Value

True if the item was added, false if not

 Visual Basic for Applications (VBA) Syntax

See [SldWorks::AddMenuPopuPltem2](#).

 See Also

- [ISldWorks Interface](#)
- [ISldWorks Members](#)
- [ISldWorks::AddMenu\\_Method](#)
- [ISldWorks::AddToolBar4\\_Method](#)
- [ISldWorks::AddToolBarCommand2\\_Method](#)
- [ISldWorks::RemoveFromMenu\\_Method](#)
- [ISldWorks::RemoveFromPopupMenu\\_Method](#)
- [ISldWorks::RemoveMenu\\_Method](#)
- [ISldWorks::RemoveMenuPopuPltem2\\_Method](#)

 Availability

SOLIDWORKS 2003 FCS, Revision Number 11.0

SOLIDWORKS API Help

[Send comments on this topic.](#)

AddMenuPopuPltem3 Method (ISldWorks)

[See Also](#)



[SolidWorks.Interop.sldworks Namespace](#) > [ISldWorks Interface](#) : AddMenuPopuPltem3 Method (ISldWorks)

Adds a menu item and zero or more submenus to shortcut menus of entities of the specified type in documents of the specified type.

 .NET Syntax

Visual Basic (Declaration)

```

Function AddMenuPopupItem3( _
    ByVal DocumentType As System.Integer, _
    ByVal Cookie As System.Integer, _
    ByVal SelectType As System.Integer, _
    ByVal PopupItemName As System.String, _
    ByVal MenuCallback As System.String, _
    ByVal MenuEnableMethod As System.String, _
    ByVal HintString As System.String, _
    ByVal CustomNames As System.String _
) As System.Integer

```

Visual Basic (Usage)



```

Dim instance As ISldWorks
Dim DocumentType As System.Integer
Dim Cookie As System.Integer
Dim SelectType As System.Integer
Dim PopupItemName As System.String
Dim MenuCallback As System.String
Dim MenuEnableMethod As System.String
Dim HintString As System.String
Dim CustomNames As System.String
Dim value As System.Integer

```

```

value = instance.AddMenuPopupItem3(DocumentType, Cookie, SelectType, PopupItemName, MenuCallback,
MenuEnableMethod, HintString, CustomNames)

```

C#

```

System.int AddMenuPopupItem3(
    System.int DocumentType,
    System.int Cookie,
    System.int SelectType,
    System.string PopupItemName,
    System.string MenuCallback,
    System.string MenuEnableMethod,
    System.string HintString,
    System.string CustomNames
)

```

C++/CLI

```

System.int AddMenuPopupItem3(
    & System.int DocumentType,
    & System.int Cookie,
    & System.int SelectType,
    & System.String^ PopupItemName,
    & System.String^ MenuCallback,
    & System.String^ MenuEnableMethod,
    & System.String^ HintString,
    & System.String^ CustomNames
)

```

**NOTE:** See [Differences Between Unmanaged C++ and C++/CLI Code](#).

#### Parameters

*DocumentType*

Document type as defined by [swDocumentTypes\\_e](#)

*Cookie*

Cookie specified as defined in [ISwAddin::ConnectToSW](#)

*SelectType*

Selection type as defined in [swSelectType\\_e](#)

*PopupItemName*

Description displayed on the shortcut menu (see **Remarks**)

*MenuCallback*

Function to be called when the user clicks your menu item (see description in [ISldWorks::AddMenuItem4](#)) (see **Remarks**)

*MenuEnableMethod*

Optional function that controls the state of the menu item

If specified:

- SOLIDWORKS calls this function before displaying the menu
- Display of the menu item is controlled by the return value of MenuEnableMethod

| If your method returns... | Then SOLIDWORKS...                                                                                      |
|---------------------------|---------------------------------------------------------------------------------------------------------|
| 0                         | Deselects and disables the menu item.                                                                   |
| 1                         | Deselects and enables the menu item (this is the default menu state if no update function is specified) |
| 2                         | Selects and disables the menu item                                                                      |
| 3                         | Selects and enables the menu item                                                                       |
| 4                         | Hides the menu item                                                                                     |

(See **Remarks**)  
*HintString*  
Text to show in the SOLIDWORKS status bar when the user moves their mouse over this menu item; if you specify a HintString, it must be preceded by a comma  
*CustomNames*  
Semi-colon separated list of the names of the custom feature types; this argument is applicable only if SelectType is a custom feature type (like swSelATTRIBUTES); in the case of swSelATTRIBUTES, set this field to the name of the attribute definition

**Return Value**  
SOLIDWORKS runtime command ID or -1 if the method fails

 **Visual Basic for Applications (VBA) Syntax**

See [SldWorks::AddMenuPopupItem3](#)

 **Remarks**

Call this method for every unique set of DocumentType and SelectType in whose menus you want this menu item to display.  
In PopupItemName use the at-sign (@) to create submenus. To add a separator bar after a menu item, append an at-sign to PopupItemName and enclose PopupItemName in double quotes ("").  
For example, specifying:

- **Edge** adds menu item **Edge** to the shortcut menu.
- **Edge@Color** adds menu item **Edge** to the shortcut menu and submenu **Color** to **Edge**.
- **Edge@Appearance@Color** adds menu item **Edge** to the shortcut menu, submenu **Appearance** to **Edge**, and submenu **Color** to **Appearance**.
- **"Edge@"** adds menu item **Edge** to the shortcut menu and a separator bar after **Edge**.
- **"Edge@Appearance@"** adds menu item **Edge** to the shortcut menu, submenu **Appearance** to **Edge**, and a separator bar after **Appearance**.

See [Add-in Callback and Enable Methods](#) to learn how to specify MenuCallback and MenuEnableMethod.

 **See Also**

[ISldWorks Interface](#)  
[ISldWorks Members](#)  
[ISldWorks::AddMenu Method](#)  
[ISldWorks::AddToolBar4 Method](#)  
[ISldWorks::AddToolBarCommand2 Method](#)  
[ISldWorks::RemoveFromMenu Method](#)  
[ISldWorks::RemoveMenu Method](#)  
[ISldWorks::RemoveMenuPopupItem2 Method](#)

 **Availability**

SOLIDWORKS 2009 FCS, Revision Number 17.0

SOLIDWORKS API Help [Send comments on this topic.](#)

**AddMenuPopupItem4 Method (ISldWorks)**

[See Also](#)



[SolidWorks.Interop.sldworks Namespace](#) > [ISldWorks Interface](#) : AddMenuPopupItem4 Method (ISldWorks)

Adds a menu item and zero or more submenus to shortcut menus of features of the specified type in documents of the specified type.

 **.NET Syntax**

[Visual Basic \(Declaration\)](#)

```

Function AddMenuPopupItem4( _
    ByVal DocumentType As System.Integer, _
    ByVal Cookie As System.Integer, _
    ByVal SelectType As System.String, _
    ByVal PopupItemName As System.String, _
    ByVal MenuCallback As System.String, _
    ByVal MenuEnableMethod As System.String, _
    ByVal HintString As System.String, _
    ByVal CustomNames As System.String _
) As System.Integer

```

Visual Basic (Usage)



```

Dim instance As ISldWorks
Dim DocumentType As System.Integer
Dim Cookie As System.Integer
Dim SelectType As System.String
Dim PopupItemName As System.String
Dim MenuCallback As System.String
Dim MenuEnableMethod As System.String
Dim HintString As System.String
Dim CustomNames As System.String
Dim value As System.Integer

```

```

value = instance.AddMenuPopupItem4(DocumentType, Cookie, SelectType, PopupItemName, MenuCallback,
MenuEnableMethod, HintString, CustomNames)

```

C#

```

System.int AddMenuPopupItem4(
    System.int DocumentType,
    System.int Cookie,
    System.string SelectType,
    System.string PopupItemName,
    System.string MenuCallback,
    System.string MenuEnableMethod,
    System.string HintString,
    System.string CustomNames
)

```

C++/CLI

```

System.int AddMenuPopupItem4(
    & System.int DocumentType,
    & System.int Cookie,
    & System.String^ SelectType,
    & System.String^ PopupItemName,
    & System.String^ MenuCallback,
    & System.String^ MenuEnableMethod,
    & System.String^ HintString,
    & System.String^ CustomNames
)

```

**NOTE:** See [Differences Between Unmanaged C++ and C++/CLI Code](#).

#### Parameters

*DocumentType*

Document type as defined by [swDocumentTypes\\_e](#)

*Cookie*

Cookie as defined in [ISwAddin::ConnectToSW](#)

*SelectType*

Selection type as returned by [IFeature::GetTypeNames2](#) (see **Remarks**)

*PopupItemName*

Description displayed on the shortcut menu (see **Remarks**)

*MenuCallback*

Function to call when this menu item is selected (see **Remarks**)

*MenuEnableMethod*

Optional function that controls the state of the menu item

If specified:

- SOLIDWORKS calls this function before displaying the menu
- Display of the menu item is controlled by the return value of MenuEnableMethod

| If MenuEnableMethod returns... | Then SOLIDWORKS...                                                                                      |
|--------------------------------|---------------------------------------------------------------------------------------------------------|
| 0                              | Deselects and disables the menu item                                                                    |
| 1                              | Deselects and enables the menu item (this is the default menu state if no update function is specified) |
| 2                              | Selects and disables the menu item                                                                      |
| 3                              | Selects and enables the menu item                                                                       |
| 4                              | Hides the menu item                                                                                     |

(see **Remarks**)  
*HintString*  
Text to show in the SOLIDWORKS status bar when the user moves a mouse over this menu item  
*CustomNames*  
Semi-colon separated list of the names of the custom features; this argument is applicable only if SelectType is a custom feature type (like Attribute); in the case of Attribute, set this field to a list of attribute definitions

**Return Value**

SOLIDWORKS runtime command ID or -1 if the method fails

 **Visual Basic for Applications (VBA) Syntax**

See [ISldWorks::AddMenuPopupItem4](#)

 **Remarks**

Call this method for every unique set of DocumentType and SelectType in whose menus you want this menu item to display.

For SelectTypes that are macro features, components, faces, edges or other non-feature entities, use [ISldWorks::AddMenuPopupItem3](#) instead of this method.

In PopupiltemName use the at-sign (@) to create submenus. To add a separator bar after a menu item, append an at-sign to PopupiltemName and enclose PopupiltemName in double quotes ("").

For example, specifying:

- **Feature** adds menu item **Feature** to the shortcut menu.
- **Feature@Color** adds menu item **Feature** to the shortcut menu and submenu **Color** to **Feature**.
- **Feature@Appearance@Color** adds menu item **Feature** to the shortcut menu, submenu **Appearance** to **Feature**, and submenu **Color** to **Appearance**.
- **"Feature@"** adds menu item **Feature** to the shortcut menu and a separator bar after **Feature**.
- **"Feature@Appearance@"** adds menu item **Feature** to the shortcut menu, submenu **Appearance** to **Feature**, and a separator bar after **Appearance**.

See [Add-in Callback and Enable Methods](#) to learn how to specify MenuCallback and MenuEnableMethod.

 **See Also**

[ISldWorks Interface](#)  
[ISldWorks Members](#)  
[ISldWorks::AddMenu Method](#)  
[ISldWorks::AddToolBar4 Method](#)  
[ISldWorks::AddToolBarCommand2 Method](#)  
[ISldWorks::RemoveFromMenu Method](#)  
[ISldWorks::RemoveMenuPopupiltem2 Method](#)  
[ISldWorks::RemoveMenu Method](#)

 **Availability**

SOLIDWORKS 2011 FCS, Revision Number 19.0



## .NET Syntax

### Visual Basic (Declaration)

```
Function AddToolbar( _  
    ByVal ModuleName As System.String, _  
    ByVal Title As System.String, _  
    ByVal SmallBitmapHandle As System.Integer, _  
    ByVal LargeBitmapHandle As System.Integer _  
) As System.Integer
```

### Visual Basic (Usage)



```
Dim instance As ISldWorks  
Dim ModuleName As System.String  
Dim Title As System.String  
Dim SmallBitmapHandle As System.Integer  
Dim LargeBitmapHandle As System.Integer  
Dim value As System.Integer  
  
value = instance.AddToolbar(ModuleName, Title, SmallBitmapHandle, LargeBitmapHandle)
```

### C#

```
System.int AddToolbar(  
    System.string ModuleName,  
    System.string Title,  
    System.int SmallBitmapHandle,  
    System.int LargeBitmapHandle  
)
```

### C++/CLI

```
System.int AddToolbar(  
& System.String^ ModuleName,  
& System.String^ Title,  
& System.int SmallBitmapHandle,  
& System.int LargeBitmapHandle  
)
```

**NOTE:** See [Differences Between Unmanaged C++ and C++/CLI Code](#).

### Parameters

*ModuleName*

*Title*

*SmallBitmapHandle*

*LargeBitmapHandle*

## Visual Basic for Applications (VBA) Syntax

See [SldWorks::AddToolBar](#).

## See Also

[ISldWorks Interface](#)  
[ISldWorks Members](#)

SOLIDWORKS API Help

[Send comments on this topic.](#)

## AddToolBar2 Method (ISldWorks)

[See Also](#)



[SolidWorks.Interop.sldworks Namespace](#) > [ISldWorks Interface](#) : AddToolBar2 Method (ISldWorks)

Obsolete. Superseded by [ISldWorks::AddToolBar4](#).

## .NET Syntax

```

Function AddToolbar2( _
    ByVal ModuleNameIn As System.String, _
    ByVal TitleIn As System.String, _
    ByVal SmallBitmapHandleIn As System.Integer, _
    ByVal LargeBitmapHandleIn As System.Integer, _
    ByVal MenuPosIn As System.Integer, _
    ByVal DecTemplateTypeIn As System.Integer _
) As System.Integer

```



```

Dim instance As ISldWorks
Dim ModuleNameIn As System.String
Dim TitleIn As System.String
Dim SmallBitmapHandleIn As System.Integer
Dim LargeBitmapHandleIn As System.Integer
Dim MenuPosIn As System.Integer
Dim DecTemplateTypeIn As System.Integer
Dim value As System.Integer

value = instance.AddToolbar2(ModuleNameIn, TitleIn, SmallBitmapHandleIn, LargeBitmapHandleIn,
MenuPosIn, DecTemplateTypeIn)

```

```

System.int AddToolbar2(
    System.string ModuleNameIn,
    System.string TitleIn,
    System.int SmallBitmapHandleIn,
    System.int LargeBitmapHandleIn,
    System.int MenuPosIn,
    System.int DecTemplateTypeIn
)

```

```

System.int AddToolbar2(
    & System.String^ ModuleNameIn,
    & System.String^ TitleIn,
    & System.int SmallBitmapHandleIn,
    & System.int LargeBitmapHandleIn,
    & System.int MenuPosIn,
    & System.int DecTemplateTypeIn
)

```

**NOTE:** See [Differences Between Unmanaged C++ and C++/CLI Code](#).

#### Parameters

*ModuleNameIn*

*TitleIn*

*SmallBitmapHandleIn*

*LargeBitmapHandleIn*

*MenuPosIn*

*DecTemplateTypeIn*

## Visual Basic for Applications (VBA) Syntax

See [SldWorks::AddToolbar2](#).

## See Also

[ISldWorks Interface](#)  
[ISldWorks Members](#)

## AddToolbar3 Method (ISldWorks)

[See Also](#)



[SolidWorks.Interop.sldworks Namespace](#) > [ISldWorks Interface](#) : AddToolbar3 Method (ISldWorks)

Obsolete. Superseded by [ISldWorks::AddToolbar4](#).

### .NET Syntax

Visual Basic (Declaration)

```
Function AddToolbar3( _  
    ByVal Cookie As System.Integer, _  
    ByVal Title As System.String, _  
    ByVal SmallBitmapResourceID As System.Integer, _  
    ByVal LargeBitmapResourceID As System.Integer, _  
    ByVal MenuPositionForToolbar As System.Integer, _  
    ByVal DocumentType As System.Integer _  
) As System.Integer
```

Visual Basic (Usage)



```
Dim instance As ISldWorks  
Dim Cookie As System.Integer  
Dim Title As System.String  
Dim SmallBitmapResourceID As System.Integer  
Dim LargeBitmapResourceID As System.Integer  
Dim MenuPositionForToolbar As System.Integer  
Dim DocumentType As System.Integer  
Dim value As System.Integer  
  
value = instance.AddToolbar3(Cookie, Title, SmallBitmapResourceID, LargeBitmapResourceID,  
MenuPositionForToolbar, DocumentType)
```

C#

```
System.int AddToolbar3(  
    System.int Cookie,  
    System.string Title,  
    System.int SmallBitmapResourceID,  
    System.int LargeBitmapResourceID,  
    System.int MenuPositionForToolbar,  
    System.int DocumentType  
)
```

C++/CLI

```
System.int AddToolbar3(  
& System.int Cookie,  
& System.String^ Title,  
& System.int SmallBitmapResourceID,  
& System.int LargeBitmapResourceID,  
& System.int MenuPositionForToolbar,  
& System.int DocumentType  
)
```

**NOTE:** See [Differences Between Unmanaged C++ and C++/CLI Code](#).

#### Parameters

*Cookie*

*Title*

*SmallBitmapResourceID*

*LargeBitmapResourceID*

*MenuPositionForToolbar*

*DocumentType*

### Visual Basic for Applications (VBA) Syntax

See [ISldWorks::AddToolBar3](#).

## See Also

[ISldWorks Interface](#)  
[ISldWorks Members](#)

SOLIDWORKS API Help

[Send comments](#) on this topic.

## AddToolBar4 Method (ISldWorks)

[See Also](#) [Example](#)



[SolidWorks.Interop.sldworks Namespace](#) > [ISldWorks Interface](#) : AddToolBar4 Method (ISldWorks)

Obsolete. Superseded by [ISldWorks::AddToolBar5](#).

## .NET Syntax

### Visual Basic (Declaration)

```
Function AddToolBar4( _  
    ByVal Cookie As System.Integer, _  
    ByVal Title As System.String, _  
    ByVal SmallBitmapImage As System.String, _  
    ByVal LargeBitmapImage As System.String, _  
    ByVal MenuPositionForToolbar As System.Integer, _  
    ByVal DocumentType As System.Integer _  
) As System.Integer
```

### Visual Basic (Usage)



```
Dim instance As ISldWorks  
Dim Cookie As System.Integer  
Dim Title As System.String  
Dim SmallBitmapImage As System.String  
Dim LargeBitmapImage As System.String  
Dim MenuPositionForToolbar As System.Integer  
Dim DocumentType As System.Integer  
Dim value As System.Integer  
  
value = instance.AddToolBar4(Cookie, Title, SmallBitmapImage, LargeBitmapImage,  
MenuPositionForToolbar, DocumentType)
```

### C#

```
System.int AddToolBar4(  
    System.int Cookie,  
    System.string Title,  
    System.string SmallBitmapImage,  
    System.string LargeBitmapImage,  
    System.int MenuPositionForToolbar,  
    System.int DocumentType  
)
```

### C++/CLI

```
System.int AddToolBar4(  
& System.int Cookie,  
& System.String^ Title,  
& System.String^ SmallBitmapImage,  
& System.String^ LargeBitmapImage,  
& System.int MenuPositionForToolbar,  
& System.int DocumentType  
)
```

**NOTE:** See [Differences Between Unmanaged C++ and C++/CLI Code](#).

### Parameters

*Cookie*

Resource ID of the toolbar; this is the same cookie that you specified in [ISwAddin::ConnectToSW](#)

*Title*

Title of the toolbar

*SmallBitmapImage*

Bitmap file to use for the small bitmap for the toolbar (see **Remarks**)

*LargeBitmapImage*

Bitmap file to use for the large bitmap for the toolbar (see **Remarks**)

*MenuPositionForToolbar*

Not used (SOLIDWORKS always puts toolbar names in alphabetical order)

*DocumentType*

Bitwise values indicating what frame window types should have this toolbar's name added to the **View > Toolbars** menu; values from [swDocTemplateTypes\\_e](#)

**Return Value**

Toolbar ID for use with other methods or -1 if not created

## Visual Basic for Applications (VBA) Syntax

See [ISldWorks::AddToolBar4](#).

## Example

[Create Toolbars \(C++\)](#).

## Remarks

For information about using this method with the [ISwAddin](#) object, see [Using ISwAddin to Create a SOLIDWORKS Add-in](#).

This method:

- Only operates properly when the application is implemented as a DLL and not as an .exe.
- Adds the toolbar name to the **View > Toolbars** menu.
- Only creates the toolbar and passes the image for the buttons to SOLIDWORKS. To add functionality, use [ISldWorks::AddToolBarCommand2](#).

The bitmap images should contain the bitmaps for each of the buttons, including separators, in the toolbar as a single bitmap. For a small bitmap the image for each button must be 16x16; for a large bitmap, it must be 24x24. The bitmaps should use a 256-color palette.

If either SmallBitmapImage or LargeBitmapImage is null or empty, then the provided image is scaled to create the appropriately sized bitmap for the other argument.

### NOTES:

- When your add-in is unloaded, you must call [ISldWorks::RemoveToolBar2](#) to remove this toolbar.
- If you want the toolbar to show up in specific locations only, do not use the now obsolete ISldWorks::ShowToolBar2 method. If your application uses that method, your application ignores the DocumentType argument. ISldWorks::ShowToolBar2 assumes that the application is controlling the visibility state of the toolbar, and not the user. This means that the toolbar will be available in all locations.

## See Also

[ISldWorks Interface](#)  
[ISldWorks Members](#)  
[ISldWorks::AddMenu Method](#)  
[ISldWorks::AddMenuItem3 Method](#)  
[ISldWorks::AddMenuItem2 Method](#)  
[ISldWorks::RemoveFromMenu Method](#)  
[ISldWorks::RemoveMenuItem2 Method](#)  
[ISldWorks::DragToolBarButton Method](#)  
[ISldWorks::GetToolBarDock2 Method](#)  
[ISldWorks::GetToolBarState2 Method](#)  
[ISldWorks::HideToolBar2 Method](#)  
[ISldWorks::SetToolBarDock2 Method](#)

## Availability

SOLIDWORKS 2004 FCS, Revision Number 12.0

SOLIDWORKS API Help

[Send comments on this topic.](#)

## AddToolBar5 Method (ISldWorks)

[See Also](#) [Example](#)



[SolidWorks.Interop.sldworks Namespace](#) > [ISldWorks Interface](#) : AddToolBar5 Method (ISldWorks)

Creates a Windows-style dockable toolbar.

## .NET Syntax

```

Function AddToolbar5( _
    ByVal Cookie As System.Integer, _
    ByVal Title As System.String, _
    ByVal ImageList As System.Object, _
    ByVal MenuPositionForToolbar As System.Integer, _
    ByVal DocumentType As System.Integer _
) As System.Integer

```



```

Dim instance As ISldWorks
Dim Cookie As System.Integer
Dim Title As System.String
Dim ImageList As System.Object
Dim MenuPositionForToolbar As System.Integer
Dim DocumentType As System.Integer
Dim value As System.Integer

value = instance.AddToolbar5(Cookie, Title, ImageList, MenuPositionForToolbar, DocumentType)

```

```

System.int AddToolbar5(
    System.int Cookie,
    System.string Title,
    System.object ImageList,
    System.int MenuPositionForToolbar,
    System.int DocumentType
)

```

```

System.int AddToolbar5(
    & System.int Cookie,
    & System.String^ Title,
    & System.Object^ ImageList,
    & System.int MenuPositionForToolbar,
    & System.int DocumentType
)

```

**NOTE:** See [Differences Between Unmanaged C++ and C++/CLI Code](#).

#### Parameters

*Cookie*

Resource ID of the toolbar; this is the same cookie that you specified in [ISwAddin::ConnectToSW](#)

*Title*

Title of the toolbar

*ImageList*

Array of strings of the paths for the icons for the toolbar (see **Remarks**)

*MenuPositionForToolbar*

Not used (SOLIDWORKS always puts toolbar names in alphabetical order)

*DocumentType*

Bitwise values indicating what frame window types should have this toolbar's name added to the **View > Toolbars** menu; values from [swDocTemplateTypes\\_e](#)

#### Return Value

Toolbar ID for use with other methods or -1 if not created

### Visual Basic for Applications (VBA) Syntax

See [SldWorks::AddToolbar5](#).

### Example

[Add Toolbars \(C#\)](#)  
[Add Toolbars \(VB.NET\)](#)

### Remarks

For information about using this method with the [ISwAddin](#) object, see [Using ISwAddin to Create a SOLIDWORKS Add-in](#).

This method:

- only operates properly when the application is implemented as a **.dll** and not as an **.exe**.
- adds the toolbar name to the **View > Toolbars** menu.
- only creates the toolbar and passes the images for the icons to SOLIDWORKS. To add functionality, use [ISldWorks::AddToolbarCommand2](#).
- supports scaling for high resolution screens with high resolution operating system scaling options.

ImageList icons can be:

- 20 x 20 pixels
- 32 x 32 pixels
- 40 x 40 pixels
- 64 x 64 pixels
- 96 x 96 pixels
- 128 x 128 pixels

Each image file (**.bmp** or **.png**) should contain all of the same-size icons for the toolbar buttons and separators. For example:



Each icon strip should use a 256-color palette.

#### NOTES:

- When your add-in is unloaded, you must call [ISldWorks::RemoveToolbar2](#) to remove this toolbar.
- If you want the toolbar to show up in specific locations only, do not use the now obsolete [ISldWorks::ShowToolbar2](#) method. If your application uses that method, your application ignores the `DocumentType` argument. [ISldWorks::ShowToolbar2](#) assumes that the application is controlling the visibility state of the toolbar, and not the user. This means that the toolbar will be available in all locations.

#### See Also

[ISldWorks Interface](#)  
[ISldWorks Members](#)  
[ISldWorks::AddMenu Method \(\)](#)  
[ISldWorks::DragToolbarButton Method \(\)](#)  
[ISldWorks::DragToolbarButtonFromCommandID Method \(\)](#)  
[ISldWorks::GetButtonPosition Method \(\)](#)  
[ISldWorks::GetToolbarDock2 Method \(\)](#)  
[ISldWorks::GetToolbarState2 Method \(\)](#)  
[ISldWorks::GetToolbarVisibility Method \(\)](#)  
[ISldWorks::HideToolbar2 Method \(\)](#)  
[ISldWorks::RemoveFromMenu Method \(\)](#)  
[ISldWorks::SetToolbarDock2 Method \(\)](#)  
[ISldWorks::SetToolbarVisibility Method \(\)](#)  
[ISldWorks::GetImageSize Method \(\)](#)

#### Availability

SOLIDWORKS 2016 FCS, Revision Number 24.0

SOLIDWORKS API Help

[Send comments on this topic.](#)

## AddToolbarCommand Method (ISldWorks)

[See Also](#)



[SolidWorks.Interop.sldworks Namespace](#) > [ISldWorks Interface](#) : AddToolbarCommand Method (ISldWorks)

Obsolete. Superseded by [ISldWorks::AddToolbarCommand2](#).

#### .NET Syntax

Visual Basic (Declaration)

```
Function AddToolbarCommand( _  
    ByVal ModuleName As System.String, _  
    ByVal ToolbarId As System.Integer, _  
    ByVal ToolbarIndex As System.Integer, _  
    ByVal CommandString As System.String _  
) As System.Boolean
```

Visual Basic (Usage)

```
Dim instance As ISldWorks  
Dim ModuleName As System.String  
Dim ToolbarId As System.Integer  
Dim ToolbarIndex As System.Integer  
Dim CommandString As System.String  
Dim value As System.Boolean
```



```
value = instance.AddToolBarCommand(ModuleName, ToolbarId, ToolbarIndex, CommandString)
```

C#

```
System.bool AddToolBarCommand(  
    System.string ModuleName,  
    System.int ToolbarId,  
    System.int ToolbarIndex,  
    System.string CommandString  
)
```

C++/CLI

```
System.bool AddToolBarCommand(  
    & System.String^ ModuleName,  
    & System.int ToolbarId,  
    & System.int ToolbarIndex,  
    & System.String^ CommandString  
)
```

**NOTE:** See [Differences Between Unmanaged C++ and C++/CLI Code](#).

#### Parameters

*ModuleName*

*ToolbarId*

*ToolbarIndex*

*CommandString*

### Visual Basic for Applications (VBA) Syntax

See [SldWorks::AddToolBarCommand](#).

### See Also

[ISldWorks Interface](#)  
[ISldWorks Members](#)

SOLIDWORKS API Help

[Send comments on this topic.](#)

## AddToolBarCommand2 Method (ISldWorks)

[See Also](#) [Example](#)



[SolidWorks.Interop.sldworks Namespace](#) > [ISldWorks Interface](#) : AddToolBarCommand2 Method (ISldWorks)

Specifies the application functions to call when a toolbar button is clicked or sets a separator.

### .NET Syntax

Visual Basic (Declaration)

```
Function AddToolBarCommand2( _  
    ByVal Cookie As System.Integer, _  
    ByVal ToolbarId As System.Integer, _  
    ByVal ToolbarIndex As System.Integer, _  
    ByVal ButtonCallback As System.String, _  
    ByVal ButtonEnableMethod As System.String, _  
    ByVal ToolTip As System.String, _  
    ByVal HintString As System.String _  
) As System.Boolean
```

Visual Basic (Usage)

```
Dim instance As ISldWorks  
Dim Cookie As System.Integer  
Dim ToolbarId As System.Integer  
Dim ToolbarIndex As System.Integer  
Dim ButtonCallback As System.String
```



```
Dim ButtonEnableMethod As System.String
Dim ToolTip As System.String
Dim HintString As System.String
Dim value As System.Boolean
```

```
value = instance.AddToolBarCommand2(Cookie, ToolbarId, ToolbarIndex, ButtonCallback,
ButtonEnableMethod, ToolTip, HintString)
```

C#

```
System.bool AddToolBarCommand2(
    System.int Cookie,
    System.int ToolbarId,
    System.int ToolbarIndex,
    System.string ButtonCallback,
    System.string ButtonEnableMethod,
    System.string ToolTip,
    System.string HintString
)
```

C++/CLI

```
System.bool AddToolBarCommand2(
    & System.int Cookie,
    & System.int ToolbarId,
    & System.int ToolbarIndex,
    & System.String^ ButtonCallback,
    & System.String^ ButtonEnableMethod,
    & System.String^ ToolTip,
    & System.String^ HintString
)
```

**NOTE:** See [Differences Between Unmanaged C++ and C++/CLI Code](#).

#### Parameters

*Cookie*

Resource ID of the toolbar; this is the same cookie that you specified in [ISwAddin::ConnectToSW](#)

*ToolbarId*

Toolbar ID from [ISldWorks::AddToolbars](#)

*ToolbarIndex*

0-based index of the bitmap button

*ButtonCallback*

Function called when the user clicks the button (see **Remarks**)

*ButtonEnableMethod*

Function called to check whether the button should be enabled; typically used to check the type of object selected (see **Remarks**)

*ToolTip*

ToolTip for the toolbar button

*HintString*

Text that SOLIDWORKS Design displays in the status bar when the user moves their mouse over this toolbar button

#### Return Value

True if successful, false if unsuccessful

### Visual Basic for Applications (VBA) Syntax

See [SldWorks::AddToolBarCommand2](#).

### Example

[Create Toolbars \(C++\)](#)  
[Add Toolbars \(C#\)](#)  
[Add Toolbars \(VB.NET\)](#)

### Remarks

See [Add-in Callback and Enable Methods](#) to learn how to specify ButtonCallback and ButtonEnableMethod.

Call this method to specify the functions that get called by the SOLIDWORKS Design software when the button is pressed and to check if the button is enabled. Until this method is called, the SOLIDWORKS Design software does not display the button.

| If ButtonEnableMethod returns... | Then SOLIDWORKS Design...                                                                              |
|----------------------------------|--------------------------------------------------------------------------------------------------------|
| 0                                | Deselects and disables the menu item                                                                   |
| 1                                | Deselects and enables the menu item; this is the default menu state if no update function is specified |
| 2                                | Selects and disables the menu item                                                                     |
| 3                                | Selects and enables the menu item                                                                      |

To create a separator, all of the method's string parameters (ButtonCallback, ButtonEnableMethod, ToolTip, and HintString) must be blank strings. A bitmap button must still be defined in the add-in's resources, but it is not used.

## See Also

[ISldWorks Interface](#)  
[ISldWorks Members](#)  
[ISldWorks::AddMenu Method](#)  
[ISldWorks::AddMenuItem3 Method](#)  
[ISldWorks::AddMenuPopupItem2 Method](#)  
[ISldWorks::RemoveFromMenu Method](#)  
[ISldWorks::RemoveFromPopupMenu Method](#)  
[ISldWorks::RemoveMenu Method](#)  
[ISldWorks::RemoveMenuPopupItem2 Method](#)  
[ISldWorks::RemoveToolBar2 Method](#)  
[ISldWorks::DragToolBarButton Method](#)  
[ISldWorks::GetToolBarDock2 Method](#)  
[ISldWorks::GetToolBarState2 Method](#)  
[ISldWorks::HideToolBar2 Method](#)  
[ISldWorks::SetToolBarDock2 Method](#)

## Availability

SOLIDWORKS 2001Plus FCS, Revision Number 10.0

SOLIDWORKS API Help

[Send comments on this topic.](#)

## AllowFailedFeatureCreation Method (ISldWorks)

[See Also](#) [Example](#)



[SolidWorks.Interop.sldworks Namespace](#) > [ISldWorks Interface](#) : AllowFailedFeatureCreation Method (ISldWorks)

Sets whether to allow the creation of a feature that has rebuild errors.

## .NET Syntax

Visual Basic (Declaration)

```
Function AllowFailedFeatureCreation( _
    ByVal YesNo As System.Boolean _
) As System.Boolean
```

Visual Basic (Usage)



```
Dim instance As ISldWorks
Dim YesNo As System.Boolean
Dim value As System.Boolean

value = instance.AllowFailedFeatureCreation(YesNo)
```

C#

```
System.bool AllowFailedFeatureCreation(
    System.bool YesNo
)
```

C++/CLI

```
System.bool AllowFailedFeatureCreation(
    & System.bool YesNo
)
```

**NOTE:** See [Differences Between Unmanaged C++ and C++/CLI Code](#).

## Parameters

YesNo  
True if features are to be created regardless of rebuild errors, false if not

#### Return Value

The previous value, which is now replaced by the value for YesNo

### Visual Basic for Applications (VBA) Syntax

See [SldWorks::AllowFailedFeatureCreation](#).

### Example

[Create Feature With Invalid Geometry \(VBA\)](#)

### Remarks

By default, features are not created when invalid geometry is specified; however, after calling this method with YesNo set to True, the features are created but with rebuild errors.

### See Also

[ISldWorks Interface](#)  
[ISldWorks Members](#)

SOLIDWORKS API Help

[Send comments on this topic.](#)

## ApplicationType Property (ISldWorks)

[See Also](#)



[SolidWorks.Interop.sldworks Namespace](#) > [ISldWorks Interface](#) : ApplicationType Property (ISldWorks)

Gets the type of this SOLIDWORKS application.

### .NET Syntax

Visual Basic (Declaration)

ReadOnly Property ApplicationType As System.Integer

Visual Basic (Usage)



```
Dim instance As ISldWorks  
Dim value As System.Integer  
  
value = instance.ApplicationType
```

C#

```
System.int ApplicationType {get;}
```

C++/CLI

```
property System.int ApplicationType {  
    System.int get();  
}
```

**NOTE:** See [Differences Between Unmanaged C++ and C++/CLI Code](#).

#### Property Value

Type of application as defined by [swApplicationType\\_e](#)

### Visual Basic for Applications (VBA) Syntax

See [SldWorks::ApplicationType](#).

### See Also

[ISldWorks Interface](#)  
[ISldWorks Members](#)

## Availability

SOLIDWORKS 2020 SP3.1, Revision Number 28.3.1

SOLIDWORKS API Help

[Send comments on this topic.](#)

## ArrangeIcons Method (ISldWorks)

[See Also](#)



[SolidWorks.Interop.sldworks Namespace](#) > [ISldWorks Interface](#) : ArrangeIcons Method (ISldWorks)

Arranges the icons in SOLIDWORKS.

## .NET Syntax

Visual Basic (Declaration)

```
Sub ArrangeIcons()
```

Visual Basic (Usage)



```
Dim instance As ISldWorks  
  
instance.ArrangeIcons()
```

C#

```
void ArrangeIcons()
```

C++/CLI

```
void ArrangeIcons();
```

**NOTE:** See [Differences Between Unmanaged C++ and C++/CLI Code](#).

## Visual Basic for Applications (VBA) Syntax

See [SldWorks::ArrangeIcons](#).

## See Also

[ISldWorks Interface](#)  
[ISldWorks Members](#)

SOLIDWORKS API Help

[Send comments on this topic.](#)

## ArrangeWindows Method (ISldWorks)

[See Also](#) [Example](#)



[SolidWorks.Interop.sldworks Namespace](#) > [ISldWorks Interface](#) : ArrangeWindows Method (ISldWorks)

Arranges the open windows in SOLIDWORKS.

## .NET Syntax

Visual Basic (Declaration)

```
Sub ArrangeWindows( _  
    ByVal Style As System.Integer _  
)
```

Visual Basic (Usage)



```
Dim instance As ISldWorks  
Dim Style As System.Integer  
  
instance.ArrangeWindows(Style)
```

C#

```
void ArrangeWindows(  
    System.int Style  
)
```

C++/CLI

```
void ArrangeWindows(  
&    System.int Style  
)
```

**NOTE:** See [Differences Between Unmanaged C++ and C++/CLI Code](#).

#### Parameters

*Style*

Type of arrangement where:

- 0 = Cascade
- 1 = Tile horizontally
- 2 = Tile vertically

### Visual Basic for Applications (VBA) Syntax

See [ISldWorks::ArrangeWindows](#).

### Example

[Access Assembly \(C++\)](#)  
[Create and Arrange Windows \(VBA\)](#)

### See Also

[ISldWorks Interface](#)  
[ISldWorks Members](#)  
[ISldWorks::CreateNewWindow Method](#)

SOLIDWORKS API Help

[Send comments on this topic.](#)

## BlockSkinning Method (ISldWorks)

[See Also](#)



[SolidWorks.Interop.sldworks Namespace](#) > [ISldWorks Interface](#) : BlockSkinning Method (ISldWorks)

Blocks skinning a window, which prevents a window from looking like a SOLIDWORKS window.

### .NET Syntax

Visual Basic (Declaration)

```
Function BlockSkinning() As System.Boolean
```

Visual Basic (Usage)



```
Dim instance As ISldWorks  
Dim value As System.Boolean  
  
value = instance.BlockSkinning()
```

C#

```
System.bool BlockSkinning()
```

C++/CLI

```
System.bool BlockSkinning();
```

**NOTE:** See [Differences Between Unmanaged C++ and C++/CLI Code](#).

#### Return Value

True if successful, false if not

## Visual Basic for Applications (VBA) Syntax

See [ISldWorks::BlockSkinning](#).

## Remarks

You must call [ISldWorks::ResumeSkinning](#) after creating your unskinned window so that new windows created by SOLIDWORKS and other add-ins are displayed as intended.

## See Also

[ISldWorks Interface](#)  
[ISldWorks Members](#)

## Availability

SOLIDWORKS 2008 FCS, Revision Number 16.0

SOLIDWORKS API Help

[Send comments on this topic.](#)

## CallBack Method (ISldWorks)

[See Also](#)



[SolidWorks.Interop.sldworks Namespace](#) > [ISldWorks Interface](#) : CallBack Method (ISldWorks)

Allows an out-of-process executable or a SOLIDWORKS macro to call back a function in a SOLIDWORKS add-in DLL.

## .NET Syntax

### Visual Basic (Declaration)

```
Function CallBack( _  
    ByVal CallBackFunc As System.String, _  
    ByVal DefaultRetVal As System.Integer, _  
    ByVal CallBackArgs As System.String _  
    ) As System.Integer
```

### Visual Basic (Usage)



```
Dim instance As ISldWorks  
Dim CallBackFunc As System.String  
Dim DefaultRetVal As System.Integer  
Dim CallBackArgs As System.String  
Dim value As System.Integer  
  
value = instance.CallBack(CallBackFunc, DefaultRetVal, CallBackArgs)
```

### C#

```
System.int CallBack(  
    System.string CallBackFunc,  
    System.int DefaultRetVal,  
    System.string CallBackArgs  
)
```

### C++/CLI

```
System.int CallBack(  
& System.String^ CallBackFunc,  
& System.int DefaultRetVal,  
& System.String^ CallBackArgs  
)
```

**NOTE:** See [Differences Between Unmanaged C++ and C++/CLI Code](#).

### Parameters

*CallBackFunc*  
Function to call

*DefaultRetVal*  
Default return value

*CallBackArgs*

Arguments to pass to the callback function

#### Return Value

Return value from the callback function, if it is called; DefaultRetVal if it is not called

### Visual Basic for Applications (VBA) Syntax

See [ISldWorks::CallBack](#).

### Example

To set the filename:

```
result = swApp.CallBack("pworks@miEval", 0, "RenderToFile Filename d:\image\xyz.jpg")
```

### Remarks

The CallBackFunc value contains the callback function to call. The syntax is:

dllname@function

where:

- dllname is the name of the add-in library as specified in your project .def file.
- function is the name of the function that gets called by this method. It must be declared as an export in your project .def file.

If the callback function is actually called, then the return value contains the value returned by the callback function, and the DefaultRetVal is not used.

If the callback function is not called, then the DefaultRetVal value is passed back from the API in the retval value. This allows the caller of this API to specify a return value that is different from any return value that the callback function might return so that it can tell if a problem occurred that caused the callback to never get called.

The CallBackArgs value contains the information to pass to the callback function. This value is untouched by the API and is passed through to the callback as a BSTR. Therefore, the format of what is inside of the string can be whatever the caller wants it to be. Handling and use of it is the sole responsibility of the callback function.

### See Also

[ISldWorks Interface](#)  
[ISldWorks Members](#)  
[ISldWorks::AddCallback Method](#)  
[ISldWorks::RemoveCallback Method](#)  
[ISldWorks::SetAddinCallbackInfo Method](#)

SOLIDWORKS API Help

[Send comments on this topic.](#)

## CheckpointConvertedDocument Method (ISldWorks)

[See Also](#)



[SolidWorks.Interop.sldworks Namespace](#) > [ISldWorks Interface](#) : CheckpointConvertedDocument Method (ISldWorks)

Saves the specified open document if its version is older than the version of the SOLIDWORKS Design product being used.

### .NET Syntax

Visual Basic (Declaration)

```
Function CheckpointConvertedDocument( _  
    ByVal DocName As System.String _  
) As System.Integer
```

Visual Basic (Usage)

```
Dim instance As ISldWorks  
Dim DocName As System.String  
Dim value As System.Integer
```

```
value = instance.CheckpointConvertedDocument(DocName)
```

C#



Copy Code

```
System.int CheckpointConvertedDocument(  
    System.string DocName  
)
```

C++/CLI

```
System.int CheckpointConvertedDocument(  
& System.String^ DocName  
)
```

**NOTE:** See [Differences Between Unmanaged C++ and C++/CLI Code](#).

#### Parameters

*DocName*

Full pathname of the file to save

#### Return Value

0 for no error or a bitwise OR of the errors encountered as defined in [swFileSaveError\\_e](#)

### Visual Basic for Applications (VBA) Syntax

See [ISldWorks::CheckpointConvertedDocument](#).

### Remarks

This saves the document even if the document is read-only.

This method requires that the document is currently open in your SOLIDWORKS Design session. It specifically checks if the document has been upgraded to the current version of the SOLIDWORKS Design product in this session. If it has not, then this method has no effect.

Be careful when using this method because this method attempts to change the file permissions to read-write if the file is read-only, and if successful, it overwrites the file and restores the permission to read-only. Although it may appear the file is safe because it is read-only before and after the operation, it might have been overwritten by this method.

This method was designed to be used with the ISldWorks event [DocumentConversionNotify](#). It does not require that the notification be used, but it should work in response to that notification.

### See Also

[ISldWorks Interface](#)  
[ISldWorks Members](#)

### Availability

SOLIDWORKS 99 SP1, datecode 1999229

SOLIDWORKS API Help

[Send comments on this topic.](#)

## CloseAllDocuments Method (ISldWorks)

[See Also](#) [Example](#)



[SolidWorks.Interop.sldworks Namespace](#) > [ISldWorks Interface](#) : CloseAllDocuments Method (ISldWorks)

Closes all open documents in the SOLIDWORKS Design session.

### .NET Syntax

Visual Basic (Declaration)

```
Function CloseAllDocuments( _  
    ByVal IncludeUnsaved As System.Boolean _  
) As System.Boolean
```

Visual Basic (Usage)

```
Dim instance As ISldWorks  
Dim IncludeUnsaved As System.Boolean  
Dim value As System.Boolean
```



```
value = instance.CloseAllDocuments(IncludeUnsaved)
```

C#

```
System.bool CloseAllDocuments(  
    System.bool IncludeUnsaved  
)
```

C++/CLI

```
System.bool CloseAllDocuments(  
& System.bool IncludeUnsaved  
)
```

**NOTE:** See [Differences Between Unmanaged C++ and C++/CLI Code](#).

#### Parameters

*IncludeUnsaved*

- True = Close all documents, including dirty documents
- False = Close all documents, excluding dirty documents

#### Return Value

True if method executes successfully, false if not

### Visual Basic for Applications (VBA) Syntax

See [SldWorks::CloseAllDocuments](#).

### Example

[Close All Documents \(VBA\)](#)  
[Keep SOLIDWORKS Invisible While Activating Documents \(C#\)](#)  
[Keep SOLIDWORKS Invisible While Activating Documents \(VB.NET\)](#)  
[Keep SOLIDWORKS Invisible While Activating Documents \(VBA\)](#)  
[Switch Documents \(C#\)](#)  
[Switch Documents \(VB.NET\)](#)  
[Switch Documents \(VBA\)](#)

### See Also

[ISldWorks Interface](#)  
[ISldWorks Members](#)  
[ISldWorks::CloseDoc Method](#)  
[ISldWorks::GetOpenDocument Method](#)  
[ISldWorks::GetOpenDocumentByName Method](#)  
[ISldWorks::OpenDoc6 Method](#)  
[ISldWorks::ActiveDoc Property](#)  
[ISldWorks::!ActiveDoc2 Property](#)  
[ISldWorks::QuitDoc Method](#)  
[ISldWorks::GetFirstDocument Method](#)  
[ISldWorks::!GetFirstDocument2 Method](#)  
[ISldWorks::!GetDocuments Method](#)  
[ISldWorks::GetDocuments Method](#)  
[ISldWorks::GetDocumentCount Method](#)  
[ISldWorks::CloseAndReopen Method](#)

### Availability

SOLIDWORKS 2006 SP2, Revision Number 14.2

SOLIDWORKS API Help

[Send comments on this topic.](#)

## CloseAndReopen Method (ISldWorks)

[See Also](#)



[SolidWorks.Interop.sldworks Namespace](#) > [ISldWorks Interface](#) : CloseAndReopen Method (ISldWorks)

Closes and reopens the specified drawing document without unloading its references from memory.

### .NET Syntax

Visual Basic (Declaration)

```
Function CloseAndReopen(  
    ByVal Doc As ModelDoc2, _  
    ByVal Option As System.Integer, _
```

```
ByRef NewDoc As ModelDoc2 _  
) As System.Integer
```

Visual Basic (Usage)



```
Dim instance As ISldWorks  
Dim Doc As ModelDoc2  
Dim Option As System.Integer  
Dim NewDoc As ModelDoc2  
Dim value As System.Integer  
  
value = instance.CloseAndReopen(Doc, Option, NewDoc)
```

C#

```
System.int CloseAndReopen(  
    ModelDoc2 Doc,  
    System.int Option,  
    out ModelDoc2 NewDoc  
)
```

C++/CLI

```
System.int CloseAndReopen(  
    & ModelDoc2^ Doc,  
    & System.int Option,  
    & [Out] ModelDoc2^ NewDoc  
)
```

**NOTE:** See [Differences Between Unmanaged C++ and C++/CLI Code](#).

#### Parameters

*Doc*  
[IModelDoc2](#): drawing document to close and reopen  
*Option*  
Reopen options as defined in [swCloseReopenOption\\_e](#)  
*NewDoc*  
[IModelDoc2](#): reopened drawing document

#### Return Value

Error code as defined in [swCloseReopenError\\_e](#)

### Visual Basic for Applications (VBA) Syntax

See [SldWorks::CloseAndReopen](#).

### Example

Contact SOLIDWORKS API Support to obtain **Close and Reopen a Drawing Document (VBA, VB.NET, C#)**.

### Remarks

Before a third-party application can process a drawing document that is open in SOLIDWORKS, it must close the document. Usually when a drawing document is closed, its references are unloaded from memory, and reopening the drawing document takes a lot of time. This method closes a drawing document, keeps its references in memory, and quickly reopens it.

After the drawing document is closed and before it is reopened, SOLIDWORKS fires a [FileCloseNotify](#) event with reason [swFileCloseNotifyReason\\_e.swFileCloseNotifyReason\\_CloseForReload](#). In the handler of this event, a third-party application can call [ISldWorks::SetPromptFileName2](#) to open a different file, or it can process the specified document before it is reopened in SOLIDWORKS.

See [IModelDoc2::ReloadOrReplace](#) to perform a similar function with part and assembly documents.

### See Also

[ISldWorks Interface](#)  
[ISldWorks Members](#)  
[ISldWorks::CloseAllDocuments Method](#)  
[ISldWorks::CloseDoc Method](#)  
[ISldWorks::QuitDoc Method](#)

### Availability

## CloseAndReopen2 Method (ISldWorks)

[See Also](#)[SolidWorks.Interop.sldworks Namespace](#) > [ISldWorks Interface](#) : CloseAndReopen2 Method (ISldWorks)

Closes and reopens the specified drawing document without unloading its references from memory.

## .NET Syntax

## Visual Basic (Declaration)

```
Function CloseAndReopen2( _
    ByVal Doc As System.Object, _
    ByVal Option As System.Integer, _
    ByRef NewDoc As System.Object _
) As System.Integer
```

## Visual Basic (Usage)



```
Dim instance As ISldWorks
Dim Doc As System.Object
Dim Option As System.Integer
Dim NewDoc As System.Object
Dim value As System.Integer

value = instance.CloseAndReopen2(Doc, Option, NewDoc)
```

## C#

```
System.int CloseAndReopen2(
    System.object Doc,
    System.int Option,
    out System.object NewDoc
)
```

## C++/CLI

```
System.int CloseAndReopen2(
    & System.Object^ Doc,
    & System.int Option,
    & [Out] System.Object^ NewDoc
)
```

**NOTE:** See [Differences Between Unmanaged C++ and C++/CLI Code](#).

## Parameters

*Doc*[IModelDoc2](#); drawing document to close and reopen*Option*Reopen options as defined in [swCloseReopenOption\\_e](#)*NewDoc*[IModelDoc2](#); reopened drawing document

## Return Value

Error code as defined in [swCloseReopenError\\_e](#)

## Visual Basic for Applications (VBA) Syntax

See [SldWorks::CloseAndReopen2](#).

## Example

Contact SOLIDWORKS API Support to obtain **Close and Reopen a Drawing Document (VBA, VB.NET, C#)**.

## Remarks

Before a third-party application can process a drawing document that is open in SOLIDWORKS, it must close the document. Usually when a drawing document is closed, its references are unloaded from memory, and reopening the drawing document takes a lot of time. This method closes a drawing document, keeps its references in memory, and quickly reopens it.

After the drawing document is closed and before it is reopened, SOLIDWORKS fires a [FileCloseNotify](#) event with reason [swFileCloseNotifyReason\\_e.swFileCloseNotifyReason\\_CloseForReload](#). In the handler of this event, a third-party application can call [ISldWorks::SetPromptFileName2](#) to open a different file, or it can process the specified document before it is reopened in SOLIDWORKS.

See [IModelDoc2::ReloadOrReplace](#) to perform a similar function with part and assembly documents.

## See Also

[ISldWorks Interface](#)  
[ISldWorks Members](#)  
[ISldWorks::CloseAllDocuments Method \(\)](#)  
[ISldWorks::CloseDoc Method \(\)](#)  
[ISldWorks::QuitDoc Method \(\)](#)

## Availability

SOLIDWORKS 2022 FCS, Revision Number 30

SOLIDWORKS API Help

[Send comments on this topic.](#)

## CloseDoc Method (ISldWorks)

[See Also](#) [Example](#)



[SolidWorks.Interop.sldworks Namespace](#) > [ISldWorks Interface](#) : CloseDoc Method (ISldWorks)

Closes the specified document.

## .NET Syntax

Visual Basic (Declaration)

```
Sub CloseDoc( _  
    ByVal Name As System.String _  
)
```

Visual Basic (Usage)



```
Dim instance As ISldWorks  
Dim Name As System.String  
  
instance.CloseDoc(Name)
```

C#

```
void CloseDoc(  
    System.string Name  
)
```

C++/CLI

```
void CloseDoc(  
& System.String^ Name  
)
```

**NOTE:** See [Differences Between Unmanaged C++ and C++/CLI Code](#).

### Parameters

*Name*

Name of document (see **Remarks**)

## Visual Basic for Applications (VBA) Syntax

See [SldWorks::CloseDoc](#).

## Example

[Close Document \(VBA\)](#)  
[Get Excel Design Table Worksheet \(VBA\)](#)  
[Run or Attach to a SOLIDWORKS Session \(VBA\)](#)

[Get Names of Creators of Features \(C++\)](#)  
[Get Names of Creators of Features \(VBA\)](#)  
[Get Names of Creators of Features \(VB.NET\)](#)  
[Get Names of Creators of Features \(C#\)](#)

## Remarks

If Name is specified with:

- the name of a document that is not open, then this method does nothing.
- an empty string (""), then the active document is closed without saving.
- the name of a document in the dirty state (modified, but not saved), then this method closes the document without saving it.

This method also closes any non-active hidden documents.

For documents referenced by other documents loaded in memory, call this method to release user-interface resources while keeping the model data loaded.

If you are closing the only document open in the SOLIDWORKS Design session and this SOLIDWORKS Design session is a background session, then calling this method, or calling [ISldWorks::QuitDoc](#), results in the SOLIDWORKS Design session being closed.

A background SOLIDWORKS Design session can be created when the SOLIDWORKS Design session is started by your application and the session is not controlled by the user; i.e., [ISldWorks::UserControl](#) set to false.

To keep the SOLIDWORKS Design session open, set ISldWorks::UserControl to True, which makes the session visible, or you can close your documents at the end of your program execution.

## See Also

[ISldWorks Interface](#)  
[ISldWorks Members](#)  
[ISldWorks::CloseAllDocuments Method](#)  
[ISldWorks::GetOpenDocument Method](#)  
[ISldWorks::GetOpenDocumentByName Method](#)  
[ISldWorks::OpenDoc6 Method](#)  
[ISldWorks::ActiveDoc Property](#)  
[ISldWorks::IActiveDoc2 Property](#)  
[ISldWorks::IGetFirstDocument2 Method](#)  
[ISldWorks::GetFirstDocument Method](#)  
[ISldWorks::GetDocuments Method](#)  
[ISldWorks::GetDocumentCount Method](#)  
[ISldWorks::IGetDocuments Method](#)  
[ISldWorks::CloseAndReopen Method](#)

SOLIDWORKS API Help

[Send comments on this topic.](#)

## CloseUserNotification Method (ISldWorks)

[See Also](#)



[SolidWorks.Interop.sldworks Namespace](#) > [ISldWorks Interface](#) : CloseUserNotification Method (ISldWorks)

Closes the specified user notification.

## .NET Syntax

Visual Basic (Declaration)

```
Sub CloseUserNotification( _  
    ByVal Definition As System.Object _  
)
```

Visual Basic (Usage)



```
Dim instance As ISldWorks  
Dim Definition As System.Object  
  
instance.CloseUserNotification(Definition)
```

C#

```
void CloseUserNotification(  
    System.object Definition  
)
```

C++/CLI

```
void CloseUserNotification(  
& System.Object^ Definition  
)
```

**NOTE:** See [Differences Between Unmanaged C++ and C++/CLI Code](#).

**Parameters**

*Definition*  
[IUserNotificationDefinition](#)

 **Visual Basic for Applications (VBA) Syntax**

See [SldWorks::CloseUserNotification](#).

 **See Also**

[ISldWorks Interface](#)  
[ISldWorks Members](#)

 **Availability**

SOLIDWORKS 2022 FCS, Revision Number 30

SOLIDWORKS API Help

[Send comments](#) on this topic.

**Command Method (ISldWorks)**

[See Also](#)



[SolidWorks.Interop.sldworks Namespace](#) > [ISldWorks Interface](#) : Command Method (ISldWorks)

Opens the specified dialog or file.

 **.NET Syntax**

**Visual Basic (Declaration)**

```
Function Command( _  
    ByVal Command As System.Integer, _  
    ByVal Args As System.Object _  
) As System.Object
```

**Visual Basic (Usage)**



```
Dim instance As ISldWorks  
Dim Command As System.Integer  
Dim Args As System.Object  
Dim value As System.Object  
  
value = instance.Command(Command, Args)
```

**C#**

```
System.object Command(  
    System.int Command,  
    System.object Args  
)
```

**C++/CLI**

```
System.Object^ Command(  
& System.int Command,  
& System.Object^ Args  
)
```

**NOTE:** See [Differences Between Unmanaged C++ and C++/CLI Code](#).

**Parameters**

*Command*  
Command as defined by [swCommand\\_e](#)  
*Args*  
See **Remarks**

 **Visual Basic for Applications (VBA) Syntax**

See [SldWorks::Command](#).

## Remarks

| If command specified is...                                                                                  | Then pass...                                                                                                                                                                   |
|-------------------------------------------------------------------------------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| swOpenHTMLHelp                                                                                              | Path and filename for the compiled HTML file (has .chm filename extension)                                                                                                     |
| <ul style="list-style-type: none"><li>. swFileOpen</li><li>. swFileNew</li><li>. swOpenRecentFile</li></ul> | Empty VARIANT; for example:<br><br>VARIANT args;<br><br>V_VT(&args) = VT_EMPTY;<br><br>// Call Command API and open the File, Open dialog<br>swApp->Command(0, args, &retval); |

## See Also

[ISldWorks Interface](#)  
[ISldWorks Members](#)

## Availability

SOLIDWORKS 2004 FCS, Revision Number 12.0

SOLIDWORKS API Help

[Send comments](#) on this topic.

## CommandInProgress Property (ISldWorks)

[See Also](#)



[SolidWorks.Interop.sldworks Namespace](#) > [ISldWorks Interface](#) : CommandInProgress Property (ISldWorks)

Improves performance of out-of-process applications by informing SOLIDWORKS that a sequence of API calls will be made by the out-of-process application.

## .NET Syntax

Visual Basic (Declaration)

```
Property CommandInProgress As System.Boolean
```

Visual Basic (Usage)



```
Dim instance As ISldWorks  
Dim value As System.Boolean  
  
instance.CommandInProgress = value  
  
value = instance.CommandInProgress
```

C#

```
System.bool CommandInProgress {get; set;}
```

C++/CLI

```
property System.bool CommandInProgress {  
    System.bool get();  
    void set ( & System.bool value);  
}
```

**NOTE:** See [Differences Between Unmanaged C++ and C++/CLI Code](#).

### Property Value

Set to True before calling the sequence of API calls, then set to false after calling the sequence of API calls

## Visual Basic for Applications (VBA) Syntax

See [SldWorks::CommandInProgress](#).

## Remarks

SOLIDWORKS then reduces the number of updates it makes during these calls. Use of this property only effects out-of-process applications.

## See Also

[ISldWorks Interface](#)  
[ISldWorks Members](#)

## Availability

SOLIDWORKS 2006 SP2, Revision Number 14.2

SOLIDWORKS API Help

[Send comments on this topic.](#)

## CopyAppearance Method (ISldWorks)

[See Also](#) [Example](#)



[SolidWorks.Interop.sldworks Namespace](#) > [ISldWorks Interface](#) : CopyAppearance Method (ISldWorks)

Copies the appearance of the specified entity to the clipboard.

## .NET Syntax

### Visual Basic (Declaration)

```
Function CopyAppearance( _  
    ByVal Object As System.Object _  
) As System.Boolean
```

### Visual Basic (Usage)



```
Dim instance As ISldWorks  
Dim Object As System.Object  
Dim value As System.Boolean  
  
value = instance.CopyAppearance(Object)
```

### C#

```
System.bool CopyAppearance(  
    System.object Object  
)
```

### C++/CLI

```
System.bool CopyAppearance(  
& System.Object^ Object  
)
```

**NOTE:** See [Differences Between Unmanaged C++ and C++/CLI Code](#).

### Parameters

*Object*

[Face](#), [body](#), [feature](#), [component](#), or [part](#) whose appearance you want to copy

### Return Value

True if appearance is successfully copied to the clipboard, false if not

## Visual Basic for Applications (VBA) Syntax

See [SldWorks::CopyAppearance](#).

## Example

[Copy and Paste Appearances \(VBA\)](#)  
[Copy and Paste Appearances \(VB.NET\)](#)  
[Copy and Paste Appearances \(C#\)](#)

## See Also

[ISldWorks Interface](#)  
[ISldWorks Members](#)  
[ISldWorks::PasteAppearance Method](#)

## Availability

SOLIDWORKS 2013 FCS, Revision Number 21.0

SOLIDWORKS API Help

[Send comments on this topic.](#)

## CopyDocument Method (ISldWorks)

[See Also](#) [Example](#)



[SolidWorks.Interop.sldworks Namespace](#) > [ISldWorks Interface](#) : CopyDocument Method (ISldWorks)

Copies a document and optionally updates references to it.

## .NET Syntax

### Visual Basic (Declaration)

```
Function CopyDocument( _  
    ByVal SourceDoc As System.String, _  
    ByVal DestDoc As System.String, _  
    ByVal FromChildren As System.Object, _  
    ByVal ToChildren As System.Object, _  
    ByVal Option As System.Integer _  
) As System.Integer
```

### Visual Basic (Usage)



```
Dim instance As ISldWorks  
Dim SourceDoc As System.String  
Dim DestDoc As System.String  
Dim FromChildren As System.Object  
Dim ToChildren As System.Object  
Dim Option As System.Integer  
Dim value As System.Integer  
  
value = instance.CopyDocument(SourceDoc, DestDoc, FromChildren, ToChildren, Option)
```

### C#

```
System.int CopyDocument(  
    System.string SourceDoc,  
    System.string DestDoc,  
    System.object FromChildren,  
    System.object ToChildren,  
    System.int Option  
)
```

### C++/CLI

```
System.int CopyDocument(  
& System.String^ SourceDoc,  
& System.String^ DestDoc,  
& System.Object^ FromChildren,  
& System.Object^ ToChildren,  
& System.int Option  
)
```

**NOTE:** See [Differences Between Unmanaged C++ and C++/CLI Code](#).

### Parameters

*SourceDoc*

Full path and filename of the document to copy

*DestDoc*

Full path and filename of the document to which to copy SourceDoc

*FromChildren*

Array containing the full path and filenames of the child documents dependent on the document specified for SourceDoc

*ToChildren*

Array of strings containing the new full path and filenames of the child documents to which to copy the child documents specified for FromChildren  
*Option*  
Copy options as defined by [swMoveCopyOptions\\_e](#)

**Return Value**

Success or error code as defined by [swMoveCopyError\\_e](#)

 **Visual Basic for Applications (VBA) Syntax**

See [SldWorks::CopyDocument](#).

 **Example**

[Copy Document \(VBA\)](#)  
[Copy Document and Its Dependencies \(VBA\)](#)  
[Copy Document and Its Dependencies \(VB.NET\)](#)  
[Copy Document and Its Dependencies \(C#\)](#)

 **Remarks**

There can be no documents open when using this method.

 **See Also**

[ISldWorks Interface](#)  
[ISldWorks Members](#)  
[ISldWorks::MoveDocument Method](#)  
[ISldWorks::ICopyDocument Method](#)  
[IModelDocExtension::SaveAs Method](#)

 **Availability**

SOLIDWORKS 2004 FCS, Revision Number 12.0

[SOLIDWORKS API Help](#)

[Send comments on this topic.](#)

**CreateNewWindow Method (ISldWorks)**

[See Also](#) [Example](#)



[SolidWorks.Interop.sldworks Namespace](#) > [ISldWorks Interface](#) : CreateNewWindow Method (ISldWorks)

Creates a client window containing the active document.

 **.NET Syntax**

Visual Basic (Declaration)

```
Sub CreateNewWindow()
```

Visual Basic (Usage)

```
Dim instance As ISldWorks  
  
instance.CreateNewWindow()
```

C#

```
void CreateNewWindow()
```

C++/CLI

```
void CreateNewWindow();
```

**NOTE:** See [Differences Between Unmanaged C++ and C++/CLI Code](#).

 **Visual Basic for Applications (VBA) Syntax**

See [SldWorks::CreateNewWindow](#).

 **Example**

[Create and Arrange Windows \(VBA\)](#)  
[Switch Documents \(C#\)](#)  
[Switch Documents \(VB.NET\)](#)  
[Switch Documents \(VBA\)](#)

## See Also

[ISldWorks Interface](#)  
[ISldWorks Members](#)  
[ISldWorks::ArrangeWindows Method](#)

SOLIDWORKS API Help

[Send comments on this topic.](#)

## CreatePropertyManagerPage Method (ISldWorks)

[See Also](#) [Example](#)



[SolidWorks.Interop.sldworks Namespace](#) > [ISldWorks Interface](#) : CreatePropertyManagerPage Method (ISldWorks)

Creates a PropertyManager page.

## .NET Syntax

### Visual Basic (Declaration)

```
Function CreatePropertyManagerPage( _  
    ByVal Title As System.String, _  
    ByVal Options As System.Integer, _  
    ByVal Handler As System.Object, _  
    ByRef Errors As System.Integer _  
) As System.Object
```

### Visual Basic (Usage)



```
Dim instance As ISldWorks  
Dim Title As System.String  
Dim Options As System.Integer  
Dim Handler As System.Object  
Dim Errors As System.Integer  
Dim value As System.Object  
  
value = instance.CreatePropertyManagerPage(Title, Options, Handler, Errors)
```

### C#

```
System.object CreatePropertyManagerPage(  
    System.string Title,  
    System.int Options,  
    System.object Handler,  
    out System.int Errors  
)
```

### C++/CLI

```
System.Object^ CreatePropertyManagerPage(  
& System.String^ Title,  
& System.int Options,  
& System.Object^ Handler,  
& [Out] System.int Errors  
)
```

**NOTE:** See [Differences Between Unmanaged C++ and C++/CLI Code](#).

### Parameters

*Title*

Title of the page

*Options*

Options as defined in [swPropertyManagerPageOptions\\_e](#)

*Handler*

Pointer to the event handler for this page ([IPropertyManagerPage2Handler5](#))

*Errors*

Status of the creation as defined in [swPropertyManagerPageStatus\\_e](#)

### Return Value

## Visual Basic for Applications (VBA) Syntax

See [ISldWorks::CreatePropertyManagerPage](#).

## Example

See the [IPropertyManagerPage2](#) examples.

## Example

[Cut Body In Half Using Macro Feature \(VBA\)](#)  
[Create PropertyManager Page \(VBA\)](#)

## Remarks

Specify `swPropertyManagerPageOptions_e.swPropertyManagerOptions_LockedPage` in the `Options` parameter when you create your PropertyManager page. It is important that when a handler (such as [IPropertyManagerPage2Handler5::OnButtonPress](#) or [IPropertyManagerPage2Handler5::OnClose](#)) is finished and control returns to SOLIDWORKS that the PropertyManager page is still there. If the PropertyManager page is not there, SOLIDWORKS might crash. Some methods try to close the PropertyManager page, but you can avoid this scenario by creating the PropertyManager page as Locked.

## See Also

[ISldWorks Interface](#)  
[ISldWorks Members](#)  
[ISldWorks::ICreatePropertyManagerPage Method](#)

## Availability

SOLIDWORKS 2001Plus FCS, Revision Number 10.0

SOLIDWORKS API Help

[Send comments on this topic.](#)

## CreateTaskpaneView Method (ISldWorks)

[See Also](#)



[SolidWorks.Interop.sldworks Namespace](#) > [ISldWorks Interface](#) : CreateTaskpaneView Method (ISldWorks)

Obsolete. Superseded by [ISldworks::CreateTaskpaneView2](#).

## .NET Syntax

Visual Basic (Declaration)

```
Function CreateTaskpaneView( _  
    ByRef Bitmap As System.Integer, _  
    ByVal ToolTip As System.String, _  
    ByVal PHandler As System.Object _  
) As TaskpaneView
```

Visual Basic (Usage)



```
Dim instance As ISldWorks  
Dim Bitmap As System.Integer  
Dim ToolTip As System.String  
Dim PHandler As System.Object  
Dim value As TaskpaneView  
  
value = instance.CreateTaskpaneView(Bitmap, ToolTip, PHandler)
```

C#

```
TaskpaneView CreateTaskpaneView(  
    ref System.int Bitmap,  
    System.string ToolTip,  
    System.object PHandler  
)
```

C++/CLI

```
TaskpaneView^ CreateTaskpaneView(  
& System.int% Bitmap,  
& System.String^ ToolTip,  
& System.Object^ PHandler  
)
```

**NOTE:** See [Differences Between Unmanaged C++ and C++/CLI Code](#).

#### Parameters

*Bitmap*

*ToolTip*

*PHandler*

### Visual Basic for Applications (VBA) Syntax

See [SldWorks::CreateTaskpaneView](#).

### See Also

[ISldWorks Interface](#)  
[ISldWorks Members](#)

SOLIDWORKS API Help

[Send comments](#) on this topic.

## CreateTaskpaneView2 Method (ISldWorks)

[See Also](#)



[SolidWorks.Interop.sldworks Namespace](#) > [ISldWorks Interface](#) : CreateTaskpaneView2 Method (ISldWorks)

Obsolete. Superseded by [ISldWorks::CreateTaskpaneView3](#).

### .NET Syntax

Visual Basic (Declaration)

```
Function CreateTaskpaneView2( _  
    ByVal Bitmap As System.String, _  
    ByVal ToolTip As System.String _  
) As TaskpaneView
```

Visual Basic (Usage)

```
Dim instance As ISldWorks  
Dim Bitmap As System.String  
Dim ToolTip As System.String  
Dim value As TaskpaneView  
  
value = instance.CreateTaskpaneView2(Bitmap, ToolTip)
```

C#

```
TaskpaneView CreateTaskpaneView2(  
    System.string Bitmap,  
    System.string ToolTip  
)
```

C++/CLI

```
TaskpaneView^ CreateTaskpaneView2(  
& System.String^ Bitmap,
```



```
& System.String^ ToolTip  
)
```

**NOTE:** See [Differences Between Unmanaged C++ and C++/CLI Code](#).

#### Parameters

*Bitmap*

Path and file name of the bitmap for the tab of this Task Pane view (see **Remarks**)

*ToolTip*

ToolTip for this Task Pane view

#### Return Value

[Task Pane view](#)

### Visual Basic for Applications (VBA) Syntax

See [SldWorks::CreateTaskpaneView2](#).

### Remarks

The bitmap should be 16 colors and 16 x 18 (width x height) pixels. Any portions of the bitmap that are white (RGB 255,255,255) will be transparent.

### See Also

[ISldWorks Interface](#)

[ISldWorks Members](#)

[ISldWorks::ActivateTaskPane Method](#)

[ISldWorks::RefreshTaskpaneContent Method](#)

[ISldWorks::TaskPanelsPinned Property](#)

### Availability

SOLIDWORKS 2006 FCS, Revision Number 14.0

SOLIDWORKS API Help

[Send comments on this topic.](#)

## CreateTaskpaneView3 Method (ISldWorks)

[See Also](#) [Example](#)



[SolidWorks.Interop.sldworks Namespace](#) > [ISldWorks Interface](#) : CreateTaskpaneView3 Method (ISldWorks)

Creates an application-level Task Pane view.

### .NET Syntax

Visual Basic (Declaration)

```
Function CreateTaskpaneView3( _  
    ByVal ImageList As System.Object, _  
    ByVal ToolTip As System.String _  
) As TaskpaneView
```

Visual Basic (Usage)

```
Dim instance As ISldWorks  
Dim ImageList As System.Object  
Dim ToolTip As System.String  
Dim value As TaskpaneView
```

```
value = instance.CreateTaskpaneView3(ImageList, ToolTip)
```

C#

```
TaskpaneView CreateTaskpaneView3(  
    System.object ImageList,  
    System.string ToolTip  
)
```

C++/CLI



```
TaskpaneView^ CreateTaskpaneView3(  
& System.Object^ ImageList,  
& System.String^ ToolTip  
)
```

**NOTE:** See [Differences Between Unmanaged C++ and C++/CLI Code](#).

**Parameters**

*ImageList*  
Array of strings of paths to six image files for the tab of this Task Pane view (see **Remarks**)  
*ToolTip*  
Tool tip for this Task Pane view

**Return Value**

[Task Pane view](#)

 **Visual Basic for Applications (VBA) Syntax**

See [SldWorks::CreateTaskpaneView3](#).

 **Example**

[Add Task Pane View \(VBA\)](#)  
[Add Task Pane View \(VB.NET\)](#)  
[Add Task Pane View \(C#\)](#)

 **Remarks**

This method supports high resolution screens with high resolution operating system scaling options.

ImageList contains paths to PNG or BMP images in six pixel sizes:

- 20 X 20
- 32 X 32
- 40 X 40
- 64 X 64
- 96 X 96
- 128 X 128

The SOLIDWORKS Design user interface displays icons in three sizes: small, medium and large. After using this method to specify an image in six sizes, SOLIDWORKS selects the appropriate images to display as required by the current screen resolution or operating system scale.

| If OS scale is... | Then SOLIDWORKS icon... | Uses image pixel size... |
|-------------------|-------------------------|--------------------------|
| 100%              | Small                   | 20X20                    |
|                   | Medium                  | 32X32                    |
|                   | Large                   | 40X40                    |
| 150%              | Small                   | 32X32                    |
|                   | Medium                  | 40X40                    |
|                   | Large                   | 64X64                    |
| 200%              | Small                   | 40X40                    |
|                   | Medium                  | 64X64                    |
|                   | Large                   | 96X96                    |
| 250%              | Small                   | 64X64                    |
|                   | Medium                  | 96X96                    |
|                   | Large                   | 128X128                  |

The images should use a 256-color palette and gray (192, 192, 192) for transparent areas.

 **See Also**

[ISldWorks Interface](#)  
[ISldWorks Members](#)  
[ISldWorks::ActivateTaskPane Method \(\)](#)  
[ISldWorks::RefreshTaskpaneContent Method \(\)](#)  
[ISldWorks::TaskPanelsPinned Property \(\)](#)  
[ISldWorks::GetImageSize Method \(\)](#)

 **Availability**

SOLIDWORKS 2017 FCS, Revision Number 25.0



Obsolete. Superseded by [ISldWorks::RevisionNumber](#).

## .NET Syntax

### Visual Basic (Declaration)

```
Function DateCode() As System.Integer
```

### Visual Basic (Usage)



```
Dim instance As ISldWorks
Dim value As System.Integer

value = instance.DateCode()
```

### C#

```
System.int DateCode()
```

### C++/CLI

```
System.int DateCode();
```

**NOTE:** See [Differences Between Unmanaged C++ and C++/CLI Code](#).

## Visual Basic for Applications (VBA) Syntax

See [SldWorks::DateCode](#).

## See Also

[ISldWorks Interface](#)  
[ISldWorks Members](#)

SOLIDWORKS API Help

[Send comments on this topic.](#)

## DefineAttribute Method (ISldWorks)

[See Also](#) [Example](#)



SolidWorks.Interop.sldworks Namespace > ISldWorks Interface : DefineAttribute Method (ISldWorks)

Creates an attribute definition, which is the first step in generating attributes.

## .NET Syntax

### Visual Basic (Declaration)

```
Function DefineAttribute( _
    ByVal Name As System.String _
) As System.Object
```

### Visual Basic (Usage)



```
Dim instance As ISldWorks
Dim Name As System.String
Dim value As System.Object

value = instance.DefineAttribute(Name)
```

### C#

```
System.object DefineAttribute(
    System.string Name
)
```

### C++/CLI

```
System.Object^ DefineAttribute(
    & System.String^ Name
```

)

**NOTE:** See [Differences Between Unmanaged C++ and C++/CLI Code](#).

#### Parameters

##### Name

Name to give to the attribute definition; the name must be unique and qualified among the attributes defined in the current session (see **Remarks**)

##### Return Value

[Attribute definition](#)

### Visual Basic for Applications (VBA) Syntax

See [ISldWorks::DefineAttribute](#).

### Example

[Create Attribute \(VBA\)](#)  
[Delete Faces \(VBA\)](#)  
[Add Attribute to Feature and Include in Library Feature \(C#\)](#)  
[Add Attribute to Feature and Include in Library Feature \(VB.NET\)](#)  
[Add Attribute to Feature and Include in Library Feature \(VBA\)](#)  
[Delete Blended Faces \(C#\)](#)  
[Delete Blended Faces \(VB.NET\)](#)  
[Delete Blended Faces \(VBA\)](#)

### Remarks

An attribute definition is a container that can hold a group of parameters. For example, you can use this container to hold machining information or BOM data. Instances of this container may then be created as [IAttribute](#) objects on the document object, or on faces, edges, vertices, and features within the document. Once created, you can get any of the IAttribute objects and query or change its parameter values.

The Name argument used for this attribute definition must be unique and qualified among the attributes defined in the current session. To ensure this, the first three letters of the name must be an officially recognized third-party identifier. Contact SOLIDWORKS Corporation if you need one. You can also use the prefix: "pub" ( for "public" ) if you are just testing.

#### General sequence of steps in attribute creation

1. Create an attribute definition (ISldWorks::DefineAttribute or [ISldWorks::IDefineAttribute](#))
2. Add parameters to the attribute definition ([IAttributeDef::AddParameter](#))
3. Register the attribute definition ([IAttributeDef::Register](#))
4. Create instances of the attribute definition on objects throughout the model ([IAttributeDef::CreateInstance5](#))

Perform steps 1 through 3 only once for each working session. In other words, perform steps 1 through 3 when your DLL or EXE is initially loaded or run. Until the DLL is unloaded, or the EXE is closed, you can create as many instances of the attribute definition as you want as shown in step 4.

Calling this method attaches to an existing attribute definition with the specified Name or creates new attribute definition if a match is not found. The attribute definition exists throughout the current SOLIDWORKS Design session and persistent across SOLIDWORKS Design sessions if an attribute instance with that definition exists in the document. If an attribute definition exists, you cannot add or remove its parameters.

After an attribute instance is added to a face, edge, vertex, loop, feature, or document, there are several ways to get back to the attribute for query or modification.

1. Because an attribute instance is a feature, you can use any of the standard feature traversal routines (the FeatureByName methods, [IModelDoc2::FirstFeature](#) or [IModelDoc2::IFirstFeature](#), and [IFeature::GetNextFeature](#) or [IModelDoc2::IGetNextFeature](#)) to grab the feature representation of the attribute. After you have the [IFeature](#) object that represents the attribute instance, you can call [IFeature::GetSpecificFeature2](#) to get the underlying [IAttribute](#) object.
2. If the end-user selected the attribute in the FeatureManager design tree, you can use standard selection control to get the IFeature object representing the attribute instance ([ISelectionMgr::GetSelectedObject6](#)) and then call [IFeature::GetSpecificFeature2](#) to get the underlying IAttribute object.
3. If you are traversing body topology, then you can locate any IAttribute objects with a call to [IEntity::FindAttribute](#) or [IEntity::IFindAttribute](#) from the particular [IEntity](#) object (the is, face, edge, and so on). If the attribute instance was placed on the document, then you would need to use option 1 to get back to it.

After you have the IAttribute object that you want to query or modify, use the [IAttribute::GetParameter](#) or [IAttribute::IGetParameter](#) method to return the desired attribute parameter object. The [IParameter](#) object provides a set of functions to query or modify specific attribute values.

### See Also

[ISldWorks interface](#)  
[ISldWorks Members](#)  
[ISldWorks::IDefineAttribute Method](#)

SOLIDWORKS API Help

[Send comments on this topic.](#)

## DefineMessageBar Method (ISldWorks)

[See Also](#)



[SolidWorks.Interop.sldworks Namespace](#) > [ISldWorks interface](#) : DefineMessageBar Method (ISldWorks)

Called by a SOLIDWORKS add-in, creates a message bar definition object.

### .NET Syntax

#### Visual Basic (Declaration)

```
Function DefineMessageBar( _  
    ByVal UniqueName As System.String _  
) As System.Object
```

#### Visual Basic (Usage)



```
Dim instance As ISldWorks  
Dim UniqueName As System.String  
Dim value As System.Object  
  
value = instance.DefineMessageBar(UniqueName)
```

#### C#

```
System.object DefineMessageBar(  
    System.string UniqueName  
)
```

#### C++/CLI

```
System.Object^ DefineMessageBar(  
& System.String^ UniqueName  
)
```

**NOTE:** See [Differences Between Unmanaged C++ and C++/CLI Code](#).

#### Parameters

*UniqueName*  
Unique ID of this message bar

#### Return Value

[IMessageBarDefinition](#)

### Visual Basic for Applications (VBA) Syntax

See [SldWorks::DefineMessageBar](#).

### Example

See the [IMessageBarHandler](#) examples.

### Remarks

It is the add-in's responsibility to ensure that the ID is unique by using, for example, a combination of add-in module name and unique message identifier:

"MyAddInName+ID\_MYMESSAGE1"

### See Also

[ISldWorks Interface](#)  
[ISldWorks Members](#)

### Availability

SOLIDWORKS 2022 FCS, Revision Number 30

SOLIDWORKS API Help

[Send comments on this topic.](#)

## DefineUserNotification Method (ISldWorks)

[See Also](#)



[SolidWorks.Interop.sldworks Namespace](#) > [ISldWorks Interface](#) : DefineUserNotification Method (ISldWorks)

Called by a SOLIDWORKS add-in, creates a user notification definition object.

## Visual Basic Syntax

### Visual Basic (Declaration)

```
Function DefineUserNotification( _  
    ByVal UniqueName As System.String _  
) As System.Object
```

### Visual Basic (Usage)



```
Dim instance As ISldWorks  
Dim UniqueName As System.String  
Dim value As System.Object  
  
value = instance.DefineUserNotification(UniqueName)
```

### C#

```
System.Object DefineUserNotification(  
    System.string UniqueName  
)
```

### C++/CLI

```
System.Object^ DefineUserNotification(  
& System.String^ UniqueName  
)
```

**NOTE:** See [Differences Between Unmanaged C++ and C++/CLI Code](#).

#### Parameters

*UniqueName*  
Unique ID of this user notification

#### Return Value

[IUserNotificationDefinition](#)

## Visual Basic for Applications (VBA) Syntax

See [SldWorks::DefineUserNotification](#).

## Example

See the [IUserNotificationHandler](#) examples.

## Remarks

It is the add-in's responsibility to ensure that the ID is unique by using, for example, a combination of add-in module name and unique notification identifier:

"MyAddInName+ID\_MYNOTIFICATION1"

## See Also

[ISldWorks Interface](#)  
[ISldWorks Members](#)

## Availability

SOLIDWORKS 2022 FCS, Revision Number 30

SOLIDWORKS API Help

[Send comments on this topic.](#)

DisplayStatusBar Method (ISldWorks)

[See Also](#)



[SolidWorks.Interop.sldworks Namespace](#) > [ISldWorks Interface](#) : DisplayStatusBar Method (ISldWorks)

Sets whether to display the status bar.

## .NET Syntax

### Visual Basic (Declaration)

```
Sub DisplayStatusBar( _  
    ByVal OnOff As System.Boolean _  
)
```

### Visual Basic (Usage)



```
Dim instance As ISldWorks  
Dim OnOff As System.Boolean  
  
instance.DisplayStatusBar(OnOff)
```

### C#

```
void DisplayStatusBar(  
    System.bool OnOff  
)
```

### C++/CLI

```
void DisplayStatusBar(  
    & System.bool OnOff  
)
```

**NOTE:** See [Differences Between Unmanaged C++ and C++/CLI Code](#).

#### Parameters

*OnOff*

True if you want the status bar displayed, false if not

## Visual Basic for Applications (VBA) Syntax

See [SldWorks::DisplayStatusBar](#).

## See Also

[ISldWorks Interface](#)  
[ISldWorks Members](#)  
[IModelDoc2::Lock Method](#)  
[IModelDoc2::Unlock Method](#)  
[IStatusBarPane Interface](#)

SOLIDWORKS API Help

[Send comments on this topic.](#)

## DocumentVisible Method (ISldWorks)

[See Also](#)



[SolidWorks.Interop.sldworks Namespace](#) > [ISldWorks Interface](#) : DocumentVisible Method (ISldWorks)

Allows the application to control the display of a document in a window upon creation or retrieval.

## .NET Syntax

### Visual Basic (Declaration)

```
Sub DocumentVisible( _  
    ByVal Visible As System.Boolean, _  
    ByVal Type As System.Integer _  
)
```

### Visual Basic (Usage)



```
Dim instance As ISldWorks  
Dim Visible As System.Boolean  
Dim Type As System.Integer
```

```
instance.DocumentVisible(Visible, Type)
```

C#

```
void DocumentVisible(  
    System.bool Visible,  
    System.int Type  
)
```

C++/CLI

```
void DocumentVisible(  
& System.bool Visible,  
& System.int Type  
)
```

**NOTE:** See [Differences Between Unmanaged C++ and C++/CLI Code](#).

#### Parameters

*Visible*

True if the documents of the specified type are displayed upon creation or retrieval, false if not

*Type*

Type of document to which you apply visibility as defined in [swDocumentTypes\\_e](#)

### Visual Basic for Applications (VBA) Syntax

See [ISldWorks::DocumentVisible](#).

### Remarks

This method is a flag that allows you to display or hide documents as they are loaded.

If you create a document invisibly by passing false to this method, then you cannot make it visible with [IModelDoc2::Visible](#). Instead you should close it and then reopen it as a visible document.

Additionally if SOLIDWORKS was hidden by a call to [ISldWorks::UserControlBackground](#), and a document is opened (e.g., a configuration is loaded), then you must call this method to keep the SOLIDWORKS Design user interface hidden.

### See Also

[ISldWorks Interface](#)  
[ISldWorks Members](#)  
[ISldWorks::UserControlBackground](#)  
[ISldWorks::Visible Property](#)

SOLIDWORKS API Help

[Send comments on this topic.](#)

## DownloadFromMySolidWorksSettings Method (ISldWorks)

[See Also](#)



[SolidWorks.Interop.sldworks Namespace](#) > [ISldWorks Interface](#) : DownloadFromMySolidWorksSettings Method (ISldWorks)

Downloads the specified [SOLIDWORKS Design connected to the 3DEXPERIENCE platform](#) settings to SOLIDWORKS Design.

### .NET Syntax

Visual Basic (Declaration)

```
Function DownloadFromMySolidWorksSettings( _  
    ByVal SystemOptions As System.Boolean, _  
    ByVal FileLocations As System.Boolean, _  
    ByVal Customizations As System.Boolean _  
) As System.Integer
```

Visual Basic (Usage)



```
Dim instance As ISldWorks  
Dim SystemOptions As System.Boolean  
Dim FileLocations As System.Boolean  
Dim Customizations As System.Boolean
```

```
Dim value As System.Integer
```

```
value = instance.DownloadFromMySolidWorksSettings(SystemOptions, FileLocations, Customizations)
```

C#

```
System.int DownloadFromMySolidWorksSettings(  
    System.bool SystemOptions,  
    System.bool FileLocations,  
    System.bool Customizations  
)
```

C++/CLI

```
System.int DownloadFromMySolidWorksSettings(  
& System.bool SystemOptions,  
& System.bool FileLocations,  
& System.bool Customizations  
)
```

**NOTE:** See [Differences Between Unmanaged C++ and C++/CLI Code](#).

#### Parameters

*SystemOptions*  
True to download, false to not  
*FileLocations*  
True to download, false to not  
*Customizations*  
True to download, false to not

#### Return Value

Return code as defined by [swConnectedSyncSettingsErrors\\_e](#)

### Visual Basic for Applications (VBA) Syntax

See [ISldWorks::DownloadFromMySolidWorksSettings](#).

### Remarks

In order to use this method, you must be logged into SOLIDWORKS Design connected to the 3DEXPERIENCE platform.

To turn on auto synchronization of settings, call:

- [ISldWorks::SetUserPreferenceToggle](#)([swUserPreferenceToggle\\_e](#).swAutomaticSyncSettings, True)

and then call one, two, or all three of:

- [ISldWorks::SetUserPreferenceToggle](#)([swUserPreferenceToggle\\_e](#).swAutoSyncSettingsToInclude\_SystemOptions, True)
- [ISldWorks::SetUserPreferenceToggle](#)([swUserPreferenceToggle\\_e](#).swAutoSyncSettingsToInclude\_FileLocations, True)
- [ISldWorks::SetUserPreferenceToggle](#)([swUserPreferenceToggle\\_e](#).swAutoSyncSettingsToInclude\_Customizations, True)

To get the timestamp of the last synchronization,

call [ISldWorks::GetUserPreferenceStringValue](#)([swUserPreferenceStringValue\\_e](#).swLastSynchronizationTimeStamp).

### See Also

[ISldWorks Interface](#)  
[ISldWorks Members](#)  
[ISldWorks::UploadToMySolidWorksSettings Method \(\)](#)

### Availability

SOLIDWORKS 2021 FCS, Revision Number 29

SOLIDWORKS API Help

[Send comments on this topic.](#)

## DragToolBarButton Method (ISldWorks)

[See Also](#)



[SolidWorks.Interop.sldworks Namespace](#) > [ISldWorks Interface](#) : DragToolBarButton Method (ISldWorks)

Copies the specified toolbar button from the specified native SOLIDWORKS toolbar or [ICommandGroup](#) toolbar to the specified native SOLIDWORKS toolbar or ICommandGroup toolbar.

### .NET Syntax

Visual Basic (Declaration)

```

Sub DragToolBarButton( _
    ByVal SourceToolBar As System.Integer, _
    ByVal TargetToolBar As System.Integer, _
    ByVal SourceIndex As System.Integer, _
    ByVal TargetIndex As System.Integer _
)

```

Visual Basic (Usage)



```

Dim instance As ISldWorks
Dim SourceToolBar As System.Integer
Dim TargetToolBar As System.Integer
Dim SourceIndex As System.Integer
Dim TargetIndex As System.Integer

instance.DragToolBarButton(SourceToolBar, TargetToolBar, SourceIndex, TargetIndex)

```

C#

```

void DragToolBarButton(
    System.int SourceToolBar,
    System.int TargetToolBar,
    System.int SourceIndex,
    System.int TargetIndex
)

```

C++/CLI

```

void DragToolBarButton(
    & System.int SourceToolBar,
    & System.int TargetToolBar,
    & System.int SourceIndex,
    & System.int TargetIndex
)

```

**NOTE:** See [Differences Between Unmanaged C++ and C++/CLI Code](#).

#### Parameters

*SourceToolBar*

ToolBar as defined by [swToolBar](#) or if a CommandGroup toolbar, use [ICommandGroup::ToolBarId](#)

*TargetToolBar*

ToolBar as defined by [swToolBar](#) or if a CommandGroup toolbar, use [ICommandGroup::ToolBarId](#)

*SourceIndex*

0-based index of the toolbar button on the native SOLIDWORKS toolbar or CommandGroup toolbar

*TargetIndex*

0-based index of the toolbar button on the native SOLIDWORKS toolbar or CommandGroup toolbar

## Visual Basic for Applications (VBA) Syntax

See [SldWorks::DragToolBarButton](#).

## Remarks

This method makes a copy of the specified source toolbar button and moves a copy of the toolbar button to the target toolbar. This method does not remove the specified source toolbar button from the source toolbar.

Examine the toolbars in the user interface to determine the values for SourceIndex and TargetIndex.

Using this method to drag a toolbar button from one toolbar to another is persistent across sessions of SOLIDWORKS and need only be performed once. For example, do not include this operation in any SolidsWorks API start-up routine because you would then be adding a copy of the same toolbar button to the same target toolbar every time you start up SOLIDWORKS.

## See Also

[ISldWorks Interface](#)

[ISldWorks Members](#)

[ISldWorks::AddToolBar4 Method](#)

[ISldWorks::AddToolBarCommand2 Method](#)

[ISldWorks::GetCommandID Method](#)

[ISldWorks::GetLastToolBarID Method](#)

[ISldWorks::GetToolBarDock2 Method](#)

[ISldWorks::GetToolBarState2 Method](#)

[ISldWorks::HideToolBar2 Method](#)  
[ISldWorks::RemoveToolBar2 Method](#)  
[ISldWorks::SetToolBarDock2 Method](#)  
[ISldWorks::DragToolBarButtonFromCommandID Method](#)

## Availability

SOLIDWORKS 206 FCS, Revision Number 14.0

SOLIDWORKS API Help

[Send comments on this topic.](#)

## DragToolBarButtonFromCommandID Method (ISldWorks)

[See Also](#)



[SolidWorks.Interop.sldworks Namespace](#) > [ISldWorks Interface](#) : DragToolBarButtonFromCommandID Method (ISldWorks)

Copies a button to a toolbar using a command ID.

## .NET Syntax

### Visual Basic (Declaration)

```
Function DragToolBarButtonFromCommandID( _  
    ByVal CommandID As System.Integer, _  
    ByVal TargetToolBar As System.Integer, _  
    ByVal TargetIndex As System.Integer _  
) As System.Integer
```

### Visual Basic (Usage)



```
Dim instance As ISldWorks  
Dim CommandID As System.Integer  
Dim TargetToolBar As System.Integer  
Dim TargetIndex As System.Integer  
Dim value As System.Integer  
  
value = instance.DragToolBarButtonFromCommandID(CommandID, TargetToolBar, TargetIndex)
```

### C#

```
System.int DragToolBarButtonFromCommandID(  
    System.int CommandID,  
    System.int TargetToolBar,  
    System.int TargetIndex  
)
```

### C++/CLI

```
System.int DragToolBarButtonFromCommandID(  
& System.int CommandID,  
& System.int TargetToolBar,  
& System.int TargetIndex  
)
```

**NOTE:** See [Differences Between Unmanaged C++ and C++/CLI Code](#).

### Parameters

*CommandID*

Command ID as defined by [swCommands\\_e](#)

*TargetToolBar*

ToolBar as defined by [swToolBar\\_e](#) or if a CommandGroup toolbar, use [ICommandGroup::ToolBarId](#)

*TargetIndex*

0-based index of the toolbar button on the native SOLIDWORKS toolbar or CommandGroup toolbar

### Return Value

Index of the toolbar or -1 if the button is not added

## Visual Basic for Applications (VBA) Syntax

See [SldWorks::DragToolBarButtonFromCommandID](#).

## See Also

[ISldWorks Interface](#)  
[ISldWorks Members](#)  
[ISldWorks::DragToolBarButton Method](#)  
[ISldWorks::AddToolBar4 Method](#)  
[ISldWorks::AddToolBarCommand2 Method](#)  
[ISldWorks::GetLastToolBarID Method](#)  
[ISldWorks::GetToolBarDock2 Method](#)  
[ISldWorks::GetToolBarState2 Method](#)  
[ISldWorks::HideToolBar2 Method](#)  
[ISldWorks::RemoveToolBar2 Method](#)  
[ISldWorks::SetToolBarDock2 Method](#)

## Availability

SOLIDWORKS 2008 SP4, Revision Number 16.4

SOLIDWORKS API Help

[Send comments on this topic.](#)

## EnableBackgroundProcessing Property (ISldWorks)

[See Also](#) [Example](#)



[SolidWorks.Interop.sldworks Namespace](#) > [ISldWorks Interface](#) : EnableBackgroundProcessing Property (ISldWorks)

Gets or sets whether to enable background processing.

## .NET Syntax

Visual Basic (Declaration)

Property EnableBackgroundProcessing As System.Boolean

Visual Basic (Usage)



```
Dim instance As ISldWorks
Dim value As System.Boolean

instance.EnableBackgroundProcessing = value
value = instance.EnableBackgroundProcessing
```

C#

```
System.bool EnableBackgroundProcessing {get; set;}
```

C++/CLI

```
property System.bool EnableBackgroundProcessing {
    System.bool get();
    void set ( & System.bool value);
}
```

**NOTE:** See [Differences Between Unmanaged C++ and C++/CLI Code](#).

### Property Value

True to enable background processing, false to not

## Visual Basic for Applications (VBA) Syntax

See [SldWorks::EnableBackgroundProcessing](#).

## Example

[Fire Notifications for Background Processing Events \(VBA\)](#)  
[Fire Notifications for Background Processing Events \(VB.NET\)](#)  
[Fire Notifications for Background Processing Events \(C#\)](#)

## Remarks

SOLIDWORKS recommends that you only use this property with [ISldWorks::IsBackgroundProcessingCompleted](#) and [IDrawingDoc::BackgroundProcessingOption](#) when you can quickly open a drawing document via the user interface, but that same drawing takes significantly more time to open programmatically.

To more efficiently and programmatically open a drawing document that requires a lot of CPU time and no user input:

1. Set [ISldWorks::EnableBackgroundProcessing](#) to true.
2. Use [ISldWorks Event BackgroundProcessingStartNotify](#) to handle the background processing start event.

3. Open the drawing document by calling either [ISldWorks::OpenDoc6](#) or [ISldWorks::OpenDoc7](#).
4. Set IDrawingDoc::BackgroundProcessingOption to [swBackgroundProcessOption\\_e.swBackgroundProcessing\\_DeferToApplication](#).
5. Call ISldWorks::IsBackgroundProcessingCompleted repeatedly, which polls the status of the open operation, to know when background processing ends.
6. Use [ISldWorks Event BackgroundProcessingEndNotify](#) to handle the background processing end event.
7. When the open operation is finished, set ISldWorks::EnableBackgroundProcessing to false.

## See Also

[ISldWorks Interface](#)  
[ISldWorks Members](#)

## Availability

SOLIDWORKS 2010 FCS, Revision Number 18.0

SOLIDWORKS API Help

[Send comments on this topic.](#)

## EnableFileMenu Property (ISldWorks)

[See Also](#)



[SolidWorks.Interop.sldworks Namespace](#) > [ISldWorks Interface](#) : EnableFileMenu Property (ISldWorks)

Gets or sets whether to enable file-related menus and toolbars.

## .NET Syntax

### Visual Basic (Declaration)

Property EnableFileMenu As System.Boolean

### Visual Basic (Usage)



```
Dim instance As ISldWorks
Dim value As System.Boolean

instance.EnableFileMenu = value

value = instance.EnableFileMenu
```

### C#

```
System.bool EnableFileMenu {get; set;}
```

### C++/CLI

```
property System.bool EnableFileMenu {
    System.bool get();
    void set ( & System.bool value);
}
```

**NOTE:** See [Differences Between Unmanaged C++ and C++/CLI Code](#).

### Property Value

True to enable file-related menus and toolbars (e.g., open a document, create a new document, open a recent document, etc.); false to disable file-related menus and toolbars

## Visual Basic for Applications (VBA) Syntax

See [SldWorks::EnableFileMenu](#).

## Example

### Visual Basic for Applications (VBA)

Option Explicit

```
Dim swApp As SldWorks.SldWorks
Sub main()
```

```
Set swApp = Application.SldWorks
```

```
' Disable file-related menus and toolbars
swApp.EnableFileMenu = False
```

' Enable file-related menus and toolbars

swApp.**EnableFileMenu** = True

End Sub

#### See Also

[ISldWorks Interface](#)  
[ISldWorks Members](#)  
[IModelDoc2::Toolbars](#)

#### Availability

SOLIDWORKS 2009 FCS, Revision Number 17.0

SOLIDWORKS API Help

[Send comments](#) on this topic.

### EnablePhotoWorksProgressiveRender Method (ISldWorks)

[See Also](#)



[SolidWorks.Interop.sldworks Namespace](#) > [ISldWorks Interface](#) : EnablePhotoWorksProgressiveRender Method (ISldWorks)

Obsolete. Not superseded.

#### .NET Syntax

##### Visual Basic (Declaration)

```
Sub EnablePhotoWorksProgressiveRender( _  
    ByVal BEnable As System.Boolean _  
)
```

##### Visual Basic (Usage)



```
Dim instance As ISldWorks  
Dim BEnable As System.Boolean  
  
instance.EnablePhotoWorksProgressiveRender(BEnable)
```

##### C#

```
void EnablePhotoWorksProgressiveRender(  
    System.bool BEnable  
)
```

##### C++/CLI

```
void EnablePhotoWorksProgressiveRender(  
& System.bool BEnable  
)
```

**NOTE:** See [Differences Between Unmanaged C++ and C++/CLI Code](#).

#### Parameters

*BEnable*

True to enable PhotoWorks progressive rendering, false to not

#### Visual Basic for Applications (VBA) Syntax

See [SldWorks::EnablePhotoWorksProgressiveRender](#).

#### See Also

[ISldWorks Interface](#)  
[ISldWorks Members](#)

## Availability

SOLIDWORKS 2009 FCS, Revision Number 17.0

SOLIDWORKS API Help

[Send comments on this topic.](#)

## EnableStereoDisplay Method (ISldWorks)

[See Also](#)



[SolidWorks.Interop.sldworks Namespace](#) > [ISldWorks Interface](#) : EnableStereoDisplay Method (ISldWorks)

Obsolete and not superseded. Functionality no longer implemented.

## .NET Syntax

### Visual Basic (Declaration)

```
Function EnableStereoDisplay( _  
    ByVal BEnable As System.Boolean _  
) As System.Boolean
```

### Visual Basic (Usage)



```
Dim instance As ISldWorks  
Dim BEnable As System.Boolean  
Dim value As System.Boolean  
  
value = instance.EnableStereoDisplay(BEnable)
```

### C#

```
System.bool EnableStereoDisplay(  
    System.bool BEnable  
)
```

### C++/CLI

```
System.bool EnableStereoDisplay(  
& System.bool BEnable  
)
```

**NOTE:** See [Differences Between Unmanaged C++ and C++/CLI Code](#).

### Parameters

*BEnable*

Bitfield flags that control the application's stereo support status

### Return Value

True if stereo attribute setting was successful, false if not

## Visual Basic for Applications (VBA) Syntax

See [SldWorks::EnableStereoDisplay](#).

## Remarks

You must select the **Enable Quadbuffered Stereo API** check box for NVIDIA Quadro4 OpenGL video cards before opening any windows.

Calling this method with bit #0, the low bit, of the flags field set (flags |= 0x01) sets up all subsequently opened document windows to be capable of displaying stereo; already opened document windows are not affected. If this method is not called, or if it is called with the low bit of flags cleared, the document windows are not be capable of displaying stereo.

Bit #1 controls whether or not 3D scenes are displayed to separate left-eye and right-eye stereoscopic buffers. If bit #1 of the flags field is set (flags |= 0x02), separately buffered stereo pairs are rendered for all windows with 3D scenes that are capable of displaying stereo.

Thus, any plug-in that might need to display stereoscopically should, upon loading, immediately call this method, with the flags field set to 0x01. To actually activate stereo display, call this method with the flags field set to 0x03. To deactivate stereo display, call this method with the flags field set to 0x01. Finally, just before the plug-in uninstalls, restore SOLIDWORKS' default behavior by calling this method with the flags field set to 0x00.

For the stereo pair renderings to appear stereoscopic, call [IModelView::SetStereoSeparation](#) or [IModelView::!SetStereoSeparation](#). By default, the stereo rendering-control attributes that are set by [IModelView::SetStereoSeparation](#) or [IModelView::!SetStereoSeparation](#) are set for identical left-eye and right-eye renderings.

## See Also

[ISldWorks Interface](#)  
[ISldWorks Members](#)

SOLIDWORKS API Help

[Send comments](#) on this topic.

## EnumDocuments Method (ISldWorks)

[See Also](#)



[SolidWorks.Interop.sldworks Namespace](#) > [ISldWorks Interface](#) : EnumDocuments Method (ISldWorks)

Obsolete. Superseded by [ISldWorks::EnumDocuments2](#).

## .NET Syntax

### Visual Basic (Declaration)

```
Function EnumDocuments() As EnumDocuments
```

### Visual Basic (Usage)



```
Dim instance As ISldWorks  
Dim value As EnumDocuments  
  
value = instance.EnumDocuments()
```

### C#

```
EnumDocuments EnumDocuments()
```

### C++/CLI

```
EnumDocuments^ EnumDocuments();
```

**NOTE:** See [Differences Between Unmanaged C++ and C++/CLI Code](#).

## Visual Basic for Applications (VBA) Syntax

See [SldWorks::EnumDocuments](#).

## See Also

[ISldWorks Interface](#)  
[ISldWorks Members](#)

SOLIDWORKS API Help

[Send comments](#) on this topic.

## EnumDocuments2 Method (ISldWorks)

[See Also](#) [Example](#)



[SolidWorks.Interop.sldworks Namespace](#) > [ISldWorks Interface](#) : EnumDocuments2 Method (ISldWorks)

Gets a list of documents currently open in the application.

## .NET Syntax

### Visual Basic (Declaration)

```
Function EnumDocuments2() As EnumDocuments2
```

### Visual Basic (Usage)



```
Dim instance As ISldWorks  
Dim value As EnumDocuments2  
  
value = instance.EnumDocuments2()
```

### C#

```
EnumDocuments2 EnumDocuments2()
```

C++/CLI

```
EnumDocuments2^ EnumDocuments2();
```

**NOTE:** See [Differences Between Unmanaged C++ and C++/CLI Code](#).

#### Return Value

[Documents enumeration](#)

### Visual Basic for Applications (VBA) Syntax

See [SldWorks::EnumDocuments2](#).

### Example

[Get List of Open Documents \(C++\)](#)

### Remarks

The list of [IModelDoc2](#) objects contained in the [IEnumDocuments2](#) object contain any open IModelDoc2 pointer. This includes IModelDoc2 objects that may have been opened as file references, for example, from an assembly or drawing.

You might want to use the [IModelDoc2.Visible](#) property to determine if a particular document has its own window and is visible to the user.

### See Also

[ISldWorks Interface](#)  
[ISldWorks Members](#)  
[ISldWorks.GetOpenDocument Method](#)  
[ISldWorks.GetOpenDocumentByName Method](#)  
[ISldWorks.CloseAllDocuments Method](#)  
[ISldWorks::CloseDoc Method](#)  
[ISldWorks::GetFirstDocument2 Method](#)  
[ISldWorks::GetFirstDocument Method](#)  
[ISldWorks::ActiveDoc Property](#)  
[ISldWorks::IActiveDoc2 Property](#)

### Availability

SOLIDWORKS 2001Plus FCS, Revision Number 10.0

SOLIDWORKS API Help

[Send comments on this topic.](#)

## ExitApp Method (ISldWorks)

[See Also](#)



[SolidWorks.Interop.sldworks Namespace](#) > [ISldWorks Interface](#) : ExitApp Method (ISldWorks)

Shuts down SOLIDWORKS Design.

### .NET Syntax

Visual Basic (Declaration)

```
Sub ExitApp()
```

Visual Basic (Usage)



```
Dim instance As ISldWorks
```

```
instance.ExitApp()
```

C#

```
void ExitApp()
```

C++/CLI

```
void ExitApp();
```

**NOTE:** See [Differences Between Unmanaged C++ and C++/CLI Code](#).

#### Visual Basic for Applications (VBA) Syntax

See [SLDWorks::ExitApp](#).

#### Remarks

This method is not normally used with macros (\*.swp) because it shuts down your SOLIDWORKS Design session.

For C++ and Visual Basic projects, ending your program does not guarantee that the SLDWORKS processes are closed. During development, you can determine whether processes are left running by checking the Process Viewer and looking for any SLDWORKS processes. Typically, you do not want the SLDWORKS process running after your program has ended. Calling this method ensures that no SLDWORKS processes are left running when your program ends.

However, the CreateObject ("SLDWorks.Application") statement used to start up the SOLIDWORKS Design software either creates a new SOLIDWORKS Design session or it attaches to an existing SOLIDWORKS Design session. If the end-user currently has an open SOLIDWORKS Design session, then your program attaches to it. Performing this method ends that session.

#### See Also

[ISldWorks Interface](#)  
[ISldWorks Members](#)