

SOLIDWORKS API (.NET, VBA, C#) — Reference (284/337): ISldWorks (part 4 of 8)

SOLIDWORKS API Documentation (converted from CHM)

ISldWorks (part 4 of 8) (Type)

SOLIDWORKS API Help

[Send comments](#) on this topic.

GetLineStyle Method (ISldWorks)

[See Also](#) [Example](#)



[SolidWorks.Interop.sldworks Namespace](#) > [ISldWorks Interface](#) : GetLineStyle Method (ISldWorks)

Gets all of the line styles in the specified file.

.NET Syntax

Visual Basic (Declaration)

```
Function GetLineStyle( _  
    ByVal StyleFile As System.String, _  
    ByRef StyleNameList As System.Object, _  
    ByRef StyleList As System.Object _  
) As System.Boolean
```

Visual Basic (Usage)



```
Dim instance As ISldWorks  
Dim StyleFile As System.String  
Dim StyleNameList As System.Object  
Dim StyleList As System.Object  
Dim value As System.Boolean  
  
value = instance.GetLineStyle(StyleFile, StyleNameList, StyleList)
```

C#

```
System.bool GetLineStyle(  
    System.string StyleFile,  
    out System.object StyleNameList,  
    out System.object StyleList  
)
```

C++/CLI

```
System.bool GetLineStyle(  
& System.String^ StyleFile,  
& [Out] System.Object^ StyleNameList,  
& [Out] System.Object^ StyleList  
)
```

NOTE: See [Differences Between Unmanaged C++ and C++/CLI Code](#).

Parameters

StyleFile

Full pathname of the file containing line styles to get

StyleNameList

Array of strings containing line style names

StyleList

Array of strings containing line style types

Return Value

True if successful, false if not

Visual Basic for Applications (VBA) Syntax

See [SldWorks::GetLineStyle](#).

Example

[Manage Drawing Document Line Styles \(C#\)](#)
[Manage Drawing Document Line Styles \(VB.NET\)](#)
[Manage Drawing Document Line Styles \(VBA\)](#)

See Also

[ISldWorks Interface](#)
[ISldWorks Members](#)
[IDrawingDoc::AddLineStyle Method](#)
[IDrawingDoc::DeleteLineStyle Method](#)
[IDrawingDoc::GetLineStyles Method](#)
[IDrawingDoc::LoadLineStyles Method](#)
[IDrawingDoc::SaveLineStyles Method](#)

Availability

SOLIDWORKS 2011 FCS, Revision Number 19.0

SOLIDWORKS API Help

[Send comments on this topic.](#)

GetLocalizedMenuName Method (ISldWorks)

[See Also](#) [Example](#)



[SolidWorks.Interop.sldworks Namespace](#) > [ISldWorks Interface](#) : GetLocalizedMenuName Method (ISldWorks)

Gets a localized menu name for the specified menu ID.

.NET Syntax

Visual Basic (Declaration)

```
Function GetLocalizedMenuName( _  
    ByVal MenuId As System.Integer _  
) As System.String
```

Visual Basic (Usage)



```
Dim instance As ISldWorks  
Dim MenuId As System.Integer  
Dim value As System.String  
  
value = instance.GetLocalizedMenuName(MenuId)
```

C#

```
System.string GetLocalizedMenuName(  
    System.int MenuId  
)
```

C++/CLI

```
System.String^ GetLocalizedMenuName(  
& System.int MenuId  
)
```

NOTE: See [Differences Between Unmanaged C++ and C++/CLI Code](#).

Parameters

MenuId
Menu ID as defined in [swMenuIdentifiers_e](#)

Return Value

String containing the localized menu name

Visual Basic for Applications (VBA) Syntax

See [SldWorks::GetLocalizedMenuName](#).

Example

[Get Language and Localized Menu Names \(VBA\)](#)

Remarks

The string returned allows the application to provide a correctly localized string representing the menu name that menus and menu items can be when added to in the SOLIDWORKS Design user interface.

This method should be called before [ISldWorks::AddMenu](#), [ISldWorks::AddMenuItem3](#), [IFrame::AddMenu](#), or [IFrame::AddMenuItem2](#).

See Also

[ISldWorks Interface](#)
[ISldWorks Members](#)

SOLIDWORKS API Help

[Send comments on this topic.](#)

GetMacroMethods Method (ISldWorks)

[See Also](#)



[SolidWorks.Interop.sldworks Namespace](#) > [ISldWorks Interface](#) : GetMacroMethods Method (ISldWorks)

Gets the names of the modules in the specified macro.

.NET Syntax

Visual Basic (Declaration)

```
Function GetMacroMethods( _  
    ByVal FilePathName As System.String, _  
    ByVal Filter As System.Integer _  
) As System.Object
```

Visual Basic (Usage)



```
Dim instance As ISldWorks  
Dim FilePathName As System.String  
Dim Filter As System.Integer  
Dim value As System.Object  
  
value = instance.GetMacroMethods(FilePathName, Filter)
```

C#

```
System.object GetMacroMethods(  
    System.string FilePathName,  
    System.int Filter  
)
```

C++/CLI

```
System.Object^ GetMacroMethods(  
& System.String^ FilePathName,  
& System.int Filter  
)
```

NOTE: See [Differences Between Unmanaged C++ and C++/CLI Code](#).

Parameters

FilePathName
Path and macro filename whose module names you want
Filter
Filter as defined in [swMacroMethods e](#)

Return Value

Array of names of the modules in FilePathName

Visual Basic for Applications (VBA) Syntax

See [SldWorks::GetMacroMethods](#).

See Also

[ISldWorks Interface](#)
[ISldWorks Members](#)
[ISldWorks::GetCurrentMacroPathFolder Method](#)

[ISldWorks::GetCurrentMacroPathName Method](#)
[ISldWorks::GetCurrentWorkingDirectory Method](#)
[ISldWorks::RunMacro Method](#)

Availability

SOLIDWORKS 2009 FCS, Revision Number 17.0

SOLIDWORKS API Help

[Send comments](#) on this topic.

GetMassProperties Method (ISldWorks)

[See Also](#)



[SolidWorks.Interop.sldworks Namespace](#) > [ISldWorks Interface](#) : GetMassProperties Method (ISldWorks)

Obsolete. Superseded by [ISldWorks::GetMassProperties2](#) and [ISldWorks::IGetMassProperties2](#).

.NET Syntax

Visual Basic (Declaration)

```
Function GetMassProperties( _  
    ByVal FilePathName As System.String, _  
    ByVal ConfigurationName As System.String _  
) As System.Object
```

Visual Basic (Usage)



```
Dim instance As ISldWorks  
Dim FilePathName As System.String  
Dim ConfigurationName As System.String  
Dim value As System.Object  
  
value = instance.GetMassProperties(FilePathName, ConfigurationName)
```

C#

```
System.object GetMassProperties(  
    System.string FilePathName,  
    System.string ConfigurationName  
)
```

C++/CLI

```
System.Object^ GetMassProperties(  
& System.String^ FilePathName,  
& System.String^ ConfigurationName  
)
```

NOTE: See [Differences Between Unmanaged C++ and C++/CLI Code](#).

Parameters

FilePathName

ConfigurationName

Visual Basic for Applications (VBA) Syntax

See [SldWorks::GetMassProperties](#).

See Also

[ISldWorks Interface](#)
[ISldWorks Members](#)

SOLIDWORKS API Help

[Send comments](#) on this topic.

GetMassProperties2 Method (ISldWorks)

[See Also](#) [Example](#)



[SolidWorks.Interop.sldworks Namespace](#) > [ISldWorks Interface](#) : GetMassProperties2 Method (ISldWorks)

Gets the mass properties from the specified document for the specified configuration.

.NET Syntax

Visual Basic (Declaration)

```
Function GetMassProperties2( _  
    ByVal FilePathName As System.String, _  
    ByVal ConfigurationName As System.String, _  
    ByVal Accuracy As System.Integer _  
    ) As System.Object
```

Visual Basic (Usage)



```
Dim instance As ISldWorks  
Dim FilePathName As System.String  
Dim ConfigurationName As System.String  
Dim Accuracy As System.Integer  
Dim value As System.Object  
  
value = instance.GetMassProperties2(FilePathName, ConfigurationName, Accuracy)
```

C#

```
System.object GetMassProperties2(  
    System.string FilePathName,  
    System.string ConfigurationName,  
    System.int Accuracy  
)
```

C++/CLI

```
System.Object^ GetMassProperties2(  
& System.String^ FilePathName,  
& System.String^ ConfigurationName,  
& System.int Accuracy  
)
```

NOTE: See [Differences Between Unmanaged C++ and C++/CLI Code](#).

Parameters

FilePathName

Document path and file name

ConfigurationName

Name of the configuration to use

Accuracy

- 0 = as is
- 1 = default
- 2 = maximum

Return Value

Array of doubles of size 13; last element is the accuracy at which mass properties are calculated

Visual Basic for Applications (VBA) Syntax

See [SldWorks::GetMassProperties2](#).

Example

[Get Mass Properties of Inactive Document \(VBA\)](#)

Remarks

You can get the density of the current SOLIDWORKS part using [ISldWorks::GetUserPreferenceDoubleValue](#) and `swMaterialPropertyDensity`. If the density has not been explicitly set by the user, then SOLIDWORKS uses 1.0. You can also derive the density of the body from the following calculation:

$$\text{Density} = (\text{Mass} / \text{Volume})$$

Consistent with all other functions, this method returns metric units unless otherwise specified.

If this [IModelDoc2](#) object is an assembly, then any suppressed components are not included in the mass property analysis. See [IComponent2::GetSuppression](#) to determine the state of each of the assembly components.

This method returns an empty array if mass properties are not calculated when saving the model. This is a system-level setting and is controlled by [ISldWorks::SetUserPreferenceToggle](#) and `swUpdateMassPropsDuringSave`.

NOTE: The calculated origin for the return values is based on the default coordinate systems of the IModelDoc2, not on the a selected coordinate system.

See Also

[ISldWorks Interface](#)
[ISldWorks Members](#)
[ISldWorks::IGetMassProperties2 Method](#)
[IMassProperty Interface](#)

Availability

SOLIDWORKS 2003 FCS, Revision Number 11.0

SOLIDWORKS API Help

[Send comments on this topic.](#)

GetMaterialDatabaseCount Method (ISldWorks)

[See Also](#)



[SolidWorks.Interop.sldworks Namespace](#) > [ISldWorks Interface](#) : GetMaterialDatabaseCount Method (ISldWorks)

Gets the number of material databases.

.NET Syntax

Visual Basic (Declaration)

```
Function GetMaterialDatabaseCount() As System.Integer
```

Visual Basic (Usage)



```
Dim instance As ISldWorks  
Dim value As System.Integer  
  
value = instance.GetMaterialDatabaseCount()
```

C#

```
System.int GetMaterialDatabaseCount()
```

C++/CLI

```
System.int GetMaterialDatabaseCount();
```

NOTE: See [Differences Between Unmanaged C++ and C++/CLI Code](#).

Return Value

Number of material databases

Visual Basic for Applications (VBA) Syntax

See [SldWorks::GetMaterialDatabaseCount](#).

See Also

[ISldWorks Interface](#)
[ISldWorks Members](#)
[ISldWorks::IGetMaterialDatabases Method](#)
[ISldWorks::GetMaterialDatabases Method](#)

Availability

SOLIDWORKS 2004 FCS, Revision Number 12.0

GetMaterialDatabases Method (ISldWorks)

[See Also](#) [Example](#)



[SolidWorks.Interop.sldworks Namespace](#) > [ISldWorks Interface](#) : GetMaterialDatabases Method (ISldWorks)

Gets the names of the material databases.

.NET Syntax

Visual Basic (Declaration)

```
Function GetMaterialDatabases() As System.Object
```

Visual Basic (Usage)



```
Dim instance As ISldWorks  
Dim value As System.Object
```

```
value = instance.GetMaterialDatabases()
```

C#

```
System.object GetMaterialDatabases()
```

C++/CLI

```
System.Object^ GetMaterialDatabases();
```

NOTE: See [Differences Between Unmanaged C++ and C++/CLI Code](#).

Return Value

Array of strings of the names of the material databases

Visual Basic for Applications (VBA) Syntax

See [SldWorks::GetMaterialDatabases](#).

Example

[Get Material Database and XML Schema File Names \(VBA\)](#)
[Get Material Database Paths of Document \(VBA\)](#)
[Set Material \(C#\)](#)
[Set Material \(VB.NET\)](#)
[Set Material \(VBA\)](#)

Remarks

Material database names must be unique. Do not re-use the name of a material database.

See Also

[ISldWorks Interface](#)
[ISldWorks Members](#)
[ISldWorks::GetMaterialDatabaseCount Method](#)
[ISldWorks::GetMaterialDatabases Method](#)
[ISldWorks::GetMaterialSchemaPathName Method](#)

Availability

SOLIDWORKS 2004 FCS, Revision Number 12.0

GetMaterialSchemaPathName Method (ISldWorks)

[See Also](#) [Example](#)



[SolidWorks.Interop.sldworks Namespace](#) > [ISldWorks Interface](#) : GetMaterialSchemaPathName Method (ISldWorks)

Gets the path for the XML material schema file.

.NET Syntax

Visual Basic (Declaration)

```
Function GetMaterialSchemaPathName() As System.String
```

Visual Basic (Usage)



```
Dim instance As ISldWorks  
Dim value As System.String  
  
value = instance.GetMaterialSchemaPathName()
```

C#

```
System.string GetMaterialSchemaPathName()
```

C++/CLI

```
System.String^ GetMaterialSchemaPathName();
```

NOTE: See [Differences Between Unmanaged C++ and C++/CLI Code](#).

Return Value

Path for the XML material schema file

Visual Basic for Applications (VBA) Syntax

See [SldWorks::GetMaterialSchemaPathName](#).

Example

[Get Material Database and XML Schema File Names \(VBA\)](#)
[Set Material \(C#\)](#)
[Set Material \(VB.NET\)](#)
[Set Material \(VBA\)](#)

See Also

[ISldWorks Interface](#)
[ISldWorks Members](#)
[ISldWorks::IGetMaterialDatabases Method](#)
[ISldWorks::GetMaterialDatabases Method](#)
[ISldWorks::GetMaterialDatabaseCount Method](#)

Availability

SOLIDWORKS 2004 FCS, Revision Number 12.0

SOLIDWORKS API Help

[Send comments](#) on this topic.

GetMathUtility Method (ISldWorks)

[See Also](#) [Example](#)



[SolidWorks.Interop.sldworks Namespace](#) > [ISldWorks Interface](#) : GetMathUtility Method (ISldWorks)

Gets [IMathUtility](#).

.NET Syntax

Visual Basic (Declaration)

```
Function GetMathUtility() As System.Object
```

Visual Basic (Usage)



```
Dim instance As ISldWorks  
Dim value As System.Object  
  
value = instance.GetMathUtility()
```

C#

```
System.Object GetMathUtility()
```

C++/CLI

```
System.Object^ GetMathUtility();
```

NOTE: See [Differences Between Unmanaged C++ and C++/CLI Code](#).

Return Value

[IMathUtility](#) or null if the operation fails

Visual Basic for Applications (VBA) Syntax

See [SldWorks::GetMathUtility](#).

Example

[Align Assembly Component to Assembly Origin and Planes \(VBA\)](#)
[Dimension Edge in Drawing \(VBA\)](#)
[Get Names of Sketch Segments \(VBA\)](#)
[Rotate Assembly Component on Axis \(VBA\)](#)
[Transform Sketch to Model \(VBA\)](#)
[Zoom to Region \(VBA\)](#)
[Create a Callout Independent of a Selection \(C#\)](#)
[Create a Callout Independent of a Selection \(VB.NET\)](#)
[Create a Callout Independent of a Selection \(VBA\)](#)

See Also

[ISldWorks Interface](#)
[ISldWorks Members](#)
[ISldWorks::IGetMathUtility Method](#)

Availability

SOLIDWORKS 2001 FCS, Revision Number 9.0

SOLIDWORKS API Help

[Send comments on this topic.](#)

GetMenuStrings Method (ISldWorks)

[See Also](#)



[SolidWorks.Interop.sldworks Namespace](#) > [ISldWorks Interface](#) : GetMenuStrings Method (ISldWorks)

Gets the name of the parent menu of the specified menu command.

.NET Syntax

Visual Basic (Declaration)

```
Function GetMenuStrings( _  
    ByVal CommandID As System.Integer, _  
    ByVal DocumentType As System.Integer, _  
    ByRef ParentMenuName As System.String _  
) As System.String
```

Visual Basic (Usage)



```
Dim instance As ISldWorks  
Dim CommandID As System.Integer  
Dim DocumentType As System.Integer  
Dim ParentMenuName As System.String  
Dim value As System.String
```

```
value = instance.GetMenuStrings(CommandID, DocumentType, ParentMenuName)
```

C#

```
System.string GetMenuStrings(  
    System.int CommandID,  
    System.int DocumentType,  
    out System.string ParentMenuName  
)
```

C++/CLI

```
System.String^ GetMenuStrings(  
& System.int CommandID,  
& System.int DocumentType,  
& [Out] System.String^ ParentMenuName  
)
```

NOTE: See [Differences Between Unmanaged C++ and C++/CLI Code](#).

Parameters

CommandID

Command ID of the command whose parent menu's name you want

DocumentType

Document types in which this command exists as defined in [swDocumentTypes](#) e

ParentMenuName

Name of the parent menu of the specified menu command

Return Value

Menu string

Visual Basic for Applications (VBA) Syntax

See [ISldWorks::GetMenuStrings](#).

Remarks

Use this method with methods that require you to supply the name of the menu, such as [ISldWorks::RemoveMenu](#), [IFrame::RenameMenu](#) and [IFrame::RemoveMenu](#).

See Also

[ISldWorks Interface](#)

[ISldWorks Members](#)

Availability

SOLIDWORKS 2007 SP2, Revision Number 15.2

SOLIDWORKS API Help

[Send comments](#) on this topic.

GetModeler Method (ISldWorks)

[See Also](#) [Example](#)



[SolidWorks.Interop.sldworks Namespace](#) > [ISldWorks Interface](#) : GetModeler Method (ISldWorks)

Gets the [IModeler](#) interface.

.NET Syntax

Visual Basic (Declaration)

```
Function GetModeler() As System.Object
```

Visual Basic (Usage)



```
Dim instance As ISldWorks  
Dim value As System.Object
```

```
value = instance.GetModeler()
```

C#

```
System.object GetModeler()
```

C++/CLI

```
System.Object^ GetModeler();
```

NOTE: See [Differences Between Unmanaged C++ and C++/CLI Code](#).

Return Value

[IModeler](#)

Visual Basic for Applications (VBA) Syntax

See [SldWorks::GetModeler](#).

Example

[Create Body From Selected Faces \(VBA\)](#)
[Cut Body in Half Using Macro Feature \(VBA\)](#)
[Get Body Outline \(VBA\)](#)
[Get Parameters and Spline Points for Curve \(VBA\)](#)
[Get Tolerance \(VBA\)](#)
[Create Loft Body \(C#\)](#)
[Create Loft Body \(VB.NET\)](#)
[Create Loft Body \(VBA\)](#)
[Create and Convert Non-manifold Bodies \(C#\)](#)
[Create and Convert Non-manifold Bodies \(VB.NET\)](#)
[Create and Convert Non-manifold Bodies \(VBA\)](#)

See Also

[ISldWorks Interface](#)
[ISldWorks Members](#)
[ISldWorks::IGetModeler Method](#)

SOLIDWORKS API Help

[Send comments on this topic.](#)

GetMouseDragMode Method (ISldWorks)

[See Also](#)



[SolidWorks.Interop.sldworks Namespace](#) > [ISldWorks Interface](#) : GetMouseDragMode Method (ISldWorks)

Gets whether the specified command-mouse mode is in effect.

.NET Syntax

Visual Basic (Declaration)

```
Function GetMouseDragMode( _  
    ByVal Command As System.Integer _  
) As System.Boolean
```

Visual Basic (Usage)



```
Dim instance As ISldWorks  
Dim Command As System.Integer  
Dim value As System.Boolean  
  
value = instance.GetMouseDragMode(Command)
```

C#

```
System.bool GetMouseDragMode(  
    System.int Command  
)
```

C++/CLI

```
System.bool GetMouseDragMode(  
&    System.int Command  
)
```

NOTE: See [Differences Between Unmanaged C++ and C++/CLI Code](#).

Parameters

Command

Command mode you wish to check as defined in [swMouseDragMode_e](#)

Return Value

True if the specified command is the currently running command, false if not

Visual Basic for Applications (VBA) Syntax

See [ISldWorks::GetMouseDragMode](#).

Remarks

This method determines if a special mouse mode is in use. Generally, these mouse modes are indicated visually with a different cursor and different mouse input interpretation. For example, one such mode is View Rotate mode. This is indicated visually to the user with a different cursor. When in this mode, the mouse input manipulates interactive view rotation, and the View Rotate toolbar button is pressed.

A complete list of valid mouse modes can be found in the [swMouseDragMode_e](#) enumeration.

The mouse mode applies to your whole SOLIDWORKS Design session, not a specific document. Therefore, if the user is currently working in an assembly document and is in Translate Assembly Component mode, then switching to a part or drawing document does not exit the mouse mode. If you call this method at this time to check for `swTranslateAssemblyComponent`, it returns True.

That mode is retained until a new command is entered, regardless if that this mode is not appropriate for a part or drawing document. When a new interactive command or API command runs, it terminates the Translate Assembly Component mode.

There is currently no general method to enable these mouse modes. However, several specific functions exist that enable or toggle certain modes. For example, [IAssemblyDoc::TranslateComponent](#) and [IAssemblyDoc::RotateComponent](#). To disable any of these modes, use [IModelDoc2::SetPickMode](#).

See Also

[ISldWorks Interface](#)
[ISldWorks Members](#)
[ISldWorks::SetMouseDragMode Method](#)

Availability

SOLIDWORKS 99, datecode 1999207

SOLIDWORKS API Help

[Send comments on this topic.](#)

GetOpenDocSpec Method (ISldWorks)

[See Also](#) [Example](#)



[SolidWorks.Interop.sldworks Namespace](#) > [ISldWorks Interface](#) : GetOpenDocSpec Method (ISldWorks)

Gets the specifications to use when opening a model document.

.NET Syntax

Visual Basic (Declaration)

```
Function GetOpenDocSpec( _  
    ByVal FileName As System.String _  
) As System.Object
```

Visual Basic (Usage)



```
Dim instance As ISldWorks  
Dim FileName As System.String  
Dim value As System.Object  
  
value = instance.GetOpenDocSpec(FileName)
```

C#

```
System.object GetOpenDocSpec(  
    System.string FileName  
)
```

C++/CLI

```
System.Object^ GetOpenDocSpec(  
& System.String^ FileName  
)
```

NOTE: See [Differences Between Unmanaged C++ and C++/CLI Code](#).

Parameters

FileName

Path and file name of the document to open

Return Value

[Document specification](#)

Visual Basic for Applications (VBA) Syntax

See [ISldWorks::GetOpenDocSpec](#).

Example

[Hide All Edges in Drawing View \(VBA\)](#)
[Open Drawing Document Read-only \(VBA\)](#)
[Get Whether Components Are Loaded \(C#\)](#)
[Get Whether Components Are Loaded \(VB.NET\)](#)
[Get Whether Components Are Loaded \(VBA\)](#)
[Open Assembly Document \(C#\)](#)
[Open Assembly Document \(VB.NET\)](#)
[Open Assembly Document \(VBA\)](#)

See Also

[ISldWorks Interface](#)
[ISldWorks Members](#)

Availability

SOLIDWORKS 2008 FCS, Revision Number 16.0

SOLIDWORKS API Help

[Send comments on this topic.](#)

GetOpenDocument Method (ISldWorks)

[See Also](#) [Example](#)



[SolidWorks.Interop.sldworks Namespace](#) > [ISldWorks Interface](#) : GetOpenDocument Method (ISldWorks)

Gets the open document with the specified name.

.NET Syntax

Visual Basic (Declaration)

```
Function GetOpenDocument( _  
    ByVal DocName As System.String _  
) As ModelDoc2
```

Visual Basic (Usage)



```
Dim instance As ISldWorks  
Dim DocName As System.String  
Dim value As ModelDoc2  
  
value = instance.GetOpenDocument(DocName)
```

C#

```
ModelDoc2 GetOpenDocument(  
    System.string DocName  
)
```

C++/CLI

```
ModelDoc2^ GetOpenDocument(  
&    System.String^ DocName  
)
```

NOTE: See [Differences Between Unmanaged C++ and C++/CLI Code](#).

Parameters

DocName
Name of the document (see **Remarks**)

Return Value

[Model document](#)

 Visual Basic for Applications (VBA) Syntax

See [SldWorks::GetOpenDocument](#).

 Example

[Get Names of Open Documents \(VBA\)](#)

 Remarks

Only call this method for a document that has already been opened in its own window. If you call this method for a document that has not been opened in its own window, then methods on the returned object may not work as expected.

If you do not specify a file extension in the DocName argument, then the file extension of the document is ignored. This can cause problems if you have two different document types with the same name opened; for example, **12345.sldprt** and **12345.sldasm**.

If you do not specify the file extension in your call to this method, then you cannot be sure which document is retrieved. To avoid this problem, you can specify the filename extension in the DocName parameter or you can check the document type after it is activated using [IModelDoc2::GetType](#).

If DocName is an empty string, and...

An assembly is opened

Multiple assemblies are opened

Multile parts are opened

Then this method returns...

The first part of the assembly

The first part of the first assembly

The first part

 See Also

[ISldWorks Interface](#)
[ISldWorks Members](#)
[ISldWorks::CloseAllDocuments Method](#)
[ISldWorks::CloseDoc Method](#)
[ISldWorks::EnumDocuments2 Method](#)
[ISldWorks::GetFirstDocument Method](#)
[ISldWorks::GetOpenDocumentByName Method](#)
[ISldWorks::IGetFirstDocument2 Method](#)
[ISldWorks::IGetDocuments Method](#)
[ISldWorks::GetDocuments Method](#)
[ISldWorks::GetDocumentCount Method](#)

 Availability

SOLIDWORKS 2005 FCS, Revision Number 13.0

SOLIDWORKS API Help

[Send comments on this topic.](#)

GetOpenDocumentByName Method (ISldWorks)

[See Also](#) [Example](#)



[SolidWorks.Interop.sldworks Namespace](#) > [ISldWorks Interface](#) : GetOpenDocumentByName Method (ISldWorks)

Gets the open document with the specified name.

 .NET Syntax

Visual Basic (Declaration)

```
Function GetOpenDocumentByName(  
    ByVal DocumentName As System.String _  
) As System.Object
```

Visual Basic (Usage)



```
Dim instance As ISldWorks  
Dim DocumentName As System.String  
Dim value As System.Object  
  
value = instance.GetOpenDocumentByName(DocumentName)
```

C#

```
System.Object GetOpenDocumentByName(  
    System.String DocumentName  
)
```

C++/CLI

```
System.Object^ GetOpenDocumentByName(  
& System.String^ DocumentName  
)
```

NOTE: See [Differences Between Unmanaged C++ and C++/CLI Code](#).

Parameters

DocumentName

Fully qualified name of the open document (path, filename, and file extension)

Return Value

Open [model document](#) or NULL if the operation fails

Visual Basic for Applications (VBA) Syntax

See [SldWorks::GetOpenDocumentByName](#).

Example

[Get Differences Between Parts \(VBA\)](#)

Remarks

Only call this method for a document that has already been opened in its own window. If you call this method for a document that has not been opened in its own window, then methods on the returned object may not work as expected.

This method is useful for getting a SOLIDWORKS document object when you only have the document name. For example, SOLIDWORKS ever [FileOpenNotify2](#) provides the file name of the document opened, and you can use that name with this method to get the document's object pointer.

See Also

[ISldWorks Interface](#)
[ISldWorks Members](#)
[ISldWorks::CloseAllDocuments Method](#)
[ISldWorks::CloseDoc Method](#)
[ISldWorks::GetFirstDocument Method](#)
[ISldWorks::GetOpenDocument Method](#)
[ISldWorks::IGetFirstDocument2 Method](#)
[ISldWorks::EnumDocuments2 Method](#)
[ISldWorks::IGetOpenDocumentByName2 Method](#)
[ISldWorks::GetDocumentCount Method](#)
[ISldWorks::GetDocuments Method](#)
[ISldWorks::IGetDocuments Method](#)

Availability

SOLIDWORKS 2000 FCS, Revision Number 8.0

GetOpenedFileInfo Method (ISldWorks)

[See Also](#)[SolidWorks.Interop.sldworks Namespace](#) > [ISldWorks Interface](#) : GetOpenedFileInfo Method (ISldWorks)

Gets the name of the last model successfully opened by SOLIDWORKS and the options that were in effect when it opened.

.NET Syntax

Visual Basic (Declaration)

```
Sub GetOpenedFileInfo( _
    ByRef FileName As System.String, _
    ByRef Options As System.Integer _
)
```

Visual Basic (Usage)



```
Dim instance As ISldWorks
Dim FileName As System.String
Dim Options As System.Integer

instance.GetOpenedFileInfo(FileName, Options)
```

C#

```
void GetOpenedFileInfo(
    out System.string FileName,
    out System.int Options
)
```

C++/CLI

```
void GetOpenedFileInfo(
    & [Out] System.String^ FileName,
    & [Out] System.int Options
)
```

NOTE: See [Differences Between Unmanaged C++ and C++/CLI Code](#).

Parameters

FileName

Full path and filename of the last model successfully opened by SOLIDWORKS

*Options*Options in effect when *FileName* opened as defined in [swOpenDocOptions_e](#)

Visual Basic for Applications (VBA) Syntax

See [SldWorks::GetOpenedFileInfo](#).

Example

'VBA

```
Dim swApp As SldWorks.SldWorks
Dim path As String
Dim docspec As SldWorks.DocumentSpecification
Dim opened As String
Dim Options As Long
Dim Part As SldWorks.ModelDoc2
Dim boolstatus As Boolean
Dim longstatus As Long, longwarnings As Long
Option Explicit
Sub main()

    Set swApp = Application.SldWorks
    swApp.CloseAllDocuments True
    path = "C:\Users\Public\Documents\SOLIDWORKS\SOLIDWORKS 2018\tutorial\api\bagel.sldprt"
    Set docspec = swApp.GetOpenDocSpec(path)
```

```

Set Part = swApp.OpenDoc7(docspec)
Set Part = swApp.OpenDoc6("C:\Users\Public\Documents\SOLIDWORKS\SOLIDWORKS
2018\tutorial\api\coffeecup.sldprt", 1, 0, "", longstatus, longwarnings)
Set Part = swApp.OpenDoc6("C:\Users\Public\Documents\SOLIDWORKS\SOLIDWORKS
2018\tutorial\api\toaster.sldprt", 1, 0, "", longstatus, longwarnings)

' None of the above documents successfully opened through the API get returned by
GetOpenedFileInfo
swApp.GetOpenedFileInfo opened, Options
Debug.Print "Last successfully opened file: " & opened
Debug.Print "Options as defined in swOpenDocOptions_e: " & Options

End Sub

```

Remarks

This method considers only models opened through the SOLIDWORKS Design user interface. This method does not consider models successfully opened through the API, unless the API open an assembly. In that case, each assembly component is opened by SOLIDWORKS, and this method determines which of those assembly's components was successfully opened last.

See Also

[ISldWorks Interface](#)
[ISldWorks Members](#)
[ISldWorks::GetOpenDocument Method](#)
[ISldWorks::GetOpenDocumentByName Method](#)
[ISldWorks::GetOpenFileName Method](#)
[ISldWorks::IGetOpenDocumentByName2 Method](#)
[ISldWorks::EnumDocuments2 Method](#)

Availability

SOLIDWORKS 2005 FCS, Revision Number 13.0

SOLIDWORKS API Help

[Send comments on this topic.](#)

GetOpenFileName Method (ISldWorks)

[See Also](#)



[SolidWorks.Interop.sldworks Namespace](#) > [ISldWorks Interface](#) : GetOpenFileName Method (ISldWorks)

Obsolete. Superseded by [ISldWorks::GetOpenFileName2](#).

.NET Syntax

Visual Basic (Declaration)

```

Function GetOpenFileName( _
    ByVal DialogTitle As System.String, _
    ByVal InitialFileName As System.String, _
    ByVal FileFilter As System.String, _
    ByRef OpenOptions As System.Integer, _
    ByRef ConfigName As System.String, _
    ByRef DisplayName As System.String _
) As System.String

```

Visual Basic (Usage)

```

Dim instance As ISldWorks
Dim DialogTitle As System.String
Dim InitialFileName As System.String
Dim FileFilter As System.String
Dim OpenOptions As System.Integer
Dim ConfigName As System.String
Dim DisplayName As System.String
Dim value As System.String

```



```
value = instance.GetOpenFileName(DialogTitle, InitialFileName, FileFilter, OpenOptions,
ConfigName, DisplayName)
```

C#

```
System.string GetOpenFileName(
    System.string DialogTitle,
    System.string InitialFileName,
    System.string FileFilter,
    out System.int OpenOptions,
    out System.string ConfigName,
    out System.string DisplayName
)
```

C++/CLI

```
System.String^ GetOpenFileName(
    & System.String^ DialogTitle,
    & System.String^ InitialFileName,
    & System.String^ FileFilter,
    & [Out] System.int OpenOptions,
    & [Out] System.String^ ConfigName,
    & [Out] System.String^ DisplayName
)
```

NOTE: See [Differences Between Unmanaged C++ and C++/CLI Code](#).

Parameters

DialogTitle
Title of the dialog
InitialFileName
Path and file name of the file to open
FileFilter
File name extension of the file to open
OpenOptions
Not used
ConfigName
Name of the configuration
DisplayName
Recommended file name to use

Return Value

Path and file name of the file to open

Visual Basic for Applications (VBA) Syntax

See [SldWorks::GetOpenFileName](#).

See Also

[ISldWorks Interface](#)
[ISldWorks Members](#)
[ISldWorks::EnumDocuments2 Method](#)
[ISldWorks::GetOpenDocument Method](#)
[ISldWorks::GetOpenDocumentByName Method](#)
[ISldWorks::GetOpenedFileInfo Method](#)
[ISldWorks::iGetOpenDocumentByName2 Method](#)

Availability

SOLIDWORKS 2005 FCS, Revision Number 13.0

SOLIDWORKS API Help

[Send comments on this topic.](#)

GetOpenFileName2 Method (ISldWorks)

[See Also](#) [Example](#)



[SolidWorks.Interop.sldworks Namespace](#) > [ISldWorks Interface](#) : GetOpenFileName2 Method (ISldWorks)

Prompts the user for the name of the file to open.

.NET Syntax

Visual Basic (Declaration)

```

Function GetOpenFileName2( _
    ByVal DialogTitle As System.String, _
    ByVal InitialFileName As System.String, _
    ByVal FileFilter As System.String, _
    ByRef OpenOptions As System.Integer, _
    ByRef ConfigName As System.String, _
    ByRef DisplayName As System.String, _
    ByRef DisplayStateName As System.String _
) As System.String

```

Visual Basic (Usage)



```

Dim instance As ISldWorks
Dim DialogTitle As System.String
Dim InitialFileName As System.String
Dim FileFilter As System.String
Dim OpenOptions As System.Integer
Dim ConfigName As System.String
Dim DisplayName As System.String
Dim DisplayStateName As System.String
Dim value As System.String

value = instance.GetOpenFileName2(DialogTitle, InitialFileName, FileFilter, OpenOptions,
ConfigName, DisplayName, DisplayStateName)

```

C#

```

System.string GetOpenFileName2(
    System.string DialogTitle,
    System.string InitialFileName,
    System.string FileFilter,
    out System.int OpenOptions,
    out System.string ConfigName,
    out System.string DisplayName,
    out System.string DisplayStateName
)

```

C++/CLI

```

System.String^ GetOpenFileName2(
    & System.String^ DialogTitle,
    & System.String^ InitialFileName,
    & System.String^ FileFilter,
    & [Out] System.int OpenOptions,
    & [Out] System.String^ ConfigName,
    & [Out] System.String^ DisplayName,
    & [Out] System.String^ DisplayStateName
)

```

NOTE: See [Differences Between Unmanaged C++ and C++/CLI Code](#).

Parameters

DialogTitle

Title of the dialog

InitialFileName

Path and file name of the file to open

FileFilter

File name extension of the file to open

OpenOptions

Open options as defined by [swGetOpenFileNameOptions_e](#)

ConfigName

Name of configuration of InitialFileName; comma-separated list of sheet names beginning with active sheet if OpenOptions is

swGetOpenFileNameOptions_e.swGetOpenFileNameOptions_SelectedSheets

DisplayName

Recommended name to use for opened file

DisplayStateName

Selected display state name

Return Value

Path and file name of the file to open

See [SldWorks::GetOpenFileName2](#).

Example

[Open File \(VBA\)](#)

See Also

[ISldWorks Interface](#)
[ISldWorks Members](#)

Availability

SOLIDWORKS 2022 FCS, Revision Number 30

SOLIDWORKS API Help

[Send comments on this topic.](#)

GetPreviewBitmap Method (ISldWorks)

[See Also](#) [Example](#)



[SolidWorks.Interop.sldworks Namespace](#) > [ISldWorks Interface](#) : GetPreviewBitmap Method (ISldWorks)

Gets the preview bitmap (.bmp) for the specified configuration, regardless if the SOLIDWORKS document is open or closed.

.NET Syntax

Visual Basic (Declaration)

```
Function GetPreviewBitmap( _  
    ByVal FilePathName As System.String, _  
    ByVal ConfigName As System.String _  
) As System.Object
```

Visual Basic (Usage)



```
Dim instance As ISldWorks  
Dim FilePathName As System.String  
Dim ConfigName As System.String  
Dim value As System.Object  
  
value = instance.GetPreviewBitmap(FilePathName, ConfigName)
```

C#

```
System.object GetPreviewBitmap(  
    System.string FilePathName,  
    System.string ConfigName  
)
```

C++/CLI

```
System.Object^ GetPreviewBitmap(  
& System.String^ FilePathName,  
& System.String^ ConfigName  
)
```

NOTE: See [Differences Between Unmanaged C++ and C++/CLI Code](#).

Parameters

FilePathName

Path and file name of the SOLIDWORKS document

ConfigName

Name of the configuration

Return Value

Dispatch pointer to IPictureDisp interface, the preview bitmap (.bmp) (see **Remarks**)

Visual Basic for Applications (VBA) Syntax

See [ISldWorks::GetPreviewBitmap](#).

Example

[Get Preview Bitmap \(VBA\)](#)

Remarks

The preview bitmap is the bitmap (.bmp) that appears in the **Preview** box on the Open dialog.

NOTES:

- Currently only in-process applications (that is, macros or add-ins) can use this method; out-of-process applications (that is, executables) will get an automation error because the IPictureDisp interface cannot be marshalled across process boundaries. This is a Microsoft behavior by design. See the Microsoft Knowledge Base for details.
- This method is not supported in macros or out-of-process applications in SOLIDWORKS x64.

See Also

[ISldWorks Interface](#)
[ISldWorks Members](#)
[ISldWorks::PreviewDoc Method](#)
[ISldWorks::PreviewDocx64 Method](#)
[ISldWorks::GetPreviewBitmapFile Method](#)
[IModelDoc2::SaveBMP Method](#)

Availability

SOLIDWORKS 2003 SP1, Revision Number 11.1

SOLIDWORKS API Help

[Send comments on this topic.](#)

GetPreviewBitmapFile Method (ISldWorks)

[See Also](#) [Example](#)



[SolidWorks.Interop.sldworks Namespace](#) > [ISldWorks Interface](#) : GetPreviewBitmapFile Method (ISldWorks)

Gets the specified preview bitmap of a document and saves it as a Windows bitmap file (.bmp) using the specified filename.

.NET Syntax

Visual Basic (Declaration)

```
Function GetPreviewBitmapFile( _  
    ByVal DocumentPath As System.String, _  
    ByVal ConfigName As System.String, _  
    ByVal BitMapFile As System.String _  
    ) As System.Boolean
```

Visual Basic (Usage)

```
Dim instance As ISldWorks  
Dim DocumentPath As System.String  
Dim ConfigName As System.String  
Dim BitMapFile As System.String  
Dim value As System.Boolean  
  
value = instance.GetPreviewBitmapFile(DocumentPath, ConfigName, BitMapFile)
```

C#

```
System.bool GetPreviewBitmapFile(  
    System.string DocumentPath,  
    System.string ConfigName,  
    System.string BitMapFile  
)
```

C++/CLI

```
System.bool GetPreviewBitmapFile(  
& System.String^ DocumentPath,  
& System.String^ ConfigName,
```

```
& System.String^ BitMapFile
)
```

NOTE: See [Differences Between Unmanaged C++ and C++/CLI Code](#).

Parameters

DocumentPath
Path and file name of the SOLIDWORKS document whose preview bitmap (.bmp) you want to save
ConfigName
Name of the configuration
BitMapFile
Filename for the preview

Return Value

True if the preview bitmap (.bmp) is saved, false if not

Visual Basic for Applications (VBA) Syntax

See [SldWorks::GetPreviewBitmapFile](#).

Example

[Save Configuration Data \(C#\)](#)
[Save Configuration Data \(VB.NET\)](#)
[Save Configuration Data \(VBA\)](#)

See Also

[ISldWorks Interface](#)
[ISldWorks Members](#)
[ISldWorks::GetPreviewBitmap Method](#)
[ISldWorks::PreviewDoc Method](#)
[ISldWorks::PreviewDocx64 Method](#)
[IModelDoc2::SaveBMP Method](#)

Availability

SOLIDWORKS 2008 Sp2, Revision Number 16.2

SOLIDWORKS API Help

[Send comments on this topic.](#)

GetProcessID Method (ISldWorks)

[See Also](#) [Example](#)



[SolidWorks.Interop.sldworks Namespace](#) > [ISldWorks Interface](#) : GetProcessID Method (ISldWorks)

Gets the process ID for the current SOLIDWORKS Design session.

.NET Syntax

Visual Basic (Declaration)

```
Function GetProcessID() As System.Integer
```

Visual Basic (Usage)



```
Dim instance As ISldWorks
Dim value As System.Integer

value = instance.GetProcessID()
```

C#

```
System.int GetProcessID()
```

C++/CLI

```
System.int GetProcessID();
```

NOTE: See [Differences Between Unmanaged C++ and C++/CLI Code](#).

Return Value

Process ID

Visual Basic for Applications (VBA) Syntax

See [SldWorks::GetProcessID](#).

Example

[Get Process ID of SOLIDWORKS Session \(C#\)](#)
[Get Process ID of SOLIDWORKS Session \(VB.NET\)](#)
[Get Process ID of SOLIDWORKS Session \(VBA\)](#)

See Also

[ISldWorks Interface](#)
[ISldWorks Members](#)

Availability

SOLIDWORKS 2001Plus FCS, Revision Number 10.0

SOLIDWORKS API Help

[Send comments](#) on this topic.

GetRayTraceRenderer Method (ISldWorks)

[See Also](#) [Example](#)



[SolidWorks.Interop.sldworks Namespace](#) > [ISldWorks Interface](#) : GetRayTraceRenderer Method (ISldWorks)

Get a ray-trace rendering engine.

.NET Syntax

Visual Basic (Declaration)

```
Function GetRayTraceRenderer( _  
    ByVal RendererType As System.Integer _  
) As System.Object
```

Visual Basic (Usage)



```
Dim instance As ISldWorks  
Dim RendererType As System.Integer  
Dim value As System.Object  
  
value = instance.GetRayTraceRenderer(RendererType)
```

C#

```
System.object GetRayTraceRenderer(  
    System.int RendererType  
)
```

C++/CLI

```
System.Object^ GetRayTraceRenderer(  
& System.int RendererType  
)
```

NOTE: See [Differences Between Unmanaged C++ and C++/CLI Code](#).

Parameters

RendererType

Type of ray-trace rendering engine as defined in [swRayTraceRenderType_e](#)

Return Value

[Ray trace renderer](#)

Visual Basic for Applications (VBA) Syntax

See [SldWorks::GetRayTraceRenderer](#).

Example

[Render Model \(C#\)](#)
[Render Model \(VB.NET\)](#)
[Render Model \(VBA\)](#)

See Also

[ISldWorks Interface](#)
[ISldWorks Members](#)
[ISldWorks::IGetRayTraceRenderer Method](#)

Availability

SOLIDWORKS 2011 FCS, Revision Number 19.0

SOLIDWORKS API Help

[Send comments on this topic.](#)

GetRecentFiles Method (ISldWorks)

[See Also](#)



[SolidWorks.Interop.sldworks Namespace](#) > [ISldWorks Interface](#) : GetRecentFiles Method (ISldWorks)

Gets a list of the most recently used files.

.NET Syntax

Visual Basic (Declaration)

```
Function GetRecentFiles() As System.Object
```

Visual Basic (Usage)



```
Dim instance As ISldWorks
Dim value As System.Object

value = instance.GetRecentFiles()
```

C#

```
System.Object GetRecentFiles()
```

C++/CLI

```
System.Object^ GetRecentFiles();
```

NOTE: See [Differences Between Unmanaged C++ and C++/CLI Code](#).

Return Value

List of most recently used files (see **Remarks**)

Visual Basic for Applications (VBA) Syntax

See [SldWorks::GetRecentFiles](#).

Example

```
'-----
Option Explicit
Sub main()
    Dim swApp           As SldWorks.SldWorks
    Dim vFileArr         As Variant
    Dim i                As Long
    Set swApp = Application.SldWorks
```

```

vFileArr = swApp.GetRecentFiles

For i = 0 To UBound(vFileArr) Step 2
    Debug.Print vFileArr(i + 1) & " --> " & vFileArr(i)
Next i
End Sub
'-----

```

Remarks

The list is returned in pairs of files. For each pair, the first item is the fully qualified path to the file. The second item is just the filename, as it appears in the most recent used list in the SOLIDWORKS **File** menu.

See Also

[ISldWorks Interface](#)
[ISldWorks Members](#)

Availability

SOLIDWORKS 2004 FCS, Revision Number 12.0

SOLIDWORKS API Help

[Send comments on this topic.](#)

GetRoutingSettings Method (ISldWorks)

[See Also](#) [Example](#)



[SolidWorks.Interop.sldworks Namespace](#) > [ISldWorks Interface](#) : GetRoutingSettings Method (ISldWorks)

Gets routing settings.

.NET Syntax

Visual Basic (Declaration)

```
Function GetRoutingSettings() As RoutingSettings
```

Visual Basic (Usage)

```
Dim instance As ISldWorks
Dim value As RoutingSettings

value = instance.GetRoutingSettings()
```

C#

```
RoutingSettings GetRoutingSettings()
```

C++/CLI

```
RoutingSettings^ GetRoutingSettings();
```

NOTE: See [Differences Between Unmanaged C++ and C++/CLI Code](#).

Return Value

[IRoutingSettings](#)

Visual Basic for Applications (VBA) Syntax

See [SldWorks::GetRoutingSettings](#).

Example

[Get and Save Routing Settings \(VBA\)](#)
[Get and Save Routing Settings \(VB.NET\)](#)
[Get and Save Routing Settings \(C#\)](#)

See Also

[ISldWorks Interface](#)
[ISldWorks Members](#)

Availability

SOLIDWORKS 2011 FCS, Revision Number 19.0

SOLIDWORKS API Help

[Send comments on this topic.](#)

GetRunningCommandInfo Method (ISldWorks)

[See Also](#) [Example](#)



[SolidWorks.Interop.sldworks Namespace](#) > [ISldWorks Interface](#) : GetRunningCommandInfo Method (ISldWorks)

Get a command's ID or PropertyManager page's command ID, title, and whether it is active in the user-interface.

.NET Syntax

Visual Basic (Declaration)

```
Sub GetRunningCommandInfo( _  
    ByRef CommandID As System.Integer, _  
    ByRef PMTitle As System.String, _  
    ByRef IsUiActive As System.Boolean _  
)
```

Visual Basic (Usage)



```
Dim instance As ISldWorks  
Dim CommandID As System.Integer  
Dim PMTitle As System.String  
Dim IsUiActive As System.Boolean  
  
instance.GetRunningCommandInfo(CommandID, PMTitle, IsUiActive)
```

C#

```
void GetRunningCommandInfo(  
    out System.int CommandID,  
    out System.string PMTitle,  
    out System.bool IsUiActive  
)
```

C++/CLI

```
void GetRunningCommandInfo(  
& [Out] System.int CommandID,  
& [Out] System.String^ PMTitle,  
& [Out] System.bool IsUiActive  
)
```

NOTE: See [Differences Between Unmanaged C++ and C++/CLI Code](#).

Parameters

CommandID
Command's ID or PropertyManager page's command ID as defined in [swCommands](#) e
PMTitle
Title of PropertyManager page
IsUiActive
True if command or PropertyManager page is active in the user-interface, false if not

Visual Basic for Applications (VBA) Syntax

See [SldWorks::GetRunningCommandInfo](#).

Example

[Fire Events When PropertyManager Page Opened and Canceled \(VBA\)](#)
[Fire Events When PropertyManager Page Opened and Canceled \(VB.NET\)](#)
[Fire Events When PropertyManager Page Opened and Canceled \(C#\)](#)

Remarks

Before using this method, you must add a reference to the SOLIDWORKS commands type library or DLL to access the SOLIDWORKS commands.

See Also

[ISldWorks Interface](#)
[ISldWorks Members](#)
[ISldWorks::RunCommand Method](#)
[ISldWorks::IsCommandEnabled Method](#)
[DSldWorksEvents.CommandOpenPreNotifyEventHandler Delegate](#)
[DSldWorksEvents.CommandCloseNotifyEventHandler Delegate](#)

Availability

SOLIDWORKS 2011 FCS, Revision Number 19.0

SOLIDWORKS API Help

[Send comments on this topic.](#)

GetSafeArrayUtility Method (ISldWorks)

[See Also](#) [Example](#)



[SolidWorks.Interop.sldworks Namespace](#) > [ISldWorks Interface](#) : GetSafeArrayUtility Method (ISldWorks)

Gets the ISafeArrayUtility object.

.NET Syntax

Visual Basic (Declaration)

```
Function GetSafeArrayUtility() As System.Object
```

Visual Basic (Usage)



```
Dim instance As ISldWorks  
Dim value As System.Object  
  
value = instance.GetSafeArrayUtility()
```

C#

```
System.Object GetSafeArrayUtility()
```

C++/CLI

```
System.Object^ GetSafeArrayUtility();
```

NOTE: See [Differences Between Unmanaged C++ and C++/CLI Code](#).

Return Value

[ISafeArrayUtility](#) object

Visual Basic for Applications (VBA) Syntax

See [SldWorks::GetSafeArrayUtility](#).

Example

[Get Names of Configurations Using Variant \(C++\)](#)
[Get Object's Persistent Reference ID \(C++\)](#)
[Get Spline Points \(C++\)](#)
[Get Scale Factor of Each Model View \(C++\)](#)

See Also

[ISldWorks Interface](#)
[ISldWorks Members](#)

Availability

SOLIDWORKS 2015 FCS, Revision Number 23.0

SOLIDWORKS API Help

[Send comments on this topic.](#)

GetSaveTo3DExperienceOptions Method (ISldWorks)

[See Also](#)



[SolidWorks.Interop.sldworks Namespace](#) > [ISldWorks Interface](#) : GetSaveTo3DExperienceOptions Method (ISldWorks)

Initializes save options for a [SOLIDWORKS Design connected to the 3DEXPERIENCE platform](#) document.

.NET Syntax

Visual Basic (Declaration)

```
Function GetSaveTo3DExperienceOptions() As System.Object
```

Visual Basic (Usage)



```
Dim instance As ISldWorks  
Dim value As System.Object
```

```
value = instance.GetSaveTo3DExperienceOptions()
```

C#

```
System.Object GetSaveTo3DExperienceOptions()
```

C++/CLI

```
System.Object^ GetSaveTo3DExperienceOptions();
```

NOTE: See [Differences Between Unmanaged C++ and C++/CLI Code](#).

Return Value

[ISaveTo3DExperienceOptions](#)

Visual Basic for Applications (VBA) Syntax

See [SldWorks::GetSaveTo3DExperienceOptions](#).

See Also

[ISldWorks Interface](#)
[ISldWorks Members](#)

Availability

SOLIDWORKS 2020 SP3.1, Revision Number 28.3.1

SOLIDWORKS API Help

[Send comments on this topic.](#)

GetSearchFolders Method (ISldWorks)

[See Also](#) [Example](#)



[SolidWorks.Interop.sldworks Namespace](#) > [ISldWorks Interface](#) : GetSearchFolders Method (ISldWorks)

Gets the current folder search path as shown in **Tools > Options > System Options > File Locations > Show folders for > Referenced Documents**.

.NET Syntax

Visual Basic (Declaration)

```
Function GetSearchFolders( _
    ByVal FolderType As System.Integer _
) As System.String
```

Visual Basic (Usage)



```
Dim instance As ISldWorks
Dim FolderType As System.Integer
Dim value As System.String

value = instance.GetSearchFolders(FolderType)
```

C#

```
System.string GetSearchFolders(
    System.int FolderType
)
```

C++/CLI

```
System.String^ GetSearchFolders(
    & System.int FolderType
)
```

NOTE: See [Differences Between Unmanaged C++ and C++/CLI Code](#).

Parameters

FolderType

Search folder type; the only type supported is swDocumentType; for an up-to-date listing, see [swSearchFolderTypes_e](#)

Return Value

String containing all of the search folders; each search folder is separated by a semicolon

Visual Basic for Applications (VBA) Syntax

See [SldWorks::GetSearchFolders](#).

Example

[Get and Set Search Folders \(VBA\)](#)
[Get and Set Search Folders \(VB.NET\)](#)
[Get and Set Search Folders \(C#\)](#)

Remarks

Search folder settings are ignored unless **Tools > Options > System Options > External References > Search file locations for external references** is selected. To get and set **Search file locations for external references** in the SOLIDWORKS API, use [swUserPreferenceToggle_e](#).swUseFolderSearchRules with [ISldWorks::GetUserPreferenceToggle](#) and [ISldWorks::SetUserPreferenceToggle](#), respectively.

See Also

[ISldWorks Interface](#)
[ISldWorks Members](#)
[ISldWorks::SetSearchFolders Method](#)
[ISldWorks::GetDataFolder Method](#)
[ISldWorks::SetMissingReferencePathName Method](#)

SOLIDWORKS API Help

[Send comments on this topic.](#)

GetSelectionFilter Method (ISldWorks)

[See Also](#)



[SolidWorks.Interop.sldworks Namespace](#) > [ISldWorks Interface](#) : GetSelectionFilter Method (ISldWorks)

Gets the current selection filter settings for the specified item type.

.NET Syntax

Visual Basic (Declaration)

```
Function GetSelectionFilter( _  
    ByVal SelType As System.Integer _  
) As System.Boolean
```

Visual Basic (Usage)



```
Dim instance As ISldWorks  
Dim SelType As System.Integer  
Dim value As System.Boolean  
  
value = instance.GetSelectionFilter(SelType)
```

C#

```
System.bool GetSelectionFilter(  
    System.int SelType  
)
```

C++/CLI

```
System.bool GetSelectionFilter(  
& System.int SelType  
)
```

NOTE: See [Differences Between Unmanaged C++ and C++/CLI Code](#).

Parameters

SelType

Selection type to verify as defined in [swSelectType_e](#)

Return Value

True if selection of the specified type is allowed, false if selection of the specified type is disabled

Visual Basic for Applications (VBA) Syntax

See [SldWorks::GetSelectionFilter](#).

See Also

[ISldWorks Interface](#)
[ISldWorks Members](#)
[ISldWorks::GetApplySelectionFilter Method](#)
[ISldWorks::GetSelectionFilters Method](#)
[ISldWorks::IGetSelectionFilters Method](#)
[ISldWorks::IGetSelectionFiltersCount Method](#)
[ISldWorks::ISetSelectionFilters Method](#)
[ISldWorks::SetSelectionFilter Method](#)
[ISldWorks::SetSelectionFilters Method](#)
[ISldWorks::SetApplySelectionFilter Method](#)

Availability

SOLIDWORKS 99, datecode 1999207

SOLIDWORKS API Help

[Send comments](#) on this topic.

GetSelectionFilters Method (ISldWorks)

[See Also](#) [Example](#)



[SolidWorks.Interop.sldworks Namespace](#) > [ISldWorks Interface](#) : GetSelectionFilters Method (ISldWorks)

Gets all active selection filters.

.NET Syntax

Visual Basic (Declaration)

```
Function GetSelectionFilters() As System.Object
```

Visual Basic (Usage)



```
Dim instance As ISldWorks  
Dim value As System.Object  
  
value = instance.GetSelectionFilters()
```

C#

```
System.Object GetSelectionFilters()
```

C++/CLI

```
System.Object^ GetSelectionFilters();
```

NOTE: See [Differences Between Unmanaged C++ and C++/CLI Code](#).

Return Value

Array of long values representing the [swSelectType_e](#) enumeration

Visual Basic for Applications (VBA) Syntax

See [SldWorks::GetSelectionFilters](#).

Example

[Set and Toggle Selection Filters \(VBA\)](#)

Remarks

To determine if the selection filter is active, call [ISldWorks::GetApplySelectionFilter](#).

See Also

[ISldWorks Interface](#)
[ISldWorks Members](#)
[ISldWorks::GetSelectionFilter Method](#)
[ISldWorks::IGetSelectionFilters Method](#)
[ISldWorks::IGetSelectionFiltersCount Method](#)
[ISldWorks::ISetSelectionFilters Method](#)
[ISldWorks::SetSelectionFilter Method](#)
[ISldWorks::SetSelectionFilters Method](#)
[ISldWorks::SetApplySelectionFilter Method](#)

Availability

SOLIDWORKS 2000 FCS, Revision Number 8.0

SOLIDWORKS API Help

[Send comments on this topic.](#)

GetSSOFormattedURL Method (ISldWorks)

[See Also](#)



[SolidWorks.Interop.sldworks Namespace](#) > [ISldWorks Interface](#) : GetSSOFormattedURL Method (ISldWorks)

Formats the specified URL for single sign-on.

.NET Syntax

Visual Basic (Declaration)

```
Function GetSSOFormattedURL( _  
    ByVal TargetUrl As System.String _  
) As System.String
```

Visual Basic (Usage)



Copy Code

```
Dim instance As ISldWorks
Dim TargetUrl As System.String
Dim value As System.String

value = instance.GetSSOFormattedURL(TargetUrl)
```

C#

```
System.string GetSSOFormattedURL(
    System.string TargetUrl
)
```

C++/CLI

```
System.String^ GetSSOFormattedURL(
    & System.String^ TargetUrl
)
```

NOTE: See [Differences Between Unmanaged C++ and C++/CLI Code](#).

Parameters

TargetUrl
URL to format

Return Value

URL formatted for single sign-on

Visual Basic for Applications (VBA) Syntax

See [SldWorks::GetSSOFormattedURL](#).

Remarks

Use this method to log into SOLIDWORKS add-ins using the current SOLIDWORKS credentials.

See Also

[ISldWorks Interface](#)
[ISldWorks Members](#)

Availability

SOLIDWORKS 2018 FCS, Revision Number 26.0

SOLIDWORKS API Help

[Send comments on this topic.](#)

GetTemplateSizes Method (ISldWorks)

[See Also](#) [Example](#)



[SolidWorks.Interop.sldworks Namespace](#) > [ISldWorks Interface](#) : GetTemplateSizes Method (ISldWorks)

Gets the sheet properties from a template document.

.NET Syntax

Visual Basic (Declaration)

```
Function GetTemplateSizes( _
    ByVal FileName As System.String _
) As System.Object
```

Visual Basic (Usage)



```
Dim instance As ISldWorks
Dim FileName As System.String
Dim value As System.Object

value = instance.GetTemplateSizes(FileName)
```

C#

```
System.Object GetTemplateSizes(
    System.string FileName
)
```

C++/CLI

```
System.Object^ GetTemplateSizes(
    & System.String^ FileName
)
```

NOTE: See [Differences Between Unmanaged C++ and C++/CLI Code](#).

Parameters

FileName

Name of template with full directory path

Return Value

Array of 3 doubles containing the paper size, width, and height

Visual Basic for Applications (VBA) Syntax

See [SldWorks::GetTemplateSizes](#).

Example

[Get Drawing Template Size \(VBA\)](#)

See Also

[ISldWorks Interface](#)
[ISldWorks Members](#)
[ISldWorks::GetTemplateSizes Method](#)
[ISldWorks::GetDocumentTemplate Method](#)
[ISldWorks::PreSelectDwgTemplateSize Method](#)

Availability

SOLIDWORKS 2001 FCS, Revision Number 9.0

SOLIDWORKS API Help

[Send comments on this topic.](#)

GetToolBarDock Method (ISldWorks)

[See Also](#)



[SolidWorks.Interop.sldworks Namespace](#) > [ISldWorks Interface](#) : GetToolBarDock Method (ISldWorks)

Obsolete. Superseded by [ISldWorks::GetToolBarDock2](#).

.NET Syntax

Visual Basic (Declaration)

```
Function GetToolBarDock( _
    ByVal ModuleIn As System.String, _
    ByVal ToolBarIDIn As System.Integer _
) As System.Integer
```

Visual Basic (Usage)



```
Dim instance As ISldWorks
Dim ModuleIn As System.String
```

```
Dim ToolbarIDIn As System.Integer
Dim value As System.Integer

value = instance.GetToolbarDock(ModuleIn, ToolbarIDIn)
```

C#

```
System.int GetToolbarDock(
    System.string ModuleIn,
    System.int ToolbarIDIn
)
```

C++/CLI

```
System.int GetToolbarDock(
    & System.String^ ModuleIn,
    & System.int ToolbarIDIn
)
```

NOTE: See [Differences Between Unmanaged C++ and C++/CLI Code](#).

Parameters

ModuleIn

ToolbarIDIn

Visual Basic for Applications (VBA) Syntax

See [ISldWorks::GetToolbarDock](#).

See Also

[ISldWorks Interface](#)
[ISldWorks Members](#)

SOLIDWORKS API Help

[Send comments](#) on this topic.

GetToolbarDock2 Method (ISldWorks)

[See Also](#)



[SolidWorks.Interop.sldworks Namespace](#) > [ISldWorks Interface](#) : GetToolbarDock2 Method (ISldWorks)

Gets the docking state of the toolbar.

.NET Syntax

Visual Basic (Declaration)

```
Function GetToolbarDock2( _
    ByVal Cookie As System.Integer, _
    ByVal ToolbarId As System.Integer _
) As System.Integer
```

Visual Basic (Usage)



```
Dim instance As ISldWorks
Dim Cookie As System.Integer
Dim ToolbarId As System.Integer
Dim value As System.Integer

value = instance.GetToolbarDock2(Cookie, ToolbarId)
```

C#

```
System.int GetToolbarDock2(
    System.int Cookie,
    System.int ToolbarId
)
```

C++/CLI

```
System.int GetToolbarDock2(  
& System.int Cookie,  
& System.int ToolBarId  
)
```

NOTE: See [Differences Between Unmanaged C++ and C++/CLI Code](#).

Parameters

Cookie

Identifier of toolbar; this is the same Cookie you specified in [ISwAddin::ConnectToSW](#)

ToolBarId

ID of the toolbar as defined in [swToolBar_e](#)

Return Value

Docking state of the toolbar as defined in [swToolBarDockStatePosition_e](#)

Visual Basic for Applications (VBA) Syntax

See [SldWorks::GetToolbarDock2](#).

Remarks

For information about using this method with the [ISwAddin](#) object, see [Using ISwAddin to Create a SOLIDWORKS Add-in](#).

See Also

[ISldWorks Interface](#)
[ISldWorks Members](#)
[ISldWorks::AddToolBar4 Method](#)
[ISldWorks::AddToolBarCommand2 Method](#)
[ISldWorks::DragToolBarButton Method](#)
[ISldWorks::GetToolBarState2 Method](#)
[ISldWorks::HideToolBar2 Method](#)
[ISldWorks::RemoveToolBar2 Method](#)
[ISldWorks::SetToolBarDock2 Method](#)

Availability

SOLIDWORKS 2001Plus FCS, Revision Number 10.0

SOLIDWORKS API Help

[Send comments on this topic](#).

GetToolBarState Method (ISldWorks)

[See Also](#)



[SolidWorks.Interop.sldworks Namespace](#) > [ISldWorks Interface](#) : GetToolBarState Method (ISldWorks)

Obsolete. Superseded by [ISldWorks::GetToolBarState2](#).

.NET Syntax

Visual Basic (Declaration)

```
Function GetToolBarState(  
    ByVal Module As System.String, _  
    ByVal ToolBarId As System.Integer, _  
    ByVal ToolBarState As System.Integer _  
) As System.Boolean
```

Visual Basic (Usage)



```
Dim instance As ISldWorks  
Dim Module As System.String  
Dim ToolbarId As System.Integer  
Dim ToolbarState As System.Integer  
Dim value As System.Boolean  
  
value = instance.GetToolBarState(Module, ToolbarId, ToolbarState)
```

C#

```
System.bool GetToolbarState(  
    System.string Module,  
    System.int ToolBarId,  
    System.int ToolBarState  
)
```

C++/CLI

```
System.bool GetToolbarState(  
& System.String^ Module,  
& System.int ToolBarId,  
& System.int ToolBarState  
)
```

NOTE: See [Differences Between Unmanaged C++ and C++/CLI Code](#).

Parameters

Module

ToolBarId

ToolBarState

Visual Basic for Applications (VBA) Syntax

See [ISldWorks::GetToolbarState](#).

See Also

[ISldWorks Interface](#)
[ISldWorks Members](#)

SOLIDWORKS API Help

[Send comments](#) on this topic.

GetToolbarState2 Method (ISldWorks)

[See Also](#)



[SolidWorks.Interop.sldworks Namespace](#) > [ISldWorks Interface](#) : GetToolbarState2 Method (ISldWorks)

Gets the state of the toolbar.

.NET Syntax

Visual Basic (Declaration)

```
Function GetToolbarState2( _  
    ByVal Cookie As System.Integer, _  
    ByVal ToolBarId As System.Integer, _  
    ByVal ToolBarState As System.Integer _  
) As System.Boolean
```

Visual Basic (Usage)



```
Dim instance As ISldWorks  
Dim Cookie As System.Integer  
Dim ToolBarId As System.Integer  
Dim ToolBarState As System.Integer  
Dim value As System.Boolean  
  
value = instance.GetToolbarState2(Cookie, ToolBarId, ToolBarState)
```

C#

```
System.bool GetToolbarState2(  
    System.int Cookie,  
    System.int ToolBarId,  
    System.int ToolBarState  
)
```

C++/CLI

```
System.bool GetToolbarState2(  
& System.int Cookie,  
& System.int ToolbarId,  
& System.int ToolbarState  
)
```

NOTE: See [Differences Between Unmanaged C++ and C++/CLI Code](#).

Parameters

Cookie

Identifier of toolbar; this is the same Cookie you specified in [ISwAddin::ConnectToSW](#)

ToolbarId

ID of the toolbar as defined in [swToolbar e](#)

ToolbarState

Toolbar state to query as defined in [swToolbarStates e](#)

Return Value

True or false based on the value specified in ToolbarState

Visual Basic for Applications (VBA) Syntax

See [SldWorks::GetToolbarState2](#).

Remarks

For information about using this method with the [ISwAddin](#) object, see [Using ISwAddin to Create a SOLIDWORKS Add-in](#).

See Also

[ISldWorks Interface](#)
[ISldWorks Members](#)
[ISldWorks::AddToolbar4 Method](#)
[ISldWorks::AddToolbarCommand2 Method](#)
[ISldWorks::DragToolbarButton Method](#)
[ISldWorks::GetToolbarDock2 Method](#)
[ISldWorks::HideToolbar2 Method](#)
[ISldWorks::RemoveToolbar2 Method](#)
[ISldWorks::SetToolbarDock2 Method](#)

Availability

SOLIDWORKS 2001Plus FCS, Revision Number 10.0

SOLIDWORKS API Help

[Send comments on this topic.](#)

GetToolbarVisibility Method (ISldWorks)

[See Also](#)



[SolidWorks.Interop.sldworks Namespace](#) > [ISldWorks Interface](#) : GetToolbarVisibility Method (ISldWorks)

Gets whether this toolbar is visible.

.NET Syntax

Visual Basic (Declaration)

```
Function GetToolbarVisibility( _  
    ByVal Toolbar As System.Integer _  
) As System.Boolean
```

Visual Basic (Usage)



```
Dim instance As ISldWorks  
Dim Toolbar As System.Integer  
Dim value As System.Boolean  
  
value = instance.GetToolbarVisibility(Toolbar)
```

C#

```
System.bool GetToolbarVisibility(  
    System.int Toolbar  
)
```

C++/CLI

```
System.bool GetToolbarVisibility(  
& System.int Toolbar  
)
```

NOTE: See [Differences Between Unmanaged C++ and C++/CLI Code](#).

Parameters

Toolbar

Identifier of toolbar as defined in [swToolbar e](#)

Return Value

True if the toolbar is visible, false if it is hidden

Visual Basic for Applications (VBA) Syntax

See [SldWorks::GetToolbarVisibility](#).

See Also

[ISldWorks Interface](#)
[ISldWorks Members](#)
[ISldWorks::SetToolbarVisibility Method](#)
[ISldWorks::HideToolbar2 Method](#)
[ISldWorks::GetToolbarState2 Method](#)
[IModelDoc2::GetToolbarVisibility Method](#)
[IModelDoc2::SetToolbarVisibility Method](#)
[ISldWorks::AddToolbar5 Method](#)

Availability

SOLIDWORKS 2009 SP03, Revision Number 17.3

SOLIDWORKS API Help

[Send comments](#) on this topic.

GetUserPreferenceDoubleValue Method (ISldWorks)

[See Also](#) [Example](#)



[SolidWorks.Interop.sldworks Namespace](#) > [ISldWorks Interface](#) : GetUserPreferenceDoubleValue Method (ISldWorks)

Gets system default user preference values.

.NET Syntax

Visual Basic (Declaration)

```
Function GetUserPreferenceDoubleValue(  
    ByVal UserPreferenceValue As System.Integer _  
) As System.Double
```

Visual Basic (Usage)



```
Dim instance As ISldWorks  
Dim UserPreferenceValue As System.Integer  
Dim value As System.Double  
  
value = instance.GetUserPreferenceDoubleValue(UserPreferenceValue)
```

C#

```
System.double GetUserPreferenceDoubleValue(  
    System.int UserPreferenceValue  
)
```

C++/CLI

```
System.double GetUserPreferenceDoubleValue(  
& System.int UserPreferenceValue  
)
```

NOTE: See [Differences Between Unmanaged C++ and C++/CLI Code](#).

Parameters

UserPreferenceValue
User preference as defined in [swUserPreferenceDoubleValue_e](#)

Return Value

Value of UserPreferenceValue

Visual Basic for Applications (VBA) Syntax

See [ISldWorks::GetUserPreferenceDoubleValue](#).

Example

[Save Document as TIFF \(VBA\)](#)
[Save Drawing as DXF \(VBA\)](#)
[Save Drawing Sheets as DXF \(VBA\)](#)
[Get and Set User Preferences \(VBA\)](#)
[Get and Set User Preferences \(VB.NET\)](#)
[Get and Set User Preferences \(C#\)](#)

Remarks

This method is intended for user preferences of type double and is equivalent to interactively getting system options in the SOLIDWORKS Design software. See [System Options and Document Properties](#) for details.

See Also

[ISldWorks Interface](#)
[ISldWorks Members](#)
[ISldWorks::GetUserPreferenceIntegerValue Method](#)
[ISldWorks::GetUserPreferenceStringListValue Method](#)
[ISldWorks::GetUserPreferenceStringValue Method](#)
[ISldWorks::GetUserPreferenceToggle Method](#)
[ISldWorks::SetUserPreferenceDoubleValue Method](#)
[ISldWorks::SetUserPreferenceIntegerValue Method](#)
[ISldWorks::SetUserPreferenceStringValue Method](#)
[ISldWorks::SetUserPreferenceToggle Method](#)
[IModelDocExtension::GetUserPreferenceDouble Method](#)
[IModelDocExtension::GetUserPreferenceDoubleValueRange Method](#)
[IModelDocExtension::GetUserPreferenceInteger Method](#)
[IModelDocExtension::GetUserPreferenceString Method](#)
[IModelDocExtension::GetUserPreferenceTextFormat Method](#)
[IModelDocExtension::GetUserPreferenceToggle Method](#)
[IModelDocExtension::SetUserPreferenceDouble Method](#)
[IModelDocExtension::SetUserPreferenceInteger Method](#)
[IModelDocExtension::SetUserPreferenceString Method](#)
[IModelDocExtension::SetUserPreferenceTextFormat Method](#)
[IModelDocExtension::SetUserPreferenceToggle Method](#)

SOLIDWORKS API Help

[Send comments](#) on this topic.

GetUserPreferenceIntegerValue Method (ISldWorks)

[See Also](#) [Example](#)



[SolidWorks.Interop.sldworks Namespace](#) > [ISldWorks Interface](#) : GetUserPreferenceIntegerValue Method (ISldWorks)

Gets system default user preference values.

.NET Syntax

Visual Basic (Declaration)

```
Function GetUserPreferenceIntegerValue( _  
    ByVal UserPreferenceValue As System.Integer _  
) As System.Integer
```

Visual Basic (Usage)



```
Dim instance As ISldWorks
Dim UserPreferenceValue As System.Integer
Dim value As System.Integer

value = instance.GetUserPreferenceIntegerValue(UserPreferenceValue)
```

C#

```
System.int GetUserPreferenceIntegerValue(
    System.int UserPreferenceValue
)
```

C++/CLI

```
System.int GetUserPreferenceIntegerValue(
    & System.int UserPreferenceValue
)
```

NOTE: See [Differences Between Unmanaged C++ and C++/CLI Code](#).

Parameters

UserPreferenceValue

User preference as defined in [swUserPreferenceIntegerValue_e](#)

Return Value

Value of UserPreferenceValue

Visual Basic for Applications (VBA) Syntax

See [SldWorks::GetUserPreferenceIntegerValue](#).

Example

[Get DXF User Preference Settings \(VBA\)](#)
[Import Models as Solids \(VBA\)](#)
[Open All External References \(VBA\)](#)
[Save Drawing as DXF \(VBA\)](#)
[Save Drawing Sheets as DXF \(VBA\)](#)
[Save Rolledback Part as Parasolid File \(VBA\)](#)
[Get and Set User Preferences \(VBA\)](#)
[Get and Set User Preferences \(VB.NET\)](#)
[Get and Set User Preferences \(C#\)](#)

Remarks

This method is intended for user preferences of type integer and is equivalent to interactively getting system options in the SOLIDWORKS Design software. See [System Options and Document Properties](#) for details.

See Also

[ISldWorks Interface](#)
[ISldWorks Members](#)
[ISldWorks::GetUserPreferenceDoubleValue Method](#)
[ISldWorks::GetUserPreferenceStringListValue Method](#)
[ISldWorks::GetUserPreferenceStringValue Method](#)
[ISldWorks::GetUserPreferenceToggle Method](#)
[ISldWorks::SetUserPreferenceDoubleValue Method](#)
[ISldWorks::SetUserPreferenceIntegerValue Method](#)
[ISldWorks::SetUserPreferenceStringListValue Method](#)
[ISldWorks::SetUserPreferenceStringValue Method](#)
[ISldWorks::SetUserPreferenceToggle Method](#)
[IModelDocExtension::SetUserPreferenceDouble Method](#)
[IModelDocExtension::SetUserPreferenceInteger Method](#)
[IModelDocExtension::SetUserPreferenceString Method](#)
[IModelDocExtension::SetUserPreferenceTextFormat Method](#)
[IModelDocExtension::SetUserPreferenceToggle Method](#)
[IModelDocExtension::GetUserPreferenceDouble Method](#)
[IModelDocExtension::GetUserPreferenceDoubleValueRange Method](#)
[IModelDocExtension::GetUserPreferenceInteger Method](#)
[IModelDocExtension::GetUserPreferenceString Method](#)
[IModelDocExtension::GetUserPreferenceTextFormat Method](#)
[IModelDocExtension::GetUserPreferenceToggle Method](#)

Gets the name of the DXF mapping file.

.NET Syntax

Visual Basic (Declaration)

```
Function GetUserPreferenceStringListValue( _  
    ByVal UserPreference As System.Integer _  
) As System.String
```

Visual Basic (Usage)



```
Dim instance As ISldWorks  
Dim UserPreference As System.Integer  
Dim value As System.String  
  
value = instance.GetUserPreferenceStringListValue(UserPreference)
```

C#

```
System.string GetUserPreferenceStringListValue(  
    System.int UserPreference  
)
```

C++/CLI

```
System.String^ GetUserPreferenceStringListValue(  
& System.int UserPreference  
)
```

NOTE: See [Differences Between Unmanaged C++ and C++/CLI Code](#).

Parameters

UserPreference

User preference as defined in [swUserPreferenceStringValue_e](#)

Return Value

Value of UserPreference

Visual Basic for Applications (VBA) Syntax

See [SldWorks::GetUserPreferenceStringListValue](#).

Example

[Save Drawing as DXF \(VBA\)](#)
[Save Drawing Sheets as DXF \(VBA\)](#)

Remarks

See [System Options and Document Properties](#) for details.

See Also

[ISldWorks Interface](#)
[ISldWorks Members](#)
[ISldWorks::GetUserPreferenceDoubleValue Method](#)
[ISldWorks::GetUserPreferenceIntegerValue Method](#)
[ISldWorks::GetUserPreferenceStringValue Method](#)
[ISldWorks::GetUserPreferenceToggle Method](#)
[ISldWorks::SetUserPreferenceIntegerValue Method](#)
[ISldWorks::SetUserPreferenceStringValue Method](#)
[ISldWorks::SetUserPreferenceToggle Method](#)
[IModelDocExtension::GetUserPreferenceDouble Method](#)
[IModelDocExtension::GetUserPreferenceDoubleValueRange Method](#)
[IModelDocExtension::GetUserPreferenceInteger Method](#)
[IModelDocExtension::GetUserPreferenceString Method](#)
[IModelDocExtension::GetUserPreferenceTextFormat Method](#)
[IModelDocExtension::GetUserPreferenceToggle Method](#)
[IModelDocExtension::SetUserPreferenceDouble Method](#)
[IModelDocExtension::SetUserPreferenceInteger Method](#)
[IModelDocExtension::SetUserPreferenceString Method](#)

GetUserPreferenceStringValue Method (ISldWorks)

[See Also](#) [Example](#)



[SolidWorks.Interop.sldworks Namespace](#) > [ISldWorks Interface](#) : GetUserPreferenceStringValue Method (ISldWorks)

Gets system default user preference values.

.NET Syntax

Visual Basic (Declaration)

```
Function GetUserPreferenceStringValue( _  
    ByVal UserPreference As System.Integer _  
) As System.String
```

Visual Basic (Usage)



```
Dim instance As ISldWorks  
Dim UserPreference As System.Integer  
Dim value As System.String  
  
value = instance.GetUserPreferenceStringValue(UserPreference)
```

C#

```
System.string GetUserPreferenceStringValue(  
    System.int UserPreference  
)
```

C++/CLI

```
System.String^ GetUserPreferenceStringValue(  
& System.int UserPreference  
)
```

NOTE: See [Differences Between Unmanaged C++ and C++/CLI Code](#).

Parameters

UserPreference

User preference as defined in [swUserPreferenceStringValue_e](#)

Return Value

Value of UserPreference

Visual Basic for Applications (VBA) Syntax

See [SldWorks::GetUserPreferenceStringValue](#).

Example

[Get Locations and Names of Document Templates \(VBA\)](#)
[Get or Set the Backup Directory \(VBA\)](#)
[Get and Set User Preferences \(VBA\)](#)
[Get and Set User Preferences \(VB.NET\)](#)
[Get and Set User Preferences \(C#\)](#)
[Insert Model Annotations \(C#\)](#)
[Insert Model Annotations \(VB.NET\)](#)
[Insert Model Annotations \(VBA\)](#)
[Fill Holes in Part \(C#\)](#)
[Fill Holes in Part \(VB.NET\)](#)
[Fill Holes in Part \(VBA\)](#)

Remarks

This method is intended for user preferences of type string and is equivalent to interactively getting system options in the SOLIDWORKS Design software. See [System Options and Document Properties](#) for details.

See Also

[ISldWorks Interface](#)
[ISldWorks Members](#)
[ISldWorks::GetUserPreferenceDoubleValue Method](#)
[ISldWorks::GetUserPreferenceIntegerValue Method](#)
[ISldWorks::GetUserPreferenceStringListValue Method](#)
[ISldWorks::GetUserPreferenceToggle Method](#)
[ISldWorks::SetUserPreferenceDoubleValue Method](#)
[ISldWorks::SetUserPreferenceIntegerValue Method](#)
[ISldWorks::SetUserPreferenceStringListValue Method](#)
[ISldWorks::SetUserPreferenceStringValue Method](#)
[ISldWorks::SetUserPreferenceToggle Method](#)
[IModelDocExtension::SetUserPreferenceDouble Method](#)
[IModelDocExtension::SetUserPreferenceInteger Method](#)
[IModelDocExtension::SetUserPreferenceString Method](#)
[IModelDocExtension::SetUserPreferenceTextFormat Method](#)
[IModelDocExtension::SetUserPreferenceToggle Method](#)
[IModelDocExtension::GetUserPreferenceDouble Method](#)
[IModelDocExtension::GetUserPreferenceDoubleValueRange Method](#)
[IModelDocExtension::GetUserPreferenceInteger Method](#)
[IModelDocExtension::GetUserPreferenceString Method](#)
[IModelDocExtension::GetUserPreferenceTextFormat Method](#)
[IModelDocExtension::GetUserPreferenceToggle Method](#)

Availability

SOLIDWORKS 2000 FCS, Revision Number 8.0

SOLIDWORKS API Help

[Send comments](#) on this topic.

GetUserPreferenceToggle Method (ISldWorks)

[See Also](#) [Example](#)



[SolidWorks.Interop.sldworks Namespace](#) > [ISldWorks Interface](#) : GetUserPreferenceToggle Method (ISldWorks)

Gets document default user preference values.

.NET Syntax

Visual Basic (Declaration)

```
Function GetUserPreferenceToggle( _  
    ByVal UserPreferenceToggle As System.Integer _  
) As System.Boolean
```

Visual Basic (Usage)



```
Dim instance As ISldWorks  
Dim UserPreferenceToggle As System.Integer  
Dim value As System.Boolean  
  
value = instance.GetUserPreferenceToggle(UserPreferenceToggle)
```

C#

```
System.bool GetUserPreferenceToggle(  
    System.int UserPreferenceToggle  
)
```

C++/CLI

```
System.bool GetUserPreferenceToggle(  
& System.int UserPreferenceToggle  
)
```

NOTE: See [Differences Between Unmanaged C++ and C++/CLI Code](#).

Parameters

UserPreferenceToggle
User preference as defined in [swUserPreferenceToggle_e](#)

Return Value

True if UserPreferenceToggle is toggled on; false if toggled off

Visual Basic for Applications (VBA) Syntax

See [SldWorks::GetUserPreferenceToggle](#).

Example

[Rename Assembly Components \(VBA\)](#)
[Save Document as TIFF \(VBA\)](#)
[Save Drawing as DXF \(VBA\)](#)
[Save Drawing Sheets as DXF \(VBA\)](#)
[Suppress Rebuild Error Dialogs \(VBA\)](#)
[Get and Set User Preferences \(VBA\)](#)
[Get and Set User Preferences \(VB.NET\)](#)
[Get and Set User Preferences \(C#\)](#)

Remarks

This method is intended for user preferences that can be toggled and is equivalent to interactively getting system options in the SOLIDWORKS Design software.

For example:

```
boolean curState = swapp.GetUserPreferenceToggle( swUseFolderSearchRules)
```

See [System Options and Document Properties](#) for details.

See Also

[ISldWorks Interface](#)
[ISldWorks Members](#)
[ISldWorks::SetUserPreferenceToggle Method](#)
[ISldWorks::SetUserPreferenceStringValue Method](#)
[ISldWorks::SetUserPreferenceStringListValue Method](#)
[ISldWorks::SetUserPreferenceIntegerValue Method](#)
[ISldWorks::SetUserPreferenceDoubleValue Method](#)
[ISldWorks::GetUserPreferenceDoubleValue Method](#)
[ISldWorks::GetUserPreferenceIntegerValue Method](#)
[ISldWorks::GetUserPreferenceStringListValue Method](#)
[ISldWorks::GetUserPreferenceStringValue Method](#)
[IModelDocExtension::GetUserPreferenceDouble Method](#)
[IModelDocExtension::GetUserPreferenceDoubleValueRange Method](#)
[IModelDocExtension::GetUserPreferenceInteger Method](#)
[IModelDocExtension::GetUserPreferenceString Method](#)
[IModelDocExtension::GetUserPreferenceTextFormat Method](#)
[IModelDocExtension::GetUserPreferenceToggle Method](#)
[IModelDocExtension::SetUserPreferenceDouble Method](#)
[IModelDocExtension::SetUserPreferenceInteger Method](#)
[IModelDocExtension::SetUserPreferenceString Method](#)
[IModelDocExtension::SetUserPreferenceTextFormat Method](#)
[IModelDocExtension::SetUserPreferenceToggle Method](#)

SOLIDWORKS API Help

[Send comments on this topic.](#)

GetUserProgressBar Method (ISldWorks)

[See Also](#) [Example](#)



[SolidWorks.Interop.sldworks Namespace](#) > [ISldWorks Interface](#) : GetUserProgressBar Method (ISldWorks)

Gets a progress indicator.

.NET Syntax

Visual Basic (Declaration)

```
Function GetUserProgressBar( _  
    ByRef PProgressBar As UserProgressBar _  
) As System.Boolean
```

Visual Basic (Usage)

```
Dim instance As ISldWorks  
Dim PProgressBar As UserProgressBar  
Dim value As System.Boolean  
  
value = instance.GetUserProgressBar(PProgressBar)
```

C#

```
System.bool GetUserProgressBar(  
    out UserProgressBar PProgressBar
```



)

C++/CLI

```
System.bool GetUserProgressBar(  
& [Out] UserProgressBar^ PProgressBar  
)
```

NOTE: See [Differences Between Unmanaged C++ and C++/CLI Code](#).

Parameters

[PProgressBar](#)
[IUserProgressBar](#)

Return Value

True if the progress indicator object is returned, false if not

Visual Basic for Applications (VBA) Syntax

See [SldWorks::GetUserProgressBar](#).

Example

[Start, Update, and Stop Progress Indicator \(VBA\)](#)
[Start, Update, and Stop Progress Indicator \(VB.NET\)](#)
[Start, Update, and Stop Progress Indicator \(C#\)](#)

See Also

[ISldWorks Interface](#)
[ISldWorks Members](#)
[IStatusBarPane Interface](#)

Availability

SOLIDWORKS 2007 FCS, Revision Number 15.0

SOLIDWORKS API Help

[Send comments on this topic.](#)

GetUserTypeLibReferenceCount Method (ISldWorks)

[See Also](#)



[SolidWorks.Interop.sldworks Namespace](#) > [ISldWorks Interface](#) : GetUserTypeLibReferenceCount Method (ISldWorks)

Gets the number of user-specified type library references.

.NET Syntax

Visual Basic (Declaration)

```
Function GetUserTypeLibReferenceCount() As System.Integer
```

Visual Basic (Usage)

```
Dim instance As ISldWorks  
Dim value As System.Integer  
  
value = instance.GetUserTypeLibReferenceCount()
```

C#

```
System.int GetUserTypeLibReferenceCount()
```

C++/CLI

```
System.int GetUserTypeLibReferenceCount();
```

NOTE: See [Differences Between Unmanaged C++ and C++/CLI Code](#).

Return Value

Number of user-specified type library references

Visual Basic for Applications (VBA) Syntax

See [ISldWorks::GetUserTypeLibReferenceCount](#).

Remarks

Call this method before calling [ISldWorks::IGetUserTypeLibReferences](#) to get the size of the array for that method.

See [Type Libraries](#) for details.

See Also

[ISldWorks Interface](#)
[ISldWorks Members](#)
[ISldWorks::UserTypeLibReferences Property](#)
[ISldWorks::IGetUserTypeLibReferences Method](#)
[ISldWorks::RemoveUserTypeLibReferences Method](#)
[ISldWorks::IGetUserTypeLibReferences Method](#)

Availability

SOLIDWORKS 2005 FCS, Revision Number

SOLIDWORKS API Help

[Send comments](#) on this topic.

GetUserUnit Method (ISldWorks)

[See Also](#)



[SolidWorks.Interop.sldworks Namespace](#) > [ISldWorks Interface](#) : GetUserUnit Method (ISldWorks)

Gets an empty [IUserUnit](#) object of the specified type.

.NET Syntax

Visual Basic (Declaration)

```
Function GetUserUnit( _  
    ByVal UnitType As System.Integer _  
) As System.Object
```

Visual Basic (Usage)



```
Dim instance As ISldWorks  
Dim UnitType As System.Integer  
Dim value As System.Object  
  
value = instance.GetUserUnit(UnitType)
```

C#

```
System.object GetUserUnit(  
    System.int UnitType  
)
```

C++/CLI

```
System.Object^ GetUserUnit(  
& System.int UnitType  
)
```

NOTE: See [Differences Between Unmanaged C++ and C++/CLI Code](#).

Parameters

UnitType

Unit type as defined in [swUserUnitsType_e](#)

Return Value

IUserUnit

Visual Basic for Applications (VBA) Syntax

See [ISldWorks::GetUserUnit](#).

Remarks

The instance of IUserUnit returned by this method is read-write, not persistent, and not tied to any document. Use this instance as a template to store units properties at runtime.

Call [IModelDoc2::GetUserUnit](#) to get the user units of a document.

See Also

[ISldWorks Interface](#)
[ISldWorks Members](#)
[ISldWorks::IGetUserUnit Method](#)
[IModelDoc2::IGetUserUnit Method](#)

Availability

SOLIDWORKS 2001 SP1, Revision Number 9.1

SOLIDWORKS API Help

[Send comments on this topic.](#)

HideBubbleTooltip Method (ISldWorks)

[See Also](#)



[SolidWorks.Interop.sldworks Namespace](#) > [ISldWorks Interface](#) : HideBubbleTooltip Method (ISldWorks)

Hides the bubble ToolTip displayed by [ISldWorks::ShowBubbleTooltipAt2](#).

.NET Syntax

Visual Basic (Declaration)

```
Sub HideBubbleTooltip()
```

Visual Basic (Usage)



```
Dim instance As ISldWorks  
  
instance.HideBubbleTooltip()
```

C#

```
void HideBubbleTooltip()
```

C++/CLI

```
void HideBubbleTooltip();
```

NOTE: See [Differences Between Unmanaged C++ and C++/CLI Code](#).

Visual Basic for Applications (VBA) Syntax

See [SldWorks::HideBubbleTooltip](#).

Example

The following examples show how to display and hide a bubble ToolTip. Click a link to jump to the example in that programming language.

- [C#](#)
- [VB.NET](#)
- [VBA](#)

C#

```
//-----  
  
// Preconditions: SOLIDWORKS is running.
```

```

// Postconditions:
// (1) Bubble ToolTip is shown.
// (2) Bubble ToolTip is hidden.
//-----
using
SOLIDWORKS.Interop.sldworks;
using
SOLIDWORKS.Interop.swconst;
using
System;
namespace
ShowBubbleToolTipAt2SldWorksCSharp.csproj
{
    public partial class SOLIDWORKSMacro
    {
        public void Main()
        {
            // Show bubble ToolTip
            swApp.ShowBubbleToolTipAt2(300, 400, (
int)swArrowPosition.swArrowLeftTop, "Sample Bubble Tooltip", "Message of Sample Bubble
ToolTip", (int)swBitMaps.swBitmapUserDefined, "C:\\Program Files\\SOLIDWORKS
Corp\\SOLIDWORKS\\data\\user macro icons\\questionmark.bmp", "", 0,
(int)swLinkString.swLinkStringNone, "", "");

            // 1. Insert a breakpoint at next command.
            // 2. Examine the SOLIDWORKS graphics area to see the bubble ToolTip.
            // 3. Toggle the breakpoint to hide the bubble ToolTip.
            swApp.HideBubbleTooltip();
        }
        /// <summary>
        /// The SldWorks swApp variable is pre-assigned for you.
        /// </summary>
        public SldWorks swApp;
    }
}

```

VB.NET

```

'-----
' Preconditions: SOLIDWORKS is running.
' Postconditions:
'   (1) Bubble ToolTip is shown.
'   (2) Bubble ToolTip is hidden.
'-----

Imports
SOLIDWORKS.Interop.sldworks
Imports

```

```

SOLIDWORKS.Interop.swconst
Imports

System
Partial Class SOLIDWORKSMacro
Public Sub main()
    ' Show bubble ToolTip
    swApp.ShowBubbleToolTipAt2(300, 400, swArrowPosition.swArrowLeftTop, "Sample Bubble
ToolTip", "Message of Sample Bubble ToolTip", swBitMaps.swBitmapUserDefined,
"C:\Program Files\SOLIDWORKS Corp\SOLIDWORKS\data\user macro icons\questionmark.bmp",
"", 0, swLinkString.swLinkStringNone, "", "")

    Stop

    swApp.HideBubbleToolTip()

End Sub
''' <summary>
''' The SldWorks swApp variable is pre-assigned for you.
''' </summary>
Public swApp As SldWorks
End Class

```

VBA

```

'-----
' Preconditions: SOLIDWORKS is running
'
' Postconditions:
'     (1) Bubble ToolTip is shown.
'     (2) Bubble ToolTip is hidden.
'-----

```

```
Option Explicit
```

```
Sub main()
```

```

    Dim swApp As SldWorks.SldWorks
    Set swApp = Application.SldWorks

    ' Show Bubble ToolTip
    swApp.ShowBubbleToolTipAt2 300, 400, swArrowLeftTop, "Sample Bubble Tooltip",
"Message of Sample Bubble Tooltip", swBitmapUserDefined, "C:\Program Files\SOLIDWORKS
Corp\SOLIDWORKS\data\user macro icons\questionmark.bmp", "", 0, swLinkStringNone, "",
""

```

```
    Stop
```

```
    swApp.HideBubbleToolTip
```

```
End Sub
```

```
'-----
```

See Also

[ISldWorks Interface](#)
[ISldWorks Members](#)

Availability

SOLIDWORKS 2010 FCS, Revision Number 18.0

SOLIDWORKS API Help

[Send comments](#) on this topic.

HideToolbar Method (ISldWorks)

[See Also](#)



[SolidWorks.Interop.sldworks Namespace](#) > [ISldWorks Interface](#) : HideToolbar Method (ISldWorks)

Obsolete. Superseded by [ISldWorks::HideToolbar2](#).

.NET Syntax

Visual Basic (Declaration)

```
Function HideToolbar( _  
    ByVal ModuleName As System.String, _  
    ByVal ToolBarId As System.Integer _  
) As System.Boolean
```

Visual Basic (Usage)



```
Dim instance As ISldWorks  
Dim ModuleName As System.String  
Dim ToolbarId As System.Integer  
Dim value As System.Boolean  
  
value = instance.HideToolbar(ModuleName, ToolbarId)
```

C#

```
System.bool HideToolbar(  
    System.string ModuleName,  
    System.int ToolBarId  
)
```

C++/CLI

```
System.bool HideToolbar(  
& System.String^ ModuleName,  
& System.int ToolBarId  
)
```

NOTE: See [Differences Between Unmanaged C++ and C++/CLI Code](#).

Parameters

ModuleName

ToolBarId

Visual Basic for Applications (VBA) Syntax

See [SldWorks::HideToolbar](#).

See Also

[ISldWorks Interface](#)
[ISldWorks Members](#)

SOLIDWORKS API Help

[Send comments](#) on this topic.

HideToolbar2 Method (ISldWorks)

[See Also](#)



[SolidWorks.Interop.sldworks Namespace](#) > [ISldWorks Interface](#) : HideToolbar2 Method (ISldWorks)

Hides a toolbar created with [ISldWorks::AddToolbar5](#).

.NET Syntax

Visual Basic (Declaration)

```
Function HideToolbar2( _  
    ByVal Cookie As System.Integer, _  
    ByVal ToolBarId As System.Integer _  
) As System.Boolean
```

Visual Basic (Usage)



```
Dim instance As ISldWorks  
Dim Cookie As System.Integer  
Dim ToolbarId As System.Integer  
Dim value As System.Boolean  
  
value = instance.HideToolbar2(Cookie, ToolbarId)
```

C#

```
System.bool HideToolbar2(  
    System.int Cookie,  
    System.int ToolBarId  
)
```

C++/CLI

```
System.bool HideToolbar2(  
& System.int Cookie,  
& System.int ToolBarId  
)
```

NOTE: See [Differences Between Unmanaged C++ and C++/CLI Code](#).

Parameters

Cookie

Identifier of toolbar; this is the same Cookie you specified in [ISwAddin::ConnectToSW](#)

ToolBarId

ID of the toolbar as defined in [swToolBar_e](#)

Return Value

True if toolbar is hidden, false if not

Visual Basic for Applications (VBA) Syntax

See [SldWorks::HideToolbar2](#).

Remarks

For information about using this method with the [ISwAddin](#) object, see [Using ISwAddin to Create a SOLIDWORKS Add-in](#).

See Also

[ISldWorks Interface](#)
[ISldWorks Members](#)
[ISldWorks::AddToolbarCommand2 Method](#)
[ISldWorks::DragToolbarButton Method](#)
[ISldWorks::GetToolBarDock2 Method](#)
[ISldWorks::GetToolBarState2 Method](#)
[ISldWorks::RemoveToolBar2 Method](#)
[ISldWorks::SetToolBarDock2 Method](#)

Availability

SOLIDWORKS 2001Plus FCS, Revision Number 10.0

SOLIDWORKS API Help

[Send comments on this topic.](#)

IActivateDoc Method (ISldWorks)

[See Also](#)



[SolidWorks.Interop.sldworks Namespace](#) > [ISldWorks Interface](#) : IActivateDoc Method (ISldWorks)

Obsolete. Superseded by [ISldWorks::ActivateDoc2](#) and [ISldWorks::IActivateDoc3](#).

.NET Syntax

Visual Basic (Declaration)

```
Function IActivateDoc( _  
    ByVal Name As System.String _  
) As ModelDoc
```

Visual Basic (Usage)



```
Dim instance As ISldWorks  
Dim Name As System.String  
Dim value As ModelDoc  
  
value = instance.IActivateDoc(Name)
```

C#

```
ModelDoc IActivateDoc(  
    System.string Name  
)
```

C++/CLI

```
ModelDoc^ IActivateDoc(  
& System.String^ Name  
)
```

NOTE: See [Differences Between Unmanaged C++ and C++/CLI Code](#).

Parameters

Name

Visual Basic for Applications (VBA) Syntax

See [SldWorks::IActivateDoc](#).

See Also

[ISldWorks Interface](#)
[ISldWorks Members](#)

SOLIDWORKS API Help

[Send comments on this topic.](#)

IActivateDoc2 Method (ISldWorks)

[See Also](#)



[SolidWorks.Interop.sldworks Namespace](#) > [ISldWorks Interface](#) : IActivateDoc2 Method (ISldWorks)

Obsolete. Superseded by [ISldWorks::ActivateDoc2](#) and [ISldWorks::IActivateDoc3](#).

.NET Syntax

Visual Basic (Declaration)

```
Function IActivateDoc2( _  
    ByVal Name As System.String, _
```

```
ByVal Silent As System.Boolean, _  
ByRef Errors As System.Integer _  
) As ModelDoc
```

Visual Basic (Usage)



```
Dim instance As ISldWorks  
Dim Name As System.String  
Dim Silent As System.Boolean  
Dim Errors As System.Integer  
Dim value As ModelDoc  
  
value = instance.IActivateDoc2(Name, Silent, Errors)
```

C#

```
ModelDoc IActivateDoc2(  
    System.string Name,  
    System.bool Silent,  
    out System.int Errors  
)
```

C++/CLI

```
ModelDoc^ IActivateDoc2(  
& System.String^ Name,  
& System.bool Silent,  
& [Out] System.int Errors  
)
```

NOTE: See [Differences Between Unmanaged C++ and C++/CLI Code](#).

Parameters

Name

Silent

Errors

Visual Basic for Applications (VBA) Syntax

See [SldWorks.IActivateDoc2](#).

See Also

[ISldWorks Interface](#)
[ISldWorks Members](#)