

SOLIDWORKS API (.NET, VBA, C#) — Reference (287/337): ISldWorks (part 7 of 8)

SOLIDWORKS API Documentation (converted from CHM)

ISldWorks (part 7 of 8) (Type)

SOLIDWORKS API Help

[Send comments](#) on this topic.

RemoveMenu Method (ISldWorks)

[See Also](#)



[SolidWorks.Interop.sldworks Namespace](#) > [ISldWorks Interface](#) : RemoveMenu Method (ISldWorks)

Removes a menu item from the specified document frame.

.NET Syntax

Visual Basic (Declaration)

```
Function RemoveMenu( _  
    ByVal DocType As System.Integer, _  
    ByVal MenuItemString As System.String, _  
    ByVal CallbackFcnAndModule As System.String _  
) As System.Boolean
```

Visual Basic (Usage)



```
Dim instance As ISldWorks  
Dim DocType As System.Integer  
Dim MenuItemString As System.String  
Dim CallbackFcnAndModule As System.String  
Dim value As System.Boolean  
  
value = instance.RemoveMenu(DocType, MenuItemString, CallbackFcnAndModule)
```

C#

```
System.bool RemoveMenu(  
    System.int DocType,  
    System.string MenuItemString,  
    System.string CallbackFcnAndModule  
)
```

C++/CLI

```
System.bool RemoveMenu(  
& System.int DocType,  
& System.String^ MenuItemString,  
& System.String^ CallbackFcnAndModule  
)
```

NOTE: See [Differences Between Unmanaged C++ and C++/CLI Code](#).

Parameters

DocType

Document type as defined in [swDocumentTypes_e](#)

MenuItemString

Menu string (e.g., submenuString@menuString)

CallbackFcnAndModule

Callback function and module for this menu item as specified when the menu item was added; see [IFrame::AddMenuItem2](#)

Return Value

True if the menu item was removed successfully, false if not

Visual Basic for Applications (VBA) Syntax

See [SldWorks::RemoveMenu](#).

Remarks

When a menu item is added with [ISldWorks::AddMenuItem4](#) or [IFrame::AddMenu](#), the document type for which the menu appears is specified. The DocType argument for this method must match the one used when the menu was created.

See Also

[ISldWorks Interface](#)
[ISldWorks Members](#)
[ISldWorks::GetMenuStrings Method](#)
[ISldWorks::AddMenu Method](#)
[ISldWorks::AddMenuItem3 Method](#)
[ISldWorks::AddMenuPopupItem2 Method](#)
[ISldWorks::RemoveFromMenu Method](#)
[ISldWorks::RemoveFromPopupMenu Method](#)
[ISldWorks::RemoveMenuPopupItem2 Method](#)

SOLIDWORKS API Help

[Send comments](#) on this topic.

RemoveMenuPopupItem Method (ISldWorks)

[See Also](#)



[SolidWorks.Interop.sldworks Namespace](#) > [ISldWorks Interface](#) : RemoveMenuPopupItem Method (ISldWorks)

Obsolete. Superseded by [ISldWorks::RemoveMenuPopupItem2](#).

.NET Syntax

Visual Basic (Declaration)

```
Function RemoveMenuPopupItem( _  
    ByVal DocType As System.Integer, _  
    ByVal SelectType As System.Integer, _  
    ByVal Item As System.String, _  
    ByVal CallbackFcnAndModule As System.String, _  
    ByVal CustomNames As System.String, _  
    ByVal Unused As System.Integer _  
) As System.Boolean
```

Visual Basic (Usage)



```
Dim instance As ISldWorks  
Dim DocType As System.Integer  
Dim SelectType As System.Integer  
Dim Item As System.String  
Dim CallbackFcnAndModule As System.String  
Dim CustomNames As System.String  
Dim Unused As System.Integer  
Dim value As System.Boolean  
  
value = instance.RemoveMenuPopupItem(DocType, SelectType, Item, CallbackFcnAndModule, CustomNames, Unused)
```

C#

```
System.bool RemoveMenuPopupItem(  
    System.int DocType,  
    System.int SelectType,  
    System.string Item,  
    System.string CallbackFcnAndModule,  
    System.string CustomNames,  
    System.int Unused  
)
```

C++/CLI

```
System.bool RemoveMenuPopupItem(  
& System.int DocType,  
& System.int SelectType,  
& System.String^ Item,  
& System.String^ CallbackFcnAndModule,  
& System.String^ CustomNames,  
& System.int Unused  
)
```

NOTE: See [Differences Between Unmanaged C++ and C++/CLI Code](#).

Parameters

DocType
SelectType
Item
CallbackFcnAndModule
CustomNames
Unused

Visual Basic for Applications (VBA) Syntax

See [SldWorks::RemoveMenuPopupItem](#).

See Also

[ISldWorks Interface](#)
[ISldWorks Members](#)

SOLIDWORKS API Help

[Send comments](#) on this topic.

RemoveMenuPopupItem2 Method (ISldWorks)

[See Also](#)



[SolidWorks.Interop.sldworks Namespace](#) > [ISldWorks Interface](#) : RemoveMenuPopupItem2 Method (ISldWorks)

Removes an item on a pop-up (shortcut) menu.

.NET Syntax

Visual Basic (Declaration)

```
Function RemoveMenuPopupItem2( _  
    ByVal DocumentType As System.Integer, _  
    ByVal Cookie As System.Integer, _  
    ByVal SelectType As System.Integer, _  
    ByVal PopupItemName As System.String, _  
    ByVal MenuCallback As System.String, _  
    ByVal MenuEnableMethod As System.String, _  
    ByVal HintString As System.String, _  
    ByVal CustomNames As System.String _  
) As System.Boolean
```

Visual Basic (Usage)

```
Dim instance As ISldWorks  
Dim DocumentType As System.Integer  
Dim Cookie As System.Integer  
Dim SelectType As System.Integer  
Dim PopupItemName As System.String  
Dim MenuCallback As System.String  
Dim MenuEnableMethod As System.String  
Dim HintString As System.String  
Dim CustomNames As System.String  
Dim value As System.Boolean
```

```
value = instance.RemoveMenuPopupItem2(DocumentType, Cookie, SelectType, PopupItemName,  
MenuCallback, MenuEnableMethod, HintString, CustomNames)
```

C#

```
System.bool RemoveMenuPopupItem2(  
    System.int DocumentType,  
    System.int Cookie,  
    System.int SelectType,  
    System.string PopupItemName,  
    System.string MenuCallback,  
    System.string MenuEnableMethod,  
    System.string HintString,
```



Copy Code

```
System.string CustomNames  
)
```

C++/CLI

```
System.bool RemoveMenuPopupItem2(  
& System.int DocumentType,  
& System.int Cookie,  
& System.int SelectType,  
& System.String^ PopupItemName,  
& System.String^ MenuCallback,  
& System.String^ MenuEnableMethod,  
& System.String^ HintString,  
& System.String^ CustomNames  
)
```

NOTE: See [Differences Between Unmanaged C++ and C++/CLI Code](#).

Parameters

DocumentType

Document type as defined in [swDocumentTypes_e](#)

Cookie

Cookie specified in [ISwAddin::ConnectToSW](#)

SelectType

Selection type as defined in [swSelectType_e](#)

PopupItemName

Description displayed on the shortcut menu

MenuCallback

Function to call when the user clicks your menu item (see description in [ISldWorks::AddMenuItem3](#))

MenuEnableMethod

Optional function that controls the state of the menu item

If specified, SOLIDWORKS:

- Calls this function before displaying the menu
- Display of the menu item is controlled by the return value of MenuEnableMethod

If your method returns...	Then SOLIDWORKS...
0	Deselects and disables the menu item
1	Deselects and enables the menu item. This is the default menu state with if no update function is specified
2	Selects and disables the menu item
3	Selects and enables the menu item

HintString

Text to show in the SOLIDWORKS status bar when the user moves their mouse over this menu item; if you specify a HintString, it must be preceded by a comma

CustomNames

Semi-colon separated list of the names of the custom feature types. This argument is applicable only if SelectType is a custom feature type (like swSelATTRIBUTES); in the case of swSelATTRIBUTES, set this field to the name of the attribute definition

Return Value

True if the item was removed, false if not

Visual Basic for Applications (VBA) Syntax

See [SldWorks::RemoveMenuPopupItem2](#).

Remarks

The enumeration swDocNONE is not valid for DocumentType.

See Also

[ISldWorks Interface](#)

[ISldWorks Members](#)

[ISldWorks::AddMenu Method](#)

[ISldWorks::AddMenuPopuptem2 Method](#)
[ISldWorks::RemoveFromMenu Method](#)
[ISldWorks::RemoveFromPopupMenu Method](#)
[ISldWorks::RemoveMenu Method](#)

Availability

SOLIDWORKS 2003 FCS, Revision Number 11.0

SOLIDWORKS API Help

[Send comments on this topic.](#)

RemoveToolbar Method (ISldWorks)

[See Also](#)



[SolidWorks.Interop.sldworks Namespace](#) > [ISldWorks Interface](#) : RemoveToolbar Method (ISldWorks)

Obsolete. Superseded by [ISldWorks::RemoveToolbar2](#)

.NET Syntax

Visual Basic (Declaration)

```
Function RemoveToolbar( _  
    ByVal Module As System.String, _  
    ByVal ToolBarId As System.Integer _  
) As System.Boolean
```

Visual Basic (Usage)



```
Dim instance As ISldWorks  
Dim Module As System.String  
Dim ToolbarId As System.Integer  
Dim value As System.Boolean  
  
value = instance.RemoveToolbar(Module, ToolbarId)
```

C#

```
System.bool RemoveToolbar(  
    System.string Module,  
    System.int ToolBarId  
)
```

C++/CLI

```
System.bool RemoveToolbar(  
& System.String^ Module,  
& System.int ToolBarId  
)
```

NOTE: See [Differences Between Unmanaged C++ and C++/CLI Code](#).

Parameters

Module

ToolBarId

Visual Basic for Applications (VBA) Syntax

See [SldWorks::RemoveToolbar](#).

See Also

[ISldWorks Interface](#)
[ISldWorks Members](#)

SOLIDWORKS API Help

[Send comments on this topic.](#)

RemoveToolbar2 Method (ISldWorks)

[See Also](#)



Removes a toolbar created with [ISldWorks::AddToolBar5](#).

.NET Syntax

Visual Basic (Declaration)

```
Function RemoveToolbar2( _  
    ByVal Cookie As System.Integer, _  
    ByVal ToolBarId As System.Integer _  
) As System.Boolean
```

Visual Basic (Usage)



```
Dim instance As ISldWorks  
Dim Cookie As System.Integer  
Dim ToolbarId As System.Integer  
Dim value As System.Boolean  
  
value = instance.RemoveToolbar2(Cookie, ToolbarId)
```

C#

```
System.bool RemoveToolbar2(  
    System.int Cookie,  
    System.int ToolBarId  
)
```

C++/CLI

```
System.bool RemoveToolbar2(  
& System.int Cookie,  
& System.int ToolBarId  
)
```

NOTE: See [Differences Between Unmanaged C++ and C++/CLI Code](#).

Parameters

Cookie

Resource ID of the toolbar; this is the same cookie that you specified in [ISwAddin::ConnectToSW](#)

ToolBarId

Toolbar ID

Return Value

True if the toolbar is removed, false if not

Visual Basic for Applications (VBA) Syntax

See [SldWorks::RemoveToolbar2](#).

Remarks

If the SOLIDWORKS Design application is exiting and your application is still added-in, then you should not call this method. You should, however, clean up all other items such as the Cbitmap objects, which allows your toolbar to get reloaded in the same position next time you start the SOLIDWORKS Design application.

See Also

[ISldWorks Interface](#)
[ISldWorks Members](#)
[ISldWorks::DragToolBarButton Method](#)
[ISldWorks::HideToolBar2 Method](#)

Availability

SOLIDWORKS 2001Plus FCS, Revision Number 10.0

RemoveUserMenu Method (ISldWorks)

[See Also](#)



[SolidWorks.Interop.sldworks Namespace](#) > [ISldWorks Interface](#) : RemoveUserMenu Method (ISldWorks)

Obsolete. Superseded by [ISldWorks::RemoveMenu](#).

.NET Syntax

Visual Basic (Declaration)

```
Function RemoveUserMenu( _  
    ByVal DocType As System.Integer, _  
    ByVal MenuIdIn As System.Integer, _  
    ByVal ModuleName As System.String _  
) As System.Boolean
```

Visual Basic (Usage)



```
Dim instance As ISldWorks  
Dim DocType As System.Integer  
Dim MenuIdIn As System.Integer  
Dim ModuleName As System.String  
Dim value As System.Boolean  
  
value = instance.RemoveUserMenu(DocType, MenuIdIn, ModuleName)
```

C#

```
System.bool RemoveUserMenu(  
    System.int DocType,  
    System.int MenuIdIn,  
    System.string ModuleName  
)
```

C++/CLI

```
System.bool RemoveUserMenu(  
& System.int DocType,  
& System.int MenuIdIn,  
& System.String^ ModuleName  
)
```

NOTE: See [Differences Between Unmanaged C++ and C++/CLI Code](#).

Parameters

DocType

MenuIdIn

ModuleName

Visual Basic for Applications (VBA) Syntax

See [SldWorks::RemoveUserMenu](#).

See Also

[ISldWorks Interface](#)
[ISldWorks Members](#)

SOLIDWORKS API Help

[Send comments on this topic.](#)

RemoveUserTypeLibReferences Method (ISldWorks)

[See Also](#)



[SolidWorks.Interop.sldworks Namespace](#) > [ISldWorks Interface](#) : RemoveUserTypeLibReferences Method (ISldWorks)

Removes the user-specified type library references.

Visual Basic Syntax

Visual Basic (Declaration)

```
Function RemoveUserTypeLibReferences( _  
    ByVal VTlbRef As System.Object _  
) As System.Boolean
```

Visual Basic (Usage)



```
Dim instance As ISldWorks  
Dim VTlbRef As System.Object  
Dim value As System.Boolean  
  
value = instance.RemoveUserTypeLibReferences(VTlbRef)
```

C#

```
System.bool RemoveUserTypeLibReferences(  
    System.object VTlbRef  
)
```

C++/CLI

```
System.bool RemoveUserTypeLibReferences(  
& System.Object^ VTlbRef  
)
```

NOTE: See [Differences Between Unmanaged C++ and C++/CLI Code](#).

Parameters

VTlbRef

Array of strings of the user-specified type library references

Return Value

True if the user-specified type library references are removed, false if not

Visual Basic for Applications (VBA) Syntax

See [SldWorks::RemoveUserTypeLibReferences](#).

Remarks

Any macro recorded after this method is called will not have references to the removed user-specified type libraries.

An add-in can use this method to remove its type library references when the add-in is unloaded.

See [Type Libraries](#) for details.

See Also

[ISldWorks Interface](#)
[ISldWorks Members](#)
[ISldWorks::GetUserTypeLibReferenceCount Method](#)
[ISldWorks::GetUserTypeLibReferences Method](#)
[ISldWorks::RemoveUserTypeLibReferences Method](#)
[ISldWorks::SetUserTypeLibReferences Method](#)
[ISldWorks::UserTypeLibReferences Property](#)

Availability

SOLIDWORKS 2005 FCS, Revision Number 13.0

SOLIDWORKS API Help

[Send comments on this topic.](#)

ReplaceReferencedDocument Method (ISldWorks)

[See Also](#) [Example](#)



[SolidWorks.Interop.sldworks Namespace](#) > [ISldWorks Interface](#) : ReplaceReferencedDocument Method (ISldWorks)

Replaces a referenced document.

Visual Basic Syntax

Visual Basic (Declaration)

```
Function ReplaceReferencedDocument( _  
    ByVal ReferencingDocument As System.String, _  
    ByVal ReferencedDocument As System.String, _  
    ByVal NewReference As System.String _  
) As System.Boolean
```

Visual Basic (Usage)



```
Dim instance As ISldWorks  
Dim ReferencingDocument As System.String  
Dim ReferencedDocument As System.String  
Dim NewReference As System.String  
Dim value As System.Boolean
```

```
value = instance.ReplaceReferencedDocument(ReferencingDocument, ReferencedDocument, NewReference)
```

C#

```
System.bool ReplaceReferencedDocument(  
    System.string ReferencingDocument,  
    System.string ReferencedDocument,  
    System.string NewReference  
)
```

C++/CLI

```
System.bool ReplaceReferencedDocument(  
& System.String^ ReferencingDocument,  
& System.String^ ReferencedDocument,  
& System.String^ NewReference  
)
```

NOTE: See [Differences Between Unmanaged C++ and C++/CLI Code](#).

Parameters

ReferencingDocument

Document whose references to modify; the document cannot be open

ReferencedDocument

Document is referenced by ReferencingDocument; all of its references within ReferencingDocument are replaced by NewReference

NewReference

New document used by ReferencingDocument

Return Value

True if the the referenced document is replaced, false if not

Visual Basic for Applications (VBA) Syntax

See [SldWorks::ReplaceReferencedDocument](#).

Example

[Replace Referenced Document \(VBA\)](#)

Remarks

Mates, dimensions, and other references might fail when the referencingDocument is opened.

If the internal ID of the ReferencedDocument does not match the internal ID of the NewReference document, then an error message is displayed when the ReferencingDocument is opened. The internal ID is a time stamp that was generated when the file was created. Unless the NewReference is actually a renamed copy of the ReferencedDocument document, then it is unlikely that the internal IDs will match.

This method does not check for the existence of the NewReference document. If the document does not exist when the ReferencingDocument is opened, then the user is warned and prompted to browse for a replacement.

The ReferencedDocument and NewReference file types must match. For example, if ReferencingDocument is an assembly with four subassemblies, you cannot replace any of the subassembly references with a part document. If you were to replace any of the subassembly

references, they would need to be replaced by another SOLIDWORKS assembly document.

You might also notice that the component name, which is visible in the FeatureManager design tree, will not change to the name of the NewReference unless the proper user preference is set (**Tools, Options, System Options, External References, Update component names when documents are replaced**).

See Also

[ISldWorks Interface](#)
[ISldWorks Members](#)

SOLIDWORKS API Help

[Send comments on this topic.](#)

ResetPresetDrawingParameters Method (ISldWorks)

[See Also](#) [Example](#)



[SolidWorks.Interop.sldworks Namespace](#) > [ISldWorks Interface](#) : ResetPresetDrawingParameters Method (ISldWorks)

Resets SOLIDWORKS back to its default behavior after calling [ISldWorks::PresetNewDrawingParameters](#) (i.e., display **Sheet Format/Size** dialog when opening a new drawing document).

.NET Syntax

Visual Basic (Declaration)

```
Sub ResetPresetDrawingParameters()
```

Visual Basic (Usage)



```
Dim instance As ISldWorks
```

```
instance.ResetPresetDrawingParameters()
```

C#

```
void ResetPresetDrawingParameters()
```

C++/CLI

```
void ResetPresetDrawingParameters();
```

NOTE: See [Differences Between Unmanaged C++ and C++/CLI Code](#).

Visual Basic for Applications (VBA) Syntax

See [SldWorks::ResetPresetDrawingParameters](#).

Example

[Preset and Reset Template and Sheet Parameters for New Drawing Documents \(VBA\)](#)

See Also

[ISldWorks Interface](#)
[ISldWorks Members](#)

Availability

SOLIDWORKS 2008 FCS, Revision Number 16.0

SOLIDWORKS API Help

[Send comments on this topic.](#)

ResetUntitledCount Method (ISldWorks)

[See Also](#) [Example](#)



[SolidWorks.Interop.sldworks Namespace](#) > [ISldWorks Interface](#) : ResetUntitledCount Method (ISldWorks)

Resets the index of untitled documents.

.NET Syntax

```
Function ResetUntitledCount( _
    ByVal PartValue As System.Integer, _
    ByVal AssemValue As System.Integer, _
    ByVal DrawingValue As System.Integer _
) As System.Integer
```



```
Dim instance As ISldWorks
Dim PartValue As System.Integer
Dim AssemValue As System.Integer
Dim DrawingValue As System.Integer
Dim value As System.Integer

value = instance.ResetUntitledCount(PartValue, AssemValue, DrawingValue)
```

```
System.int ResetUntitledCount(
    System.int PartValue,
    System.int AssemValue,
    System.int DrawingValue
)
```

```
System.int ResetUntitledCount(
    & System.int PartValue,
    & System.int AssemValue,
    & System.int DrawingValue
)
```

NOTE: See [Differences Between Unmanaged C++ and C++/CLI Code](#).

Parameters

PartValue
Starting index for part documents

AssemValue
Starting index for assembly documents

DrawingValue
Starting index for drawing documents

Return Value

Total number of successful resets

Visual Basic for Applications (VBA) Syntax

See [SldWorks::ResetUntitledCount](#)

Example

[Reset Untitled Document Count \(VBA\)](#)
[Reset Untitled Document Count \(VB.NET\)](#)
[Reset Untitled Document Count \(C#\)](#)

Remarks

Use this method to reset untitled document indexes so that playbacks of the macro recorder increment untitled documents in a reproducible fashion.

For example, if the first playback of a macro creates Part1 and Part2, then the second playback may fail because it creates Part3 and Part4 instead of Part1 and Part2.

To ensure reproducible results, call ISldWorks::ResetUntitledCount at the beginning or end of a macro program.

See Also

[ISldWorks Interface](#)
[ISldWorks Members](#)

Availability

SOLIDWORKS 2009 SP1, Revision Number 17.1

SOLIDWORKS API Help

[Send comments on this topic.](#)

RestoreSettings Method (ISldWorks)

[See Also](#)



[SolidWorks.Interop.sldworks Namespace](#) > [ISldWorks Interface](#) : RestoreSettings Method (ISldWorks)

Restores the specified SOLIDWORKS settings from the specified *.sldreg file.

.NET Syntax

Visual Basic (Declaration)

```
Function RestoreSettings( _  
    ByVal FileName As System.String, _  
    ByVal SystemOptions As System.Boolean, _  
    ByVal ToolbarLayout As System.Boolean, _  
    ByVal KeyboardShortcuts As System.Boolean, _  
    ByVal MouseGestures As System.Boolean, _  
    ByVal MenuCustomization As System.Boolean, _  
    ByVal SavedViews As System.Boolean, _  
    ByVal CreateBackup As System.Boolean _  
) As System.Integer
```

Visual Basic (Usage)



```
Dim instance As ISldWorks  
Dim FileName As System.String  
Dim SystemOptions As System.Boolean  
Dim ToolbarLayout As System.Boolean  
Dim KeyboardShortcuts As System.Boolean  
Dim MouseGestures As System.Boolean  
Dim MenuCustomization As System.Boolean  
Dim SavedViews As System.Boolean  
Dim CreateBackup As System.Boolean  
Dim value As System.Integer  
  
value = instance.RestoreSettings(FileName, SystemOptions, ToolbarLayout, KeyboardShortcuts,  
MouseGestures, MenuCustomization, SavedViews, CreateBackup)
```

C#

```
System.int RestoreSettings(  
    System.string FileName,  
    System.bool SystemOptions,  
    System.bool ToolbarLayout,  
    System.bool KeyboardShortcuts,  
    System.bool MouseGestures,  
    System.bool MenuCustomization,  
    System.bool SavedViews,  
    System.bool CreateBackup  
)
```

C++/CLI

```
System.int RestoreSettings(  
& System.String^ FileName,  
& System.bool SystemOptions,  
& System.bool ToolbarLayout,  
& System.bool KeyboardShortcuts,  
& System.bool MouseGestures,  
& System.bool MenuCustomization,  
& System.bool SavedViews,  
& System.bool CreateBackup  
)
```

NOTE: See [Differences Between Unmanaged C++ and C++/CLI Code](#).

Parameters

FileName

Full path and filename of the settings to restore (*.sldreg) (see **Remarks**)

SystemOptions

True to restore system options, false to not

ToolbarLayout

True to restore the toolbar layout, false to not

KeyboardShortcuts

True to restore keyboard shortcuts, false to not (see **Remarks**)

MouseGestures

True to restore mouse gestures, false to not

MenuCustomization

True to restore menu customizations, false to not

SavedViews

True to restore saved views, false to not (see **Remarks**)

CreateBackup

True to create a backup of the current settings, false to not (see **Remarks**)

Return Value

Error code as defined in [swSaveRestoreSettingsResults_e](#)

Visual Basic for Applications (VBA) Syntax

See [ISldWorks::RestoreSettings](#).

Example

' VBA precondition:

' c:\temp exists

```
Dim swApp As SldWorks.SldWorks
```

```
Option Explicit
```

```
Sub main()
```

```
    Set swApp = Application.SldWorks
```

```
    Dim boolStatus As Long
```

```
    Dim path As String
```

```
    path = "C:\temp\swSettings2.sldreg"
```

```
    boolStatus = swApp.SaveSettings(path, True,
```

```
swToolbarLayoutOption_e.swToolbarLayoutOption_AllToolbars, True, True, True, True)
```

```
    path = "C:\temp\swSettings2.sldreg"
```

```
    boolStatus = swApp.RestoreSettings(path, True, True, True, True, True, True, True)
```

```
End Sub
```

Remarks

This method is valid only if [ISldWorks::SaveSettings](#) was called previously.

KeyboardShortcuts and SavedViews are valid only if these settings were previously saved using ISldWorks::SaveSettings.

If CreateBackup is true, this method backs up the current settings to **backup_userid_yyyymmdd_hhmmss.sldreg** in the same location as specified in FileName.

For C++ only, specify all System.bool parameters using VARIANT_TRUE (-1) and VARIANT_FALSE (0).

See Also

[ISldWorks Interface](#)

[ISldWorks Members](#)

[ISldWorks::LoadAdminSettingsFile Method \(\)](#)

Availability

SOLIDWORKS 2018 FCS, Revision Number 26.0

[See Also](#)



[SolidWorks.Interop.sldworks Namespace](#) > [ISldWorks Interface](#) : ResumeSkinning Method (ISldWorks)

Resumes skinning windows.

.NET Syntax

Visual Basic (Declaration)

```
Function ResumeSkinning() As System.Boolean
```

Visual Basic (Usage)



```
Dim instance As ISldWorks  
Dim value As System.Boolean  
  
value = instance.ResumeSkinning()
```

C#

```
System.bool ResumeSkinning()
```

C++/CLI

```
System.bool ResumeSkinning();
```

NOTE: See [Differences Between Unmanaged C++ and C++/CLI Code](#).

Return Value

True if successful, false if not

Visual Basic for Applications (VBA) Syntax

See [SldWorks::ResumeSkinning](#).

See Also

[ISldWorks Interface](#)
[ISldWorks Members](#)

Availability

SOLIDWORKS 2008 FCS, Revision Number 16.0

SOLIDWORKS API Help

[Send comments](#) on this topic.

RevisionNumber Method (ISldWorks)

[See Also](#) [Example](#)



[SolidWorks.Interop.sldworks Namespace](#) > [ISldWorks Interface](#) : RevisionNumber Method (ISldWorks)

Gets the version number of this SOLIDWORKS Design installation.

.NET Syntax

Visual Basic (Declaration)

```
Function RevisionNumber() As System.String
```

Visual Basic (Usage)



```
Dim instance As ISldWorks  
Dim value As System.String  
  
value = instance.RevisionNumber()
```

C#

```
System.string RevisionNumber()
```

C++/CLI

```
System.String^ RevisionNumber();
```

NOTE: See [Differences Between Unmanaged C++ and C++/CLI Code](#).

Return Value

SOLIDWORKS Design version number (See **Remarks**)

Visual Basic for Applications (VBA) Syntax

See [SldWorks::RevisionNumber](#).

Example

[Create Infinite Plane \(VBA\)](#)
[Get Material Property Names \(VBA\)](#)
[Get Version Number \(C#\)](#)
[Get Version Number \(VB.NET\)](#)
[Get Version Number \(VBA\)](#)

Remarks

This method returns a string in the form "*major.minor*", where *major* is an integer (e.g., 1), and *minor* is a decimal number (e.g., 0.0).

For all SOLIDWORKS Design executables prior to the initial public release of SOLIDWORKS 2000, this method returns **1.0.0** (major = 1, minor = 0.0).

For the initial public release of SOLIDWORKS 2000, this method returns **8.0.0** (major = 8, minor = 0.0). For SOLIDWORKS 2000 SP1, this method returns **8.1.0**, and each successive service pack or service pack hot fix of SOLIDWORKS 2000 increments the minor decimal number (e.g., SP1.1 returns **8.1.1**, SP2 returns **8.2.0**, SP3 returns **8.3.0**, etc.).

For the initial public release of SOLIDWORKS 2005, this method returns **13.0.0**. For SOLIDWORKS 2005 SP0.1, it returns **13.0.1**. For SOLIDWORKS 2005 SP1, it returns **13.1.0**.

In general, each successive major public release increments the major number by one, each service pack increments the minor decimal number by 1.0, and each service pack hot fix increments the minor decimal number by 0.1. For the initial public release, the minor decimal number is always **0.0**.

Alpha, beta, and pre-release versions return negative minor decimal numbers:

- a1: **-1.0**
- b1: **-2.0**
- b2: **-3.0**
- b3: **-4.0**
- PR1: **-5.0** (This value might be lower or higher depending on the number of beta releases.)

For SOLIDWORKS 2015 b2, this method returns **23.-3.0**.

See Also

[ISldWorks Interface](#)
[ISldWorks Members](#)
[ISldWorks::VersionHistory Method](#)
[ISldWorks::IVersionHistory Method](#)
[IModelDoc2::VersionHistory Method](#)
[IModelDoc2::IVersionHistory Method](#)
[ISldWorks::GetBuildNumbers2 Method](#)
[Accessing SOLIDWORKS Add-in Objects](#)

SOLIDWORKS API Help

[Send comments on this topic.](#)

RunAttachedMacro Method (ISldWorks)

[See Also](#)



[SolidWorks.Interop.sldworks Namespace](#) > [ISldWorks Interface](#) : RunAttachedMacro Method (ISldWorks)

Runs the specified attached macro, module, and procedure.

.NET Syntax

Visual Basic (Declaration)

```
Function RunAttachedMacro( _  
    ByVal FileName As System.String, _
```

```

        ByVal ModuleName As System.String, _
        ByVal ProcedureName As System.String _
    ) As System.Boolean

```

Visual Basic (Usage)



```

Dim instance As ISldWorks
Dim FileName As System.String
Dim ModuleName As System.String
Dim ProcedureName As System.String
Dim value As System.Boolean

value = instance.RunAttachedMacro(FileName, ModuleName, ProcedureName)

```

C#

```

System.bool RunAttachedMacro(
    System.string FileName,
    System.string ModuleName,
    System.string ProcedureName
)

```

C++/CLI

```

System.bool RunAttachedMacro(
    & System.String^ FileName,
    & System.String^ ModuleName,
    & System.String^ ProcedureName
)

```

NOTE: See [Differences Between Unmanaged C++ and C++/CLI Code](#).

Parameters

FileName

Filename of macro to run (do not include a path)

ModuleName

Module of specified macro to run

ProcedureName

Procedure of specified macro to run

Return Value

True if macro runs, false if not

Visual Basic for Applications (VBA) Syntax

See [SldWorks::RunAttachedMacro](#).

Example

Visual Basic for Applications (VBA)

Create two VBA macros using the following code samples. Attach **RunMacroSub.swp** to the active document's Design Binder. Then run **RunAttachedMacro.swp**.

```

'-----
' RunAttachedMacro.swp
'-----

Option Explicit
Dim swApp As SldWorks.SldWorks
Dim boolstatus As Boolean

Sub main()
    Set swApp = Application.SldWorks
    Dim RunMacroError As Long
    boolstatus = swApp.RunAttachedMacro("RunMacroSub.swp", "RunMacroSub1", "main")
End Sub

```

```

'-----
' RunMacroSub.swp'
'-----

Option Explicit
Dim swApp As SldWorks.SldWorks

Sub alternate()
    Set swApp = Application.SldWorks
    swApp.SendMsgToUser "RunMacroSub1:alternate() called."
End Sub

Sub main()
    Set swApp = Application.SldWorks
    swApp.SendMsgToUser "RunMacroSub1:main() called."

End Sub

```

Remarks

An example of an attached macro is a macro that is attached to the active document's Design Binder.

See Also

[ISldWorks Interface](#)
[ISldWorks Members](#)
[ISldWorks::RunMacro2 Method](#)

Availability

SOLIDWORKS 2009 FCS, Revision Number 17.0

SOLIDWORKS API Help

[Send comments on this topic.](#)

RunBatchSaveProcess Method (ISldWorks)

[See Also](#)



[SolidWorks.Interop.sldworks Namespace](#) > [ISldWorks Interface](#) : RunBatchSaveProcess Method (ISldWorks)

Batch saves files to 3DEXPERIENCE.

.NET Syntax

Visual Basic (Declaration)

```
Function RunBatchSaveProcess() As System.Boolean
```

Visual Basic (Usage)

```
Dim instance As ISldWorks
Dim value As System.Boolean

value = instance.RunBatchSaveProcess()
```

C#

```
System.bool RunBatchSaveProcess()
```

C++/CLI

```
System.bool RunBatchSaveProcess();
```

NOTE: See [Differences Between Unmanaged C++ and C++/CLI Code](#).

Return Value

True if batch save successful, false if not



Visual Basic for Applications (VBA) Syntax

See [ISldWorks::RunBatchSaveProcess](#).

Remarks

This method is valid only for [SOLIDWORKS Design connected to the 3DEXPERIENCE platform](#).

Call this method:

- after loading the files to save using [ISldWorks::ShowBatchSaveTo3DEXperienceDlg](#).
- before calling [ISldWorks::GetBatchUploadedFilesInfo](#).

See Also

[ISldWorks Interface](#)
[ISldWorks Members](#)

Availability

SOLIDWORKS 2022 SP03, Revision Number 30.3

SOLIDWORKS API Help

[Send comments](#) on this topic.

RunCommand Method (ISldWorks)

[See Also](#) [Example](#)



[SolidWorks.Interop.sldworks Namespace](#) > [ISldWorks Interface](#) : RunCommand Method (ISldWorks)

Runs the specified SOLIDWORKS command.

.NET Syntax

Visual Basic (Declaration)

```
Function RunCommand( _  
    ByVal CommandID As System.Integer, _  
    ByVal NewTitle As System.String _  
) As System.Boolean
```

Visual Basic (Usage)



```
Dim instance As ISldWorks  
Dim CommandID As System.Integer  
Dim NewTitle As System.String  
Dim value As System.Boolean  
  
value = instance.RunCommand(CommandID, NewTitle)
```

C#

```
System.bool RunCommand(  
    System.int CommandID,  
    System.string NewTitle  
)
```

C++/CLI

```
System.bool RunCommand(  
& System.int CommandID,  
& System.String^ NewTitle  
)
```

NOTE: See [Differences Between Unmanaged C++ and C++/CLI Code](#).

Parameters

CommandID
SOLIDWORKS command as defined in [swCommands_e](#) (see **Remarks**)
NewTitle
Your title for the SOLIDWORKS PropertyManager page, if invoked by this command

Return Value

True if the SOLIDWORKS command ran, false if not

Visual Basic for Applications (VBA) Syntax

See [SldWorks::RunCommand](#).

Example

[Fire Events When PropertyManager Page Opened and Canceled \(VBA\)](#)
[Record Macros \(C#\)](#)
[Record Macros \(VB.NET\)](#)
[Record Macros \(VBA\)](#)

See Also

[ISldWorks Interface](#)
[ISldWorks Members](#)
[IModelDocExtension::RunCommand Method](#)
[ISldWorks::IsCommandEnabled Method](#)
[ISldWorks::GetRunningCommandInfo Method](#)
[DSldWorksEvents _CommandCloseNotifyEventHandler Delegate](#)
[DSldWorksEvents _CommandOpenPreNotifyEventHandler Delegate](#)
[ISldWorks::RecordLine Method](#)
[ISldWorks::RecordLineCSharp Method](#)
[ISldWorks::RecordLineVBnet Method](#)

Availability

SOLIDWORKS 2008 FCS, Revision Number 16.0

SOLIDWORKS API Help

[Send comments on this topic.](#)

RunJournalCmd Method (ISldWorks)

[See Also](#)



[SolidWorks.Interop.sldworks Namespace](#) > [ISldWorks Interface](#) : RunJournalCmd Method (ISldWorks)

Do not use.

.NET Syntax

Visual Basic (Declaration)

```
Function RunJournalCmd( _  
    ByVal Cmd As System.String _  
) As System.Boolean
```

Visual Basic (Usage)



```
Dim instance As ISldWorks  
Dim Cmd As System.String  
Dim value As System.Boolean  
  
value = instance.RunJournalCmd(Cmd)
```

C#

```
System.bool RunJournalCmd(  
    System.string Cmd  
)
```

C++/CLI

```
System.bool RunJournalCmd(  
& System.String^ Cmd  
)
```

NOTE: See [Differences Between Unmanaged C++ and C++/CLI Code](#).

Parameters

Cmd

See Also

[ISldWorks Interface](#)
[ISldWorks Members](#)

SOLIDWORKS API Help

[Send comments](#) on this topic.

RunMacro Method (ISldWorks)

[See Also](#) [Example](#)



[SolidWorks.Interop.sldworks Namespace](#) > [ISldWorks Interface](#) : RunMacro Method (ISldWorks)

Obsolete. Superseded by [ISldWorks::RunMacro2](#).

.NET Syntax

Visual Basic (Declaration)

```
Function RunMacro( _  
    ByVal FilePathName As System.String, _  
    ByVal ModuleName As System.String, _  
    ByVal ProcedureName As System.String _  
) As System.Boolean
```

Visual Basic (Usage)



```
Dim instance As ISldWorks  
Dim FilePathName As System.String  
Dim ModuleName As System.String  
Dim ProcedureName As System.String  
Dim value As System.Boolean  
  
value = instance.RunMacro(FilePathName, ModuleName, ProcedureName)
```

C#

```
System.bool RunMacro(  
    System.string FilePathName,  
    System.string ModuleName,  
    System.string ProcedureName  
)
```

C++/CLI

```
System.bool RunMacro(  
& System.String^ FilePathName,  
& System.String^ ModuleName,  
& System.String^ ProcedureName  
)
```

NOTE: See [Differences Between Unmanaged C++ and C++/CLI Code](#).

Parameters

FilePathName
Path and file name of the project file containing the macro
ModuleName
Name of the module in the macro
ProcedureName
Name of the procedure in the module

Return Value

True if macro runs successfully, false if not

Visual Basic for Applications (VBA) Syntax

See [SldWorks::RunMacro](#).

Example

[Run Macro \(VBA\)](#)

Remarks

See [SOLIDWORKS Macros](#) for details.

See Also

[ISldWorks Interface](#)
[ISldWorks Members](#)
[ISldWorks::GetCurrentMacroPathFolder Method](#)
[ISldWorks::GetCurrentMacroPathName Method](#)
[ISldWorks::RecordLine Method](#)
[ISldWorks::GetMacroMethods Method](#)

Availability

SOLIDWORKS 2003 FCS, Revision Number 11.0

[SOLIDWORKS API Help](#)

[Send comments on this topic.](#)

RunMacro2 Method (ISldWorks)

[See Also](#)



[SolidWorks.Interop.sldworks Namespace](#) > [ISldWorks Interface](#) : RunMacro2 Method (ISldWorks)

Runs a macro from a project file.

.NET Syntax

Visual Basic (Declaration)

```
Function RunMacro2( _  
    ByVal FilePathName As System.String, _  
    ByVal ModuleName As System.String, _  
    ByVal ProcedureName As System.String, _  
    ByVal Options As System.Integer, _  
    ByRef Error As System.Integer _  
) As System.Boolean
```

Visual Basic (Usage)



```
Dim instance As ISldWorks  
Dim FilePathName As System.String  
Dim ModuleName As System.String  
Dim ProcedureName As System.String  
Dim Options As System.Integer  
Dim Error As System.Integer  
Dim value As System.Boolean  
  
value = instance.RunMacro2(FilePathName, ModuleName, ProcedureName, Options, Error)
```

C#

```
System.bool RunMacro2(  
    System.string FilePathName,  
    System.string ModuleName,  
    System.string ProcedureName,  
    System.int Options,  
    out System.int Error  
)
```

C++/CLI

```
System.bool RunMacro2(  
& System.String^ FilePathName,  
& System.String^ ModuleName,  
& System.String^ ProcedureName,  
& System.int Options,  
& [Out] System.int Error  
)
```

NOTE: See [Differences Between Unmanaged C++ and C++/CLI Code](#).

Parameters

FilePathName

Path and filename of the project file containing the macro

ModuleName

Name of the module in the macro

ProcedureName

Name of the procedure in the module

Options

Option as defined [swRunMacroOption_e](#) (supports VBA macros only)

Error

Error as defined by [swRunMacroError_e](#) (supports VBA macros only)

Return Value

True if macro runs, false if not

Visual Basic for Applications (VBA) Syntax

See [SldWorks::RunMacro2](#).

Example

Visual Basic for Applications (VBA)

1. Create two VBA macros using the following code samples.
2. Store **RunMacroSub.swp** in **c:\test**.
3. Run **RunMacro.swp**.

```
'-----  
' RunMacro.swp  
'-----
```

Option Explicit

Dim swApp As SldWorks.SldWorks

Dim boolstatus As Boolean

Sub main()

 Set swApp = Application.SldWorks

 Dim runMacroError As Long

 boolstatus = swApp.**RunMacro2**("c:\test\RunMacroSub.swp", "RunMacroSub1", "main",
swRunMacroUnloadAfterRun, runMacroError)

End Sub

```
'-----  
' RunMacroSub.swp  
'-----
```

Option Explicit

Dim swApp As SldWorks.SldWorks

Sub alternate()

 Set swApp = Application.SldWorks

 swApp.SendMsgToUser "RunMacroSub1:alternate() called."

End Sub

Sub main()

 Set swApp = Application.SldWorks

 swApp.SendMsgToUser "RunMacroSub1:main() called."

End Sub

Running a C# DLL from VBA

boolstatus =

Me.swApp.**RunMacro2**('C:\Test\CSharpMacro\SwMacro\bin\Release\CSharpMacro.dll',
'', 'Main', swRunMacroOption_e.swRunMacroDefault, runMacroError)

Remarks

If you specify **swRunMacroUnloadAfterRun** for Options, then the macro is unloaded from the VBA IDE after running.

Use the path and filename of the compiled DLL for the **FilePathName** argument for a .NET macro. By default, the procedure is called **Main** in a C# macro. Because C# is case sensitive, you must specify **Main** for **ProcedureName** in this method.. See **Running a C# DLL from VBA** in the **Example** section.

Running a macro from an add-in application, standalone .exe, or VBA macro is supported. Running a .NET macro from a .NET macro is also supported, but only if both .NET macros were created using the same VSTA version.

See [SOLIDWORKS Macros](#) for details.

See Also

[ISldWorks Interface](#)
[ISldWorks Members](#)
[ISldWorks::GetCurrentMacroPathFolder Method](#)
[ISldWorks::GetCurrentMacroPathName Method](#)
[ISldWorks::GetMacroMethods Method](#)
[ISldWorks::RunAttachedMacro Method](#)
[ISldWorks::RecordLine Method](#)
[ISldWorks::RecordLineCSharp Method](#)
[ISldWorks::RecordLineVBnet Method](#)

Availability

SOLIDWORKS 2009 FCS, Revision Number 17.0

SOLIDWORKS API Help

[Send comments on this topic.](#)

SaveSettings Method (ISldWorks)

[See Also](#)



[SolidWorks.Interop.sldworks Namespace](#) > [ISldWorks Interface](#) : SaveSettings Method (ISldWorks)

Saves the specified SOLIDWORKS settings to the specified *.sldreg file.

.NET Syntax

Visual Basic (Declaration)

```
Function SaveSettings( _  
    ByVal FileName As System.String, _  
    ByVal SystemOptions As System.Boolean, _  
    ByVal ToolbarLayout As System.Integer, _  
    ByVal KeyboardShortcuts As System.Boolean, _  
    ByVal MouseGestures As System.Boolean, _  
    ByVal MenuCustomization As System.Boolean, _  
    ByVal SavedViews As System.Boolean _  
) As System.Integer
```

Visual Basic (Usage)



```
Dim instance As ISldWorks  
Dim FileName As System.String  
Dim SystemOptions As System.Boolean  
Dim ToolbarLayout As System.Integer  
Dim KeyboardShortcuts As System.Boolean  
Dim MouseGestures As System.Boolean  
Dim MenuCustomization As System.Boolean  
Dim SavedViews As System.Boolean  
Dim value As System.Integer
```

```
value = instance.SaveSettings(FileName, SystemOptions, ToolbarLayout, KeyboardShortcuts,  
MouseGestures, MenuCustomization, SavedViews)
```

C#

```
System.int SaveSettings(  
    System.string FileName,  
    System.bool SystemOptions,  
    System.int ToolbarLayout,  
    System.bool KeyboardShortcuts,  
    System.bool MouseGestures,  
    System.bool MenuCustomization,  
    System.bool SavedViews  
)
```

```

System.int SaveSettings(
& System.String^ FileName,
& System.bool SystemOptions,
& System.int ToolbarLayout,
& System.bool KeyboardShortcuts,
& System.bool MouseGestures,
& System.bool MenuCustomization,
& System.bool SavedViews
)

```

NOTE: See [Differences Between Unmanaged C++ and C++/CLI Code](#).

Parameters

FileName

Full path and filename to which to save the settings (*.sldreg)

SystemOptions

True to save system options, false to not

ToolbarLayout

Toolbar layout as defined in [swToolbarLayoutOption_e](#)

KeyboardShortcuts

True to save keyboard shortcuts, false to not

MouseGestures

True to save mouse gestures, false to not

MenuCustomization

True to save menu customizations, false to not

SavedViews

True to save views, false to not

Return Value

Error code as defined in [swSaveRestoreSettingsResults_e](#)

Visual Basic for Applications (VBA) Syntax

See [SldWorks::SaveSettings](#).

Example

' VBA precondition:

' c:\temp exists

```
Dim swApp As SldWorks.SldWorks
```

```
Option Explicit
```

```
Sub main()
```

```
    Set swApp = Application.SldWorks
```

```
    Dim boolStatus As Long
```

```
    Dim path As String
```

```
    path = "C:\temp\swSettings2.sldreg"
```

```
    boolStatus = swApp.SaveSettings(path, True,  
swToolbarLayoutOption_e.swToolbarLayoutOption_AllToolbars, True, True, True, True)
```

```
End Sub
```

Remarks

For C++ only, specify all System.bool parameters using VARIANT_TRUE (-1) and VARIANT_FALSE (0).

See Also

[ISldWorks Interface](#)

[ISldWorks Members](#)

[ISldWorks::RestoreSettings Method \(\)](#)

[ISldWorks::LoadAdminSettingsFile Method \(\)](#)

Availability

SendMsgToUser Method (ISldWorks)

[See Also](#)[SolidWorks.Interop.sldworks Namespace](#) > [ISldWorks Interface](#) : SendMsgToUser Method (ISldWorks)**Obsolete.** Superseded by [ISldWorks::SendMsgToUser2](#).

.NET Syntax

Visual Basic (Declaration)

```
Sub SendMsgToUser( _
    ByVal Message As System.String _
)
```

Visual Basic (Usage)



```
Dim instance As ISldWorks
Dim Message As System.String

instance.SendMsgToUser(Message)
```

C#

```
void SendMsgToUser(
    System.string Message
)
```

C++/CLI

```
void SendMsgToUser(
    & System.String^ Message
)
```

NOTE: See [Differences Between Unmanaged C++ and C++/CLI Code](#).

Parameters

Message

Visual Basic for Applications (VBA) Syntax

See [SldWorks::SendMsgToUser](#).

See Also

[ISldWorks Interface](#)
[ISldWorks Members](#)

SendMsgToUser2 Method (ISldWorks)

[See Also](#) [Example](#)[SolidWorks.Interop.sldworks Namespace](#) > [ISldWorks Interface](#) : SendMsgToUser2 Method (ISldWorks)

Displays a message box containing a message to the user, who is required to interact with it before continuing.

.NET Syntax

Visual Basic (Declaration)

```
Function SendMsgToUser2( _
    ByVal Message As System.String, _
    ByVal Icon As System.Integer, _
    ByVal Buttons As System.Integer _
) As System.Integer
```

```

Dim instance As ISldWorks
Dim Message As System.String
Dim Icon As System.Integer
Dim Buttons As System.Integer
Dim value As System.Integer

value = instance.SendMsgToUser2(Message, Icon, Buttons)

```

C#

```

System.int SendMsgToUser2(
    System.string Message,
    System.int Icon,
    System.int Buttons
)

```

C++/CLI

```

System.int SendMsgToUser2(
    & System.String^ Message,
    & System.int Icon,
    & System.int Buttons
)

```

NOTE: See [Differences Between Unmanaged C++ and C++/CLI Code](#).

Parameters*Message*

Message for user

*Icon*Icon to show in the message box as defined in [swMessageBoxIcon_e](#)*Buttons*Buttons to show in the message box as defined in [swMessageBoxBtn_e](#)**Return Value**Value corresponding to the button the user clicked as defined in [swMessageBoxResult_e](#)**Visual Basic for Applications (VBA) Syntax**See [SldWorks::SendMsgToUser2](#).**Example**

[Access Assembly \(C++\)](#)
[Detecting In-context Edit \(C++\)](#)
[Access Selections \(VBA\)](#)
[Save Drawing As DXF \(VBA\)](#)
[Save Drawing as DXF \(VB.NET\)](#)
[Save Drawing as DXF \(C#\)](#)
[Get Names of Configurations Using Variant \(C++\)](#)

See Also

[ISldWorks Interface](#)
[ISldWorks Members](#)

SetAddinCallbackInfo Method (ISldWorks)[See Also](#)[SolidWorks.Interop.sldworks Namespace](#) > [ISldWorks Interface](#) : SetAddinCallbackInfo Method (ISldWorks)

Obsolete. Superseded by [ISldWorks::SetAddinCallbackInfo2](#).

.NET Syntax

```
Function SetAddinCallbackInfo( _
    ByVal ModuleHandle As System.Integer, _
    ByVal AddinCallbacks As System.Object, _
    ByVal Cookie As System.Integer _
) As System.Boolean
```

Visual Basic (Usage)



```
Dim instance As ISldWorks
Dim ModuleHandle As System.Integer
Dim AddinCallbacks As System.Object
Dim Cookie As System.Integer
Dim value As System.Boolean

value = instance.SetAddinCallbackInfo(ModuleHandle, AddinCallbacks, Cookie)
```

C#

```
System.bool SetAddinCallbackInfo(
    System.int ModuleHandle,
    System.object AddinCallbacks,
    System.int Cookie
)
```

C++/CLI

```
System.bool SetAddinCallbackInfo(
    & System.int ModuleHandle,
    & System.Object^ AddinCallbacks,
    & System.int Cookie
)
```

NOTE: See [Differences Between Unmanaged C++ and C++/CLI Code](#).

Parameters

ModuleHandle

Instance handle of the add-in

AddinCallbacks

Object that includes the add-in callback methods

Cookie

Add-in ID; this is the same Cookie you specified in [ISwAddin::ConnectToSW](#)

Return Value

True if the add-in callback commands are set, false if not

Visual Basic for Applications (VBA) Syntax

See [SldWorks::SetAddinCallbackInfo](#).

Example

```
' -----
' Module-level variables
Dim iSldWorks                As SldWorks.SldWorks
Dim iCookie                  As Long
' -----

'Implementation methods of the SwAddin interface
Private Function SwAddin_ConnectToSW(ByVal ThisSW As Object, ByVal Cookie As Long) As Boolean
    Dim bRet                  As Boolean
```

```

' Store reference to SOLIDWORKS Design session
Set iSldWorks = ThisSW

' Store cookie from SOLIDWORKS Design
iCookie = Cookie

'Inform SOLIDWORKS Design about the object that contains the callbacks
bRet = iSldWorks.SetAddinCallbackInfo(App.hInstance, Me, iCookie)

...

SwAddin_ConnectToSW = True
End Function
'-----

```

See Also

[ISldWorks Interface](#)
[ISldWorks Members](#)
[ISldWorks::AddCallback Method](#)
[ISldWorks::CallBack Method](#)
[ISldWorks::RemoveCallback Method](#)

Availability

SOLIDWORKS 2001Plus FCS, Revision Number 10.0

SOLIDWORKS API Help

[Send comments on this topic.](#)

SetAddinCallbackInfo2 Method (ISldWorks)

[See Also](#) [Example](#)



[SolidWorks.Interop.sldworks Namespace](#) > [ISldWorks Interface](#) : SetAddinCallbackInfo2 Method (ISldWorks)

Sets add-in callback commands.

.NET Syntax

Visual Basic (Declaration)

```

Function SetAddinCallbackInfo2( _
    ByVal ModuleHandle As System.Long, _
    ByVal AddinCallbacks As System.Object, _
    ByVal Cookie As System.Integer _
) As System.Boolean

```

Visual Basic (Usage)



```

Dim instance As ISldWorks
Dim ModuleHandle As System.Long
Dim AddinCallbacks As System.Object
Dim Cookie As System.Integer
Dim value As System.Boolean

```

```
value = instance.SetAddinCallbackInfo2(ModuleHandle, AddinCallbacks, Cookie)
```

C#

```

System.bool SetAddinCallbackInfo2(
    System.long ModuleHandle,
    System.object AddinCallbacks,
    System.int Cookie
)

```

C++/CLI

```
System.bool SetAddinCallbackInfo2(  
    & System.int64 ModuleHandle,  
    & System.Object^ AddinCallbacks,  
    & System.int Cookie  
)
```

NOTE: See [Differences Between Unmanaged C++ and C++/CLI Code](#).

Parameters

ModuleHandle

Instance handle of the add-in

AddinCallbacks

Object that includes the add-in callback methods

Cookie

Add-in ID; this is the same cookie you specify in [ISwAddin::ConnectToSW](#)

Return Value

True if the add-in callback commands are set, false if not

Visual Basic for Applications (VBA) Syntax

See [ISldWorks::SetAddinCallbackInfo2](#).

Example

[Create Flyouts in the CommandManager \(C#\)](#)

[Create Flyouts in the CommandManager \(VB.NET\)](#)

See Also

[ISldWorks Interface](#)

[ISldWorks Members](#)

[ISldWorks::AddCallback Method \(\)](#)

[ISldWorks::RemoveCallback Method \(\)](#)

[ISldWorks::CallBack Method \(\)](#)

Availability

SOLIDWORKS 2015 FCS, Revision Number 23.0

SOLIDWORKS API Help

[Send comments on this topic.](#)

SetApplySelectionFilter Method (ISldWorks)

[See Also](#)



[SolidWorks.Interop.sldworks Namespace](#) > [ISldWorks Interface](#) : SetApplySelectionFilter Method (ISldWorks)

Sets the current state of the selection filter.

.NET Syntax

Visual Basic (Declaration)

```
Sub SetApplySelectionFilter( _  
    ByVal State As System.Boolean _  
)
```

Visual Basic (Usage)



```
Dim instance As ISldWorks  
Dim State As System.Boolean  
  
instance.SetApplySelectionFilter(State)
```

C#

```
void SetApplySelectionFilter(  
    System.bool State  
)
```

C++/CLI

```
void SetApplySelectionFilter(  
& System.bool State  
)
```

NOTE: See [Differences Between Unmanaged C++ and C++/CLI Code](#).

Parameters

State

True to activate the selection filter, false to not

Visual Basic for Applications (VBA) Syntax

See [SldWorks::SetApplySelectionFilter](#).

Remarks

If the selection filter is active, then the settings found in [ISldWorks::GetSelectionFilter](#) and [ISldWorks::GetSelectionFilters](#) or [ISldworks::!GetSelectionFilters](#) apply.

See Also

[ISldWorks Interface](#)
[ISldWorks Members](#)
[ISldWorks::SetSelectionFilter Method](#)
[ISldWorks::SetSelectionFilters Method](#)
[ISldWorks::!SetSelectionFilters Method](#)
[ISldWorks::!GetSelectionFiltersCount Method](#)
[ISldWorks::GetApplySelectionFilter Method](#)

Availability

SOLIDWORKS 99, datecode 1999207

SOLIDWORKS API Help

[Send comments on this topic.](#)

SetCurrentWorkingDirectory Method (ISldWorks)

[See Also](#) [Example](#)



[SolidWorks.Interop.sldworks Namespace](#) > [ISldWorks Interface](#) : SetCurrentWorkingDirectory Method (ISldWorks)

Sets the current working directory to be used by SOLIDWORKS.

.NET Syntax

Visual Basic (Declaration)

```
Function SetCurrentWorkingDirectory( _  
    ByVal CurrentWorkingDirectory As System.String _  
) As System.Boolean
```

Visual Basic (Usage)



```
Dim instance As ISldWorks  
Dim CurrentWorkingDirectory As System.String  
Dim value As System.Boolean  
  
value = instance.SetCurrentWorkingDirectory(CurrentWorkingDirectory)
```

C#

```
System.bool SetCurrentWorkingDirectory(  
    System.string CurrentWorkingDirectory  
)
```

C++/CLI

```
System.bool SetCurrentWorkingDirectory(  
& System.String^ CurrentWorkingDirectory  
)
```

NOTE: See [Differences Between Unmanaged C++ and C++/CLI Code](#).

Parameters

CurrentWorkingDirectory

Directory to set as the current working directory

Return Value

True if specified direction is set as the current working directory, false if not

Visual Basic for Applications (VBA) Syntax

See [ISldWorks::SetCurrentWorkingDirectory](#).

Example

[Open Document \(VBA\)](#)
[Open Document \(VB.NET\)](#)
[Open Document \(C#\)](#)

Remarks

The current working directory is used when opening documents containing references. If explicit search folders are not set (see [ISldWorks::SetSearchFolders](#)), then SOLIDWORKS will initially try to locate file references (for example, assembly component parts) in the current working directory. Interactively, the current working directory is used by the File Open dialog and is set when you choose the Open dialog button.

The [ISldWorks::OpenDoc6](#) method does not set the current working directory. Therefore, you may want to set the current working directory using [ISldWorks::SetCurrentWorkingDirectory](#) before opening a file that contains references. By doing so, you will get the same behavior as if the file was opened interactively using the File Open dialog.

For more information on the search criteria used by SOLIDWORKS when loading file references, see SOLIDWORKS Help.

See Also

[ISldWorks Interface](#)
[ISldWorks Members](#)
[ISldWorks::GetCurrentWorkingDirectory Method](#)
[ISldWorks::GetCurrentMacroPathFolder Method](#)
[ISldWorks::GetCurrentMacroPathName Method](#)
[ISldWorks::GetExecutablePath Method](#)

Availability

SOLIDWORKS 98Plus, datecode 1999087

SOLIDWORKS API Help

[Send comments on this topic.](#)

SetMissingReferencePathName Method (ISldWorks)

[See Also](#)



[SolidWorks.Interop.sldworks Namespace](#) > [ISldWorks Interface](#) : SetMissingReferencePathName Method (ISldWorks)

Sets the missing reference file name. Use with the SOLIDWORKS event [ReferenceNotFoundNotify](#).

.NET Syntax

Visual Basic (Declaration)

```
Sub SetMissingReferencePathName( _  
    ByVal FileName As System.String _  
)
```

Visual Basic (Usage)

```
Dim instance As ISldWorks  
Dim FileName As System.String  
  
instance.SetMissingReferencePathName(FileName)
```

C#



```
void SetMissingReferencePathName(  
    System.string FileName  
)
```

C++/CLI

```
void SetMissingReferencePathName(  
&    System.String^ FileName  
)
```

NOTE: See [Differences Between Unmanaged C++ and C++/CLI Code](#).

Parameters

FileName

Path and filename of the missing reference

Visual Basic for Applications (VBA) Syntax

See [SldWorks::SetMissingReferencePathName](#).

Remarks

Use with the SOLIDWORKS event [ReferenceNotFoundNotify](#).

See Also

[ISldWorks Interface](#)

[ISldWorks Members](#)

Availability

SOLIDWORKS 2001 FCS, Revision Number 9.0

SOLIDWORKS API Help

[Send comments on this topic.](#)

SetMouseDragMode Method (ISldWorks)

[See Also](#)



[SolidWorks.Interop.sldworks Namespace](#) > [ISldWorks Interface](#) : SetMouseDragMode Method (ISldWorks)

Sets the command-mouse mode.

.NET Syntax

Visual Basic (Declaration)

```
Function SetMouseDragMode(  
    ByVal Command As System.Integer _  
) As System.Boolean
```

Visual Basic (Usage)



```
Dim instance As ISldWorks  
Dim Command As System.Integer  
Dim value As System.Boolean
```

```
value = instance.SetMouseDragMode(Command)
```

C#

```
System.bool SetMouseDragMode(  
    System.int Command  
)
```

C++/CLI

```
System.bool SetMouseDragMode(  
&    System.int Command
```

)

NOTE: See [Differences Between Unmanaged C++ and C++/CLI Code](#).

Parameters

Command

Command mode that you want to check as defined in [swMouseDragMode_e](#)

Return Value

True if the specified command mode was set, false if not

Visual Basic for Applications (VBA) Syntax

See [SldWorks::SetMouseDragMode](#).

See Also

[ISldWorks Interface](#)

[ISldWorks Members](#)

[ISldWorks::GetMouseDragMode Method](#)

Availability

SOLIDWORKS 2001Plus FCS, Revision Number 10.0

SOLIDWORKS API Help

[Send comments on this topic.](#)

SetMultipleFileNamesPrompt Method (ISldWorks)

[See Also](#)



[SolidWorks.Interop.sldworks Namespace](#) > [ISldWorks Interface](#) : SetMultipleFileNamesPrompt Method (ISldWorks)

Sets the new filenames to open in response to the ISldWorks [PromptForMultipleFileNamesNotify](#) event.

.NET Syntax

Visual Basic (Declaration)

```
Sub SetMultipleFileNamesPrompt( _  
    ByVal FileName As System.Object _  
)
```

Visual Basic (Usage)



```
Dim instance As ISldWorks  
Dim FileName As System.Object  
  
instance.SetMultipleFileNamesPrompt(FileName)
```

C#

```
void SetMultipleFileNamesPrompt(  
    System.object FileName  
)
```

C++/CLI

```
void SetMultipleFileNamesPrompt(  
& System.Object^ FileName  
)
```

NOTE: See [Differences Between Unmanaged C++ and C++/CLI Code](#).

Parameters

FileName

Array of filenames

Visual Basic for Applications (VBA) Syntax

See [SldWorks::SetMultipleFileNamesPrompt](#).

Remarks

The filenames specified are only used if the SOLIDWORKS [PromptForMultipleFileNamesNotify](#) event returns S_FALSE. This implies that you cannot specify initial filenames for SOLIDWORKS to use in the standard dialog. Instead, you must provide your own file dialog and return the filenames after the user selects them.

Guidelines for using this method when the cause argument of the SOLIDWORKS PromptForMultipleFileNamesNotify event is set to [swSaveVirtualComponentExternally](#):

- Length of the Filename argument array must be equal to the length of the suggestedFileNames argument array passed into ISldWorks::SetMultipleFileNamesPrompt. If there is a mismatch, all virtual components will be saved internal to the assembly with the suggested file name passed by the SOLIDWORKS PromptForMultipleFileNamesNotify event.
- Supplying a full path and file name will save a virtual component external to the assembly using that path and file name.
- Supplying only a file name (i.e., no path) will save the virtual component internal to the assembly with the suggested file name passed by the SOLIDWORKS PromptForMultipleFileNamesNotify event.
- This method cannot be used to change the name of an internally saved virtual component.
- Supplying an empty string will save the virtual component external to the assembly and in the same folder as the assembly with the suggested file name passed by the SOLIDWORKS PromptForMultipleFileNamesNotify event.
- Supplying an invalid path and file name or insufficient access rights will save the virtual component internal to the assembly with the suggested file name passed by the SOLIDWORKS PromptForMultipleFileNamesNotify event.
- Insufficient access rights to the path and file name will save the virtual component internal to the assembly with the suggested file name passed by the SOLIDWORKS PromptForMultipleFileNamesNotify event.

See Also

[ISldWorks Interface](#)
[ISldWorks Members](#)
[ISldWorks::SetNewFilename Method](#)
[ISldWorks::SetPromptFilename Method](#)

Availability

SOLIDWORKS 2008 SP1, Revision Number 16.0

SOLIDWORKS API Help

[Send comments on this topic.](#)

SetNewFilename Method (ISldWorks)

[See Also](#)



[SolidWorks.Interop.sldworks Namespace](#) > [ISldWorks Interface](#) : SetNewFilename Method (ISldWorks)

Sets the name of the new SOLIDWORKS file.

.NET Syntax

Visual Basic (Declaration)

```
Function SetNewFilename( _  
    ByVal FileName As System.String _  
) As System.Boolean
```

Visual Basic (Usage)



```
Dim instance As ISldWorks  
Dim FileName As System.String  
Dim value As System.Boolean  
  
value = instance.SetNewFilename(FileName)
```

C#

```
System.bool SetNewFilename(  
    System.string FileName  
)
```

C++/CLI

```
System.bool SetNewFilename(  
& System.String^ FileName  
)
```

NOTE: See [Differences Between Unmanaged C++ and C++/CLI Code](#).

Parameters

FileName
Path and file name for new SOLIDWORKS file

Return Value

True if the name of the new SOLIDWORKS file is set, false if not

Visual Basic for Applications (VBA) Syntax

See [SldWorks::SetNewFilename](#).

Remarks

Use with SldWorks [FileNewPreNotifyEventHandler](#).

See Also

[ISldWorks Interface](#)
[ISldWorks Members](#)

Availability

SOLIDWORKS 2009 FCS, Revision Number 17.0

SOLIDWORKS API Help

[Send comments](#) on this topic.

SetPromptFilename Method (ISldWorks)

[See Also](#)



[SolidWorks.Interop.sldworks Namespace](#) > [ISldWorks Interface](#) : SetPromptFilename Method (ISldWorks)

Obsolete. Superseded by [ISldWorks::SetPromptFilename2](#)

.NET Syntax

Visual Basic (Declaration)

```
Sub SetPromptFilename( _  
    ByVal FileName As System.String _  
)
```

Visual Basic (Usage)



```
Dim instance As ISldWorks  
Dim FileName As System.String  
  
instance.SetPromptFilename(FileName)
```

C#

```
void SetPromptFilename(  
    System.string FileName  
)
```

C++/CLI

```
void SetPromptFilename(  
    & System.String^ FileName  
)
```

NOTE: See [Differences Between Unmanaged C++ and C++/CLI Code](#).

Parameters

FileName
Filename

Visual Basic for Applications (VBA) Syntax

See [SldWorks::SetPromptFilename](#).

Remarks

The filename specified is only used if the SOLIDWORKS events [PromptForFileNameNotify](#) or [ReferencedFilePreNotify](#) returns S_FALSE. This implies that you cannot specify an initial filename for SOLIDWORKS to use in the standard dialog. Instead, you must provide your own file dialog and return the filename after the user selects it.

See Also

[ISldWorks Interface](#)
[ISldWorks Members](#)
[ISldWorks::LoadFile4 Method](#)
[ISldWorks::OpenDoc6 Method](#)
[ISldWorks::SetMultipleFileNamesPrompt Method](#)
[ISldWorks::SetNewFilename Method](#)

Availability

SOLIDWORKS 2001Plus FCS, Revision Number 10.0

SOLIDWORKS API Help

[Send comments on this topic.](#)

SetPromptFilename2 Method (ISldWorks)

[See Also](#)



[SolidWorks.Interop.sldworks Namespace](#) > [ISldWorks Interface](#) : SetPromptFilename2 Method (ISldWorks)

Sets the file to open in response to a SOLIDWORKS event.

.NET Syntax

Visual Basic (Declaration)

```
Sub SetPromptFilename2( _  
    ByVal FileName As System.String, _  
    ByVal ConfigName As System.String _  
)
```

Visual Basic (Usage)



```
Dim instance As ISldWorks  
Dim FileName As System.String  
Dim ConfigName As System.String  
  
instance.SetPromptFilename2(FileName, ConfigName)
```

C#

```
void SetPromptFilename2(  
    System.string FileName,  
    System.string ConfigName  
)
```

C++/CLI

```
void SetPromptFilename2(  
& System.String^ FileName,  
& System.String^ ConfigName  
)
```

NOTE: See [Differences Between Unmanaged C++ and C++/CLI Code](#).

Parameters

FileName
Full pathname of file to open
ConfigName
Configuration name of file to open

Visual Basic for Applications (VBA) Syntax

See [SldWorks::SetPromptFilename2](#).

Example

Contact SOLIDWORKS API Support to obtain **Close and Reopen a Drawing Document (VBA, VB.NET, C#)**.

Remarks

FileName is used only:

When the handler of this event...

Returns...

[FileCloseNotify](#)

non-0 value

[PromptForFileNameNotify](#)

non-0 value

[ReferencedFilePreNotify](#)

non-0 value

Because the filename specified is used only when [PromptForFileNameNotify](#) and [ReferencedFilePreNotify](#) return S_FALSE, you cannot specify an initial filename for SOLIDWORKS to use in the standard dialog. Instead, you must provide your own file dialog and return the filename after the user selects it.

See Also

[ISldWorks Interface](#)
[ISldWorks Members](#)
[ISldWorks::LoadFile4 Method](#)
[ISldWorks::OpenDoc7 Method](#)
[ISldWorks::SetMultipleFileNamesPrompt Method](#)
[ISldWorks::SetNewFilename Method](#)

Availability

SOLIDWORKS 2012 FCS, Revision Number 20.0

SOLIDWORKS API Help

[Send comments on this topic.](#)

SetSearchFolders Method (ISldWorks)

[See Also](#) [Example](#)



[SolidWorks.Interop.sldworks Namespace](#) > [ISldWorks Interface](#) : SetSearchFolders Method (ISldWorks)

Sets the current folder search path as shown in **Tools > Options > System Options > File Locations > Show folders for > Referenced Documents**.

.NET Syntax

Visual Basic (Declaration)

```
Function SetSearchFolders( _  
    ByVal FolderType As System.Integer, _  
    ByVal Folders As System.String _  
) As System.Boolean
```

Visual Basic (Usage)



```
Dim instance As ISldWorks  
Dim FolderType As System.Integer  
Dim Folders As System.String  
Dim value As System.Boolean
```

```
value = instance.SetSearchFolders(FolderType, Folders)
```

C#

```
System.bool SetSearchFolders(  
    System.int FolderType,  
    System.string Folders  
)
```

C++/CLI

```
System.bool SetSearchFolders(  
& System.int FolderType,  
& System.String^ Folders  
)
```

NOTE: See [Differences Between Unmanaged C++ and C++/CLI Code](#).

Parameters

FolderType

The search folder type; the only type currently supported is swDocumentType; for an up-to-date listing, see [swSearchFolderTypes_e](#)

Folders

String containing all of the search folders; each search folder should be separated by a semicolon

Return Value

True if the search folders were set, false if not

Visual Basic for Applications (VBA) Syntax

See [ISldWorks::SetSearchFolders](#).

Example

[Get and Set Search Folders \(VBA\)](#)
[Get and Set Search Folders \(VB.NET\)](#)
[Get and Set Search Folders \(C#\)](#)

Remarks

The search folders are used by SOLIDWORKS based on their order. Folders at the top of the list get searched first and folders at the bottom of the list get searched last.

This method does not allow you to incrementally add to the search folders list. Calling this method overwrites the existing search folder settings. If you want to add a folder to the existing search folder list, you must get the current search folder list using [ISldWorks::GetSearchFolders](#) and then add your folder string at the appropriate location.

Search folder settings are ignored unless **Tools > Options > System Options > External References > Search file locations for external references** is selected. To get and set **Search file locations for external references** in the SOLIDWORKS API, use [swUserPreferenceToggle_e](#).swUseFolderSearchRules with [ISldWorks::GetUserPreferenceToggle](#) and [ISldWorks::SetUserPreferenceToggle](#), respectively.

See Also

[ISldWorks Interface](#)
[ISldWorks Members](#)
[ISldWorks::GetSearchFolders Method](#)
[ISldWorks::SetMissingReferencePathName Method](#)
[ISldWorks::GetDataFolder Method](#)

SOLIDWORKS API Help

[Send comments on this topic.](#)

SetSelectionFilter Method (ISldWorks)

[See Also](#)



[SolidWorks.Interop.sldworks Namespace](#) > [ISldWorks Interface](#) : SetSelectionFilter Method (ISldWorks)

Sets the current selection filter values for the specified item type.

.NET Syntax

Visual Basic (Declaration)

```
Sub SetSelectionFilter( _  
    ByVal SelType As System.Integer, _  
    ByVal State As System.Boolean _  
)
```

Visual Basic (Usage)

```
Dim instance As ISldWorks  
Dim SelType As System.Integer  
Dim State As System.Boolean  
  
instance.SetSelectionFilter(SelType, State)
```

C#

```
void SetSelectionFilter(  
    System.int SelType,  
    System.bool State  
)
```



```
void SetSelectionFilter(
& System.int SelType,
& System.bool State
)
```

NOTE: See [Differences Between Unmanaged C++ and C++/CLI Code](#).

Parameters

SelType

Selection type enable or disable as defined in [swSelectType_e](#)

State

True to enable selection of the specified type, false to disable the end-user's ability to select the item

Visual Basic for Applications (VBA) Syntax

See [ISldWorks::SetSelectionFilter](#).

See Also

[ISldWorks Interface](#)

[ISldWorks Members](#)

[ISldWorks::GetApplySelectionFilter Method](#)

[ISldWorks::GetSelectionFilter Method](#)

[ISldWorks::GetSelectionFilters Method](#)

[ISldWorks::!GetSelectionFilters Method](#)

[ISldWorks::!GetSelectionFiltersCount Method](#)

[ISldWorks::!SetSelectionFilters Method](#)

[ISldWorks::SetApplySelectionFilter Method](#)

[ISldWorks::SetSelectionFilters Method](#)

Availability

SOLIDWORKS 99, datecode 1999207

SOLIDWORKS API Help

[Send comments on this topic.](#)

SetSelectionFilters Method (ISldWorks)

[See Also](#) [Example](#)



[SolidWorks.Interop.sldworks Namespace](#) > [ISldWorks Interface](#) : SetSelectionFilters Method (ISldWorks)

Sets the status for multiple selection filters.

.NET Syntax

Visual Basic (Declaration)

```
Sub SetSelectionFilters( _
    ByVal SelType As System.Object, _
    ByVal State As System.Boolean _
)
```

Visual Basic (Usage)

```
Dim instance As ISldWorks
Dim SelType As System.Object
Dim State As System.Boolean
```

```
instance.SetSelectionFilters(SelType, State)
```

C#

```
void SetSelectionFilters(
    System.object SelType,
    System.bool State
)
```

C++/CLI

```
void SetSelectionFilters(
& System.Object^ SelType,
```



```
& System.bool State
)
```

NOTE: See [Differences Between Unmanaged C++ and C++/CLI Code](#).

Parameters

SelType

Array of long values representing the [swSelectType_e](#)

State

True to activate the selection filters, false to not

Visual Basic for Applications (VBA) Syntax

See [ISldWorks::SetSelectionFilters](#).

Example

[Set and Toggle Selection Filters \(VBA\)](#)

Remarks

The state is applied to all elements in the *SelType* array. To determine if the selection filter is active, use [ISldWorks::GetApplySelectionFilter](#).

See Also

[ISldWorks Interface](#)

[ISldWorks Members](#)

[ISldWorks::GetSelectionFilter Method](#)

[ISldWorks::GetSelectionFilters Method](#)

[ISldWorks::!GetSelectionFilters Method](#)

[ISldWorks::!GetSelectionFiltersCount Method](#)

[ISldWorks::!SetSelectionFilters Method](#)

[ISldWorks::SetApplySelectionFilter Method](#)

[ISldWorks::SetSelectionFilter Method](#)

Availability

SOLIDWORKS 2000 FCS, Revision Number 8.0

SOLIDWORKS API Help

[Send comments on this topic.](#)

SetThirdPartyPopupMenuState Method (ISldWorks)

[See Also](#)



[SolidWorks.Interop.sldworks Namespace](#) > [ISldWorks Interface](#) : SetThirdPartyPopupMenuState Method (ISldWorks)

Sets whether to show or hide a third-party popup (shortcut) menu.

.NET Syntax

Visual Basic (Declaration)

```
Function SetThirdPartyPopupMenuState( _
    ByVal RegisterId As System.Integer, _
    ByVal IsActive As System.Boolean _
) As System.Boolean
```

Visual Basic (Usage)



```
Dim instance As ISldWorks
Dim RegisterId As System.Integer
Dim IsActive As System.Boolean
Dim value As System.Boolean
```

```
value = instance.SetThirdPartyPopupMenuState(RegisterId, IsActive)
```

C#

```
System.bool SetThirdPartyPopupMenuState(
    System.int RegisterId,
```

```
        System.bool IsActive  
    )
```

C++/CLI

```
System.bool SetThirdPartyPopupMenuState(  
& System.int RegisterId,  
& System.bool IsActive  
)
```

NOTE: See [Differences Between Unmanaged C++ and C++/CLI Code](#).

Parameters

RegisterId

ID of shortcut menu from [ISldWorks::RegisterThirdPartyPopupMenu](#)

IsActive

True to show the shortcut menu, false to hide it

Return Value

True if shortcut menu is shown, false if it is hidden

Remarks

This method is supported in C++ applications only.

Typical steps in creating and displaying your shortcut menu:

1. [Add menu](#) and [add menu items](#) to the SOLIDWORKS main menu bar for your shortcut menu, or [add an icon to a context-sensitive menu](#) that displays your shortcut menu, or both.
2. [Register](#) your shortcut menu.
3. [Add](#) your shortcut menu items.
4. [Show](#) your shortcut menu at a specific location in the SOLIDWORKS graphics area, typically from a mouse event handler.
5. [Remove](#) a menu item from your shortcut menu, if desired.
6. Toggle the visibility of your shortcut menu.
7. [Remove the shortcut menu](#) from the SOLIDWORKS main menu bar and [remove the icon from the context-sensitive menu](#), if added.

See Also

[ISldWorks Interface](#)
[ISldWorks Members](#)

Availability

SOLIDWORKS 2010 FCS, Revision Number 18.0

SOLIDWORKS API Help

[Send comments on this topic.](#)

SetToolBarDock Method (ISldWorks)

[See Also](#)



[SolidWorks.Interop.sldworks Namespace](#) > [ISldWorks Interface](#) : SetToolBarDock Method (ISldWorks)

Obsolete. Superseded by [ISldWorks::SetToolBarDock2](#).

.NET Syntax

Visual Basic (Declaration)

```
Sub SetToolBarDock( _  
    ByVal ModuleIn As System.String, _  
    ByVal ToolBarIDIn As System.Integer, _  
    ByVal DocStatePosIn As System.Integer _  
)
```

Visual Basic (Usage)



```
Dim instance As ISldWorks  
Dim ModuleIn As System.String  
Dim ToolBarIDIn As System.Integer  
Dim DocStatePosIn As System.Integer  
  
instance.SetToolBarDock(ModuleIn, ToolBarIDIn, DocStatePosIn)
```

C#

```
void SetToolbarDock(  
    System.string ModuleIn,  
    System.int ToolbarIDIn,  
    System.int DocStatePosIn  
)
```

C++/CLI

```
void SetToolbarDock(  
& System.String^ ModuleIn,  
& System.int ToolbarIDIn,  
& System.int DocStatePosIn  
)
```

NOTE: See [Differences Between Unmanaged C++ and C++/CLI Code](#).

Parameters

ModuleIn

ToolbarIDIn

DocStatePosIn

Visual Basic for Applications (VBA) Syntax

See [ISldWorks::SetToolbarDock](#).

See Also

[ISldWorks Interface](#)
[ISldWorks Members](#)

SOLIDWORKS API Help

[Send comments](#) on this topic.

SetToolbarDock2 Method (ISldWorks)

[See Also](#)



[SolidWorks.Interop.sldworks Namespace](#) > [ISldWorks Interface](#) : SetToolbarDock2 Method (ISldWorks)

Sets the docking state of the toolbar.

.NET Syntax

Visual Basic (Declaration)

```
Function SetToolbarDock2(  
    ByVal Cookie As System.Integer, _  
    ByVal ToolbarId As System.Integer, _  
    ByVal DockingState As System.Integer _  
) As System.Boolean
```

Visual Basic (Usage)



```
Dim instance As ISldWorks  
Dim Cookie As System.Integer  
Dim ToolbarId As System.Integer  
Dim DockingState As System.Integer  
Dim value As System.Boolean
```

```
value = instance.SetToolbarDock2(Cookie, ToolbarId, DockingState)
```

C#

```
System.bool SetToolbarDock2(  
    System.int Cookie,  
    System.int ToolbarId,  
    System.int DockingState  
)
```

C++/CLI

```
System.bool SetToolbarDock2(  
& System.int Cookie,  
& System.int ToolbarId,  
& System.int DockingState  
)
```

NOTE: See [Differences Between Unmanaged C++ and C++/CLI Code](#).

Parameters

Cookie

Identifier of toolbar; this is the same cookie you specified in [ISwAddin::ConnectToSW](#)

ToolbarId

ID of the toolbar as defined in [swToolbar_e](#)

DockingState

Docking state of the toolbar as defined in [swToolbarDockStatePosition_e](#)

Return Value

True if the docking state of the toolbar is set, false if not

Visual Basic for Applications (VBA) Syntax

See [ISldWorks::SetToolbarDock2](#).

See Also

[ISldWorks Interface](#)

[ISldWorks Members](#)

[ISldWorks::AddToolBar4 Method](#)

[ISldWorks::AddToolBarCommand2 Method](#)

[ISldWorks::GetToolBarDock2 Method](#)

[ISldWorks::GetToolBarState2 Method](#)

[ISldWorks::HideToolBar2 Method](#)

[ISldWorks::DragToolBarButton Method](#)

Availability

SOLIDWORKS 2001Plus FCS, Revision Number 10.0

SOLIDWORKS API Help

[Send comments](#) on this topic.

SetToolbarVisibility Method (ISldWorks)

[See Also](#)



[SolidWorks.Interop.sldworks Namespace](#) > [ISldWorks Interface](#) : SetToolbarVisibility Method (ISldWorks)

Sets whether the specified toolbar is visible.

.NET Syntax

Visual Basic (Declaration)

```
Sub SetToolbarVisibility( _  
    ByVal Toolbar As System.Integer, _  
    ByVal Visibility As System.Boolean _  
)
```

Visual Basic (Usage)



```
Dim instance As ISldWorks  
Dim Toolbar As System.Integer  
Dim Visibility As System.Boolean
```

```
instance.SetToolbarVisibility(Toolbar, Visibility)
```

C#

```
void SetToolbarVisibility(  
    System.int Toolbar,  
    System.bool Visibility  
)
```

```
void SetToolbarVisibility(
& System.int Toolbar,
& System.bool Visibility
)
```

NOTE: See [Differences Between Unmanaged C++ and C++/CLI Code](#).

Parameters

Toolbar

Identifier of toolbar as defined in [swToolbar_e](#)

Visibility

True to show the toolbar, false to hide it

Visual Basic for Applications (VBA) Syntax

See [ISldWorks::SetToolbarVisibility](#).

See Also

[ISldWorks Interface](#)
[ISldWorks Members](#)
[ISldWorks::GetToolbarVisibility Method](#)
[ISldWorks::GetToolbarState2 Method](#)
[ISldWorks::HideToolbar2 Method](#)
[ISldWorks::ShowToolbar2 Method](#)
[IModelDoc2::GetToolbarVisibility Method](#)
[IModelDoc2::SetToolbarVisibility Method](#)
[ISldWorks::AddToolbars Method](#)

Availability

SOLIDWORKS 2009 SP03, Revision Number 17.3

SOLIDWORKS API Help

[Send comments on this topic.](#)

SetUserPreferenceDoubleValue Method (ISldWorks)

[See Also](#) [Example](#)



[SolidWorks.Interop.sldworks Namespace](#) > [ISldWorks Interface](#) : SetUserPreferenceDoubleValue Method (ISldWorks)

Sets system default user preference values.

.NET Syntax

Visual Basic (Declaration)

```
Function SetUserPreferenceDoubleValue( _
    ByVal UserPreferenceValue As System.Integer, _
    ByVal Value As System.Double _
) As System.Boolean
```

Visual Basic (Usage)



```
Dim instance As ISldWorks
Dim UserPreferenceValue As System.Integer
Dim Value As System.Double
Dim value As System.Boolean
```

```
value = instance.SetUserPreferenceDoubleValue(UserPreferenceValue, Value)
```

C#

```
System.bool SetUserPreferenceDoubleValue(
    System.int UserPreferenceValue,
    System.double Value
)
```

```
System.bool SetUserPreferenceDoubleValue(  
& System.int UserPreferenceValue,  
& System.double Value  
)
```

NOTE: See [Differences Between Unmanaged C++ and C++/CLI Code](#).

Parameters

UserPreferenceValue

User preference as defined in [swUserPreferenceDoubleValue_e](#)

Value

Value of UserPreferenceValue

Return Value

True if UserPreferenceValue is set, false if not

Visual Basic for Applications (VBA) Syntax

See [SldWorks::SetUserPreferenceDoubleValue](#).

Example

[Save Document As TIFF \(VBA\)](#)

[Get and Set User Preferences \(VBA\)](#)

[Get and Set User Preferences \(VB.NET\)](#)

[Get and Set User Preferences \(C#\)](#)

Remarks

This method is intended for user preferences of type double.

This method is equivalent to interactively setting system options in the SOLIDWORKS Design software.

To use this method, choose one of the items from the swUserPreferenceDoubleValue_e enumeration. Then, call this method and pass in the desired user preference from the swUserPreferenceDoubleValue_e enumeration and the desired value for that user preference.

For a description of the user-preference types and which object supports that type, see [swUserPreferenceDoubleValue_e](#).

See [System Options and Document Properties](#) for details.

See Also

[ISldWorks Interface](#)

[ISldWorks Members](#)

[ISldWorks::GetUserPreferenceDoubleValue Method](#)

[ISldWorks::GetUserPreferenceIntegerValue Method](#)

[ISldWorks::GetUserPreferenceStringListValue Method](#)

[ISldWorks::GetUserPreferenceStringValue Method](#)

[ISldWorks::GetUserPreferenceToggle Method](#)

[ISldWorks::SetUserPreferenceIntegerValue Method](#)

[ISldWorks::SetUserPreferenceStringListValue Method](#)

[ISldWorks::SetUserPreferenceStringValue Method](#)

[ISldWorks::SetUserPreferenceToggle Method](#)

[IModelDocExtension::SetUserPreferenceDouble Method](#)

[IModelDocExtension::SetUserPreferenceInteger Method](#)

[IModelDocExtension::SetUserPreferenceString Method](#)

[IModelDocExtension::SetUserPreferenceTextFormat Method](#)

[IModelDocExtension::SetUserPreferenceToggle Method](#)

[IModelDocExtension::GetUserPreferenceDouble Method](#)

[IModelDocExtension::GetUserPreferenceDoubleValueRange Method](#)

[IModelDocExtension::GetUserPreferenceInteger Method](#)

[IModelDocExtension::GetUserPreferenceString Method](#)

[IModelDocExtension::GetUserPreferenceTextFormat Method](#)

[IModelDocExtension::GetUserPreferenceToggle Method](#)

SOLIDWORKS API Help

[Send comments](#) on this topic.

SetUserPreferenceIntegerValue Method (ISldWorks)

See Also [Example](#)



[SolidWorks.Interop.sldworks Namespace](#) > [ISldWorks Interface](#) : SetUserPreferenceIntegerValue Method (ISldWorks)

Sets system default user preference values.

.NET Syntax

Visual Basic (Declaration)

```
Function SetUserPreferenceIntegerValue( _
    ByVal UserPreferenceValue As System.Integer, _
    ByVal Value As System.Integer _
) As System.Boolean
```

Visual Basic (Usage)



```
Dim instance As ISldWorks
Dim UserPreferenceValue As System.Integer
Dim Value As System.Integer
Dim value As System.Boolean

value = instance.SetUserPreferenceIntegerValue(UserPreferenceValue, Value)
```

C#

```
System.bool SetUserPreferenceIntegerValue(
    System.int UserPreferenceValue,
    System.int Value
)
```

C++/CLI

```
System.bool SetUserPreferenceIntegerValue(
    & System.int UserPreferenceValue,
    & System.int Value
)
```

NOTE: See [Differences Between Unmanaged C++ and C++/CLI Code](#).

Parameters

UserPreferenceValue

User preference as defined in [swUserPreferenceIntegerValue_e](#)

Value

Value of UserPreferenceValue

Return Value

True if UserPreferenceValue is set, false if not

Visual Basic for Applications (VBA) Syntax

See [SldWorks::SetUserPreferenceIntegerValue](#).

Example

[Force Rebuild \(VBA\)](#)
[Import Models As Solids \(VBA\)](#)
[Open All External References \(VBA\)](#)
[Save Rolledback Part As Parasolid File \(VBA\)](#)
[Get and Set User Preferences \(VBA\)](#)
[Get and Set User Preferences \(VB.NET\)](#)
[Get and Set User Preferences \(C#\)](#)

Remarks

This method is intended for user preferences of type integer.

This method is equivalent to interactively setting system options in the SOLIDWORKS Design software.

See [System Options and Document Properties](#) for details.

See Also

[ISldWorks Interface](#)
[ISldWorks Members](#)
[ISldWorks::GetUserPreferenceDoubleValue Method](#)
[ISldWorks::GetUserPreferenceIntegerValue Method](#)
[ISldWorks::GetUserPreferenceStringListValue Method](#)
[ISldWorks::GetUserPreferenceStringValue Method](#)
[ISldWorks::GetUserPreferenceToggle Method](#)
[ISldWorks::SetUserPreferenceDoubleValue Method](#)

[ISldWorks::SetUserPreferenceStringListValue Method](#)
[ISldWorks::SetUserPreferenceStringValue Method](#)
[ISldWorks::SetUserPreferenceToggle Method](#)
[IModelDocExtension::GetUserPreferenceDouble Method](#)
[IModelDocExtension::GetUserPreferenceDoubleValueRange Method](#)
[IModelDocExtension::GetUserPreferenceInteger Method](#)
[IModelDocExtension::GetUserPreferenceString Method](#)
[IModelDocExtension::GetUserPreferenceTextFormat Method](#)
[IModelDocExtension::GetUserPreferenceToggle Method](#)
[IModelDocExtension::SetUserPreferenceDouble Method](#)
[IModelDocExtension::SetUserPreferenceInteger Method](#)
[IModelDocExtension::SetUserPreferenceString Method](#)
[IModelDocExtension::SetUserPreferenceTextFormat Method](#)
[IModelDocExtension::SetUserPreferenceToggle Method](#)

SOLIDWORKS API Help

[Send comments on this topic.](#)

SetUserPreferenceStringListValue Method (ISldWorks)

[See Also](#)



[SolidWorks.Interop.sldworks Namespace](#) > [ISldWorks Interface](#) : SetUserPreferenceStringListValue Method (ISldWorks)

Sets the name of the DXF mapping files.

.NET Syntax

Visual Basic (Declaration)

```
Sub SetUserPreferenceStringListValue( _  
    ByVal UserPreference As System.Integer, _  
    ByVal Value As System.String _  
)
```

Visual Basic (Usage)



```
Dim instance As ISldWorks  
Dim UserPreference As System.Integer  
Dim Value As System.String  
  
instance.SetUserPreferenceStringListValue(UserPreference, Value)
```

C#

```
void SetUserPreferenceStringListValue(  
    System.int UserPreference,  
    System.string Value  
)
```

C++/CLI

```
void SetUserPreferenceStringListValue(  
& System.int UserPreference,  
& System.String^ Value  
)
```

NOTE: See [Differences Between Unmanaged C++ and C++/CLI Code](#).

Parameters

UserPreference

User preference as defined in [swUserPreferenceStringValue_e](#)

Value

Value of UserPreference

Visual Basic for Applications (VBA) Syntax

See [SldWorks::SetUserPreferenceStringListValue](#).

Remarks

Multiple strings in the value argument must be separated by new line characters (vbNewLine" or "VbLf in Visual Basic, \n in Visual C or Visual C++).

This method is equivalent to interactively setting system options in the SOLIDWORKS Design software.

See [System Options and Document Properties](#) for details.

See Also

[ISldWorks Interface](#)
[ISldWorks Members](#)
[ISldWorks::GetUserPreferenceDoubleValue Method](#)
[ISldWorks::GetUserPreferenceIntegerValue Method](#)
[ISldWorks::GetUserPreferenceStringListValue Method](#)
[ISldWorks::GetUserPreferenceStringValue Method](#)
[ISldWorks::GetUserPreferenceToggle Method](#)
[ISldWorks::SetUserPreferenceDoubleValue Method](#)
[ISldWorks::SetUserPreferenceIntegerValue Method](#)
[ISldWorks::SetUserPreferenceStringValue Method](#)
[ISldWorks::SetUserPreferenceToggle Method](#)
[IModelDocExtension::SetUserPreferenceDouble Method](#)
[IModelDocExtension::SetUserPreferenceInteger Method](#)
[IModelDocExtension::SetUserPreferenceString Method](#)
[IModelDocExtension::SetUserPreferenceTextFormat Method](#)
[IModelDocExtension::SetUserPreferenceToggle Method](#)
[IModelDocExtension::GetUserPreferenceDouble Method](#)
[IModelDocExtension::GetUserPreferenceDoubleValueRange Method](#)
[IModelDocExtension::GetUserPreferenceInteger Method](#)
[IModelDocExtension::GetUserPreferenceString Method](#)
[IModelDocExtension::GetUserPreferenceTextFormat Method](#)
[IModelDocExtension::GetUserPreferenceToggle Method](#)

SOLIDWORKS API Help

[Send comments](#) on this topic.

SetUserPreferenceStringValue Method (ISldWorks)

[See Also](#) [Example](#)



[SolidWorks.Interop.sldworks Namespace](#) > [ISldWorks Interface](#) : SetUserPreferenceStringValue Method (ISldWorks)

Sets system default user preference values.

.NET Syntax

Visual Basic (Declaration)

```
Function SetUserPreferenceStringValue( _  
    ByVal UserPreference As System.Integer, _  
    ByVal Value As System.String _  
) As System.Boolean
```

Visual Basic (Usage)



```
Dim instance As ISldWorks  
Dim UserPreference As System.Integer  
Dim Value As System.String  
Dim value As System.Boolean  
  
value = instance.SetUserPreferenceStringValue(UserPreference, Value)
```

C#

```
System.bool SetUserPreferenceStringValue(  
    System.int UserPreference,  
    System.string Value  
)
```

C++/CLI

```
System.bool SetUserPreferenceStringValue(  
& System.int UserPreference,  
& System.String^ Value  
)
```

NOTE: See [Differences Between Unmanaged C++ and C++/CLI Code](#).

Parameters

UserPreference

User preference as defined in [swUserPreferenceStringValue_e](#)

Value

Value of UserPreference

Return Value

True if UserPreference is set, false if not

Visual Basic for Applications (VBA) Syntax

See [SldWorks::SetUserPreferenceStringValue](#).

Example

[Change Labels of SOLIDWORKS Triad \(VBA\)](#)
[Get and Set User Preferences \(VBA\)](#)
[Get and Set User Preferences \(VB.NET\)](#)
[Get and Set User Preferences \(C#\)](#)

Remarks

This method is intended for user preferences of type string.

This method is equivalent to interactively setting system options in the SOLIDWORKS Design software.

See [System Options and Document Properties](#) for details.

See Also

[ISldWorks Interface](#)
[ISldWorks Members](#)
[ISldWorks::GetUserPreferenceDoubleValue Method](#)
[ISldWorks::GetUserPreferenceIntegerValue Method](#)
[ISldWorks::GetUserPreferenceStringListValue Method](#)
[ISldWorks::GetUserPreferenceStringValue Method](#)
[ISldWorks::GetUserPreferenceToggle Method](#)
[ISldWorks::SetUserPreferenceDoubleValue Method](#)
[ISldWorks::SetUserPreferenceIntegerValue Method](#)
[ISldWorks::SetUserPreferenceStringListValue Method](#)
[ISldWorks::SetUserPreferenceToggle Method](#)
[IModelDocExtension::GetUserPreferenceDouble Method](#)
[IModelDocExtension::GetUserPreferenceDoubleValueRange Method](#)
[IModelDocExtension::GetUserPreferenceInteger Method](#)
[IModelDocExtension::GetUserPreferenceString Method](#)
[IModelDocExtension::GetUserPreferenceTextFormat Method](#)
[IModelDocExtension::GetUserPreferenceToggle Method](#)
[IModelDocExtension::SetUserPreferenceDouble Method](#)
[IModelDocExtension::SetUserPreferenceInteger Method](#)
[IModelDocExtension::SetUserPreferenceString Method](#)
[IModelDocExtension::SetUserPreferenceTextFormat Method](#)
[IModelDocExtension::SetUserPreferenceToggle Method](#)

Availability

SOLIDWORKS 2000 FCS, Revision Number 8.0

SOLIDWORKS API Help

[Send comments on this topic.](#)

SetUserPreferenceToggle Method (ISldWorks)

[See Also](#) [Example](#)



[SolidWorks.Interop.sldworks Namespace](#) > [ISldWorks Interface](#) : SetUserPreferenceToggle Method (ISldWorks)

Sets system default user preference values.

.NET Syntax

Visual Basic (Declaration)

```
Sub SetUserPreferenceToggle( _  
    ByVal UserPreferenceValue As System.Integer, _  
    ByVal OnFlag As System.Boolean _  
)
```

Visual Basic (Usage)



```
Dim instance As ISldWorks  
Dim UserPreferenceValue As System.Integer  
Dim OnFlag As System.Boolean
```

```
instance.SetUserPreferenceToggle(UserPreferenceValue, OnFlag)
```

C#

```
void SetUserPreferenceToggle(
    System.int UserPreferenceValue,
    System.bool OnFlag
)
```

C++/CLI

```
void SetUserPreferenceToggle(
    & System.int UserPreferenceValue,
    & System.bool OnFlag
)
```

NOTE: See [Differences Between Unmanaged C++ and C++/CLI Code](#).

Parameters

UserPreferenceValue

User preference as defined in [swUserPreferenceToggle_e](#)

OnFlag

True to toggle UserPreferenceValue on, false to toggle UserPreferenceValue off

Visual Basic for Applications (VBA) Syntax

See [SldWorks::SetUserPreferenceToggle](#).

Example

[Display Shadows in Shaded Mode \(C++\)](#)
[Change Labels of SOLIDWORKS Triad \(VBA\)](#)
[Rename Assembly Components \(VBA\)](#)
[Save Drawing Sheets As DXF \(VBA\)](#)
[Suppress Rebuild Error Dialogs \(VBA\)](#)
[Get and Set User Preferences \(VBA\)](#)
[Get and Set User Preferences \(VB.NET\)](#)
[Get and Set User Preferences \(C#\)](#)

Remarks

This method is intended for user preferences that can be toggled.

This method is equivalent to interactively setting system options in the SOLIDWORKS Design software.

To use this method, choose one of the available items from the swUserPreferenceToggle_e enumeration. Pass true to turn the item on, and false to turn the item off.

For example, the following command forces the SOLIDWORKS Design application to use the Search Folders when loading files:

```
swapp.SetUserPreferenceToggle swUseFolderSearchRules, True
```

See [System Options and Document Properties](#) for details.

See Also

[ISldWorks Interface](#)
[ISldWorks Members](#)
[ISldWorks::GetUserPreferenceDoubleValue Method](#)
[ISldWorks::GetUserPreferenceIntegerValue Method](#)
[ISldWorks::GetUserPreferenceStringListValue Method](#)
[ISldWorks::GetUserPreferenceStringValue Method](#)
[ISldWorks::GetUserPreferenceToggle Method](#)
[ISldWorks::SetUserPreferenceDoubleValue Method](#)
[ISldWorks::SetUserPreferenceIntegerValue Method](#)
[ISldWorks::SetUserPreferenceStringListValue Method](#)
[ISldWorks::SetUserPreferenceStringValue Method](#)
[IModelDocExtension::SetUserPreferenceDouble Method](#)
[IModelDocExtension::SetUserPreferenceInteger Method](#)
[IModelDocExtension::SetUserPreferenceString Method](#)
[IModelDocExtension::SetUserPreferenceTextFormat Method](#)
[IModelDocExtension::SetUserPreferenceToggle Method](#)
[IModelDocExtension::GetUserPreferenceDouble Method](#)
[IModelDocExtension::GetUserPreferenceDoubleValueRange Method](#)
[IModelDocExtension::GetUserPreferenceInteger Method](#)
[IModelDocExtension::GetUserPreferenceString Method](#)
[IModelDocExtension::GetUserPreferenceTextFormat Method](#)
[IModelDocExtension::GetUserPreferenceToggle Method](#)



[SolidWorks.Interop.sldworks Namespace](#) > [ISldWorks Interface](#) : ShadedEdgeThickness Property (ISldWorks)

Gets or sets the edge thickness when the display style is "Shaded with Edges".

.NET Syntax

Visual Basic (Declaration)

Property ShadedEdgeThickness As System.Integer

Visual Basic (Usage)



```
Dim instance As ISldWorks
Dim value As System.Integer

instance.ShadedEdgeThickness = value

value = instance.ShadedEdgeThickness
```

C#

```
System.int ShadedEdgeThickness {get; set;}
```

C++/CLI

```
property System.int ShadedEdgeThickness {
    System.int get();
    void set ( & System.int value);
}
```

NOTE: See [Differences Between Unmanaged C++ and C++/CLI Code](#).

Property Value

Edge thickness

Visual Basic for Applications (VBA) Syntax

See [SldWorks::ShadedEdgeThickness](#).

Remarks

This property is valid only when the Render system is turned on. To turn on the Render system, select **Tools > Options > System Options > Performance > Enhanced graphics performance (requires SOLIDWORKS restart)**.

The set value of this property cannot exceed 6.

See Also

[ISldWorks Interface](#)
[ISldWorks Members](#)

Availability

SOLIDWORKS 2026 FCS, Revision Number 34

SOLIDWORKS API Help

[Send comments on this topic.](#)

ShowBatchSaveTo3DExperienceDlg Method (ISldWorks)

[See Also](#)



[SolidWorks.Interop.sldworks Namespace](#) > [ISldWorks Interface](#) : ShowBatchSaveTo3DExperienceDlg Method (ISldWorks)

Opens a dialog to save files in the specified folder to 3DEXPERIENCE.

.NET Syntax

Visual Basic (Declaration)

```
Function ShowBatchSaveTo3DExperienceDlg( _
    ByVal FolderPath As System.String, _
    ByVal Options As System.Integer _
) As System.Integer
```

Visual Basic (Usage)



```
Dim instance As ISldWorks
Dim FolderPath As System.String
Dim Options As System.Integer
Dim value As System.Integer

value = instance.ShowBatchSaveTo3DExperienceDlg(FolderPath, Options)
```

C#

```
System.int ShowBatchSaveTo3DExperienceDlg(
    System.string FolderPath,
    System.int Options
)
```

C++/CLI

```
System.int ShowBatchSaveTo3DExperienceDlg(
    & System.String^ FolderPath,
    & System.int Options
)
```

NOTE: See [Differences Between Unmanaged C++ and C++/CLI Code](#).

Parameters

FolderPath
Path of files to save
Options
not used

Return Value

0 if successful, -1 if not

Visual Basic for Applications (VBA) Syntax

See [SldWorks::ShowBatchSaveTo3DExperienceDlg](#).

Remarks

This method is valid only for [SOLIDWORKS Design connected to the 3DEXPERIENCE platform](#).

Call [ISldWorks::RunBatchSaveProcess](#) after using this method.

See Also

[ISldWorks Interface](#)
[ISldWorks Members](#)

Availability

SOLIDWORKS 2022 SP03, Revision Number 30.3

SOLIDWORKS API Help

[Send comments on this topic.](#)

ShowBubbleTooltip Method (ISldWorks)

[See Also](#) [Example](#)



[SolidWorks.Interop.sldworks Namespace](#) > [ISldWorks Interface](#) : ShowBubbleTooltip Method (ISldWorks)

Displays a bubble ToolTip and flashes the specified toolbar button.

.NET Syntax

```
Sub ShowBubbleTooltip( _
    ByVal PointAt As System.Integer, _
    ByVal FlashButtonIDs As System.String, _
    ByVal TitleResID As System.Integer, _
    ByVal TitleString As System.String, _
    ByVal MessageString As System.String _
)
```



```
Dim instance As ISldWorks
Dim PointAt As System.Integer
Dim FlashButtonIDs As System.String
Dim TitleResID As System.Integer
Dim TitleString As System.String
Dim MessageString As System.String

instance.ShowBubbleTooltip(PointAt, FlashButtonIDs, TitleResID, TitleString, MessageString)
```

```
void ShowBubbleTooltip(
    System.int PointAt,
    System.string FlashButtonIDs,
    System.int TitleResID,
    System.string TitleString,
    System.string MessageString
)
```

```
void ShowBubbleTooltip(
    & System.int PointAt,
    & System.String^ FlashButtonIDs,
    & System.int TitleResID,
    & System.String^ TitleString,
    & System.String^ MessageString
)
```

NOTE: See [Differences Between Unmanaged C++ and C++/CLI Code](#).

Parameters

PointAt

Toolbar button ID

FlashButtonIDs

Array of strings for the toolbar buttons

TitleResID

Title resource ID of bubble Tooltip or 0

TitleString

Title of bubble ToolTip

MessageString

Message string of bubble ToolTip

Visual Basic for Applications (VBA) Syntax

See [SldWorks::ShowBubbleTooltip](#).

Example

[Flash an Add-in's Toolbar Button \(VBA\)](#)

See Also

[ISldWorks Interface](#)

[ISldWorks Members](#)

[ISldWorks::ShowBubbleTooltipAt2 Method](#)

