

SOLIDWORKS HTML Control API (.NET) — Reference (1/1): namespace hierarchy — SolidWorks.Interop.swhtmlcontrol

SOLIDWORKS API Documentation (converted from CHM)

_namespace_hierarchy (Type)

SOLIDWORKS HTML Control Type Library

[Send comments on this topic.](#)

SolidWorks.Interop.swhtmlcontrol Namespace Inheritance Hierarchy

[See Also](#)



Inheritance Hierarchy

System.Object



See Also

[SolidWorks.Interop.swhtmlcontrol Assembly.](#)

ISwHtmlInterface (Type)

SOLIDWORKS HTML Control Type Library

ISwHtmlInterface Interface

See Also Members Example

[Send comments on this topic.](#)

SolidWorks.Interop.swhtmlcontrol Namespace : ISwHtmlInterface Interface

Must be implemented in each add-in's Quick Tips HTML page so that users can interact with the add-in's Quick Tips and see associated Bubble ToolTips.
NOTE: Click the **Members** link, located near the top of the topic, to see this interface's methods and properties.

Visual Basic (Declaration)

Public Interface ISwHtmlInterface

Visual Basic (Usage)

Dim instance As [ISwHtmlInterface](#)

C#

public interface ISwHtmlInterface

C++/CLI

public interface class ISwHtmlInterface

Visual Basic for Applications (VBA) Syntax

See [SwHtmlInterface](#).

Example

Show Bubble ToolTip (VBA)

Remarks

To access this API, include the following line of code in your application. See [Quick Tips and Bubble ToolTips](#) for more information.
CreateObject('SwHtmlControl.SwHtmlInterface')

See Also

[ISwHtmlInterface Members](#)
[SolidWorks.Interop.swhtmlcontrol Namespace](#)
[ISldWorks::InstallQuickTipGuide](#)
[ISldWorks::RefreshQuickTipWindow](#)
[ISldWorks::UninstallQuickTipGuide](#)
[ISwQuickTip](#)

SOLIDWORKS HTML Control Type Library

ISwHtmlInterface Interface Methods

See Also

[Send comments on this topic.](#)

SolidWorks.Interop.swhtmlcontrol Namespace : ISwHtmlInterface Interface

For a list of all members of this type, see [ISwHtmlInterface members](#).

Public Methods

Name	Description
 GetCommandID	Gets the SOLIDWORKS resource ID for an add-in's CommandManager -style toolbar button.
 GetCurrentTOIndex	Gets the index of the current Tip of the Day.
 GetInterfaceBrightnessTheme	Gets the background theme of SOLIDWORKS.
 GetPrevTipOfTheDay	Gets the previous Tip of the Day.
 HideBubbleToolTip	Hides the Bubble ToolTip displayed by ISwHtmlInterface::ShowBubbleToolTipAt .
 IsX64	Gets whether you are running SOLIDWORKS (32-bit) or SOLIDWORKS x64 (64-bit).
 ShowBubbleToolTip	Displays a Bubble ToolTip and flashes the specified toolbar button.

		
	ShowBubbleToolTipAt	Displays a Bubble ToolTip at the specified location.
	ShowBubbleToolTipForAddinToolBar	Displays a Bubble ToolTip for the specified add-in and flashes the specified toolbar button.
	ShowHomeIconMarker	Displays a home icon.
	ShowToolTip	Shows the Bubble ToolTip and flashes the specified toolbar or toolbar buttons.

[Top](#)

See Also

[ISwHtmlInterface Interface](#)
[SolidWorks.Interop.swhtmlcontrol Namespace](#)
[ISldWorks::InstallQuickTipGuide](#)
[ISldWorks::RefreshQuickTipWindow](#)
[ISldWorks::UninstallQuickTipGuide](#)
[ISwQuickTip](#)

[Send comments on this topic.](#)

SOLIDWORKS HTML Control Type Library
ISwHtmlInterface Interface Members
[See Also](#) [Methods](#)

 [SolidWorks.Interop.swhtmlcontrol Namespace](#) : [ISwHtmlInterface Interface](#)

The following tables list the members exposed by [ISwHtmlInterface](#).

Public Methods

Name	Description
 GetCommandID	Gets the SOLIDWORKS resource ID for an add-in's CommandManager -style toolbar button.
 GetCurrentTOIndex	Gets the index of the current Tip of the Day.
 GetInterfaceBrightnessTheme	Gets the background theme of SOLIDWORKS.
 GetPrevTipOfTheDay	Gets the previous Tip of the Day.
 HideBubbleToolTip	Hides the Bubble ToolTip displayed by ISwHtmlInterface::ShowBubbleToolTipAt .
 IsX64	Gets whether you are running SOLIDWORKS (32-bit) or SOLIDWORKS x64 (64-bit).
 ShowBubbleToolTip	Displays a Bubble ToolTip and flashes the specified toolbar button.
 ShowBubbleToolTipAt	Displays a Bubble ToolTip at the specified location.
 ShowBubbleToolTipForAddinToolBar	Displays a Bubble ToolTip for the specified add-in and flashes the specified toolbar button.
 ShowHomeIconMarker	Displays a home icon.
 ShowToolTip	Shows the Bubble ToolTip and flashes the specified toolbar or toolbar buttons.

[Top](#)

See Also

[ISwHtmlInterface Interface](#)
[SolidWorks.Interop.swhtmlcontrol Namespace](#)
[ISldWorks::InstallQuickTipGuide](#)
[ISldWorks::RefreshQuickTipWindow](#)
[ISldWorks::UninstallQuickTipGuide](#)
[ISwQuickTip](#)

[Send comments on this topic.](#)

SOLIDWORKS HTML Control Type Library
GetCommandID Method (ISwHtmlInterface)
[See Also](#) [Example](#)



[SolidWorks.Interop.swhtmlcontrol Namespace](#) > [ISwHtmlInterface Interface](#) : [GetCommandID Method \(ISwHtmlInterface\)](#)

Gets the SOLIDWORKS resource ID for an add-in's [CommandManager](#)-style toolbar button.

.NET Syntax

Visual Basic (Declaration)

```
Function GetCommandID( _  
    ByVal ClsID As System.String, _  
    ByVal UserCmdID As System.Integer _  
) As System.Integer
```

Visual Basic (Usage)



```

Dim instance As ISwHtmlInterface
Dim ClsID As System.String
Dim UserCmdID As System.Integer
Dim value As System.Integer

value = instance.GetCommandID(ClsID, UserCmdID)

```

C#

```

System.int GetCommandID(
    System.string ClsID,
    System.int UserCmdID
)

```

C++/CLI

```

System.int GetCommandID(
    & System.String^ ClsID,
    & System.int UserCmdID
)

```

Parameters

ClsID

Add-in's class ID

UserCmdID

Unique ID that the add-in application identified as a CommandManager-style toolbar button

Return Value

Currently bound ID for the CommandManager-style toolbar button

Visual Basic for Applications (VBA) Syntax

See [SwHtmlInterface::GetCommandID](#).

Example

[Flash an Add-in's Toolbar Button \(VBA\)](#)

See Also

[ISwHtmlInterface Interface](#)

[ISwHtmlInterface Members](#)

[ISldWorks::ShowBubbleToolTip](#)

[ISwHtmlInterface::ShowBubbleToolTip Method](#)

[ISwHtmlInterface::ShowBubbleToolTipForAddinToolbar Method](#)

Availability

SOLIDWORKS 2006 SP3, Revision Number 14.3

SOLIDWORKS HTML Control Type Library

[Send comments on this topic.](#)

[GetCurrentTODIndex Method \(ISwHtmlInterface\)](#)

[See Also](#)



[SolidWorks.Interop.swhtmlcontrol Namespace](#) > [ISwHtmlInterface Interface](#) : [GetCurrentTODIndex Method \(ISwHtmlInterface\)](#)

Gets the index of the current Tip of the Day.

.NET Syntax

Visual Basic (Declaration)

```

Function GetCurrentTODIndex() As System.Integer

```

Visual Basic (Usage)



```

Dim instance As ISwHtmlInterface
Dim value As System.Integer

```

```
value = instance.GetCurrentTODIndex()
```

C#

```
System.int GetCurrentTODIndex()
```

C++/CLI

```
System.int GetCurrentTODIndex();
```

Return Value

Index of the current Tip of the Day

Visual Basic for Applications (VBA) Syntax

See [SwHtmlInterface::GetCurrentTODIndex](#).

See Also

[ISwHtmlInterface Interface](#)
[ISwHtmlInterface Members](#)
[ISwHtmlInterface::GetPrevTipOfTheDay Method](#)

Availability

SOLIDWORKS 2013 FCS, Revision Number 21.0

SOLIDWORKS HTML Control Type Library

[Send comments on this topic.](#)

GetInterfaceBrightnessTheme Method (ISwHtmlInterface)

[See Also](#)



[SolidWorks.Interop.swhtmlcontrol Namespace](#) > [ISwHtmlInterface Interface](#) : GetInterfaceBrightnessTheme Method (ISwHtmlInterface)

Gets the background theme of SOLIDWORKS.

.NET Syntax

Visual Basic (Declaration)

```
Function GetInterfaceBrightnessTheme() As System.Integer
```

Visual Basic (Usage)



```
Dim instance As ISwHtmlInterface  
Dim value As System.Integer
```

```
value = instance.GetInterfaceBrightnessTheme()
```

C#

```
System.int GetInterfaceBrightnessTheme()
```

C++/CLI

```
System.int GetInterfaceBrightnessTheme();
```

Return Value

SOLIDWORKS background theme as defined in [swInterfaceBrightnessTheme_e](#)

Visual Basic for Applications (VBA) Syntax

See [SwHtmlInterface::GetInterfaceBrightnessTheme](#).

See Also

[ISwHtmlInterface Interface](#)
[ISwHtmlInterface Members](#)

[ISldWorks::GetInterfaceBrightnessThemeColors](#)

Availability

SOLIDWORKS 2016 SP1, Revision Number 24.1

SOLIDWORKS HTML Control Type Library

[Send comments on this topic.](#)

GetPrevTipOfTheDay Method (ISwHtmlInterface)

[See Also](#)



[SolidWorks.Interop.swhtmlcontrol Namespace](#) > [ISwHtmlInterface Interface](#) : GetPrevTipOfTheDay Method (ISwHtmlInterface)

Gets the previous Tip of the Day.

.NET Syntax

Visual Basic (Declaration)

```
Function GetPrevTipOfTheDay() As System.String
```

Visual Basic (Usage)



```
Dim instance As ISwHtmlInterface  
Dim value As System.String  
  
value = instance.GetPrevTipOfTheDay()
```

C#

```
System.string GetPrevTipOfTheDay()
```

C++/CLI

```
System.String^ GetPrevTipOfTheDay();
```

Return Value

Previous Tip of the Day string

Visual Basic for Applications (VBA) Syntax

See [SwHtmlInterface::GetPrevTipOfTheDay](#).

See Also

[ISwHtmlInterface Interface](#)

[ISwHtmlInterface Members](#)

[ISwHtmlInterface::GetCurrentTODIndex Method](#)

Availability

SOLIDWORKS 2013 FCS, Revision Number 21.0

SOLIDWORKS HTML Control Type Library

[Send comments on this topic.](#)

HideBubbleTooltip Method (ISwHtmlInterface)

[See Also](#)



[SolidWorks.Interop.swhtmlcontrol Namespace](#) > [ISwHtmlInterface Interface](#) : HideBubbleTooltip Method (ISwHtmlInterface)

Hides the Bubble ToolTip displayed by [ISwHtmlInterface::ShowBubbleTooltipAt](#).

.NET Syntax

Visual Basic (Declaration)

```
Sub HideBubbleTooltip()
```

Visual Basic (Usage)



```
Dim instance As ISwHtmlInterface
```

```
instance.HideBubbleTooltip()
```

C#

```
void HideBubbleTooltip()
```

C++/CLI

```
void HideBubbleTooltip();
```

Visual Basic for Applications (VBA) Syntax

See [SwHtmlInterface::HideBubbleTooltip](#).

Example

Visual Basic for Applications (VBA)

This example shows how to display and hide a Bubble ToolTip.

```
'-----  
'  
' Preconditions: Substitute the path and filename of your HTML file for path_filename.  
'  
' Postconditions: Contents of the HTML file are displayed in a Bubble ToolTip,  
'                  and then are hidden from view.  
'  
'-----
```

Option Explicit

Sub main()

 Const sURLpath As String = "*path_filename*"

 Dim pSldWorks As Object

 Set pSldWorks = CreateObject("SwHtmlControl.SwHtmlInterface")

 ' Show Bubble ToolTip

 pSldWorks.**ShowBubbleTooltipAt** 300, 400, swArrowLeftTop, "Sample Bubble ToolTip",
"Message of Sample Bubble ToolTip", sURLpath

 Stop

 ' Hide Bubble ToolTip

 pSldWorks.**HidebubbleTooltip**

End Sub

```
'-----
```

 See Also

[ISwHtmlInterface Interface](#)
[ISwHtmlInterface Members](#)

 Availability

SOLIDWORKS 2008 FCS, Revision Number 16.0

[Send comments on this topic.](#)

SOLIDWORKS HTML Control Type Library

IsX64 Method (ISwHtmlInterface)

[See Also](#)



[SolidWorks.Interop.swhtmlcontrol Namespace](#) > [ISwHtmlInterface Interface](#) : IsX64 Method (ISwHtmlInterface)

Gets whether you are running SOLIDWORKS (32-bit) or SOLIDWORKS x64 (64-bit).

 .NET Syntax

Visual Basic (Declaration)

```
Function IsX64() As System.Integer
```

Visual Basic (Usage)



```
Dim instance As ISwHtmlInterface  
Dim value As System.Integer  
  
value = instance.IsX64()
```

C#

```
System.int IsX64()
```

C++/CLI

```
System.int IsX64();
```

Return Value

TRUE if you are running SOLIDWORKS x64, FALSE if not

 Visual Basic for Applications (VBA) Syntax

See [SwHtmlInterface::IsX64](#).

 Remarks

If running...

Then this method returns...

SOLIDWORKS on 32-bit machine
SOLIDWORKS on a 64-bit machine
SOLIDWORKS x64 on a 64-bit machine

FALSE
FALSE
TRUE

 See Also

[ISwHtmlInterface Interface](#)
[ISwHtmlInterface Members](#)

 Availability

SOLIDWORKS 2006 SP3, Revision Number 14.3

[Send comments on this topic.](#)

SOLIDWORKS HTML Control Type Library

ShowBubbleTooltip Method (ISwHtmlInterface)

[See Also](#) [Example](#)



.NET Syntax

Visual Basic (Declaration)

```
Sub ShowBubbleTooltip( _  
    ByVal pointAt As System.Integer, _  
    ByVal flashButtonIDs As System.String, _  
    ByVal titleResID As System.Integer, _  
    ByVal titleString As System.String, _  
    ByVal messageString As System.String _  
)
```

Visual Basic (Usage)



```
Dim instance As ISwHtmlInterface  
Dim pointAt As System.Integer  
Dim flashButtonIDs As System.String  
Dim titleResID As System.Integer  
Dim titleString As System.String  
Dim messageString As System.String  
  
instance.ShowBubbleTooltip(pointAt, flashButtonIDs, titleResID, titleString, messageString)
```

C#

```
void ShowBubbleTooltip(  
    System.int pointAt,  
    System.string flashButtonIDs,  
    System.int titleResID,  
    System.string titleString,  
    System.string messageString  
)
```

C++/CLI

```
void ShowBubbleTooltip(  
& System.int pointAt,  
& System.String^ flashButtonIDs,  
& System.int titleResID,  
& System.String^ titleString,  
& System.String^ messageString  
)
```

Parameters

pointAt
Toolbar button ID to which to point

flashButtonIDs
Array of toolbar buttons

titleResID
Title resource ID of Bubble Tooltip or 0

titleString
Title of Bubble ToolTip

messageString
Message string of Bubble ToolTip

Visual Basic for Applications (VBA) Syntax

See [SwHtmlInterface::ShowBubbleTooltip](#).

Example

[Flash an Add-in's Toolbar Button \(VBA\)](#)

See Also

Availability

SOLIDWORKS 2006 SP3, Revision Number 14.3

[Send comments on this topic.](#)

SOLIDWORKS HTML Control Type Library

ShowBubbleTooltipAt Method (ISwHtmlInterface)

[See Also](#) [Example](#)



[SolidWorks.Interop.swhtmlcontrol Namespace](#) > [ISwHtmlInterface Interface](#) : ShowBubbleTooltipAt Method (ISwHtmlInterface)

Displays a Bubble ToolTip at the specified location.

.NET Syntax

Visual Basic (Declaration)

```
Sub ShowBubbleTooltipAt( _  
    ByVal pointX As System.Integer, _  
    ByVal pointY As System.Integer, _  
    ByVal arrowPos As System.Integer, _  
    ByVal titleString As System.String, _  
    ByVal messageString As System.String, _  
    ByVal urlLoc As System.String _  
)
```

Visual Basic (Usage)



```
Dim instance As ISwHtmlInterface  
Dim pointX As System.Integer  
Dim pointY As System.Integer  
Dim arrowPos As System.Integer  
Dim titleString As System.String  
Dim messageString As System.String  
Dim urlLoc As System.String  
  
instance.ShowBubbleTooltipAt(pointX, pointY, arrowPos, titleString, messageString, urlLoc)
```

C#

```
void ShowBubbleTooltipAt(  
    System.int pointX,  
    System.int pointY,  
    System.int arrowPos,  
    System.string titleString,  
    System.string messageString,  
    System.string urlLoc  
)
```

C++/CLI

```
void ShowBubbleTooltipAt(  
& System.int pointX,  
& System.int pointY,  
& System.int arrowPos,  
& System.String^ titleString,  
& System.String^ messageString,  
& System.String^ urlLoc  
)
```

Parameters

pointX
x coordinate in pixels relative to upper-left corner of screen

pointY
y coordinate in pixels relative to upper-left corner of screen

arrowPos
Arrow position as defined in [swArrowPosition e](#)

titleString
Title of Bubble ToolTip

messageString
Message string of Bubble ToolTip

urlLoc
Any valid Windows Internet Explorer file

See [SwHtmlInterface::ShowBubbleToolTipAt](#).

Example

Visual Basic for Applications (VBA)

This example shows how to display and hide a Bubble ToolTip.

```

'-----
'
' Preconditions: Substitute the path and filename of your HTML file for
"path_filename".
'
' Postconditions: Contents of the HTML file are displayed in a Bubble ToolTip,
'                  and then are hidden from view.
'
'-----
Option Explicit

Sub main()
    Const sURLpath As String = "path_filename"
    Dim pSldWorks As Object

    Set pSldWorks = CreateObject("SwHtmlControl.SwHtmlInterface")

    ' Show Bubble ToolTip
    pSldWorks.ShowBubbleToolTipAt 300, 400, swArrowLeftTop, "Sample Bubble ToolTip",
    "Message of Sample Bubble ToolTip", sURLpath

    Stop

    ' Hide Bubble ToolTip
    pSldWorks.HidebubbleToolTip

End Sub
'-----

```

Example

[Show Bubble ToolTip \(VBA\)](#)

Remarks

Remarks

If you specified a ...	Then the ToolTip's bubble...
gif, .jpg, or .jpeg image for urlLoc	Is automatically expanded to accommodate the image

URL for urlLoc

Cannot be resized and shows only the URL

See Also

[ISwHtmlInterface Interface](#)
[ISwHtmlInterface Members](#)
[ISwHtmlInterface::ShowTooltip Method](#)

Availability

SOLIDWORKS 2005 FCS, Revision Number 13.0

[Send comments on this topic.](#)

SOLIDWORKS HTML Control Type Library

ShowBubbleTooltipForAddinToolbar Method (ISwHtmlInterface)

[See Also](#)



[SolidWorks.Interop.swhtmlcontrol Namespace](#) > [ISwHtmlInterface Interface](#) : ShowBubbleTooltipForAddinToolbar Method (ISwHtmlInterface)

Displays a Bubble Tooltip for the specified add-in and flashes the specified toolbar button.

.NET Syntax

Visual Basic (Declaration)

```
Sub ShowBubbleTooltipForAddinToolbar( _  
    ByVal addInCLSID As System.String, _  
    ByVal pointAt\_UserID As System.Integer, _  
    ByVal flashButton\_UserIDs As System.String, _  
    ByVal titleResID As System.Integer, _  
    ByVal titleString As System.String, _  
    ByVal messageString As System.String _  
)
```

Visual Basic (Usage)



```
Dim instance As ISwHtmlInterface  
Dim addInCLSID As System.String  
Dim pointAt_UserID As System.Integer  
Dim flashButton_UserIDs As System.String  
Dim titleResID As System.Integer  
Dim titleString As System.String  
Dim messageString As System.String  
  
instance.ShowBubbleTooltipForAddinToolbar(addInCLSID, pointAt_UserID, flashButton_UserIDs,  
titleResID, titleString, messageString)
```

C#

```
void ShowBubbleTooltipForAddinToolbar(  
    System.string addInCLSID,  
    System.int pointAt\_UserID,  
    System.string flashButton\_UserIDs,  
    System.int titleResID,  
    System.string titleString,  
    System.string messageString  
)
```

C++/CLI

```
void ShowBubbleTooltipForAddinToolbar(  
& System.String^ addInCLSID,  
& System.int pointAt\_UserID,  
& System.String^ flashButton\_UserIDs,  
& System.int titleResID,  
& System.String^ titleString,  
& System.String^ messageString  
)
```

Parameters

addinCLSID
Add-in's class ID
pointAt_UserID
Toolbar button ID to which to point
flashButton_UserIDs
Array of toolbar buttons
titleResID
Title resource ID of Bubble Tooltip or 0
titleString
Title of Bubble ToolTip
messageString
Message string of Bubble ToolTip

 Visual Basic for Applications (VBA) Syntax

See [ISwHtmlInterface::ShowBubbleTooltipForAddinToolbar](#).

 See Also

[ISwHtmlInterface Interface](#)
[ISwHtmlInterface Members](#)
[ISldWorks::ShowBubbleTooltip](#)
[ISwHtmlInterface::GetCommandID Method](#)
[ISwHtmlInterface::ShowBubbleTooltip Method](#)

 Availability

SOLIDWORKS 2007 FCS, Revision Number 15.0

SOLIDWORKS HTML Control Type Library

[Send comments on this topic.](#)

ShowHomeIconMarker Method (ISwHtmlInterface)

[See Also](#)



[SolidWorks.Interop.swhtmlcontrol Namespace](#) > [ISwHtmlInterface Interface](#) : ShowHomeIconMarker Method (ISwHtmlInterface)

Displays a home icon.

 .NET Syntax

Visual Basic (Declaration)

Function ShowHomeIconMarker() As System.Integer

Visual Basic (Usage)

 Copy Code

Dim instance As [ISwHtmlInterface](#)
Dim value As System.Integer

value = instance.ShowHomeIconMarker()

C#

System.int ShowHomeIconMarker()

C++/CLI

System.int ShowHomeIconMarker();

Return Value
0 if successful, 1 if not

 Visual Basic for Applications (VBA) Syntax

See [ISwHtmlInterface::ShowHomeIconMarker](#).

 See Also

[ISwHtmlInterface Interface](#)
[ISwHtmlInterface Members](#)

 Availability



Shows the Bubble ToolTip and flashes the specified toolbar or toolbar buttons.

.NET Syntax

Visual Basic (Declaration)

```
Sub ShowTooltip( _
    ByVal ToolbarName As System.String, _
    ByVal buttonIndex As System.Integer, _
    ByVal mask1 As System.Integer, _
    ByVal mask2 As System.Integer, _
    ByVal titleString As System.String, _
    ByVal messageString As System.String _
)
```

Visual Basic (Usage)



```
Dim instance As ISwHtmlInterface
Dim ToolbarName As System.String
Dim buttonIndex As System.Integer
Dim mask1 As System.Integer
Dim mask2 As System.Integer
Dim titleString As System.String
Dim messageString As System.String

instance.ShowTooltip(ToolbarName, buttonIndex, mask1, mask2, titleString, messageString)
```

C#

```
void ShowTooltip(
    System.string ToolbarName,
    System.int buttonIndex,
    System.int mask1,
    System.int mask2,
    System.string titleString,
    System.string messageString
)
```

C++/CLI

```
void ShowTooltip(
    & System.String^ ToolbarName,
    & System.int buttonIndex,
    & System.int mask1,
    & System.int mask2,
    & System.String^ titleString,
    & System.String^ messageString
)
```

Parameters

ToolbarName

Name of toolbar

buttonIndex

0-based index indicating a toolbar button

mask1

0-31 bitmask indicating the toolbar buttons to flash

mask2

32-63 bitmask indicating the toolbar buttons to flash

titleString

Title of Bubble ToolTip

messageString

Message of Bubble ToolTip

Visual Basic for Applications (VBA) Syntax

See [SwHtmlInterface::ShowTooltip](#).

See Also

[ISwHtmlInterface Interface](#)
[ISwHtmlInterface Members](#)

Availability

SOLIDWORKS 2005 FCS, Revision Number 13.0

SolidWorks.Interop.swhtmlcontrol (Namespace Overview)

SOLIDWORKS HTML Control Type Library

SolidWorks.Interop.swhtmlcontrol Namespace
[See Also](#) [Inheritance Hierarchy](#)

[Send comments on this topic.](#)



SOLIDWORKS API for an add-in's Quick Tips, associated Bubble ToolTips, and CommandManager toolbar button's resource IDs

Interfaces

Interface	Description
ISwHtmlInterface	Must be implemented in each add-in's Quick Tips HTML page so that users can interact with the add-in's Quick Tips and see associated Bubble ToolTips.

See Also

[SolidWorks.Interop.swhtmlcontrol Assembly](#)