FINAL PROJECT PROPOSAL

DAMG 7245 — Big Data and Intelligent Analytics

CurateAI

Real-Time Content Intelligence Engine for Personalized Newsletters & Enterprise SEO Strategy

Team Members

Aakash Belide
Abhinav Kumar Piyush
Rahul Bothra

Attestation

WE ATTEST THAT WE HAVEN'T USED ANY OTHER STUDENTS' WORK IN OUR ASSIGNMENT AND ABIDE BY THE POLICIES LISTED IN THE STUDENT HANDBOOK.

Aakash Belide: 33.3% | Abhinav Kumar Piyush: 33.3% | Rahul Bothra: 33.3%

Table of Contents

Table of Contents 2
1. Title 4
2. Introduction 4
  2.1 Background 4
  2.2 Objective 4
3. Project Overview 5
  3.1 Scope 5
    In-Scope 5
    Out-of-Scope 5
  3.2 Stakeholders / End Users 5
4. Problem Statement 6
  4.1 Current Challenges 6
  4.2 Opportunities 6
5. Methodology 7
  5.1 Data Sources 7
    RSS Feeds (30+ Sources) 7
    Social & Community Signals 7
    Full-Text Article Content 7
    Justification of Scale 7
  5.2 Technology Stack 8
    Tool Selection Rationale 8
  5.3 Architecture 9
    Architecture Diagram 9
    Prototype-Validated Metrics 9
  5.4 Data Processing & Transformation 14
  5.5 LLM Integration Strategy 14
    B2B SEO Intelligence Agents 14
  5.6 Guardrails & Human-in-the-Loop (HITL) 14
  5.7 Evaluations & Testing 16
  5.8 Proof of Concept (POC) 16
6. Project Plan & Timeline 17
  6.1 Milestones 17
    Week 1 — Data Foundation & Pipeline Infrastructure 17
    Week 2 — LLM Agents, Backend & Frontend 17

Week 3 — Integration, Testing & Deployment 17
6.2 Timeline 17
7. Team Roles & Responsibilities 19
Project Management 19
8. Risks & Mitigation 20
8.1 Potential Risks 20
9. Expected Outcomes & Metrics 21
9.1 KPIs 21
9.2 Expected Benefits 21
10. Token & Cost Report 22
Optimization Strategies 22
Projected Monthly Cost 22
11. Conclusion 23
12. References 24
Data Sources 24
Frameworks & Libraries 24
Research 24
Appendix 25
A. Prototype Validation Data 25
B. Architecture Decision: TF-IDF vs Semantic Vectors 25
C. Source Reliability Matrix 25
D. Mermaid Diagrams 25
E. Pseudocode & Code Snippets 26
E.1 RSS Feed Ingestion (rss_prototype.py) 26
E.2 Full-Text Extraction (article_extraction_prototype.py) 26
E.3 Semantic Vector Deduplication (pipeline_prototype.py) 26
E.4 Hybrid Topic Classification (classification_prototype.py) 26
E.5 Trend Detection (trend_detection_prototype.py) 26
E.6 Dual-Layer Personalization (personalization_prototype.py) 27
E.7 Editor Agent / Guardrails (editor_agent_prototype.py) 27
E.8 Persona-First Summary Cache (summarization_prototype.py) 27
F. Prototype File Manifest 28

1. Title

CurateAI — Real-Time Content Intelligence Engine for Personalized Newsletters & Enterprise SEO Strategy

2. Introduction

2.1 Background

The newsletter economy has exploded — platforms like Substack, Beehiiv, and ConvertKit host hundreds of thousands of creators, and email marketing delivers $36–$42 return per dollar spent. Yet the production bottleneck has never been distribution; it has always been the curation and writing workflow. Newsletter creators typically spend 5–10 hours per issue scanning dozens of websites, reading articles, deciding what matters, and synthesizing insights.

The core challenge is twofold. On the creator side, relevant content is fragmented across RSS feeds, social platforms like Reddit and Hacker News, research repositories like ArXiv, and mainstream tech publications — each with different formats, update cadences, and signal-to-noise ratios. On the reader side, newsletters are one-size-fits-all. A machine learning researcher and a venture capitalist both subscribing to the same AI newsletter receive identical content, even though their interests diverge significantly.

Existing AI newsletter tools (Newsblocks, Jenova, ProCurator) address only the writing step — they take a topic and generate text. None of them build a continuously updated data pipeline that ingests thousands of articles daily, detects cross-source trends, performs semantic deduplication, and generates personalized newsletters grounded in retrieved evidence with full source traceability.

2.2 Objective

The objective of this project is to build CurateAI, a cloud-native content intelligence platform that continuously ingests content from 30+ sources, applies semantic deduplication and trend detection at scale, and uses a multi-agent LLM system to generate personalized, citation-backed newsletters.

We aim to deliver across four key areas:

- **Big Data Engineering:** End-to-end ingestion of 3,000+ articles daily from RSS feeds, Reddit, Hacker News, and NewsAPI. Semantic vector-based deduplication using Sentence-Transformers. All data stored in Snowflake with S3/GCS for raw storage and Qdrant for vector search.
- **Significant LLM Use:** A LangGraph multi-agent system coordinating classification, trend analysis, persona-aware summarization, editorial synthesis (Writer Agent), and guardrail enforcement (Editor Agent). RAG-powered newsletter generation with inline citations.
- **Cloud-Native Architecture:** Airflow for orchestration, Snowflake for structured data, S3/GCS for raw storage, Qdrant for vectors, Docker Compose for containerization, and cloud deployment via GCP Cloud Run.
- **User-Facing Application:** A Next.js dashboard where users configure interest profiles, browse content intelligence feeds, review AI-generated drafts, and publish via HITL workflow. An MCP server enables Claude Desktop integration.

3. Project Overview

3.1 Scope

In-Scope

- **Data Sources:** 30+ RSS feeds (TechCrunch, The Verge, Wired, Ars Technica, VentureBeat, MIT Technology Review, IEEE Spectrum, Bloomberg, BBC Tech, NYT Tech), AI blogs (OpenAI, DeepMind, Hugging Face, NVIDIA, Microsoft Research), research feeds (ArXiv cs.AI, cs.LG), social platforms (Reddit — 5 subreddits; Hacker News), and NewsAPI.org. Validated throughput: 3,129 raw articles per cycle.
- **ETL Pipelines:** Automated multi-source ingestion via Airflow DAGs, full-text extraction with trafilatura (85%+ success rate), semantic dedup using Sentence-Transformer vectors, hybrid topic classification (keyword + LLM fallback), and batch embedding generation.
- **LLM Components:** LangGraph multi-agent system with Topic Classifier, Trend Detector, Persona-Aware Summarizer, Writer Agent, and Editor Agent. RAG over article corpus via Qdrant.
- **Cloud Infrastructure:** Snowflake, GCS, Qdrant, Airflow, FastAPI, Next.js, Docker Compose.
- **Guardrails & HITL:** Editor Agent validates citations, detects hallucinations, enforces tone consistency. Pydantic schema enforcement. Human editors review and approve drafts. Feedback loop into personalization.
- **Evaluation:** Classification accuracy, dedup precision/recall, newsletter quality (LLM-as-judge rubric), citation accuracy, cost tracking, latency.

Out-of-Scope

- Real-time push notifications, paid subscription/billing, email delivery (Mailchimp/SendGrid), podcast transcripts.

3.2 Stakeholders / End Users

- **Primary:** Newsletter creators automating research/curation. Professionals wanting personalized daily briefings.
- **Secondary:** Content teams at tech companies. Research teams tracking emerging trends.

4. Problem Statement

4.1 Current Challenges

- **Content Fragmentation:** Information scattered across 30+ sources with different formats and update frequencies. No unified aggregation system.
- **Manual Curation Burden:** Creators spend 5–10 hours per issue. 62% of content creators report burnout.
- **Duplicate Coverage:** Same story covered by multiple outlets. Without semantic dedup, feeds are 20–30% redundant. Our prototype validated: TF-IDF caught 119 duplicates while Sentence-Transformers caught 206 (73% improvement).
- **No Personalization:** Existing newsletters deliver identical content regardless of reader role or expertise.
- **LLM Cost at Scale:** Per-user newsletter generation creates O(users × articles) LLM calls — financially unsustainable.
- **Trend Blindness:** A single LLM prompt cannot compute cross-source trend signals. Detecting topic velocity requires continuous data ingestion and historical comparison.

4.2 Opportunities

CurateAI introduces a unified semantically deduplicated pipeline processing 3,000+ articles daily; automated cross-source trend detection; dual-layer personalization (Highlights + Niche Gems); persona-first caching reducing LLM costs by 98%; and a polished HITL workflow with feedback loops.

5. Methodology

5.1 Data Sources

All data sources have been validated through prototyping. No sources require scraping — all use official APIs or open feed protocols.

RSS Feeds (30+ Sources)

Validated sources include TechCrunch, The Verge, Ars Technica, WIRED, VentureBeat, MIT News AI, Google AI Blog, OpenAI Blog, Google DeepMind, Hugging Face Blog, MIT Technology Review, IEEE Spectrum, ArXiv cs.AI, ArXiv cs.LG, BBC Technology, AWS ML Blog, HackerNoon AI, Bloomberg Technology, NYT Technology, NVIDIA Technical Blog, and Microsoft Research Blog.

Validated Volume: 2,880 articles per ingestion cycle from RSS alone.

Validated Latency: Average feed fetch time 0.16–1.26 seconds per feed.

Social & Community Signals

Reddit API (5 subreddits): r/MachineLearning (26% retention), r/artificial (36%), r/technology (100%), r/LocalLLaMA (100%), r/programming (38%). Hacker News API: 99% success rate, average score 211, average 107 comments per story.

Combined Volume: 3,129 raw articles per ingestion cycle.

Full-Text Article Content

Extraction Tool: trafilatura (on-demand for top-ranked articles).

Success Rate: 85% across all sources (18/22 at 100%; Bloomberg, NYT, OpenAI, VentureBeat blocked with graceful RSS fallback).

Latency: Average <0.4 seconds per article.

Justification of Scale

3,129 articles per cycle running daily produces ~90,000 raw articles per month. After dedup, ~25,000–30,000 unique articles flow into Snowflake monthly. Over a semester, this grows to 100,000+ indexed articles — a genuinely large-scale corpus requiring efficient infrastructure.

5.2 Technology Stack

Layer	Technology	Justification
Cloud	GCP / AWS	Free student credits, Cloud Run for deployment
Storage (Structured)	Snowflake	Columnar analytics, VARIANT type for article metadata
Storage (Raw)	S3 / GCS	Raw article snapshots, RSS dumps, pipeline artifacts
Vector Store	Qdrant	Qdrant: open-source, self-hosted, HNSW indexing, handles 100K+ vectors
Embeddings (Dedup)	Sentence-Transformers	Local inference, zero API cost, ~2.5s for 1K titles
Embeddings (RAG)	OpenAI text-embedding-3-small	Higher quality for retrieval, $0.02/1M tokens
LLM Providers	GPT-4o + GPT-4o-mini + Claude	Via LiteLLM router with daily budget cap
Agent Framework	LangGraph (StateGraph)	Deterministic routing, typed state, HITL interrupt
Orchestration	Apache Airflow	DAG scheduling, TaskFlow API, dynamic task mapping
API	FastAPI	High-performance async Python with Pydantic
Frontend	Next.js 15 + Tailwind CSS	Dashboard, editor, HITL workflow, trend viz
MCP	MCP SDK (SSE transport)	Claude Desktop integration
Observability	Prometheus	Agent calls, API latency, token usage counters
Deployment	Docker Compose + Cloud Run	Multi-container stack with Nginx proxy

Tool Selection Rationale

- **Qdrant vs Pinecone vs ChromaDB:** Qdrant offers the best balance — open-source, self-hosted in Docker, supports dense and sparse vectors, native filtering, and handles 100K+ docs with HNSW. Pinecone is a managed fallback. ChromaDB lacks filtering for our dual-layer personalization.
- **LangGraph vs Autogen vs CrewAI:** LangGraph provides explicit StateGraph control with typed state and conditional edges — essential for Fast/Polished mode branching. Autogen's GroupChat is more rigid. CrewAI abstracts too much control.
- **Sentence-Transformers vs OpenAI for Dedup:** Dedup runs on 3,000+ articles daily. Local Sentence-Transformers has zero cost and lower latency. OpenAI embeddings reserved for RAG where quality matters more.

5.3 Architecture

The platform follows a four-layer architecture: Ingestion Layer → Intelligence Layer → Generation Layer → Presentation Layer. Complete system architecture and data flow diagrams are provided as Mermaid diagrams in the appendix and GitHub repository.

Architecture Diagram



Prototype-Validated Metrics

The following infographics are generated from our prototype benchmark data:

Figure 1 — Data Ingestion Funnel: 3,129 raw articles reduced through validation, URL dedup, and semantic vector dedup.



Figure 2 — Deduplication Comparison: Sentence-Transformers catch 73% more semantic duplicates than TF-IDF.



Figure 3 — Full-Text Extraction Success Rate: 82% of sources extract at 100%. Four paywalled sources fail gracefully.



Figure 4 — Article Volume by RSS Feed Source: Distribution across 25+ sources.



Figure 5 — Extraction Latency: Majority of sources under the 0.4s target threshold.



Figure 6 — Social Platform Metrics: Post quality retention and community engagement signals.



Figure 7 — LLM Cost Scaling: Persona-first caching achieves 98% cost savings vs per-user generation at 10K users.



Figure 8 — Dual-Layer Personalization: Only 20% overlap in Niche Gems between Researcher and Investor profiles.



5.4 Data Processing & Transformation

Batch Processing: Three Airflow DAGs run daily: content_ingestion (fetch, normalize, dedup), content_classification (keyword + LLM tagging), trend_computation (cluster analysis, scoring, tag assignment).

Data Formats: Raw: XML (RSS), JSON (Reddit/HN APIs), HTML (full-text). All normalized to common JSON schema. Stored as structured rows in Snowflake.

Parallel Processing: Airflow dynamic task mapping for per-source parallel ingestion. Embedding generation batched at 100–500 articles. Persona summarization parallelized via asyncio.gather.

Dual Embedding Strategy: Sentence-Transformers (all-MiniLM-L6-v2) locally for dedup (zero cost, 2.5s/1K titles). OpenAI text-embedding-3-small for RAG vector store (higher quality, $0.02/1M tokens).

5.5 LLM Integration Strategy

LLMs are used at four distinct points in the pipeline:

- **Topic Classification (Fallback):** GPT-4o-mini classifies the 30% of articles where keyword matching is ambiguous. Cost: ~$0.003/day.
- **Persona-Aware Summarization:** One summary per article per archetype, cached in Snowflake. Scales with archetypes (5–7), not users. This is the core cost optimization.
- **Writer Agent (Polished Mode):** Takes pre-cached summaries and produces editorial synthesis — thematic intro, transitions, closing. Lightweight: ~300–400 tokens output, ~$0.02/newsletter.
- **Editor Agent (Guardrails):** Reviews Writer output against sources. Returns structured JSON with issues, citation checks, and optional revised draft. ~$0.02/newsletter.

Total LLM Cost per Newsletter: $0.07–$0.11 (Polished Mode) or ~$0.01 (Fast Mode).

B2B SEO Intelligence Agents

- **SEO Opportunity Agent:** Matches trending topics against company authority vectors using cosine similarity. Applies a 4-signal scoring algorithm: Relevance (40%), Velocity/Blue Ocean (30%), Competition Gap (30%). Returns urgency tiers: HIDDEN GEM (≥85), ACT NOW (≥70), MONITOR (≥50), SKIP. Cost: $0 (pure mathematical scoring).
- **Content Brief Generator Agent:** Takes high-opportunity topic-company matches and generates structured SEO briefs via RAG + GPT-4o-mini with Pydantic ContentBrief output: strategic angle, 3 titles, article structure, 8–10 keywords, community questions, internal linking strategy. Cost: ~$0.05–0.10 per brief.
- **SpaCy NER Velocity Engine:** Dynamic entity discovery using SpaCy en_core_web_sm (ORG, PRODUCT, WORK_OF_ART). Temporal window splitting computes velocity surge %. Entities with 3+ sources and >50% surge flagged as SURGING. Zero LLM cost.

5.6 Guardrails & Human-in-the-Loop (HITL)

- **Input Moderation:** User profiles validated via Pydantic schemas. Profanity and adversarial inputs filtered.

- **Output Validation:** All agent outputs conform to Pydantic V2 models. Editor Agent enforces: no claims without citations, no invented statistics, tone consistency, citation integrity.
- **Safety Layers:** Writer prompt hard rules: “Never invent facts not in the provided articles.” Editor Agent independently verifies compliance.
- **HITL Loop:** Human editors receive drafts in the Next.js editor. They can approve, edit sections, swap articles, or reject with feedback. Feedback stored in Snowflake and used to refine personalization weights.

5.7 Evaluations & Testing

- **Classification Accuracy:** Golden set of 100 labeled articles. Target: 80%+ keyword-only, 90%+ hybrid.
- **Dedup Precision/Recall:** Manual review of 50 clusters. Prototype: vectors caught 73% more duplicates than TF-IDF.
- **Newsletter Quality:** LLM-as-judge rubric on synthesis quality, citation accuracy, factual grounding, readability. Scored 1–5.
- **Editor Reliability:** Tested with corrupted inputs (injected hallucinations, broken citations). Target: 100% high-severity catch rate.
- **Unit Tests:** ETL pipeline, API endpoints, agent wrappers, personalization scoring.
- **Integration Tests:** Full pipeline: ingestion → dedup → classification → trends → personalization → generation → editor.
- **CI Pipeline:** GitHub Actions on every commit: lint (ruff), schema validation, unit tests, container builds.

5.8 Proof of Concept (POC)

All 11 prototypes have been completed and validated:

Prototype	Result	Key Metric
1–3: Data Ingestion	3,129 articles from 30+ feeds + Reddit + HN	Feed latency: 0.16–1.26s
4–5: Semantic Dedup	Vector clustering: 20.6% reduction on 1K sample	73% more dupes vs TF-IDF
6: Classification	Hybrid keyword + LLM strategy	70% free, 30% via GPT-4o-mini
7: Trend Detection	BREAKING/TRENDING/PICK tags assigned	Matches real-world trends
8: Personalization	Dual-layer Highlights + Gems	20% overlap between personas
9–10: Generation	Persona-first cached summaries	2 distinct newsletters generated
11: End-to-End	Full pipeline: ingest → 2 newsletters	Total cost: <$0.50
S1–S2: SEO Authority	3 companies vectorized + deep corpus matching	<40% overlap in top-5 per company
S3: Opportunity Scoring	4-signal Blue Ocean algorithm validated	HIDDEN GEM / ACT NOW tiers working
S4: Content Briefs	Pydantic ContentBrief via GPT-4o-mini	3 distinct angles for same topic
S5: Keyword Velocity	SpaCy NER dynamic entity discovery	Top surging entities match real trends
S6: SEO Dashboard	Unified B2C + B2B master pipeline	Single execution, dual output streams

6. Project Plan & Timeline

6.1 Milestones

Week 1 — Data Foundation & Pipeline Infrastructure

1. **M1 (Days 1–3):** Snowflake schema creation, S3/GCS setup, data migration from prototype, seed initial corpus.
2. **M2 (Days 4–7):** Airflow DAGs for ingestion, dedup, classification, and trend computation. Validate full daily pipeline.

Week 2 — LLM Agents, Backend & Frontend

3. **M3 (Days 8–11):** LangGraph StateGraph with 7 agents. RAG pipeline. Persona-first caching. Fast/Polished branching. MCP server.
4. **M4 (Days 12–14):** FastAPI endpoints. Next.js frontend (dashboard, editor, HITL, trends, profiles).

Week 3 — Integration, Testing & Deployment

5. **M5 (Days 15–17):** Frontend-backend integration. Unit + integration tests. Golden-set evaluation. Editor reliability testing.
6. **M6 (Days 18–19):** Docker Compose. Prometheus observability. Cloud deployment. Secrets configuration.
7. **M7 (Days 20–21):** Prompt refinement. Architecture diagrams. Codelab documentation. Video recording. Final demo.

6.2 Timeline

Week	Dates	Mon	Tue	Wed	Thu	Fri	Sat-Sun
1	Apr 4–10	Snowflake setup	S3/GCS config	Data migration	Airflow ingest	Airflow dedup	Classify + Trend
2	Apr 11–17	LangGraph agents	RAG pipeline	Writer+Editor	FastAPI backend	Next.js dashboard	Frontend HITL+Trends
3	Apr 18–24	Integration tests	Unit tests+eval	Docker+deploy	MCP+Observability	Docs+Codelab	Video + Final Demo

Figure 9 — Gantt Chart: Visual representation of the 3-week project timeline with milestone dependencies.


CurateAI — 3-Week Project Gantt Chart (April 4–24, 2026)
WEEK 1
Data Foundation
WEEK 2
Agents + UI
WEEK 3
Test + Deploy
DEADLINE
Apr 24
M1: Snowflake + S3/GCS Setup
M2: Airflow Pipelines (Ingest/Dedup/Classify)
M3: LangGraph Agents + RAG Pipeline
M4: FastAPI Backend
M5: Next.js Frontend + HITL
M6: MCP Server + Observability
M7: Testing & Evaluations
M8: Docker + Cloud Deployment
M9: Documentation + Demo Prep
3d
4d
4d
3d
5d
2d
3d
3d
3d
Apr 05
Apr 07
Apr 09
Apr 11
Apr 13
Apr 15
Apr 17
Apr 19
Apr 21
Apr 23
Apr 25
Date

7. Team Roles & Responsibilities

Team Member	Role	Key Responsibilities
Aakash Belide	ETL, Data Pipeline & Frontend Lead	S3 / GCS storage, Sentence-Transformer dedup, embedding batch jobs, Airflow DAGs, Qdrant index, evaluation datasets, golden-set evaluation, Next.js 15 frontend
Abhinav Kumar Piyush	LLM Engineer & Agent Lead	LangGraph StateGraph (agents), persona-first caching, Fast/Polished branching, MCP server, Prometheus, prompts, guardrails, Pydantic schemas
Rahul Bothra	Backend & Cloud Lead	Snowflake schema, RAG pipeline, FastAPI endpoints, Docker Compose, Nginx, cloud deployment, integration testing, demo prep

Project Management

All task tracking is managed via GitHub Projects Kanban Board with columns: Backlog → In Progress → In Review → Done. Each milestone is broken into GitHub Issues with labels for priority (P0/P1/P2), component (pipeline/agents/frontend/infra), and sprint week (W1/W2/W3).

8. Risks & Mitigation

8.1 Potential Risks

Risk	Likelihood	Impact	Mitigation Strategy
RSS feed structure changes	Low	Low	Graceful degradation — pipeline continues with remaining sources, logs alert
API rate limits (Reddit, HN)	Low	Low	Conservative usage well within free tier limits
Full-text extraction blocked	Medium	Low	Fallback to RSS summary (validated: 4 sources blocked, all fall back cleanly)
LLM hallucinations	Medium	High	Editor Agent guardrails + Pydantic schemas + hard rules in Writer prompt
High API cost / runaway spend	Low	High	Daily budget cap via LiteLLM router; limit archetypes to 5–7
Pipeline slowdown at scale	Low	Medium	Airflow parallelism + Snowflake handles 100K+ articles efficiently
Frontend timeline overrun	Medium	Medium	Fallback: deploy core features first, defer trend charts to stretch goal

9. Expected Outcomes & Metrics

9.1 KPIs

Metric	Target	Measurement Method
Daily article throughput	3,000+ raw, 800+ unique	Airflow pipeline logs
Dedup improvement over TF-IDF	≥70% more duplicates caught	Benchmark on labeled set
Classification accuracy (keyword)	≥80%	Golden set of 100 articles
Classification accuracy (hybrid)	≥90%	Golden set of 100 articles
Newsletter quality score	≥4.0 / 5.0	LLM-as-judge rubric
Citation accuracy	≥95%	Automated citation validation
Editor catch rate (high-severity)	100%	Corrupted-input test suite
Per-newsletter cost (Polished)	≤$0.15	Token tracking per generation
Cost reduction vs naive	≥95%	Persona-cache vs direct comparison
Company topic match differentiation	<40% overlap in top-5	Cross-company recommendation comparison
Content brief company-specificity	3 distinct angles/same topic	Side-by-side brief comparison
SpaCy NER entity precision	Top 3 surging verifiable	Cross-check with HN front page
Content brief cost	≤$0.10 per brief	Token tracking per generation

9.2 Expected Benefits

- **Technical:** Production-grade content intelligence pipeline with semantic NLP, multi-agent LLM orchestration, and novel persona-first caching architecture. Reusable for any domain by swapping feeds and taxonomy.
- **Practical:** Reduces newsletter creation from 5–10 hours to under 15 minutes. Delivers personalized content discovery. Provides cross-source trend intelligence no single LLM prompt can produce.

10. Token & Cost Report

Token Measurement: Every LLM call logged with prompt tokens, completion tokens, model, agent name, and archetype. Aggregated in Snowflake for reporting.

Main Cost Drivers: Persona-aware summarization (~60%), Writer Agent (~20%), Editor Agent (~15%), Classification fallback (~5%).

Optimization Strategies

- **Persona-First Caching:** One summary per article per archetype. For 5 archetypes and 30 articles/day = 150 cached summaries regardless of user count. Validated: 98% cost reduction at 10K users.
- **Hybrid Classification:** 70% keyword-based (free), 30% GPT-4o-mini (~$0.003/day total).
- **LiteLLM Budget Cap:** Hard daily spend limit prevents runaway costs.
- **Fast Mode:** Template assembly skips Writer + Editor, reducing cost to ~$0.01/newsletter.

Projected Monthly Cost

Component	Daily Cost	Monthly Cost
Summarization (5 archetypes × 30 articles)	~$0.30	~$9.00
Writer Agent (10 newsletters/day)	~$0.15	~$4.50
Editor Agent (10 newsletters/day)	~$0.20	~$6.00
Classification fallback	~$0.003	~$0.09
Embeddings (text-embedding-3-small)	~$0.02	~$0.60
TOTAL	~$0.67	~$20.19
--- B2B SEO Layer ---		
Content Brief Generation (5/day)	~$0.50	~$15.00
SpaCy NER + Velocity (local)	$0.00	$0.00
SEO Opportunity Scoring (local)	$0.00	$0.00
COMBINED TOTAL (B2C + B2B)	~$1.17	~$35.19

11. Conclusion

CurateAI addresses a genuine, widespread problem — the unsustainable manual effort required to create quality newsletters — with a solution deeply rooted in data engineering, not just LLM prompting. The platform's core value is its intelligence pipeline: continuous multi-source ingestion of 3,000+ articles daily, semantic vector deduplication catching 73% more duplicates than keyword methods, cross-source trend detection identifying breaking stories before they peak, and dual-layer personalization delivering both universal must-know content and niche discovery.

The persona-first caching architecture solves the critical scalability challenge, reducing costs by 98% while maintaining personalization quality. The hybrid Fast/Polished mode gives users control over the cost-quality tradeoff. Every architectural decision has been empirically validated through 11 prototypes, with data covering ingestion throughput (3,129 articles), dedup effectiveness (20.6% reduction), extraction reliability (85% success), personalization differentiation (20% overlap), and end-to-end cost (<$0.50 for 2 newsletters).

12. References

Data Sources

- RSS/Atom Protocol Specification — https://www.rssboard.org/rss-specification
- Reddit API — https://www.reddit.com/dev/api
- Hacker News API — https://github.com/HackerNews/API
- NewsAPI.org — https://newsapi.org/docs
- ArXiv API — https://arxiv.org/help/api
- OpenAlex API — https://docs.openalex.org

Frameworks & Libraries

- LangGraph — https://langchain-ai.github.io/langgraph/
- Apache Airflow — https://airflow.apache.org/
- FastAPI — https://fastapi.tiangolo.com/
- Next.js — https://nextjs.org/
- Qdrant — https://qdrant.tech/documentation/
- Sentence-Transformers — https://www.sbert.net/
- LiteLLM — https://docs.litellm.ai/
- trafilatura — https://trafilatura.readthedocs.io/
- Pydantic V2 — https://docs.pydantic.dev/
- MCP SDK — https://modelcontextprotocol.io/

Research

- Sentence-BERT — Reimers & Gurevych, 2019 (arxiv.org/abs/1908.10084)
- Reciprocal Rank Fusion — Cormack et al., 2009
- RAG Patterns — OpenAI Cookbook, LangChain Documentation

Appendix

A. Prototype Validation Data

All prototype data and benchmark reports are available in the GitHub repository under /prototyping/reports/:

- feed_analysis_report.csv — Per-source RSS feed analysis
- extraction_report.csv — Per-article extraction results
- extraction_source_report.csv — Per-source success rates
- social_source_report.csv — Reddit and HN API validation
- dedup_funnel_metrics.csv — Dedup pipeline funnel
- vector_funnel_metrics.csv — Vector dedup performance
- ingestion_funnel_report.md — Complete funnel analysis

B. Architecture Decision: TF-IDF vs Semantic Vectors

Method	Unique Clusters (1K)	Duplicates Caught	Result
TF-IDF (Cosine > 0.65)	890	110	Missed semantic variants
Sentence-Transformers (all-MiniLM-L6-v2)	794	206	Caught 73% more duplicates

Example: “Nvidia releases new GeForce driver” and “New GeForce RTX 50 series drivers now available from Nvidia” — TF-IDF treated these as different stories; vectors correctly merged them.

C. Source Reliability Matrix

Source	Success	Avg Latency	Notes
TechCrunch	100%	0.10s	Reliable
The Verge	100%	0.13s	Reliable
ArXiv	100%	0.08s	Reliable
MIT Tech Review	100%	0.12s	Reliable
Hacker News	99%	19.9s (100 stories)	Reliable
Bloomberg	0%	0.18s	Blocked — RSS fallback
NYT	0%	0.14s	Blocked — RSS fallback
OpenAI Blog	0%	0.13s	Blocked — RSS fallback
VentureBeat	0%	20.16s	Blocked — RSS fallback

D. Mermaid Diagrams

System Architecture Diagram, Data Flow Diagram, LangGraph Agent Workflow, and Airflow DAG Structure are provided as Mermaid diagrams in the GitHub repository and render natively on GitHub.

E. Pseudocode & Code Snippets

All prototype scripts are available in the GitHub repository under /prototyping/. Below are key code excerpts demonstrating core pipeline logic.

E.1 RSS Feed Ingestion (rss_prototype.py)

Parses 29+ RSS/Atom feeds using feedparser, normalizes to a unified schema, deduplicates by URL and title, and stores as structured JSON.

```
for feed_url in RSS_FEEDS:
    feed = feedparser.parse(feed_url)
    for entry in feed.entries:
        article = normalize_entry(entry, source_name)
        if normalize_url(article.link) not in seen_urls:
            unique_articles.append(article)
```

E.2 Full-Text Extraction (article_extraction_prototype.py)

Uses trafilatura with custom User-Agent to extract clean article body text from URLs. Falls back to RSS summary if blocked.

```
config = trafilatura.settings.use_config()
config.set('DEFAULT', 'USER_AGENT', 'Mozilla/5.0 ...')
downloaded = trafilatura.fetch_url(url, config=config)
if downloaded:
    text = trafilatura.extract(downloaded, config=config)
else: fallback_to_rss_summary(article)
```

E.3 Semantic Vector Deduplication (pipeline_prototype.py)

Replaces TF-IDF with Sentence-Transformer embeddings. Clusters articles by cosine similarity > 0.70 threshold, merging sources and popularity signals.

```
model = SentenceTransformer('all-MiniLM-L6-v2')
sentences = [f"{a['title']} {a['summary']}" for a in articles]
embeddings = model.encode(sentences)
sim_matrix = cosine_similarity(embeddings)
for i in range(len(articles)):
    similar = np.where(sim_matrix[i] > 0.70)[0]
    cluster = merge_sources(articles[similar])
```

E.4 Hybrid Topic Classification (classification_prototype.py)

Keyword-first approach handles 70% of articles for free. GPT-4o-mini fallback classifies ambiguous cases with structured Pydantic output.

```
def hybrid_classify(title, summary, client):
    # Phase 1: Free keyword check
    for category, keywords in AXIOMATIC_KEYWORDS.items():
        if any(kw in text.lower() for kw in keywords):
            return TopicClassification(category, 0.9)
    # Phase 2: LLM fallback (structured output)
    return client.beta.chat.completions.parse(
        model='gpt-4o-mini', response_format=TopicClassification)
```

E.5 Trend Detection (trend_detection_prototype.py)

Assigns BREAKING/TRENDING/COMMUNITY-PICK tags based on editorial density (cluster_size), social popularity signal, and freshness.

```
def detect_trends(articles):
    for article in articles:
        if cluster_size >= 3: status = 'BREAKING'
        elif cluster_size >= 2: status = 'TRENDING'
        if popularity >= 150: status = 'COMMUNITY-PICK'
        article['ranking_score'] = cluster*10 + pop + boost
```

E.6 Dual-Layer Personalization (personalization_prototype.py)

Layer 1: Global Top 20 re-ordered by user bio vector similarity. Layer 2: Scans remaining 700+ articles to find niche gems matching user interests.

```
user_vector = model.encode([user['bio']])[0]
# Layer 1: Re-rank global highlights
for article in global_top_20:
    sim = cosine_similarity(user_vector, article_vector)
# Layer 2: Find hidden gems from remaining 700+
for article in other_articles:
    niche_score = sim + category_boost + cluster_bonus
```

E.7 Editor Agent / Guardrails (editor_agent_prototype.py)

Fact-checks Writer output against source articles using GPT-4o-mini with Pydantic structured output. Returns verdict (pass/needs_revision/reject) with detailed issue reports.

```
class EditorReport(BaseModel):
    verdict: Literal['pass','needs_revision','reject']
    issues: List[EditorIssue]  # hallucination, factual_error
    editorial_note: str

response = client.beta.chat.completions.parse(
    model='gpt-4o-mini', response_format=EditorReport)
```

E.8 Persona-First Summary Cache (summarization_prototype.py)

Generates one summary per article per persona archetype. Cache scales with archetypes (not users), achieving 98% cost reduction at scale.

```
persona_cache = {}  # {article_id: {persona: summary}}
for article in unique_articles:
    for persona_name, persona_desc in ARCHETYPES.items():
        prompt = f'Summarize for a {persona_desc}: ...'
        cache[article.id][persona_name] = llm(prompt)
# 1000 users with 5 archetypes = only 5 LLM calls/article
```

F. Prototype File Manifest

All 18 prototype scripts are available in the GitHub repository under /prototyping/:

Prototype	Script	Purpose
P1: RSS Ingestion	rss_prototype.py	Parse 29 RSS feeds, normalize schema, basic dedup
P1b: Feed Analysis	rss_pagination_analyzer.py	Deep analysis of feed freshness, pagination, WP API availability
P2: Full-Text Extraction	article_extraction_prototype.py	trafilatura extraction with per-source success rate benchmarking
P2b: Social Extraction	social_extraction_prototype.py	Extract articles from Reddit/HN external links
P3: Social APIs	reddit_hn_prototype.py	Reddit + Hacker News API ingestion with engagement metrics
P4: TF-IDF Dedup	dedup_prototype.py	URL + title similarity dedup with TF-IDF (baseline)
P4b: Vector Dedup	vector_dedup_test.py	Sentence-Transformer semantic clustering comparison
P4c: Dedup Benchmark	dedup_comparison_test.py	Head-to-head TF-IDF vs Vector benchmark with report
P5: Full Pipeline	pipeline_prototype.py	End-to-end: ingest, normalize, vector dedup, full-text extraction
P6: Classification	classification_prototype.py	Hybrid keyword + GPT-4o-mini with Pydantic structured output
P7: Trend Detection	trend_detection_prototype.py	BREAKING/TRENDING/PICK status assignment + ranking score
P8: Personalization	personalization_prototype.py	Dual-layer Highlights + Niche Gems with bio vector matching
P9: Summarization	summarization_prototype.py	Persona-first cache: one summary per archetype per article
P10: Newsletter Layout	newsletter_layout_prototype.py	Markdown newsletter assembly for 2 personas
P10b: Editor Agent	editor_agent_prototype.py	Guardrail agent with Pydantic EditorReport schema
Report: Funnel	funnel_report_generator.py	Global ingestion funnel with TF-IDF vs Vector comparison
Report: Vector Metrics	vector_metrics_generator.py	Vector dedup funnel metrics CSV generation
Report: WP API	wp_api_analyzer.py	WordPress API pagination test for TechCrunch/VentureBeat