

hw1_search_q11_lookahead_graph_search

Question 11: Lookahead Graph Search

4/4 points (ungraded)

Recall from lecture the general algorithm for Graph Search reproduced below.

```
function GRAPH-SEARCH(problem, fringe, strategy) return a solution, or failure
  closed ← an empty set
  fringe ← INSERT(MAKE-NODE(INITIAL-STATE[problem]), fringe)
  loop do
    if fringe is empty then return failure
    node ← REMOVE-FRONT(fringe, strategy)
    if GOAL-TEST(problem, STATE[node]) then return node
    if STATE[node] is not in closed then
      add STATE[node] to closed
      for child-node in EXPAND(STATE[node], problem) do
        fringe ← INSERT(child-node, fringe)
      end
    end
  end
```


Using GRAPH-SEARCH, when a node is expanded it is added to the closed set. This means that even if a node is added to the fringe multiple times it will not be expanded more than once. Consider an alternative version of GRAPH-SEARCH, LOOKAHEAD-GRAPH-SEARCH, which saves memory by using a "fringe-closed-set" keeping track of which states have been on the fringe and only adding a child node to the fringe if the state of that child node has not been added to it at some point. Concretely, we replace the highlighted block above with the highlighted block below.

```

function LOOKAHEAD-GRAPH-SEARCH(problem, fringe, strategy) return a solution, or failure
  fringe-closed ← an empty set
  fringe ← INSERT(MAKE-NODE(INITIAL-STATE[problem]), fringe)
  add INITIAL-STATE[problem] to fringe-closed
  loop do
    if fringe is empty then return failure
    node ← REMOVE-FRONT(fringe, strategy)
    if GOAL-TEST(problem, STATE[node]) then return node
    for child-node in EXPAND(node, problem) do
      if STATE[child-node] is not in fringe-closed then
        add STATE[child-node] to fringe-closed
        fringe ← INSERT(child-node, fringe)
    end
  end
end

```

Now, we've produced a more memory efficient graph search algorithm. However, in doing so, we might have affected some properties of the algorithm. To explore the possible differences, consider the example graph below.



If using LOOKAHEAD-GRAPH-SEARCH with an A* node expansion strategy, which path will this algorithm return? (We strongly encourage you to step through the execution of the algorithm on a scratch sheet of paper and keep track of the fringe and the search tree as nodes get added to the fringe.)

☐ $S \rightarrow A \rightarrow D \rightarrow G$

☒ $S \rightarrow B \rightarrow G$ ✓

☐ $S \rightarrow A \rightarrow C \rightarrow G$

☐ $S \rightarrow B \rightarrow D \rightarrow G$

☐ $S \rightarrow A \rightarrow B \rightarrow D \rightarrow G$

Submit

✓ Correct (4/4 points)

problem

4/4 points (ungraded)

Assume you run LOOKAHEAD-GRAPH-SEARCH with the A* node expansion strategy and a consistent heuristic, select all statements that are true.

☒ The EXPAND function can be called at most once for each state.

☒ The algorithm is complete.

☐ The algorithm will return an optimal solution.



Submit

✓ Correct (4/4 points)