

## 11.jetty分析

11.jetty分析 .....	1
1. new Server() .....	4
1.1. 初始化线程池 .....	4
1.1.1. QueuedThreadPool .....	4
execute()方法 .....	4
BlockingQueue .....	4
1.2. 初始化ServerConnector .....	5
1.2.1. 初始化ScheduledExecutorScheduler .....	5
1.2.2. 初始化ByteBufferPool .....	5
ArrayByteBufferPool .....	5
结构 .....	6
Bucket .....	6
_size .....	6
_queue .....	6
acquire .....	6
取得合适的Bucket .....	6
从Bucket中取得ByteBuffer .....	7
不存在则新建 .....	7
release .....	7
取得合适的Bucket .....	7
清空Buffer .....	7
归还Pool .....	7
例外处理 .....	7
1.2.3. 维护ConnectionFactory .....	8
1.2.4. 取得可用CPU数量 .....	8
1.2.5. 更新acceptor数量 .....	8
1.2.6. 创建acceptor线程组 .....	8
1.2.7. 初始化ServerConnectorManager .....	8
保存selector线程数量 .....	9
1.3. 设置port .....	9
1.4. 关联Sever和Connector .....	9
2. Server.start() .....	9
2.1. 设置启动状态 .....	9
2.2. 启动过程doStart() .....	9
2.2.1. 注册ShutdownMonitor .....	11
2.2.2. 获取化线程池 .....	11

QueuedThreadPool .....	12
2.2.3. 设置selector数量 .....	12
累计所有Connector的需求 .....	12
2.2.4. 计算所需的所有线程数量 .....	12
如果大于默认的200则中断程序 .....	12
2.2.5. 维护Bean .....	12
启动QueuedThreadPool .....	12
doStart() .....	12
startThreads() .....	12
创建线程 .....	13
_runnable .....	13
_jobs中取任务并执行 .....	13
设置线程的属性 .....	13
启动线程 .....	13
启动WebApplicationContext .....	13
2.2.6. 启动Connector .....	13
取得ConnectionFactory .....	13
创建selector线程并启动 .....	13
newSelector() .....	13
创建Acceptor线程 .....	14
Acceptor .....	14
设置线程名字 .....	14
设置优先级 .....	14
将自己放入_acceptors数组 .....	14
监听端口 .....	14
ServerConnector.accept() .....	15
没有Acceptor的情况 .....	15
2.3. 启动完毕 .....	16
3. Http请求 .....	16
3.1. Accept成功 .....	16
3.1.1. 设置为非阻塞模式 .....	17
3.1.2. 配置Socket .....	17
3.1.3. 正式处理 .....	17
选择可用的ManagedSelector线程 .....	17
ManagedSelector处理 .....	17
提交任务 .....	18
ConcurrentArrayQueue .....	18
3.2. 请求处理 .....	18
3.2.1. ManagedSelector.run() .....	18

select() .....	18
runChanges() .....	18
runChange() .....	18
Accept.run .....	19
select() .....	19
处理SelectionKey .....	19
processKey() .....	19
onSelected() .....	20

## 1. new Server()

```
public Server(@Name("port")int port)
{
    this((ThreadPool)null);
    ServerConnector connector=new ServerConnector(this);
    connector.setPort(port);
    setConnectors(new Connector[]{connector});
}
```

### 1.1. 初始化线程池

```
public Server(@Name("threadpool") ThreadPool pool)
{
    _threadPool=pool!=null?pool:new QueuedThreadPool();
    addBean(_threadPool);
    setServer(this);
}
```

#### 1.1.1. QueuedThreadPool

参见: [启动QueuedThreadPool](#)

实现了SizedThreadPool

### execute()方法

```
@Override
public void execute(Runnable job)
{
    if (!isRunning() || !_jobs.offer(job))
    {
        LOG.warn("{} rejected {}", this, job);
        throw new RejectedExecutionException(job.toString());
    }
    else
    {
        // Make sure there is at least one thread executing the job.
        if (getThreads() == 0)
            startThreads(1);
    }
}
```

### BlockingQueue

将任务推入

`BlockingQueue<Runnable> org.eclipse.jetty.util.thread.QueuedThreadPool._jobs`

## 1.2. 初始化ServerConnector

HTTP connector using NIO ByteChannels and Selectors

继承自 AbstractConnector

### 1.2.1. 初始化ScheduledExecutorScheduler

based on JDK's `{@link ScheduledThreadPoolExecutor}`.

### 1.2.2. 初始化ByteBufferPool

在数据传输过程中, 不可避免需要byte数组

buffer池

默认产生 ArrayByteBufferPool

ByteBufferPool 接口有2个方法:

```
public ByteBuffer acquire(int size, boolean direct);
```

```
public void release(ByteBuffer buffer);
```

这是一个很好的对象池范本

### ArrayByteBufferPool

```
public ArrayByteBufferPool(int minSize, int increment, int maxSize)
```

```
public ArrayByteBufferPool()
```

```
{
```

```
    this(0,1024,64*1024);
```

```
}
```

```
_direct=new Bucket[maxSize/increment];  
_indirect=new Bucket[maxSize/increment];
```

## 结构

### Bucket

\_direct Bucket数组  
\_indirect Bucket数组

为每一个大小, 新建一个Bucket  
但不初始化ByteBuffer

```
int size=0;  
for (int i=0;i<_direct.length;i++)  
{  
    size+=_inc;  
    _direct[i]=new Bucket(size);  
    _indirect[i]=new Bucket(size);  
}
```

一个Bucket存放**大小相同**的所有的ByteBuffer

\_size

bytebuffer大小

\_queue

```
public final Queue<ByteBuffer> _queue= new ConcurrentLinkedQueue<>();
```

### acquire

```
public ByteBuffer acquire(int size, boolean direct)
```

### 取得合适的Bucket

每个Bucket的大小不同, 这里找到最合适的

```
Bucket bucket = bucketFor(size,direct);
```

## 从Bucket中取得ByteBuffer

```
ByteBuffer buffer = bucket==null?null:bucket._queue.poll();
```

## 不存在则新建

```
if (buffer == null)
{
    int capacity = bucket==null?size:bucket._size;
    buffer = direct ? BufferUtil.allocateDirect(capacity) : BufferUtil.allocate(capacity);
}
```

## release

```
public void release(ByteBuffer buffer)
{
    if (buffer!=null)
    {
        Bucket bucket = bucketFor(buffer.capacity(),buffer.isDirect());
        if (bucket!=null)
        {
            BufferUtil.clear(buffer);
            bucket._queue.offer(buffer);
        }
    }
}
```

## 取得合适的Bucket

```
Bucket bucket = bucketFor(buffer.capacity(),buffer.isDirect());
```

## 清空Buffer

```
BufferUtil.clear(buffer);
```

## 归还Pool

```
bucket._queue.offer(buffer);
```

## 例外处理

如果申请的ByteBuffer过大或者过小,

无法在POOL中满足, 则可以申请成功, 但无法归还给POOL。

### 1.2.3. 维护ConnectionFactory

HttpConnectionFactory

用于创建连接,

比如Accept后, 需要创建一个表示连接的对象

### 1.2.4. 取得可用CPU数量

```
int cores = Runtime.getRuntime().availableProcessors();
```

### 1.2.5. 更新acceptor数量

```
if (acceptors < 0)
    acceptors=Math.max(1, Math.min(4,cores/8));
```

### 1.2.6. 创建acceptor线程组

参见: [创建Acceptor线程](#)

```
_acceptors = new Thread[acceptors];
```

### 1.2.7. 初始化ServerConnectorManager

继承自 SelectorManager

```
_manager = new ServerConnectorManager(getExecutor(), getSchedular(),
    selectors>0?selectors:Math.max(1,Math.min(4,Runtime.getRuntime().availableProcessors()/2)));
```



## 保存selector线程数量

```
Math.min(4,Runtime.getRuntime().availableProcessors()/2))
```

### 1.3. 设置port

```
connector.setPort(port);
```

### 1.4. 关联Sever和Connector

```
setConnectors(new Connector[] {connector});
```

## 2. Server.start()

```
org.eclipse.jetty.server.Server
```

启动web服务器

```
WebApplicationContext context = new WebApplicationContext();
```

```
context.setContextPath("");
```

```
context.setResourceBase("./web/");
```

```
context.setClassLoader(Thread.currentThread().getContextClassLoader());
```

```
server.setHandler(context);
```

```
server.start();
```

### 2.1. 设置启动状态

```
AbstractLifeCycle
```

```
private void setStarting()
```

```
{
```

```
    if (LOG.isDebugEnabled())
```

```
        LOG.debug("starting {}",this);
```

```
    _state = __STARTING;
```

```
    for (Listener listener : _listeners)
```

```
        listener.lifeCycleStarting(this);
```

```
}
```

### 2.2. 启动过程doStart()

```
Server
```

启动整个server

```
protected void doStart() throws Exception
```

```

{
    //If the Server should be stopped when the jvm exits, register
    //with the shutdown handler thread.
    if (getStopAtShutdown())
        ShutdownThread.register(this);

    //Register the Server with the handler thread for receiving
    //remote stop commands
    ShutdownMonitor.register(this);

    //Start a thread waiting to receive "stop" commands.
    ShutdownMonitor.getInstance().start(); // initialize

    LOG.info("jetty-" + getVersion());
    HttpGenerator.setJettyVersion(HttpConfiguration.SERVER_VERSION);
    MultiException mex=new MultiException();

    // check size of thread pool
    SizedThreadPool pool = getBean(SizedThreadPool.class);
    int max=pool==null?-1:pool.getMaxThreads();
    int selectors=0;
    int acceptors=0;
    if (mex.size()==0)
    {
        for (Connector connector : _connectors)
        {
            if (connector instanceof AbstractConnector)
                acceptors+=((AbstractConnector)connector).getAcceptors();

            if (connector instanceof ServerConnector)
                selectors+=((ServerConnector)connector).getSelectorManager().getSelectorCount();
        }
    }

    int needed=1+selectors+acceptors;
    if (max>0 && needed>max)
        throw new IllegalStateException(String.format("Insufficient threads: max=%d < needed(acceptors=%d + selectors=%d + request=1)",max,acceptors,selectors));

    try
    {
        super.doStart();
    }

```

```

    }
    catch(Throwable e)
    {
        mex.add(e);
    }

    // start connectors last
    for (Connector connector : _connectors)
    {
        try
        {
            connector.start();
        }
        catch(Throwable e)
        {
            mex.add(e);
        }
    }

    if (isDumpAfterStart())
        dumpStdErr();

    mex.ifExceptionThrow();

    LOG.info(String.format("Started @%dms", Uptime.getUptime()));
}

```

### 2.2.1. 注册ShutdownMonitor

远程控制接口

```

//Register the Server with the handler thread for receiving
//remote stop commands
ShutdownMonitor.register(this);

//Start a thread waiting to receive "stop" commands.
ShutdownMonitor.getInstance().start(); // initialize

```

### 2.2.2. 获取化线程池

```

// check size of thread pool
SizedThreadPool pool = getBean(SizedThreadPool.class);

```

## QueuedThreadPool

### 2.2.3. 设置selector数量

根据Connector数量进行累计

大部分情况下, 只有一个ServerConnector

```
for (Connector connector : _connectors)
{
    if (connector instanceof AbstractConnector)
        acceptors+=((AbstractConnector)connector).getAcceptors();

    if (connector instanceof ServerConnector)
        selectors+=((ServerConnector)connector).getSelectorManager().getSelectorCount();
}
```

累计所有Connector的需求

### 2.2.4. 计算所需的所有线程数量

```
int needed=1+selectors+acceptors;
```

如果大于默认的200则中断程序

```
if (max>0 && needed>max)
    throw new IllegalStateException(String.format("Insufficient threads: max=%d < needed(acceptors=%d + selectors=%d + request=1)",max,acceptors,selectors));
```

### 2.2.5. 维护Bean

启动QueuedThreadPool

参见: [QueuedThreadPool](#)

**doStart()**

**startThreads()**

建立需要的线程

## 创建线程

```
Thread thread = new Thread(_runnable);
```

## \_runnable

## \_jobs中取任务并执行

## 设置线程的属性

```
thread.setDaemon(isDaemon());  
thread.setPriority(getThreadsPriority());  
thread.setName(_name + "-" + thread.getId());  
_threads.add(thread);
```

## 启动线程

```
thread.start();
```

## 启动WebApplicationContext

如果需要使用, 在此处启动

## 2.2.6. 启动Connector

## 取得ConnectionFactory

```
_defaultConnectionFactory = getConnectionFactory(_defaultProtocol);
```

## 创建selector线程并启动

```
for (int i = 0; i < _selectors.length; i++)  
{  
    ManagedSelector selector = newSelector(i);  
    _selectors[i] = selector;  
    selector.start();  
    execute(new NonBlockingThread(selector));  
}
```

## newSelector()

参见: [ManagedSelector处理](#)

```
protected ManagedSelector newSelector(int id)
{
    return new ManagedSelector(id);
}
```

## 创建Acceptor线程

参见: [创建acceptor线程组](#)

```
_stopping=new CountDownLatch(_acceptors.length);
for (int i = 0; i < _acceptors.length; i++)
{
    Acceptor a = new Acceptor(i);
    addBean(a);
    getExecutor().execute(a);
}
```

## Acceptor

参见: [Accept成功](#)

## 设置线程名字

```
final Thread thread = Thread.currentThread();
String name=thread.getName();
_name=String.format("%s-acceptor-%d@%x-
%s",name,_acceptor,hashCode(),AbstractConnector.this.toString());
thread.setName(_name);
```

## 设置优先级

## 将自己放入\_acceptors数组

```
synchronized (AbstractConnector.this)
{
    _acceptors[_acceptor] = thread;
}
```

## 监听端口

```
try
{
    while (isAccepting())
    {
        try
        {
```

```

        accept(_acceptor);
    }
    catch (Throwable e)
    {
        if (isAccepting())
            LOG.warn(e);
        else
            LOG.ignore(e);
    }
}
finally
{
    thread.setName(name);
    if (_acceptorPriorityDelta!=0)
        thread.setPriority(priority);

    synchronized (AbstractConnector.this)
    {
        _acceptors[_acceptor] = null;
    }
    CountDownLatch stopping=_stopping;
    if (stopping!=null)
        stopping.countDown();
}

```

### ServerConnector.accept()

```

public void accept(int acceptorID) throws IOException
{
    ServerSocketChannel serverChannel = _acceptChannel;
    if (serverChannel != null && serverChannel.isOpen())
    {
        SocketChannel channel = serverChannel.accept();
        accepted(channel);
    }
}

```

在accept的地方等待

### 没有Acceptor的情况

channel默认是blocking的

如果acceptor数量为0, 没有安排线程专门进行accept, 则设置为非阻塞模式  
若是非0, 有专门线程进行accept, 因此, 为阻塞模式

```
protected void doStart() throws Exception
{
    super.doStart();

    if (getAcceptors()==0)
    {
        _acceptChannel.configureBlocking(false);
        _manager.acceptor(_acceptChannel);
    }
}
```

## 2.3. 启动完毕

AbstractLifeCycle

```
private void setStarted()
{
    _state = __STARTED;
    if (LOG.isDebugEnabled())
        LOG.debug(STARTED+" @{}ms {}",Uptime.getUptime(),this);
    for (Listener listener : _listeners)
        listener.lifeCycleStarted(this);
}
```

## 3. Http请求

### 3.1. Accept成功

参见: [Acceptor](#)

```
private void accepted(SocketChannel channel) throws IOException
{
    channel.configureBlocking(false);
    Socket socket = channel.socket();
    configure(socket);
    _manager.accept(channel);
}
```



### 3.1.1. 设置为非阻塞模式

```
channel.configureBlocking(false);
```

### 3.1.2. 配置Socket

```
Socket socket = channel.socket();  
configure(socket);
```

### 3.1.3. 正式处理

```
SelectorManager _manager;  
_manager.accept(channel);
```

## 选择可用的ManagedSelector线程

```
private ManagedSelector chooseSelector()  
{  
    // The ++ increment here is not atomic, but it does not matter,  
    // so long as the value changes sometimes, then connections will  
    // be distributed over the available selectors.  
    long s = _selectorIndex++;  
    int index = (int)(s % getSelectorCount());  
    return _selectors[index];  
}
```

## ManagedSelector处理

参见: [newSelector\(\)](#)

ManagedSelector 是一个线程

封装了Selector 的使用

## 提交任务

参见: [runChanges\(\)](#)

```
selector.submit(selector.new Accept(channel, attachment));
```

提交这个处理任务到ManagedSelector:

```
private final Queue<Runnable> _changes = new ConcurrentArrayQueue<>();  
_changes.offer(change);
```

### ConcurrentArrayQueue

与ConcurrentLinkedQueue相似的性能, 但直接保存元素  
而不是node, 因此需要更少的对象, 更少的GC

## 3.2. 请求处理

### 3.2.1. ManagedSelector.run()

```
while (isRunning())  
    select();
```

#### select()

发现有任务就执行

```
runChanges();
```

#### runChanges()

参见: [提交任务](#)

```
private void runChanges()  
{  
    Runnable change;  
    while ((change = _changes.poll()) != null)  
        runChange(change);  
}
```

#### runChange()

```
change.run();
```

## Accept.run

```
SelectionKey key = channel.register(_selector, 0, attachment);
EndPoint endpoint = createEndPoint(channel, key);
key.attach(endpoint);
```

## select()

```
int selected = _selector.select();
```

## 处理SelectionKey

```
Set<SelectionKey> selectedKeys = _selector.selectedKeys();
for (SelectionKey key : selectedKeys)
{
    if (key.isValid())
    {
        processKey(key);
    }
    else
    {
        if (debug)
            LOG.debug("Selector loop ignoring invalid key for channel {}", key.channel());
        Object attachment = key.attachment();
        if (attachment instanceof EndPoint)
            ((EndPoint)attachment).close();
    }
}
selectedKeys.clear();
```

## processKey()

```
private void processKey(SelectionKey key)
{
    Object attachment = key.attachment();
    try
    {
        if (attachment instanceof SelectableEndPoint)
        {
            ((SelectableEndPoint)attachment).onSelected();
        }
        else if (key.isConnectable())
        {
            processConnect(key, (Connect)attachment);
        }
        else if (key.isAcceptable())
        {
        }
    }
}
```

```

        {
            processAccept(key);
        }
        else
        {
            throw new IllegalStateException();
        }
    }
}
catch (CancelledKeyException x)
{
    LOG.debug("Ignoring cancelled key for channel {}", key.channel());
    if (attachment instanceof EndPoint)
        closeNoExceptions((EndPoint)attachment);
}
catch (Throwable x)
{
    LOG.warn("Could not process key for channel " + key.channel(), x);
    if (attachment instanceof EndPoint)
        closeNoExceptions((EndPoint)attachment);
}
}

```

## onSelected()

```

@Override
public void onSelected()
{
    assert _selector.isSelectorThread();
    int oldInterestOps = _key.interestOps();
    int readyOps = _key.readyOps();
    int newInterestOps = oldInterestOps & ~readyOps;
    setKeyInterests(oldInterestOps, newInterestOps);
    updateLocalInterests(readyOps, false);
    if (_key.isReadable())
        getFillInterest().fillable();
    if (_key.isWritable())
        getWriteFlusher().completeWrite();
}

```

**会使用新的线程进行HTTP业务处理 (提交到线程池)**