

clarigen-tests bitcoin-dao / contracts
/ bitcoin-dao.clar

Go to file

...



radicleart Switched data to event based - much simpler and lots of dead code can...

3fb66ba · 5 months ago



Executable File · 87 lines (70 loc) · 2.69 KB

Code

Blame

Raw



```
1 ;; Bitcoin DAO
2 ;; Author Mike Cohen - based on Marvin Janssen' Executor DAO
3 ;; Synopsis:
4 ;; bitcoin-dao is the core of the dao framework.
5 ;; Description:
6 ;; Valid extensions must be registered here. The DAO is bootstrapped
7 ;; by calling construct with a bootstrap proposal.
8
9 (use-trait extension-trait .extension-trait.extension-trait)
10 (use-trait proposal-trait .proposal-trait.proposal-trait)
11
12 (define-constant err-unauthorised (err u1000))
13 (define-constant err-already-executed (err u1001))
14 (define-constant err-invalid-extension (err u1002))
15
16 (define-data-var executive principal tx-sender)
17 (define-map executed-proposals principal uint)
18 (define-map extensions principal bool)
19
20 ;; --- Authorisation check
21
22 (define-private (is-self-or-extension)
23   (ok (asserts! (or (is-eq tx-sender (as-contract tx-sender)) (is-extension contract-ca
24   )
25
26   ;; --- Extensions
27
28   (define-read-only (is-extension (extension principal))
29     (default-to false (map-get? extensions extension)))
30   )
31
32   (define-public (set-extension (extension principal) (enabled bool))
33     (begin
34       (try! (is-self-or-extension))
35       (print {event: "extension", extension: extension, enabled: enabled})
36       (ok (map-set extensions extension enabled))
37     )
```

```

38 )
39
40 (define-private (set-extensions-iter (item {extension: principal, enabled: bool}))
41   (begin
42     (print {event: "extension", extension: (get extension item), enabled: (get er
43       (map-set extensions (get extension item) (get enabled item))
44   )
45 )
46
47 (define-public (set-extensions (extension-list (list 200 {extension: principal, enabled: bool
48   (begin
49     (try! (is-self-or-extension))
50     (ok (map set-extensions-iter extension-list))
51   )
52 )
53
54 ;; --- Proposals
55
56 (define-read-only (executed-at (proposal <proposal-trait>))
57   (map-get? executed-proposals (contract-of proposal))
58 )
59
60 (define-public (execute (proposal <proposal-trait>) (sender principal))
61   (begin
62     (try! (is-self-or-extension))
63     (asserts! (map-insert executed-proposals (contract-of proposal) block-height)
64       (print {event: "execute", proposal: proposal})
65       (as-contract (contract-call? proposal execute sender))
66   )
67 )
68
69 ;; --- Bootstrap
70
71 (define-public (construct (proposal <proposal-trait>))
72   (let ((sender tx-sender))
73     (asserts! (is-eq sender (var-get executive)) err-unauthorised)
74     (var-set executive (as-contract tx-sender))
75     (as-contract (execute proposal sender))
76   )
77 )
78
79 ;; --- Extension requests
80
81 (define-public (request-extension-callback (extension <extension-trait>) (memo (buff 34)))
82   (let ((sender tx-sender))
83     (asserts! (is-extension contract-caller) err-invalid-extension)
84     (asserts! (is-eq contract-caller (contract-of extension)) err-invalid-extensi
85     (as-contract (contract-call? extension callback sender memo))
86   )
87 )

```



clarigen-tests ▾

bitcoin-dao / contracts / extensions
/ bde000-governance-token.clar

Go to file



radicleart Switched data to event based - much simpler and lots of dead code can...



3fb66ba · 5 months ago

Executable File · 168 lines (132 loc) · 4.14 KB

Code

Blame

Raw



```
1  ;; Title: BDE000 Governance Token
2  ;; Author: Mike Cohen (based upon work of Marvin Janssen)
3  ;; Depends-On:
4  ;; Synopsis:
5  ;; This extension defines the governance token of Bitcoin DAO.
6  ;; Description:
7  ;; The governance token is a simple SIP010-compliant fungible token
8  ;; with some added functions to make it easier to manage by
9  ;; Bitcoin DAO proposals and extensions.
10
11  (impl-trait .governance-token-trait.governance-token-trait)
12  (impl-trait .sip010-ft-trait.sip010-ft-trait)
13  (impl-trait .extension-trait.extension-trait)
14
15  (define-constant err-unauthorised (err u3000))
16  (define-constant err-not-token-owner (err u4))
17
18  (define-fungible-token bdg-token)
19  (define-fungible-token bdg-token-locked)
20
21  (define-data-var token-name (string-ascii 32) "{{token_name}}")
22  (define-data-var token-symbol (string-ascii 10) "{{symbol}}")
23  (define-data-var token-uri (optional (string-utf8 256)) (some u"{{token_uri}}"))
24  (define-data-var token-decimals uint u6)
25
26  ;; --- Authorisation check
27
28  (define-public (is-dao-or-extension)
29    (ok (asserts! (or (is-eq tx-sender .bitcoin-dao) (contract-call? .bitcoin-dao is-exte
30  )
31
32  ;; --- Internal DAO functions
33
34  ;; governance-token-trait
35
36  (define-public (bdg-transfer (amount uint) (sender principal) (recipient principal))
37    (begin
```

```

38         (try! (is-dao-or-extension))
39         (ft-transfer? bdg-token amount sender recipient)
40     )
41 )
42
43 (define-public (bdg-lock (amount uint) (owner principal))
44     (begin
45         (try! (is-dao-or-extension))
46         (try! (ft-burn? bdg-token amount owner))
47         (ft-mint? bdg-token-locked amount owner)
48     )
49 )
50
51 (define-public (bdg-unlock (amount uint) (owner principal))
52     (begin
53         (try! (is-dao-or-extension))
54         (try! (ft-burn? bdg-token-locked amount owner))
55         (ft-mint? bdg-token amount owner)
56     )
57 )
58
59 (define-public (bdg-mint (amount uint) (recipient principal))
60     (begin
61         (try! (is-dao-or-extension))
62         (ft-mint? bdg-token amount recipient)
63     )
64 )
65
66 (define-public (bdg-burn (amount uint) (owner principal))
67     (begin
68         (try! (is-dao-or-extension))
69         (ft-burn? bdg-token amount owner)
70     )
71 )
72 )
73
74 ;; Other
75
76 (define-public (set-name (new-name (string-ascii 32)))
77     (begin
78         (try! (is-dao-or-extension))
79         (ok (var-set token-name new-name))
80     )
81 )
82
83 (define-public (set-symbol (new-symbol (string-ascii 10)))
84     (begin
85         (try! (is-dao-or-extension))
86         (ok (var-set token-symbol new-symbol))
87     )
88 )
89
90 (define-public (set-decimals (new-decimals uint))
91     (begin
92         (try! (is-dao-or-extension))
93         (ok (var-set token-decimals new-decimals))

```

```

94     )
95 )
96
97 (define-public (set-token-uri (new-uri (optional (string-utf8 256))))
98     (begin
99         (try! (is-dao-or-extension))
100         (ok (var-set token-uri new-uri))
101     )
102 )
103
104 (define-private (bdg-mint-many-iter (item {amount: uint, recipient: principal}))
105     (ft-mint? bdg-token (get amount item) (get recipient item))
106 )
107
108 (define-public (bdg-mint-many (recipients (list 200 {amount: uint, recipient: principal})))
109     (begin
110         (try! (is-dao-or-extension))
111         (ok (map bdg-mint-many-iter recipients))
112     )
113 )
114
115 ;; --- Public functions
116
117 ;; sip010-ft-trait
118
119 (define-public (transfer (amount uint) (sender principal) (recipient principal) (memo (optional string-utf8 256)))
120     (begin
121         (asserts! (or (is-eq tx-sender sender) (is-eq contract-caller sender)) err-no-sender)
122         (ft-transfer? bdg-token amount sender recipient)
123     )
124 )
125
126 (define-read-only (get-name)
127     (ok (var-get token-name))
128 )
129
130 (define-read-only (get-symbol)
131     (ok (var-get token-symbol))
132 )
133
134 (define-read-only (get-decimals)
135     (ok (var-get token-decimals))
136 )
137
138 (define-read-only (get-balance (who principal))
139     (ok (+ (ft-get-balance bdg-token who) (ft-get-balance bdg-token-locked who)))
140 )
141
142 (define-read-only (get-total-supply)
143     (ok (+ (ft-get-supply bdg-token) (ft-get-supply bdg-token-locked)))
144 )
145
146 (define-read-only (get-token-uri)
147     (ok (var-get token-uri))
148 )
149

```

```
150 ;; governance-token-trait
151
152 (define-read-only (bdg-get-balance (who principal))
153   (get-balance who)
154 )
155
156 (define-read-only (bdg-has-percentage-balance (who principal) (factor uint))
157   (ok (>= (* (unwrap-panic (get-balance who)) factor) (* (unwrap-panic (get-total-supply)
158   )
159 )
160 (define-read-only (bdg-get-locked (owner principal))
161   (ok (ft-get-balance bdg-token-locked owner))
162 )
163
164 ;; --- Extension callback
165
166 (define-public (callback (sender principal) (memo (buff 34)))
167   (ok true)
168 )
```



clarigen-tests ▾

bitcoin-dao / contracts / extensions
/ bde001-proposal-voting.clar

Go to file



radicleart Switched data to event based - much simpler and lots of dead code can...



3fb66ba · 5 months ago

Executable File · 152 lines (130 loc) · 5.56 KB

Code

Blame

Raw



```
1  ;; Title: BDE001 Snapshot Proposal Voting
2  ;; Author: Mike Cohen (based upon work of Marvin Janssen)
3  ;; Depends-On:
4  ;; Synopsis:
5  ;; This extension is a concept that allows all STX holders to
6  ;; vote on proposals based on their STX balance.
7  ;; Description:
8  ;; This extension allows anyone with STX to vote on proposals. The maximum upper
9  ;; bound, or voting power, depends on the amount of STX tokens the tx-sender
10 ;; owned at the start block height of the proposal. The name "snapshot" comes
11 ;; from the fact that the extension effectively uses the STX balance sheet
12 ;; at a specific block heights to determine voting power.
13 ;; Custom majority thresholds for voting are also possible on a per proposal basis.
14 ;; A custom majority of 66% mean the percent of votes for must be greater than 66 for
15 ;; the vote to carry.
16
17 (impl-trait .extension-trait.extension-trait)
18 (use-trait proposal-trait .proposal-trait.proposal-trait)
19
20 (define-constant err-unauthorised (err u3000))
21 (define-constant err-proposal-already-executed (err u3001))
22 (define-constant err-proposal-already-exists (err u3002))
23 (define-constant err-unknown-proposal (err u3003))
24 (define-constant err-proposal-already-concluded (err u3004))
25 (define-constant err-proposal-inactive (err u3005))
26 (define-constant err-insufficient-voting-capacity (err u3006))
27 (define-constant err-end-burn-height-not-reached (err u3007))
28 (define-constant err-not-majority (err u3008))
29 (define-constant err-exceeds-voting-cap (err u3009))
30
31 (define-constant custom-majority-upper u10000)
32 (define-constant vote-cap u140000000000)
33
34 (define-map proposals
35   principal
36   {
37     votes-for: uint,
```

```

38         votes-against: uint,
39         start-height-stacks: uint,
40         start-burn-height: uint,
41         end-burn-height: uint,
42         concluded: bool,
43         passed: bool,
44         custom-majority: (optional uint), ;; u10000 = 100%
45         proposer: principal
46     }
47 )
48
49 (define-map member-total-votes {proposal: principal, voter: principal} uint)
50
51 ;; --- Authorisation check
52
53 (define-public (is-dao-or-extension)
54   (ok (asserts! (or (is-eq tx-sender .bitcoin-dao) (contract-call? .bitcoin-dao is-exte
55 ))
56
57 ;; --- Internal DAO functions
58
59 ;; Proposals
60
61 (define-public (add-proposal (proposal <proposal-trait>) (data {start-height-stacks: uint, st
62   (begin
63     (try! (is-dao-or-extension))
64     (asserts! (is-none (contract-call? .bitcoin-dao executed-at proposal)) err-pr
65     (asserts! (match (get custom-majority data) majority (> majority u5000) true)
66     (print {event: "propose", proposal: proposal, proposer: tx-sender}))
67     (ok (asserts! (map-insert proposals (contract-of proposal) (merge {votes-for:
68   )
69 )
70
71 ;; --- Public functions
72
73 ;; Proposals
74
75 (define-read-only (get-proposal-data (proposal principal))
76   (map-get? proposals proposal)
77 )
78
79 ;; Votes
80
81 (define-read-only (get-current-total-votes (proposal principal) (voter principal))
82   (default-to u0 (map-get? member-total-votes {proposal: proposal, voter: voter}))
83 )
84
85 (define-read-only (get-historical-values (height uint) (who principal))
86   (at-block (unwrap! (get-block-info? id-header-hash height) none)
87     (some
88       {
89         user-balance: (stx-get-balance who),
90         voting-cap: vote-cap,
91         ;;voting-cap: (contract-call? 'SP0000000000000000000002Q6VF78.
92       }
93     )

```



```

94     )
95 )
96
97 (define-public (vote (amount uint) (for bool) (proposal principal))
98   (let
99     (
100       (proposal-data (unwrap! (map-get? proposals proposal) err-unknown-proposal))
101       (new-total-votes (+ (get-current-total-votes proposal tx-sender) amount))
102       (historical-values (unwrap! (get-historical-values (get start-height proposal) historical-values) err-not-found))
103     )
104     (asserts! (>= burn-block-height (get start-burn-height proposal-data)) err-proposal-burn-height)
105     (asserts! (< burn-block-height (get end-burn-height proposal-data)) err-proposal-end-burn-height)
106     (asserts!
107       (<= new-total-votes (get user-balance historical-values))
108       err-insufficient-voting-capacity)
109     )
110     (asserts!
111       (< new-total-votes (get voting-cap historical-values))
112       err-exceeds-voting-cap)
113     )
114     (map-set member-total-votes {proposal: proposal, voter: tx-sender} new-total-votes)
115     (map-set proposals proposal
116       (if for
117         (merge proposal-data {votes-for: (+ (get votes-for proposal-data) amount)})
118         (merge proposal-data {votes-against: (+ (get votes-against proposal-data) amount)}))
119       )
120     )
121     (print {event: "vote", proposal: proposal, voter: tx-sender, for: for, amount: amount})
122     (ok true)
123   )
124 )
125
126 ;; Conclusion
127
128 (define-public (conclude (proposal <proposal-trait>))
129   (let
130     (
131       (proposal-data (unwrap! (map-get? proposals (contract-of proposal)) err-unknown-proposal))
132       (passed
133         (match (get custom-majority proposal-data)
134           (majority (> (* (get votes-for proposal-data) custom-majority) (get votes-against proposal-data)))
135           )
136       )
137     )
138     (asserts! (not (get concluded proposal-data)) err-proposal-already-concluded)
139     (asserts! (>= burn-block-height (get end-burn-height proposal-data)) err-end-burn-height)
140     (map-set proposals (contract-of proposal) (merge proposal-data {concluded: true}))
141     (print {event: "conclude", proposal: proposal, passed: passed})
142     (and passed (try! (contract-call? .bitcoin-dao execute proposal tx-sender)))
143     (ok passed)
144   )
145 )
146 )
147
148 ;; --- Extension callback
149

```

```
150      (define-public (callback (sender principal) (memo (buff 34))))
151      (ok true)
152    )
```



clarigen-tests ▾

bitcoin-dao / contracts / extensions

Go to file



/ bde002-proposal-submission.clar



radicleart Switched data to event based - much simpler and lots of dead code can...



3fb66ba · 5 months ago



Executable File · 154 lines (127 loc) · 5.92 KB

Code

Blame

Raw



```
1 ;; Title: BDE002 Funded Custom End Proposal Submission
2 ;; Author: Mike Cohen (based upon work of Marvin Janssen)
3 ;; Depends-On: BDE001, BDE007
4 ;; Synopsis:
5 ;; This extension part of the core of Bitcoin DAO. It allows members to
6 ;; bring proposals to the voting phase by funding them with a preset amount
7 ;; of tokens.
8 ;; Description:
9 ;; The level of funding is determined by a DAO parameter and can be changed by proposal.
10 ;; Any funder can reclaim their stx up to the point the proposal is fully funded and submitted.
11 ;; Proposals can also be marked as refundable in which case a funder can reclaim their stx
12 ;; even after submission (during or after the voting period).
13 ;; This extension provides the ability for the final funding transaction to set a
14 ;; custom majority for voting. This changes the threshold from the
15 ;; default of 50% to anything up to 100%.
16
17 (impl-trait .extension-trait.extension-trait)
18 (use-trait proposal-trait .proposal-trait.proposal-trait)
19
20 (define-constant err-unauthorised (err u3100))
21 (define-constant err-not-governance-token (err u3101))
22 (define-constant err-insufficient-balance (err u3102))
23 (define-constant err-unknown-parameter (err u3103))
24 (define-constant err-proposal-minimum-start-delay (err u3104))
25 (define-constant err-proposal-minimum-duration (err u3105))
26 (define-constant err-already-funded (err u3106))
27 (define-constant err-nothing-to-refund (err u3107))
28 (define-constant err-refund-not-allowed (err u3108))
29
30 (define-map refundable-proposals principal bool)
31 (define-map funded-proposals principal bool)
32 (define-map proposal-funding principal uint)
33 (define-map funding-per-principal {proposal: principal, funder: principal} uint)
34
35 (define-map parameters (string-ascii 30) uint)
36
37 (map-set parameters "funding-cost" u500000) ;; funding cost in uSTX. 5 STX in this case.
```

```

38 (map-set parameters "minimum-proposal-start-delay" u6) ;; eg 6 = ~1 hour minimum delay before
39 (map-set parameters "minimum-proposal-duration" u72) ;; eg 72 = ~1/2 days minimum duration of
40
41 ;; --- Authorisation check
42
43 (define-public (is-dao-or-extension)
44   (ok (asserts! (or (is-eq tx-sender .bitcoin-dao) (contract-call? .bitcoin-dao is-exte
45   )
46
47 ;; --- Internal DAO functions
48
49 ;; Proposals
50
51 (define-private (submit-proposal-for-vote (proposal <proposal-trait>) (start-height-stacks ui
52   (contract-call? .bde001-proposal-voting add-proposal
53     proposal
54     {
55       start-height-stacks: start-height-stacks,
56       start-burn-height: start-burn-height,
57       end-burn-height: (+ start-burn-height duration),
58       custom-majority: custom-majority,
59       proposer: tx-sender ;; change to original submitter
60     }
61   )
62 )
63
64 ;; Parameters
65
66 (define-public (set-parameter (parameter (string-ascii 30)) (value uint))
67   (begin
68     (try! (is-dao-or-extension))
69     (try! (get-parameter parameter))
70     (ok (map-set parameters parameter value))
71   )
72 )
73
74 ;; Refunds
75
76 (define-public (set-refundable (proposal principal) (refundable bool))
77   (begin
78     (try! (is-dao-or-extension))
79     (ok (map-set refundable-proposals proposal refundable))
80   )
81 )
82
83 ;; --- Public functions
84
85 ;; Parameters
86
87 (define-read-only (get-parameter (parameter (string-ascii 30)))
88   (ok (unwrap! (map-get? parameters parameter) err-unknown-parameter))
89 )
90
91 ;; Funding status
92
93 (define-read-only (is-proposal-funded (proposal principal))

```

```

94     (default-to false (map-get? funded-proposals proposal))
95 )
96
97 (define-read-only (get-proposal-funding (proposal principal))
98   (default-to u0 (map-get? proposal-funding proposal))
99 )
100
101 (define-read-only (get-proposal-funding-by-principal (proposal principal) (funder principal))
102   (default-to u0 (map-get? funding-per-principal {proposal: proposal, funder: funder}))
103 )
104
105 (define-read-only (can-refund (proposal principal) (funder principal))
106   (or
107     (default-to false (map-get? refundable-proposals proposal))
108     (and (not (is-proposal-funded proposal)) (is-eq funder tx-sender))
109   )
110 )
111
112 ;; Proposals
113
114 (define-public (fund (proposal <proposal-trait>) (start-delay uint) (duration uint) (amount u))
115   (let
116     (
117       (proposal-principal (contract-of proposal))
118       (current-total-funding (get-proposal-funding proposal-principal))
119       (funding-cost (try! (get-parameter "funding-cost")))
120       (difference (if (> funding-cost current-total-funding) (- funding-cost
121       (funded (<= difference amount))
122       (transfer-amount (if funded difference amount))
123     )
124     (asserts! (not (is-proposal-funded proposal-principal)) err-already-funded)
125     (and (> transfer-amount u0) (try! (stx-transfer? transfer-amount tx-sender .b
126     (map-set funding-per-principal {proposal: proposal-principal, funder: tx-senc
127     (map-set proposal-funding proposal-principal (+ current-total-funding transfe
128     (asserts! funded (ok false))
129     (asserts! (>= start-delay (try! (get-parameter "minimum-proposal-start-delay"
130     (asserts! (>= duration (try! (get-parameter "minimum-proposal-duration"))) er
131     (map-set funded-proposals proposal-principal true)
132     (submit-proposal-for-vote proposal block-height (+ burn-block-height start-de
133   )
134 )
135
136 (define-public (refund (proposal principal) (funder (optional principal)))
137   (let
138     (
139       (recipient (default-to tx-sender funder))
140       (refund-amount (get-proposal-funding-by-principal proposal recipient)
141     )
142     (asserts! (> refund-amount u0) err-nothing-to-refund)
143     (asserts! (can-refund proposal recipient) err-refund-not-allowed)
144     (map-set funding-per-principal {proposal: proposal, funder: recipient} u0)
145     (map-set proposal-funding proposal (- (get-proposal-funding proposal) refund-
146     (contract-call? .bde006-treasury stx-transfer refund-amount recipient none)
147   )
148 )
149

```

```
150      ;; --- Extension callback
151
152      (define-public (callback (sender principal) (memo (buff 34)))
153        (ok true)
154      )
```



clarigen-tests ▾

bitcoin-dao / contracts / extensions
/ bde003-core-proposals.clar

Go to file



radicleart Clarigne tests updated

6be7546 · 5 months ago



Executable File · 79 lines (65 loc) · 2.81 KB

Code

Blame

Raw



```
1 ;; Title: BDE003 Core Proposals
2 ;; Author: Mike Cohen (based upon work of Marvin Janssen)
3 ;; Depends-On: BDE001
4 ;; Synopsis:
5 ;; This extension allows for the creation of core proposals by a few trusted
6 ;; principals.
7 ;; Description:
8 ;; Only a list of trusted principals, designated as the
9 ;; "core team", can create core proposals. The core proposal
10 ;; extension has an optional ~3 month sunset period, after which no more core
11 ;; proposals can be made – set it to 0 to disable. The core team members, sunset period, and
12 ;; core vote duration can be changed by means of a future proposal.
13
14 (impl-trait .extension-trait.extension-trait)
15 (use-trait proposal-trait .proposal-trait.proposal-trait)
16
17 (define-data-var core-team-sunset-height uint u0) ;; does not expire by default – can be char
18
19 (define-constant err-unauthorised (err u3300))
20 (define-constant err-not-core-team-member (err u3301))
21 (define-constant err-sunset-height-reached (err u3302))
22 (define-constant err-sunset-height-in-past (err u3303))
23 (define-constant err-proposal-minimum-start-delay (err u3304))
24 (define-constant err-proposal-minimum-duration (err u3305))
25
26 (define-map core-team principal bool)
27
28 ;; --- Authorisation check
29
30 (define-public (is-dao-or-extension)
31   (ok (asserts! (or (is-eq tx-sender .bitcoin-dao) (contract-call? .bitcoin-dao is-exte
32 )
33
34 ;; --- Internal DAO functions
35
36 (define-public (set-core-team-sunset-height (height uint))
37   (begin
38     (try! (is-dao-or-extension))
39     (asserts! (> height burn-block-height) err-sunset-height-in-past)
```

```

39      (asserts! (= height burn-block-height) err sunset-height-in-past)
40      (ok (var-set core-team-sunset-height height))
41    )
42  )
43
44  (define-public (set-core-team-member (who principal) (member bool))
45    (begin
46      (try! (is-dao-or-extension))
47      (ok (map-set core-team who member))
48    )
49  )
50
51  ;; --- Public functions
52
53  (define-read-only (is-core-team-member (who principal))
54    (default-to false (map-get? core-team who))
55  )
56
57  (define-public (core-propose (proposal <proposal-trait>) (start-burn-height uint) (duration uint))
58    (begin
59      (asserts! (is-core-team-member tx-sender) err-not-core-team-member)
60      (asserts! (or (is-eq (var-get core-team-sunset-height) u0) (< burn-block-height u0)) err-sunset-height-in-past)
61      (asserts! (>= start-burn-height (+ burn-block-height u2)) err-proposal-minimum-burn-height)
62      (asserts! (>= (+ start-burn-height duration) (+ burn-block-height u72)) err-proposal-maximum-duration)
63      (contract-call? .bde001-proposal-voting add-proposal proposal
64        {
65          start-height-stacks: block-height,
66          start-burn-height: start-burn-height,
67          end-burn-height: (+ start-burn-height duration),
68          custom-majority: custom-majority,
69          proposer: tx-sender ;; change to original submitter
70        }
71      )
72    )
73  )
74
75  ;; --- Extension callback
76
77  (define-public (callback (sender principal) (memo (buff 34)))
78    (ok true)
79  )

```




clarigen-tests ▾

bitcoin-dao / contracts / extensions
/ bde004-core-execute.clar

Go to file



radicleart Switched data to event based - much simpler and lots of dead code can...

3fb66ba · 5 months ago

Executable File · 101 lines (82 loc) · 3.6 KB

Code

Blame

Raw



```
1  ;; Title: BDE004 Core Execute
2  ;; Author: Mike Cohen (based on Marvin Janssen)
3  ;; Depends-On:
4  ;; Synopsis:
5  ;; This extension allows a small number of very trusted principals to immediately
6  ;; execute a proposal once a super majority is reached.
7  ;; Description:
8  ;; An extension meant for the bootstrapping period of a DAO. It temporarily gives
9  ;; some very trusted principals the ability to perform an "executive action";
10 ;; meaning, they can skip the voting process to immediately executive a proposal.
11 ;; The Core execute extension has an optional sunset period of ~1 month from deploy
12 ;; time, set it to 0 to disable. The core executive team, parameters, and sunset period may b
13 ;; by means of a future proposal.
14
15 (impl-trait .extension-trait.extension-trait)
16 (use-trait proposal-trait .proposal-trait.proposal-trait)
17
18 (define-data-var executive-team-sunset-height uint u0) ;; does not expire by default - can be
19
20 (define-constant err-unauthorised (err u3400))
21 (define-constant err-not-executive-team-member (err u3401))
22 (define-constant err-already-executed (err u3402))
23 (define-constant err-sunset-height-reached (err u3403))
24 (define-constant err-sunset-height-in-past (err u3404))
25
26 (define-map executive-team principal bool)
27 (define-map executive-action-signals {proposal: principal, team-member: principal} bool)
28 (define-map executive-action-signal-count principal uint)
29
30 (define-data-var executive-signals-required uint u1) ;; signals required for an executive act
31
32 ;; --- Authorisation check
33
34 (define-public (is-dao-or-extension)
35   (ok (asserts! (or (is-eq tx-sender .bitcoin-dao) (contract-call? .bitcoin-dao is-exte
36 )
37
```

```

38 ;; --- Internal DAO functions
39
40 (define-public (set-executive-team-sunset-height (height uint))
41   (begin
42     (try! (is-dao-or-extension))
43     (asserts! (> height burn-block-height) err-sunset-height-in-past)
44     (ok (var-set executive-team-sunset-height height))
45   )
46 )
47
48 (define-public (set-executive-team-member (who principal) (member bool))
49   (begin
50     (try! (is-dao-or-extension))
51     (ok (map-set executive-team who member))
52   )
53 )
54
55 (define-public (set-signals-required (new-requirement uint))
56   (begin
57     (try! (is-dao-or-extension))
58     (ok (var-set executive-signals-required new-requirement))
59   )
60 )
61
62 ;; --- Public functions
63
64 (define-read-only (is-executive-team-member (who principal))
65   (default-to false (map-get? executive-team who))
66 )
67
68 (define-read-only (has-signalled (proposal principal) (who principal))
69   (default-to false (map-get? executive-action-signals {proposal: proposal, team-member
70 )
71
72 (define-read-only (get-signals-required)
73   (var-get executive-signals-required)
74 )
75
76 (define-read-only (get-signals (proposal principal))
77   (default-to u0 (map-get? executive-action-signal-count proposal))
78 )
79
80 (define-public (executive-action (proposal <proposal-trait>))
81   (let
82     (
83       (proposal-principal (contract-of proposal))
84       (signals (+ (get-signals proposal-principal) (if (has-signalled propo
85     )
86     (asserts! (is-executive-team-member tx-sender) err-not-executive-team-member)
87     (asserts! (or (is-eq (var-get executive-team-sunset-height) u0) (< burn-block
88     (and (>= signals (var-get executive-signals-required))
89     (try! (contract-call? .bitcoin-dao execute proposal tx-sender))
90   )
91   (map-set executive-action-signals {proposal: proposal-principal, team-member:
92   (map-set executive-action-signal-count proposal-principal signals)
93   (ok signals)

```

```
94      )
95    )
96
97    ;; --- Extension callback
98
99    (define-public (callback (sender principal) (memo (buff 34)))
100      (ok true))
101  )
```



clarigen-tests ▾

bitcoin-dao / contracts / extensions
/ bde006-treasury.clar

Go to file



radicleart Switched data to event based - much simpler and lots of dead code can...



3fb66ba · 5 months ago



Executable File · 157 lines (128 loc) · 4.95 KB

Code

Blame

Raw



```
1  ;; Title: EDE006 Treasury
2  ;; Author: Mike Cohen (based upon work of Marvin Janssen)
3  ;; Depends-On:
4  ;; Synopsis:
5  ;; A treasury that can manage STX, SIP009, SIP010, and SIP013 tokens.
6  ;; Description:
7  ;; An extension contract that is meant to hold tokens on behalf of the
8  ;; DAO. It can hold and transfer STX, SIP009, SIP010, and SIP013 tokens.
9  ;; They can be deposited by simply transferring them to the contract.
10 ;; Any extension or executing proposal can trigger transfers.
11 ;; Technically, the ExecutorDAO core can hold and transfer tokens
12 ;; directly. The treasury extension merely adds a bit of separation.
13
14 (impl-trait .extension-trait.extension-trait)
15
16 (define-constant err-unauthorised (err u3000))
17
18 ;; --- Transferable traits
19
20 (define-trait sip009-transferable
21   (
22     (transfer (uint principal principal) (response bool uint))
23   )
24 )
25
26 (define-trait sip010-transferable
27   (
28     (transfer (uint principal principal (optional (buff 34))) (response bool uint)
29   )
30 )
31
32 (define-trait sip013-transferable
33   (
34     (transfer (uint uint principal principal) (response bool uint))
35     (transfer-memo (uint uint principal principal (buff 34)) (response bool uint)
36   )
37 )
```

```

38
39 (define-trait sip013-transferable-many
40   (
41     (transfer-many ((list 200 {token-id: uint, amount: uint, sender: principal, r
42     (transfer-many-memo ((list 200 {token-id: uint, amount: uint, sender: princip
43   )
44 )
45
46 ;; --- Authorisation check
47
48 (define-public (is-dao-or-extension)
49   (ok (asserts! (or (is-eq tx-sender .bitcoin-dao) (contract-call? .bitcoin-dao is-exte
50 )
51
52 ;; --- Internal DAO functions
53
54 ;; STX
55
56 (define-public (stx-transfer (amount uint) (recipient principal) (memo (optional (buff 34))))
57   (begin
58     (try! (is-dao-or-extension))
59     (match memo to-print (print to-print) 0x)
60     (as-contract (stx-transfer? amount tx-sender recipient))
61   )
62 )
63
64 (define-public (stx-transfer-many (transfers (list 200 {amount: uint, recipient: principal, n
65   (begin
66     (try! (is-dao-or-extension))
67     (as-contract (fold stx-transfer-many-iter transfers (ok true)))
68   )
69 )
70
71 ;; SIP009
72
73 (define-public (sip009-transfer (token-id uint) (recipient principal) (asset <sip009-transfer
74   (begin
75     (try! (is-dao-or-extension))
76     (as-contract (contract-call? asset transfer token-id tx-sender recipient))
77   )
78 )
79
80 (define-public (sip009-transfer-many (data (list 200 {token-id: uint, recipient: principal}))
81   (begin
82     (as-contract (fold sip009-transfer-many-iter data asset))
83     (ok true)
84   )
85 )
86
87 ;; SIP010
88
89 (define-public (sip010-transfer (amount uint) (recipient principal) (memo (optional (buff 34)
90   (begin
91     (try! (is-dao-or-extension))
92     (as-contract (contract-call? asset transfer amount tx-sender recipient memo))
93   )

```

```

94 )
95
96 (define-public (sip010-transfer-many (data (list 200 {amount: uint, recipient: principal, memo: (opt
97     (begin
98         (as-contract (fold sip010-transfer-many-iter data asset))
99         (ok true)
100     )
101 )
102
103 ;; SIP013
104
105 (define-public (sip013-transfer (token-id uint) (amount uint) (recipient principal) (memo (opt
106     (begin
107         (try! (is-dao-or-extension))
108         (as-contract (match memo memo-buff
109             (contract-call? asset transfer-memo token-id amount tx-sender recipient)
110             (contract-call? asset transfer token-id amount tx-sender recipient)
111         ))
112     )
113 )
114
115 (define-public (sip013-transfer-many (transfers (list 200 {token-id: uint, amount: uint, sender: principal, memo: (opt
116     (begin
117         (try! (is-dao-or-extension))
118         (as-contract (contract-call? asset transfer-many transfers))
119     )
120 )
121
122 (define-public (sip013-transfer-many-memo (transfers (list 200 {token-id: uint, amount: uint, sender: principal, memo: (opt
123     (begin
124         (try! (is-dao-or-extension))
125         (as-contract (contract-call? asset transfer-many-memo transfers))
126     )
127 )
128
129 ;; --- Iterator functions
130
131 (define-private (stx-transfer-many-iter (data {amount: uint, recipient: principal, memo: (opt
132     (begin
133         (try! previous-result)
134         (match (get memo data) to-print (print to-print) 0x)
135         (stx-transfer? (get amount data) tx-sender (get recipient data))
136     )
137 )
138
139 (define-private (sip009-transfer-many-iter (data {token-id: uint, recipient: principal}) (asset contract)
140     (begin
141         (unwrap-panic (contract-call? asset transfer (get token-id data) tx-sender (get memo data)
142             asset)
143     )
144 )
145
146 (define-private (sip010-transfer-many-iter (data {amount: uint, recipient: principal, memo: (opt
147     (begin
148         (unwrap-panic (contract-call? asset transfer (get amount data) tx-sender (get recipient data)
149             asset)

```

```
150      )
151    )
152
153    ;; --- Extension callback
154
155    (define-public (callback (sender principal) (memo (buff 34)))
156      (ok true)
157    )
```