

```
// BootRunner.cs
using System.Collections;
using Sy.Core;
using UnityEngine;
using UnityEngine.SceneManagement;
using Logger = Sy.Core.Logger;
namespace Sy.P04.Boot
{
    public static class SceneIds
    {
        public const string Boot = "S00_Boot";
        public const string Main = "S04_Main";
    }
    /// <summary>
    /// S00_Boot      Mock → →      T001④
    ///      Boot      UI T001b  Boot      =
    /// </summary>
    public sealed class BootRunner : MonoBehaviour
    {
        IEnumerator Start()
        {
            BootServices.RegisterAll();
            var sequence = new BootSequence(SwitchToMain);
            if (!sequence.RunAll())
            {
                Logger.Error("BOOT", "boot sequence failed - stay on S00_Boot");
                yield break;
            }
            yield return null;
        }
        bool SwitchToMain()
        {
            StartCoroutine(LoadMainRoutine());
            return true;
        }
        IEnumerator LoadMainRoutine()
        {
            var op = SceneManager.LoadSceneAsync(SceneIds.Main, LoadSceneMode.Single);
            while (op != null && !op.isDone) yield return null;
        }
    }
}

// BootSequence.cs
using System;
using System.Collections.Generic;
using Sy.Core;
using Sy.Platform;
namespace Sy.P04.Boot
{
    /// <summary>
```

```

/// Boot      T001
/// ①Logger→② →③Config→④Save→⑤ILocale→⑥Ads.Preload→⑦      [BOOT] n/7
/// ⑦      Play =SceneManager.LoadSceneAsync Editor dry-run=EditorSceneManager.OpenScene
/// X006      SY MOCK
/// &lt;/summary&gt;
public sealed class BootSequence
{
    public const int TotalSteps = 7;
    readonly Func&lt;bool&gt; _switchScene;
    readonly List&lt;string&gt; _lines = new();
    public BootSequence(Func&lt;bool&gt; switchScene)
    {
        _switchScene = switchScene;
    }
    public IReadOnlyList&lt;string&gt; Lines =&gt; _lines;
    public bool RunAll()
    {
        bool ok = true;
        ok &= Run(1, "Logger", LoggerStep);
        ok &= Run(2, "Time", TimeStep);
        ok &= Run(3, "Config", ConfigStep);
        ok &= Run(4, "Save", SaveStep);
        ok &= Run(5, "ILocale", LocaleStep);
        ok &= Run(6, "Ads.Preload", AdsStep);
        ok &= Run(7, "SwitchMain", () =&gt; _switchScene != null && _switchScene());
        return ok;
    }
    bool Run(int n, string name, Func&lt;bool&gt; step)
    {
        bool result;
        try
        {
            result = step();
        }
        catch (Exception e)
        {
            Logger.Error("BOOT", $"step {n} {name} exception: {e.Message}");
            result = false;
        }
        string line = $"[BOOT] {n}/{TotalSteps} {name} {(result ? "ok" : "FAIL")}";
        _lines.Add(line);
        Logger.Info("BOOT", line);
        return result;
    }
    static bool LoggerStep() =&gt; true; //      JS sink platform T001c
    static bool TimeStep()
    {
        var time = ServiceLocator.Get&lt;ITimeService&gt;();
        return time.ServerNowMs() &gt; 0 && !time.TimeCheated();
    }
}

```

```

        static bool ConfigStep()
        {
            var config = ServiceLocator.Get<IConfigService>();
            var update = config.CheckUpdate("mock://manifest");
            return update.NewVersion != null; // mock= X009 manifest
        }
        static bool SaveStep()
        {
            var save = ServiceLocator.Get<ISaveService>();
            save.Save("boot_probe", "{}");
            return !string.IsNullOrEmpty(save.Load("boot_probe"));
        }
        static bool LocaleStep()
        {
            var locale = ServiceLocator.Get<ILocaleService>();
            return !string.IsNullOrEmpty(locale.GetFontSet().NormalFont); // +
        }
        static bool AdsStep()
        {
            ServiceLocator.Get<IAdsService>().Preload("boot_warmup");
            return true;
        }
    }
}

// BootServices.cs
using System;
using System.Collections.Generic;
using System.Threading.Tasks;
using Sy.Core;
using Sy.Platform;
using UnityEngine;
using Logger = Sy.Core.Logger;
namespace Sy.P04.Boot
{
    /// <summary>
    /// Mock SY MOCK X006 Mock X002a AppID touristappid
    /// T001c WX/TT Channel Editor Boot
    /// </summary>
    public static class BootServices
    {
        public static void RegisterAll()
        {
            if (ServiceLocator.TryGet<ITimeService>(out _)) return; //
            ServiceLocator.Register<ITimeService>(new MockTimeService());
            ServiceLocator.Register<IConfigService>(new MockConfigService());
            ServiceLocator.Register<ISaveService>(new MockSaveService());
            ServiceLocator.Register<ILocaleService>(new MockLocaleService());
            ServiceLocator.Register<IAdsService>(new MockAdsService());
            Logger.Info("BOOT", "mock services registered (SY MOCK)");
        }
    }
}

```

```

}
public sealed class MockTimeService : ITimeService
{
    public TimeSource Source => TimeSource.Mock;
    public long ClientNowMs() => DateTimeOffset.UtcNow.ToUnixTimeMilliseconds();
    /// <summary>SY MOCK X006 TCB serverTime→HTTPS Date → T001b </summary>
    public long ServerNowMs() => ClientNowMs();
    public bool TimeCheated() => Math.Abs(ServerNowMs() - ClientNowMs()) > 120_000;
}
public sealed class MockConfigService : IConfigService
{
    public T GetTable<T>(string tableId) where T : class
        => throw new KeyNotFoundException("mock config table not loaded: " + tableId);
    public bool TryGetTable<T>(string tableId, out T table) where T : class
    {
        table = null;
        return false;
    }
    public ConfigUpdateResult CheckUpdate(string manifestUrl)
        => new ConfigUpdateResult(false, "mock-0.0.1");
    public void SwapPolicy(ConfigSwapPolicy policy) { }
    public string PinConfigVersion(string scope) => "mock-0.0.1";
}
public sealed class MockSaveService : ISaveService
{
    const string Prefix = "sy_save_";
    public void Save(string slot, string payloadJson) => PlayerPrefs.SetString(Prefix + slot, payloadJson);
    public string Load(string slot) => PlayerPrefs.GetString(Prefix + slot, string.Empty);
    /// <summary>X006 T001b v1→v2 </summary>
    public SyncResult CloudSync() => new SyncResult(false, null);
}
public sealed class MockLocaleService : ILocaleService
{
    public void SetLang(string lang) { }
    /// <summary>key key T001b cfg_i18n + NUnit </summary>
    public string GetText(string key, params string[] args)
    {
        Logger.Warn("LOCALE", "missing i18n key (fallback): " + key);
        return key;
    }
    public FontSet GetFontSet()
        => new FontSet("LegacyRuntime.ttf", "LegacyRuntime.ttf", "LegacyRuntime.ttf");
}
public sealed class MockAdsService : IAdsService
{
    public event Action<AdLifecycle> OnAdEvent;
    public Task<RewardResult> ShowRewarded(string pointId)
        => Task.FromResult(new RewardResult { Completed = true, Reason = "mock" });
    public void ShowInterstitial(string pointId) { }
    public void ShowBanner(string pointId) { }
}

```

```
        public void Preload(string pointId)
        {
            Logger.Info("ADS", "preload (mock): " + pointId);
            OnAdEvent?.Invoke(new AdLifecycle(AdLifecycleType.Fill, pointId, "mock"));
        }
    }
}

// MainUI.cs
using UnityEngine;
using UnityEngine.SceneManagement;
using UnityEngine.UI;
namespace Sy.P04.Newbie
{
    /// <summary>
    /// S04    V1.4    -O-20261010-1245
    ///          .M5          —
    ///          /          /   /   /
    ///          U362 HUD          6
    /// </summary>
    public sealed class MainUI : MonoBehaviour
    {
        static readonly Color PalRed = new Color(0.902f, 0.224f, 0.275f);
        static readonly Color PalBlue = new Color(0.271f, 0.482f, 0.616f);
        static readonly Color PalGold = new Color(1f, 0.843f, 0f);
        static readonly Color PalGreen = new Color(0.165f, 0.616f, 0.561f);
        static readonly Color PalBlack = new Color(0.114f, 0.114f, 0.114f);
        static readonly Color LockedGray = new Color(0.35f, 0.35f, 0.35f, 0.85f);
        Canvas _canvas;
        Sprite _square;
        Text _walletText;
        RectTransform _codexPanel;
        int _lastWallet = -1;
        public void StartHunt()
        {
            SceneManager.LoadScene(NewbieSceneIds.Battle);
        }
        void Awake()
        {
            Application.targetFrameRate = 30;
            Sy.Core.MainArtInjector.Apply(transform, "P04_scene_01", "P04_unit_01");
            _canvas = FindObjectOfType<Canvas>();
            _square = MakeSquareSprite();
            //
            var old = GameObject.Find("StartButton");
            if (old != null)
            {
                var rt = (RectTransform)old.transform;
                rt.anchorMin = rt.anchorMax = new Vector2(0.5f, 0.5f);
                rt.anchoredPosition = new Vector2(0, 320);
                rt.sizeDelta = new Vector2(560, 130);
            }
        }
    }
}
```

```
        var label = old.GetComponentInChildren<Text>();
        if (label != null)
        {
            label.text = "      .      ";
            label.fontSize = 44;
        }
        var img = old.GetComponent<Image>();
        if (img != null) img.color = PalGreen;
    }
    BuildModeButtons();
    BuildWalletLine();
    BuildCodexPanel();
    SyncWallet(true);
}
void BuildModeButtons()
{
    MakeModeButton("      .      ", new Vector2(0, 160), PalRed, () =>{
        {
            Yaotide.YaotideBattleLaunch.StartRandom();
            SceneManager.LoadScene("S04_Yaotide");
        }
    });
    if (Yaotide.DailyRift.IsEligible())
    {
        MakeModeButton("      .      ", new Vector2(0, 0), PalGold, () =>{
            {
                Yaotide.YaotideBattleLaunch.StartDailyRift();
                SceneManager.LoadScene("S04_Yaotide");
            }
        });
    }
    MakeModeButton("      ", new Vector2(-300, -180), PalBlack, ToggleCodex);
    MakeModeButton("      .      ", new Vector2(300, -180), PalBlack, () =>{
        {
            var wallet = Yaotide.SealCharmWallet.Load();
            int got = wallet.TryExchange(Random.Range(0, 99));
            SyncWallet(true);
            ShowToast(got > 0
                ? "      " + (Yaotide.YaoCodexById(got)?.Name ?? "?") + "      "
                : wallet.CanExchange ? "      " : "      60      ");
        }
    });
}
void BuildWalletLine()
{
    _walletText = MakeText(_canvas.transform, " 0", 44, new Vector2(0, -320), TextAnchor.MiddleCenter, 500, 60)
    _walletText.color = PalGold;
    MakeModeButton("      .      ", new Vector2(0, -400), PalGreen, () =>{
        {
            long now = System.DateTimeOffset.Now.ToUnixTimeMilliseconds();
            var claim = Yaotide.RiftOfflinePay.OfflineClaim.Open(now);
            if (!claim.Claimable)
            {

```

```

        ShowToast("    1    ");
        return;
    }
    int got = claim.TryCollect(false);
    if (got > 0)
    {
        SyncWallet(true);
        ShowToast("    +" + got);
    }
    });
}
void SyncWallet(bool force)
{
    int balance = Yaotide.SealCharmWallet.Load().Balance;
    if (!force && balance == _lastWallet) return;
    _lastWallet = balance;
    _walletText.text = "    " + balance + (balance >= Yaotide.SealCharmWallet.ExchangeCost ? "    " : "");
}
void BuildCodexPanel()
{
    _codexPanel = MakeOverlayPanel();
    MakeText(_codexPanel, "    .    ", 72, new Vector2(0, 760), TextAnchor.MiddleCenter, 900, 90).color = PalG
    var yaos = Yaotide.YaoCodex.All;
    for (int i = 0; i < yaos.Count; i++)
    {
        int row = i / 2, col = i % 2;
        var y = yaos[i];
        bool sealedUp = Yaotide.YaoCodex.IsSealed(y.Id);
        var card = new GameObject("Codex_" + y.Id, typeof(RectTransform), typeof(Image));
        card.transform.SetParent(_codexPanel, false);
        var rt = (RectTransform)card.transform;
        rt.anchorMin = rt.anchorMax = new Vector2(0.5f, 0.5f);
        rt.anchoredPosition = new Vector2(-300 + col * 600, 520 - row * 230);
        rt.sizeDelta = new Vector2(560, 200);
        var img = card.GetComponent<Image>();
        img.sprite = _square;
        img.color = sealedUp ? (y.Tier == Yaotide.YaoCodex.Tier.Gold ? PalGold
            : y.Tier == Yaotide.YaoCodex.Tier.Purple ? PalRed : PalGreen) : LockedGray;
        MakeText(card.transform, sealedUp ? y.Name : "    " + y.SealHint + "    ", 48,
            new Vector2(0, 50), TextAnchor.MiddleCenter, 520, 70).color = sealedUp ? PalBlack : new Color(0.7f,
        MakeText(card.transform, sealedUp ? y.Role : "    ", 38,
            new Vector2(0, -50), TextAnchor.MiddleCenter, 520, 60).color = sealedUp
            ? new Color(0.1f, 0.1f, 0.1f, 0.75f) : new Color(0.55f, 0.55f, 0.5f);
    }
    var close = MakeModeButtonCore("    ", new Vector2(0, -740), PalGreen, ToggleCodex);
    close.transform.SetParent(_codexPanel, false);
    _codexPanel.gameObject.SetActive(false);
}
void ToggleCodex()
{

```

```

bool show = !_codexPanel.gameObject.activeSelf;
if (show)
{
    var yaos = Yaotide.YaoCodex.All;
    for (int i = 0; i < yaos.Count; i++)
    {
        var card = _codexPanel.Find("Codex_" + yaos[i].Id);
        if (card == null) continue;
        var img = card.GetComponent<Image>();
        bool sealedUp = Yaotide.YaoCodex.IsSealed(yaos[i].Id);
        var y = yaos[i];
        img.color = sealedUp ? (y.Tier == Yaotide.YaoCodex.Tier.Gold ? PalGold
            : y.Tier == Yaotide.YaoCodex.Tier.Purple ? PalRed : PalGreen) : LockedGray;
    }
}
_codexPanel.gameObject.SetActive(show);
}

void ShowToast(string message)
{
    _walletText.text = message;
    CancelInvoke(nameof(RestoreWallet));
    Invoke(nameof(RestoreWallet), 1.6f);
}

void RestoreWallet() => SyncWallet(true);
// —— UI          UGUI·    YAML    ——
Button MakeModeButton(string text, Vector2 pos, Color color, System.Action onClick)
    => MakeModeButtonCore(text, pos, color, onClick, _canvas.transform);
Button MakeModeButtonCore(string text, Vector2 pos, Color color, System.Action onClick, Transform parent = null)
{
    var go = new GameObject("ModeBtn_" + text, typeof(RectTransform), typeof(Image), typeof(Button));
    go.transform.SetParent(parent != null ? parent : _canvas.transform, false);
    var rt = (RectTransform)go.transform;
    rt.anchorMin = rt.anchorMax = new Vector2(0.5f, 0.5f);
    rt.anchoredPosition = pos;
    rt.sizeDelta = new Vector2(560, 130);
    var img = go.GetComponent<Image>();
    img.sprite = _square;
    img.color = color;
    var label = MakeText(go.transform, text, 44, Vector2.zero, TextAnchor.MiddleCenter, 560, 130);
    label.color = color == PalGold ? PalBlack : new Color(0.96f, 0.94f, 0.9f);
    var btn = go.GetComponent<Button>();
    btn.onClick.AddListener(() => onClick());
    return btn;
}

RectTransform MakeOverlayPanel()
{
    var go = new GameObject("CodexPanel", typeof(RectTransform), typeof(Image));
    go.transform.SetParent(_canvas.transform, false);
    var rt = (RectTransform)go.transform;
    rt.anchorMin = Vector2.zero;

```

```

        rt.anchorMax = Vector2.one;
        rt.offsetMin = rt.offsetMax = Vector2.zero;
        var img = go.GetComponent<Image>();
        img.sprite = _square;
        img.color = new Color(0.05f, 0.03f, 0.08f, 0.96f);
        return rt;
    }

    static Text MakeText(Transform parent, string text, int size, Vector2 pos, TextAnchor anchor, float w, float h)
    {
        var go = new GameObject("Text", typeof(RectTransform), typeof(Text));
        go.transform.SetParent(parent, false);
        var rt = (RectTransform)go.transform;
        rt.anchorMin = rt.anchorMax = new Vector2(0.5f, 0.5f);
        rt.anchoredPosition = pos;
        rt.sizeDelta = new Vector2(w, h);
        var t = go.GetComponent<Text>();
        t.font = Resources.GetBuiltinResource<Font>("LegacyRuntime.ttf");
        t.text = text;
        t.fontSize = size;
        t.alignment = anchor;
        t.color = new Color(0.91f, 0.89f, 0.85f);
        t.supportRichText = true;
        return t;
    }

    static Sprite MakeSquareSprite()
    {
        var tex = new Texture2D(8, 8, TextureFormat.RGBA32, false);
        var px = tex.GetPixels32();
        for (int i = 0; i < px.Length; i++) px[i] = new Color32(255, 255, 255, 255);
        tex.SetPixels32(px);
        tex.Apply(false, false);
        return Sprite.Create(tex, new Rect(0, 0, 8, 8), new Vector2(0.5f, 0.5f), 8f);
    }
}

// BattleLauncher.cs
using System.Collections.Generic;
using UnityEngine;
namespace Sy.P04.Newbie
{
    public static class NewbieSceneIds
    {
        {
            public const string Main = "S04_Main";
            public const string Battle = "S04_Battle";
        }
        /// <summary>
        /// S04_Battle      IdleSim+TutorialFlow+BattleView    Tick
        /// Sy.Telemetry Editor =Debug sink T001e              +TCB
        /// HUD              6
        /// </summary>

```

```
public sealed class BattleLauncher : MonoBehaviour
{
    IdleSim _sim;
    TutorialFlow _tutorial;
    BattleView _view;
    Sy.Telemetry.TelemetryService _telemetry;
    int _lastFloor = -1, _lastCharms = -1, _lastKills = -1, _lastCodex = -1;
    void Awake()
    {
        Application.targetFrameRate = 30;
        var canvas = FindObjectOfType<Canvas>();
        _sim = new IdleSim();
        _view = gameObject.AddComponent<BattleView>();
        _view.Initialize(canvas, _sim);
        _telemetry = new Sy.Telemetry.TelemetryService();
        _telemetry.AddSink(new TelemetryDebugSink());
        _tutorial = new TutorialFlow(
            _sim,
            hint =>
            {
                Debug.Log("[HINT] " + hint);
                _view.SetHint(hint);
            },
            step => _telemetry.Track(Sy.Telemetry.EventIds.NewbieStep,
                new Dictionary<string, string> { { "step", step.ToString() } }));
        _view.SealRequested += OnSealRequested;
        _view.FormationPlaced += OnFormationPlaced;
        _sim.StateChanged += OnStateChanged;
    }
    void Update()
    {
        _sim.Tick(Time.deltaTime);
        _view.SyncView(_sim);
        if (_sim.Floor != _lastFloor) { _lastFloor = _sim.Floor; _view.SetFloor(_lastFloor); }
        if (_sim.SealCharms != _lastCharms) { _lastCharms = _sim.SealCharms; _view.SetCharms(_lastCharms); }
        if (_sim.Kills != _lastKills) { _lastKills = _sim.Kills; _view.SetKills(_lastKills); }
        if (_sim.CodexLitCount != _lastCodex) { _lastCodex = _sim.CodexLitCount; _view.SetCodex(_lastCodex); }
    }
    void OnSealRequested()
    {
        _sim.PressSeal();
    }
    void OnFormationPlaced()
    {
        _sim.PlaceGudiao();
    }
    void OnStateChanged(IdleSim.IdleState state)
    {
        switch (state)
        {
```

```
        case IdleSim.IdleState.Fighting:
            _view.HideIntro();
            break;
        case IdleSim.IdleState.SealAnim:
            _view.PlaySealAnim();
            break;
        case IdleSim.IdleState.SealFailAnim:
            _view.PlaySealFail();
            break;
        case IdleSim.IdleState.FloorSkip:
            _view.ShowFloorSkip(true);
            break;
        case IdleSim.IdleState.WallDemo:
            _view.ShowFloorSkip(false);
            _view.ShowWallBanner(true);
            break;
        case IdleSim.IdleState.Formation:
            _view.ShowWallBanner(false);
            _view.ShowFormationPanel(true);
            break;
        case IdleSim.IdleState.BossFight:
            _view.ShowFormationPanel(false);
            break;
        case IdleSim.IdleState.Settled:
            _view.ShowSettle(_sim.Kills, _sim.SealCharms, _sim.CodexLitCount);
            break;
    }
}

sealed class TelemetryDebugSink : Sy.Telemetry.TelemetryService.ISink
{
    public void Write(string evtId, Dictionary<string, string> fields)
    {
        var sb = new System.Text.StringBuilder(evtId);
        foreach (var kv in fields)
        {
            sb.Append(' ').Append(kv.Key).Append('=').Append(kv.Value);
        }
        Debug.Log("[TELEMETRY] " + sb);
    }
}

}

// BattleView.cs
using System;
using System.Collections;
using System.Collections.Generic;
using UnityEngine;
using UnityEngine.UI;
namespace Sy.P04.Newbie
{
```

```

/// <summary>
///             UGUI—           / / / /
/// X025         =           0.8s+           $ V1.2         =           0.5s+
///             =           4-9             =
/// UI Initialize           YAML
/// </summary>
public sealed class BattleView : MonoBehaviour
{
    //           x=-350       x=+500           0.3
    const float FriendX = -350f;
    const float FieldSpan = 850f;
    static readonly float[] RowY = { 300f, 0f, -300f };
    Canvas _canvas;
    Sprite _square;
    RectTransform _field;
    readonly Image[] _friendHpFills = new Image[NewbieConfig.FriendCount];
    Text _floorText, _charmText, _killsText, _hintText;
    Button _sealButton;
    Image _sealButtonImage;
    Text _sealLabel;
    RectTransform _introOverlay, _sealOverlay, _failOverlay, _skipBanner, _wallBanner, _formationPanel, _settlePanel
    RectTransform _magicRing;           //           6
    Image _sealFlash;                   //
    Text _settleStats;
    readonly Image[] _codexSlots = new Image[NewbieConfig.CodexSlots];
    readonly Text[] _codexLabels = new Text[NewbieConfig.CodexSlots];
    readonly Dictionary<int, EnemyVisual> _enemies = new();
    readonly List<int> _scratch = new();
    public event Action SealRequested;
    public event Action FormationPlaced;
    static readonly Color PalRed = new Color(0.902f, 0.224f, 0.275f); //           #E63946
    static readonly Color PalBlue = new Color(0.271f, 0.482f, 0.616f); //           #457B9D
    static readonly Color PalGold = new Color(1f, 0.843f, 0f); //           #FFD700
    static readonly Color PalGreen = new Color(0.165f, 0.616f, 0.561f); //           #2A9D8F
    static readonly Color PalBlack = new Color(0.114f, 0.114f, 0.114f); //           #1D1D1D
    static readonly Color PalFrostedGold = new Color(0.63f, 0.55f, 0.31f); //           .           $
    static readonly Color PanelBg = new Color(0.07f, 0.08f, 0.10f, 0.95f);
    public void Initialize(Canvas canvas, IdleSim sim)
    {
        _canvas = canvas;
        _square = MakeSquareSprite();
        BuildBackdrop();
        BuildHud();
        BuildField();
        BuildCodex();
        BuildIntroOverlay();
        BuildSealOverlay();
        BuildFailOverlay();
        BuildSkipBanner();
        BuildWallBanner();
    }

```

```

        BuildFormationPanel();
        BuildSettlePanel();
        SetHint("      ·      .....");
    }
    // ——
    /// <summary>X027 generated art: fullscreen backdrop behind all UI; skipped
    /// entirely when the art key is missing so headless checks stay green.</summary>
    void BuildBackdrop()
    {
        var art = Sy.Core.ArtRuntime.Get("P04_scene_01");
        if (art == null) return;
        var go = new GameObject("ArtBackdrop", typeof(RectTransform), typeof(Image));
        go.transform.SetParent(_canvas.transform, false);
        var rt = (RectTransform)go.transform;
        rt.anchorMin = Vector2.zero;
        rt.anchorMax = Vector2.one;
        rt.offsetMin = rt.offsetMax = Vector2.zero;
        rt.SetAsFirstSibling();
        var image = go.GetComponent<Image>();
        image.sprite = art;
        image.color = Color.white;
        image.preserveAspect = true;
        image.raycastTarget = false;
    }
    void BuildHud()
    {
        var root = _canvas.transform;
        _floorText = MakeText(root, " 0 ", 46, new Vector2(0, 880), TextAnchor.UpperLeft, 300, 70);
        _floorText.color = PalGold;
        MakeText(root, "  + NewbieConfig.StartLife, 46, new Vector2(0, 880), TextAnchor.UpperRight, 340, 70);
        _charmText = MakeText(root, " x" + NewbieConfig.StartSealCharms, 44, new Vector2(0, 820), TextAnchor.Upper
        _charmText.color = PalGold;
        _killsText = MakeText(root, " 0", 44, new Vector2(0, 820), TextAnchor.UpperRight, 400, 60);
        _hintText = MakeText(root, "", 40, new Vector2(0, -560), TextAnchor.MiddleCenter, 1020, 150);
        _hintText.color = new Color(0.95f, 0.87f, 0.6f);
        var btnGo = new GameObject("SealButton", typeof(Image), typeof(Button));
        btnGo.transform.SetParent(root, false);
        var btnRt = (RectTransform)btnGo.transform;
        btnRt.anchorMin = btnRt.anchorMax = new Vector2(0.5f, 0f);
        btnRt.anchoredPosition = new Vector2(0, 140);
        btnRt.sizeDelta = new Vector2(460, 140);
        _sealButtonImage = btnGo.GetComponent<Image>();
        _sealButtonImage.sprite = _square;
        _sealButtonImage.color = new Color(0.35f, 0.35f, 0.38f);
        _sealButton = btnGo.GetComponent<Button>();
        _sealButton.interactable = false;
        _sealLabel = MakeText(btnGo.transform, " 2 ", 46, Vector2.zero, TextAnchor.MiddleCenter, 460, 140);
        _sealLabel.color = new Color(0.7f, 0.7f, 0.7f);
        _sealButton.onClick.AddListener(() => SealRequested?.Invoke());
    }
}

```

```

void BuildField()
{
    var fieldGo = new GameObject("Field", typeof(RectTransform), typeof(Image));
    fieldGo.transform.SetParent(_canvas.transform, false);
    _field = (RectTransform)fieldGo.transform;
    _field.anchorMin = _field.anchorMax = new Vector2(0.5f, 0.5f);
    _field.anchoredPosition = new Vector2(0, 60);
    _field.sizeDelta = new Vector2(1040, 1360);
    var fieldImg = fieldGo.GetComponent<Image>();
    fieldImg.sprite = _square;
    fieldImg.color = PanelBg;
    var lineGo = new GameObject("FriendLine", typeof(RectTransform), typeof(Image));
    lineGo.transform.SetParent(_field, false);
    var lineRt = (RectTransform)lineGo.transform;
    lineRt.anchorMin = lineRt.anchorMax = new Vector2(0.5f, 0.5f);
    lineRt.anchoredPosition = new Vector2(FriendX - 110f, 0);
    lineRt.sizeDelta = new Vector2(6, 1240);
    var lineImg = lineGo.GetComponent<Image>();
    lineImg.sprite = _square;
    lineImg.color = new Color(PalGold.r, PalGold.g, PalGold.b, 0.5f);
    for (int i = 0; i < NewbieConfig.FriendCount; i++)
    {
        var go = new GameObject("Friend_" + i, typeof(RectTransform), typeof(Image));
        go.transform.SetParent(_field, false);
        var rt = (RectTransform)go.transform;
        rt.anchorMin = rt.anchorMax = new Vector2(0.5f, 0.5f);
        rt.anchoredPosition = new Vector2(FriendX, RowY[i]);
        rt.sizeDelta = new Vector2(150, 150);
        var image = go.GetComponent<Image>();
        image.sprite = _square;
        image.color = i == 0 ? PalGreen : i == 1 ? PalBlue : new Color(0.85f, 0.78f, 0.55f);
        MakeText(go.transform, NewbieConfig.FriendNames[i].Substring(0, 1), 52, new Vector2(0, -100), TextAnchor
        var hpGo = new GameObject("Hp", typeof(RectTransform), typeof(Image));
        hpGo.transform.SetParent(go.transform, false);
        var hpRt = (RectTransform)hpGo.transform;
        hpRt.anchorMin = new Vector2(0f, 1f);
        hpRt.anchorMax = new Vector2(1f, 1f);
        hpRt.anchoredPosition = new Vector2(0, -6);
        hpRt.sizeDelta = new Vector2(-8, 10);
        _friendHpFills[i] = hpGo.GetComponent<Image>();
        _friendHpFills[i].sprite = _square;
        _friendHpFills[i].type = Image.Type.Filled;
        _friendHpFills[i].fillMethod = Image.FillMethod.Horizontal;
        _friendHpFills[i].color = PalGreen;
    }
}

void BuildCodex()
{
    var root = _canvas.transform;
    MakeText(root, " ", 36, new Vector2(400, 750), TextAnchor.UpperCenter, 200, 50).color = PalGold;
}

```

```

for (int i = 0; i < NewbieConfig.CodexSlots; i++)
{
    var go = new GameObject("Codex_" + i, typeof(RectTransform), typeof(Image));
    go.transform.SetParent(root, false);
    var rt = (RectTransform)go.transform;
    rt.anchorMin = rt.anchorMax = new Vector2(0.5f, 0.5f);
    rt.anchoredPosition = new Vector2(400, 620 - i * 170);
    rt.sizeDelta = new Vector2(140, 140);
    var image = go.GetComponent<Image>();
    image.sprite = _square;
    image.color = new Color(0.16f, 0.16f, 0.18f);
    _codexSlots[i] = image;
    _codexLabels[i] = MakeText(go.transform, "?", 60, Vector2.zero, TextAnchor.MiddleCenter, 140, 140);
    _codexLabels[i].color = new Color(0.45f, 0.45f, 0.48f);
}
}

void BuildIntroOverlay()
{
    _introOverlay = MakeOverlayPanel("IntroOverlay", new Color(0.03f, 0.03f, 0.05f, 0.92f));
    MakeText(_introOverlay, "      ", 90, new Vector2(0, 180), TextAnchor.MiddleCenter, 1000, 120).color = P
    MakeText(_introOverlay, "      —      ", 52, new Vector2(0, 40), TextAnchor.MiddleCenter, 1040, 90)
}

void BuildSealOverlay()
{
    _sealOverlay = MakeOverlayPanel("SealOverlay", new Color(0.05f, 0.04f, 0.02f, 0.85f));
    //      6      § V1.2      = + 0.8s+
    var ringGo = new GameObject("MagicRing", typeof(RectTransform));
    ringGo.transform.SetParent(_sealOverlay, false);
    _magicRing = (RectTransform)ringGo.transform;
    _magicRing.anchorMin = _magicRing.anchorMax = new Vector2(0.5f, 0.5f);
    _magicRing.anchoredPosition = new Vector2(0, 120);
    _magicRing.sizeDelta = new Vector2(600, 600);
    Color[] ringColors = { PalRed, PalBlue, PalGold, PalGreen, PalRed, PalBlue };
    for (int i = 0; i < 6; i++)
    {
        var go = new GameObject("Shard_" + i, typeof(RectTransform), typeof(Image));
        go.transform.SetParent(_magicRing, false);
        var rt = (RectTransform)go.transform;
        rt.anchorMin = rt.anchorMax = new Vector2(0.5f, 0.5f);
        float ang = i * 60f * Mathf.Deg2Rad;
        rt.anchoredPosition = new Vector2(Mathf.Cos(ang), Mathf.Sin(ang)) * 240f;
        rt.sizeDelta = new Vector2(70, 110);
        rt.localRotation = Quaternion.Euler(0f, 0f, i * 60f + 90f);
        var img = go.GetComponent<Image>();
        img.sprite = _square;
        img.color = ringColors[i];
    }
    var flashGo = new GameObject("Flash", typeof(RectTransform), typeof(Image));
    flashGo.transform.SetParent(_sealOverlay, false);
    var flashRt = (RectTransform)flashGo.transform;

```

```

        flashRt.anchorMin = flashRt.anchorMax = new Vector2(0.5f, 0.5f);
        flashRt.anchoredPosition = new Vector2(0, 120);
        flashRt.sizeDelta = new Vector2(900, 900);
        _sealFlash = flashGo.GetComponent<Image>();
        _sealFlash.sprite = _square;
        _sealFlash.color = new Color(PalGold.r, PalGold.g, PalGold.b, 0f);
        MakeText(_sealOverlay, "      ·      ", 72, new Vector2(0, -280), TextAnchor.MiddleCenter, 1000, 100).color = Pa
        _sealOverlay.gameObject.SetActive(false);
    }
    void BuildFailOverlay()
    {
        _failOverlay = MakeOverlayPanel("FailOverlay", new Color(0.08f, 0.08f, 0.09f, 0.8f));
        MakeText(_failOverlay, "      ", 84, new Vector2(0, 200), TextAnchor.MiddleCenter, 1000, 110).color = new Colo
        MakeText(_failOverlay, "      —          ×1          50% \n      " + NewbieConfig.PityGuaranteeCount + "      ", 46, ne
        _failOverlay.gameObject.SetActive(false);
    }
    void BuildSkipBanner()
    {
        var go = new GameObject("SkipBanner", typeof(RectTransform), typeof(Image));
        go.transform.SetParent(_canvas.transform, false);
        _skipBanner = (RectTransform)go.transform;
        _skipBanner.anchorMin = new Vector2(0f, 1f);
        _skipBanner.anchorMax = new Vector2(1f, 1f);
        _skipBanner.pivot = new Vector2(0.5f, 1f);
        _skipBanner.anchoredPosition = Vector2.zero;
        _skipBanner.sizeDelta = new Vector2(0, 340);
        var img = go.GetComponent<Image>();
        img.sprite = _square;
        img.color = new Color(0.10f, 0.38f, 0.35f, 0.9f);
        MakeText(_skipBanner, "      ", 80, new Vector2(0, 190), TextAnchor.MiddleCenter, 1000, 100);
        MakeText(_skipBanner, " " + NewbieConfig.FloorSkipFrom + " → " + NewbieConfig.FloorSkipTo + "
        _skipBanner.gameObject.SetActive(false);
    }
    void BuildWallBanner()
    {
        var go = new GameObject("WallBanner", typeof(RectTransform), typeof(Image));
        go.transform.SetParent(_canvas.transform, false);
        _wallBanner = (RectTransform)go.transform;
        _wallBanner.anchorMin = new Vector2(0f, 1f);
        _wallBanner.anchorMax = new Vector2(1f, 1f);
        _wallBanner.pivot = new Vector2(0.5f, 1f);
        _wallBanner.anchoredPosition = Vector2.zero;
        _wallBanner.sizeDelta = new Vector2(0, 420);
        var img = go.GetComponent<Image>();
        img.sprite = _square;
        img.color = new Color(0.45f, 0.11f, 0.13f, 0.88f);
        MakeText(_wallBanner, " 10 · ", 80, new Vector2(0, 130), TextAnchor.MiddleCenter, 1000, 100);
        MakeText(_wallBanner, " 10% —          ", 40, new Vector2(0, 20), TextAnchor.MiddleCenter, 1000, 70);
        var btnGo = new GameObject("HeavenAidButton", typeof(RectTransform), typeof(Image), typeof(Button));
        btnGo.transform.SetParent(_wallBanner, false);

```

```

var btnRt = (RectTransform)btnGo.transform;
btnRt.anchorMin = btnRt.anchorMax = new Vector2(0.5f, 0.5f);
btnRt.anchoredPosition = new Vector2(0, -110);
btnRt.sizeDelta = new Vector2(380, 100);
var btnImg = btnGo.GetComponent<Image>();
btnImg.sprite = _square;
btnImg.color = new Color(0.35f, 0.35f, 0.35f, 0.8f); //
var btn = btnGo.GetComponent<Button>();
btn.interactable = false;
MakeText(btnGo.transform, "      ", 40, Vector2.zero, TextAnchor.MiddleCenter, 380, 100).color = new Color(
_wallBanner.gameObject.SetActive(false);
}
void BuildFormationPanel()
{
_formationPanel = MakeOverlayPanel("FormationPanel", new Color(0.04f, 0.05f, 0.07f, 0.94f));
MakeText(_formationPanel, "      ·      ", 72, new Vector2(0, 620), TextAnchor.MiddleCenter, 1000, 100).color = P
MakeText(_formationPanel, "      ·      ", 42, new Vector2(0, 460), TextAnchor.MiddleCenter, 1000, 70);
for (int i = 0; i < NewbieConfig.FriendCount; i++)
{
var slot = MakeSlot(_formationPanel, new Vector2(-300 + i * 300, 300), PalGreen);
MakeText(slot, NewbieConfig.FriendNames[i].Substring(0, 1), 56, Vector2.zero, TextAnchor.MiddleCenter, 2
}
MakeText(_formationPanel, "      · 1      ", 42, new Vector2(0, 90), TextAnchor.MiddleCenter, 1000, 70).color = Pa
var btnGo = new GameObject("PlaceGudiaoButton", typeof(RectTransform), typeof(Image), typeof(Button));
btnGo.transform.SetParent(_formationPanel, false);
var btnRt = (RectTransform)btnGo.transform;
btnRt.anchorMin = btnRt.anchorMax = new Vector2(0.5f, 0.5f);
btnRt.anchoredPosition = new Vector2(0, -80);
btnRt.sizeDelta = new Vector2(300, 300);
var btnImg = btnGo.GetComponent<Image>();
btnImg.sprite = _square;
btnImg.color = PalFrostedGold; //      ·      §
MakeText(btnGo.transform, "      ", 80, new Vector2(0, 40), TextAnchor.MiddleCenter, 300, 200).color = PalBlack;
MakeText(btnGo.transform, "      ", 36, new Vector2(0, -100), TextAnchor.MiddleCenter, 300, 80).color = Pal
btnGo.GetComponent<Button>().onClick.AddListener(() =>{
{
_formationPanel.gameObject.SetActive(false);
FormationPlaced?.Invoke();
});
MakeText(_formationPanel, "      —      +18%", 36, new Vector2(0, -320), TextAnchor.MiddleCenter
_formationPanel.gameObject.SetActive(false);
}
}
void BuildSettlePanel()
{
_settlePanel = MakeOverlayPanel("SettlePanel", new Color(0.04f, 0.05f, 0.07f, 0.96f));
MakeText(_settlePanel, "      ·      ", 76, new Vector2(0, 520), TextAnchor.MiddleCenter, 1040, 110).color =
_settleStats = MakeText(_settlePanel, "", 44, new Vector2(0, 280), TextAnchor.MiddleCenter, 1020, 340);
MakeActionButton(_settlePanel, "      ", new Vector2(-260, -300), () => UnityEngine.SceneManagement.SceneMa
MakeActionButton(_settlePanel, "      ", new Vector2(260, -300), () => UnityEngine.SceneManagement.SceneMa
_settlePanel.gameObject.SetActive(false);
}

```

```

    }
    // ----- reconcile -----
    public void SyncView(IdleSim sim)
    {
        ReconcileEnemies(sim);
        foreach (var kv in _enemies)
        {
            var v = kv.Value;
            v.Rt.anchoredPosition = new Vector2(FriendX + v.Pos * FieldSpan, RowY[v.Row]);
            v.Fill.fillAmount = v.MaxHp > 0f ? v.Hp / v.MaxHp : 0f;
            if (v.SealReady != v.LastSealReady)
            {
                v.LastSealReady = v.SealReady;
                v.SealLabel.gameObject.SetActive(v.SealReady);
                v.Fill.color = v.SealReady ? PalGold : new Color(0.2f, 0.9f, 0.3f);
                v.LastAttempts = -1;
            }
            if (v.SealReady && v.LastAttempts != v.Attempts)
            {
                v.LastAttempts = v.Attempts;
                int next = v.Attempts + 1;
                v.SealLabel.text = next >= NewbieConfig.PityGuaranteeCount
                    ? "      " + next + "/" + NewbieConfig.PityGuaranteeCount + " . "
                    : "      " + next + "/" + NewbieConfig.PityGuaranteeCount + " ";
            }
            if (v.Shielded != v.LastShielded)
            {
                v.LastShielded = v.Shielded;
                v.ShieldLabel.gameObject.SetActive(v.Shielded);
            }
        }
        for (int i = 0; i < _friendHpFills.Length; i++)
        {
            var f = sim.Friends[i];
            _friendHpFills[i].fillAmount = f.MaxHp > 0f ? f.Hp / f.MaxHp : 0f;
        }
        bool canSeal = sim.SealReadyEnemy != null;
        if (_sealButton.interactable != canSeal)
        {
            _sealButton.interactable = canSeal;
            _sealButtonImage.color = canSeal ? PalGold : new Color(0.35f, 0.35f, 0.38f);
            _sealLabel.color = canSeal ? PalBlack : new Color(0.7f, 0.7f, 0.7f);
        }
    }
    void ReconcileEnemies(IdleSim sim)
    {
        _scratch.Clear();
        foreach (var kv in _enemies)
            if (!ContainsEnemy(sim, kv.Key)) _scratch.Add(kv.Key);
        for (int i = 0; i < _scratch.Count; i++)
    }

```

```

    {
        Destroy(_enemies[_scratch[i]].Go);
        _enemies.Remove(_scratch[i]);
    }
    for (int i = 0; i < sim.Enemies.Count; i++)
    {
        var e = sim.Enemies[i];
        if (!_enemies.TryGetValue(e.Id, out var v))
        {
            v = CreateEnemyVisual(e);
            _enemies[e.Id] = v;
        }
        v.Pos = e.Pos;
        v.Row = e.Row;
        v.Hp = e.Hp;
        v.MaxHp = e.MaxHp;
        v.SealReady = e.SealReady;
        v.Shielded = e.Shielded;
        v.Attempts = e.SealAttempts;
    }
}
static bool ContainsEnemy(IdleSim sim, int id)
{
    for (int i = 0; i < sim.Enemies.Count; i++)
        if (sim.Enemies[i].Id == id) return true;
    return false;
}
EnemyVisual CreateEnemyVisual(IdleSim.EnemyInst e)
{
    var go = new GameObject("Enemy_" + e.Id, typeof(RectTransform), typeof(Image));
    go.transform.SetParent(_field, false);
    var rt = (RectTransform)go.transform;
    rt.anchorMin = rt.anchorMax = new Vector2(0.5f, 0.5f);
    rt.sizeDelta = e.Boss ? new Vector2(200, 200) : e.Collectible ? new Vector2(160, 160) : new Vector2(90, 90);
    var image = go.GetComponent<Image>();
    var bossArt = e.Boss ? Sy.Core.ArtRuntime.Get("P04_unit_01") : null;
    if (bossArt != null)
    {
        image.sprite = bossArt;
        image.color = Color.white;
        image.preserveAspect = true;
    }
    else
    {
        image.sprite = _square;
        image.color = e.Boss ? PalBlue : e.Collectible ? PalGold : PalRed; //
    }
    if (e.Collectible)
        MakeText(go.transform, e.Name.Substring(0, 1), 64, Vector2.zero, TextAnchor.MiddleCenter, 200, 200).color = Color.white;
    var hpGo = new GameObject("Hp", typeof(RectTransform), typeof(Image));

```

```

        hpGo.transform.SetParent(go.transform, false);
        var hpRt = (RectTransform)hpGo.transform;
        hpRt.anchorMin = new Vector2(0f, 1f);
        hpRt.anchorMax = new Vector2(1f, 1f);
        hpRt.anchoredPosition = new Vector2(0, -8);
        hpRt.sizeDelta = new Vector2(-10, 12);
        var hp = hpGo.GetComponent<Image>();
        hp.sprite = _square;
        hp.type = Image.Type.Filled;
        hp.fillMethod = Image.FillMethod.Horizontal;
        hp.color = new Color(0.2f, 0.9f, 0.3f);
        var seallLabel = MakeText(go.transform, "    ", 34, new Vector2(0, 150), TextAnchor.MiddleCenter, 300, 50);
        seallLabel.color = PalGold;
        seallLabel.gameObject.SetActive(false);
        var shieldLabel = MakeText(go.transform, "    ", 34, new Vector2(0, 190), TextAnchor.MiddleCenter, 280, 50);
        shieldLabel.color = PalBlue;
        shieldLabel.gameObject.SetActive(false);
        return new EnemyVisual
        {
            Go = go,
            Rt = rt,
            Fill = hp,
            SeallLabel = seallLabel,
            ShieldLabel = shieldLabel.gameObject,
            Pos = e.Pos,
            Row = e.Row,
            Hp = e.Hp,
            MaxHp = e.MaxHp,
        };
    }
}
// ----- HUD -----
public void SetFloor(int f) => _floorText.text = " " + f + " ";
public void SetCharms(int n) => _charmText.text = "    x" + n;
public void SetKills(int k) => _killsText.text = "    " + k;
public void SetHint(string hint) => _hintText.text = hint;
public void HideIntro() => _introOverlay.gameObject.SetActive(false);
public void ShowWallBanner(bool show) => _wallBanner.gameObject.SetActive(show);
public void ShowFormationPanel(bool show) => _formationPanel.gameObject.SetActive(show);
public void ShowFloorSkip(bool show) => _skipBanner.gameObject.SetActive(show);
public void SetCodex(int litCount)
{
    for (int i = 0; i < NewbieConfig.CodexSlots; i++)
    {
        bool lit = i < litCount;
        _codexSlots[i].color = lit ? PalFrostedGold : new Color(0.16f, 0.16f, 0.18f); // .
        _codexLabels[i].text = lit ? (i == 0 ? " " : " ") : "?";
        _codexLabels[i].color = lit ? PalBlack : new Color(0.45f, 0.45f, 0.48f);
    }
}
}
public void PlaySealAnim()

```

```
{
    StartCoroutine(SealAnimRoutine());
}
IEnumerator SealAnimRoutine()
{
    _sealOverlay.gameObject.SetActive(true);
    float t = 0f;
    bool flashed = false;
    while (t < NewbieConfig.SealAnimSeconds)
    {
        t += Time.unscaledDeltaTime;
        float k = t / NewbieConfig.SealAnimSeconds;
        _magicRing.localRotation = Quaternion.Euler(0f, 0f, k * 540f); // 1.5
        _magicRing.localScale = Vector3.one * Mathf.Lerp(1.3f, 0.55f, k); //
        if (!flashed && k > 0.75f)
        {
            flashed = true;
            StartCoroutine(FlashRoutine());
        }
        yield return null;
    }
    _sealOverlay.gameObject.SetActive(false);
    _magicRing.localRotation = Quaternion.identity;
    _magicRing.localScale = Vector3.one;
}
IEnumerator FlashRoutine()
{
    float t = 0f;
    while (t < 0.25f)
    {
        t += Time.unscaledDeltaTime;
        float a = Mathf.PingPong(t / 0.25f * 2f, 1f);
        _sealFlash.color = new Color(PalGold.r, PalGold.g, PalGold.b, 0.75f * a);
        yield return null;
    }
    _sealFlash.color = new Color(PalGold.r, PalGold.g, PalGold.b, 0f);
}
public void PlaySealFail()
{
    StartCoroutine(FailRoutine());
}
IEnumerator FailRoutine()
{
    _failOverlay.gameObject.SetActive(true);
    yield return new WaitForSecondsRealtime(NewbieConfig.SealFailAnimSeconds);
    _failOverlay.gameObject.SetActive(false);
}
public void ShowSettle(int kills, int charms, int codex)
{
    _settlePanel.gameObject.SetActive(true);
}
```

```

        _settleStats.text = $"          {codex}/{NewbieConfig.CodexSlots}·      \n      ×{charms}      +{Newbie
    }
    // ——    ——
    RectTransform MakeOverlayPanel(string name, Color color)
    {
        var go = new GameObject(name, typeof(RectTransform), typeof(Image));
        go.transform.SetParent(_canvas.transform, false);
        var rt = (RectTransform)go.transform;
        rt.anchorMin = Vector2.zero;
        rt.anchorMax = Vector2.one;
        rt.offsetMin = rt.offsetMax = Vector2.zero;
        var image = go.GetComponent<Image>();
        image.sprite = _square;
        image.color = color;
        return rt;
    }
    RectTransform MakeSlot(RectTransform parent, Vector2 pos, Color color)
    {
        var go = new GameObject("Slot", typeof(RectTransform), typeof(Image));
        go.transform.SetParent(parent, false);
        var rt = (RectTransform)go.transform;
        rt.anchorMin = rt.anchorMax = new Vector2(0.5f, 0.5f);
        rt.anchoredPosition = pos;
        rt.sizeDelta = new Vector2(220, 220);
        var image = go.GetComponent<Image>();
        image.sprite = _square;
        image.color = new Color(color.r, color.g, color.b, 0.6f);
        return rt;
    }
    void MakeActionButton(RectTransform parent, string text, Vector2 pos, Action onClick)
    {
        var go = new GameObject(text, typeof(RectTransform), typeof(Image), typeof(Button));
        go.transform.SetParent(parent, false);
        var rt = (RectTransform)go.transform;
        rt.anchorMin = rt.anchorMax = new Vector2(0.5f, 0.5f);
        rt.anchoredPosition = pos;
        rt.sizeDelta = new Vector2(420, 120);
        var image = go.GetComponent<Image>();
        image.sprite = _square;
        image.color = PalGreen;
        MakeText(go.transform, text, 46, Vector2.zero, TextAnchor.MiddleCenter, 420, 120);
        go.GetComponent<Button>().onClick.AddListener(() => onClick());
    }
    static Text MakeText(Transform parent, string text, int size, Vector2 pos, TextAnchor anchor, float w, float h)
    {
        var go = new GameObject("Text", typeof(RectTransform), typeof(Text));
        go.transform.SetParent(parent, false);
        var rt = (RectTransform)go.transform;
        rt.anchorMin = rt.anchorMax = new Vector2(0.5f, 0.5f);
        rt.anchoredPosition = pos;

```

```

        rt.sizeDelta = new Vector2(w, h);
        var t = go.GetComponent<Text>();
        t.font = Resources.GetBuiltinResource<Font>("LegacyRuntime.ttf");
        t.text = text;
        t.fontSize = size;
        t.alignment = anchor;
        t.color = new Color(0.91f, 0.89f, 0.85f);
        t.supportRichText = true;
        return t;
    }
    static Sprite MakeSquareSprite()
    {
        var tex = new Texture2D(8, 8, TextureFormat.RGBA32, false);
        var px = tex.GetPixels32();
        for (int i = 0; i < px.Length; i++) px[i] = new Color32(255, 255, 255, 255);
        tex.SetPixels32(px);
        tex.Apply(false, false);
        var sprite = Sprite.Create(tex, new Rect(0, 0, 8, 8), new Vector2(0.5f, 0.5f), 8f);
        return sprite;
    }
    // -----
    sealed class EnemyVisual
    {
        public GameObject Go;
        public RectTransform Rt;
        public Image Fill;
        public Text SealLabel;
        public GameObject ShieldLabel;
        public bool LastSealReady;
        public bool LastShielded;
        public int LastAttempts;
        public float Pos;
        public int Row;
        public float Hp;
        public float MaxHp;
        public bool SealReady;
        public bool Shielded;
        public int Attempts;
    }
}

// IdleSim.cs
using System;
using System.Collections.Generic;
namespace Sy.P04.Newbie
{
    /// <summary>
    /// C#      Play  Editor  headless  NewbieFlowCheck
    /// X025    ·    V1.2
    /// ①      1-3  →    4-9  → 10    —$4.1  "    "

```

```

/// ②      §4.2-1      50% + 3      —      x2→
/// ③      §4.3 IdleFormula 2/      —
///      HP      +      + Buff 10%
/// &lt;/summary&gt;
public sealed class IdleSim
{
    public enum IdleState { Prep, Fighting, SealAnim, SealFailAnim, FloorSkip, WallDemo, Formation, BossFight, Sett1
    public sealed class FriendInst
    {
        public int Id;
        public string Name;
        public int Row;
        public float Hp;
        public float MaxHp;
        public float Cooldown;
    }
    public sealed class EnemyInst
    {
        public int Id;
        public string Name;
        public int Row;
        public float Pos;          // 1.0=      → FriendEngageRange=
        public float Hp;
        public float MaxHp;
        public float Atk;
        public float Speed;
        public float Cooldown;
        public bool Collectible;
        public bool Boss;
        public bool Shielded;
        public bool SealReady;
        public bool Dead;
        public int SealAttempts; //      3
    }
    public IdleState State { get; private set; } = IdleState.Prep;
    readonly List&lt;FriendInst&gt; _friends = new();
    readonly List&lt;EnemyInst&gt; _enemies = new();
    readonly List&lt;EnemyInst&gt; _deadThisTick = new();
    int _nextId = 1;
    int _floor;          // 1..3 =10
    int _floorSpawnIdx;
    float _floorTime;    //
    float _floorGapTimer; //      &gt;0=
    float _prepTimer;
    float _sealTimer;
    float _wallTimer;
    float _skipTimer;
    bool _firstSealDone;
    EnemyInst _sealTarget;
    EnemyInst _sealReadyEnemy;

```

```

int _attackRotate;
public IReadOnlyList<FriendInst> Friends => _friends;
public IReadOnlyList<EnemyInst> Enemies => _enemies;
public int Life => NewbieConfig.StartLife;
public int SealCharms { get; private set; } = NewbieConfig.StartSealCharms;
public int CodexLitCount { get; private set; }
public int Kills { get; private set; }
public int Seals { get; private set; } //
public int SealFails { get; private set; } //
public int SealRefunds { get; private set; } //
public int PitySaves { get; private set; } //
public int IdleIncomeGranted { get; private set; } //
public bool FloorSkipShown { get; private set; } // 4-9
public bool GudiaoJoined { get; private set; } //
public float BattleTime { get; private set; }
public float YinBuff { get; private set; } = 1f;
public EnemyInst SealReadyEnemy => _sealReadyEnemy;
public bool AdPopupShown => false; //
/// <summary> Prep=0 1-3 =9 =10 </summary>
public int Floor
{
    get
    {
        if (State == IdleState.Prep) return 0;
        if (State == IdleState.FloorSkip) return NewbieConfig.FloorSkipTo;
        if (State == IdleState.Settled || State == IdleState.Lost) return NewbieConfig.WallFloor;
        if (State == IdleState.WallDemo || State == IdleState.Formation || State == IdleState.BossFight
            || State == IdleState.SealAnim || State == IdleState.SealFailAnim)
            return _firstSealDone ? NewbieConfig.WallFloor : _floor;
        return _floor;
    }
}
public event Action<EnemyInst> EnemyKilled;
public event Action<EnemyInst> SealEnabled;
public event Action<EnemyInst> Sealed;
public event Action<EnemyInst, int> SealFailed; // ( , )
public event Action WallDemoShown;
public event Action FormationUnlocked;
public event Action GudiaoPlaced;
public event Action<int> CharmsChanged;
public event Action<IdleState> StateChanged;
public IdleSim()
{
    for (int i = 0; i < NewbieConfig.FriendCount; i++)
    {
        _friends.Add(new FriendInst
        {
            Id = _nextId++,
            Name = NewbieConfig.FriendNames[i],
            Row = i,

```

```
        Hp = NewbieConfig.FriendHp,
        MaxHp = NewbieConfig.FriendHp,
    });
}
}
public void Tick(float dt)
{
    switch (State)
    {
        case IdleState.Prep:
            _prepTimer += dt;
            if (_prepTimer >= NewbieConfig.IntroSeconds) StartHunt();
            return;
        case IdleState.Fighting:
        case IdleState.BossFight:
            TickBattle(dt);
            return;
        case IdleState.SealAnim:
            _sealTimer -= dt;
            if (_sealTimer <= 0f) FinishSeal();
            return;
        case IdleState.SealFailAnim:
            _sealTimer -= dt;
            if (_sealTimer <= 0f) FinishSealFail();
            return;
        case IdleState.FloorSkip:
            BattleTime += dt;
            _skipTimer -= dt;
            if (_skipTimer <= 0f) EnterWallDemo();
            return;
        case IdleState.WallDemo:
            BattleTime += dt;
            TickEnemiesMove(dt);
            _wallTimer -= dt;
            if (_wallTimer <= 0f)
            {
                SetState(IdleState.Formation);
                FormationUnlocked?.Invoke();
            }
            return;
        // Formation —
    }
}
void StartHunt()
{
    if (State != IdleState.Prep) return;
    BattleTime = 0f;
    BeginFloor(1);
}
void BeginFloor(int floor)
```

```

{
    _floor = floor;
    _floorSpawnIdx = 0;
    _floorTime = 0f;
    _floorGapTimer = 0f;
    SetState(IdleState.Fighting);
}
SpawnDef[] CurrentFloorSpawns() => NewbieConfig.FloorSpawns[_floor - 1];
void TickBattle(float dt)
{
    BattleTime += dt;
    if (State == IdleState.Fighting)
    {
        if (_floorGapTimer > 0f)
        {
            _floorGapTimer -= dt;
            if (_floorGapTimer <= 0f) BeginFloor(_floor + 1);
            return;
        }
        _floorTime += dt;
        TickFloorSpawns();
        //          +      3      — HP      FinishSeal
        if (_floorSpawnIdx >= CurrentFloorSpawns().Length && _enemies.Count == 0
            && _floor < NewbieConfig.TutorialFloors)
        {
            _floorGapTimer = NewbieConfig.FloorGapSeconds;
        }
    }
    TickEnemiesMove(dt);
    TickFriendsAttack(dt);
    TickEnemiesAttack(dt);
    RemoveDead();
}
void TickFloorSpawns()
{
    var spawns = CurrentFloorSpawns();
    while (_floorSpawnIdx < spawns.Length && spawns[_floorSpawnIdx].At <= _floorTime)
    {
        _enemies.Add(NewEnemy(spawns[_floorSpawnIdx], shielded: false));
        _floorSpawnIdx++;
    }
}
EnemyInst NewEnemy(SpawnDef def, bool shielded)
{
    return new EnemyInst
    {
        Id = _nextId++,
        Name = def.Name,
        Row = def.Row,
        Pos = 1f,
    }
}

```

```
        Hp = def.Hp,
        MaxHp = def.Hp,
        Atk = def.Atk,
        Speed = def.Speed,
        Cooldown = def.Atk > 0f ? 1f : 0f,
        Collectible = def.Collectible,
        Boss = def.Boss,
        Shielded = shielded,
    };
}
void TickEnemiesMove(float dt)
{
    for (int i = 0; i < _enemies.Count; i++)
    {
        var e = _enemies[i];
        if (e.Pos > NewbieConfig.FriendEngageRange)
            e.Pos = Math.Max(NewbieConfig.FriendEngageRange, e.Pos - e.Speed * dt);
    }
}
void TickFriendsAttack(float dt)
{
    for (int i = 0; i < _friends.Count; i++)
    {
        var f = _friends[i];
        f.Cooldown -= dt;
        if (f.Cooldown > 0f) continue;
        var target = PickTarget(f);
        if (target == null) { f.Cooldown = 0.05f; continue; }
        f.Cooldown = NewbieConfig.FriendAtkInterval;
        DamageEnemy(target, NewbieConfig.FriendAtk * YinBuff);
    }
}
EnemyInst PickTarget(FriendInst f)
{
    // —
    EnemyInst best = null;
    for (int i = 0; i < _enemies.Count; i++)
    {
        var e = _enemies[i];
        if (e.Dead || e.Pos > NewbieConfig.FriendEngageRange) continue;
        if (e.Row == f.Row) { best = e; break; }
        if (best == null) best = e;
    }
    return best;
}
void DamageEnemy(EnemyInst e, float dmg)
{
    if (e.Shielded) return;
    float lockHp = e.Collectible ? e.MaxHp * NewbieConfig.SealHpRatio : 0f;
    e.Hp -= dmg;
```

```

        if (e.Hp > lockHp) return;
        if (!e.Collectible)
        {
            e.Dead = true;
            _deadThisTick.Add(e);
            return;
        }
        e.Hp = lockHp; // HP
        if (e.SealReady) return;
        e.SealReady = true;
        _sealReadyEnemy = e;
        SealEnabled?.Invoke(e);
    }
    void TickEnemiesAttack(float dt)
    {
        for (int i = 0; i < _enemies.Count; i++)
        {
            var e = _enemies[i];
            if (e.Atk <= 0f || e.Dead || e.Shielded) continue;
            if (e.Pos > NewbieConfig.FriendEngageRange) continue;
            e.Cooldown -= dt;
            if (e.Cooldown > 0f) continue;
            e.Cooldown = 1.2f;
            var f = _friends[_attackRotate % _friends.Count];
            _attackRotate++;
            f.Hp = Math.Max(1f, f.Hp - e.Atk); // 5 +
        }
    }
    void RemoveDead()
    {
        for (int i = 0; i < _deadThisTick.Count; i++)
        {
            var e = _deadThisTick[i];
            _enemies.Remove(e);
            Kills++;
            EnemyKilled?.Invoke(e);
        }
        _deadThisTick.Clear();
    }
    /// <summary> HP 2 §4.2-1
    /// 06 M2 10 = x2→ 3 </summary>
    public bool PressSeal()
    {
        if (_sealReadyEnemy == null || _sealReadyEnemy.Dead) return false;
        if (State != IdleState.Fighting && State != IdleState.BossFight) return false;
        if (SealCharms < NewbieConfig.SealCost) return false;
        _sealTarget = _sealReadyEnemy;
        _sealTarget.SealAttempts++;
        SealCharms -= NewbieConfig.SealCost;
        CharmsChanged?.Invoke(SealCharms);
    }

```

```
bool success = _sealTarget.Boss
    ? _sealTarget.SealAttempts >= NewbieConfig.PityGuaranteeCount
    : true;
_sealTimer = success ? NewbieConfig.SealAnimSeconds : NewbieConfig.SealFailAnimSeconds;
SetState(success ? IdleState.SealAnim : IdleState.SealFailAnim);
return true;
}
void FinishSeal()
{
    var e = _sealTarget;
    _sealTarget = null;
    _sealReadyEnemy = null;
    e.Dead = true;
    _enemies.Remove(e);
    Seals++;
    if (e.Boss && e.SealAttempts >= NewbieConfig.PityGuaranteeCount) PitySaves++;
    CodexLitCount++;
    Sealed?.Invoke(e);
    if (!_firstSealDone)
    {
        _firstSealDone = true;
        SetState(IdleState.FloorSkip);
        _skipTimer = NewbieConfig.FloorSkipSeconds;
        FloorSkipShown = true;
    }
    else
    {
        //          §4.3 IdleFormula      2/
        IdleIncomeGranted = NewbieConfig.IdleIncomeCharmsPerDay;
        SealCharms += IdleIncomeGranted;
        CharmsChanged?.Invoke(SealCharms);
        SetState(IdleState.Settled);
    }
}
void FinishSealFail()
{
    var e = _sealTarget;
    _sealTarget = null;
    SealFails++;
    SealCharms += NewbieConfig.FailRefundCharm; // ① 50%
    SealRefunds++;
    CharmsChanged?.Invoke(SealCharms);
    SealFailed?.Invoke(e, e.SealAttempts);
    SetState(IdleState.BossFight); // HP —
}
void EnterWallDemo()
{
    _floor = NewbieConfig.WallFloor;
    SetState(IdleState.WallDemo);
    _wallTimer = NewbieConfig.WallDemoSeconds;
```

```
{
    value = 0;
    int at = payload.IndexOf(tag, StringComparison.Ordinal);
    if (at < 0) return false;
    int start = at + tag.Length;
    int end = start;
    while (end < payload.Length && (char.IsDigit(payload[end])
        || (end == start && payload[end] == '-'))) end++;
    return end > start && int.TryParse(payload.Substring(start, end - start), out value);
}
}
}
// RiftOfflinePay.cs
using System;
namespace Sy.P04.Yaotide
{
    /// <summary>
    ///     P03 OfflinePay    3 / 8h    1
    ///     12 PlayerPrefs=
    /// </summary>
    public static class RiftOfflinePay
    {
        public const string SeenKey = "p04_offline_seen_ms";
        public const int CharmsPerHour = 3;
        public const int MaxAccrualHours = 8;
        public const int MaxPerDay = CharmsPerHour * MaxAccrualHours;
        public const int MinClaimCharms = CharmsPerHour;
        static readonly long MsPerHour = 3_600_000L;
        public static int CharmsFor(long elapsedMs)
        {
            if (elapsedMs < 0) return 0;
            long hours = elapsedMs / MsPerHour;
            if (hours > MaxAccrualHours) hours = MaxAccrualHours;
            return (int)hours * CharmsPerHour;
        }
        public static int CharmsBetween(long lastSeenMs, long nowMs)
            => CharmsFor(nowMs - lastSeenMs);
        public static void Stamp(long nowMs)
        {
            UnityEngine.PlayerPrefs.SetString(SeenKey, nowMs.ToString());
            UnityEngine.PlayerPrefs.Save();
        }
        public static void ClearForTests()
            => UnityEngine.PlayerPrefs.DeleteKey(SeenKey);
        public sealed class OfflineClaim
        {
            public int Pending { get; }
            public long SeenAtMs { get; }
            public bool Claimable => Pending >= MinClaimCharms;
            public bool Consumed { get; private set; }
        }
    }
}
```

```

        long _nowMs;
        OfflineClaim(int pending, long seenAtMs, long nowMs)
        {
            Pending = pending;
            SeenAtMs = seenAtMs;
            _nowMs = nowMs;
        }
        public static OfflineClaim Open(long nowMs)
        {
            long seen = 0;
            var raw = UnityEngine.PlayerPrefs.GetString(SeenKey, "");
            if (long.TryParse(raw, out var parsed)) seen = parsed;
            int pending = seen > 0 ? CharmsBetween(seen, nowMs) : 0;
            return new OfflineClaim(pending, seen, nowMs);
        }
        /// <summary>
        / </summary>
        public int TryCollect(bool doubled)
        {
            if (Consumed || Pending <= 0) return -1;
            int granted = doubled ? Pending * 2 : Pending;
            SealCharmWallet.Load().Deposit(granted);
            Stamp(_nowMs);
            Consumed = true;
            return granted;
        }
    }
}

// SealCharmWallet.cs
using System;
using System.Collections.Generic;
using System.Text;
using UnityEngine;
namespace Sy.P04.Yaotide
{
    /// <summary>
    ///      . P03 BannerWallet
    ///      60
    ///      =10+ x2+ ÷10 = x2+ ÷5 12 PlayerPrefs=
    /// </summary>
    public sealed class SealCharmWallet
    {
        public const string BalanceKey = "p04_charm_wallet";
        public const string RedeemedKey = "p04_yaos";
        public const int ExchangeCost = 60;
        public int Balance { get; private set; }
        public List<int> RedeemedYaoIds { get; } = new List<int>();
        SealCharmWallet() { }
        public static SealCharmWallet Load()
        {

```

```
var w = new SealCharmWallet();
w.Balance = PlayerPrefs.GetInt(BalanceKey, 0);
string raw = PlayerPrefs.GetString(RedeemedKey, "");
if (raw.Length > 0)
{
    foreach (var part in raw.Split(','))
        if (int.TryParse(part, out int id)) w.RedeemedYaoIds.Add(id);
}
return w;
}
void Save()
{
    PlayerPrefs.SetInt(BalanceKey, Balance);
    var sb = new StringBuilder();
    for (int i = 0; i < RedeemedYaoIds.Count; i++)
    {
        if (i > 0) sb.Append(',');
        sb.Append(RedeemedYaoIds[i]);
    }
    PlayerPrefs.SetString(RedeemedKey, sb.ToString());
    PlayerPrefs.Save();
}
public static int EarnFor(bool won, int waveReached, int kills)
{
    int earned = waveReached * 2 + Math.Max(0, kills) / (won ? 10 : 5);
    if (won) earned += 10;
    return earned;
}
public void Deposit(int charms)
{
    if (charms <= 0) return;
    Balance += charms;
    Save();
}
public bool CanExchange => Balance >= ExchangeCost;
/// <summary> + id -1= / </summary>
public int TryExchange(int roll)
{
    if (!CanExchange) return -1;
    var pool = YaoCodex.UnsealedIds();
    if (pool.Length == 0) return -1;
    int id = pool[(roll % pool.Length) + pool.Length % pool.Length];
    YaoCodex.Seal(id);
    RedeemedYaoIds.Add(id);
    Balance = 0;
    Save();
    return id;
}
public static void ClearForTests()
{

```

```
        PlayerPrefs.DeleteKey(BalanceKey);
        PlayerPrefs.DeleteKey(RedeemedKey);
        YaoCodex.ClearForTests();
    }
}
// YaoCodex.cs
using System;
using System.Collections.Generic;
using UnityEngine;
namespace Sy.P04.Yaotide
{
    /// <summary>
    ///     V1.4 . . /
    /// = 12 PlayerPrefs
    /// </summary>
    public static class YaoCodex
    {
        public enum Tier { Common, Purple, Gold }
        public sealed class YaoDef
        {
            public int Id;
            public string Name; //
            public string Role; //
            public Tier Tier;
            public float Range;
            public float Atk;
            public float Interval;
            public bool Aoe;
            public string SealHint;
            public YaoDef(int id, string name, string role, Tier tier,
                float range, float atk, float interval, bool aoe, string sealHint)
            {
                Id = id; Name = name; Role = role; Tier = tier;
                Range = range; Atk = atk; Interval = interval; Aoe = aoe;
                SealHint = sealHint;
            }
        }
        static readonly YaoDef[] Yaos =
        {
            new YaoDef(1, " ", " ", Tier.Common, 280f, 12f, 0.8f, true, " "),
            new YaoDef(2, " ", " ", Tier.Common, 520f, 26f, 1.1f, false, " "),
            new YaoDef(3, " ", " ", Tier.Purple, 480f, 10f, 1.2f, true, " "),
            new YaoDef(4, " ", " ", Tier.Purple, 360f, 34f, 1.0f, false, " "),
            new YaoDef(5, " ", " ", Tier.Purple, 420f, 14f, 1.1f, false, " "),
            new YaoDef(6, " ", " ", Tier.Gold, 300f, 40f, 1.3f, true, " "),
            new YaoDef(7, " ", " ", Tier.Gold, 460f, 18f, 0.5f, false, " "),
            new YaoDef(8, " ", " ", Tier.Gold, 520f, 30f, 1.2f, false, " "),
        };
        const string SealedKey = "p04_codex_sealed";
    }
}
```

```
public static IReadOnlyList<YaoDef> All => Yaos;
public static YaoDef ById(int id)
{
    for (int i = 0; i < Yaos.Length; i++)
        if (Yaos[i].Id == id) return Yaos[i];
    return null;
}
static HashSet<int> LoadSealed()
{
    var set = new HashSet<int>();
    string raw = PlayerPrefs.GetString(SealedKey, "");
    if (raw.Length == 0)
    {
        set.Add(1);
        set.Add(2);
        return set;
    }
    foreach (var part in raw.Split(','))
        if (int.TryParse(part, out int id)) set.Add(id);
    return set;
}
static void SaveSealed(HashSet<int> set)
{
    var sb = new System.Text.StringBuilder();
    int n = 0;
    foreach (int id in set)
    {
        if (n++ > 0) sb.Append(',');
        sb.Append(id);
    }
    PlayerPrefs.SetString(SealedKey, sb.ToString());
    PlayerPrefs.Save();
}
public static bool IsSealed(int id) => LoadSealed().Contains(id);
/// <summary> . + false= </summary>
public static bool Seal(int id)
{
    var set = LoadSealed();
    if (!set.Add(id)) return false;
    SaveSealed(set);
    return true;
}
public static List<YaoDef> Sealed()
{
    var set = LoadSealed();
    var list = new List<YaoDef>();
    for (int i = 0; i < Yaos.Length; i++)
        if (set.Contains(Yaos[i].Id)) list.Add(Yaos[i]);
    return list;
}
```

```

    /// <summary>
    public static int[] UnsealedIds()
    {
        var set = LoadSealed();
        var ids = new List<int>();
        for (int i = 0; i < Yaos.Length; i++)
            if (!set.Contains(Yaos[i].Id)) ids.Add(Yaos[i].Id);
        return ids.ToArray();
    }
    public static void ClearForTests() => PlayerPrefs.DeleteKey(SealedKey);
}

// YaotideBattleLaunch.cs
using UnityEngine;
namespace Sy.P04.Yaotide
{
    /// <summary>
    /// P03 BattleLaunch →
    /// S04_Yaotide YaotideLauncher =
    /// </summary>
    public static class YaotideBattleLaunch
    {
        public enum Mode { Random, DailyRift, FromCode }
        public static Mode Next = Mode.Random;
        public static int NextSeed;
        public static void StartRandom()
        {
            Next = Mode.Random;
            NextSeed = Mathf.Abs(UnityEngine.Random.Range(int.MinValue, int.MaxValue)) % 100000 + 1;
        }
        public static void StartDailyRift()
        {
            Next = Mode.DailyRift;
            NextSeed = DailyRift.SeedForToday();
        }
        public static bool StartFromFormationCode(string code)
        {
            var plan = YaotideFormationCodec.TryDecode(code);
            if (plan == null) return false;
            Next = Mode.FromCode;
            NextSeed = plan.Value.Seed;
            return true;
        }
        public static (Mode mode, int seed) Take()
        {
            var taken = (Next, NextSeed);
            Next = Mode.Random;
            NextSeed = 0;
            return taken;
        }
    }
}

```

```
    }
}
// YaotideFormationCodec.cs
using System;
using System.Collections.Generic;
using System.Text;
namespace Sy.P04.Yaotide
{
    /// <summary>
    ///     P03 FormationCodec + base36+
    ///     3bit+ 1bit
    /// </summary>
    public static class YaotideFormationCodec
    {
        const string Alphabet = "0123456789ABCDEFGHIJKLMNOPQRSTUVWXYZ";
        const int Version = 1;
        public static string Encode(int seed, IReadOnlyList<YaotideSim.TowerInst> towers)
        {
            var sb = new StringBuilder();
            sb.Append(Digit(Version));
            AppendUnsigned(sb, seed > 0 ? (uint)seed : 0u, 6);
            sb.Append(Digit(towers.Count));
            for (int i = 0; i < towers.Count; i++)
                sb.Append(Digit(((towers[i].Slot & 0x7) << 1) | (towers[i].IsAoE ? 1 : 0)));
            sb.Append(ChecksumChar(sb.ToString()));
            return sb.ToString();
        }
        public static string Encode(YaotideSim sim)
            => Encode(sim.Seed, sim.Towers);
        public readonly struct FormationPlan
        {
            public readonly int Seed;
            public readonly int[] Slots;
            public readonly bool[] IsAoE;
            public FormationPlan(int seed, int[] slots, bool[] isAoE)
            {
                Seed = seed;
                Slots = slots;
                IsAoE = isAoE;
            }
        }
        public static FormationPlan? TryDecode(string code)
        {
            if (string.IsNullOrEmpty(code) || code.Length < 9) return null;
            string body = code.Substring(0, code.Length - 1);
            if (code[code.Length - 1] != ChecksumChar(body)) return null;
            int at = 0;
            if (Value(body[at++]) != Version) return null;
            uint seed = ReadUnsigned(body, ref at, 6);
            int count = Value(body[at++]);
```

```

        if (count < 0 || count > 8) return null;
        if (body.Length - at != count) return null;
        var slots = new int[count];
        bool[] aoe = new bool[count];
        for (int i = 0; i < count; i++)
        {
            int cell = Value(body[at++]);
            if (cell < 0) return null;
            slots[i] = (cell >> 1) & 0x7;
            aoe[i] = (cell & 1) == 1;
        }
        return new FormationPlan((int)seed, slots, aoe);
    }
    static char Digit(int v) => Alphabet[v % 36];
    static int Value(char c) => Alphabet.IndexOf(char.ToUpperInvariant(c));
    static void AppendUnsigned(StringBuilder sb, uint v, int chars)
    {
        char[] buf = new char[chars];
        uint x = v;
        for (int i = chars - 1; i >= 0; i--)
        {
            buf[i] = Alphabet[(int)(x % 36u)];
            x /= 36u;
        }
        for (int i = 0; i < chars; i++) sb.Append(buf[i]);
    }
    static uint ReadUnsigned(string s, ref int at, int chars)
    {
        uint v = 0;
        for (int i = 0; i < chars && at < s.Length; i++)
            v = v * 36u + (uint)Math.Max(0, Value(s[at++]));
        return v;
    }
    static char ChecksumChar(string body)
    {
        int sum = 0;
        for (int i = 0; i < body.Length; i++) sum += body[i];
        return Alphabet[sum % 36];
    }
}

// YaotideLauncher.cs
using System.Collections.Generic;
using UnityEngine;
namespace Sy.P04.Yaotide
{
    /// <summary>
    /// S04_Yaotide      P03 BattleLauncher      YaotideSim+YaotideView
    /// Tick      evt_rift      =RunResult      +      +      KV
    /// HUD              6

```

```

/// <summary>
public sealed class YaotideLauncher : MonoBehaviour
{
    YaotideSim _sim;
    YaotideView _view;
    Sy.Telemetry.TelemetryService _telemetry;
    int _lastWave = -1, _lastLives = -1, _lastCharms = -1, _lastKills = -1;
    void Awake()
    {
        Application.targetFrameRate = 30;
        var canvas = FindObjectOfType<Canvas>();
        var (mode, seed) = YaotideBattleLaunch.Take();
        bool isRift = mode == YaotideBattleLaunch.Mode.DailyRift;
        _sim = new YaotideSim(YaotideLevel.Generate(seed), isRift);
        _view = gameObject.AddComponent<YaotideView>();
        _view.Initialize(canvas, _sim);
        _telemetry = new Sy.Telemetry.TelemetryService();
        _telemetry.AddSink(new TelemetryDebugSink());
        if (isRift) _telemetry.Track("evt_rift", DailyRift.EntryFields("entry_click"));
        _view.SlotTapped += slot => _sim.PlaceTower(slot);
        _view.ContractPicked += index => _sim.PickContract(index);
        _view.ExecuteRequested += () => _sim.TryExecute();
        _view.EnemyTapped += id => _sim.TapFocus(id);
        _sim.TowerPlaced += (tower, slot) => _view.SetTower(slot, tower.IsAoE, tower.YaoId);
        _sim.ContractOffered += () => _view.ShowContractPanel(_sim.ContractEntries);
        _sim.ExecutedFired += () => _view.PlayExecute();
        _sim.YaoSealed += id => _view.SetHint(YaoCodex.ById(id) != null
            ? YaoCodex.ById(id).Name + " "
            : " ");
        _sim.StateChanged += OnStateChanged;
    }
    void Update()
    {
        _sim.Tick(Time.deltaTime);
        _view.SyncView(_sim);
        if (_sim.Wave != _lastWave) { _lastWave = _sim.Wave; _view.SetWave(_lastWave); }
        if (_sim.Lives != _lastLives) { _lastLives = _sim.Lives; _view.SetLives(_lastLives); }
        if (_sim.Charms != _lastCharms) { _lastCharms = _sim.Charms; _view.SetCharms(_lastCharms); }
        if (_sim.Kills != _lastKills) { _lastKills = _sim.Kills; _view.SetKills(_lastKills); }
    }
    void OnStateChanged(YaotideSim.YaotideState state)
    {
        switch (state)
        {
            case YaotideSim.YaotideState.Prepare:
                _view.HideIntro();
                break;
            case YaotideSim.YaotideState.Won:
                Settle(true);
                break;
        }
    }
}

```

```

        case YaotideSim.YaotideState.Lost:
            Settle(false);
            break;
    }
}
void Settle(bool won)
{
    var result = YaotideRunResult.Snapshot(_sim, won);
    SealCharmWallet.Load().Deposit(result.CharmsEarned);
    DailyRift.TrySubmit(result,
        Sy.Core.ServiceLocator.TryGet(out Sy.Platform.IOpenDataBoard board) ? board : null);
    _telemetry.Track("evt_rift",
        DailyRift.RunEndFields(result.Seed, result.Won, result.WaveReached));
    _view.ShowSettle(result);
}
sealed class TelemetryDebugSink : Sy.Telemetry.TelemetryService.ISink
{
    public void Write(string evtId, Dictionary<string, string> fields)
    {
        var sb = new System.Text.StringBuilder(evtId);
        foreach (var kv in fields)
            sb.Append(' ').Append(kv.Key).Append('=').Append(kv.Value);
        Debug.Log("[TELEMETRY] " + sb);
    }
}
}
}
// YaotideLevel.cs
using System;
namespace Sy.P04.Yaotide
{
    /// <summary>
    ///      V1.4      ·CEO   0-20261010-1245·      P03 SiegeLevel
    ///      —
    ///  =   /   =   /   = +2/   =   /   =
    ///  12   —
    /// </summary>
    public sealed class YaotideLevel
    {
        public const int WaveWindowMin = 5;
        public const int WaveWindowMax = 8;
        public readonly int Seed;
        public readonly int TotalWaves;
        public readonly float HpBase;
        public readonly float HpGrowth;
        public readonly float SpeedBase;
        public readonly float SpeedGrow;
        public readonly int CountBase;
        public readonly float SpawnInt;
        public readonly float WaveGap;
    }
}

```

```

public readonly int StartCharms;
public readonly bool MidElite;
public readonly string CalamityName;
public readonly int CalamityId;
public readonly float CalamityPower;
YaotideLevel(int seed, System.Random r, int waveMin, int waveMax)
{
    Seed = seed;
    TotalWaves = r.Next(waveMin, waveMax + 1);
    HpBase = Lerp(r, 40f, 58f);
    HpGrowth = Lerp(r, 1.18f, 1.28f);
    SpeedBase = Lerp(r, 72f, 88f);
    SpeedGrow = Lerp(r, 1.5f, 3.5f);
    CountBase = r.Next(7, 10);
    SpawnInt = Lerp(r, 0.6f, 1.0f);
    WaveGap = Lerp(r, 1.6f, 2.6f);
    StartCharms = r.Next(12, 20);
    MidElite = r.NextDouble() < 0.5;
    CalamityId = r.Next(0, 5);
    CalamityPower = Lerp(r, 0.10f, 0.25f);
    CalamityName = CalamityId switch
    {
        0 => " ",
        1 => " ",
        2 => " ",
        3 => " ",
        _ => " ",
    };
}

public static YaotideLevel Generate(int seed)
    => Generate(seed, WaveWindowMin, WaveWindowMax);
public static YaotideLevel Generate(int seed, int waveMin, int waveMax)
    => new YaotideLevel(seed, new System.Random(seed), waveMin, waveMax);
public WaveDef GetWave(int w)
{
    float hp = HpBase * (float)Math.Pow(HpGrowth, w - 1)
        * (CalamityId == 1 ? 1f + CalamityPower : 1f);    //
    int count = CountBase + (w / 3) + (CalamityId == 2 ? 2 : 0);    //
    float speed = SpeedBase + SpeedGrow * w + (CalamityId == 0 ? SpeedBase * CalamityPower : 0f);
    bool boss = w == TotalWaves || (MidElite && w == TotalWaves - 1 && w >= 3);
    return new WaveDef(w, count, hp, speed, boss);
}

static float Lerp(System.Random r, float min, float max)
    => min + (float)r.NextDouble() * (max - min);
}

public readonly struct WaveDef
{
    public readonly int Wave;
    public readonly int Count;
    public readonly float Hp;

```

```
        public readonly float Speed;
        public readonly bool Boss;
        public WaveDef(int wave, int count, float hp, float speed, bool boss)
        {
            Wave = wave;
            Count = count;
            Hp = hp;
            Speed = speed;
            Boss = boss;
        }
    }
}

// YaotideRunResult.cs
namespace Sy.P04.Yaotide
{
    /// <summary>          P03 RunResult          </summary>
    public sealed class YaotideRunResult
    {
        public bool Won;
        public int Seed;
        public bool IsDailyRift;
        public int WaveReached;
        public int Kills;
        public int LivesLeft;
        public int CharmsLeft;
        public int CharmsEarned;
        public float DurationSec;
        public string FormationCode;
        public string CalamityName;
        public int SealedYaoId;    //          -1=
        public static YaotideRunResult Snapshot(YaotideSim sim, bool won)
        {
            return new YaotideRunResult
            {
                Won = won,
                Seed = sim.Seed,
                IsDailyRift = sim.IsDailyRift,
                WaveReached = sim.Wave,
                Kills = sim.Kills,
                LivesLeft = sim.Lives,
                CharmsLeft = sim.Charms,
                DurationSec = sim.BattleTime,
                FormationCode = YaotideFormationCodec.Encode(sim),
                CalamityName = sim.Level != null ? sim.Level.CalamityName : "",
                CharmsEarned = SealCharmWallet.EarnFor(won, sim.Wave, sim.Kills),
                SealedYaoId = sim.SealedThisRun,
            };
        }
    }
}
```

```
// YaotideSim.cs
using System;
using System.Collections.Generic;
namespace Sy.P04.Yaotide
{
    /// <summary>
    /// C# ·V1.4 TD·CEO O-20261010-1245
    /// S A*·AI +8 + + +
    /// + ≤40% + =
    /// = / .
    /// 12
    /// </summary>
    public sealed class YaotideSim
    {
        public enum YaotideState { Intro, Prep, Fighting, ContractPause, Won, Lost }
        public sealed class TowerInst
        {
            public int Id;
            public int Slot;
            public bool IsAoE;
            public int YaoId;
            public float Range, Atk, Interval, Cooldown;
        }
        public sealed class EnemyInst
        {
            public int Id;
            public bool Boss; //
            public bool Elite; //
            public int Seg;
            public float SegT;
            public float X, Y;
            public float Hp, MaxHp;
            public float Speed;
            public bool Dead;
        }
        public YaotideState State { get; private set; } = YaotideState.Intro;
        public YaotideLevel Level { get; }
        public int Seed { get; }
        public bool IsDailyRift { get; private set; }
        public int TotalWaves => Level.TotalWaves;
        /// <summary> RunResult -1= </summary>
        public int SealedThisRun { get; private set; } = -1;
        // S 8 7 → 8
        public static readonly float[] PathX = { -460f, 340f, 340f, -340f, -340f, 340f, 340f, -500f };
        public static readonly float[] PathY = { 740f, 740f, 300f, 300f, -140f, -140f, -580f, -580f };
        public static readonly float[] SlotX = { 0f, 0f, 0f, -320f, 320f, -320f, 320f, -420f };
        public static readonly float[] SlotY = { 620f, 420f, -280f, 620f, 420f, -280f, 620f, -280f };
        public const float IntroSeconds = 3f;
        public const float PrepStartSeconds = 15f;
        public const float FocusSeconds = 4f;
    }
}
```

```
public const float BossHpBase = 900f;
public const float BossSpeed = 55f;
public const int ExecuteHpRatioPer mille = 400;    // ≤40%
public const int KillCharm = 2;
public const int WaveClearCharm = 8;
readonly List<TowerInst> _towers = new();
readonly List<EnemyInst> _enemies = new();
readonly float[] _segLens;
int _nextId = 1;
float _stateTimer;
int _placed;
int _waveSpawned;
float _spawnTimer;
bool _spawning;
float _waveGapTimer;
int _lastCleared = -1;
int _contractCount;
readonly int[] _contractPool;    //
int _focusId = -1;
float _focusTimer;
float _enemySpeedMul = 1f;
float _atkMul = 1f;
float _towerIntervalMul = 1f;
float _charmMul = 1f;
float _fireMul = 1f;    //
int _waveBonus;
readonly int _eliteYaoId;
public IReadOnlyList<TowerInst> Towers => _towers;
public IReadOnlyList<EnemyInst> Enemies => _enemies;
public int Wave { get; private set; }
public int Lives { get; private set; } = 3;
public int Charms { get; private set; }
public int Kills { get; private set; }
public int PlacedCount => _placed;
public float BattleTime { get; private set; }
public event Action<TowerInst, int> TowerPlaced;
public event Action<int> WaveStarted;
public event Action<int> WaveCleared;
public event Action<EnemyInst> EnemySpawned;
public event Action<EnemyInst> EnemyKilled;
public event Action<int> LifeLost;
public event Action ContractOffered;
public event Action<int> ContractPicked;
public event Action BossKilled;
public event Action ExecutedFired;
public event Action<int> YaoSealed;
public event Action<YaotideState> StateChanged;
public int[] ContractEntries => _contractPool;
public YaotideSim(YaotideLevel level, bool isDailyRift)
{
```

```

Level = level ?? throw new ArgumentNullException(nameof(level));
IsDailyRift = isDailyRift;
Seed = level.Seed;
Charms = level.StartCharms;
_segLens = new float[PathX.Length - 1];
for (int s = 0; s < _segLens.Length; s++)
{
    float dx = PathX[s + 1] - PathX[s];
    float dy = PathY[s + 1] - PathY[s];
    _segLens[s] = (float)Math.Sqrt(dx * dx + dy * dy);
}
if (level.CalamityId == 3) _charmMul = 1f + level.CalamityPower; //
if (level.CalamityId == 4) _towerIntervalMul = 1f + level.CalamityPower; //
var rng = new System.Random(level.Seed ^ 0x5A11);
var bag = new List<int> { 0, 1, 2, 3, 4, 5 };
_contractPool = new int[3];
for (int i = 0; i < 3; i++)
{
    int at = rng.Next(bag.Count);
    _contractPool[i] = bag[at];
    bag.RemoveAt(at);
}
_eliteYaoId = 3 + level.Seed % 3; // / /
}
(int Count, float Hp, float Speed, bool Boss, bool Elite) WaveAt(int w)
{
    var def = Level.GetWave(w);
    float hp = def.Hp * _fireMul;
    _fireMul = 1f;
    bool final = w == Level.TotalWaves;
    bool elite = def.Boss && !final;
    return (def.Count, hp, def.Speed, final, elite);
}
/// <summary> + </summary>
public bool PlaceTower(int slot)
{
    if (State != YaotideState.Prepare && State != YaotideState.Fighting) return false;
    if (slot < 0 || slot >= SlotX.Length) return false;
    for (int i = 0; i < _towers.Count; i++)
        if (_towers[i].Slot == slot) return false;
    var sealedList = YaoCodex.Sealed();
    if (sealedList.Count == 0) return false;
    var def = sealedList[_placed % sealedList.Count];
    int cost = CostFor(def.Tier);
    if (Charms < cost) return false;
    Charms -= cost;
    var tower = new TowerInst
    {
        Id = _nextId++,
        Slot = slot,

```

```

        IsAoE = def.Aoe,
        YaoId = def.Id,
        Range = def.Range,
        Atk = def.Atk,
        Interval = def.Interval,
    };
    _towers.Add(tower);
    _placed++;
    TowerPlaced?.Invoke(tower, slot);
    return true;
}
static int CostFor(YaoCodex.Tier tier) => tier switch
{
    YaoCodex.Tier.Purple => 9,
    YaoCodex.Tier.Gold => 12,
    _ => 6,
};
public void TapFocus(int enemyId)
{
    for (int i = 0; i < _enemies.Count; i++)
        if (_enemies[i].Id == enemyId)
        {
            _focusId = enemyId;
            _focusTimer = FocusSeconds;
            return;
        }
}
public bool IsFocused(EnemyInst e) => e.Id == _focusId && _focusTimer > 0f;
/// <summary> ≤40% </summary>
public bool ExecuteReady
{
    get
    {
        for (int i = 0; i < _enemies.Count; i++)
        {
            var e = _enemies[i];
            if (e.Boss && e.Hp * 1000f <= e.MaxHp * ExecuteHpRatioPer mille) return true;
        }
        return false;
    }
}
/// <summary> </summary>
public bool TryExecute()
{
    if (State != YaotideState.Fighting || !ExecuteReady) return false;
    for (int i = 0; i < _enemies.Count; i++)
    {
        var e = _enemies[i];
        if (!e.Boss) continue;
        ExecutedFired?.Invoke();
    }
}

```

```
        DamageEnemy(e, e.Hp + 1f);
        return true;
    }
    return false;
}
/// <summary>          0-5          </summary>
public void PickContract(int index)
{
    if (State != YaotideState.ContractPause) return;
    if (index < 0 || index >= _contractPool.Length) return;
    int entry = _contractPool[index];
    switch (entry)
    {
        case 0: _enemySpeedMul = 0.8f; break;           //
        case 1: _atkMul = 1.25f; break;                 //
        case 2: _waveBonus = 10; break;                 //
        case 3: Charms += (int)(15 * _charmMul); break;  //
        case 4: Lives += 1; break;                      //
        case 5: _fireMul = 0.85f; break;                //
    }
    _waveGapTimer = 0f;
    ContractPicked?.Invoke(entry);
    SetState(YaotideState.Fighting);
}
public void Tick(float dt)
{
    switch (State)
    {
        case YaotideState.Intro:
            _stateTimer += dt;
            if (_stateTimer >= IntroSeconds) SetState(YaotideState.Prep);
            return;
        case YaotideState.Prep:
            _stateTimer += dt;
            if (_placed &= 1 && (_stateTimer >= PrepStartSeconds))
            {
                SetState(YaotideState.Fighting);
                BeginWave(1);
            }
            return;
        case YaotideState.Fighting:
            BattleTime += dt;
            if (_focusTimer > 0f) _focusTimer -= dt;
            TickSpawns(dt);
            TickEnemies(dt);
            TickTowers(dt);
            TickWaves(dt);
            if (Lives <= 0) SetState(YaotideState.Lost);
            return;
    }
}
```

```
}
void BeginWave(int w)
{
    Wave = w;
    _waveSpawned = 0;
    _spawnTimer = 0f;
    _waveGapTimer = 0f;
    _spawning = true;
    WaveStarted?.Invoke(w);
    float bossHp = BossHpBase * (1f + 0.12f * Level.TotalWaves);
    var (_, _, _, boss, elite) = WaveAt(w);
    if (boss || elite)
    {
        var e = new EnemyInst
        {
            Id = _nextId++,
            Boss = boss,
            Elite = elite,
            Seg = 0,
            SegT = 0f,
            X = PathX[0],
            Y = PathY[0],
            Hp = boss ? bossHp : bossHp * 0.55f,
            MaxHp = boss ? bossHp : bossHp * 0.55f,
            Speed = elite ? BossSpeed * 1.25f : BossSpeed,
        };
        _enemies.Add(e);
        EnemySpawned?.Invoke(e);
    }
}
void TickSpawns(float dt)
{
    if (!_spawning) return;
    var (count, hp, speed, _, _) = WaveAt(Wave);
    _spawnTimer += dt;
    while (_spawnTimer >= Level.SpawnInt && _waveSpawned < count)
    {
        _spawnTimer -= Level.SpawnInt;
        _waveSpawned++;
        var e = new EnemyInst
        {
            Id = _nextId++,
            Seg = 0,
            SegT = 0f,
            X = PathX[0],
            Y = PathY[0],
            Hp = hp,
            MaxHp = hp,
            Speed = speed,
        };
    }
}
```

```
        _enemies.Add(e);
        EnemySpawned?.Invoke(e);
    }
    if (_waveSpawned &gt;= count) _spawning = false;
}
void TickEnemies(float dt)
{
    for (int i = _enemies.Count - 1; i &gt;= 0; i--)
    {
        var e = _enemies[i];
        float move = e.Speed * _enemySpeedMul * dt;
        while (move &gt; 0f)
        {
            float segLen = _segLens[e.Seg];
            float remain = (1f - e.SegT) * segLen;
            if (move &lt; remain)
            {
                e.SegT += move / segLen;
                move = 0f;
            }
            else
            {
                move -= remain;
                e.Seg++;
                e.SegT = 0f;
                if (e.Seg &gt;= _segLens.Length)
                {
                    //          =
                    if (e.Boss)
                    {
                        e.Seg = 0;
                        e.SegT = 0f;
                    }
                    else
                    {
                        _enemies.RemoveAt(i);
                    }
                    Lives = Math.Max(0, Lives - 1);
                    LifeLost?.Invoke(Lives);
                    break;
                }
            }
        }
        if (e.Seg &lt; _segLens.Length)
        {
            e.X = Lerp(PathX[e.Seg], PathX[e.Seg + 1], e.SegT);
            e.Y = Lerp(PathY[e.Seg], PathY[e.Seg + 1], e.SegT);
        }
    }
}
```

```
static float Lerp(float a, float b, float t) => a + (b - a) * t;
void TickTowers(float dt)
{
    for (int i = 0; i < _towers.Count; i++)
    {
        var t = _towers[i];
        t.Cooldown -= dt;
        if (t.Cooldown > 0f) continue;
        bool any = false;
        if (t.IsAoE)
        {
            float r2 = t.Range * t.Range;
            for (int j = _enemies.Count - 1; j >= 0; j--)
            {
                var e = _enemies[j];
                float dx = e.X - SlotX[t.Slot], dy = e.Y - SlotY[t.Slot];
                if (dx * dx + dy * dy > r2) continue;
                any = true;
                DamageEnemy(e, t.Atk * _atkMul);
            }
        }
        else
        {
            float r2 = t.Range * t.Range;
            EnemyInst target = null;
            float best = float.MaxValue;
            for (int j = 0; j < _enemies.Count; j++)
            {
                var e = _enemies[j];
                float dx = e.X - SlotX[t.Slot], dy = e.Y - SlotY[t.Slot];
                float d2 = dx * dx + dy * dy;
                if (d2 > r2) continue;
                if (IsFocused(e)) { target = e; best = -1f; break; }
                if (d2 < best) { best = d2; target = e; }
            }
            if (target != null)
            {
                any = true;
                DamageEnemy(target, t.Atk * _atkMul);
            }
        }
        t.Cooldown = any ? t.Interval * _towerIntervalMul : 0.05f;
    }
}

void DamageEnemy(EnemyInst e, float dmg)
{
    e.Hp -= dmg;
    if (e.Hp > 0f) return;
    e.Dead = true;
    _enemies.Remove(e);
}
```

```
Kills++;
Charms += (int)(KillCharm * _charmMul);
if (e.Boss)
{
    SealInto(_bossYaoId());
    //
    for (int i = _enemies.Count - 1; i >= 0; i--)
    {
        var rest = _enemies[i];
        rest.Dead = true;
        _enemies.RemoveAt(i);
        Kills++;
        Charms += (int)(KillCharm * _charmMul);
        EnemyKilled?.Invoke(rest);
    }
    BossKilled?.Invoke();
    EnemyKilled?.Invoke(e);
    SetState(YaotideState.Won);
    return;
}
if (e.Elite)
{
    SealInto(_eliteYaoId);
}
EnemyKilled?.Invoke(e);
}
int _bossYaoId() => 8; //
void SealInto(int yaoId)
{
    SealedThisRun = yaoId;
    YaoCodex.Seal(yaoId);
    YaoSealed?.Invoke(yaoId);
}
void TickWaves(float dt)
{
    if (_spawning || _enemies.Count > 0) return;
    _waveGapTimer += dt;
    if (_waveGapTimer < Level.WaveGap) return;
    int cleared = Wave;
    if (cleared >= TotalWaves) return; //
    if (_lastCleared != cleared)
    {
        _lastCleared = cleared;
        Charms += (int)((WaveClearCharm + _waveBonus) * _charmMul);
        WaveCleared?.Invoke(cleared);
    }
    if (_contractCount < _contractPool.Length)
    {
        _contractCount++;
        SetState(YaotideState.ContractPause);
    }
}
```

```

        ContractOffered?.Invoke();
        return;
    }
    BeginWave(cleared + 1);
}
void SetState(YaotideState s)
{
    if (State == s) return;
    State = s;
    _stateTimer = 0f;
    StateChanged?.Invoke(s);
}
}
}
// YaotideView.cs
using System;
using System.Collections;
using System.Collections.Generic;
using UnityEngine;
using UnityEngine.UI;
namespace Sy.P04.Yaotide
{
    /// <summary>
    ///         UGUI·         x x x x
    ///     / / / /HUD/     / /
    /// HUD         6 30fps
    /// </summary>
    public sealed class YaotideView : MonoBehaviour
    {
        Canvas _canvas;
        Sprite _square;
        Text _waveText, _livesText, _charmText, _killsText, _hintText, _calamityText;
        Button _executeButton;
        Image _executeImage;
        RectTransform _introOverlay, _contractPanel, _executeOverlay, _settlePanel;
        Text _settleStats, _settleTitle;
        int _totalWaves = YaotideLevel.WaveWindowMax;
        readonly Text[] _contractNames = new Text[3];
        readonly Text[] _contractDescs = new Text[3];
        readonly Dictionary<int, EnemyVisual> _enemies = new();
        readonly List<int> _scratch = new();
        readonly Image[] _slotImages = new Image[YaotideSim.SlotX.Length];
        readonly Text[] _slotLabels = new Text[YaotideSim.SlotX.Length];
        public event Action<int> SlotTapped;
        public event Action<int> EnemyTapped;
        public event Action<int> ContractPicked;
        public event Action ExecuteRequested;
        static readonly Color PalRed = new Color(0.902f, 0.224f, 0.275f); // #E63946
        static readonly Color PalBlue = new Color(0.271f, 0.482f, 0.616f); // #457B9D
        static readonly Color PalGold = new Color(1f, 0.843f, 0f); // #FFD700
    }
}

```

```
static readonly Color PalGreen = new Color(0.165f, 0.616f, 0.561f); // #2A9D8F
static readonly Color PalBlack = new Color(0.114f, 0.114f, 0.114f); // #1D1D1D
static readonly Color PathCol = new Color(0.16f, 0.10f, 0.10f);
/// <summary> id 0-5 YaotideSim.PickContract </summary>
public static readonly (string Name, string Desc)[] ContractCards =
{
    (" ", " -20%"),
    (" ", " +25%"),
    (" ", " +10"),
    (" ", " +15"),
    (" ", " +1"),
    (" ", " -15%"),
};

public void Initialize(Canvas canvas, YaotideSim sim)
{
    _canvas = canvas;
    _square = MakeSquareSprite();
    _totalWaves = sim.TotalWaves;
    BuildBackdrop();
    BuildHud();
    BuildPath();
    BuildSlots();
    BuildIntroOverlay();
    BuildContractPanel();
    BuildExecuteOverlay();
    BuildSettlePanel();
    SetHint(" — ");
    if (sim.Level != null) SetCalamity(" · " + sim.Level.CalamityName);
}

void BuildBackdrop()
{
    var art = Sy.Core.ArtRuntime.Get("P04_scene_01");
    if (art == null) return;
    var go = new GameObject("ArtBackdrop", typeof(RectTransform), typeof(Image));
    go.transform.SetParent(_canvas.transform, false);
    var rt = (RectTransform)go.transform;
    rt.anchorMin = Vector2.zero;
    rt.anchorMax = Vector2.one;
    rt.offsetMin = rt.offsetMax = Vector2.zero;
    rt.SetAsFirstSibling();
    var image = go.GetComponent<Image>();
    image.sprite = art;
    image.color = Color.white;
    image.preserveAspect = true;
    image.raycastTarget = false;
}

void BuildHud()
{
    var root = _canvas.transform;
    _waveText = MakeText(root, " 0/" + _totalWaves, 46, new Vector2(0, 880), TextAnchor.UpperLeft, 380, 70);
}
```

```

_waveText.color = PalGold;
_livesText = MakeText(root, " 3", 46, new Vector2(0, 880), TextAnchor.UpperRight, 340, 70);
_charmText = MakeText(root, " 0", 44, new Vector2(0, 820), TextAnchor.UpperLeft, 380, 60);
_charmText.color = PalGold;
_killsText = MakeText(root, " 0", 44, new Vector2(0, 820), TextAnchor.UpperRight, 380, 60);
_calamityText = MakeText(root, "", 36, new Vector2(0, 760), TextAnchor.UpperLeft, 520, 50);
_calamityText.color = PalGreen;
_hintText = MakeText(root, "", 40, new Vector2(0, -780), TextAnchor.MiddleCenter, 1020, 150);
_hintText.color = new Color(0.95f, 0.87f, 0.6f);
var btnGo = new GameObject("ExecuteButton", typeof(Image), typeof(Button));
btnGo.transform.SetParent(root, false);
var btnRt = (RectTransform)btnGo.transform;
btnRt.anchorMin = btnRt.anchorMax = new Vector2(0.5f, 0f);
btnRt.anchoredPosition = new Vector2(0, 120);
btnRt.sizeDelta = new Vector2(460, 140);
_executeImage = btnGo.GetComponent<Image>();
_executeImage.sprite = _square;
_executeImage.color = new Color(0.35f, 0.35f, 0.35f);
_executeButton = btnGo.GetComponent<Button>();
_executeButton.interactable = false;
MakeText(btnGo.transform, " ", 54, Vector2.zero, TextAnchor.MiddleCenter, 460, 140).color = PalBlack;
_executeButton.onClick.AddListener(() => ExecuteRequested?.Invoke());
}
void BuildPath()
{
    for (int s = 0; s < YaotideSim.PathX.Length - 1; s++)
    {
        float x0 = YaotideSim.PathX[s], y0 = YaotideSim.PathY[s];
        float x1 = YaotideSim.PathX[s + 1], y1 = YaotideSim.PathY[s + 1];
        bool horiz = Math.Abs(y1 - y0) < 1f;
        var go = new GameObject("PathSeg_" + s, typeof(RectTransform), typeof(Image));
        go.transform.SetParent(_canvas.transform, false);
        var rt = (RectTransform)go.transform;
        rt.anchorMin = rt.anchorMax = new Vector2(0.5f, 0.5f);
        rt.anchoredPosition = new Vector2((x0 + x1) * 0.5f, (y0 + y1) * 0.5f);
        rt.sizeDelta = horiz
            ? new Vector2(Math.Abs(x1 - x0) + 90f, 90f)
            : new Vector2(90f, Math.Abs(y1 - y0) + 90f);
        var img = go.GetComponent<Image>();
        img.sprite = _square;
        img.color = PathCol;
    }
    MakeText(_canvas.transform, " ", 34, new Vector2(-460f, 820f), TextAnchor.MiddleCenter, 260, 50).color =
    MakeText(_canvas.transform, " ", 34, new Vector2(-500f, -660f), TextAnchor.MiddleCenter, 260, 50).color =
}
void BuildSlots()
{
    for (int i = 0; i < YaotideSim.SlotX.Length; i++)
    {
        int index = i;

```

```

        var go = new GameObject("Slot_" + i, typeof(RectTransform), typeof(Image), typeof(Button));
        go.transform.SetParent(_canvas.transform, false);
        var rt = (RectTransform)go.transform;
        rt.anchorMin = rt.anchorMax = new Vector2(0.5f, 0.5f);
        rt.anchoredPosition = new Vector2(YaotideSim.SlotX[i], YaotideSim.SlotY[i]);
        rt.sizeDelta = new Vector2(140, 140);
        var img = go.GetComponent<Image>();
        var slotArt = Sy.Core.ArtRuntime.Get("P04_unit_01");
        if (slotArt != null)
        {
            img.sprite = slotArt;
            img.color = Color.white;
            img.preserveAspect = true;
        }
        else
        {
            img.sprite = _square;
            img.color = new Color(0.13f, 0.13f, 0.13f, 0.9f);
        }
        _slotImages[i] = img;
        _slotLabels[i] = MakeText(go.transform, " ", 34, Vector2.zero, TextAnchor.MiddleCenter, 140, 140);
        _slotLabels[i].color = new Color(0.55f, 0.52f, 0.45f);
        go.GetComponent<Button>().onClick.AddListener(() => SlotTapped?.Invoke(index));
    }
}

void BuildIntroOverlay()
{
    _introOverlay = MakeOverlayPanel("IntroOverlay", new Color(0.05f, 0.02f, 0.08f, 0.95f));
    MakeText(_introOverlay, "      ", 100, new Vector2(0, 100), TextAnchor.MiddleCenter, 1000, 130).color = Pal
    MakeText(_introOverlay, "      .      ", 46, new Vector2(0, -60), TextAnchor.MiddleCenter, 1000, 80).color
}

void BuildContractPanel()
{
    _contractPanel = MakeOverlayPanel("ContractPanel", new Color(0.03f, 0.03f, 0.06f, 0.92f));
    MakeText(_contractPanel, "      .      ", 76, new Vector2(0, 560), TextAnchor.MiddleCenter, 1000, 100).color = Pa
    for (int i = 0; i < 3; i++)
    {
        int index = i;
        var card = ContractCards[i];
        var go = new GameObject("Contract_" + i, typeof(RectTransform), typeof(Image), typeof(Button));
        go.transform.SetParent(_contractPanel, false);
        var rt = (RectTransform)go.transform;
        rt.anchorMin = rt.anchorMax = new Vector2(0.5f, 0.5f);
        rt.anchoredPosition = new Vector2(-330 + i * 330, 0);
        rt.sizeDelta = new Vector2(300, 420);
        var img = go.GetComponent<Image>();
        img.sprite = _square;
        img.color = i == 0 ? new Color(0.55f, 0.12f, 0.15f) : new Color(0.14f, 0.16f, 0.20f);
        _contractNames[i] = MakeText(go.transform, " " + card.Name + " ", 56, new Vector2(0, 120), TextAnchor.Mi
        _contractNames[i].color = PalGold;
    }
}

```

```

        _contractDescs[i] = MakeText(go.transform, card.Desc, 38, new Vector2(0, -40), TextAnchor.MiddleCenter,
        _contractDescs[i].color = new Color(0.85f, 0.85f, 0.8f);
        go.GetComponent<Button>().onClick.AddListener(() =>{
            _contractPanel.gameObject.SetActive(false);
            ContractPicked?.Invoke(index);
        });
    }
    MakeText(_contractPanel, "    —    ", 40, new Vector2(0, -400), TextAnchor.MiddleCenter, 1000, 80).color =
    _contractPanel.gameObject.SetActive(false);
}
/// <summary>        </summary>
public void ShowContractPanel(int[] entries)
{
    for (int i = 0; i < 3 && i < entries.Length; i++)
    {
        var card = ContractCards[Math.Max(0, Math.Min(ContractCards.Length - 1, entries[i]))];
        _contractNames[i].text = " " + card.Name + " ";
        _contractDescs[i].text = card.Desc;
    }
    _contractPanel.gameObject.SetActive(true);
}
void BuildExecuteOverlay()
{
    _executeOverlay = MakeOverlayPanel("ExecuteOverlay", new Color(1f, 0.98f, 0.92f, 0.75f));
    var lineGo = new GameObject("Executeline", typeof(RectTransform), typeof(Image));
    lineGo.transform.SetParent(_executeOverlay, false);
    var lineRt = (RectTransform)lineGo.transform;
    lineRt.anchorMin = lineRt.anchorMax = new Vector2(0.5f, 0.5f);
    lineRt.anchoredPosition = Vector2.zero;
    lineRt.sizeDelta = new Vector2(2200, 16);
    lineRt.localRotation = Quaternion.Euler(0f, 0f, 24f);
    var lineImg = lineGo.GetComponent<Image>();
    lineImg.sprite = _square;
    lineImg.color = PalRed;
    MakeText(_executeOverlay, " ", 110, new Vector2(0, -180), TextAnchor.MiddleCenter, 1000, 140).color = PalBl
    _executeOverlay.gameObject.SetActive(false);
}
void BuildSettlePanel()
{
    _settlePanel = MakeOverlayPanel("SettlePanel", new Color(0.03f, 0.03f, 0.05f, 0.96f));
    _settleTitle = MakeText(_settlePanel, "    ", 90, new Vector2(0, 560), TextAnchor.MiddleCenter, 1040, 110);
    _settleTitle.color = PalGold;
    _settleStats = MakeText(_settlePanel, "", 46, new Vector2(0, 380), TextAnchor.MiddleCenter, 1000, 260);
    MakeActionButton(_settlePanel, "    ", new Vector2(-260, -260), () => UnityEngine.SceneManagement.SceneMa
    MakeActionButton(_settlePanel, "    ", new Vector2(260, -260), () => UnityEngine.SceneManagement.SceneMa
    _settlePanel.gameObject.SetActive(false);
}
// ————
public void SyncView(YaotideSim sim)

```

```
{
    ReconcileEnemies(sim);
    foreach (var kv in _enemies)
    {
        var v = kv.Value;
        v.Rt.anchoredPosition = new Vector2(v.X, v.Y);
        if (v.Fill != null) v.Fill.fillAmount = v.MaxHp > 0f ? v.Hp / v.MaxHp : 0f;
        bool focused = v.Focused;
        if (focused != v.LastFocused)
        {
            v.LastFocused = focused;
            v.FocusLabel.gameObject.SetActive(focused);
        }
    }
    bool ready = sim.ExecuteReady;
    if (_executeButton.interactable != ready)
    {
        _executeButton.interactable = ready;
        _executeImage.color = ready ? PalRed : new Color(0.35f, 0.35f, 0.35f);
    }
}

void ReconcileEnemies(YaotideSim sim)
{
    _scratch.Clear();
    foreach (var kv in _enemies)
        if (!ContainsEnemy(sim, kv.Key)) _scratch.Add(kv.Key);
    for (int i = 0; i < _scratch.Count; i++)
    {
        Destroy(_enemies[_scratch[i]].Go);
        _enemies.Remove(_scratch[i]);
    }
    for (int i = 0; i < sim.Enemies.Count; i++)
    {
        var e = sim.Enemies[i];
        if (!_enemies.TryGetValue(e.Id, out var v))
        {
            v = CreateEnemyVisual(e);
            _enemies[e.Id] = v;
        }
        v.X = e.X;
        v.Y = e.Y;
        v.Hp = e.Hp;
        v.MaxHp = e.MaxHp;
        v.Focused = sim.IsFocused(e);
    }
}

static bool ContainsEnemy(YaotideSim sim, int id)
{
    for (int i = 0; i < sim.Enemies.Count; i++)
        if (sim.Enemies[i].Id == id) return true;
}
```

```

        return false;
    }
    EnemyVisual CreateEnemyVisual(YaotideSim.EnemyInst e)
    {
        int id = e.Id;
        var go = new GameObject("Enemy_" + e.Id, typeof(RectTransform), typeof(Image), typeof(Button));
        go.transform.SetParent(_canvas.transform, false);
        var rt = (RectTransform)go.transform;
        rt.anchorMin = rt.anchorMax = new Vector2(0.5f, 0.5f);
        rt.sizeDelta = e.Boss ? new Vector2(160, 160) : (e.Elite ? new Vector2(110, 110) : new Vector2(70, 70));
        var image = go.GetComponent<Image>();
        image.sprite = _square;
        image.color = e.Boss ? PalGold : (e.Elite ? PalGreen : new Color(0.35f, 0.32f, 0.42f));
        if (e.Boss)
            MakeText(go.transform, " ", 64, Vector2.zero, TextAnchor.MiddleCenter, 160, 160).color = PalBlack;
        else if (e.Elite)
            MakeText(go.transform, " ", 44, Vector2.zero, TextAnchor.MiddleCenter, 110, 110).color = PalBlack;
        var hpGo = new GameObject("Hp", typeof(RectTransform), typeof(Image));
        hpGo.transform.SetParent(go.transform, false);
        var hpRt = (RectTransform)hpGo.transform;
        hpRt.anchorMin = new Vector2(0f, 1f);
        hpRt.anchorMax = new Vector2(1f, 1f);
        hpRt.anchoredPosition = new Vector2(0, -6);
        hpRt.sizeDelta = new Vector2(-8, 10);
        var fill = hpGo.GetComponent<Image>();
        fill.sprite = _square;
        fill.type = Image.Type.Filled;
        fill.fillMethod = Image.FillMethod.Horizontal;
        fill.color = new Color(0.2f, 0.9f, 0.3f);
        var focusLabel = MakeText(go.transform, " ", 34, new Vector2(0, 120), TextAnchor.MiddleCenter, 220, 50);
        focusLabel.color = PalGold;
        focusLabel.gameObject.SetActive(false);
        go.GetComponent<Button>().onClick.AddListener(() => EnemyTapped?.Invoke(id));
        return new EnemyVisual
        {
            Go = go,
            Rt = rt,
            Fill = fill,
            FocusLabel = focusLabel.gameObject,
            X = e.X,
            Y = e.Y,
            Hp = e.Hp,
            MaxHp = e.MaxHp,
        };
    }
    // —— HUD ——
    public void SetWave(int w) => _waveText.text = " " + w + "/" + _totalWaves;
    public void SetCalamity(string name) => _calamityText.text = name;
    public void SetLives(int l) => _livesText.text = " " + l;
    public void SetCharms(int c) => _charmText.text = " " + c;

```

```

public void SetKills(int k) => _killsText.text = " " + k;
public void SetHint(string hint) => _hintText.text = hint;
public void HideIntro() => _introOverlay.gameObject.SetActive(false);
public void SetTower(int slot, bool isAoE, int yaoId)
{
    _slotImages[slot].color = isAoE ? PalRed : PalBlue;
    var def = YaoCodexById(yaoId);
    string label = def != null && def.Name.Length > 0 ? def.Name.Substring(0, 1) : (isAoE ? " " : " ");
    _slotLabels[slot].text = label;
    _slotLabels[slot].color = PalBlack;
    _slotLabels[slot].fontSize = 64;
}
public void PlayExecute()
{
    StartCoroutine(ExecuteRoutine());
}
IEnumerator ExecuteRoutine()
{
    _executeOverlay.gameObject.SetActive(true);
    yield return new WaitForSeconds(0.5f);
    _executeOverlay.gameObject.SetActive(false);
}
public void ShowSettle(YaotideRunResult result)
{
    _settleTitle.text = result.Won ? " " : " ";
    string seal = result.SealedYaoId > 0 && YaoCodexById(result.SealedYaoId) != null
        ? YaoCodexById(result.SealedYaoId).Name + " "
        : "";
    _settleStats.text = result.Won
        ? $" {result.WaveReached}/{_totalWaves} · {result.Kills} · +{result.CharmsEarned}\n<size=40>
        : $" {result.WaveReached}/{_totalWaves} · {result.Kills} · +{result.CharmsEarned}\n<size=40>
    _settlePanel.gameObject.SetActive(true);
}
// _____
RectTransform MakeOverlayPanel(string name, Color color)
{
    var go = new GameObject(name, typeof(RectTransform), typeof(Image));
    go.transform.SetParent(_canvas.transform, false);
    var rt = (RectTransform)go.transform;
    rt.anchorMin = Vector2.zero;
    rt.anchorMax = Vector2.one;
    rt.offsetMin = rt.offsetMax = Vector2.zero;
    var image = go.GetComponent<Image>();
    image.sprite = _square;
    image.color = color;
    return rt;
}
void MakeActionButton(RectTransform parent, string text, Vector2 pos, Action onClick)
{
    var go = new GameObject(text, typeof(RectTransform), typeof(Image), typeof(Button));

```

```

        go.transform.SetParent(parent, false);
        var rt = (RectTransform)go.transform;
        rt.anchorMin = rt.anchorMax = new Vector2(0.5f, 0.5f);
        rt.anchoredPosition = pos;
        rt.sizeDelta = new Vector2(420, 120);
        var image = go.GetComponent<Image>();
        image.sprite = _square;
        image.color = PalGreen;
        MakeText(go.transform, text, 46, Vector2.zero, TextAnchor.MiddleCenter, 420, 120);
        go.GetComponent<Button>().onClick.AddListener(() => onClick());
    }

    static Text MakeText(Transform parent, string text, int size, Vector2 pos, TextAnchor anchor, float w, float h)
    {
        var go = new GameObject("Text", typeof(RectTransform), typeof(Text));
        go.transform.SetParent(parent, false);
        var rt = (RectTransform)go.transform;
        rt.anchorMin = rt.anchorMax = new Vector2(0.5f, 0.5f);
        rt.anchoredPosition = pos;
        rt.sizeDelta = new Vector2(w, h);
        var t = go.GetComponent<Text>();
        t.font = Resources.GetBuiltinResource<Font>("LegacyRuntime.ttf");
        t.text = text;
        t.fontSize = size;
        t.alignment = anchor;
        t.color = new Color(0.91f, 0.89f, 0.85f);
        t.supportRichText = true;
        return t;
    }

    static Sprite MakeSquareSprite()
    {
        var tex = new Texture2D(8, 8, TextureFormat.RGBA32, false);
        var px = tex.GetPixels32();
        for (int i = 0; i < px.Length; i++) px[i] = new Color32(255, 255, 255, 255);
        tex.SetPixels32(px);
        tex.Apply(false, false);
        return Sprite.Create(tex, new Rect(0, 0, 8, 8), new Vector2(0.5f, 0.5f), 8f);
    }

    sealed class EnemyVisual
    {
        public GameObject Go;
        public RectTransform Rt;
        public Image Fill;
        public GameObject FocusLabel;
        public bool LastFocused;
        public bool Focused;
        public float X, Y;
        public float Hp, MaxHp;
    }
}

```